



On this page



Introduction

Welcome to the **Wapisender API**. This documentation is designed to help you integrate WhatsApp messaging capabilities seamlessly into your applications, CRM, or websites.

What you can do:

- Send automated text messages (OTP, Notifications).
- Send rich media (Images, PDFs, Documents).
- Manage and use centralized message templates.
- Programmatically control WhatsApp communication flow.

Server Information

Base URL

`https://wapisender.id/api`

Content Type

`application/json`

Standard Response Format

All API responses follow a consistent JSON structure to help you parse results easily.

Response Envelope



```
{
  "status": true,           // Success status (true/false)
  "message": "Success...",  // Human-readable message
  "data": { ... },         // Response payload (optional)
  "errors": { ... }        // Validation errors (if any)
}
```



Authentication



Authenticate your API requests by including your API Key in the request. You can pass it as a JSON parameter, a query parameter, or in the Authorization header.

 **Your API Key**

Keep this key secret. Do not share it in client-side code.

Please generate an API Token in Settings

 Copy

Authentication Methods

Option 1: JSON Body (Recommended)

Body Parameter

```
{
  "api_key": "YOUR_API_KEY",
  ...
}
```

Option 2: Authorization Header

Header

```
Authorization: Bearer YOUR_API_KEY
```

 Profile

POST /me

Get User Profile

Retrieve your account profile information including current balance.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Profile retrieved successfully",
  "data": {
    "name": "John Doe",
    "username": "johndoe",
    "email": "john@example.com",
    "balance": "50000.00"
  }
}
```

Messaging

GET/POST /message/send

Send Message

Send a text message, media, location, sticker, contact, poll, or reaction. Supports both GET and POST for simple text. **Parameter is priority defaults to true if omitted** (faster queue). API waits until WhatsApp confirms delivery and returns `message_id` + `wa_status` in the response.

Body / Query Parameters

Parameter	Type	Required	Description
<code>api_key</code>	string	Required	Your API Secret Key.
<code>device_key</code>	string	Required	The unique_id of the device sending the message (e.g., WAPI-XXXXXX).
<code>to</code>	string	Optional	Target phone number for personal message (e.g., 628123456789). Use

Parameter	Type	Required	Description
			one of "to", "group", or "channel".
group	string	Optional	WhatsApp Group JID for group message (e.g., 120363123456789@g.us). Use one of "to", "group", or "channel".
channel	string	Optional	WhatsApp Channel (Newsletter) ID (e.g., 12345678). Use one of "to", "group", or "channel".
message	string	Required	The text message to be sent.
mentions	array<string> string	Optional	Optional mention list. You can pass array (recommended for POST JSON) or comma-separated string (for GET query). Format accepted: phone numbers (e.g. 62812xxx) or full JIDs (e.g. 62812xxx@s.whatsapp.net). Mentions are most useful in group messages.
is_priority	boolean	Optional	Default: true if you omit this field. Uses the priority send path in the WhatsApp worker (shorter delay, typically ~1–2s between messages). Set to <code>false</code> for high-volume / campaign-style sending to use the 5–15s anti-ban spacing instead.
simulate_typing	boolean	Optional	If true, simulates typing indicator (adds delay). Default: false (instant). Panduan Penggunaan: Gunakan false: Untuk API, integrasi, atau pengiriman massal (bulk). Respon instan dan bebas timeout. Gunakan true: Hanya untuk chatbot/auto-reply agar terlihat lebih "manusiawi". Tidak disarankan untuk pengiriman massal. Saran: Untuk broadcast atau integrasi sistem, biarkan tetap false demi stabilitas.
quoted_id	string	Optional	ID of the message you want to reply to. ↑

Parameter	Type	Required	Description
template_id	integer	Optional	ID of the template to use (Optional). If provided, it overrides the message content.
template_vars	object	Optional	JSON object containing values for template variables.

 GET REQUEST EXAMPLE

GET URL 

```
curl -X GET "https://wapisender.id/api/message/send?api_key=YOUR_KEY&device_key=WAPI-XX"
```

REQUEST EXAMPLE (POST/JSON)

JSON Payload 

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "group": "120363123456789@g.us",
  "message": "Halo @andi, tolong cek ya.",
  "mentions": ["6281299999999"],
  "is_priority": true,
  "simulate_typing": false,
  "quoted_id": "3EB0..."
}
```

RESPONSE EXAMPLE

JSON Response 

```
{
  "status": true,
  "message": "Message sent successfully",
  "data": {
    "device": "WAPI-ABC1234",
    "target": "628123456789",
    "message": "Hello World!",
    "message_id": "3EB0X123456789",
    "wa_status": "sent",
    "response": {
      "status": "sent",
      "to": "628123456789",
      "id": "3EB0X123456789"
    }
  }
}
```

```
}  
}  
}
```

<> PHP SCRIPT SAMPLE

PHP cURL Script



```
<?php  
$url = "https://wapisender.id/api/message/send";  
$data = [  
    "api_key" => "YOUR_API_KEY",  
    "device_key" => "WAPI-XXXXXX",  
    "group" => "120363123456789@g.us",  
    "message" => "Halo @andi, ini mention dari API.",  
    // Mention list: phone numbers or JIDs (works best in group chat)  
    "mentions" => ["6281299999999"],  
    // Optional: defaults to true if omitted - faster queue. Use false for bulk/campaign  
    "is_priority" => true,  
    "simulate_typing" => false,  
];  
  
$ch = curl_init($url);  
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);  
curl_setopt($ch, CURLOPT_POST, true);  
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));  
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);  
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);  
curl_setopt($ch, CURLOPT_TIMEOUT, 160);  
  
$response = curl_exec($ch);  
curl_close($ch);  
  
echo $response;  
?>
```

POST /message/media

Send Media

Send image, video, or document. Supports multipart upload, sending by URL (server will download), or base64.



Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
to	string	Optional	Target phone number for personal. Use one of "to", "group", or "channel".
group	string	Optional	WhatsApp Group JID. Use one of "to", "group", or "channel".
channel	string	Optional	WhatsApp Channel ID (e.g., 12345678). Use one of "to", "group", or "channel".
file	file	Optional	Media file to upload (multipart/form-data). Use exactly one: file OR file_url OR media_data.
file_url	string	Optional	Public URL to media file. Server will download then send. Use exactly one: file OR file_url OR media_data.
media_data	string	Optional	Base64-encoded file content. Use exactly one: file OR file_url OR media_data.
filename	string	Optional	Optional filename for media_data (recommended).
mimetype	string	Optional	Optional mimetype for media_data (e.g., image/jpeg).
caption	string	Optional	Caption for image/video.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

// Option A (multipart upload)

```
// Requires: multipart/form-data
api_key: "YOUR_KEY"
device_key: "WAPI-XXX"
to: "08123456789"
caption: "Hello Image"
file: (binary_data)

// Option B (send by URL) - JSON
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-XXX",
  "to": "08123456789",
  "caption": "Hello Image",
  "file_url": "https://example.com/image.jpg"
}

// Option C (send by base64) - JSON
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-XXX",
  "to": "08123456789",
  "caption": "Hello Image",
  "filename": "image.jpg",
  "mimetype": "image/jpeg",
  "media_data": "BASE64_STRING_HERE"
}
```

RESPONSE EXAMPLE

JSON Response



```
{
  "status": true,
  "message": "Media sent successfully",
  "data": {
    "device": "WAPI-XXX",
    "target": "628123456789",
    "caption": "Hello Image",
    "source": "upload",
    "response": {
      "file": "image.jpg",
      "status": "sent",
      "to": "628123456789",
      "id": "3EB0X..."
    }
  }
}
```



```
<?php
$url = "https://wapisender.id/api/message/media";
$file_path = "path/to/your/image.jpg"; // Absolute path recommended

$data = [
    "api_key" => "YOUR_API_KEY",
    "device_key" => "WAPI-XXXXXX",
    "to" => "628123456789",
    "caption" => "Lihat foto ini!",
    "file" => new CURLFile($file_path)
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, $data); // multipart/form-data
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
?>
```

POST /message/location

Send Location

Send a static location.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.



Parameter	Type	Required	Description
to	string	Optional	Target phone number (Personal). Use either "to" or "group".
group	string	Optional	Group JID (Group). Use either "to" or "group".
lat	float	Required	Latitude.
long	float	Required	Longitude.
name	string	Optional	Location Name.
address	string	Optional	Location Address.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "to": "628123456789",
  "lat": -6.175392,
  "long": 106.827153,
  "name": "Monas",
  "address": "Gambir, Jakarta"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Location sent",
  "data": {
    "status": "sent",
    "to": "628123456789",
    "type": "location",
    "id": "3EB0X..."
  }
}
```

<> PHP SCRIPT SAMPLE

PHP cURL Script



```
<?php
$url = "https://wapisender.id/api/message/location";
$data = [
    "api_key" => "YOUR_API_KEY",
    "device_key" => "WAPI-XXXXXX",
    "to" => "628123456789",
    "lat" => -6.175392,
    "long" => 106.827153,
    "name" => "Monas",
    "address" => "Gambir, Jakarta"
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
?>
```

POST /message/sticker

Send Sticker

Send a WEBP sticker.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.



Parameter	Type	Required	Description
device_key	string	Required	Device Unique ID.
to	string	Optional	Target phone number (Personal). Use either "to" or "group".
group	string	Optional	Group JID (Group). Use either "to" or "group".
file	file	Required	Sticker file (WEBP recommended).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
// Multipart form request
file: sticker.webp
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Sticker sent",
  "data": {
    "status": "sent",
    "to": "...",
    "type": "sticker",
    "id": "3EB0X..."
  }
}
```

<> PHP SCRIPT SAMPLE

PHP cURL Script

```
<?php
$url = "https://wapisender.id/api/message/sticker";
$sticker_path = "path/to/sticker.webp";

$data = [
  "api_key" => "YOUR_API_KEY",
```

```

"device_key" => "WAPI-XXXXXX",
"to" => "628123456789",
"file" => new CURLFile($sticker_path)
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, $data);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
?>

```

POST **/message/contact**

Send Contact (vCard)

Send a vCard contact to a phone number.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
to	string	Optional	Target phone number (Personal). Use either "to" or "group".
group	string	Optional	Group JID (Group). Use either "to" or "group".
contact_name	string	Required	The name of the contact to display.



Parameter	Type	Required	Description
contact_number	string	Required	The phone number of the contact (e.g., 628123...).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "to": "120363...@g.us",
  "contact_name": "John Doe",
  "contact_number": "628123456789"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Contact sent",
  "data": {
    "status": "sent",
    "to": "120363...@g.us",
    "type": "contact",
    "id": "3EB0X..."
  }
}
```

<> PHP SCRIPT SAMPLE

PHP cURL Script

```
<?php
$url = "https://wapisender.id/api/message/contact";
$data = [
  "api_key" => "YOUR_API_KEY",
  "device_key" => "WAPI-XXXXXX",
  "to" => "628123456789",
  "contact_name" => "Rudi Tabuti",
  "contact_number" => "628123456789"
];
```

```

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
?>

```

POST /message/poll

Send Poll

Create a poll with options.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
to	string	Optional	Target phone number for personal. Use one of "to", "group", or "channel".
group	string	Optional	WhatsApp Group JID. Use one of "to", "group", or "channel".
channel	string	Optional	WhatsApp Channel ID. Use one of "to", "group", or "channel".
question	string	Required	Poll Question.
options	array	Required	Array of options (min 2).
max_validators	integer	Optional	Max selectable options (default 1).



REQUEST EXAMPLE (POST/JSON)

JSON Payload



```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "to": "120363...@g.us",
  "question": "Makan siang apa?",
  "options": ["Nasi Goreng", "Mie Ayam", "Bakso"],
  "max_validators": 1
}
```

RESPONSE EXAMPLE

JSON Response



```
{
  "status": true,
  "message": "Poll sent",
  "data": {
    "status": "sent",
    "to": "120363...@g.us",
    "type": "poll"
  }
}
```

<> PHP SCRIPT SAMPLE

PHP cURL Script



```
<?php
$url = "https://wapisender.id/api/message/poll";
$data = [
    "api_key" => "YOUR_API_KEY",
    "device_key" => "WAPI-XXXXXX",
    "to" => "120363...@g.us",
    "question" => "Mau makan apa hari ini?",
    "options" => ["Bakso", "Soto Ayam", "Nasi Uduk"],
    "max_validators" => 1
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
```

```
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
?>
```

POST /message/poll/vote

Vote Poll

Vote on an existing poll.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
to	string	Optional	Target phone number (Personal). Use either "to" or "group".
group	string	Optional	Group JID (Group). Use either "to" or "group".
poll_msg_id	string	Required	Message ID of the poll.
selected_options	array	Required	Array of selected options (MUST match exact option text).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
```

```
"to": "120363...@g.us",
"poll_msg_id": "3EB0...",
"selected_options": ["Nasi Goreng"]
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Poll vote sent",
  "data": {
    "status": "sent",
    "to": "...",
    "type": "poll_vote",
    "id": "3EB0X..."
  }
}
```

<> PHP SCRIPT SAMPLE

PHP cURL Script

```
<?php
$url = "${window.location.origin}/api/message/poll/vote";
$data = [
  "api_key" => "YOUR_API_KEY",
  "device_key" => "WAPI-XXXXXX",
  "to" => "120363...@g.us",
  "poll_msg_id" => "3EB0...", // ID of the poll message
  "selected_options" => ["Bakso"]
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);
```

```
echo $response;
?>
```

POST /message/reaction

Send Emoji Reaction

Send an emoji reaction (like, love, etc.) to a specific message. This requires the ID of the target message and the JID of its sender.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
to	string	Optional	Target phone number or Group JID where the message exists.
group	string	Optional	Group JID (Alternative to "to").
message_id	string	Required	The ID of the message to react to (e.g., 3EB0...).
sender_jid	string	Required	The JID of the original message sender (e.g., 62812...@s.whatsapp.net).
emoji	string	Required	The emoji character (e.g., "👍", "❤️"). Send an empty string "" to remove a reaction.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
```

```
"device_key": "WAPI-ABC1234",
"to": "628123456789",
"message_id": "3EB0...",
"sender_jid": "628123456789@s.whatsapp.net",
"emoji": "👍"
}
```

RESPONSE EXAMPLE

JSON Response



```
{
  "status": true,
  "message": "Reaction sent",
  "data": {
    "status": "sent",
    "to": "628123456789",
    "type": "reaction",
    "id": "3EB0X..."
  }
}
```

<> PHP SCRIPT SAMPLE


PHP cURL Script



```
<?php
$url = "https://wapisender.id/api/message/reaction";
$data = [
    "api_key" => "YOUR_API_KEY",
    "device_key" => "WAPI-XXXXXX",
    "to" => "628123456789",
    "message_id" => "3EB0123...",
    "sender_jid" => "628123456789@s.whatsapp.net",
    "emoji" => "❤️"
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);
```



```
echo $response;
?>
```

🔒 Cara Mendapatkan Message ID

Untuk mengirim reaction, Anda wajib menyertakan **message_id** dan **sender_jid**. Informasi ini bisa didapatkan dari dua cara:

- **Response Send Message:** Saat Anda mengirim pesan melalui API `/message/send`, respon akan berisi id pesan tersebut.
- **Webhook (Pesan Masuk):** Saat ada pesan masuk ke nomor Anda, payload **Webhook** akan mengirimkan `message_id` dan `sender_jid` secara real-time.

💡 MENGAPA PARAMETER INI WAJIB? (ANALOGI PERPUSTAKAAN)

WhatsApp tidak menyimpan pesan secara global, melainkan terorganisir per Chat. Untuk menemukan 1 pesan spesifik, sistem butuh 3 koordinat:

1. **Target Chat (to/group):** "Rak Bukunya". Lorong chat mana pesan itu berada.
2. **Sender JID:** "Penulisnya". Siapa yang mengirim pesan tersebut (sangat penting di Grup).
3. **Message ID:** "Judul Buku". Identitas unik pesan di dalam Lorong tersebut.

Mudahnya: Jika Anda menggunakan **Webhook**, ketiga data ini sudah kami sertakan dalam satu paket JSON. Anda tinggal mengembalikannya saja ke API Reaction.

POST `/message/delete`

Delete / Unsend Message

Unsend (revoke) a message for everyone or delete it locally (for me). Note that WhatsApp has a time limit to unsend messages for everyone.

Body / Query Parameters

Parameter	Type	Required	Description
<code>api_key</code>	string	Required	Your API Secret Key.
<code>device_key</code>	string	Required	Device Unique ID.
<code>to</code>	string	Optional	Target phone number, Group JID, or Channel JID. Use either "to" or "group".
<code>group</code>	string	Optional	Group JID (Alternative to "to").

Parameter	Type	Required	Description
message_id	string	Required	The exact ID of the message to delete/unsend.
delete_type	string	Optional	Pilihan: "everyone" (default, unsend untuk semua) atau "me" (hapus dari sisi bot sendiri).
sender_jid	string	Optional	Opsional: JID pengirim asli jika bot bertindak sebagai admin grup yang ingin meng-unsend pesan orang lain.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "to": "628123456789",
  "message_id": "3EB0...",
  "delete_type": "everyone"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Message deleted successfully",
  "data": {
    "status": "deleted",
    "to": "628123456789",
    "type": "everyone",
    "message_id": "3EB0...",
    "id": "3EB0..."
  }
}
```



```
<?php
$url = "${window.location.origin}/api/message/delete";
$data = [
    "api_key" => "YOUR_API_KEY",
    "device_key" => "WAPI-XXXXXX",
    "to" => "628123456789",
    "message_id" => "3EB0...",
    "delete_type" => "everyone"
];

$ch = curl_init($url);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($data));
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
curl_setopt($ch, CURLOPT_TIMEOUT, 160);

$response = curl_exec($ch);
curl_close($ch);

echo $response;
?>
```



Device Management

Programmatically manage your WhatsApp device connections.

POST**/device/create**

Create Device

Create a new device programmatically. You must provide a valid `package_id` to automatically purchase a subscription for the new device.



Valid Package IDs

Package ID	Name	Duration	Price
1	Starter	30 Days	Rp 25.000



Package ID	Name	Duration	Price
2	Professional	30 Days	Rp 50.000
5	Starter	365 Days	Rp 300.000
6	Professional	365 Days	Rp 600.000

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
name	string	Required	Name of the new device.
package_id	integer	Required	ID of the package to purchase for the new device.
voucher_code	string	Optional	Optional. Voucher code to apply discount on the package price.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "name": "My New Device API",
  "package_id": 1
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Device created successfully.",
  "data": {
    "unique_id": "WAPI-ABC1234",
    "name": "My New Device API",
    "status": "scanning",
    "subscription_end_date": "2026-04-15 12:00:00"
  }
}
```

POST /device/connect

Get QR Code

Initiate a connection session and retrieve the QR code (Base64 string) for scanning.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Connection initiated.",
  "data": {
    "code": "2@...Base64String...==", // Render this as QR Code
    "duration": 20000 // Valid duration in ms
  }
}
```



POST /device/pair

Get Pairing Code

Generate an 8-digit pairing code to link a device via phone number.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
phone	string	Required	Exact phone number to pair (e.g. 62812... without +).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "phone": "628123456789"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Pairing code generated.",
  "data": {
    "code": "ABC-1234" // Display this code to the user
  }
}
```



POST /device/disconnect

Disconnect Device

Logout and disconnect a device from WhatsApp. This will clear the session and require re-authentication.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Device disconnected successfully.",
  "data": {
    "device_key": "WAPI-ABC1234",
    "status": "disconnected"
  }
}
```

POST /device/validate

Validate WhatsApp Number (Single & Bulk)



Check if one or multiple phone numbers are registered on WhatsApp. Device must be connected to use this endpoint.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID (must be connected).
phone	string	Optional	Single phone number to validate (e.g. 628123456789). Required if phones is empty.
phones	array	Optional	List of phone numbers for bulk validation. Required if phone is empty.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "phones": ["628123456789", "628987654321"]
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Bulk number validation completed.",
  "data": [
    {
      "phone": "628123456789",
      "valid": true,
      "jid": "628123456789@es.whatsapp.net"
    },
    {
      "phone": "628987654321",
      "valid": false
    }
  ]
}
```

```
}  
]  
}
```

POST /device/groups

Get Joined Groups

Retrieve all WhatsApp groups that the device has joined. Device must be connected.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID (must be connected).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{  
  "api_key": "YOUR_KEY",  
  "device_key": "WAPI-ABC1234"  
}
```

RESPONSE EXAMPLE

JSON Response

```
{  
  "status": true,  
  "message": "Groups retrieved successfully.",  
  "data": [  
    {  
      "jid": "120363123456789@g.us",  
      "name": "My Group Name",  
      "topic": "Group description",  
      "owner": "628123456789@s.whatsapp.net",  
    }  
  ]  
}
```

```
        "participants": 25
      },
      {
        "jid": "120363987654321@g.us",
        "name": "Another Group",
        "topic": "",
        "owner": "628987654321@s.whatsapp.net",
        "participants": 10
      }
    ]
  }
}
```

POST /device/channels

Get Subscribed Channels

Retrieve all WhatsApp Channels (Newsletters) that the device is subscribed to or owns. Device must be connected.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID (must be connected).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234"
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Channels retrieved successfully.",
  "data": [
    {
      "id": "12345678@newsletter",
      "state": { "type": "ACTIVE" },
      "creation_time": 1678900000,
      "name": {
        "text": "My Channel Name",
        "update_time": 1678900000
      },
      "role": "OWNER"
    }
  ]
}
```

POST /device/info

Get Device Information

Retrieve detailed information about a device, its connection status, and subscription/expiry details.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234"
}
```

RESPONSE EXAMPLE

JSON Response



```
{
  "status": true,
  "message": "Device information retrieved successfully.",
  "data": {
    "unique_id": "WAPI-ABC1234",
    "name": "My Device",
    "phone": "628123456789",
    "status": "connected",
    "webhook_url": "https://your-webhook.com/handler",
    "subscription": {
      "package_name": "Pro Plan (365 Days)",
      "status": "active",
      "start_date": "2024-01-01 10:00:00",
      "end_date": "2025-01-01 10:00:00",
      "is_expired": false
    }
  }
}
```



Group Management

Manage WhatsApp groups programmatically.

POST

/groups/create

Create Group

Create a new WhatsApp group with initial participants.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID (must be connected).
name	string	Required	Name of the new group.



Parameter	Type	Required	Description
participants	array	Required	List of phone numbers to invite (e.g. ["6281...", "6282..."]).

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "name": "My New Group",
  "participants": ["628123456789", "628987654321"]
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Group creation queued.",
  "data": {
    "jid": "120363123456789@g.us"
  }
}
```

GET /groups/{groupJid}

Get Group Info

Get details and participants of a specific group.

Body / Query Parameters



Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key (send as query param).
device_key	string	Required	Device Unique ID (send as query param).

REQUEST EXAMPLE (POST/JSON)

JSON Payload



GET /api/groups/120363123456789@g.us?api_key=KEY&device_key=WAPI-ABC

RESPONSE EXAMPLE

JSON Response



```
{
  "status": true,
  "data": {
    "jid": "120363123456789@g.us",
    "name": "My New Group",
    "owner": "628123456789@s.whatsapp.net",
    "topic": "Group Description",
    "participants": [
      { "jid": "628123456789@s.whatsapp.net", "admin": true, "super_admin": true },
      { "jid": "628987654321@s.whatsapp.net", "admin": false, "super_admin": false }
    ]
  }
}
```

POST /groups/{groupJid}/participants

Update Participants

Add, remove, promote, or demote participants in a group.

Body / Query Parameters



Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
action	string	Required	One of: add, remove, promote, demote.
participants	array	Required	List of phone numbers/JIDs.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "action": "add",
  "participants": ["628555666777"]
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Participant update queued."
}
```

GET

/groups/{groupJid}/join-requests
Get Join Requests

List pending join requests for the group (admin only).

Body / Query Parameters



Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

GET /api/groups/120363...@g.us/join-requests?api_key=...&device_key=...

RESPONSE EXAMPLE

JSON Response

{
 "status": true,
 "data": [
 { "jid": "628111222333@s.whatsapp.net", "requested_at": 1700000000 }
]
}

POST /groups/{groupId}/join-requests

Update Join Requests

Approve or reject join requests.

Body / Query Parameters

Parameter	Type	Required	Description
api_key	string	Required	Your API Secret Key.
device_key	string	Required	Device Unique ID.
action	string	Required	One of: approve, reject.



Parameter	Type	Required	Description
participants	array	Required	List of JIDs to approve/reject.

REQUEST EXAMPLE (POST/JSON)

JSON Payload

```
{
  "api_key": "YOUR_KEY",
  "device_key": "WAPI-ABC1234",
  "action": "approve",
  "participants": ["628111222333@s.whatsapp.net"]
}
```

RESPONSE EXAMPLE

JSON Response

```
{
  "status": true,
  "message": "Join request update queued."
}
```

⚡ Webhooks

Configure a Webhook URL in your device settings to receive real-time HTTP POST notifications when a message is received.

⚡ How it works

When a new message arrives on your connected WhatsApp device, our system immediately sends a POST request to your configured URL with the message details in JSON format.

Payload Format

The JSON body sent to your webhook URL:

Webhook Payload (General)

```
{
  "event": "message",
  "event_id": "WAPI-MESSAGE-20260303-ABCD",
  "device_id": "WAPI-ABC1234",
  "phone": "628123456789",
  "chat_jid": "628123456789@s.whatsapp.net",
  "sender_jid": "628123456789@s.whatsapp.net",
  "message_id": "3EB0X123456789",
  "message": "Hello there!",
  "timestamp": 1707890000,
  "push_name": "John Doe",
  "is_group": false,
  "media_data": "...", // Base64 string (only for media events)
  "mimetype": "image/jpeg" // File mimetype (only for media events)
}
```

Event Types

message	image	video
audio	document	location
live_location	contact	sticker
reaction	group_participant_join	group_participant_leave

Location Event Details

When the event is `location` or `live_location`, an additional `location` object is provided:

Location Object Structure

```
{
  "event": "location",
  "event_id": "WAPI-LOCATION-20260303-XYZ1",
  ...
  "location": {
    "latitude": -6.175392,
    "longitude": 106.827153,
    "name": "Monas",
    "address": "Gambir, Jakarta Pusat"
  }
}
```

Media Event Details (Image, Video, Audio, Document, Sticker)

For media-related events, the payload includes the raw file content in `base64` format. You can decode this to save the file locally or to cloud storage.



Media Data Handling



```
{
  "event": "image",
  "event_id": "WAPI-IMAGE-20260303-IMG1",
  ...
  "media_data": "/9j/4AAQSkZJRg...", // Long base64 string
  "mimetype": "image/jpeg"
}
```

Group Events

Participant Join

group_participant_join



```
{
  "event": "group_participant_join",
  "device_id": "WAPI-ABC1234",
  "group_jid": "120363...@g.us",
  "member_jid": "62812...@s.whatsapp.net",
  "role": "member",
  "timestamp": 1707890000
}
```

Participant Leave

group_participant_leave



```
{
  "event": "group_participant_leave",
  "device_id": "WAPI-ABC1234",
  "group_jid": "120363...@g.us",
  "member_jid": "62812...@s.whatsapp.net",
  "timestamp": 1707890000
}
```

Reaction Event Details

When a user reacts to a message, your webhook will receive a reaction event:

Reaction Event Structure



```
{
  "event": "reaction",
  "device_id": "WAPI-ABC1234",
  "phone": "628123456789",
  "chat_jid": "628123456789@s.whatsapp.net",
}
```



```
"sender_jid": "628123456789@s.whatsapp.net",
"message_id": "3EB0X123456789", // ID of the reaction message itself
"reaction": {
  "text": "👍", // The emoji
  "target_id": "3EB0ASDFGHJ123", // ID of the message being reacted to
  "sender_jid": "628123456789@s.whatsapp.net" // Who sent the reaction
},
"timestamp": 1707890000
}
```

Code Examples

● PHP (Laravel)

WebhookController.php



```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use Illuminate\Support\Facades\Log;

class WebhookController extends Controller
{
    public function handle(Request $request)
    {
        // 1. Get the JSON payload
        $data = $request->all();


        // 2. Validate event type
        if (($data['event'] ?? '') !== 'message') {
            return response()->json(['status' => 'ignored']);
        }

        // 3. Process the message
        $sender = $data['phone'];
        $message = $data['message'];
        $deviceId = $data['device_id'];

        // --- Handle Media ---
        if (isset($data['media_data'])) {
            $fileBinary = base64_decode($data['media_data']);
            $filename = "media_" . time() . ".bin";
            // In a real app, use $data['mimetype'] to determine proper extension
            file_put_contents(storage_path("app/public/webhooks/" . $filename), $fileBinary);
        }

        Log::info("New Message from $sender on $deviceId: $message");

        // TODO: Add your custom logic here (e.g., save to DB, auto-reply)
```



```
        return response()->json(['status' => 'success']);
    }
}
```

● Node.js (Express)

```
app.js

const express = require('express');
const app = express();

// Middleware to parse JSON bodies
app.use(express.json());

app.post('/webhook', (req, res) => {
    const data = req.body;

    // 1. Validate event
    if (data.event !== 'message') {
        return res.status(200).send('Ignored');
    }

    // 2. Process message
    const { phone, message, device_id } = data;

    console.log(`New Message from ${phone} on ${device_id}: ${message}`);

    // TODO: Add your business logic here

    res.status(200).json({ status: 'success' });
});

app.listen(3000, () => console.log('Webhook server running on port 3000'));
```

● PHP (Auto-Reply Bot)

```
bot.php

<?php
/**
 * WhatsApp Auto-Reply Bot Example
 * This script will automatically reply to "hai" with a quoted/reply message.
 */

// 1. Configuration
$api_key = "YOUR_API_KEY";
$device_key = "WAPI-XXXXXX"; // Your Device ID
$api_url = "https://wapisender.id/api/message/send";
```

```
// 2. Get the Webhook Data
$input = file_get_contents("php://input");
$data = json_decode($input, true);

// 3. Simple Bot Logic
if (isset($data['event']) && $data['event'] === 'message') {
    $sender = $data['phone'];
    $message = strtolower(trim($data['message']));
    $chat_jid = $data['chat_jid'];
    $message_id = $data['message_id']; // ID pesan yang masuk

    // Respond if message is "hai"
    if ($message === 'hai') {
        $reply_text = "Halo! Ini adalah balasan otomatis dari bot. 😊";

        $payload = [
            "api_key" => $api_key,
            "device_key" => $device_key,
            "message" => $reply_text,
            "quoted_id" => $message_id, // Membalas pesan asli (Quote)
            "quoted_participant" => $data['sender_jid'], // JID pengirim asli (Penting untuk Qu
            "is_priority" => true, // optional; default true if omitted (faster queue)
        ];

        // determine target (group or personal)
        if ($data['is_group']) {
            $payload['group'] = $chat_jid;
        } else {
            $payload['to'] = $sender;
        }

        // Send Reply via API
        $ch = curl_init($api_url);
        curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
        curl_setopt($ch, CURLOPT_POST, true);
        curl_setopt($ch, CURLOPT_POSTFIELDS, json_encode($payload));
        curl_setopt($ch, CURLOPT_HTTPHEADER, ["Content-Type: application/json"]);
        curl_setopt($ch, CURLOPT_CONNECTTIMEOUT, 10);
        curl_setopt($ch, CURLOPT_TIMEOUT, 160);

        $result = curl_exec($ch);
        curl_close($ch);
    }
}

// Always return 200 OK to the webhook sender
http_response_code(200);
echo json_encode(["status" => "processed"]);
?>
```



Tips & Troubleshooting

⚠️ 503 Service Unavailable (Apache / Nginx)

Jika respons berupa halaman HTML 503 Service Unavailable dari Apache setelah ~100 detik, request Anda sudah sampai ke server tetapi **web server memutus koneksi** sebelum PHP selesai menunggu antrian WhatsApp (~150s). Ini bukan format JSON error dari API — payload Anda biasanya sudah benar.

- **Naikkan timeout client & server:** API menunggu konfirmasi kirim (bisa sampai ~150 detik). Set `CURLOPT_TIMEOUT ≥ 160` dan pastikan Apache/PHP timeout $≥ 180$ detik.
- **Cloudflare:** grey cloud (DNS only) untuk domain API — orange cloud timeout ~100 detik.
- Naikkan `proxy_read_timeout / fastcgi_read_timeout` di Nginx/Apache menjadi $≥ 180$ detik.
- PHP-FPM: `request_terminate_timeout` dan `max_execution_time ≥ 180`.
- Cek device connected dan tidak ada antrian panjang di device yang sama.
- Untuk bulk, kirim dengan jeda 1–2 detik antar request; jangan paralel banyak request ke satu device.

🕒 Operation Timed Out (20s / 30s / 60s)

Ini adalah kendala yang paling sering ditemui saat integrasi API. Pesan error seperti `Operation timed out after 20001 milliseconds` atau `30000 milliseconds` muncul jika script Anda (CURL/Guzzle/Axios) memutus koneksi sebelum server selesai memproses antrian proteksi. Wapisender mendukung antrian hingga ~150 detik — timeout client harus lebih tinggi.

• Penyebab Utama Antrian:

- **Concurrency Lock:** Setiap akun memiliki pembatasan `Max Concurrent Sending` (default: 1). Jika Anda mengirim 20 request sekaligus secara instan, request terakhir mungkin harus mengantri di server lebih lama dari 30 detik.
- **Random Delay:** Jika fitur jeda acak aktif (Profil > API Settings), server sengaja menahan pesan 1-15 detik per pesan agar terlihat manusiawi.
- **Simulate Typing:** Menyalakan `simulate_typing: true` menambahkan delay waktu mengetik sebelum pesan terkirim.

✓ Solusi Rekomendasi:

1. **Naikkan Timeout Client:** Atur timeout di script Anda menjadi ****160 detik**** (contoh: `curl_setopt($ch, CURLOPT_TIMEOUT, 160);`). Nilai default PHP cURL (~30s) atau Guzzle (~20–30s) terlalu pendek.
2. **Gunakan Delay Sisi Client:** Jangan membombardir server dengan request instan. Beri jeda 1-2 detik antar request di script Anda sendiri agar antrian di server tetap lancar.



3. **Matikan Fitur Delay Jika Tidak Perlu:** Matikan Random Delay dan set `simulate_typing: false` untuk kecepatan maksimal (namun risiko banned lebih tinggi).

4. **Sesuaikan Concurrency:** Jika beban kirim tinggi, naikan Max Concurrent Sending di dashboard profil Anda (gunakan dengan bijak).



IP Whitelist Error

Jika muncul error `IP is not whitelisted` secara tiba-tiba, pastikan IP server Anda tidak berubah.

Tambahkan `0.0.0.0` hanya untuk testing sementara.



Device Connected Status

API hanya akan memproses pengiriman jika status perangkat **connected**. Selalu gunakan webhook event `device_status` untuk memantau koneksi secara realtime.