Lab 11: 4-way Handshake Over EAPoL and WiFi Cracking With aircrack-ng

Part 1: Understanding the 4-way Handshake


Nothing to submit.

Part 2: Analyzing a Wireless Capture File

? Question 1 - How many sets of 4-way handshake exchanges are there (4 messages in one set)

2

? Question 2 - Submit a screenshot of your filtered results.



!? Question 3 - What protocol is listed under the protocol column?

EAPOL

? Question 4 - What encryption key type is being used for this key exchange?

```
▼ 802.1X Authentication

     Version: 802.1X-2004 (2)
     Type: Key (3)
     Length: 95
     Key Descriptor Type: EAPOL RSN Key (2)
     [Message number: 1]

✓ Key Information: 0x008a

       .... .... .010 = Key Descriptor Version: AES Cipher, HMAC-SHA1 MIC (2)
       .... 1... = Key Type: Pairwise Key
       .... = Key Index: 0
       .... .... .0.. .... = Install: Not set
       .... 1... = Key ACK: Set
       .... ...0 .... = Key MIC: Not set
       .... ..0. .... = Secure: Not set
       .... .0.. .... = Error: Not set
       .... 0... ... = Request: Not set
       ...0 .... = Encrypted Key Data: Not set
       ..0. .... = SMK Message: Not set
     Key Length: 16
     Replay Counter: 1
     WPA Key Nonce: 04c2fd885a0aaf64fec6be834047fa7d623c9502b4171922d8075094f8e051b1
     WPA Key RSC: 0000000000000000
     WPA Key ID: 0000000000000000
     WPA Key Data Length: 0
Anonce
```

!? Question 5 - Based on that encryption key type, what possible encryption standards are being used for this communication?

```
▼ 802.1X Authentication

     Version: 802.1X-2004 (2)
     Type: Key (3)
     Length: 95
     Key Descriptor Type: EAPOL RSN Key (2)
     [Message number: 1]


✓ Key Information: 0x008a
       .... .... .010 = Key Descriptor Version: AES Cipher, HMAC-SHA1 MIC (2)
       .... 1... = Key Type: Pairwise Key
       .... = Key Index: 0
       .... .0.. ... = Install: Not set
       .... 1... = Key ACK: Set
       .... 0 .... = Key MIC: Not set
       .... ..0. .... = Secure: Not set
       .... .0.. .... = Error: Not set
       .... 0... .... = Request: Not set
        ...0 .... = Encrypted Key Data: Not set
        ..0. .... = SMK Message: Not set
     Key Length: 16
     Replay Counter: 1
     WPA Key Nonce: 04c2fd885a0aaf64fec6be834047fa7d623c9502b4171922d8075094f8e051b1
     WPA Key RSC: 0000000000000000
     WPA Key ID: 0000000000000000
     WPA Key Data Length: 0
WPA, AES
```

!? Question 6 - Look through the first set of key exchanges under the 802.1x Authentication > Key Information field. What changes do you notice during the handshake.

Replay counter, Key nonce and the length

Part 3: Key Cracking with aircrack-ng

? Question 7 - Submit a screenshot of your terminal running the aircrack-ng program.



!? Question 8 - What are the three fields on the left hand side of the aircrack-ng display. Match each one of these fields with the key abbreviations described in Part 1 of this lab.

Master key → mpk and the transient key is PTK and Eapol Mac HMac is Snonce

? Question 9 - In your own words, what is aircrack-ng doing and what is it solving for?

Aircrack ng is decrypting all of the information in the plain text that is encrypted in the file via the PSK

Part 4: Submission

Convert your network document into a .PDF and upload a single <code>lastname_lab11.pdf</code> file to Brightspace through the attachment uploads option.