Table 5.2 Summary of SQL Syntax

```
CREATE TABLE  ( <column name> <column type> [ <attribute constraint> ]
                            { , <column name> <column type> [ <attribute constraint> ] }
                            [  { ,  } ] )
DROP TABLE 
ALTER TABLE  ADD <column name> <column type>
SELECT [ DISTINCT ] <attribute list>
FROM ( { <alias> } | <joined table> ) { , (  { <alias> } | <joined table> ) }
[ WHERE < condition> ]
[ GROUP BY <grouping attributes> [ HAVING <group selection condition> ] ]
[ORDER BY <column name> [ <order> ] { , <column name> [ <order> ] } ]
<attribute list> ::= ( * | ( <column name> | <function> ( ( [ DISTINCT ] <column name> | * ) ) )
                    { , ( <column name> | <function> ( ( [ DISTINCT] <column name> | * ) ) } ) )
<grouping attributes> ::= <column name> { , <column name> }
<order> ::= ( ASC | DESC )
INSERT INTO  [ ( <column name> { , <column name> } ) ]
( VALUES ( <constant value> , { <constant value> } ) { , ( <constant value> { , <constant value> } ) }
< < select statement> )
DELETE FROM 
[ WHERE <selection condition> ]
UPDATE 
SET <column name> = <value expression> { , <column name> = <value expression> }
[ WHERE <selection condition> ]
CREATE [ UNIQUE] INDEX <index name>
ON  ( <column name> [ <order> ] { , <column name> [ <order> ] } )
[CLUSTER]
DROP INDEX <index name>
CREATE VIEW <view name> [ ( <column name> { , <column name> } ) ]
AS <select statement>
DROP VIEW <view name>
```