

# My bs notes

Makus

November 8, 2023

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>math</b>	<b>1</b>
2.1	general . . . . .	1
2.1.1	bases . . . . .	1
2.2	calculus . . . . .	2
2.2.1	Newton's iteration . . . . .	2
<b>3</b>	<b>Computer Science</b>	<b>2</b>
3.1	bit shit . . . . .	2
3.1.1	bitwise operator quirks? . . . . .	2
3.1.2	IEEE 754 . . . . .	2

## 1 Introduction

just random ass notes, separated by sections.

## 2 math

### 2.1 general

#### 2.1.1 bases

given

$n$  = base of number representation  
 $x$  = number that is represented in base  $n$ ,

Then  $\frac{x}{n}$  shifts everything in  $x$  towards the left by one and  $x \cdot n$  shifts everything to the right.

## 2.2 calculus

### 2.2.1 Newton's iteration

## 3 Computer Science

will be using c++ for every example

### 3.1 bit shit

#### 3.1.1 bitwise operator quirks?

In C++, every number is represented in binary, or base 2. Thus if anyone were to divide a number by two, then

```
x=x>>1;//shifting towards the right
```

works the same, but is faster. it also rounds up. Conversely, if anyone were to multiply by two, then

```
x=x<<1;//shifting towards the left
```

does the same.

#### 3.1.2 IEEE 754

This is how floats in C++ are stored. Floats are stored in 32 bit. the first bit is sign. The second to ninth bit is exponent, and the 10th to 32th bit is the mantissa. the exponent has an offset of 127, because it needs negative exponents. The mantissa, 23 bits,