UCI Online Retail

Dataset-Specific Laboratory Workbook

Data Acquisition & Manipulation with Pandas

GROUP Group A • Source: UCI Machine Learning Repository — Online Retail (Excel; transaction-line data)

How to use this workbook

You are a junior data analyst supporting an online retailer. Finance and operations need a trustworthy sales table before they will accept country, customer, product, and cancellation summaries.

This workbook assumes Python essentials and notebook use. Its focus is not Python syntax revision; it is disciplined Pandas reasoning: acquire → inspect → diagnose → select/filter → clean/transform → group/aggregate → merge/reconcile → export.

ROW GRAIN One row represents an invoice-product line, not necessarily one invoice.

KEYS & IDENTITY InvoiceNo identifies invoices; StockCode identifies products; CustomerID is an identifier, not a quantity.

Learning outcomes

- Acquire the dataset using the source-appropriate Pandas/API/database syntax.
- Diagnose structure, dtypes, missingness, duplicates, ranges, categories and memory implications before cleaning.
- Use loc/iloc, boolean masks, query, isin, between, sort_values and column selection intentionally.
- Clean and transform without overwriting raw data or silently changing analytical meaning.
- Use groupby, agg, named aggregation, value_counts, pivot/crosstab/transform where justified.
- Join/merge/concat with explicit key/cardinality reasoning and post-operation validation.
- Export reproducible outputs and explain why each transformation was necessary.

Acquisition starter

```
# Excel acquisition
import pandas as pd
path = "Online Retail.xlsx"
df = pd.read_excel(path, sheet_name=0)

# Optional: inspect workbook first
xls = pd.ExcelFile(path)
print(xls.sheet_names)

# Memory-conscious subset
use = ["InvoiceNo","StockCode","Description","Quantity",
       "InvoiceDate","UnitPrice","CustomerID","Country"]
df = pd.read_excel(path, usecols=use, parse_dates=["InvoiceDate"])
```

Core Pandas syntax map

Capability	Methods / properties
Inspect	shape, head(), tail(), sample(), columns, dtypes, info(), memory_usage(), describe(), nunique(), value_counts(), isna(), duplicated()
Select	df[col], df[[...]], loc[rows, cols], iloc[rows, cols], filter(), select_dtypes()
Filter	boolean masks with & | ~, isin(), between(), str methods, query(), notna()/isna()
Clean	copy(), dropna(), fillna(), drop_duplicates(), astype(), to_numeric(), to_datetime(), str.strip(), replace(), map(), rename()
Transform	assign(), where(), mask(), cut(), qcut(), apply()/map() when justified; prefer vectorization
Group	groupby(), size(), count(), sum(), mean(), median(), min(), max(), nunique(), agg(), transform(), pivot_table(), crosstab()
Combine	merge(how=..., on=..., validate=..., indicator=True), join(), concat(), suffixes
Validate/export	assert, equals(), compare counts/totals, to_csv(index=False), to_excel(index=False), to_parquet()

Case Study 1: Acquisition & structural audit

REAL-LIFE QUESTION Can Finance safely calculate sales from the workbook as delivered?

WHY THIS MATTERS A Pandas method is justified by the analytical question, the row grain, data quality, and the risk of changing meaning—not by habit.

1. **1. State the grain before coding:** Write one sentence defining what one row represents. Identify candidate keys and whether they should be unique.
2. **2. Inspect before transforming:** Run the inspection code. Record shape, dtypes, missingness, duplicates, ranges/categories, and suspicious values.
3. **3. Predict the effect:** Before running the transformation, predict whether row count, column count, null count, or grain should change.
4. **4. Execute the Pandas operation:** Run the code below one logical block at a time. Do not run the whole notebook blindly.
5. **5. Validate:** Compare before/after counts, key uniqueness, totals or category counts. A successful cell is not evidence that the result is correct.
6. **6. Interpret:** Write 2–4 sentences: what changed, why it was justified, what remains uncertain, and what you would tell the business user.

Guided implementation

```
df.shape
df.head()
df.tail()
df.sample(5, random_state=42)
df.columns.tolist()
df.info()
df.dtypes
df.memory_usage(deep=True).sort_values(ascending=False)
df.isna().sum().sort_values(ascending=False)
df.duplicated().sum()
df.nunique().sort_values()
df.describe(include="all").T
```

Stop & Predict

- Which object(s) will change shape after this code?

- Could this operation silently remove or duplicate valid records? How will you detect that?
- What alternative Pandas method could solve part of this task, and why is the chosen one preferable here?

Checkpoint evidence

Evidence	Your result	Interpretation
Shape / row count	_____	_____
Missing / duplicate check	_____	_____
Key or total reconciliation	_____	_____

Practice ladder

Basic — Modify one filter/selection condition and return only the columns needed to answer a narrower business question.

Intermediate — Produce a second summary using at least two of: query(), isin(), between(), sort_values(), value_counts(), agg(), transform(), pivot_table(). Explain the grain.

Challenge — Design a validation test with assert or explicit before/after reconciliation that would catch a plausible silent error.

Debug — Create or identify one wrong approach (chained assignment, == NaN, and/or, unvalidated merge, blanket dropna, or iterrows) and repair it.

Case Study 2: Filtering & selecting valid business populations

REAL-LIFE QUESTION Which rows are completed positive-value sales, which are cancellations, and which require review?

WHY THIS MATTERS A Pandas method is justified by the analytical question, the row grain, data quality, and the risk of changing meaning—not by habit.

7. **1. State the grain before coding:** Write one sentence defining what one row represents. Identify candidate keys and whether they should be unique.
8. **2. Inspect before transforming:** Run the inspection code. Record shape, dtypes, missingness, duplicates, ranges/categories, and suspicious values.
9. **3. Predict the effect:** Before running the transformation, predict whether row count, column count, null count, or grain should change.
10. **4. Execute the Pandas operation:** Run the code below one logical block at a time. Do not run the whole notebook blindly.
11. **5. Validate:** Compare before/after counts, key uniqueness, totals or category counts. A successful cell is not evidence that the result is correct.
12. **6. Interpret:** Write 2–4 sentences: what changed, why it was justified, what remains uncertain, and what you would tell the business user.

Guided implementation

```
df["InvoiceNo"] = df["InvoiceNo"].astype("string")
df["is_cancelled"] = df["InvoiceNo"].str.upper().str.startswith("C", na=False)
df["line_value"] = df["Quantity"] * df["UnitPrice"]

completed = df.loc[
    (~df["is_cancelled"]) &
    (df["Quantity"] > 0) &
    (df["UnitPrice"] > 0),
    ["InvoiceNo","StockCode","Description","Quantity","UnitPrice",
     "line_value","CustomerID","Country","InvoiceDate"]
].copy()

review = df.loc[
    df["is_cancelled"] | (df["Quantity"] <= 0) | (df["UnitPrice"] <= 0)
```

```
].copy()

completed.sort_values(["Country","InvoiceDate"], ascending=[True,False]).head()
```

Stop & Predict

- Which object(s) will change shape after this code?
- Could this operation silently remove or duplicate valid records? How will you detect that?
- What alternative Pandas method could solve part of this task, and why is the chosen one preferable here?

Checkpoint evidence

Evidence	Your result	Interpretation
Shape / row count	_____	_____
Missing / duplicate check	_____	_____
Key or total reconciliation	_____	_____

Practice ladder

Basic — Modify one filter/selection condition and return only the columns needed to answer a narrower business question.

Intermediate — Produce a second summary using at least two of: query(), isin(), between(), sort_values(), value_counts(), agg(), transform(), pivot_table(). Explain the grain.

Challenge — Design a validation test with assert or explicit before/after reconciliation that would catch a plausible silent error.

Debug — Create or identify one wrong approach (chained assignment, == NaN, and/or, unvalidated merge, blanket dropna, or iterrows) and repair it.

Case Study 3: Cleaning & feature creation

REAL-LIFE QUESTION How should missing customer IDs, duplicate lines and inconsistent text be handled without destroying auditability?

WHY THIS MATTERS A Pandas method is justified by the analytical question, the row grain, data quality, and the risk of changing meaning—not by habit.

13. **1. State the grain before coding:** Write one sentence defining what one row represents. Identify candidate keys and whether they should be unique.
14. **2. Inspect before transforming:** Run the inspection code. Record shape, dtypes, missingness, duplicates, ranges/categories, and suspicious values.
15. **3. Predict the effect:** Before running the transformation, predict whether row count, column count, null count, or grain should change.
16. **4. Execute the Pandas operation:** Run the code below one logical block at a time. Do not run the whole notebook blindly.
17. **5. Validate:** Compare before/after counts, key uniqueness, totals or category counts. A successful cell is not evidence that the result is correct.
18. **6. Interpret:** Write 2–4 sentences: what changed, why it was justified, what remains uncertain, and what you would tell the business user.

Guided implementation

```
clean = completed.copy()
clean["Description"] = clean["Description"].astype("string").str.strip()
clean["Country"] = clean["Country"].astype("string").str.strip()

# Do not drop CustomerID blindly: anonymous sales may still be valid revenue.
```

```
clean["CustomerID"] = clean["CustomerID"].astype("string")

before = len(clean)
exact_dupes = clean.duplicated().sum()
clean = clean.drop_duplicates().copy()
print("Removed exact duplicates:", before - len(clean))

clean["invoice_date"] = clean["InvoiceDate"].dt.date
clean["invoice_month"] = clean["InvoiceDate"].dt.to_period("M").astype(str)

clean.to_csv("online_retail_clean.csv", index=False)
```

Stop & Predict

- Which object(s) will change shape after this code?
- Could this operation silently remove or duplicate valid records? How will you detect that?
- What alternative Pandas method could solve part of this task, and why is the chosen one preferable here?

Checkpoint evidence

Evidence	Your result	Interpretation
Shape / row count	_____	_____
Missing / duplicate check	_____	_____
Key or total reconciliation	_____	_____

Practice ladder

Basic — Modify one filter/selection condition and return only the columns needed to answer a narrower business question.

Intermediate — Produce a second summary using at least two of: query(), isin(), between(), sort_values(), value_counts(), agg(), transform(), pivot_table(). Explain the grain.

Challenge — Design a validation test with assert or explicit before/after reconciliation that would catch a plausible silent error.

Debug — Create or identify one wrong approach (chained assignment, == NaN, and/or, unvalidated merge, blanket dropna, or iterrows) and repair it.

Case Study 4: Grouping & aggregation

REAL-LIFE QUESTION Which countries generate revenue and orders, and why is invoice count different from row count?

WHY THIS MATTERS A Pandas method is justified by the analytical question, the row grain, data quality, and the risk of changing meaning—not by habit.

19. **1. State the grain before coding:** Write one sentence defining what one row represents. Identify candidate keys and whether they should be unique.
20. **2. Inspect before transforming:** Run the inspection code. Record shape, dtypes, missingness, duplicates, ranges/categories, and suspicious values.
21. **3. Predict the effect:** Before running the transformation, predict whether row count, column count, null count, or grain should change.
22. **4. Execute the Pandas operation:** Run the code below one logical block at a time. Do not run the whole notebook blindly.
23. **5. Validate:** Compare before/after counts, key uniqueness, totals or category counts. A successful cell is not evidence that the result is correct.
24. **6. Interpret:** Write 2–4 sentences: what changed, why it was justified, what remains uncertain, and what you would tell the business user.

Guided implementation

```
country_kpi = (
    clean.groupby("Country", dropna=False)
         .agg(revenue=("line_value","sum"),
              units=("Quantity","sum"),
              orders=("InvoiceNo","nunique"),
              customers=("CustomerID","nunique"))
         .assign(avg_order_value=lambda x: x["revenue"] / x["orders"])
         .sort_values("revenue", ascending=False)
         .reset_index()
)
country_kpi.head(10)

# Reconciliation
assert round(country_kpi["revenue"].sum(), 2) == round(clean["line_value"].sum(), 2)
```

Stop & Predict

- Which object(s) will change shape after this code?
- Could this operation silently remove or duplicate valid records? How will you detect that?
- What alternative Pandas method could solve part of this task, and why is the chosen one preferable here?

Checkpoint evidence

Evidence	Your result	Interpretation
Shape / row count	_____	_____
Missing / duplicate check	_____	_____
Key or total reconciliation	_____	_____

Practice ladder

Basic — Modify one filter/selection condition and return only the columns needed to answer a narrower business question.

Intermediate — Produce a second summary using at least two of: query(), isin(), between(), sort_values(), value_counts(), agg(), transform(), pivot_table(). Explain the grain.

Challenge — Design a validation test with assert or explicit before/after reconciliation that would catch a plausible silent error.

Debug — Create or identify one wrong approach (chained assignment, == NaN, and/or, unvalidated merge, blanket dropna, or iterrows) and repair it.

Case Study 5: Merge challenge

REAL-LIFE QUESTION Management gives you a customer master table. Can you enrich transactions without multiplying rows?

WHY THIS MATTERS A Pandas method is justified by the analytical question, the row grain, data quality, and the risk of changing meaning—not by habit.

25. **1. State the grain before coding:** Write one sentence defining what one row represents. Identify candidate keys and whether they should be unique.
26. **2. Inspect before transforming:** Run the inspection code. Record shape, dtypes, missingness, duplicates, ranges/categories, and suspicious values.
27. **3. Predict the effect:** Before running the transformation, predict whether row count, column count, null count, or grain should change.
28. **4. Execute the Pandas operation:** Run the code below one logical block at a time. Do not run the whole notebook blindly.

29. **5. Validate:** Compare before/after counts, key uniqueness, totals or category counts. A successful cell is not evidence that the result is correct.
30. **6. Interpret:** Write 2–4 sentences: what changed, why it was justified, what remains uncertain, and what you would tell the business user.

Guided implementation

```
customers = pd.read_csv("customers.csv", dtype={"CustomerID":"string"})
assert customers["CustomerID"].is_unique


before = len(clean)
enriched = clean.merge(
    customers,
    on="CustomerID",
    how="left",
    validate="many_to_one",
    indicator=True
)
assert len(enriched) == before
print(enriched["_merge"].value_counts(dropna=False))
unmatched = enriched.loc[enriched["_merge"]=="left_only", "CustomerID"].drop_duplicates()
```

Stop & Predict

- Which object(s) will change shape after this code?
- Could this operation silently remove or duplicate valid records? How will you detect that?
- What alternative Pandas method could solve part of this task, and why is the chosen one preferable here?

Checkpoint evidence

Evidence	Your result	Interpretation
Shape / row count	_____	_____
Missing / duplicate check	_____	_____
Key or total reconciliation	_____	_____

Practice ladder

Basic — Modify one filter/selection condition and return only the columns needed to answer a narrower business question.

Intermediate — Produce a second summary using at least two of: query(), isin(), between(), sort_values(), value_counts(), agg(), transform(), pivot_table(). Explain the grain.

Challenge — Design a validation test with assert or explicit before/after reconciliation that would catch a plausible silent error.

Debug — Create or identify one wrong approach (chained assignment, == NaN, and/or, unvalidated merge, blanket dropna, or iterrows) and repair it.

Final Integrated Case

Management gives you the raw source and asks for a decision-ready table. Build an end-to-end notebook without copying the guided solution blocks. Your notebook must contain:

- source/provenance note and acquisition code
- grain and key statement
- dataset-health table
- documented filtering population
- cleaning decision log
- at least two derived features where meaningful
- at least two grouped summaries

- one merge/concat/reconciliation task appropriate to this dataset
- three validation assertions/checks
- clean export with index=False where CSV/Excel is used
- 200–300 word management note stating findings, exclusions, assumptions and limitations

Common pitfalls — non-negotiable

Pitfall	Required response
and / or in Series filters	Use & / | with each condition in parentheses.
Chained assignment	Use .loc[...] = ...; do not use df[df['a']>5]['b']=0.
Comparing NaN with ==	Use .isna() / .notna().
Modifying a slice	Use .copy() when creating a working subset.
Ignoring dtypes	Run info() early; IDs often should not be numeric measures.
Blind dropna/fillna	First explain what missing means in that field and question.
iterrows on large data	Prefer vectorized expressions/groupby/merge.
Unvalidated merge	Check key uniqueness, use validate= and indicator=True, reconcile rows/totals.
Overwriting raw files	Keep raw immutable; write clean/derived files separately.
CSV index leakage	Use to_csv(..., index=False) unless the index is intentionally part of the data.

Oral defence prompts

31. What does one row represent?
32. Which columns are identifiers rather than measures?
33. Which missing values did you retain, drop or impute—and why?
34. Show one operation that changed row count. Prove the change was intended.
35. What was the cardinality of your merge? How did you verify it?
36. Which metric would be wrong if you counted rows instead of unique business entities?
37. What would you change if this dataset had 50 million rows?
38. Which part belongs in SQL/API/source filtering rather than Pandas?
39. What conclusion can you NOT make from this dataset?

END OF DATASET LAB • Preserve raw data • Explain every decision • Validate every join