

latex2plain

Convert LaTeX math notation in Markdown files to clean, readable plain Unicode text.

```
f(n) \le C \cdot g(n) \quad \text{for all } n \ge n_0
```

becomes:

```
f(n) ≤ C · g(n)    for all  n ≥ n0
```

Install

```
npm install -g latex2plain
```

Or run locally after cloning:

```
npm install
npm run build
npm install -g .
```

Usage

```
latex2plain [options] [input] [output]
latex2plain [options] <directory>
cat notes.md | latex2plain
```

Examples

```
# Overwrite file in place
latex2plain notes.md

# Write to a new (plain Markdown) file
latex2plain notes.md clean.md

# Generate an accessible HTML page from the converted output
latex2plain notes.md clean.html

# Generate a PDF from the converted output
latex2plain notes.md clean.pdf

# Preview without writing
latex2plain notes.md --dry-run

# Show what changed
latex2plain notes.md --diff

# Read from stdin, write to stdout
cat notes.md | latex2plain

# Convert all .md files in a directory (recursive)
latex2plain docs/
```

Options

Flag	Description
<code>-h, --help</code>	Show help
<code>-v, --version</code>	Show version
<code>-y, --yes</code>	Skip overwrite confirmation
<code>--dry-run</code>	Preview output without writing
<code>--diff</code>	Show before/after diff
<code>--stdin</code>	Force reading from stdin
<code>--verbose</code>	Print conversion stages
<code>--no-subscripts</code>	Skip subscript conversion
<code>--no-superscripts</code>	Skip superscript conversion
<code>--no-fractions</code>	Skip fraction conversion

<code>--no-roots</code>	Skip root conversion
<code>--no-mappings</code>	Skip symbol mapping
<code>--no-stripping</code>	Skip stripping wrapper commands (font, color, accents, boxes, etc.)
<code>--no-environments</code>	Skip environment stripping (<code>\begin{...}</code> / <code>\end{...}</code>)

HTML Output

You can generate an accessible, self-contained HTML page by specifying a `.html` output path:

```
latex2plain notes.md clean.html
```

The HTML page includes:

- **Full accessibility** — Semantic HTML5 landmarks, ARIA labels, skip-to-content link, keyboard-navigable focus styles
- **Responsive design** — Adapts to mobile, tablet, and desktop viewports
- **Dark mode** — Automatically respects system `prefers-color-scheme`
- **Print-friendly** — Clean layout when printed or saved as PDF via browser
- **Math font stack** — Unicode math symbols rendered with proper math fonts (STIX Two, Cambria Math, etc.)
- **Syntax highlighting** — Code blocks rendered with distinct backgrounds and borders
- **Self-contained** — No external CSS, JS, or web fonts; everything is inline

Notes

- The `.html` output is completely standalone — open it in any browser, email it, or upload it to a static site.
 - All conversion flags (`--no-superscripts` , `--no-fractions` , etc.) apply before HTML generation.
 - The generated page includes a metadata footer linking back to latex2plain.
-

PDF Generation

You can generate a PDF directly from a LaTeX-markdown file by specifying a `.pdf` output path:

```
latex2plain notes.md clean.pdf
```

This runs the full LaTeX-to-plain-text conversion pipeline, then generates a PDF using [md-to-pdf](#) which renders the converted markdown through headless Chrome (Puppeteer) for pixel-perfect output.

How it works

1. The input Markdown + LaTeX is converted to plain Unicode Markdown (same pipeline as `.md` output).
2. The converted Markdown is rendered to PDF with **custom CSS styling** that matches the HTML template's design:
 - Sans-serif system fonts for body text
 - Serif math font stack for Greek letters and operators (α , $\int$, $\rightarrow$, etc.)
 - Monospace font for code blocks with rounded, light-gray backgrounds
 - Purple accent color for blockquotes and links
3. The final PDF is written to the specified `.pdf` path — no temporary files are created.

Design

- **A4 page size** with comfortable margins (0.78in top/bottom, 0.9in left/right)
- **Automatic page breaks** — content flows across pages naturally
- **Code blocks** with rounded, light-gray backgrounds
- **Heading hierarchy** with appropriate sizing (22pt h1 $\rightarrow$ 11pt h6)

Notes

- The `--dry-run` and `--diff` flags work as expected with `.pdf` output (they display the converted text, not a PDF).
- All conversion flags (`--no-superscripts`, `--no-fractions`, etc.) apply to the intermediate markdown before PDF generation.

- PDF output is not supported when reading from stdin or processing directories — those flows produce plain Markdown as usual.

Conversion Pipeline

Stage	Input	Output
Code block protection	<code>@@CODEBLOCK-8@@</code>	placeholder (restored after)
Dollar stripping	<code>\$x^2\$</code> → <code>x^2</code> , <code>\$\$\n...\n\$\$</code> → <code>...</code>	content with delimiters removed
Display math stripping	<code>\[x^2\]</code>	<code>x^2</code>
Style command stripping	<code>\displaystyle</code> , <code>\textstyle</code> , <code>\scriptstyle</code> , <code>\scriptscriptstyle</code>	(removed)
<code>\pmod{}</code>	<code>\pmod{n}</code>	<code>(mod n)</code>
<code>\lim</code> formatting	<code>\lim_{x \to \infty}</code>	<code>lim (x → ∞)</code>
Symbol mappings	<code>\alpha</code> → <code>α</code> , <code>\infty</code> → <code>∞</code> , <code>\rightarrow</code> → <code>→</code>	Unicode symbols
<code>\text{}</code>	<code>\text{hello}</code>	<code>hello</code>
<code>\tag{}</code>	<code>\tag{1}</code>	<code>(1)</code>
Font commands	<code>\mathrm{xyz}</code> , <code>\mathbf{x}</code> , <code>\textit{x}</code> , <code>\textbf{x}</code> , <code>\mathcal{X}</code> , <code>\operatorname{foo}</code> , <code>\emph{...}</code> , <code>\boldsymbol{x}</code>	inner content only
Color commands	<code>\color{red}{x}</code> , <code>\textcolor{red}{x}</code>	inner content only
Cancel	<code>\cancel{x}</code> , <code>\cancelto{0}{x}</code>	<code>x</code> , <code>0</code>
Sout	<code>\sout{x}</code>	<code>x</code>
Underline / Overline	<code>\underline{x}</code> , <code>\overline{x}</code>	<code>x</code>
Over/Under braces	<code>\underbrace{x}</code> , <code>\overbrace{x}</code>	<code>x</code>
Boxes	<code>\boxed{x}</code> , <code>\fbox{x}</code>	<code>x</code>

Phantom	<code></code> , <code>\hphantom{x}</code> , <code>\vphantom{x}</code>	x
Accents	<code>\vec{x}</code> , <code>\hat{x}</code> , <code>\bar{x}</code> , <code>\tilde{x}</code> , <code>\dot{x}</code> , <code>\ddot{x}</code> , <code>\widehat{ABC}</code> , <code>\widetilde{ABC}</code>	inner content only
Extensible arrows	<code>\xrightarrow{text}</code> , <code>\xleftarrow{text}</code>	<code>text</code>
Invisible delimiters	<code>\left.</code> , <code>\right.</code>	<i>(removed)</i>
Environments	<code>\begin{align}...\end{align}</code> , <code>\begin{cases}...\end{cases}</code> , etc.	inner content with <code>\</code> → <code>;</code> and <code>&</code> → space
Matrix delimiters	<code>\begin{pmatrix}...\end{pmatrix}</code>	<code>(a b ; c d)</code> with <code>()</code> wrappers
Matrix delimiters	<code>\begin{bmatrix}...\end{bmatrix}</code>	<code>[a b ; c d]</code> with <code>[]</code> wrappers
Matrix delimiters	<code>\begin{vmatrix}...\end{vmatrix}</code>	<code>`</code>
Matrix delimiters	<code>\begin{Vmatrix}...\end{Vmatrix}</code>	<code> a b ; c d </code> with <code> </code> wrappers
<code>\hline</code> / <code>\hdashline</code>	<code>\hline</code>	<i>(removed)</i>
<code>\binom{}{}</code>	<code>\binom{n}{k}</code>	$C(n,k)$
<code>\over</code>	<code>{a \over b}</code>	(a/b)
<code>\choose</code>	<code>{n \choose k}</code>	$C(n,k)$
<code>\atop</code>	<code>{a \atop b}</code>	(a / b)
<code>\label{foo}</code>	<i>(removed)</i>	—
<code>\ref{foo}</code>	<code>foo</code>	—
<code>\eqref{foo}</code>	<code>(foo)</code>	—
<code>\notag</code>	<i>(removed)</i>	—
<code>\tag*{1}</code>	<code>(1)</code>	—
Subscripts	<code>n_0</code> , <code>x_{123}</code>	n_0 , x_{123}
Superscripts	<code>x^2</code> , <code>e^{-n}</code>	x^2 , e^{-n}
Fractions	<code>\frac{1}{2}</code> , <code>\frac{a+b}{c}</code>	$(1/2)$, $(a+b)/c$
Fractions (shorthand)	<code>\frac12</code> , <code>\frac1{2}</code> , <code>\frac{1}{2}</code>	$1/2$

Roots	<code>\sqrt{x}</code> , <code>\sqrt[3]{x}</code>	$\sqrt{x}$, $\sqrt[3]{x}$
Function parenthesization	<code>\sin x</code> , <code>\log n</code> , <code>\exp(i\theta)</code>	<code>\sin(x)</code> , <code>\log(n)</code> , <code>\exp(i\theta)</code>
Cleanup	extra spaces / blank lines	normalized
Code block restoration	placeholder	original <code>@@CODEBLOCK-9@@</code>

Recursive Conversion

Nested LaTeX is properly handled throughout the pipeline:

Input	Output
<code>\frac{\sqrt{x}}{y}</code>	<code>(\sqrt{x} / y)</code>
<code>\sqrt{\frac{a}{b}}</code>	<code>\sqrt{(a / b)}</code>
<code>\binom{\frac{1}{2}}{3}</code>	<code>C((1/2),3)</code>
<code>\pmod{\frac{a}{b}}</code>	<code>(\text{mod } a/b)</code>
<code>{ \frac{a}{b} \over c }</code>	<code>((a/b) / c)</code>

Stripping Reference

The stripping stage removes wrapper commands that add formatting but carry no semantic meaning in plain text.

Font Commands

LaTeX	Action
<code>\mathrm{...}</code>	Stripped (content preserved)
<code>\mathbf{...}</code>	Stripped
<code>\mathit{...}</code>	Stripped
<code>\mathsf{...}</code>	Stripped
<code>\mathtt{...}</code>	Stripped

<code>\mathnormal{...}</code>	Stripped
<code>\mathcal{...}</code>	Stripped
<code>\operatorname{...}</code>	Stripped
<code>\boldsymbol{...}</code>	Stripped
<code>\textbf{...}</code>	Stripped
<code>\textit{...}</code>	Stripped
<code>\textrm{...}</code>	Stripped
<code>\emph{...}</code>	Stripped

Accent Commands

LaTeX	Action	LaTeX	Action
<code>\vec{x}</code>	→ <code>x</code>	<code>\hat{x}</code>	→ <code>x</code>
<code>\bar{x}</code>	→ <code>x</code>	<code>\tilde{x}</code>	→ <code>x</code>
<code>\dot{x}</code>	→ <code>x</code>	<code>\ddot{x}</code>	→ <code>x</code>
<code>\check{x}</code>	→ <code>x</code>	<code>\breve{x}</code>	→ <code>x</code>
<code>\acute{x}</code>	→ <code>x</code>	<code>\grave{x}</code>	→ <code>x</code>
<code>\widehat{ABC}</code>	→ <code>ABC</code>	<code>\widetilde{ABC}</code>	→ <code>ABC</code>

Boxes & Decorations

LaTeX	Action
<code>\boxed{x}</code>	→ <code>x</code>
<code>\fbox{x}</code>	→ <code>x</code>
<code>\cancel{x}</code>	→ <code>x</code>
<code>\cancelto{0}{x}</code>	→ <code>0</code> (keeps to-value)
<code>\sout{x}</code>	→ <code>x</code>
<code>\underline{x}</code>	→ <code>x</code>
<code>\overline{x}</code>	→ <code>x</code>

<code>\underbrace{x}</code>	→ <code>x</code>
<code>\overbrace{x}</code>	→ <code>x</code>
<code></code>	→ <code>x</code>
<code>\hphantom{x}</code>	→ <code>x</code>
<code>\vphantom{x}</code>	→ <code>x</code>
<code>\xrightarrow{abc}</code>	→ <code>abc</code>
<code>\xleftarrow{abc}</code>	→ <code>abc</code>

Symbol Reference

Functions

These LaTeX function names are converted to plain text (backslash removed). After all other conversions, parenthesization is applied so `\sin x` becomes `\sin(x)` :

LaTeX	Output	LaTeX	Output
<code>\sin</code>	<code>sin</code>	<code>\arcsin</code>	<code>arcsin</code>
<code>\cos</code>	<code>cos</code>	<code>\arccos</code>	<code>arccos</code>
<code>\tan</code>	<code>tan</code>	<code>\arctan</code>	<code>arctan</code>
<code>\sinh</code>	<code>sinh</code>	<code>\csc</code>	<code>csc</code>
<code>\cosh</code>	<code>cosh</code>	<code>\sec</code>	<code>sec</code>
<code>\tanh</code>	<code>tanh</code>	<code>\cot</code>	<code>cot</code>
<code>\coth</code>	<code>coth</code>	<code>\sech</code>	<code>sech</code>
<code>\csch</code>	<code>csch</code>		
<code>\exp</code>	<code>exp</code>	<code>\log</code>	<code>log</code>
<code>\ln</code>	<code>ln</code>	<code>\lg</code>	<code>lg</code>
<code>\lim</code>	<code>lim</code>	<code>\limsup</code>	<code>lim sup</code>
<code>\liminf</code>	<code>lim inf</code>	<code>\Pr</code>	<code>Pr</code>
<code>\det</code>	<code>det</code>	<code>\dim</code>	<code>dim</code>

<code>\hom</code>	hom	<code>\ker</code>	ker
<code>\arg</code>	arg	<code>\deg</code>	deg
<code>\max</code>	max	<code>\min</code>	min
<code>\sup</code>	sup	<code>\inf</code>	inf
<code>\gcd</code>	gcd	<code>\lcm</code>	lcm
<code>\bmod</code>	mod		

`\lim`

Formatting

The `\lim` command (and `\limsup` , `\liminf`) with subscripts is converted to a parenthesized form:

LaTeX	Output
<code>\lim_{x \to \infty}</code>	<code>lim (x → ∞)</code>
<code>\lim_{n \to 0} \frac{1}{n}</code>	<code>lim (n → 0) (1/n)</code>
<code>\limsup_{k \to \infty}</code>	<code>lim sup (k → ∞)</code>
<code>\liminf_{n \to \infty}</code>	<code>lim inf (n → ∞)</code>

Greek Letters

LaTeX	Unicode		LaTeX	Unicode
<code>\alpha</code>	α		<code>\beta</code>	β
<code>\gamma</code>	γ		<code>\delta</code>	δ
<code>\epsilon</code>	ε		<code>\varepsilon</code>	ε
<code>\zeta</code>	ζ		<code>\eta</code>	η
<code>\theta</code>	θ		<code>\vartheta</code>	ϑ
<code>\iota</code>	ι		<code>\kappa</code>	κ
<code>\lambda</code>	λ		<code>\mu</code>	μ
<code>\nu</code>	ν		<code>\xi</code>	ξ
<code>\pi</code>	π		<code>\varpi</code>	ϖ
<code>\rho</code>	ρ		<code>\varrho</code>	ϱ

<code>\sigma</code>	σ		<code>\varsigma</code>	ς
<code>\tau</code>	τ		<code>\upsilon</code>	υ
<code>\phi</code>	ϕ		<code>\varphi</code>	ϕ
<code>\chi</code>	χ		<code>\psi</code>	ψ
<code>\omega</code>	ω			
<code>\Gamma</code>	Γ		<code>\Delta</code>	Δ
<code>\Theta</code>	Θ		<code>\Lambda</code>	Λ
<code>\Xi</code>	Ξ		<code>\Pi</code>	Π
<code>\Sigma</code>	Σ		<code>\Upsilon</code>	Υ
<code>\Phi</code>	Φ		<code>\Psi</code>	Ψ
<code>\Omega</code>	Ω			

Comparison

LaTeX	Unicode		LaTeX	Unicode
<code>\leq</code> <code>\le</code>	$\leq$		<code>\geq</code> <code>\ge</code>	$\geq$
<code>\neq</code> <code>\ne</code>	$\neq$		<code>\approx</code>	$\approx$
<code>\approxeq</code>	$\approx$		<code>\equiv</code>	$\equiv$
<code>\sim</code>	$\sim$		<code>\simeq</code>	$\simeq$
<code>\cong</code>	$\cong$		<code>\doteq</code>	$\doteq$
<code>\asymp</code>	$\asymp$		<code>\ll</code>	$\ll$
<code>\gg</code>	$\gg$		<code>\propto</code>	$\propto$
<code>\prec</code>	$\prec$		<code>\preceq</code>	$\preceq$
<code>\succ</code>	$\succ$		<code>\succeq</code>	$\succeq$
<code>\lesssim</code>	$\lesssim$		<code>\gtrsim</code>	$\gtrsim$
<code>\lessgtr</code>	$\lessgtr$		<code>\gtrless</code>	$\gtrless$

Arithmetic & Binary Operations

LaTeX	Unicode		LaTeX	Unicode
<code>\cdot</code>	·		<code>\times</code>	×
<code>\div</code>	÷		<code>\pm</code>	±
<code>\mp</code>	∓		<code>\ast</code>	*
<code>\star</code>	*		<code>\circ</code>	°
<code>\bullet</code>	·		<code>\diamond</code>	◊
<code>\wr</code>	ℳ		<code>\dagger</code>	†
<code>\ddagger</code>	‡		<code>\oplus</code>	⊕
<code>\ominus</code>	⊖		<code>\otimes</code>	⊗
<code>\oslash</code>	⊘		<code>\odot</code>	⊙
<code>\bigcirc</code>	◯		<code>\setminus</code>	\
<code>\amalg</code>	⨿			

Calculus & Analysis

LaTeX	Unicode		LaTeX	Unicode
<code>\infty</code>	∞		<code>\partial</code>	∂
<code>\nabla</code>	∇		<code>\int</code>	∫
<code>\iint</code>	∬		<code>\iiint</code>	∭
<code>\oint</code>	∮		<code>\sum</code>	Σ
<code>\prod</code>	∏		<code>\coprod</code>	⨿

Set Theory & Logic

LaTeX	Unicode		LaTeX	Unicode
<code>\in</code>	∈		<code>\notin</code>	∉
<code>\subset</code>	⊂		<code>\subseteq</code>	⊆
<code>\subseteqq</code>	⊆		<code>\subsetneq</code>	⊊

<code>\Subset</code>	$\Subset$		
<code>\supset</code>	$\supset$	<code>\supseteq</code>	$\supseteq$
<code>\supseteqq</code>	$\supseteqq$	<code>\supsetneq</code>	$\supsetneq$
<code>\Supset</code>	$\Supset$		
<code>\cup</code>	$\cup$	<code>\cap</code>	$\cap$
<code>\sqcup</code>	$\sqcup$	<code>\sqcap</code>	$\sqcap$
<code>\vee</code> <code>\lor</code>	$\vee$	<code>\wedge</code> <code>\land</code>	$\wedge$
<code>\emptyset</code> <code>\varnothing</code>	$\emptyset$	<code>\complement</code>	$\complement$
<code>\forall</code>	$\forall$	<code>\exists</code>	$\exists$
<code>\nexists</code>	$\nexists$	<code>\neg</code> <code>\lnot</code>	$\neg$
<code>\therefore</code>	$\therefore$	<code>\because</code>	$\because$
<code>\models</code>	$\models$	<code>\vdash</code>	$\vdash$
<code>\dashv</code>	$\dashv$	<code>\bowtie</code>	$\bowtie$
<code>\mid</code>	$\mid$	<code>\nmid</code>	$\nmid$

Arrows

LaTeX	Unicode	LaTeX	Unicode
<code>\to</code> <code>\rightarrow</code>	$\rightarrow$	<code>\leftarrow</code> <code>\gets</code>	$\leftarrow$
<code>\leftrightarrow</code>	$\leftrightarrow$	<code>\Rightarrow</code>	$\Rightarrow$
<code>\Leftarrow</code>	$\Leftarrow$	<code>\Leftrightarrow</code> <code>\iff</code>	$\Leftrightarrow$
<code>\implies</code>	$\Rightarrow$	<code>\impliedby</code>	$\Leftarrow$
<code>\mapsto</code>	$\mapsto$	<code>\longmapsto</code>	$\mapsto$
<code>\hookrightarrow</code>	$\hookrightarrow$	<code>\hookleftarrow</code>	$\hookleftarrow$
<code>\twoheadrightarrow</code>	$\twoheadrightarrow$	<code>\twoheadleftarrow</code>	$\twoheadleftarrow$
<code>\rightharpoonup</code>	$\rightharpoonup$	<code>\rightharpoondown</code>	$\rightharpoondown$
<code>\leftharpoonup</code>	$\leftharpoonup$	<code>\leftharpoondown</code>	$\leftharpoondown$
<code>\rightleftharpoons</code>	$\rightleftharpoons$	<code>\leftrightharpoons</code>	$\leftrightharpoons$
<code>\uparrow</code>	$\uparrow$	<code>\downarrow</code>	$\downarrow$

<code>\updownarrow</code>	$\updownarrow$		<code>\Uparrow</code>	$\Uparrow$
<code>\Downarrow</code>	$\Downarrow$		<code>\Updownarrow</code>	$\Updownarrow$
<code>\nearrow</code>	$\nearrow$		<code>\searrow</code>	$\searrow$
<code>\swarrow</code>	$\swarrow$		<code>\nwarrow</code>	$\nwarrow$
<code>\longrightarrow</code>	$\longrightarrow$		<code>\longleftarrow</code>	$\longleftarrow$
<code>\longleftrightarrow</code>	$\longleftrightarrow$		<code>\Longrightarrow</code>	$\Rightarrow$
<code>\Longleftarrow</code>	$\Longleftarrow$		<code>\Longleftarrow</code>	$\Leftrightarrow$

Misc Symbols

LaTeX	Unicode		LaTeX	Unicode
<code>\perp</code> <code>\bot</code>	$\perp$		<code>\top</code>	$\top$
<code>\parallel</code>	$\parallel$		<code>\angle</code>	$\angle$
<code>\measuredangle</code>	$\measuredangle$		<code>\sphericalangle</code>	$\sphericalangle$
<code>\triangle</code>	$\triangle$		<code>\triangledown</code>	∇
<code>\triangleleft</code>	$\triangleleft$		<code>\triangleright</code>	$\triangleright$
<code>\prime</code>	$'$		<code>\ell</code>	ℓ
<code>\hbar</code> <code>\hslash</code>	$\hbar$		<code>\imath</code>	$\imath$
<code>\jmath</code>	$\jmath$		<code>\wp</code>	$\wp$
<code>\aleph</code>	$\aleph$		<code>\beth</code>	$\beth$
<code>\gimel</code>	$\gimel$		<code>\daleth</code>	$\daleth$
<code>\Re</code>	$\Re$		<code>\Im</code>	$\Im$
<code>\Box</code>	$\Box$		<code>\Diamond</code>	$\Diamond$
<code>\clubsuit</code>	$\clubsuit$		<code>\diamondsuit</code>	$\diamondsuit$
<code>\heartsuit</code>	$\heartsuit$		<code>\spadesuit</code>	$\spadesuit$
<code>\S</code>	$\S$		<code>\P</code>	$\P$

Number Sets

LaTeX	Unicode		LaTeX	Unicode
<code>\mathbb{R}</code>	ℝ		<code>\mathbb{N}</code>	ℕ
<code>\mathbb{Z}</code>	ℤ		<code>\mathbb{Q}</code>	ℚ
<code>\mathbb{C}</code>	ℂ		<code>\mathbb{P}</code>	ℙ
<code>\mathbb{H}</code>	ℍ		<code>\mathbb{F}</code>	℔

Brackets & Delimiters

LaTeX	Replacement		LaTeX	Replacement
<code>\left(</code>	(		<code>\right)</code>	)
<code>\left[</code>	[		<code>\right]</code>	]
<code>\left </code>			<code>\right </code>	
<code>\lfloor</code>	⌊		<code>\rfloor</code>	⌋
<code>\lceil</code>	⌈		<code>\rceil</code>	⌉
<code>\langle</code>	⟨		<code>\rangle</code>	⟩

Dots

LaTeX	Unicode		LaTeX	Unicode
<code>\ldots</code>	...		<code>\cdots</code>	⋯
<code>\vdots</code>	⋮		<code>\ddots</code>	⋱

LaTeX Escape Sequences

LaTeX	Replacement		LaTeX	Replacement
<code>\#</code>	#		<code>\%</code>	%
<code>\{</code>	{		<code>\}</code>	}
<code>\\$</code>	\$		<code>_</code>	_

<code>\&</code>	<code>&</code>	<code>\textbackslash</code>	<code>\</code>
---------------------	--------------------	-----------------------------	----------------

Spacing Commands

LaTeX	Replacement
<code>\quad</code>	4 spaces
<code>\qquad</code>	8 spaces
<code>\,</code>	1 space
<code>\;</code>	1 space
<code>\!</code>	(removed)
<code>\</code> (backslash-space)	1 space

Supported Environments

When environment stripping is enabled (default), the following LaTeX math environments are converted to plain text:

Environment	Description	Behaviour
<code>align</code> , <code>align*</code> , <code>aligned</code>	Alignment	<code>\\</code> → <code>;</code> , <code>&</code> stripped
<code>equation</code> , <code>equation*</code>	Single equation	Content extracted
<code>gather</code> , <code>gather*</code> , <code>gathered</code>	Gathering	<code>\\</code> → <code>;</code>
<code>multline</code> , <code>multline*</code>	Multi-line	<code>\\</code> → <code>;</code>
<code>split</code>	Split	<code>\\</code> → <code>;</code> , <code>&</code> stripped
<code>matrix</code>	Plain matrix	<code>\\</code> → <code>;</code> , <code>&</code> stripped, no delimiters
<code>pmatrix</code>	Parenthesised matrix	<code>\\</code> → <code>;</code> , <code>&</code> stripped, wrapped in <code>()</code>
<code>bmatrix</code>	Bracket matrix	<code>\\</code> → <code>;</code> , <code>&</code> stripped, wrapped in <code>[]</code>
<code>vmatrix</code>	Single-bar matrix	<code>\\</code> → <code>;</code> , <code>&</code> stripped, wrapped in <code>`</code>
<code>Vmatrix</code>	Double-bar matrix	<code>\\</code> → <code>;</code> , <code>&</code> stripped, wrapped in <code> </code>
<code>smallmatrix</code>	Inline matrix	<code>\\</code> → <code>;</code> , <code>&</code> stripped, no delimiters

<code>cases</code> , <code>dcases</code> , <code>rcases</code>	Cases	<code>\\</code> → <code>;</code> , <code>&</code> stripped
<code>array</code> , <code>subarray</code>	Array	<code>\\</code> → <code>;</code> , <code>&</code> stripped
<code>eqnarray</code> , <code>eqnarray*</code>	Equation array	<code>\\</code> → <code>;</code> , <code>&</code> stripped
<code>flalign</code> , <code>flalign*</code>	Full-length align	<code>\\</code> → <code>;</code> , <code>&</code> stripped
<code>alignat</code> , <code>alignat*</code>	Align at specific points	<code>\\</code> → <code>;</code> , <code>&</code> stripped

Unknown environments pass through unchanged.

Development

```
npm install
npm run build      # compile TypeScript
npm test           # run vitest suite
npm run dev        # build + run
npm run lint       # check code with ESLint
npm run format     # auto-format with Prettier
npm run format:check # verify formatting
```

The project uses [ESLint](#) for code quality and [Prettier](#) for consistent formatting. Both run automatically in CI via [GitHub Actions](#).

License

MIT