

CNN

What is a CNN?

Most generally, we can think of a CNN as an [artificial neural network](#) that has some type of specialization for being able to pick out or detect patterns. This pattern detection is what makes CNNs so useful for image analysis.

If a CNN is just an artificial neural network, though, then what differentiates it from a standard multilayer perceptron or MLP?

Although image analysis has been the most wide spread use of CNNs, they can also be used for other data analysis or classification as well.

CNNs have hidden layers called *convolutional* layers, and these layers are what make a CNN, well... a CNN!

CNNs have layers called *convolutional* layers.

CNNs can, and usually do, have other, non-convolutional layers as well, but the basis of a CNN is the convolutional layers.

Alright, so what do these convolutional layers do?

Convolutional layers

Just like any other layer, a convolutional layer receives input, transforms the input in some way, and then outputs the transformed input to the next layer. The inputs to convolutional layers are called input channels, and the outputs are called [output channels](#).

With a convolutional layer, the transformation that occurs is called a *convolution operation*.

Filters and convolution operations

As mentioned earlier, convolutional neural networks are able to detect patterns in images.

With each convolutional layer, we need to specify the number of *filters* the layer should have.

These filters are actually what detect the patterns.

Patterns

Let's expand on precisely what we mean When we say that the filters are able to *detect patterns*. Think about how much may be going on in any single image. Multiple edges, shapes, textures, objects, etc. These are what we mean by *patterns*.

- edges
- shapes
- textures
- curves
- objects
- colors

One type of pattern that a filter can detect in an image is edges, so this filter would be called an ***edge detector***.

Aside from edges, some filters may detect corners. Some may detect circles. Others, squares. Now these simple, and kind of geometric, filters are what we'd see at the start of a convolutional neural network.


The deeper the network goes, the more sophisticated the filters become. In later layers, rather than edges and simple shapes, our filters may be able to detect specific objects like eyes, ears, hair or fur, feathers, scales, and beaks.

In even deeper layers, the filters are able to detect even more sophisticated objects like full dogs, cats, lizards, and birds.

To understand what's actually happening here with these convolutional layers and their respective filters, let's look at an example.

Filters (pattern detectors)

Suppose we have a convolutional neural network that is accepting images of handwritten digits (like from the MNIST data set) and our network is classifying them into their respective categories of whether the image is of a 1, 2, 3, etc.



Let's now assume that the first hidden layer in our model is a convolutional layer. As mentioned earlier, when adding a convolutional layer to a model, we also have to specify how many filters we want the layer to have.


The number of filters determine the number of output channels.

A filter can technically just be thought of as a relatively small matrix ([tensor](#)), for which, we decide the number of rows and columns this matrix has, and the values within this matrix are initialized with random numbers.

For this first convolutional layer of ours, we're going to specify that we want the layer to contain one filter of size 3 x 3.

Convolutional layer

Let's look at an example of the convolution operation:



This showcases the convolution process without numbers. We have an input channel in blue on the bottom. A convolutional filter shaded on the bottom that is sliding across the input channel, and a green output channel:

- Blue (bottom) - Input channel
- Shaded (on top of blue) - 3×3 convolutional filter
- Green (top) - Output channel

For each position on the blue input channel, the 3×3 filter does a computation that maps the shaded part of the blue input channel to the corresponding shaded part of the green output channel.

This convolutional layer receives an input channel, and the filter will slide over each 3×3 set of pixels of the input itself until it's slid over every 3×3 block of pixels from the entire image.





Input and output channels

Suppose that this grayscale image (single color channel) of a seven from the MNIST data set is our input:



Let's suppose that we have four 3×3 filters for our first convolutional layer, and these filters are filled with the values you see below. These values can be represented visually by having -1 s correspond to black, 1 s correspond to white, and 0 s correspond to grey.

Convolutional Layer with 4 filters

<table><tr><td>-1</td><td>-1</td><td>-1</td></tr><tr><td>1</td><td>1</td><td>1</td></tr><tr><td>0</td><td>0</td><td>0</td></tr></table>	-1	-1	-1	1	1	1	0	0	0	<table><tr><td>-1</td><td>1</td><td>0</td></tr><tr><td>-1</td><td>1</td><td>0</td></tr><tr><td>-1</td><td>1</td><td>0</td></tr></table>	-1	1	0	-1	1	0	-1	1	0	<table><tr><td>0</td><td>0</td><td>0</td></tr><tr><td>1</td><td>1</td><td>1</td></tr><tr><td>-1</td><td>-1</td><td>-1</td></tr></table>	0	0	0	1	1	1	-1	-1	-1	<table><tr><td>0</td><td>1</td><td>-1</td></tr><tr><td>0</td><td>1</td><td>-1</td></tr><tr><td>0</td><td>1</td><td>-1</td></tr></table>	0	1	-1	0	1	-1	0	1	-1
-1	-1	-1																																					
1	1	1																																					
0	0	0																																					
-1	1	0																																					
-1	1	0																																					
-1	1	0																																					
0	0	0																																					
1	1	1																																					
-1	-1	-1																																					
0	1	-1																																					
0	1	-1																																					
0	1	-1																																					
																																							


If we convolve our original image of a seven with each of these four filters individually, this is what the output would look like for each filter:

Output channels from the Convolutional Layer



We can see the shapes that the filters on the left detected from the images on the right. We can see circles, curves and corners.

As we go further into our layers, the filters are able to detect much more complex patterns like dog faces or bird legs shown here:



The amazing thing is that the pattern detectors are derived automatically by the network. The filter values start out with random values, and the values change as the network learns

during training. The pattern detecting capability of the filters emerges automatically.

Pattern detectors emerge as the network learns.

In the past, computer vision experts would develop filters (pattern detectors) manually. One example of this is the [Sobel filter](#), an edge detector. However, with deep learning, we can learn these filters automatically using neural networks!