Assignment 7

HTML & CSS — Borders, Layout, Effects, Selectors, Transformations, Typography, and Forms

---

Contents

1. Borders and Padding Demonstration Page
2. Height and Width Practice Layout
3. Gradient Background Webpage
4. Shadows and Depth Effect Layout
5. Advanced CSS Selectors Demonstration
6. CSS Transformations Showcase
7. Typography and Text Styling Page
8. Box Model Exploration Page
9. Outline and Focus Styling Form
10. Navigation Bar with Transitions and Hover Effects

Question 1

Borders and Padding Demonstration Page

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q1 - Borders and Padding Demonstration</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Borders &amp;amp; Padding Demonstration</h1>
  </header>

  <main>
    <!-- Each section groups a related set of boxes -->
    <section class="box-row">
      <div class="box solid">Solid Border</div>
      <div class="box dashed">Dashed Border</div>
      <div class="box double">Double Border</div>
      <div class="box groove">Groove Border</div>
    </section>

    <section class="box-row">
      <div class="box radius-small">Small Radius</div>
      <div class="box radius-medium">Medium Radius</div>
      <div class="box radius-pill">Pill Radius</div>
      <div class="box radius-circle">Circle</div>
    </section>

    <section class="box-row">
      <div class="box pad-small">Padding 5px</div>
      <div class="box pad-medium">Padding 20px</div>
      <div class="box pad-large">Padding 40px</div>
    </section>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 1</p>
  </footer>
</body>
</html>
```

style.css

```
/* ---------- Base page styling ---------- */
* {
  box-sizing: border-box;
}

body {
  font-family: "Segoe UI", Arial, sans-serif;
  background-color: #f4f6f8;
  color: #222;
  margin: 0;
  padding: 0;
}

header, footer {
```

```
  background-color: #2c3e50;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

main {
  padding: 2rem;
}

/* ---------- Flexbox row that holds the boxes ---------- */
.box-row {
  display: flex;
  flex-wrap: wrap;          /* allow boxes to wrap on small screens */
  justify-content: center;
  gap: 20px;
  margin-bottom: 2rem;
}

/* ---------- Base box style ---------- */
.box {
  width: 160px;
  height: 100px;
  display: flex;
  align-items: center;
  justify-content: center;
  text-align: center;
  background-color: #ffffff;
  border: 4px solid #3498db;
  transition: border-color 0.4s ease; /* smooth hover transition */
}

/* Hover effect changes border color smoothly */
.box:hover {
  border-color: #e74c3c;
}

/* ---------- Border style variations ---------- */
.solid   { border-style: solid; }
.dashed  { border-style: dashed; }
.double  { border-style: double; border-width: 8px; }
.groove  { border-style: groove; border-width: 8px; }

/* ---------- Border radius variations ---------- */
.radius-small  { border-radius: 6px; }
.radius-medium { border-radius: 20px; }
.radius-pill   { border-radius: 50px; }
.radius-circle { border-radius: 50%; width: 100px; height: 100px; }

/* ---------- Padding variations (padding affects inner spacing) ---------- */
.pad-small  { padding: 5px; }
.pad-medium { padding: 20px; }
.pad-large  { padding: 40px; }
```

Question 2

Height and Width Practice Layout

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q2 - Height and Width Practice Layout</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Height &amp;amp; Width Practice Layout</h1>
  </header>

  <main class="stage">
    <div class="box box-px">
      <p>px box<br>300px &times; 150px</p>
    </div>

    <div class="box box-percent">
      <p>% box<br>width: 50%</p>
    </div>

    <div class="box box-vh-em">
      <p>vh / em box<br>height: 30vh<br>max-width: 20em</p>
    </div>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 2</p>
  </footer>
</body>
</html>
```

style.css

```
* { box-sizing: border-box; }

body {
  font-family: Arial, sans-serif;
  margin: 0;
  color: #fff;
}

header, footer {
  background: #34495e;
  text-align: center;
  padding: 1rem;
}

/* Center all boxes vertically & horizontally using Flexbox */
.stage {
  min-height: 80vh;
  display: flex;
  align-items: center;
  justify-content: center;
  gap: 30px;
  flex-wrap: wrap;
  background: #ecf0f1;
```

```
  padding: 2rem;
}

.box {
  display: flex;
  align-items: center;
  justify-content: center;
  text-align: center;
  border-radius: 10px;
  padding: 10px;
}

/* Box 1: fixed pixel dimensions */
.box-px {
  width: 300px;
  height: 150px;
  background-color: #3498db;
}

/* Box 2: percentage width (relative to parent .stage) */
.box-percent {
  width: 50%;
  min-height: 120px;         /* min-height guarantees a floor size */
  max-width: 400px;          /* max-width caps growth on wide screens */
  background-color: #2ecc71;
}

/* Box 3: viewport height + em based max-width, with overflow demo */
.box-vh-em {
  height: 30vh;
  max-width: 20em;
  overflow: auto;            /* scrolls if content exceeds the box */
  background-color: #e67e22;
}
```

Question 3

Gradient Background Webpage

index.html

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q3 - Gradient Background Webpage</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Gradient Backgrounds</h1>
  </header>

  <main>
    <section class="linear-section">
      <h2>Linear Gradient</h2>
      <p>This section uses a linear gradient that flows diagonally
         across the background, and stays fixed while you scroll.</p>
    </section>

    <section class="radial-section">
      <h2>Radial Gradient</h2>
      <p>This section uses a radial gradient that radiates outward
         from the center of the box.</p>
    </section>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 3</p>
  </footer>
</body>
</html>
```

style.css

```css
* { box-sizing: border-box; margin: 0; }

body {
  font-family: Arial, sans-serif;
  color: #fff;
}

/* Fixed header and footer */
header, footer {
  position: sticky;
  background: #1c1c1c;
  text-align: center;
  padding: 1rem;
  z-index: 2;
}
header { top: 0; }
footer { bottom: 0; }

section {
  min-height: 60vh;
  display: flex;
  flex-direction: column;
  align-items: center;
```

```
  justify-content: center;
  text-align: center;
  padding: 2rem;
}

/* Linear gradient section with a parallax-like fixed background */
.linear-section {
  background-image: linear-gradient(135deg, #ff512f, #dd2476);
  background-attachment: fixed;   /* creates the parallax effect on scroll */
}

/* Radial gradient section */
.radial-section {
  background-image: radial-gradient(circle at center, #43cea2, #185a9d);
}

h2 {
  font-size: 2rem;
  margin-bottom: 1rem;
  text-shadow: 2px 2px 4px rgba(0,0,0,0.4);
}

p {
  max-width: 500px;
  line-height: 1.6;
}
```

Question 4

Shadows and Depth Effect Layout

index.html

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q4 - Shadows and Depth Effect Layout</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Shadows &amp;amp; Depth Effects</h1>
  </header>

  <main class="card-row">
    <article class="card card-soft">
      <h2>Soft Shadow</h2>
      <p>A subtle, close shadow gives a gentle lift off the page.</p>
    </article>

    <article class="card card-strong">
      <h2>Strong Shadow</h2>
      <p>A larger offset and blur creates a bolder floating effect.</p>
    </article>

    <article class="card card-colored">
      <h2>Colored Shadow</h2>
      <p>A tinted shadow can match a card's accent color.</p>
    </article>
  </main>

  <footer>
    <p>Assignment 7 &amp;mdash; Question 4</p>
  </footer>
</body>
</html>
```

style.css

```css
* { box-sizing: border-box; }

body {
  font-family: Arial, sans-serif;
  background: #f2f2f2;
  margin: 0;
}

header, footer {
  background: #222;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

/* Arrange cards in a single row with Flexbox */
.card-row {
  display: flex;
  justify-content: center;
  gap: 2rem;
```

```
  flex-wrap: wrap;
  padding: 3rem 1rem;
}

.card {
  background: #fff;
  border-radius: 12px;
  padding: 1.5rem;
  width: 220px;
  text-align: center;
  transition: transform 0.3s ease, box-shadow 0.3s ease; /* smooth lift */
}

.card h2 {
  text-shadow: 1px 1px 3px rgba(0,0,0,0.3); /* text-shadow for depth */
}

/* Different box-shadow styles */
.card-soft {
  box-shadow: 0 2px 6px rgba(0,0,0,0.15);
}

.card-strong {
  box-shadow: 0 10px 20px rgba(0,0,0,0.3);
}

.card-colored {
  box-shadow: 0 8px 18px rgba(155, 89, 182, 0.5);
}

/* On hover, lift the card with a larger shadow */
.card:hover {
  transform: translateY(-10px);
  box-shadow: 0 20px 35px rgba(0,0,0,0.35);
}
```

Question 5

Advanced CSS Selectors Demonstration

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q5 - Advanced CSS Selectors</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Advanced CSS Selectors Demo</h1>
  </header>

  <main>
    <section class="selector-demo">
      <h2>Attribute Selectors</h2>
      <form>
        <input type="text" placeholder="Styled via [type='text']">
        <br>
        <a href="https://example.com">Secure link (styled via [href^='https'])</a>
      </form>
    </section>

    <section class="selector-demo">
      <h2>Pseudo-classes &amp; Pseudo-elements</h2>
      <ul class="item-list">
        <li>Item one</li>
        <li>Item two</li>
        <li>Item three</li>
        <li>Item four</li>
      </ul>
      <p class="quote">Hover or focus the items above to see the effects.</p>
    </section>

    <section class="selector-demo">
      <h2>Combinators</h2>
      <div class="parent">
        <p>Direct child paragraph (&gt;)</p>
        <span>Adjacent sibling span (+)</span>
        <span>General sibling span (~)</span>
        <div class="nested">
          <p>Descendant paragraph (space)</p>
        </div>
      </div>
    </section>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 5</p>
  </footer>
</body>
</html>
```

style.css

```
* { box-sizing: border-box; }

body {
```

```
  font-family: Arial, sans-serif;
  margin: 0;
  background: #fafafa;
}

header, footer {
  background: #16324f;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

.selector-demo {
  max-width: 700px;
  margin: 2rem auto;
  padding: 1.5rem;
  background: #fff;
  border-radius: 8px;
  box-shadow: 0 2px 8px rgba(0,0,0,0.1);
}

/* ---------- Attribute selectors ---------- */
input[type="text"] {                /* selects only text inputs */
  padding: 8px;
  border: 2px solid #16324f;
  border-radius: 6px;
}

a[href^="https"] {                  /* selects links starting with https */
  color: #27ae60;
  font-weight: bold;
}

/* ---------- Pseudo-classes ---------- */
.item-list li {
  list-style: none;
  padding: 10px;
  margin-bottom: 6px;
  background: #ecf0f1;
  border-radius: 4px;
  cursor: pointer;
}

.item-list li:hover {               /* mouse hover state */
  background: #16324f;
  color: #fff;
}

.item-list li:nth-child(odd) {      /* zebra-stripe odd items */
  border-left: 4px solid #e67e22;
}

input[type="text"]:focus {          /* focus state on the input */
  outline: none;
  border-color: #e67e22;
}

/* ---------- Pseudo-elements ---------- */
.quote::before {
  content: "\201C";                 /* opening quote mark */
  font-size: 1.4rem;
  margin-right: 4px;
}
```

```
.quote::after {
  content: "\201D";                  /* closing quote mark */
  font-size: 1.4rem;
  margin-left: 4px;
}

/* ---------- Combinators ---------- */
.parent > p {                        /* direct child only */
  color: #2980b9;
  font-weight: bold;
}

.parent p + span {                   /* span immediately after a p */
  color: #c0392b;
}

.parent p ~ span {                   /* every span after the p */
  display: block;
  color: #8e44ad;
}

.parent .nested p {                  /* descendant selector (any depth) */
  color: #16a085;
  font-style: italic;
}
```

Question 6

CSS Transformations Showcase

index.html

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q6 - CSS Transformations Showcase</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>CSS Transformations Showcase</h1>
  </header>

  <main class="transform-row">
    <div class="item">
      <div class="box rotate-box">Rotate</div>
      <p>rotate(45deg) on hover</p>
    </div>

    <div class="item">
      <div class="box scale-box">Scale</div>
      <p>scale(1.3) on hover</p>
    </div>

    <div class="item">
      <div class="box translate-box">Translate</div>
      <p>translate(0, -20px) on hover</p>
    </div>

    <div class="item">
      <div class="box skew-box">Skew</div>
      <p>skew(15deg, 5deg) on hover</p>
    </div>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 6</p>
  </footer>
</body>
</html>
```

style.css

```css
* { box-sizing: border-box; }

body {
  font-family: Arial, sans-serif;
  margin: 0;
  background: #fdfdfd;
}

header, footer {
  background: #333;
  color: #fff;
  text-align: center;
  padding: 1rem;
}
```

```css
/* Arrange boxes horizontally using Flexbox */
.transform-row {
  display: flex;
  justify-content: center;
  gap: 3rem;
  flex-wrap: wrap;
  padding: 4rem 1rem;
}

.item {
  text-align: center;
}

.box {
  width: 120px;
  height: 120px;
  background: #3498db;
  color: #fff;
  display: flex;
  align-items: center;
  justify-content: center;
  border-radius: 8px;
  transition: transform 0.4s ease;  /* smooth transformation on hover */
}

.rotate-box:hover    { transform: rotate(45deg); }
.scale-box:hover     { transform: scale(1.3); }
.translate-box:hover { transform: translate(0, -20px); }
.skew-box:hover       { transform: skew(15deg, 5deg); }

.item p {
  margin-top: 0.8rem;
  font-size: 0.9rem;
  color: #555;
}
```

Question 7

Typography and Text Styling Page

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q7 - Typography and Text Styling</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Typography &amp; Text Styling</h1>
  </header>

  <main>
    <article class="serif-heading">
      <h2>A Short Article on Typography</h2>
      <p class="lead">
        Good typography is invisible &mdash; it lets the reader focus on
        the words rather than the letters that form them. This short
        article demonstrates several text styling techniques used
        every day on the web, including <mark>highlighted text</mark>,
        <strong>bold emphasis</strong>, and <em>italic emphasis</em>.
      </p>

      <p class="sans-body">
        Line height, letter spacing, and text alignment all shape how
        comfortable a paragraph is to read. This paragraph uses a
        generous line height and slightly increased letter spacing so
        the text breathes on the page instead of feeling cramped.
        Notice how the very first letter is enlarged, and the first
        line is styled differently from the rest of the paragraph.
      </p>

      <p class="mono-body">
        This final paragraph uses a monospaced font at a smaller size,
        contrasting with the serif heading and sans-serif body text
        above it, to show how font family and weight can change the
        feel of a passage.
      </p>
    </article>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 7</p>
  </footer>
</body>
</html>
```

style.css

```
* { box-sizing: border-box; }

body {
  margin: 0;
  background: #fffef9;
  color: #2b2b2b;
}
```

```css
header, footer {
  background: #4b3832;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

article {
  max-width: 700px;
  margin: 2rem auto;
  padding: 0 1.5rem;
}

h2 {
  font-family: Georgia, "Times New Roman", serif;
  font-weight: 700;
  font-size: 2rem;
}

/* Lead paragraph: serif, larger, relaxed line-height */
.lead {
  font-family: Georgia, serif;
  font-size: 1.15rem;
  line-height: 1.8;
  letter-spacing: 0.3px;
  text-align: left;
}

/* Body paragraph: sans-serif with first-letter/first-line emphasis */
.sans-body {
  font-family: "Segoe UI", Arial, sans-serif;
  font-weight: 400;
  font-size: 1rem;
  line-height: 1.9;
  letter-spacing: 0.5px;
  text-align: justify;
}

.sans-body::first-letter {
  font-size: 2.4rem;
  font-weight: bold;
  color: #b5651d;
  float: left;
  margin-right: 6px;
  line-height: 1;
}

.sans-body::first-line {
  font-weight: 600;
  text-transform: uppercase;
  font-size: 0.95rem;
  letter-spacing: 1px;
}

/* Monospace paragraph for contrast */
.mono-body {
  font-family: "Courier New", monospace;
  font-size: 0.9rem;
  line-height: 1.6;
  color: #555;
}

/* Custom colors for inline emphasis elements */
mark {
```

```
  background-color: #ffe08a;
  color: #4b3832;
  padding: 0 3px;
}

strong {
  color: #b5651d;
}

em {
  color: #6a5acd;
}
```

Question 8

Box Model Exploration Page

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q8 - Box Model Exploration</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Box Model Exploration</h1>
  </header>

  <main class="stage">
    <div class="model-wrapper">
      <h2>Default (content-box)</h2>
      <div class="margin-layer">
        <span class="label">margin</span>
        <div class="border-layer">
          <span class="label">border</span>
          <div class="padding-layer">
            <span class="label">padding</span>
            <div class="content-layer">content</div>
          </div>
        </div>
      </div>
    </div>

    <div class="model-wrapper">
      <h2>box-sizing: border-box</h2>
      <div class="margin-layer">
        <span class="label">margin</span>
        <div class="border-layer border-box-demo">
          <span class="label">border</span>
          <div class="padding-layer">
            <span class="label">padding</span>
            <div class="content-layer">content</div>
          </div>
        </div>
      </div>
    </div>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 8</p>
  </footer>
</body>
</html>
```

style.css

```
body {
  margin: 0;
  font-family: Arial, sans-serif;
  background: #f7f7f7;
}

header, footer {
```

```
  background: #23272a;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

/* Center the demonstration using Flexbox */
.stage {
  display: flex;
  justify-content: center;
  gap: 3rem;
  flex-wrap: wrap;
  padding: 3rem 1rem;
}

.model-wrapper {
  text-align: center;
}

.label {
  display: block;
  font-size: 0.7rem;
  font-weight: bold;
  color: #333;
  margin-bottom: 4px;
}

/* Margin layer: outermost, shown with an outline (outlines don't affect layout) */
.margin-layer {
  outline: 2px dashed #e67e22;
  background-color: #fdf1e3;
  padding: 20px; /* visually represents the margin area */
}

/* Border layer */
.border-layer {
  border: 10px solid #3498db;
  background-color: #eaf4fc;
  width: 220px;
  height: 160px; /* default box-sizing: content-box, so width excludes border/padding */
}

/* Same box but using border-box so width INCLUDES border + padding */
.border-box-demo {
  box-sizing: border-box;
  background-color: #e8f8f0;
  border-color: #27ae60;
}

/* Padding layer */
.padding-layer {
  background-color: #fcefee;
  padding: 20px;
  height: 100%;
}

/* Content layer */
.content-layer {
  background-color: #e74c3c;
  color: #fff;
  display: flex;
  align-items: center;
  justify-content: center;
  height: 100%;
```

```
  border-radius: 4px;
}

p.description {
  max-width: 220px;
  font-size: 0.85rem;
  color: #555;
}
```

Question 9

Outline and Focus Styling Form

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q9 - Outline and Focus Styling Form</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <h1>Outline &amp;amp; Focus Styling Form</h1>
  </header>

  <main>
    <form class="contact-form">
      <label for="name">Name</label>
      <input type="text" id="name" class="field field-solid" placeholder="Solid outline on focus"
>

      <label for="email">Email</label>
      <input type="email" id="email" class="field field-dashed" placeholder="Dashed outline on fo
cus">

      <label for="message">Message</label>
      <textarea id="message" class="field field-dotted" rows="4" placeholder="Dotted outline on f
ocus"></textarea>

      <button type="submit">Submit</button>
    </form>
  </main>

  <footer>
    <p>Assignment 7 &amp;mdash; Question 9</p>
  </footer>
</body>
</html>
```

style.css

```
* { box-sizing: border-box; }

body {
  margin: 0;
  font-family: Arial, sans-serif;
  background: #eef2f5;
}

header, footer {
  background: #34495e;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

main {
  display: flex;
  justify-content: center;
  padding: 3rem 1rem;
```

```css
}

.contact-form {
  background: #fff;
  padding: 2rem;
  border-radius: 10px;
  box-shadow: 0 4px 15px rgba(0,0,0,0.1);
  width: 100%;
  max-width: 400px;
  display: flex;
  flex-direction: column;
  gap: 12px; /* uniform spacing between form elements */
}

label {
  font-weight: 600;
  font-size: 0.9rem;
  color: #34495e;
}

.field {
  padding: 10px 12px;
  border: 1px solid #ccc;
  border-radius: 6px;
  font-size: 1rem;
  outline: 3px solid transparent;   /* reserved space so layout doesn't jump */
  outline-offset: 2px;
  transition: outline-color 0.3s ease;
}

/* Different outline styles per field, applied on focus */
.field-solid:focus {
  outline-style: solid;
  outline-color: #3498db;
  outline-offset: 3px;
}

.field-dashed:focus {
  outline-style: dashed;
  outline-color: #e67e22;
  outline-offset: 5px;
}

.field-dotted:focus {
  outline-style: dotted;
  outline-color: #27ae60;
  outline-offset: 4px;
}

button {
  margin-top: 8px;
  padding: 10px;
  border: none;
  border-radius: 6px;
  background: #34495e;
  color: #fff;
  font-size: 1rem;
  cursor: pointer;
  transition: background 0.3s ease;
}

button:hover {
  background: #2c3e50;
}
```

Question 10

Navigation Bar with Transitions and Hover Effects

index.html

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Q10 - Navigation Bar with Transitions</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <header>
    <nav class="navbar">
      <a href="#" class="nav-link active">Home</a>
      <a href="#" class="nav-link">About</a>
      <a href="#" class="nav-link">Services</a>
      <a href="#" class="nav-link">Portfolio</a>
      <a href="#" class="nav-link">Contact</a>
    </nav>
  </header>

  <main>
    <p>Resize the window below 700px to see the navbar stack vertically.</p>
  </main>

  <footer>
    <p>Assignment 7 &mdash; Question 10</p>
  </footer>
</body>
</html>
```

style.css

```css
* { box-sizing: border-box; }

body {
  margin: 0;
  font-family: Arial, sans-serif;
}

/* Horizontal navbar using Flexbox */
.navbar {
  display: flex;
  background: #1a1a2e;
  padding: 0.5rem 1rem;
}

.nav-link {
  color: #fff;
  text-decoration: none;
  padding: 12px 20px;
  border: 1px solid transparent;
  border-radius: 4px;
  transition: all 0.3s ease;   /* smooth hover transition */
}

.nav-link:hover {
  background-color: #16213e;
  border-color: #0f3460;
}
```

```css
/* Highlight the active link */
.nav-link.active {
  background-color: #0f3460;
  border-bottom: 3px solid #e94560;
}

main {
  padding: 3rem 1.5rem;
  text-align: center;
  color: #333;
}

footer {
  background: #1a1a2e;
  color: #fff;
  text-align: center;
  padding: 1rem;
}

/* Responsive: stack navbar vertically below 700px */
@media (max-width: 700px) {
  .navbar {
    flex-direction: column;
  }

  .nav-link {
    text-align: center;
    border-radius: 0;
  }
}
```