

# Class\_10

Mudit

What is in the PDB database anyway? I grabbed summary data from: <https://www.rcsb.org/stats/summary>

```
pdbstats <- read.csv("Data Export Summary.csv", row.names = 1)
pdbstats
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	167,317	15,698	12,534	208	77	32
Protein/Oligosaccharide	9,645	2,639	34	8	2	0
Protein/NA	8,735	4,718	286	7	0	0
Nucleic acid (only)	2,869	138	1,507	14	3	1
Other	170	10	33	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	195,866					
Protein/Oligosaccharide	12,328					
Protein/NA	13,746					
Nucleic acid (only)	4,532					
Other	213					
Oligosaccharide (only)	22					

```
convert_comma_numbers <- function(x){
  x <- as.numeric(gsub(",", "", x))

  return(x)
}
```

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
(195866/24883887) * 100
```

```
[1] 0.07871197
```

```
n.tot <- sum(convert_comma_numbers(pdbstats$Total))  
n.tot
```

```
[1] 226707
```

```
24883887
```

The `apply` function is very useful as it can take any function and “apply” it over either the ROWS or COLs of a `data.frame`.

```
library(readr)  
Data_Export_Summary <- read_csv("Data Export Summary.csv")
```

```
Rows: 6 Columns: 8
```

```
-- Column specification -----
```

```
Delimiter: ","
```

```
chr (1): Molecular Type
```

```
dbl (3): Multiple methods, Neutron, Other
```

```
num (4): X-ray, EM, NMR, Total
```

```
i Use `spec()` to retrieve the full column specification for this data.  
i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
#View(Data_Export_Summary)
```

```
n.xray <- sum(convert_comma_numbers(pdbstats$X.ray))  
n.em <- sum(convert_comma_numbers(pdbstats$EM))
```

```
n.xray/n.tot *100
```

```
[1] 83.25592
```

```
n.em/n.tot *100
```


```
[1] 10.2348
```

Q2: What proportion of structures in the PDB are protein?

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

226707

Q4: Water molecules normally have 3 atoms. Why do we see just one atom per water molecule in this structure? ## Using Mol\*

In PDB structures, water molecules are often represented by a single oxygen atom, as the hydrogen positions can be challenging to resolve in many structural determination methods. !

Q5: There is a critical “conserved” water molecule in the binding site. Can you identify this water molecule? What residue number does this water molecule have

Water Molecular 308

Q6: Generate and save a figure clearly showing the two distinct chains of HIV-protease along with the ligand. You might also consider showing the catalytic residues ASP 25 in each chain and the critical water (we recommend “Ball & Stick” for these side-chains). Add this figure to your Quarto document.



```
library(bio3d)  
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```

```
Call: read.pdb(file = "1hsg")
```

```
Total Models#: 1
```

```
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```
Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 172 (residues: 128)
```

```
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

```
Protein sequence:
```

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
attributes(pdb)
```

```
$names
```

```
[1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"
```

```
$class
```

```
[1] "pdb" "sse"
```

```
head(pdb$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40

	segid	elesy	charge
1	<NA>	N	<NA>
2	<NA>	C	<NA>
3	<NA>	C	<NA>

```

4  <NA>      O   <NA>
5  <NA>      C   <NA>
6  <NA>      C   <NA>

```

Q7: How many amino acid residues are there in this pdb object?

residues/Calpha atoms#: 198

Q8: Name one of the two non-protein residues?

HOH (which represents water molecules; there are 127 of them) and MK1 (which is a non-protein ligand; there is 1 of them).

Q9: How many protein chains are in this structure?

Chains#: 2 (values: A B).

```
length(pdbseq(pdb))
```

```
[1] 198
```

## Functional dynamics prediction

Predicting functional motions of a single structure

```
adk <- read.pdb("6s36")
```

Note: Accessing on-line PDB file

PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
```

```
Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)
```

```
Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 244 (residues: 244)
```

Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]

Protein sequence:


MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV  
DELVIALVKERIAQEDCRNGFLLDGFPRTIPQADAMKEAGINVDYVLEFDVPDELIVDKI  
VGRRVHAPSGRVYHVKFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG  
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG

+ attr: atom, xyz, seqres, helix, sheet,  
calpha, remark, call

```
# Perform flexibility prediction  
m <- nma(adk)
```

Building Hessian... Done in 0.047 seconds.  
Diagonalizing Hessian... Done in 0.407 seconds.

```
plot(m)
```



```
mktrj(m, file="adk_m7.pdb")
```

## Comparative structure analysis of Adenylate Kinase

Q10. Which of the packages above is found only on BioConductor and not CRAN?

msa The package that is found only on Bioconductor and not on CRAN is msa. It is specifically a Bioconductor package designed for multiple sequence alignment.

Q11. Which of the above packages is not found on BioConductor or CRAN?:

bio3d-view The package that is not found on either Bioconductor or CRAN is bio3d-view. This package is installed from a Bitbucket repository using the devtools package, which allows installation from sources other than CRAN and Bioconductor.

Q12. True or False? Functions from the devtools package can be used to install packages from GitHub and BitBucket?

True. The devtools package provides functions that allow you to install packages from GitHub and Bitbucket, making it useful for accessing packages that are not available through the standard CRAN repository.

```
library(bio3d)
aa <- get.seq("1ake_A")
```

Warning in get.seq("1ake\_A"): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

```
aa
```

	1	.	.	.	.	.	60
pdb 1AKE A	MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMLRAAVKSGSELGKQAKDIMDAGKLV						
	1	.	.	.	.	.	60
	61	.	.	.	.	.	120
pdb 1AKE A	DELVIALVKERIAQEDCRNGFLLDGFRTIPQADAMKEAGINVDYVLEFDVPDELIVDRI						
	61	.	.	.	.	.	120
	121	.	.	.	.	.	180
pdb 1AKE A	VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTRKDDQEETVRKRLVEYHQMTAPLIG						
	121	.	.	.	.	.	180
	181	.	.	.	.	.	214
pdb 1AKE A	YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG						



181 . . . 214

Call:

```
read.fasta(file = outfile)
```

Class:

```
fasta
```

Alignment dimensions:

```
1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

```
+ attr: id, ali, call
```

Q13. How many amino acids are in this sequence, i.e. how long is this sequence?

214

```
hits <- NULL
hits$ pdb.id <- c('1AKE_A', '6S36_A', '6RZE_A', '3HPR_A', '1E4V_A', '5EJE_A', '1E4Y_A', '3X2S_A', '6H
```

```
# Download related PDB files
files <- get.pdb(hits$ pdb.id, path="pdb", split=TRUE, gzip=TRUE)
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):
pdb/1AKE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):
pdb/6S36.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):
pdb/6RZE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):
pdb/3HPR.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):
pdb/1E4V.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$ pdb.id, path = "pdb", split = TRUE, gzip = TRUE):
pdb/5EJE.pdb.gz exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/1E4Y.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/3X2S.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6HAP.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6HAM.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/3GMT.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4PZL.pdb.gz exists. Skipping download



```

|
|=====| 69%
|
|=====| 77%
|
|=====| 85%
|
|=====| 92%
|
|=====| 100%

```

```
# Align related PDBs
pdbbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```

pdbbs/split_chain/1AKE_A.pdb
pdbbs/split_chain/6S36_A.pdb
pdbbs/split_chain/6RZE_A.pdb
pdbbs/split_chain/3HPR_A.pdb
pdbbs/split_chain/1E4V_A.pdb
pdbbs/split_chain/5EJE_A.pdb
pdbbs/split_chain/1E4Y_A.pdb
pdbbs/split_chain/3X2S_A.pdb
pdbbs/split_chain/6HAP_A.pdb
pdbbs/split_chain/6HAM_A.pdb
pdbbs/split_chain/4K46_A.pdb
pdbbs/split_chain/3GMT_A.pdb
pdbbs/split_chain/4PZL_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...

```

Extracting sequences

```

pdb/seq: 1   name: pdbbs/split_chain/1AKE_A.pdb
  PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbbs/split_chain/6S36_A.pdb

```

```

PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/6RZE_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4   name: pdbs/split_chain/3HPR_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 6   name: pdbs/split_chain/5EJE_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 8   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 9   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 10  name: pdbs/split_chain/6HAM_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdbs/split_chain/4K46_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdbs/split_chain/4PZL_A.pdb

```

```

# Vector containing PDB codes for figure axis
ids <- basename.pdb(pdb$id)

```

```

# Draw schematic alignment
#plot(pdb, labels = ids)
#figure margins too large

```

```

anno <- pdb.annotate(ids)
unique(anno$source)

```

```

[1] "Escherichia coli"
[2] "Escherichia coli K-12"
[3] "Escherichia coli O139:H28 str. E24377A"
[4] "Escherichia coli str. K-12 substr. MDS42"
[5] "Photobacterium profundum"
[6] "Burkholderia pseudomallei 1710b"
[7] "Francisella tularensis subsp. tularensis SCHU S4"

```

```

anno

```

	structureId	chainId	macromoleculeType	chainLength	experimentalTechnique
1AKE_A	1AKE	A	Protein	214	X-ray
6S36_A	6S36	A	Protein	214	X-ray

6RZE_A	6RZE	A	Protein	214	X-ray
3HPR_A	3HPR	A	Protein	214	X-ray
1E4V_A	1E4V	A	Protein	214	X-ray
5EJE_A	5EJE	A	Protein	214	X-ray
1E4Y_A	1E4Y	A	Protein	214	X-ray
3X2S_A	3X2S	A	Protein	214	X-ray
6HAP_A	6HAP	A	Protein	214	X-ray
6HAM_A	6HAM	A	Protein	214	X-ray
4K46_A	4K46	A	Protein	214	X-ray
3GMT_A	3GMT	A	Protein	230	X-ray
4PZL_A	4PZL	A	Protein	242	X-ray

	resolution	scopDomain	pfam
1AKE_A	2.00	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)
6S36_A	1.60	<NA>	Adenylate kinase, active site lid (ADK_lid)
6RZE_A	1.69	<NA>	Adenylate kinase (ADK)
3HPR_A	2.00	<NA>	Adenylate kinase, active site lid (ADK_lid)
1E4V_A	1.85	Adenylate kinase	Adenylate kinase (ADK)
5EJE_A	1.90	<NA>	Adenylate kinase, active site lid (ADK_lid)
1E4Y_A	1.85	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)
3X2S_A	2.80	<NA>	Adenylate kinase (ADK)
6HAP_A	2.70	<NA>	Adenylate kinase (ADK)
6HAM_A	2.55	<NA>	Adenylate kinase, active site lid (ADK_lid)
4K46_A	2.01	<NA>	Adenylate kinase, active site lid (ADK_lid)
3GMT_A	2.10	<NA>	Adenylate kinase, active site lid (ADK_lid)
4PZL_A	2.10	<NA>	Adenylate kinase (ADK)

	ligandId
1AKE_A	AP5
6S36_A	CL (3),NA,MG (2)
6RZE_A	NA (3),CL (2)
3HPR_A	AP5
1E4V_A	AP5
5EJE_A	AP5,CO
1E4Y_A	AP5
3X2S_A	JPY (2),AP5,MG
6HAP_A	AP5
6HAM_A	AP5
4K46_A	ADP,AMP,PO4
3GMT_A	SO4 (2)
4PZL_A	CA,FMT,GOL

	ligandName
1AKE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6S36_A	CHLORIDE ION (3),SODIUM ION,MAGNESIUM ION (2)
6RZE_A	SODIUM ION (3),CHLORIDE ION (2)

3HPR_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
1E4V_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
5EJE_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE, COBALT (II) ION
1E4Y_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
3X2S_A	N-(pyren-1-ylmethyl)acetamide (2), BIS(ADENOSINE)-5'-PENTAPHOSPHATE, MAGNESIUM ION
6HAP_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6HAM_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE
4K46_A	ADENOSINE-5'-DIPHOSPHATE, ADENOSINE MONOPHOSPHATE, PHOSPHATE ION
3GMT_A	SULFATE ION (2)
4PZL_A	CALCIUM ION, FORMIC ACID, GLYCEROL

#### source

1AKE_A	Escherichia coli
6S36_A	Escherichia coli
6RZE_A	Escherichia coli
3HPR_A	Escherichia coli K-12
1E4V_A	Escherichia coli
5EJE_A	Escherichia coli 0139:H28 str. E24377A
1E4Y_A	Escherichia coli
3X2S_A	Escherichia coli str. K-12 substr. MDS42
6HAP_A	Escherichia coli 0139:H28 str. E24377A
6HAM_A	Escherichia coli K-12
4K46_A	Photobacterium profundum
3GMT_A	Burkholderia pseudomallei 1710b
4PZL_A	Francisella tularensis subsp. tularensis SCHU S4

1AKE\_A STRUCTURE OF THE COMPLEX BETWEEN ADENYLATE KINASE FROM ESCHERICHIA COLI AND THE INHIBIT

6S36\_A  
6RZE\_A  
3HPR\_A  
1E4V\_A  
5EJE\_A  
1E4Y\_A  
3X2S\_A  
6HAP\_A  
6HAM\_A  
4K46\_A  
3GMT\_A  
4PZL\_A

Cryst

The crys


	citation	rObserved	rFree
1AKE_A	Muller, C.W., et al. J Mol Biol (1992)	0.19600	NA
6S36_A	Rogne, P., et al. Biochemistry (2019)	0.16320	0.23560
6RZE_A	Rogne, P., et al. Biochemistry (2019)	0.18650	0.23500
3HPR_A	Schrank, T.P., et al. Proc Natl Acad Sci U S A (2009)	0.21000	0.24320

1E4V_A	Muller, C.W., et al. Proteins (1993)	0.19600	NA
5EJE_A	Kovermann, M., et al. Proc Natl Acad Sci U S A (2017)	0.18890	0.23580
1E4Y_A	Muller, C.W., et al. Proteins (1993)	0.17800	NA
3X2S_A	Fujii, A., et al. Bioconjug Chem (2015)	0.20700	0.25600
6HAP_A	Kantaev, R., et al. J Phys Chem B (2018)	0.22630	0.27760
6HAM_A	Kantaev, R., et al. J Phys Chem B (2018)	0.20511	0.24325
4K46_A	Cho, Y.-J., et al. To be published	0.17000	0.22290
3GMT_A	Buchko, G.W., et al. Biochem Biophys Res Commun (2010)	0.23800	0.29500
4PZL_A	Tan, K., et al. To be published	0.19360	0.23680


rWork spaceGroup

1AKE_A	0.19600	P	21	2	21
6S36_A	0.15940	C	1	2	1
6RZE_A	0.18190	C	1	2	1
3HPR_A	0.20620	P	21	21	2
1E4V_A	0.19600	P	21	2	21
5EJE_A	0.18630	P	21	2	21
1E4Y_A	0.17800	P	1	21	1
3X2S_A	0.20700	P	21	21	21
6HAP_A	0.22370	I	2	2	2
6HAM_A	0.20311	P	43		
4K46_A	0.16730	P	21	21	21
3GMT_A	0.23500	P	1	21	1
4PZL_A	0.19130	P	32		


```
# Perform PCA
pc.xray <- pca(pdbx)
plot(pc.xray)
```




PC1 (84.99%)



PC1 (84.99%)



PC3 (1.87%)




Eigenvalue Rank

## PCA

```
# Perform PCA
pc.xray <- pca(pdbx)
plot(pc.xray)
```






```
# Calculate RMSD
rd <- rmsd(pdb)
```

Warning in rmsd(pdb): No indices provided, using the 204 non NA positions

```
# Structure-based clustering
hc.rd <- hclust(dist(rd))
grps.rd <- cutree(hc.rd, k=3)

plot(pc.xray, 1:2, col="grey50", bg=grps.rd, pch=21, cex=1)
```




### Optional further visualization

```
# Visualize first principal component
pc1 <- mktrj(pc.xray, pc=1, file="pc_1.pdb")
```

```
#Plotting results with ggplot2
library(ggplot2)
library(ggrepel)

df <- data.frame(PC1=pc.xray$z[,1],
                 PC2=pc.xray$z[,2],
                 col=as.factor(grps.rd),
                 ids=ids)

p <- ggplot(df) +
  aes(PC1, PC2, col=col, label=ids) +
  geom_point(size=2) +
  geom_text_repel(max.overlaps = 20) +
  theme(legend.position = "none")
p
```



```
# NMA of all structures
modes <- nma(pdb)
```

#### Details of Scheduled Calculation:


```
... 13 input structures
... storing 606 eigenvectors for each structure
... dimension of x$U.subspace: ( 612x606x13 )
... coordinate superposition prior to NM calculation
... aligned eigenvectors (gap containing positions removed)
... estimated memory usage of final 'eNMA' object: 36.9 Mb
```

		0%
=====		8%
=====		15%
=====		23%



```
plot(modes, pdb, col=grps.rd)
```

Extracting SSE from pdb\$sse attribute



Q14. What do you note about this plot? Are the black and colored lines similar or different? Where do you think they differ most and why?

They differ The plot shows the fluctuations of different amino acid residues across multiple protein structures.

The black line represents the average fluctuation for each residue. The colored lines depicts the fluctuations for individual structures.

Difference between coloured and black line is most prominent around residues 120 and 150

Didn't added the below code as render gave error 'processing file: class-10.rmarkdown |..... | 90% [update.packages(ask=FALSE)] Error in startup(port = port, ...): Chrome debugging port not open after 10 seconds. Calls: .main ... withRestartList -> withOneRestart -> docall -> do.call -> fun

Quitting from lines 263-268 [update.packages(ask=FALSE)] (class-10.rmarkdown) Execution halted' from code'

```
options(r3dmol.chrome.port.timeout = 900) # Extend timeout
options(r3dmol.chrome.port = 9222) # Set a specific port
source("https://tinyurl.com/viewpdb")
```


```
library(r3dmol)
# view.pdb giving error while rendering as it says time ran out for rendering
#view.pdb(pdb)
```

```
#view.pdb(adk)
```

```
modes <- nma(adk)
```

```
Building Hessian...      Done in 0.04 seconds.
Diagonalizing Hessian... Done in 0.399 seconds.
```

```
plot(modes)
```



```
mktrj(modes, pdb = adk, file = "adk.pdb")
```