

Mudrak Patel (300878960)

## CNET 124 Lab 2

1)

```
S3#clock set ?
  hh:mm:ss Current Time

S3#clock set
% Incomplete command.

S3#clock set
% Incomplete command.

S3#clock set ?
  hh:mm:ss Current Time

S3#clock set 7:10:00
% Incomplete command.

S3#clock set 7:10:00 ?
  <1-31> Day of the month
  MONTH Month of the year

S3#clock set 7:10:00 jan 19 ?
  <1993-2035> Year

S3#clock set 7:10:00
% Incomplete command.

S3#clock set 7:10:00 Jan 19 2017
S3#clock set 7:10:00 Jan 19 2017
1d08h: %SYS-6-CLOCKUPDATE: System clock has been updated from 08:42:28 UTC Tue Mar 2 1993 to 07:10:00 UTC Thu Jan 19 2017, configclock set 19:14:00 Jan 19 2017
S3#
1d08h: %SYS-6-CLOCKUPDATE: System clock has been updated from 07:10:53 UTC Thu Jan 19 2017 to 19:14:00 UTC Thu Jan 19 2017, configured from console by console.
S3#
S3#
S3#
S3#
S3#
S3#show clock
19:14:10.460 UTC Thu Jan 19 2017
S3#
```

2)

```
Administrator: C:\Windows\system32\cmd.exe

Ping statistics for 192.168.1.11:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

C:\Users\300878960>ping 192.168.1.1

Pinging 192.168.1.1 with 32 bytes of data:
Reply from 192.168.1.10: Destination host unreachable.
Reply from 192.168.1.10: Destination host unreachable.
Reply from 192.168.1.10: Destination host unreachable.
Reply from 192.168.1.10: Destination host unreachable.

Ping statistics for 192.168.1.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

C:\Users\300878960>
C:\Users\300878960>ping 192.168.1.1

Pinging 192.168.1.1 with 32 bytes of data:
Reply from 192.168.1.10: Destination host unreachable.
Reply from 192.168.1.10: Destination host unreachable.
Reply from 192.168.1.10: Destination host unreachable.
Reply from 192.168.1.10: Destination host unreachable.

Ping statistics for 192.168.1.1:
```

3)

```
COM1 - PuTTY

SE SOFTWARE (fc1)
Copyright (c) 1986-2007 by Cisco Systems, Inc.
Compiled Thu 19-Jul-07 20:06 by nachen
Image text-base: 0x00003000, data-base: 0x00D40000

ROM: Bootstrap program is C2960 boot loader
BOOTLDR: C2960 Boot Loader (C2960-HBOOT-M) Version 12.2(25r)SEE6, RELEASE SOFTWARE (fc1)

S3 uptime is 1 day, 8 hours, 34 minutes
System returned to ROM by power-on
System image file is "flash:c2960-lanbase-mz.122-35.SE5.bin"

cisco WS-C2960-24TT-L (PowerPC405) processor (revision E0) with 61440K/4088K bytes of memory.
Processor board ID FOC1228Y3P1
Last reset from power-on
1 Virtual Ethernet interface
24 FastEthernet interfaces
2 Gigabit Ethernet interfaces
The password-recovery mechanism is enabled.

64K bytes of flash-simulated non-volatile configuration memory.
Base ethernet MAC Address      : 00:22:91:38:D4:00

S3>show clock
*08:35:46.287 UTC Tue Mar 2 1993
S3>
```

4)

```
COM1 - PuTTY
S3>
S3>
S3>
S3>show version
Cisco IOS Software, C2960 Software (C2960-LANBASE-M), Version 12.2(35)SE5, RELEA
SE SOFTWARE (fc1)
Copyright (c) 1986-2007 by Cisco Systems, Inc.
Compiled Thu 19-Jul-07 20:06 by nachen
Image text-base: 0x00003000, data-base: 0x00D40000

ROM: Bootstrap program is C2960 boot loader
BOOTLDR: C2960 Boot Loader (C2960-HBOOT-M) Version 12.2(25r)SEE6, RELEASE SOFTWA
RE (fc1)

S3 uptime is 1 day, 8 hours, 34 minutes
System returned to ROM by power-on
System image file is "flash:c2960-lanbase-mz.122-35.SE5.bin"

cisco WS-C2960-24TT-L (PowerPC405) processor (revision E0) with 61440K/4088K byt
es of memory.
Processor board ID FOC1228Y3P1
Last reset from power-on
1 Virtual Ethernet interface
24 FastEthernet interfaces
2 Gigabit Ethernet interfaces
The password-recovery mechanism is enabled.

--More-- █
```