

**Question # 1**  
**CLO1**

**[40 points (4 each), 70 mins]**

Considering the following programs and illustrate the required process in graphical form. Assume all necessary header files are included and all programs are syntactically correct.

**Illustrate a memory allocation for both type of dynamic memory allocation.**

```
void main()
{
double *ptr1,*ptr2;
ptr1=(double*)malloc(5 * sizeof(double));
ptr2=(double*)calloc(5 , sizeof(double));}
```

Show dummy addresses and garbage values to highlight the difference.


**Note: GB stands for Grabbage Value**

Variable	ptr1+0	ptr1+1	ptr1+2	ptr1+3	ptr1+4
Address	1000	1008	1016	1024	1032
Value	GB	GB	GB	GB	GB
Variable	ptr2+0	ptr2+1	ptr2+2	ptr2+3	ptr2+4
Address	2000	2008	2016	2024	2032
Value	0	0	0	0	0

**b. Draw the recursive stack of the following function, if we call sum(3) with n = 3.**

```
int sum( int n)
{
    if (n==0)
        return 10;
    else
        return n + sum(n-1);
}
```

**returns 16**



**c. Draw the recursive stack of the following function, if we call fibonacci(3) with n = 3.**

```
int fibonacci(int n)
{
    if (n==0)
        return 0;
    else if (n==1)
        return 1;
    else
        return fibonacci(n-2) + fibonacci(n-1);}
```

Solution:  
Returns 2  
Mentioned Below

**d. Illustrate a memory allocation for the following structure object student1.**

```
struct day{
    int date;char month[10];int
year;};
struct student{
    int id1, id2;
    char a; float p;
    struct day birthday;
}student1;
```

**Assume starting address as 1020**

**id1: 1020**  
**id2: 1024**

**SOLUTION**

<pre> graph TD     3((3)) --&gt; 2((2))     3((3)) --&gt; 1r((1))     2((2)) --&gt; 1l((1))     2((2)) --&gt; 0((0))     style 3 fill:#fff,stroke:#000     style 2 fill:#fff,stroke:#000     style 1l fill:#008000,stroke:#000     style 1r fill:#008000,stroke:#000     style 0 fill:#008000,stroke:#000 </pre>	<p> a: 1028  p:1032  date:1036  month:1040  year:1052 </p>
PF FINAL EXAM SOLUTION	

B. Considering the output, write down the missing part of the program. You must write only the missing part on the answer sheet with the most appropriate code. **CLO2**

```

.
#include <stdio.h>
typedef struct{
    int id; float price; char name[20];
}userTyped;
void main() {
    userTyped inst1[]={20, 5000.05,"Samsung"},
                      {30, 3300.25, "Apple"},
                      {40, 6020.05, "Acer"};

    userTyped *ptr = inst1;
    //Using variable
    for(____; ____; ____){
        _____
    }
    printf("-----\n");
    //Using pointer
    for(____; ____; ____){
        { _____
    }
}

```

**Solution:**

```

#include <stdio.h>
typedef struct{
    int id; float price; char name[20];
}userTyped;
void main() {
    userTyped inst1[]={20, 5000.05,"Samsung"},
                      {30, 3300.25, "Apple"},
                      {40, 6020.05, "Acer"};

```

Output:  
40, 6020.0, Acer  
30, 3300.2, Apple  
20, 5000.0, Samsung  
-----  
20, 5000.0, Samsung  
30, 3300.2, Apple  
40, 6020.0, Acer

<pre> userTyped *ptr = inst1; //Using variable int i; for(i = 2; i &gt;= 0; i--)     printf("%d %f %s\n", inst1[i].id, inst1[i].price, inst1[i].name); printf("-----\n"); //Using pointer for(i = 0; i &lt;= 2; i++) {     printf("%d %f %s\n", (ptr+i)-&gt;id, (ptr+i)-&gt;price, (ptr+i)-&gt;name); } </pre>	
<p>b.</p> <pre> void main(){ char country[] = "Pakistan"; void *ptr; ptr = country; while( _____ ) {     _____ } } </pre> <p><b>Solution:</b>  #include&lt;stdio.h&gt;</p> <pre> int main(){ char country[] = "Pakistan"; void *ptr; ptr = country; while( *((char*) (ptr)) != '\0') {     printf("%c", *((char*) (ptr)));     ptr++; } } </pre>	<p>Output: Pakistan</p>
<p>c.</p> <pre> void main(){ char ch, *str; int cnt=0; puts("enter any string: "); while((ch=getche()) != 13){     if(cnt==0){         str = (char *) malloc (sizeof(char));         str[cnt]=ch;}     else{         _____         _____     }     _____ }     str[cnt]='\0';     printf("\n%s",str); } //Hint: You need to extend the dynamic array in this problem <b>Solution:</b> #include&lt;stdio.h&gt; #include&lt;stdlib.h&gt; int main(){ char ch, *str; </pre>	<p>Output: It will produce <b>“Pakistan Zindabad”</b> if input is <b>“Pakistan Zindabad”</b></p>

<pre> int cnt=0; puts("enter any string: "); while((ch=getche()) != 13){     if(cnt==0){         str = (char *) malloc (sizeof(char));         str[cnt]=ch;}     else{         str = (char*) realloc(str, (cnt+2)*sizeof(char));         str[cnt] = ch;          }         cnt++;     }     str[cnt]='\0';     printf("\n%s",str); } </pre>	
<p>d. Initialize and display the record structure:</p> <pre> struct employee{     int eid;  char ename[20]; }; struct date{     int joiningYear;}; struct record{     struct employee emp;      struct date dt; }; void main(){     struct record rcd[2]={         { _____,         _____     };     _____     _____ } }  Solution: #include&lt;stdio.h&gt; #include&lt;stdlib.h&gt;  struct employee{     int eid;  char ename[20]; }; struct date{     int joiningYear;}; struct record{     struct employee emp;      struct date dt; }; void main(){     struct record rcd[2]={         {{101,"Asad"}, 2010},         {{102,"Bilal"}, 2014}};      int i;     for(i = 0; i &lt;2; i++){         printf("Employee ID: %d \nName: %s \nJoining Year: %d\n\n", rcd[i].emp.eid, rcd[i].emp.ename, rcd[i].dt.joiningYear);     } } </pre>	<p>Output: Employee ID:101 Name: Asad Joining Year: 2010</p> <p>Employee ID: 102 Name: Bilal Joining Year: 2014</p> <p>PF FINAL EXAM SOLUTION</p>
<p>e.</p> <pre> void main() { </pre>	<p>Output: P PR</p>

<pre> int arrAll[]={80, 82, 79, 71, 82, 65, 77}; for(____; ____; ____){     for(____; ____; ____){         _____         _____     } }  Solution:  #include&lt;stdio.h&gt; #include&lt;stdlib.h&gt;  int main() {     int i,j;     int arrAll[]={80, 82, 79, 71, 82, 65, 77};     for(i = 0; i &lt; 7; i++)     {         for(j = 0; j &lt;= i; j++)             printf("%c", arrAll[j]);          puts("");     } </pre>	<div>PRO</div> <div>PROG</div> <div>PROGR</div> <div>PROGRA</div> <div>PROGRAM</div> <div>PF FINAL EXAM SOLUTION</div>
<p>f.</p> <pre> void main(void){     char *p[3] = {"Rashid", "Sajid", "Ali",};     char * tmp; int i, j;     for( i = 0; i&lt;3; i++)         for( ____; ____; ____){             { _____               _____             }         }     _____     _____ } </pre> <p>Solution:</p> <pre> int main(void){     char *p[3] = {"Rashid", "Sajid", "Ali",};     char tmp[20]; int i, j;     for(i=0; i&lt;3; i++){         for(j=0; j&lt;3-1-i; j++){             if(strcmp(p[j], p[j+1]) &gt; 0){                 //swap array[j] and array[j+1]                 strcpy(tmp, p[j]);                 strcpy(p[j], p[j+1]);                 strcpy(p[j+1], tmp);             }         }     }      for( i = 0; i&lt;3; i++)         puts(p[i]); } </pre>	<div>Output:</div> <div>Ali</div> <div>Rashid</div> <div>Sajid</div>

}	
---	--

### QUESTION:2 SOLUTION:

```
#include<stdio.h>
int lighten(int image[3][3], int row, int col){
    int rowCtr, colCtr;
    for (rowCtr = 0; rowCtr < row; rowCtr++){
        for(colCtr = 0; colCtr < col; colCtr++){
            image[rowCtr][colCtr] *= 1.10;
            if(!(image[rowCtr][colCtr] >= 0 &&
image[rowCtr][colCtr] <= 255))
                return 1;
        }
    }
    return 0;
}

void display(int image[3][3], int row, int col){
    puts("\nDisplaying the matrix after lightening");
    int rowCtr, colCtr;
    for (rowCtr = 0; rowCtr < row; rowCtr++){
        for(colCtr = 0; colCtr < col; colCtr++){
            printf("%d ", image[rowCtr][colCtr]);
        }
        puts("");
    }
}

int main(){
    int row, col, rowCtr, colCtr;
    puts("Enter the number of rows and cols");
    scanf("%d %d", &row, &col);
    int image[row][col];
    for (rowCtr = 0; rowCtr < row; rowCtr++){
        for(colCtr = 0; colCtr < col; colCtr++){
            do{
                printf("Enter the row %d and col %d : \n",
rowCtr, colCtr);
                scanf("%d", &image[rowCtr][colCtr]);
            }
            while(!(image[rowCtr][colCtr] >= 0 &&
image[rowCtr][colCtr] <= 255));
        }
    }
    if(lighten(image, row, col))
        puts("Image is burnt out");
    else
        display(image, row, col);
}
```

**QUESTION:3 SOLUTION:**

```
#include <stdio.h>
```

```
#include <String.h>
```

```
struct CustomerInfo{  
    char CustomerName[50];  
    char AddressName[50];  
};
```

```
struct Car {  
    int Price;  
    int Model;  
    char Brand[50];  
    char ManufacturingDate[50];  
    char CountryOfOrigin[50];  
    struct CustomerInfo CI;  
};
```

PF FINAL EXAM SOLUTION

```
void printline() {  
    printf("\t-----\n");  
}
```

```
long ServicesTax(int Price) {  
    return (Price * 75) / 100;  
}
```

```
long RetailProfit(int Price) {  
    return (Price * 75) / 100;  
}
```

```
long importDutyTax(int Price) {  
    return (Price * 15) / 100;  
}
```

```
long SalesTax(int Price) {  
    return 10 * Price / 100;  
}
```

```
long CalulatePrice(int Price) {  
    long temp = SalesTax(Price) + ServicesTax(Price) + RetailProfit(Price) +  
importDutyTax(Price);  
    temp += Price;  
    return temp;  
}
```

```
void PrintAllDetails(struct Car c) {
```

```

        printline();
        printf("\t\tBILLING DETAILS \n");
        printline();
        printf("\tImport Duty Cost: \tRs %ld \n",importDutyTax(c.Price));
        printf("\tSales Tax Cost: \tRs %ld \n",SalesTax(c.Price));
        printf("\tRetail Price: \t\tRs %ld \n",RetailProfit(c.Price));
        printline();
        printf("\tFinal Price: \t\tRs %ld \n",CalulatePrice(c.Price));
        printf("\t*****THANKYOU FOR SHOPPING. *****\n\n\n");
    }

```

```

void printBill(int model){
    struct Car c;
    FILE *fptr = fopen("bill.txt","r");
    if(fptr == NULL){
        printf("Could not open file!");
    }
    else{
        while(fread(&c, sizeof(struct Car), 1, fptr)){

            if(c.Model == model){

                printf("\t\tEnter CUSTOMER INFORMATION \n");
                printline();

                printf("\t\tCustomer Name: %s\n",
c.Cl.CustomerName);

                printf("\t\tCustomer Address: %s\n",
c.Cl.AddressName);

                printf("\t\tCard Brand: %s\n", c.Brand);
                printf("\t\tCard Model: %d\n", c.Model);
                printf("\t\tCar price: %d\n", c.Price);
                printf("\t\tCountry of Origin: %s\n",
c.CountryOfOrigin);

                printf("\t\tCar Manufacturing Date:
%s\n",c.ManufacturingDate);

                PrintAllDetails(c);

            }

        }
        fclose(fptr);
    }
}

```

PF FINAL EXAM SOLUTION



```

void SaveBillInfo(){
    struct Car c;
    puts("\t\tEnter Customer Name!");
    printf("\t\t");
    fflush(stdin);
    scanf("%s", c.Cl.AddressName);
    puts("\t\tEnter Customer address!");
    printf("\t\t");
    scanf("%s", c.Cl.AddressName);
    puts("\t\tEnter the price of Car!");
    printf("\t\t");
    scanf("%d", &c.Price);
    puts("\t\tEnter the Model of Car!");
    printf("\t\t");
    scanf("%d", &c.Model);
    puts("\t\tEnter the brand of car");
    printf("\t\t");
    fflush(stdin);
    scanf("%s", c.Brand);
    puts("\t\tEnter Manufacturing date of the car");
    printf("\t\t");
    scanf("%s", c.ManufacturingDate);
    puts("\t\tEnter country of origin of the car!");
    printf("\t\t");
    scanf("%s", c.CountryOfOrigin);

```

PF FINAL EXAM SOLUTION

```

    FILE *fptr = fopen("bill.txt", "a");
    if(fptr == NULL){
        printf("Could not open file!");
    }
    else{
        fwrite(&c, sizeof(struct Car), 1, fptr);
        fclose(fptr);
    }
}

void GetBillInfo(){
    struct Car c;
    FILE *fptr = fopen("bill.txt", "r");
    if(fptr == NULL){
        printf("Could not open file!");
    }
    else{
        while(fread(&c, sizeof(struct Car), 1, fptr)){

            printf("\t\tCustomer Name: %s\n", c.Cl.CustomerName);
            printf("\t\tCustomer Address: %s\n", c.Cl.AddressName);
            printf("\t\tCard Brand: %s\n", c.Brand);

```

```

        printf("\t\tCard Model: %d\n", c.Model);
        printf("\t\tCar price: %d\n", c.Price);
        printf("\t\tCountry of Origin: %s\n", c.CountryOfOrigin);
        printf("\t\tCar Manufacturing Date:
%s\n",c.ManufacturingDate);
    }
    fclose(fptr);
}

}

```

```

int main(){
    int choice =0;
    outFile = fopen("Car.dat", "w+");
    do{
        printf("\n\n\tENTER CHOICE\n\t1.Save to Bill Details\n\t2.Get Bill
Details\n\t3.Print All with taxes of perticular car\n");
        printf("\tMake a choice: ");
        fflush(stdin);
        scanf("%d",&choice);

        //printf("\n\n\n Checking %d \n\n\n",choice);
        system("CLS");

        if(choice==1){
            //system("CLS");
            SaveBillInfo();
        } else if(choice==2){
            GetBillInfo();
        } else if (choice==3){
            int model;
            puts("\t\tEnter the Model No. for car");
            printf("\t\t");
            scanf("%d", &model);
            printBill(model);
        }
    }while(choice!=0);
    return 0;
}

```

#### QUESTION:4SOLUTION:

```

#include<stdio.h>
#include<stdlib.h>
struct group{

```

```

        int groupID;
        char groupName[20];
        int tasks[5];
    };
    int sum(int * arr){
        int i; int sum = 0;
        for(i = 0; i < 5; i++){
            sum += arr[i];
        }
        return sum;
    }
    void displayWinner(){
        struct group gp;
        int groupCtr = 1;
        FILE *fp = fopen("CompRecord1.txt", "r");
        if(fp == NULL){
            puts("File Did not open!");
            return;
        }
        else{
            // reading the records
            while(fread(&gp, sizeof(struct group), 1, fp)){
                if(sum(gp.tasks) >= 3){
                    printf("\n\nWinner Group Details %d are\n\n", groupCtr);
                    printf("Group ID : %d\nGroup Name : %s\n", gp.groupID,
gp.groupName);
                    puts("");
                    groupCtr++;
                }
            }
            fclose(fp);
        }
    }
    void search(){
        int ID, counter, isFound = 0;
        FILE *fp = fopen("CompRecord1.txt", "r");
        if(fp == NULL){
            puts("File Did not open!");
            return;
        }
        puts("Enter the Group ID you want to search!");
        scanf("%d", &ID);
        else{
            struct group gp;
            // reading the records
            while(fread(&gp, sizeof(struct group), 1, fp)){
                if(gp.groupID == ID){
                    puts("\n\nGroup Details are\n\n");
                }
            }
        }
    }
}

```

```

        printf("Group ID : %d\nGroup Name : %s\n", gp.groupID,
gp.groupName);

        puts("Task status is ");
        for(counter = 0; counter < 5; counter++){
            printf("Task %d : %d \n",counter+1, gp.tasks[counter]);
        }
        isFound = 1;
    }
}
if(isFound == 0)
    puts("ID not Found");
fclose(fp);
}
}

void input(){
    struct group gp;
    int ctr;
    puts("Enter Group ID");
    scanf("%d", &gp.groupID);
    fflush(stdin);
    puts("Enter Group Name");
    scanf("%s", gp.groupName);
    puts("Enter the results of tasks 1 for pass o for fail");
    for(ctr = 0; ctr < 5; ctr++){
        printf("Enter value of Task %d :", ctr+1 );
        scanf("%d", &gp.tasks[ctr]);
        if(gp.tasks[ctr] != 1 && gp.tasks[ctr] != 0){
            puts("Re-Enter the value either 0 or 1");
            ctr--;
        }
    }
    FILE *fp = fopen("CompRecord1.txt","a");
    if(fp == NULL){
        puts("File Did not open!");
        return;
    }
    else{
        fwrite(&gp, sizeof(gp), 1, fp);
        fclose(fp);
    }
}

int main(){
    // remove("CompRecord1.txt");
    char choice = 'Y';
    int op;
    while(choice == 'Y' || choice == 'y'){
        puts("Enter 1 to input the record\nEnter 2 to Display Winner\nEnter 3 to search");
        scanf("%d", &op);
    }
}

```

```

switch(op){
    case 1:
        input();
        break;
    case 2:
        diplayWinner();
        break;
    case 3:
        search();
        break;
    default:
        puts("Invalid Value");
}
puts("Enter Y to Continue!! Press any key to exit");
fflush(stdin);
scanf("%c", &choice);
}
}

```