

B-splines


Andrzej Szymczak

November 1, 2011

- ▶ Bezier curves don't have local control property (move a point and the entire curve changes)
- ▶ Bezier curves with complicated shape (many control points) have high degree
- ▶ Can join lower degree curves into longer ones, but then one has to make sure that the smoothness conditions at the join points are met
- ▶ B-splines are smooth and piecewise low degree for sequence of control points of any length
- ▶ There are several types of B-splines; here we'll cover uniform polynomial B-splines

B-splines

- ▶ Take a sequence of control points P_0, P_1, \dots, P_{n-1} .
- ▶ Zero-degree B-spline is a discontinuous 'curve' that jumps from one control point to the next every 1 unit of time
- ▶ $B_0(t) = P_{\lfloor t \rfloor}$



B-splines

- ▶ Zero degree B-spline doesn't really deserve to be called a curve, but can be improved by filtering
- ▶ Simple box filter, or averaging over a moving unit time interval, is used to derive uniform B-splines
- ▶ Formula for B_d :

$$B_{d+1}(t) := \int_t^{t+1} B_d(s) ds$$


- ▶ B_1 is the piecewise linear (polygonal) curve connecting the consecutive control points
- ▶ By the Fundamental Theorem of Calculus B_2 is differentiable and the derivative is

$$B_2'(t) = B_1(t+1) - B_1(t)$$

- ▶ B_2 's derivative is piecewise linear so B_2 is piecewise quadratic

B-splines

- ▶ black: B_1
- ▶ blue: B_2



- ▶ B_d 's domain: $[0, n - d]$
- ▶ B_d is piecewise polynomial of degree d
- ▶ B_d is C^{d-1} , i.e. has $d - 1$ continuous derivatives
- ▶ Cubic B-spline (B_3) is the most popular: it has continuous acceleration (good for physics simulation)

B-spline basis functions

- ▶ A B-spline of degree d is defined by the following formula


$$B_d(t) = \sum_{i=0}^{n-1} P_i \phi_i^{(d)}(t)$$

- ▶ $\phi_i^{(d)}$ for $i \in \{0, 1, \dots, n-1\}$ are the *B-spline basis function*
- ▶ $\phi_i^{(d)}$ can be obtained from $\phi_0^{(d)}$ by shifting by i :


$$\phi_i^{(d)}(t) = \phi_0^{(d)}(t - i).$$

- ▶ The basis functions sum to 1 for every $t \in [0, n-d]$ (B-spline curve is a subset of the convex hull of the control points)


B-spline basis functions: $d=1$



B-spline basis functions: $d=2$



B-spline basis functions: $d=3$



B-spline subdivision


- ▶ An easy and fast procedure for drawing B-spline curves
- ▶ Based on two elementary operations on sequences of points
 - ▶ Doubling: $P_0 P_1 \dots P_{n-1} \longrightarrow P_0 P_0 P_1 P_1 P_2 P_2 \dots P_{n-1} P_{n-1}$
 - ▶ Averaging: $P_0 P_1 \dots P_{n-1} \longrightarrow \frac{P_0+P_1}{2}, \frac{P_1+P_2}{2} \dots \frac{P_{n-2}+P_{n-1}}{2}$
- ▶ Subdivision step for degree d B-splines: double and do averaging d times
- ▶ Drawing a B-spline: apply subdivision a few times starting from the control point sequence; connect the consecutive points in the resulting sequence
- ▶ One can also use explicit formulas for B-splines (see a good geometric modeling book), generate a number of points along the curve and connect them with lines

B-spline subdivision: degree 1

- ▶ $P_0 P_1 \dots P_{n-1} \longrightarrow P_0 P_0 P_1 P_1 \dots P_{n-1} P_{n-1} \longrightarrow$
 $P_0, \frac{P_0+P_1}{2}, P_1, \frac{P_1+P_2}{2}, \dots, \frac{P_{n-2}+P_{n-1}}{2}, P_{n-1}$
- ▶ Basically, each subdivision step inserts a midpoint between a consecutive pair of points in the input sequence
- ▶ Result: denser and denser set of points along the curve (degree 1 B-spline)


B-spline subdivision: degree 2

- ▶ $P_0 P_1 \dots P_{n-1} \longrightarrow \frac{3P_0+P_1}{4}, \frac{P_0+3P_1}{4}, \frac{3P_1+P_2}{4}, \frac{P_1+3P_2}{4}, \dots, \frac{3P_{n-1}+P_n}{4}, \frac{P_{n-1}+3P_n}{4}$
- ▶ Corner cutting (here: as a way to make the curve smoother)
- ▶ Result: denser and denser set of points along the curve (degree 2 B-spline)
- ▶ Black: input; blue: output (lines connect consecutive points)



B-spline subdivision: degree 3

- ▶ $P_0 P_1 \dots P_{n-1} \longrightarrow \frac{P_0+P_1}{2}, \frac{P_0+6P_1+P_2}{8}, \frac{P_1+P_2}{2}, \frac{P_1+6P_2+P_3}{8}, \dots, \frac{P_{n-2}+6P_{n-1}+P_n}{8}, \frac{P_{n-1}+P_n}{2}$
- ▶ More aggressive corner cutting (in a way, twice per step)
- ▶ Result: denser and denser set of points along the curve (degree 3 B-spline)
- ▶ Black: input; red: output (lines connect consecutive points)



Other subdivision schemes


Andrzej Szymczak

November 1, 2011

4-point rule


- ▶ Wouldn't it be nice to have a way to draw a smooth curve that passes through the control points?
- ▶ This is what 4-point rule does; however, it is not a piecewise polynomial curve; in fact, there is no simple analytical expression for the curve!
- ▶ Subdivision scheme: insert the point $\frac{-P_{i-1}+9P_i+9P_{i+1}-P_{i+2}}{16}$ between P_i and P_{i+1}
- ▶ The limit curve starts at the third control point and ends at the third last; it passes through all control points between them

4-point rule






Surface subdivision

- ▶ General scheme
 - ▶ Subdivide polygons into smaller ones
 - ▶ Move vertices around to smooth the mesh
- ▶ For triangle meshes, one can apply 1 : 4 subdivision (split each triangle into 4); splitting lines (for the black mesh) are shown in red below









Loop subdivision

- ▶ Two types of vertices
 - ▶ edge vertices (at the original mesh edges)
 - ▶ old vertices: at vertices of original mesh
- ▶ Old vertices move to a weighted average of neighbors in the original mesh
- ▶ Edge vertices move to a weighted average of vertices of the two triangles (in the original mesh) incident to the edge
- ▶ Weights are shown below



Tetrahedron



More examples (Beethoven, Johnny Hendrics)



More examples (Beethoven, Johnny Hendrics)



More examples (Beethoven, Johnny Hendrics)




More examples (Beethoven, Johnny Hendrics)




More examples (Beethoven, Johnny Hendrics)




More examples (foot, Scott Wiedemann)



More examples (foot, Scott Wiedemann)




More examples (foot, Scott Wiedemann)



Butterfly subdivision

- ▶ Leave the old vertices in place
- ▶ Interpolating scheme: limit surface passes through vertices of the control mesh
- ▶ Move the edge vertices using the weights shown below (note that some of them are negative!)
- ▶ Generally, not as good properties as the Loop subdivision (but some issues can be fixed by manipulating the weights)



- ▶ Surface subdivision (does not look like Loop or butterfly)
- ▶ B-spline curve