

Test Report

Test Device:
Charging method: CCS
Schema: DIN 70121
Date: 22.01.2026
Time: 10:56
Serial number: 00002210
Firmware Rev.: A6.02.01 RC01
Hardware Rev.: 3.8.0

Tester:
Test object ID:
Filename: 2026-01-22_10-56-02_.csv
MAC-PLC: 00:16:81:13:2B:8A
Testcase: -DC95k
Error code: 0x0503
Comment:

Test result: Ok

State	Result
Slac Match:	Ok
Session Setup:	OK
Service Discovery:	OK
Payment Selection:	OK
Authorization:	OK
Charge Parameter Discovery:	OK
Isolation Check:	FAILED
Charge Loop Precharge:	FAILED
Charge Loop:	FAILED
Time Measurement:	FAILED
Welding Detection:	FAILED
Stop Charging:	FAILED

Measurement	Value	Unit
Slac Attenuation:	20.0	dB
PP Voltage:	3.7	V
PP Resistor:	1611	Ohm
Max. isolation voltage:	0.0	V
Max. charging voltage:	0.0	V
Max. charging current:	0.0	A
Charging time:	0.0	s

Value ranges transmitted by EVSE	Min. limit value	Max. limit value	Unit
Rated output voltage:	0.0	1000.0	V
Rated output current:	0.0	300.0	A
Rated output power:	150000.0		W

Date of the last zero-offset calibration: 20.01.2026