

## Test Report

Test Device:  
Charging method: CCS  
Schema: DIN 70121  
Date: 22.01.2026  
Time: 10:54  
Serial number: 00002210  
Firmware Rev.: A6.02.01 RC01  
Hardware Rev.: 3.8.0

Tester:  
Test object ID:  
Filename: 2026-01-22\_10-54-15\_.csv  
MAC-PLC: 00:16:81:13:2B:8A  
Testcase: CP-Short-120  
Error code: 0x0B03  
Comment:

## Test result: Ok

State	Result
Slac Match:	Ok
Session Setup:	OK
Service Discovery:	OK
Payment Selection:	OK
Authorization:	OK
Charge Parameter Discovery:	OK
Isolation Check:	OK
Charge Loop Precharge:	OK
Charge Loop:	OK
Time Measurement:	FAILED
Welding Detection:	FAILED
Stop Charging:	FAILED

Measurement	Value	Unit
Slac Attenuation:	19.0	dB
PP Voltage:	3.7	V
PP Resistor:	1614	Ohm
Max. isolation voltage:	504.5	V
Max. charging voltage:	0.0	V
Max. charging current:	6.9	A
Charging time:	0.0	s

Value ranges transmitted by EVSE	Min. limit value	Max. limit value	Unit
Rated output voltage:	0.0	1000.0	V
Rated output current:	0.0	300.0	A
Rated output power:	150000.0		W

Date of the last zero-offset calibration: 20.01.2026