Add Account Members
Source: https://docs.paxos.com/api-reference/endpoints/account-members/add-account-members

post /identity/account-members
Add one or more account members to a given account.

The account members added by this API do not affect existing account members. For example, if an account has two members, and one member is added using this API, then the account will end up with three members.

For more information on properties of account members, see [Account Members](#account-members).

```bash OAuth Scope theme={null}
identity:write_account
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/account-members/overview

Account Members allow you to associate an Identity with an Account on our Platform.

Each Account can be linked to multiple Identities, which supports Joint Accounts (where two Identities have the ability
to transact against a single Profile).

Account members are effectively immutable. In order to update an account member, clients should remove then re-add the account member with the desired state.

The API requires clients to have write access on the account and all identities associated with the account.

Remove Account Member
Source: https://docs.paxos.com/api-reference/endpoints/account-members/remove-account-member

delete /identity/account-members/{id}
Removes an account member from an account.

```bash OAuth Scope theme={null}
identity:write_account
```

Create Account
Source: https://docs.paxos.com/api-reference/endpoints/accounts/create-account

post /identity/accounts
Create an account for a given identity, via the `identity_id` field.
This identity is the primary owner of the account for all tax-related purposes.

To track user balances using Paxos [Profiles](#tag/Profiles), use `create_profile=true` when creating the account.
Once an account has been created, it is not possible to associate it with a [Profile](#tag/Profiles).

Account Members

In addition to the primary owner, other identities may be associated with the account, by using `members`.
The identity on the account is treated as a BENEFICIAL_OWNER.

To add a financial advisor to an account, add a member with the FINANCIAL_ADVISOR role.

Example
This example request creates a joint account for John and Jane Doe. John has identity_id=82c338f4-3cb7-4d9b-be2a-4b077c82ee3a,
and Jane has identity_id=0f5d8475-33f3-4ebd-88a0-66dedc2581c1. John is the primary owner of the account for tax-purposes, but Jane
is a full beneficial owner.

Additionally, this account has an associated financial advisor with identity_id=0d26f878-298e-4d47-81be-cdf4e982a3d3.

```json
{
"account": {
"identity_id": "82c338f4-3cb7-4d9b-be2a-4b077c82ee3a",
"members": [{
"identity_id": "0f5d8475-33f3-4ebd-88a0-66dedc2581c1",
"roles": ["BENEFICIAL_OWNER"]
}, {
"identity_id": "0d26f878-298e-4d47-81be-cdf4e982a3d3",
"roles": ["FINANCIAL_ADVISOR"]
}]
}
}
```

Fields

Any fields not listed are forbidden in this request.

Field	Notes
identity_id	Required
description	Optional
metadata	Optional
ref_id	Optional
members	Optional

```bash OAuth Scope theme={null}
identity:write_account
```

Get account
Source: https://docs.paxos.com/api-reference/endpoints/accounts/get-identityaccounts

get /identity/accounts/{id}

```bash OAuth Scope theme={null}
identity:read_account
```

List Accounts
Source: https://docs.paxos.com/api-reference/endpoints/accounts/list-accounts

get /identity/accounts
List accounts with pagination. Every response will contain a `next_page` field,
as long as the end of the list has not been reached. Pass this value into the `page_cursor` field of the next request
to retrieve the next page of results.

```bash OAuth Scope theme={null}
identity:read_account
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/accounts/overview

Accounts connect Identities (persons or institutions) to Profiles (asset balances).

Key Features

* **Balance Management**: Track and manage profile balances via [Subledgering] (/guides/crypto-brokerage/ledger-type#fiat-and-crypto-subledger)
* **Joint Account Support**: Link multiple Identities to a single Account for shared on platform balance

Accounts are required for all Identity API integrations.

Update Account
Source: https://docs.paxos.com/api-reference/endpoints/accounts/update-account

put /identity/accounts
This enables you to update an existing account with new information. Please refer to the following
table for fields that can be updated via this endpoint.

Field	Notes
account.id	Required
account.description	Optional
account.ref_id	Optional
account.metadata	Optional. This will overwrite any existing metadata added to the account.
account.members	Optional. The only roles that can be added/removed are `FINANCIAL_ADVISOR` or `AUTHORIZED_USER.` You must always specify the full members object as we do not currently support differential member updates.
set_user_disabled	Optional. Setting this to `true` will disable the account, limiting its ability to be used within the Paxos platform.

Example Requests
Disabling an account

```json
{
"set_user_disabled": true,
"account": {
"id": "82c338f4-3cb7-4d9b-be2a-4b077c82ee3a",
"description": "Account Description",
"ref_id": "82c338f4-3cb7"
}
}
```

Adding an account member
To retain the existing account members and add a new account member, the `members` field must contain the existing
account members and the new member. The below example adds an `AUTHORIZED_USER` to the account.

In order to add account members while leaving existing account members unaffected, clients should use the [Add Account Members](#operation/AddAccountMembers) API.

```json
{
"account": {
"id": "82c338f4-3cb7-4d9b-be2a-4b077c82ee3a",
"members": [{
```

```
"identity_id": "0f5d8475-33f3-4ebd-88a0-66dedc2581c1",
"roles": ["BENEFICIAL_OWNER"]
}, {
"identity_id": "0d26f878-298e-4d47-81be-cdf4e982a3d3",
"roles": ["FINANCIAL_ADVISOR"]
}, {
"identity_id": "012k23eb-298e-4d47-81be-cdf4e982a3d3",
"roles": ["AUTHORIZED_USER"]
}]
}
}
```

Removing an account member
To remove an existing account member and retain other needed members, the `members` field must contain
the existing account members without the account member you'd like to remove. The below example removes an `AUTHORIZED_USER` from the account.

Note, this API requires the `members` array to have at least one element. In order to delete all members
from an account, clients should use the [Delete Account Member]
(#operation/DeleteAccountMember) API.

```json
{
"account": {
"id": "82c338f4-3cb7-4d9b-be2a-4b077c82ee3a",
"members": [{
"identity_id": "0f5d8475-33f3-4ebd-88a0-66dedc2581c1",
"roles": ["BENEFICIAL_OWNER"]
}]
}
}
```

Updating an account members' roles
To update an account members' roles, the `members` field must contain all the existing members with their roles along
with the additional role that you'd like to add or remove. The below example adds the `FINANCIAL_ADVISOR` role to an member that is already a `BENEFICIAL_OWNER`.

```json
{
"account": {
"id": "82c338f4-3cb7-4d9b-be2a-4b077c82ee3a",
"members": [{
"identity_id": "0f5d8475-33f3-4ebd-88a0-66dedc2581c1",
"roles": ["BENEFICIAL_OWNER", "FINANCIAL_ADVISOR"]
}]
}
}
```

```bash OAuth Scope theme={null}
identity:write_account
```

Delete API Credentials
Source: https://docs.paxos.com/api-reference/endpoints/api-credentials/delete-api-credentials

delete /api-creds/credentials/{client_id}
Delete the given API Credentials, preventing them from being used for authentication.

```bash OAuth Scope theme={null}
api_creds:delete_credentials
```

List API Credentials
Source: https://docs.paxos.com/api-reference/endpoints/api-credentials/list-api-credentials

get /api-creds/credentials
List all API credentials that have been created.

```bash OAuth Scope theme={null}
api_creds:read_credentials
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/api-credentials/overview

The API Credentials API allows clients to create and manage API credentials for accessing Paxos services.

Available Endpoints

* [List API Credentials](/api-reference/endpoints/api-credentials/list-api-credentials)
* [Delete API Credentials](/api-reference/endpoints/api-credentials/delete-api-credentials)

Overview
Source: https://docs.paxos.com/api-reference/endpoints/crypto-deposits/overview

For Paxos Global PTE Ltd users, update or reject a crypto deposit that does not contain the required travel rule information.

For [Paxos Global PTE Ltd](https://help.paxos.com/hc/en-us/articles/25928845778068) users, update or reject a crypto deposit that does not contain the required travel rule information.

Deposits with the `NEEDS_INFO` status require additional sender information before they can be processed.

Required Information

* **For individuals**: Both first and last name are required.
* **For institutions**: The institution name is required.

If a deposit is rejected, the funds will no longer be available.

Learn More

Learn more about travel rule updates in the [Travel Rule Help Center](https://help.paxos.com/hc/en-us/articles/25422999706900).

Reject Crypto Deposit
Source: https://docs.paxos.com/api-reference/endpoints/crypto-deposits/reject-crypto-deposit

post /transfer/crypto-deposits/{id}/reject
Reject a crypto deposit which is waiting for required travel rule information about the originator address.
If the rejected deposit has any status other than `NEEDS_INFO`, the request will return an error.
Only the creator of the crypto deposit can reject it.

```bash OAuth Scope theme={null}
transfer:reject_crypto_deposit
```

Update Crypto Deposit
Source: https://docs.paxos.com/api-reference/endpoints/crypto-deposits/update-crypto-deposit

post /transfer/crypto-deposits/{id}/update
Crypto deposits that do not meet the minimum travel rule requirements are blocked.
To update a crypto deposit, provide the required travel rule information about the
originator address.

```bash OAuth Scope theme={null}
transfer:update_crypto_deposit
```

List Crypto Destination Addresses
Source: https://docs.paxos.com/api-reference/endpoints/crypto-destination-addresses/list-crypto-destination-addresses

get /transfer/crypto-destination-addresses
List all crypto destination addresses, optionally filtering and paging the results

```bash OAuth Scope theme={null}
transfer:read_crypto_destination_address
```

Put Crypto Destination Addresses
Source: https://docs.paxos.com/api-reference/endpoints/crypto-destination-addresses/put-crypto-destination-address

put /transfer/crypto-destination-address
Updates a specified crypto destination address. If the address does not exist, it will be created

```bash OAuth Scope theme={null}
transfer:write_crypto_destination_address
```

Create Crypto Withdrawal
Source: https://docs.paxos.com/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal

post /transfer/crypto-withdrawals
Withdraw a cryptocurrency asset to a specified destination address.

Important for Stellar Network (PYUSD):

When withdrawing PYUSD on the Stellar network, the destination address must have an established trustline with the PYUSD issuer:

- **PYUSD Issuer**: `GDQE7IXJ4HUHV6RQHIUPRJSEZE4DRS5WY577O2FY6YQ5LVWZ7JZTU2V5` (mainnet)
- **Asset Code**: `PYUSD`

How to Establish a Trustline:

The recipient must use a Stellar wallet or the Stellar SDK to:
1. Ensure their account has minimum XLM balance (at least 1 XLM recommended)
2. Create a trustline to the PYUSD issuer for the PYUSD asset
3. Confirm the trustline is active before requesting withdrawal

Verifying Trustline Status:

You can verify if an address has the required trustline by:
- Using Stellar blockchain explorers (e.g., stellar.expert)
- Querying the Stellar Horizon API
- Using the Stellar SDK to check account balances

```bash OAuth Scope theme={null}
transfer:write_crypto_withdrawal
```

Create Deposit Address
Source: https://docs.paxos.com/api-reference/endpoints/deposit-addresses/create-deposit-address

post /transfer/deposit-addresses
Create a deposit address on a blockchain network for depositing to a profile.

Important for Stellar Network (PYUSD):

When creating a deposit address for PYUSD on the Stellar network:

- Paxos automatically handles all necessary setup including trustline establishment
- The deposit address is immediately ready to receive PYUSD tokens
- No additional configuration is required by the user
- The PYUSD issuer address on Stellar mainnet is: `GDQE7IXJ4HUHV6RQHIUPRJSEZE4DRS5WY577O2FY6YQ5LVWZ7JZTU2V5`
- The PYUSD asset code is: `PYUSD`

```bash OAuth Scope theme={null}
transfer:write_deposit_address
```

List Deposit Addresses
Source: https://docs.paxos.com/api-reference/endpoints/deposit-addresses/list-deposit-addresses

get /transfer/deposit-addresses
List all deposit addresses, optionally filtering and paging the results.

```bash OAuth Scope theme={null}
transfer:read_deposit_address
```

Get Event
Source: https://docs.paxos.com/api-reference/endpoints/events/get-event

get /events/{id}
Get an Event by its (event) id, the event must have been created by the system and you must be the owner of the
the event, you can get an event id by either listing events or via a webhook integration.

```bash OAuth Scope theme={null}
events:read_event
```

List Events
Source: https://docs.paxos.com/api-reference/endpoints/events/list-events

get /events
This endpoint enables you to fetch a list of events that have been created by the system.
You can use query parameters to filter the results by the `created_at` time using
`created_at.lt`, `created_at.gt`, etc. and you can
`limit` the number of events returned.

Using `created_at` and `limit` together will allow you to paginate through all events owned by you.
Events returned will always be order in `created_at` ascending order.

```bash OAuth Scope theme={null}
events:read_event
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/events/overview

Retrieve events from your Paxos account

The Events API provides access to event data from your Paxos account. Events are generated when certain actions occur within your account, such as identity status changes, document requirements, or KYC refresh activities.

Events are immutable records of state changes that occurred in your account. They provide a reliable way to track the history of important activities and integrate with your systems using webhooks.

Create Crypto Withdrawal Fee
Source: https://docs.paxos.com/api-reference/endpoints/fees/create-crypto-withdrawal-fee

post /transfer/fees/crypto-withdrawal
Get a guaranteed fee for the given currency, valid for a period of time.
Specify exactly one of `amount` or `total`, otherwise an error is returned.

The [Create Crypto Withdrawal](#operation/CreateCryptoWithdrawal) request that uses the guaranteed fee endpoint
must specify an `amount` less than or equal to the guaranteed fee `amount`, otherwise the withdrawal is rejected.

```bash OAuth Scope theme={null}
fee:write_crypto_withdrawal_fee
```

Create Fiat Account
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/create-fiat-account

post /transfer/fiat-accounts
Create an account to initiate a fiat withdrawal.

For U.S. wires, set `fiat_network_instructions` > `wire` > `routing_details` > `routing_number_type` to `ABA`. For international (SWIFT) wires, set `fiat_network_instructions` > `wire` > `routing_details` > `routing_number_type` to `SWIFT`. For CUBIX, set `fiat_network_instructions` > `cubix` > `account_id`, and do not specify `routing_number_type`. For CUBIX, the `account_id` is the CUBIX account ID.

```bash OAuth Scope theme={null}
transfer:write_fiat_account
```

Create Fiat Deposit Instructions
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/create-fiat-deposit-

instructions

post /transfer/fiat-deposit-instructions
Create instructions for depositing fiat.

```bash OAuth Scope theme={null}
transfer:write_fiat_deposit_instructions
```

Create Fiat Withdrawal
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal

post /transfer/fiat-withdrawals
Withdraw fiat to the given destination.

```bash OAuth Scope theme={null}
transfer:write_fiat_withdrawal
```

Delete Fiat Account
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/delete-fiat-account

delete /transfer/fiat-accounts/{id}
Delete a Fiat Account.
Once a Fiat Account is deleted, transfers cannot be initiated to it.

```bash OAuth Scope theme={null}
transfer:write_fiat_account
```

Get Fiat Account
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/get-fiat-account

get /transfer/fiat-accounts/{id}
Get a single Fiat Account by ID.

In the polling workflow, this endpoint can be called to monitor a FiatAccount's status.
The Fiat Account response includes the full account number, beneficiary name and address details.

```bash OAuth Scope theme={null}
transfer:read_fiat_account
```

Get Fiat Deposit Instructions
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/get-fiat-deposit-instructions

get /transfer/fiat-deposit-instructions/{id}
Get instructions for depositing fiat using a Paxos Fiat Deposit Instructions ID.
The Fiat Deposit Instructions ID (`id`) is provided in the response of the [Create Fiat Deposit Instructions](#operation/CreateFiatDepositInstructions).

```bash OAuth Scope theme={null}
transfer:read_fiat_deposit_instructions
```

List Fiat Accounts
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/list-fiat-accounts

get /transfer/fiat-accounts
List all Fiat Accounts, optionally filtering and paging the results.
The response includes an abbreviated `FiatAccount` object:

- Beneficiary name and address details are excluded.
- Only the last four (**4**) digits of the account number are included.

Use [Get Fiat Account](#operation/GetFiatAccount) to retrieve the complete `FiatAccount` object.

The paginated results default to the maximum limit of 1,000 Fiat Accounts, unless otherwise specified with the `limit` parameter.
Every paginated response contains a `next_page` field until the last page is reached.
Pass the `next_page` value into the `page_cursor` field of the next request to retrieve the next page of results.

```bash OAuth Scope theme={null}
transfer:read_fiat_account
```

List Fiat Deposit Instructions
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/list-fiat-deposit-instructions

get /transfer/fiat-deposit-instructions
Return the associated Fiat Deposit Instructions matching the search criteria for the current Account.
The paginated results default to the maximum limit of 1,000 Fiat Deposit instructions, unless otherwise specified with the `limit` parameter.
Every paginated response contains a `next_page` field until the last page is reached.
Pass the `next_page` value into the `page_cursor` field of the next request to retrieve the next page of results.

```bash OAuth Scope theme={null}
transfer:read_fiat_deposit_instructions
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/overview

The Fiat Transfers API allows clients to deposit and withdraw fiat via Wire (Fedwire and SWIFT) and CUBIX networks.

The supported asset is USD.

Available Endpoints

For Deposits

* [Create Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/create-fiat-deposit-instructions)
* [List Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/list-fiat-deposit-instructions)
* [Get Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/get-fiat-deposit-instructions)

For Withdrawals

* [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account)
* [List Fiat Accounts](/api-reference/endpoints/fiat-transfers/list-fiat-accounts)
* [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account)
* [Delete Fiat Account](/api-reference/endpoints/fiat-transfers/delete-fiat-account)
* [Update Fiat Account](/api-reference/endpoints/fiat-transfers/update-fiat-account)

* [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal)

Update Fiat Account
Source: https://docs.paxos.com/api-reference/endpoints/fiat-transfers/update-fiat-account

put /transfer/fiat-accounts/{id}
Change an existing value or add a new value on one or more fields for the given Fiat Account and return the modified Fiat Account in `PENDING` status.
Update fields in **either** `fiat_account_owner.person_details` or `fiat_account_owner.institution_details`.
Attempts to convert the `fiat_account_owner` type results in an error.
Empty strings or null values are ignored.

Upon successful response, Paxos initiates an automated review of the requested changes and then either sets the status to `APPROVED` or `REJECTED`.
Occasionally, a manual review may be required.
Use [Get Fiat Account](#operation/GetFiatAccount) to check for status changes.

```bash OAuth Scope theme={null}
transfer:write_fiat_account
```

Document Upload
Source: https://docs.paxos.com/api-reference/endpoints/identity-documents/document-upload

put /identity/identities/{identity_id}/documents
This endpoint enables you to receive a URL to upload a document to Paxos for identity verification or enhanced due diligence purposes.
When uploading a document you must specify the document type. You will receive a URL where you can upload the document using a POST request.

Requirements:
- Uploaded documents must be less than 100 MB in size
- Supported formats include PDF, JPG, and PNG

For more information on document requirements for enhanced due diligence, see [here](https://docs.paxos.com/identity/edd).

```bash OAuth Scope theme={null}
identity:write_identity
```

List Identity Documents
Source: https://docs.paxos.com/api-reference/endpoints/identity-documents/list-identity-documents

get /identity/identities/{identity_id}/documents
This endpoint enables you to get a list of all documents associated with an identity.

```bash OAuth Scope theme={null}
identity:read_identity
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/identity-documents/overview

The Identity Documents API allows clients to send documents to Paxos to validate identities during the KYC process.

Files can be updated multiple times by re-sending the document type for processing.

Supported File Formats

We currently accept the following file formats:

* `pdf`
* `jpg`
* `png`

Upload Process

Steps to upload a document are as follows:

1. Send a `PUT` request to `/identity/identities/{id}/documents` to get
   the upload URL.
2. Send your document to the provided URL via a PUT request. Take the following example
using curl:
   ```bash theme={null}
   curl --upload-file Proof_of_residence.jpg $URI
   ```

Uploaded document metadata will be available via `GET` request to
`/identity/identities/{id}/documents`

Create Identity
Source: https://docs.paxos.com/api-reference/endpoints/identity/create-identity

post /identity/identities
Creates a new Person or Institution Identity on the Paxos Platform.

A successful response indicates that the identity has been created and is `PENDING`
approval. The identity is only
available to use on the Platform once it is `APPROVED`. For a full description of statuses
read the [status guide here](https://docs.paxos.com/identity/statuses).

For detailed guidance on which [fields are required]
(https://docs.paxos.com/identity/required-details) for your integration
or the [lifecycle of an Identity](https://docs.paxos.com/identity/statuses) on the platform,
please read the [Identity Developer Guide](https://docs.paxos.com/identity).

```bash OAuth Scope theme={null}
identity:write_identity
```

Get Identity
Source: https://docs.paxos.com/api-reference/endpoints/identity/get-identity

https://developer.paxos.com/docs/paxos-v2.openapi.json get /identity/identities/{id}
Get an Identity by its (identity) id. You can only see identities created by you.

You can use the query parameter `include_details` to include identity details
(`person_details` or `institution_details`) in
the response and the query parameter `include_institution_members` to include institution
members in the response.

```bash OAuth Scope theme={null}
identity:read_identity
```

List Identities
Source: https://docs.paxos.com/api-reference/endpoints/identity/list-identities

https://developer.paxos.com/docs/paxos-v2.openapi.json get /identity/identities

This endpoint enables you to fetch a list of Identities.
You can use query parameters to filter the results returned by `created_at`, `updated_at`, `summary_status` and `identity_type`

Note that this endpoint supports pagination and returns a cursor token for fetching next pages.

```bash OAuth Scope theme={null}
identity:read_identity
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/identity/overview

An Identity represents a person or institution who is able to take actions on the Paxos Platform.

Depending on your integration type you might not need to create Identities for your end users.

Identities must pass a set of verifications and checks before they're able to transact on the Platform. Learn more
about getting started with Identity and managing their onboarding lifecycle in the [Identity Developer Guide](/guides/identity).

Update Identity
Source: https://docs.paxos.com/api-reference/endpoints/identity/update-identity

put /identity/identities/{id}
Updates an Identity, this action performs a delta of what is submitted in the update and the existing identity.
- Updating details (`person_details` or `institution_details`) might lead to the identity being re-verified (e.g. re-screening name changes), which
could impact the identity's ability to transact on the Platform.
- Setting `set_user_disabled` to `true` will make the Identity `DISABLED` (read [more here](https://docs.paxos.com/identity/statuses) on what this means)
- Setting `tax_details` will update all the tax details for the identity
- Setting `last_kyc_refresh_date` indicates this is not an adhoc-update, and instead an update for a [periodic kyc refresh](https://docs.paxos.com/identity/kyc-refresh)

Changing an Institution Identity to a Person and vice-versa is not supported.

```bash OAuth Scope theme={null}
identity:write_identity
```

Add Institution Members
Source: https://docs.paxos.com/api-reference/endpoints/institution-members/add-institution-members

post /identity/institution-members
Add one or more institution members to a given institution.

Adding new members doesn't affect existing members. For example, if an institution has three members, and adds two members using this API, then the institution would end up with five total members.

For details on the properties that can be specified when creating institution members, see [Specifying Institution Members and Their Roles](#specifying-institution-members-and-their-roles).

```bash OAuth Scope theme={null}
```

identity:write_identity
```

# Overview
Source: https://docs.paxos.com/api-reference/endpoints/institution-members/overview

Institution Members allow you to associate persons with an institution on our Platform.

Each institution can have multiple members, with each member representing the relationship to a person identity.

When creating an institution identity, you must designate at least one institution member. This requirement ensures we have complete information about the institution's ownership structure
and key personnel, which is necessary to onboard institutions.


# Remove Institution Member
Source: https://docs.paxos.com/api-reference/endpoints/institution-members/remove-institution-member

delete /identity/institution-members/{id}
Removes an institution member from an institution.

```bash OAuth Scope theme={null}
identity:write_identity
```


Create Internal Transfer
Source: https://docs.paxos.com/api-reference/endpoints/internal-transfers/create-internal-transfer

post /transfer/internal
Transfer assets between two profiles belonging to the same customer.

```bash OAuth Scope theme={null}
transfer:write_internal_transfer
```


Create Issuer Quote
Source: https://docs.paxos.com/api-reference/endpoints/issuer-quotes/create-issuer-quote

post /issuer-quote
Creates a request for a quote where Paxos is the issuer. Note that PAXG quotes will be unavailable when the London gold market is closed.

```bash OAuth Scope theme={null}
exchange:write_issuer_quote
```


Create Issuer Quote Execution
Source: https://docs.paxos.com/api-reference/endpoints/issuer-quotes/create-issuer-quote-execution

post /issuer-quote/{quote_id}
Executes on a quote where Paxos is the issuer.

```bash OAuth Scope theme={null}
exchange:write_issuer_quote_execution
```
```

List Issuer Quote Executions
Source: https://docs.paxos.com/api-reference/endpoints/issuer-quotes/list-issuer-quote-executions

get /issuer-quotes
Retrieves full details of quote executions where Paxos is the issuer.

```bash OAuth Scope theme={null}
exchange:read_issuer_quote_execution
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/issuer-quotes/overview

Issuer Quotes are 'held rates' offered by Paxos to mint or redeem Paxos-issued assets at a specific price within a period of time.

For example, the option to buy PAXG within the next 5 seconds for \$3,000.

The typical Issuer Quotes workflow is as follows:

1. Call [Create Issuer Quote](/api-reference/endpoints/issuer-quotes/create-issuer-quote) to get a quote for the asset you want to mint or redeem to a specific profile.
2. Call [Create Issuer Quote Execution](/api-reference/endpoints/issuer-quotes/create-issuer-quote-execution) with the quote ID and profile ID.

You can call [List Issuer Quote Executions](/api-reference/endpoints/issuer-quotes/list-issuer-quote-executions) to review or construct reports on issuer quote execution activity.

List Transfer Limits
Source: https://docs.paxos.com/api-reference/endpoints/limits/list-transfer-limits

get /transfer/limits/utilizations
List all limits that apply to the given transaction type.

```bash OAuth Scope theme={null}
transfer:read_transfer_limit
```

Get Order Book
Source: https://docs.paxos.com/api-reference/endpoints/market-data/get-order-book

get /markets/{market}/order-book
Retrieves the full list of bids and asks of the order book at individual price levels with resting quantities per level.

Get Ticker
Source: https://docs.paxos.com/api-reference/endpoints/market-data/get-ticker

get /markets/{market}/ticker
Retrieves order book statistics of the exchange over the last 24 hours and from midnight UTC until current time.

List Markets
Source: https://docs.paxos.com/api-reference/endpoints/market-data/list-markets

get /markets

Retrieves the set of current available markets for trading with details.

List Recent Executions
Source: https://docs.paxos.com/api-reference/endpoints/market-data/list-recent-executions

get /markets/{market}/recent-executions
Retrieves the list of 2000 most recent executions by all users to occur in the order book.

Overview
Source: https://docs.paxos.com/api-reference/endpoints/market-data/overview

Market data provides various parameters of the order book and historical order data.

Create Monitoring Address
Source: https://docs.paxos.com/api-reference/endpoints/monitoring-addresses/create-monitoring-address

post /rewards/monitor/address
Adds an address to be monitored for rewards tracking.

Currently only `ETHEREUM`, `SOLANA`, `INK` & `XLAYER` addresses are supported.

```bash OAuth Scope theme={null}
rewards:write_monitoring_address
```

Get Monitoring Address
Source: https://docs.paxos.com/api-reference/endpoints/monitoring-addresses/get-monitoring-address

get /rewards/monitor/address/{id}
Retrieves a monitoring address by ID

```bash OAuth Scope theme={null}
rewards:read_monitoring_address
```

List Monitoring Address
Source: https://docs.paxos.com/api-reference/endpoints/monitoring-addresses/list-monitoring-address

get /rewards/monitor/address
Retrieve a list of monitoring address

Filter by network to retrieve a list of addresses on that network, or filter by network & address to retrieve a single record.

```bash OAuth Scope theme={null}
rewards:read_monitoring_address
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/monitoring-addresses/overview

A Monitoring Address is a blockchain address that Paxos monitors daily for eligible stablecoin activity.

Paxos uses monitoring addresses to determine the amount of rewards your organization will earn. We recommend adding any addresses you expect to hold, receive, or mint Paxos stablecoins as a monitoring address in order to receive rewards for all of your qualifying on-chain activity.

Important Timing

> Monitoring addresses must be added by month end (`23:59 UTC+0`) in order to earn rewards for that month. Addresses added after month end will start earning rewards for the following month.

Availability

These endpoints are only relevant for Global Dollar Network (GDN) partners.

Update Monitoring Address
Source: https://docs.paxos.com/api-reference/endpoints/monitoring-addresses/update-monitoring-address

put /rewards/monitor/address/{id}
Updates a monitored address name

```bash OAuth Scope theme={null}
rewards:write_monitoring_address
```

Create Orchestration Rule
Source: https://docs.paxos.com/api-reference/endpoints/orchestration-rules/create-orchestration-rule

post /orchestration/rules
Creates a persistent orchestration rule that automatically triggers orchestrations when matching deposits are received.

The rule will:
1. Generate deposit instructions associated with the rule.
2. Continuously monitor incoming deposits to those instructions.
3. Automatically execute orchestrations to the specified destination.

Supported Sources:

- Crypto deposit
- Fiat deposit

Supported Destinations:

- Crypto address on a supported network
- Bank account
- Profile ID

Error conditions:
- [Already Exists](https://developer.paxos.com/docs/v2/problems/already-exists): Returned if a rule with the same ref_id already exists.

```bash OAuth Scope theme={null}
orchestration:write_orchestration_rule
```

Delete Orchestration Rule
Source: https://docs.paxos.com/api-reference/endpoints/orchestration-rules/delete-orchestration-rule

delete /orchestration/rules/{id}
Deactivates an orchestration rule by updating its status to DELETED.
Once deleted, the rule will no longer trigger new orchestrations.
Any orchestrations previously created by the rule will continue to be processed.

The request accepts a single rule ID and returns the updated rule resource
with its status set to DELETED upon success.

```bash OAuth Scope theme={null}
orchestration:write_orchestration_rule
```

List Orchestration Rules
Source: https://docs.paxos.com/api-reference/endpoints/orchestration-rules/list-orchestration-rules

get /orchestration/rules
List all orchestration rules, optionally filtering and paging the results.

By default, orchestration rules are returned in reverse chronological (descending)
order by creation time. If no query parameters are supplied,
the response will include up to the last 100 rules which were created.

The paginated results default to display up to 100 rules, unless
otherwise specified with the `limit` parameter. The maximum `limit` value is 1000.
Every paginated response contains a `next_page_cursor` field until the last page is reached.

Pass the `next_page_cursor` value into the `page_cursor` field of a new
request to retrieve the next page of results.

Rules can be filtered by:
- Profile ID (`profile_id`)
- Status (`status`)
- Source asset (`source_asset`)
- Destination asset (`destination_asset`)

```bash OAuth Scope theme={null}
orchestration:read_orchestration_rule
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/orchestration-rules/overview

Automate conversions triggered by deposits with orchestration rules.

Automate fiat and stablecoin conversions triggered by incoming deposits using the
Orchestration Rules API.

Create persistent rules that define how incoming assets should be converted, retrieve active
rules, or check the status of an orchestration rule.

Create Orchestration
Source: https://docs.paxos.com/api-reference/endpoints/orchestration/create-orchestration

post /orchestration/orchestrations
Creates a one-time orchestration that moves assets from a source profile to a destination.
Use this endpoint when funds already reside on the Paxos platform and need to be transferred
or converted as part of a single workflow.

A request to create an orchestration can fail with one of the following
types of errors:

- [Insufficient Funds](https://developer.paxos.com/docs/v2/problems/insufficient-funds) if the Profile (`profile_id`) has insufficient available balance to fund the execution.
- [Already Exists](https://developer.paxos.com/docs/v2/problems/already-exists) if an orchestration with the same external ID (`ref_id`) has already been created.

```bash OAuth Scope theme={null}
orchestration:write_orchestration
```

Get Orchestration
Source: https://docs.paxos.com/api-reference/endpoints/orchestration/get-orchestration

get /orchestration/orchestrations/{id}
Retreives a specific orchestration using its orchestration ID.

```bash OAuth Scope theme={null}
orchestration:read_orchestration
```

List Orchestrations
Source: https://docs.paxos.com/api-reference/endpoints/orchestration/list-orchestrations

get /orchestration/orchestrations
List all orchestrations, optionally filtering and paging the results.

By default, orchestrations are returned in reverse chronological (descending) order by creation time. If no query parameters are supplied, the response will include up to the last 100 orchestrations which were created.

The paginated results default to display up to 100 orchestrations, unless otherwise specified with the `limit` parameter. The maximum `limit` value is 1000. Every paginated response contains a `next_page_cursor` field until the last page is reached.

Pass the `next_page_cursor` value into the `page_cursor` field of a new request to retrieve the next page of results.

When filtering by profile IDs using the `profile_ids` parameter, there is a limit of 100 profiles that can be specified in a single request.

Orchestrations are provided for various operations including:
- Deposits to a paxos-platform crypto address or bank account
- Withdrawals to a customer-owned crypto address or bank account
- Conversions from one asset to another
- Orchestrated workflows involving some or all of the above
- Invocation of an Orchestration Rule

```bash OAuth Scope theme={null}
orchestration:read_orchestration
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/orchestration/overview

Execute fiat and stablecoin conversions with orchestration workflows.

Execute fiat and stablecoin conversions, including deposits, transfers, and withdrawals, using the Orchestrations API.

Create one-time ("ad-hoc") orchestrations for funds already on the Paxos platform, or

retrieve a list of orchestrations and check their statuses.

Overview
Source: https://docs.paxos.com/api-reference/endpoints/orchestrations-conversions/overview

The Orchestrations API provides a single interface for executing fiat and stablecoin conversions on the Paxos platform.

Orchestration Rule

If the orchestration begins with a deposit from an external source, use an Orchestration Rule.

* Define orchestration behavior for incoming deposits.
* Automatically execute the specified conversion when a deposit matches a rule.
* Remain active and in effect until explicitly deleted.
* Each rule is associated with deposit instructions that must be used by the sender.

Ad-Hoc Orchestrations

If the source funds are already on the Paxos platform (e.g., held in a profile), use the Create Orchestration endpoint to initiate a one-time conversion.

* This endpoint supports sending the converted funds to either another internal profile or an external destination.
* Rules are not required for ad-hoc orchestrations.

<Warning title="Stablecoin Conversions Deprecation Notice">
  The Stablecoin Conversions API will be deprecated.

  Paxos will migrate all active conversion rules to the Orchestrations API format by December 2025.

  Customers should transition to the Orchestrations API to ensure continuity of service.
</Warning>

Cancel Order
Source: https://docs.paxos.com/api-reference/endpoints/orders/cancel-order

delete /profiles/{profile_id}/orders/{id}
Submits a cancellation request. A response indicates that the request has been acknowledged and provides no
guarantee the order has been cancelled.

```bash OAuth Scope theme={null}
exchange:write_order
```

Create Order
Source: https://docs.paxos.com/api-reference/endpoints/orders/create-order

post /profiles/{profile_id}/orders
For limit orders, create an order for buying or selling an asset:

- To buy, set `side = BUY` and set `base_amount` to the crypto amount you want to buy.
- To sell, set `side = SELL` and set `base_amount` to the crypto amount you want to sell.

For market orders, create an order for buying or selling an asset:

- To buy, set `side = BUY` and set `quote_amount` to the dollar amount you want to spend.
- To sell, set `side = SELL` and set `base_amount` to the crypto amount you want to sell.

There are five types of orders:

- Limit Orders: Buy or sell at a specified price or better. Execution not guaranteed. Taker orders will be rejected if price deviates 15% from midpoint.
- Post-Only Limit Orders: have the same properties as Limit Orders, but get rejected if they cross the orderbook.
- Market Orders: Operate as Immediate or Cancel (IOC) orders. Price is variable, executes at best available price at time of order.
- Stop Market Orders: Will convert to a market sell order with the specified quantity when the stop price is hit. The stop price does not guarantee that it will be executed at that price. Market conditions (price) might change between the order being triggered and order being executed. Currently only sell stop loss orders are supported.
- Stop Limit Orders: have a Stop Price which when hit, will convert to a limit sell order that will be executed at a specified price (or better)

Maximum notional order size by type:

Order Type	Market	Maximum Notional Value (USD)
Market	all	500,000
Limit	BTCUSD	1,500,000
Limit	ETHUSD	1,500,000
Limit	other	1,000,000

```bash OAuth Scope theme={null}
exchange:write_order
```

Get Order
Source: https://docs.paxos.com/api-reference/endpoints/orders/get-order

get /profiles/{profile_id}/orders/{id}
Retrieves the current state of an order.
- Historical data prior to May 16, 2022 is unavailable.

```bash OAuth Scope theme={null}
exchange:read_order
```

List Executions
Source: https://docs.paxos.com/api-reference/endpoints/orders/list-executions

get /executions
Retrieves full details of underlying executions with optional filters.
Notes:
- This endpoint returns a maximum of 1000 items per page.
- Filtering options are `account_id`, `profile_id` or neither (all executions).

```bash OAuth Scope theme={null}
exchange:read_order
```

List Orders
Source: https://docs.paxos.com/api-reference/endpoints/orders/list-orders

get /orders
Retrieves full details of orders associated with a Profile ID, with optional filters.

- Historical data prior to May 16, 2022 is unavailable.
- Pagination Limit has a max of 1000. Pagination Offset is now deprecated and nonfunctional.
- Filtering options are `account_id`, `profile_id` or neither (all orders).

```bash OAuth Scope theme={null}
exchange:read_order
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/orders/overview

Order management for market, limit, and post-only orders.

There are three types of orders: market, limit and post-only.

Market orders guarantee execution at a variable price and quantity. Limit orders guarantee price and quantity at the time of execution but do not guarantee execution.
Post-only is an order type that will only be placed on the order book if it is the maker side of a trade.

Create Paxos Transfer
Source: https://docs.paxos.com/api-reference/endpoints/paxos-transfers/create-paxos-transfer

post /transfer/paxos
Transfer assets between two Profiles belonging to different [Entities](https://docs.paxos.com/dashboard/organization#entity).

```bash OAuth Scope theme={null}
transfer:write_paxos_transfer
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/paxos-transfers/overview

Move assets between two Entities belonging to the same Organization or to a different Organization on the Paxos platform.

Important Notes

> Transferring USD between Entities is prohibited in some jurisdictions. Contact [Support](https://support.paxos.com/) if you run into any problems with this restriction.

Ensure the destination [Profile](/guides/dashboard/organization#profile) already exists before beginning the transfer. This may require contacting someone outside your Organization to get the destination Profile ID.

List Payments
Source: https://docs.paxos.com/api-reference/endpoints/payments/list-payments

get /statements/payments
List payments based on the provided filters

```bash OAuth Scope theme={null}
statements:read_payment
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/payments/overview

Payments represent actual transfers of rewards to the payout address associated with a given statement.

Payments are made on-chain to a specified payout address. Payments tie 1:1 with a statement amount.

Key Features

* Use the `ref_id` to link payments to statements
* Payments are made on-chain to specified payout addresses
* One-to-one relationship between payments and statement amounts

Additional Notes

> Some fields (e.g., `account_id`, `profile_id`) are populated for consistency but are not relevant to reward-specific flows.

Availability

These endpoints are only relevant for Global Dollar Network (GDN) partners.

List Historical Prices
Source: https://docs.paxos.com/api-reference/endpoints/pricing/list-historical-prices

get /markets/{market}/historical-prices
Retrieves a set of average prices at a certain increment of time for the requested market. This endpoint is suitable for retrieving historical average price trends where price precision, execution, and
other detailed information is not required.
To control the count, use either `increment` or `max_data_points`.
List Historical Prices returns an error when an unexpected value is given, or when `increment` and
`max_data_points` are both given or omitted.

When `range.begin` is omitted, the first data point shows the mid price, the average of the order book best bid
and ask price, or the earliest available date. It is possible to set `range.begin` to a future date without error.

When `range.end` is omitted, the last data point will display current mid price (average of order book best bid
and best ask) at the request timestamp. It is possible to set `range.end` to a future date without error.

When `pagination.limit` is omitted, the pagination limit will default to return the first 100 items.
If the pagination limit is set, the API will return up to the limit in one response. The pagination limit max is 1,000.

Time-series items are returned in chronological (ascending) order. All timestamps are in UTC.

```bash OAuth Scope theme={null}
exchange:historical_prices
```

List Prices
Source: https://docs.paxos.com/api-reference/endpoints/pricing/list-prices

get /all-markets/prices
Retrieve current prices, as well as 24 hour prior (yesterday) prices, for the specified markets.
Any single market that failed to be retrieved is excluded from the response.

List Tickers
Source: https://docs.paxos.com/api-reference/endpoints/pricing/list-tickers

get /all-markets/ticker
Retrieves order book statistics of the exchange for all markets over the last 24 hours and from midnight UTC until current time.

Please note: List Tickers displays pricing from external venues when the itBit exchange is not available.

Overview
Source: https://docs.paxos.com/api-reference/endpoints/pricing/overview

Pricing provides historical data related to charting of asset prices.

Note: Some Pricing API markets may be unavailable for trading.

Create Profile
Source: https://docs.paxos.com/api-reference/endpoints/profiles/create-profile

post /profiles
Create a new profile for this account. Profiles created using this endpoint always have a type of `NORMAL`.

```bash OAuth Scope theme={null}
funding:write_profile
```

Deactivate Profile
Source: https://docs.paxos.com/api-reference/endpoints/profiles/deactivate-profile

put /profiles/{profile_id}/deactivate
Deactivate the given `profile_id`. The default profile cannot be deactivated.
Deactivated profiles won't be visible for deposits.
Profiles with more than zero balances cannot be deactivated.
If a deactivated profile has a non-zero balance it will be reactivated.

```bash OAuth Scope theme={null}
funding:write_profile
```

Get Profile
Source: https://docs.paxos.com/api-reference/endpoints/profiles/get-profile

get /profiles/{profile_id}
Read a single profile by its UUID, or read the default profile using the alias "default".

```bash OAuth Scope theme={null}
funding:read_profile
```

Get Profile Balance
Source: https://docs.paxos.com/api-reference/endpoints/profiles/get-profile-balance

get /profiles/{profile_id}/balances/{asset}
Get the balance of `asset` in a profile.

```bash OAuth Scope theme={null}
funding:read_profile
```

List Profile Balances
Source: https://docs.paxos.com/api-reference/endpoints/profiles/list-profile-balances

get /profiles/{profile_id}/balances
Retrieve the Profile’s available and trading balances.
Use query parameters to retrieve a defined set of assets.
Omit query parameters to retrieve all asset balances.

```bash OAuth Scope theme={null}
funding:read_profile
```

List Profiles
Source: https://docs.paxos.com/api-reference/endpoints/profiles/list-profiles

get /profiles
Return the associated Profiles for the current Account.
The paginated results default to the maximum limit of 1,000 Profiles, unless otherwise specified with the `limit` parameter.
Every paginated response contains a `next_page` field until the last page is reached.
Pass the `next_page` value into the `page_cursor` field of the next request to retrieve the next page of results.

```bash OAuth Scope theme={null}
funding:read_profile
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/profiles/overview

Profiles hold asset balances, and every Paxos transaction is on a particular profile.

Depending on your integration type, Profiles may be used to reflect both corporate balances or individual user balances.

Profile Types

There are two types of Profiles:

* **`DEFAULT`** Profiles are system-generated.
* **`NORMAL`** Profiles are created using the [Create Profile](/api-reference/endpoints/profiles/create-profile) endpoint and are the only type of Profile you can create.

Update Profile
Source: https://docs.paxos.com/api-reference/endpoints/profiles/update-profile

put /profiles/{profile_id}
Change the `nickname` label for the given `profile_id` (Profile).

```bash OAuth Scope theme={null}
funding:write_profile
```

Create Quote Execution
Source: https://docs.paxos.com/api-reference/endpoints/quote-executions/create-quote-execution

post /profiles/{profile_id}/quote-executions
Execute on a quote for buying or selling an asset.

The side, market, and guaranteed price of the execution are specified by the quote with ID `quote_id`.

The amount to buy or sell must be specified in either fiat or crypto by setting exactly one of:
- `base_amount` to specify the amount of crypto to buy or sell.
- `quote_amount` to specify the amount of fiat to spend or acquire.

An otherwise-valid request to create a quote execution may fail with the following types of errors:
- [Expired](https://developer.paxos.com/docs/v2/problems/expired) if the quote with ID `quote_id` has expired.
- [Insufficient Funds](https://developer.paxos.com/docs/v2/problems/insufficient-funds) if the profile with ID `profile_id` has insufficient available balance to fund the execution.
- [Rejected](https://developer.paxos.com/docs/v2/problems/rejected) if extreme market conditions (e.g. a very large price swing) have invalidated the quote.
- [Already Exists](https://developer.paxos.com/docs/v2/problems/already-exists) if a Quote Execution with the same `ref_id` has already been created.

```bash OAuth Scope theme={null}
exchange:write_quote_execution
```

Get Quote Execution
Source: https://docs.paxos.com/api-reference/endpoints/quote-executions/get-quote-execution

get /profiles/{profile_id}/quote-executions/{id}
Get an existing quote execution for buying or selling an asset.

```bash OAuth Scope theme={null}
exchange:read_quote_execution
```

List Quote Executions
Source: https://docs.paxos.com/api-reference/endpoints/quote-executions/list-quote-executions

get /profiles/{profile_id}/quote-executions
List quote executions within a particular profile.

```bash OAuth Scope theme={null}
exchange:read_quote_execution
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/quote-executions/overview

Quote Executions buy or sell assets using a Quote obtained from the Quotes flow.

You can obtain a Quote using the [Quotes](/api-reference/endpoints/quotes/overview) flow.

List Quotes
Source: https://docs.paxos.com/api-reference/endpoints/quotes/list-quotes

get /quotes
List quotes for buying or selling assets. By default, the list will include the latest available quotes for both buying and selling all supported assets.

Each quote is valid until `expires_at`, and can be executed on by
calling [Create Quote Execution](#operation/CreateQuoteExecution).

Multiple calls to list quotes in quick succession may return the same quote
values. Paxos currently issues new quotes at most once per second.

```bash OAuth Scope theme={null}
exchange:read_quote
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/quotes/overview

Quotes are 'held rates' offered by Paxos to buy or sell assets at a specific price within a
period of time.

For example, the option to buy BTC within the next 30 seconds for \$8,000.

Typical Quotes Workflow

The typical Quotes workflow is as follows:

1. Call [List Quotes](/api-reference/endpoints/quotes/list-quotes) to get the latest
available
   quoted prices for the assets you want to buy or sell.
2. Present the offered price to one or more end-users, with a timer
   indicating the time to expiration.
3. If a user accepts the price, call [Create Quote Execution](/api-
reference/endpoints/quote-executions/create-quote-execution) with the amount to buy or sell.
4. Call [Get Quote Execution](/api-reference/endpoints/quote-executions/get-quote-execution)
to monitor
   for completion and know when the funds from the execution are available.

Important Considerations

It's important to show end-users the latest available price. If you cache
prices to show them to multiple users, you should refresh the cache once
per second.

You can call [List Quote Executions](/api-reference/endpoints/quote-executions/list-quote-
executions) to
review or construct reports on quote execution activity.

Create Sandbox Deposit
Source: https://docs.paxos.com/api-reference/endpoints/sandbox-deposits/create-sandbox-
deposit

post /sandbox/profiles/{profile_id}/deposit
Create a test deposit to fund a profile in the sandbox environment.

Always specify `crypto_network` when making a crypto sandbox deposit. Omit the parameter
when depositing fiat.

This functionality is only available in the sandbox environment.

```bash OAuth Scope theme={null}
funding:read_profile
```

Initiate Sandbox Fiat Deposit
Source: https://docs.paxos.com/api-reference/endpoints/sandbox-fiat-transfers/initiate-
sandbox-fiat-deposit

post /sandbox/fiat-deposits
Initiate a test fiat deposit in the sandbox environment.

The deposit will be processed based on `memo_id` from a previous Fiat Deposit Instructions response.

This functionality is only available in the sandbox environment.

```bash OAuth Scope theme={null}
transfer:write_sandbox_fiat_deposit
```

Sandbox Set Identity Status
Source: https://docs.paxos.com/api-reference/endpoints/sandbox-identity/sandbox-set-identity-status

put /identity/identities/{id}/sandbox-status
Set the various statuses for the given Identity. To enable the Person Identity to transact, set both `id_verification_status` and `sanctions_verification_status` to `"APPROVED"`.
To enable the Institution to transact, set both `sanctions_verification_status` to `"APPROVED"`.
This endpoint also allows you to set the statuses for `document_verification_status` and `additional_screening_status`

```bash OAuth Scope theme={null}
identity:write_identity
```

Affirm Transaction
Source: https://docs.paxos.com/api-reference/endpoints/settlement/affirm-transaction

put /settlement/transactions/{transaction_id}/affirm
Affirms the Settlement Transaction for settlement, the transaction is now eligible for settlement once the current time is
between the provided `settlement_window_start` and `settlement_window_end`. This action can only be done by the
customer owning the target profile (`target_profile_id`).
The transaction must be in a `"PENDING"` status for this to take effect.

```bash OAuth Scope theme={null}
settlement:write_transaction
```

Cancel Transaction
Source: https://docs.paxos.com/api-reference/endpoints/settlement/cancel-transaction

delete /settlement/transactions/{transaction_id}
Cancels the Settlement Transaction, this action can only be done by the customer owning the source profile (`source_profile_id`).
The transaction must be in a `"PENDING"` status for this to take effect, you cannot cancel a transaction which
is `"AFFIRMED"`.

```bash OAuth Scope theme={null}
settlement:write_transaction
```

Create Transaction
Source: https://docs.paxos.com/api-reference/endpoints/settlement/create-transaction

post /settlement/transactions
Creates a new bilateral Settlement Transaction with one or more legs. The customer must own the
`source_profile_id` specified in the transaction.

A successful response indicates the transaction has been accepted and will be in an initial `status` of `"PENDING"`
for settlement, the transaction is only eligible for settlement once the `status` is `"AFFIRMED"` by the
`target_profile_id` and the current time is between the provided `settlement_window_start` and `settlement_window_end`.

Settlement will only be enacted once both `source_profile_id` and `target_profile_id` have sufficient balances to
fulfill all legs specified as settlement is **atomic**.

```bash OAuth Scope theme={null}
settlement:write_transaction
```

Get Transaction
Source: https://docs.paxos.com/api-reference/endpoints/settlement/get-transaction

get /settlement/transactions/{transaction_id}
Get a Settlement Transaction by its (transaction) id, you must have created the transaction (own the `source_profile_id`) or
have had the transaction alleged against you (own the `target_profile_id`).

```bash OAuth Scope theme={null}
settlement:read_transaction
```

List Transactions
Source: https://docs.paxos.com/api-reference/endpoints/settlement/list-transactions

get /settlement/transactions
This endpoint enables you to fetch a list of Settlement Transactions that you have created (own the `source_profile_id`) or have been alleged against you (own the `target_profile_id`).
You can use query parameters to filter the results returned by `statuses`, `source_profile_id` and `target_profile_id`.

Note that this endpoint supports pagination and returns a cursor token for fetching next pages.

```bash OAuth Scope theme={null}
settlement:read_transaction
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/settlement/overview

Use the Settlements API to facilitate simultaneous exchange of pre-funded assets.

Use the Settlements API to facilitate simultaneous exchange of pre-funded assets. Automate a variety of use cases that require two-party approval, including net settlement of over-the-counter trades, withdrawal requests for tri-party collateral, payment requests, and bilateral settlement for marketplace end users.

Workflow

The simple request-and-approval workflow supports both one-directional and bidirectional

transactions to allow a user to receive an asset (for example, send USDP) or simultaneously send and receive assets (for example, send USD and receive BTC and ETH). Only when all parties are in agreement and assets are fully funded does the Settlements API allow for change of custody. Upon completion, all settled assets are immediately available for trading, transferring, withdrawal or other supported activities.

Transaction Direction

The Source Profile initiates the transaction for the Target Profile to approve. The `DIRECTION` of each asset is always relative to the Source Profile and only the owner of the Source Profile can cancel a transaction if it hasn't been approved by the Target Profile.

Learn More

Learn more about the Settlement APIs in the [Settlement Developer Guide](/guides/settlements).

Cancel Stablecoin Conversion
Source: https://docs.paxos.com/api-reference/endpoints/stablecoin-conversion/cancel-stablecoin-conversion

delete /conversion/stablecoins/{id}
Cancel a single conversion using the `id` from the [Create Stablecoin Conversion](#operation/CreateStablecoinConversion) response.

```bash OAuth Scope theme={null}
conversion:write_conversion_stablecoin
```

Create Stablecoin Conversion
Source: https://docs.paxos.com/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion

post /conversion/stablecoins
Create a Conversion request to exchange assets 1:1.

A request to create a conversion can fail with one of the following types of errors:
- [Insufficient Funds](https://developer.paxos.com/docs/v2/problems/insufficient-funds) if the Profile (`profile_id`) has insufficient available balance to fund the execution.
- [Already Exists](https://developer.paxos.com/docs/v2/problems/already-exists) if a conversion with the same external ID (`ref_id`) has already been created.

```bash OAuth Scope theme={null}
conversion:write_conversion_stablecoin
```

Get Stablecoin Conversion
Source: https://docs.paxos.com/api-reference/endpoints/stablecoin-conversion/get-stablecoin-conversion

get /conversion/stablecoins/{id}
Retrieve a single conversion using the transaction `id` from the [Create Stablecoin Conversion](#operation/CreateStablecoinConversion) response.

```bash OAuth Scope theme={null}
conversion:read_conversion_stablecoin
```

List Stablecoin Conversions

Source: https://docs.paxos.com/api-reference/endpoints/stablecoin-conversion/list-stablecoin-conversions

get /conversion/stablecoins
List all conversions, optionally filtering and paging the results.

By default, conversions are returned in reverse chronological (descending) order by creation time. If no query parameters are supplied, the response will include up to the last 100 conversions which were created.

The paginated results default to display up to 100 conversions, unless otherwise specified with the `limit` parameter. The maximum `limit` value is 1000. Every paginated response contains a `next_page_cursor` field until the last page is reached.

Pass the `next_page_cursor` value into the `page_cursor` field of a new request to retrieve the next page of results.

```bash OAuth Scope theme={null}
conversion:read_conversion_stablecoin
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/stablecoin-conversion/overview

Convert between fiat and stablecoin using the Stablecoin Conversion API.

Convert between fiat and stablecoin using [Create Stablecoin Conversion](/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion) and check the status of a [single conversion](/api-reference/endpoints/stablecoin-conversion/get-stablecoin-conversion) or retrieve a [list of conversions](/api-reference/endpoints/stablecoin-conversion/list-stablecoin-conversions).

<Warning title="Stablecoin Conversions Deprecation Notice">
  The Stablecoin Conversions API will be deprecated.

  Paxos will migrate all active conversion rules to the Orchestrations API format by December 2025.

  Customers should transition to the Orchestrations API to ensure continuity of service.
</Warning>

Learn More

Learn more about stablecoin conversions in the [Convert Developer Guide](/guides/developer/convert).

List Statements
Source: https://docs.paxos.com/api-reference/endpoints/statements/list-statements

get /statements
List statements based on the provided filters

```bash OAuth Scope theme={null}
statements:read_statement
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/statements/overview

A Statement summarizes all eligible stablecoin rewards for a given organization over a fixed time period.

It aggregates earned reward types (e.g., custody, mint, acceptance) and records whether the statement was paid.

Key Features

* Statements are generated monthly and are immutable
* Revised statements will be issued as a new statement with a unique ID
* Statements can be used to reconcile balances or for accounting and accounts receivable purposes

Availability

These endpoints are only relevant for Global Dollar Network (GDN) partners.

List Tax Form Revisions
Source: https://docs.paxos.com/api-reference/endpoints/tax-forms/list-tax-form-revisions

get /tax/tax-form-revisions
Used for more granular file retrieval for specific accounts that require updated tax forms.
Lists all versions of a tax form for single account and tax year. Revisions will increment up as new tax forms are issued for the same account, tax year, and form type pairing. The highest value revision is the most recent.
Tax Form URL links will expire after 60 seconds.
Supported form types: 1099-B, 1099-MISC, and 1099-DA. If form_types is not provided, defaults to 1099-B for tax years prior to 2025, and 1099-DA from 2025 onwards.

```bash OAuth Scope theme={null}
tax:read_tax_form
```

List Tax Forms
Source: https://docs.paxos.com/api-reference/endpoints/tax-forms/list-tax-forms

get /tax/tax-forms
Used for bulk file transfer use cases.
List tax forms for given account ids and tax year. The most recent revision number will be returned (revisions increment up; highest value revision for a specific account, tax year, and form type pairing is the most recent).
Tax Form URL links will expire after 60 seconds.
Please call ListTaxFormRevisions endpoint for all versions of a single accounts tax forms.
Supported form types: 1099-B, 1099-MISC, and 1099-DA. If form_types is not provided, defaults to 1099-B for tax years prior to 2025, and 1099-DA from 2025 onwards.

```bash OAuth Scope theme={null}
tax:read_tax_form
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/tax-forms/overview

All tax forms are associated to a single account_id.

An account_id can have multiple tax forms associated with it.

US 1099-B and 1099-Misc tax forms for the previous fiscal year will be available in February of the current calendar year.
Previous years tax forms are also available by request.

Get Transfer
Source: https://docs.paxos.com/api-reference/endpoints/transfers/get-transfer

get /transfer/transfers/{id}
Get a single transfer by ID.

In the polling workflow, this endpoint can be called to monitor transfer status changes.

```bash OAuth Scope theme={null}
transfer:read_transfer
```

List Transfers
Source: https://docs.paxos.com/api-reference/endpoints/transfers/list-transfers

get /transfer/transfers
List all transfers, optionally filtering and paging the results.

By default, transfers are returned in reverse chronological (descending) order by creation time.

The recommended polling workflow is to query the results in ascending order (by setting `order_by` to `CREATED_AT`), keeping track of the `created_at` timestamp of the most recent transfer in the paged results. Once transfers are discovered, the caller should store the returned `ID` and query GetTransfer to retrieve status updates.

```bash OAuth Scope theme={null}
transfer:read_transfer
```

Overview
Source: https://docs.paxos.com/api-reference/endpoints/transfers/overview

Each deposit to and withdrawal from a Paxos account is a Transfer.

A Transfer is associated with a particular Profile, and increases or decreases the available balance of a single asset in that Profile.

identity_documents_required
Source: https://docs.paxos.com/api-reference/events/identity-documents-required-object

Event object returned for identity.documents_required events

This object is returned by the [Get Event API](/api-reference/endpoints/events/get-event) when the event type is `identity.documents_required`.

Object Fields

<ResponseField name="id" type="string">
  Unique identifier for this event object
</ResponseField>

<ResponseField name="identity_id" type="string">
  Identifier for the identity requiring documents
</ResponseField>

<ResponseField name="required_documents" type="array">
  List of required document types
</ResponseField>

<ResponseExample>
  ```json Example theme={null}
  ```

```
    {
      "id": "d840cf31-352f-4190-a476-7522bf3eafda",
      "identity_id": "4fd025ab-f29f-47e6-a02e-df90a61c7ec9",
      "required_documents": ["DRIVERS_LICENSE", "PASSPORT"]
    }
    ```
  </ResponseExample>

  # identity_kyc_refresh
  Source: https://docs.paxos.com/api-reference/events/identity-kyc-refresh-object

  Event object returned for KYC refresh events

  This object is returned by the [Get Event API](/api-reference/endpoints/events/get-event)
  when the event type is `identity.kyc_refresh.started`, `identity.kyc_refresh.completed`, or
  `identity.kyc_refresh.expired`.

  ## Object Fields

  <ResponseField name="id" type="string">
    Unique identifier for this event object
  </ResponseField>

  <ResponseField name="identity_id" type="string">
    Identifier for the affected identity
  </ResponseField>

  <ResponseField name="last_kyc_refresh_date" type="string">
    Date of the most recent completed KYC refresh
  </ResponseField>

  <ResponseField name="next_kyc_refresh_date" type="string">
    Scheduled date for the next KYC refresh
  </ResponseField>

  <ResponseExample>
    ```json Example theme={null}
    {
      "id": "d840cf31-352f-4190-a476-7522bf3eafda",
      "identity_id": "4fd025ab-f29f-47e6-a02e-df90a61c7ec9",
      "last_kyc_refresh_date": "2024-07-15T10:30:00Z",
      "next_kyc_refresh_date": "2024-08-25T14:25:41Z"
    }
    ```
  </ResponseExample>

  # identity_summary_status_change
  Source: https://docs.paxos.com/api-reference/events/identity-summary-status-change-object

  Event object returned for identity status change events

  This object is returned by the [Get Event API](/api-reference/endpoints/events/get-event)
  when the event type is `identity.approved`, `identity.denied`, or `identity.disabled`.

  ## Object Fields

  <ResponseField name="id" type="string">
    Unique identifier for this event object
  </ResponseField>

  <ResponseField name="identity_id" type="string">
    Identifier for the affected identity
  </ResponseField>
```
```

<ResponseField name="old_summary_status" type="string">
  The previous summary status of the identity

  Available options: `PENDING`, `ERROR`, `APPROVED`, `DENIED`, `DISABLED`
</ResponseField>

<ResponseField name="new_summary_status" type="string">
  The new summary status of the identity

  Available options: `PENDING`, `ERROR`, `APPROVED`, `DENIED`, `DISABLED`
</ResponseField>

<ResponseExample>
  ```json Example theme={null}
  {
    "id": "d840cf31-352f-4190-a476-7522bf3eafda",
    "identity_id": "4fd025ab-f29f-47e6-a02e-df90a61c7ec9",
    "old_summary_status": "PENDING",
    "new_summary_status": "APPROVED"
  }
  ```
</ResponseExample>

orchestration_status_change
Source: https://docs.paxos.com/api-reference/events/orchestration-status-change-object

Event object returned for orchestration status change events

This object is returned by the [Get Event API](/api-reference/endpoints/events/get-event) when the event type is `orchestration.processing`, `orchestration.completed`, or `orchestration.failed`.

Object Fields

<ResponseField name="id" type="string">
  The Paxos orchestration ID. You can call the GetOrchestration endpoint with this ID to get more details about it.
</ResponseField>

<ResponseField name="ref_id" type="string">
  The client-specified ID of the orchestration for replay protection and lookup.
</ResponseField>

<ResponseField name="status" type="string">
  Status of the orchestration:

  Available options: `PROCESSING`, `COMPLETED`, `FAILED`
</ResponseField>

<ResponseField name="orchestration_rule_id" type="string">
  The ID of the orchestration rule that triggered this orchestration. This field will not be present for ad-hoc orchestrations. (optional)
</ResponseField>

<ResponseExample>
  ```json Rule-triggered Orchestration theme={null}
  {
    "id": "ee1a802f-7557-4c59-b833-9a1ef29630d5",
    "orchestration_rule_id": "86d3929f-0090-45e5-8195-dbcf63c43eec",
    "ref_id": "orchestration_id.ee1a802f-7557-4c59-b833-9a1ef29630d5",
    "status": "COMPLETED"
  }
  ```

```
  ```json Ad-hoc Orchestration theme={null}
  {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "ref_id": "my-orchestration-123",
    "status": "PROCESSING"
  }
  ```
</ResponseExample>

transfer_status_change
Source: https://docs.paxos.com/api-reference/events/transfer-status-change-object

Event object returned for transfer status change events

This object is returned by the [Get Event API](/api-reference/endpoints/events/get-event)
when the event type is related to transfer status changes.

Object Fields

<ResponseField name="id" type="string">
  The Paxos transfer ID. You can call the GetTransfer endpoint with this ID to get more
details about it.
</ResponseField>

<ResponseField name="type" type="string">
  Type of transfer:

  Available options: `CRYPTO_DEPOSIT`, `CRYPTO_WITHDRAWAL`, `ACT_DEPOSIT`,
`ACT_WITHDRAWAL`
</ResponseField>

<ResponseField name="status" type="string">
  Status of transfer:

  Available options: `PENDING`, `COMPLETED`, `FAILED`
</ResponseField>

<ResponseField name="profile_id" type="string">
  The Profile ID associated with the transfer
</ResponseField>

<ResponseField name="ref_id" type="string">
  The client-specified ID of the transfer for replay protection and lookup. (optional)
</ResponseField>

<ResponseField name="crypto_network" type="string">
  Cryptocurrency network (e.g. ETHEREUM, BASE, SOLANA) (optional, present for crypto
transfers)
</ResponseField>

<ResponseField name="crypto_tx_hash" type="string">
  On-chain transaction hash (optional, present for crypto transfers when available)
</ResponseField>

<ResponseField name="crypto_tx_index" type="string">
  The output index or output address (optional, present for crypto transfers when available)
</ResponseField>

<ResponseField name="memo" type="string">
  Memo associated with the transfer as an identifier (optional, present for fiat transfers
when available)
</ResponseField>
```

<ResponseExample>
```json Crypto Deposit Example theme={null}
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": "CRYPTO_DEPOSIT",
  "status": "COMPLETED",
  "profile_id": "e8c16069-8b01-4119-8ee0-08842e33b551",
  "ref_id": "my-deposit-123",
  "crypto_network": "ETHEREUM",
  "crypto_tx_hash": "0x1234567890abcdef...",
  "crypto_tx_index": "0"
}
```

```json Fiat Withdrawal Example theme={null}
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "type": "ACT_WITHDRAWAL",
  "status": "PENDING",
  "profile_id": "e8c16069-8b01-4119-8ee0-08842e33b551",
  "ref_id": "my-withdrawal-456",
  "memo": "Payment for services"
}
```
</ResponseExample>

Paxos API
Source: https://docs.paxos.com/api-reference/introduction

Welcome to Paxos APIs. At Paxos, our mission is to enable the movement of any asset, any time, in a trustworthy way.

These APIs serve that mission by making it easier than ever for you to directly integrate our product capabilities into your application, leveraging the speed, stability, and security of the Paxos platform.

The documentation that follows gives you access to our Crypto Brokerage, Trading, and Exchange products. It includes APIs for market data, orders, and the held rate quote flow.

<PreviewButton href="https://developer.paxos.com/docs/paxos-v2.openapi.json">Open the REST API Specification</PreviewButton>

To test in our sandbox environment, [sign up](https://account.sandbox.paxos.com) for an account. For more information about Paxos and our APIs, visit [Paxos.com](https://www.paxos.com/).

Getting Started

<CardGroup>
  <Card title="Authentication" icon="key" href="/guides/developer/credentials">
    Learn how to authenticate with Paxos APIs using OAuth 2.0
  </Card>

  <Card title="Sandbox Environment" icon="flask" href="https://account.sandbox.paxos.com">
    Test Paxos APIs in the sandbox environment
  </Card>
</CardGroup>

API Environments

Paxos provides two environments for API integration:

* **Production**: `https://api.paxos.com/v2`
* **Sandbox**: `https://api.sandbox.paxos.com/v2`

Authentication

Paxos APIs use OAuth 2 with the client credentials grant flow. Learn more in the [API credentials guide](/guides/developer/credentials).

Rate Limits

API endpoints have rate limits to ensure system stability. Rate limit information is provided in response headers.

Support

For more information about Paxos and the APIs, visit [Paxos.com](https://www.paxos.com/) or contact Paxos support for assistance.

409 - Rejected
Source: https://docs.paxos.com/api-reference/problems/already-exists

An Already Exists error is returned on operations which violate an at-most-once or uniqueness constraint.

For example, an Already Exists error will be returned if:

* Create Order is called with an already-used `ref_id`
* Create Profile is called with an already-existing profile nickname
* Accept Quote is called on a quote which has already been accepted

An Already Exists error has the following "meta" fields:

* `existing`: The existing record which is the subject of the conflict (for example, the existing order with the same `ref_id`)

An Already Exists error may be benign if the client is retrying an earlier attempted operation which the client believes may have failed.

However, if the request is not a retry, then resolving the error requires changing the request to avoid the conflict.

<CodeGroup>
```json Example theme={null}
{
  "detail": "nickname already exists",
  "meta": {
    "existing": {
      "id": "b7b77d82-e6a7-4ae9-9904-36231aedf985",
      "nickname": "existing nickname"
    }
  },
  "status": 409,
  "title": "Already Exists",
  "type": "https://developer.paxos.com/docs/v2/problems/already-exists"
}
```
</CodeGroup>

403 - Expired
Source: https://docs.paxos.com/api-reference/problems/expired

An Expired error is returned in response to operations acting on some resource that has expired.

For example, attempting to accept a time-limited quote after the quote has expired results in an Expired error.

An Expired error has the following "meta" fields:

* `expired_at`: The time at which the resource expired.

An expired resource will not become unexpired. The `expired_at` data is informational, for display to the end-user to give more informative feedback on why their request could not be completed.

<CodeGroup>
```json Example theme={null}
{
  "detail": "offer expired at 0001-01-01T00:00:00Z",
  "meta": {
    "expired_at": "0001-01-01T00:00:00Z"
  },
  "status": 403,
  "title": "Expired",
  "type": "https://developer.paxos.com/docs/v2/problems/expired"
}
```
</CodeGroup>

403 - Insufficient Funds
Source: https://docs.paxos.com/api-reference/problems/insufficient-funds

An Insufficient Funds error is returned on operations which require funding when the needed funds are not present in the profile funding the transaction.

For example, creating an order to buy \$100 of BTC will result in an Insufficient Funds error if the profile has an available balance less than \$100.

An Insufficient Funds error has the following "meta" fields:

* `profile_id`: The ID of the profile funding the transaction.
* `asset`: The asset needed to fund the transaction.
* `available`: The amount of the needed asset in the profile's current available balance.
* `needed`: The amount of the needed asset required to fund the transaction.

To resolve an Insufficient Funds error, assets of the needed kind should be transferred to the profile identified.

<CodeGroup>
```json Example theme={null}
{
  "detail": "insufficient USD funds in profile b7b77d82-e6a7-4ae9-9904-36231aedf985: 50 needed, 100 available",
  "meta": {
    "asset": "USD",
    "available": "50",
    "needed": "100",
    "profile_id": "b7b77d82-e6a7-4ae9-9904-36231aedf985"
  },
  "status": 403,
  "title": "Insufficient Funds",
  "type": "https://developer.paxos.com/docs/v2/problems/insufficient-funds"
}
```

```
  ```
</CodeGroup>

403 - Rejected
Source: https://docs.paxos.com/api-reference/problems/rejected

A rejected error can occur if extreme market conditions lead to a quote being invalidated.

In this case, a new quote most be issued to the user.

<CodeGroup>
  ```json Example theme={null}
  {
    "detail": "extreme market conditions have invalidated this quote execution",
    "meta": {},
    "status": 403,
    "title": "Rejected",
    "type": "https://developer.paxos.com/docs/v2/problems/rejected"
  }
  ```
</CodeGroup>

identity.approved
Source: https://docs.paxos.com/api-reference/webhooks/identity-approved

api-reference/webhooks/webhooks-openapi.json webhook identity.approved
Webhook triggered when an identity verification is approved

Triggered when identity verification is successfully approved.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`identity_summary_status_change`](/api-
reference/events/identity-summary-status-change-object#identity-summary-status-change)
object with status transition details.

identity.denied
Source: https://docs.paxos.com/api-reference/webhooks/identity-denied

api-reference/webhooks/webhooks-openapi.json webhook identity.denied
Webhook triggered when an identity verification is denied

Triggered when identity verification is denied.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`identity_summary_status_change`](/api-
reference/events/identity-summary-status-change-object#identity-summary-status-change)
object with status transition details.
```
```

identity.disabled
Source: https://docs.paxos.com/api-reference/webhooks/identity-disabled

api-reference/webhooks/webhooks-openapi.json webhook identity.disabled
Webhook triggered when an identity is disabled

Triggered when a previously approved identity is disabled.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`identity_summary_status_change`](/api-reference/events/identity-summary-status-change-object#identity-summary-status-change) object with status transition details.

identity.documents_required
Source: https://docs.paxos.com/api-reference/webhooks/identity-documents-required

api-reference/webhooks/webhooks-openapi.json webhook identity.documents_required
Webhook triggered when additional documents are required for identity verification

Triggered when additional documents are required for identity verification.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details including required documents.
</Note>

Event Object Structure

The Get Event API returns an [`identity_documents_required`](/api-reference/events/identity-documents-required-object) object with details about the required documents.

identity.kyc_refresh.completed
Source: https://docs.paxos.com/api-reference/webhooks/identity-kyc-refresh-completed

api-reference/webhooks/webhooks-openapi.json webhook identity.kyc_refresh.completed
Webhook triggered when a KYC refresh process is successfully completed

Triggered when a KYC refresh process is successfully completed.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`identity_kyc_refresh`](/api-reference/events/identity-kyc-refresh-object) object with KYC refresh details including the completion date.

identity.kyc_refresh.expired
Source: https://docs.paxos.com/api-reference/webhooks/identity-kyc-refresh-expired

api-reference/webhooks/webhooks-openapi.json webhook identity.kyc_refresh.expired
Webhook triggered when a KYC refresh process expires without completion

Triggered when a KYC refresh process expires without completion.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`identity_kyc_refresh`](/api-reference/events/identity-kyc-refresh-object) object with KYC refresh details including the expiration date.

identity.kyc_refresh.started
Source: https://docs.paxos.com/api-reference/webhooks/identity-kyc-refresh-started

api-reference/webhooks/webhooks-openapi.json webhook identity.kyc_refresh.started
Webhook triggered when a KYC refresh process is initiated

Triggered when a KYC refresh process is initiated for an existing verified identity.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details including due date.
</Note>

Event Object Structure

The Get Event API returns an [`identity_kyc_refresh`](/api-reference/events/identity-kyc-refresh-object) object with KYC refresh details including the due date.

orchestration.completed
Source: https://docs.paxos.com/api-reference/webhooks/orchestration-completed

api-reference/webhooks/webhooks-openapi.json webhook orchestration.completed
Webhook triggered when an orchestration completes successfully

Triggered when an orchestration is COMPLETED and all transfers have been successfully executed.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`orchestration_status_change`](/api-reference/events/orchestration-status-change-object) object with orchestration status details.

orchestration.failed
Source: https://docs.paxos.com/api-reference/webhooks/orchestration-failed

api-reference/webhooks/webhooks-openapi.json webhook orchestration.failed
Webhook triggered when an orchestration fails

Triggered when an orchestration has FAILED and could not be completed.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-

reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`orchestration_status_change`](/api-reference/events/orchestration-status-change-object) object with orchestration status details.

orchestration.processing
Source: https://docs.paxos.com/api-reference/webhooks/orchestration-processing

api-reference/webhooks/webhooks-openapi.json webhook orchestration.processing
Webhook triggered when an orchestration enters processing status

Triggered when an orchestration enters PROCESSING status and begins execution.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns an [`orchestration_status_change`](/api-reference/events/orchestration-status-change-object) object with orchestration status details.

transfer.act_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-act-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.act_deposit.completed
Webhook triggered when a fiat deposit via DBS is completed and funds are available

Triggered when a fiat deposit via DBS is COMPLETED and funds are available on platform.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.act_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-act-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.act_deposit.failed
Webhook triggered when a fiat deposit via DBS has failed or been cancelled

Triggered when a fiat deposit via DBS has FAILED or been cancelled.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-

status-change-object) object with transfer status details.

transfer.act_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-act-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.act_deposit.pending
Webhook triggered when a fiat deposit via DBS has been initiated and is pending

Triggered when a fiat deposit via DBS has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.act_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-act-withdrawal-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.act_withdrawal.completed
Webhook triggered when a fiat withdrawal via DBS is completed and sent to destination

Triggered when a fiat withdrawal via DBS is COMPLETED and has been sent to the destination account.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.act_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-act-withdrawal-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.act_withdrawal.failed
Webhook triggered when a fiat withdrawal via DBS has failed or been cancelled

Triggered when a fiat withdrawal via DBS has FAILED or been cancelled.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.act_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-act-withdrawal-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.act_withdrawal.pending

Webhook triggered when a fiat withdrawal via DBS has been initiated and is pending

Triggered when a fiat withdrawal via DBS has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.banking_circle_intrabank_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-banking-circle-intrabank-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook
transfer.banking_circle_intrabank_deposit.completed
Webhook triggered when a Banking Circle intrabank deposit has completed

Triggered when a Banking Circle intrabank deposit has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.banking_circle_intrabank_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-banking-circle-intrabank-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook
transfer.banking_circle_intrabank_deposit.failed
Webhook triggered when a Banking Circle intrabank deposit has failed

Triggered when a Banking Circle intrabank deposit has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.banking_circle_intrabank_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-banking-circle-intrabank-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook
transfer.banking_circle_intrabank_deposit.pending
Webhook triggered when a Banking Circle intrabank deposit has been initiated and is pending

Triggered when a Banking Circle intrabank deposit has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.banking_circle_intrabank_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-banking-circle-intrabank-withdrawal-completed

api-reference/webhooks/webhooks-openapi.json webhook
transfer.banking_circle_intrabank_withdrawal.completed
Webhook triggered when a Banking Circle intrabank withdrawal has completed

Triggered when a Banking Circle intrabank withdrawal has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.banking_circle_intrabank_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-banking-circle-intrabank-withdrawal-failed

api-reference/webhooks/webhooks-openapi.json webhook
transfer.banking_circle_intrabank_withdrawal.failed
Webhook triggered when a Banking Circle intrabank withdrawal has failed

Triggered when a Banking Circle intrabank withdrawal has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.banking_circle_intrabank_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-banking-circle-intrabank-withdrawal-pending

api-reference/webhooks/webhooks-openapi.json webhook
transfer.banking_circle_intrabank_withdrawal.pending
Webhook triggered when a Banking Circle intrabank withdrawal has been initiated and is pending

Triggered when a Banking Circle intrabank withdrawal has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.bny_intrabank_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-bny-intrabank-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.bny_intrabank_deposit.completed
Webhook triggered when a BNY intrabank deposit has completed

Triggered when a BNY intrabank deposit has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.bny_intrabank_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-bny-intrabank-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.bny_intrabank_deposit.failed
Webhook triggered when a BNY intrabank deposit has failed

Triggered when a BNY intrabank deposit has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.bny_intrabank_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-bny-intrabank-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.bny_intrabank_deposit.pending
Webhook triggered when a BNY intrabank deposit has been initiated and is pending

Triggered when a BNY intrabank deposit has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.

```
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.bny_intrabank_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-bny-intrabank-withdrawal-
completed

api-reference/webhooks/webhooks-openapi.json webhook
transfer.bny_intrabank_withdrawal.completed
Webhook triggered when a BNY intrabank withdrawal has completed

Triggered when a BNY intrabank withdrawal has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.bny_intrabank_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-bny-intrabank-withdrawal-
failed

api-reference/webhooks/webhooks-openapi.json webhook
transfer.bny_intrabank_withdrawal.failed
Webhook triggered when a BNY intrabank withdrawal has failed

Triggered when a BNY intrabank withdrawal has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.bny_intrabank_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-bny-intrabank-withdrawal-
pending

api-reference/webhooks/webhooks-openapi.json webhook
transfer.bny_intrabank_withdrawal.pending
Webhook triggered when a BNY intrabank withdrawal has been initiated and is pending

Triggered when a BNY intrabank withdrawal has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>
```

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.crypto_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-crypto-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.crypto_deposit.completed
Webhook triggered when a crypto deposit is completed and funds are available

Triggered when a crypto deposit is COMPLETED and funds are available on platform.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.crypto_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-crypto-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.crypto_deposit.failed
Webhook triggered when a crypto deposit has failed or been cancelled

Triggered when a crypto deposit has FAILED or been cancelled.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.crypto_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-crypto-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.crypto_deposit.pending
Webhook triggered when a crypto deposit is detected on-chain and is pending confirmation

Triggered when a crypto deposit is detected on-chain and is PENDING confirmation.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.crypto_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-crypto-withdrawal-completed

```
api-reference/webhooks/webhooks-openapi.json webhook transfer.crypto_withdrawal.completed
Webhook triggered when a crypto withdrawal is completed and sent to destination

Triggered when a crypto withdrawal is COMPLETED and has been sent to the destination
address.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.crypto_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-crypto-withdrawal-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.crypto_withdrawal.failed
Webhook triggered when a crypto withdrawal has failed or been cancelled

Triggered when a crypto withdrawal has FAILED or been cancelled.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.crypto_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-crypto-withdrawal-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.crypto_withdrawal.pending
Webhook triggered when a crypto withdrawal has been initiated and is pending

Triggered when a crypto withdrawal has been initiated and is PENDING on-chain processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.cubix_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-cubix-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.cubix_deposit.completed
Webhook triggered when a Cubix deposit has completed

Triggered when a Cubix deposit has COMPLETED processing.

<Note>
```

```
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.cubix_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-cubix-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.cubix_deposit.failed
Webhook triggered when a Cubix deposit has failed

Triggered when a Cubix deposit has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.cubix_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-cubix-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.cubix_deposit.pending
Webhook triggered when a Cubix deposit has been initiated and is pending

Triggered when a Cubix deposit has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.cubix_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-cubix-withdrawal-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.cubix_withdrawal.completed
Webhook triggered when a Cubix withdrawal has completed

Triggered when a Cubix withdrawal has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.
```

transfer.cubix_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-cubix-withdrawal-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.cubix_withdrawal.failed
Webhook triggered when a Cubix withdrawal has failed

Triggered when a Cubix withdrawal has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.cubix_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-cubix-withdrawal-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.cubix_withdrawal.pending
Webhook triggered when a Cubix withdrawal has been initiated and is pending

Triggered when a Cubix withdrawal has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.rtp_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-rtp-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.rtp_deposit.completed
Webhook triggered when an RTP deposit has completed

Triggered when an RTP deposit has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.rtp_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-rtp-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.rtp_deposit.failed
Webhook triggered when an RTP deposit has failed

Triggered when an RTP deposit has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.rtp_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-rtp-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.rtp_deposit.pending
Webhook triggered when an RTP deposit has been initiated and is pending

Triggered when an RTP deposit has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.scb_intrabank_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-scb-intrabank-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.scb_intrabank_deposit.completed
Webhook triggered when an SCB intrabank deposit has completed

Triggered when an SCB intrabank deposit has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.scb_intrabank_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-scb-intrabank-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.scb_intrabank_deposit.failed
Webhook triggered when an SCB intrabank deposit has failed

Triggered when an SCB intrabank deposit has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.scb_intrabank_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-scb-intrabank-deposit-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.scb_intrabank_deposit.pending
Webhook triggered when an SCB intrabank deposit has been initiated and is pending

Triggered when an SCB intrabank deposit has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.scb_intrabank_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-scb-intrabank-withdrawal-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.scb_intrabank_withdrawal.completed
Webhook triggered when an SCB intrabank withdrawal has completed

Triggered when an SCB intrabank withdrawal has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.scb_intrabank_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-scb-intrabank-withdrawal-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.scb_intrabank_withdrawal.failed
Webhook triggered when an SCB intrabank withdrawal has failed

Triggered when an SCB intrabank withdrawal has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-

status-change-object) object with transfer status details.

transfer.scb_intrabank_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-scb-intrabank-withdrawal-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.scb_intrabank_withdrawal.pending
Webhook triggered when an SCB intrabank withdrawal has been initiated and is pending

Triggered when an SCB intrabank withdrawal has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.wire_deposit.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-wire-deposit-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.wire_deposit.completed
Webhook triggered when a wire deposit has completed

Triggered when a wire deposit has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.wire_deposit.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-wire-deposit-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.wire_deposit.failed
Webhook triggered when a wire deposit has failed

Triggered when a wire deposit has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

transfer.wire_deposit.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-wire-deposit-pending

```
api-reference/webhooks/webhooks-openapi.json webhook transfer.wire_deposit.pending
Webhook triggered when a wire deposit has been initiated and is pending

Triggered when a wire deposit has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.wire_withdrawal.completed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-wire-withdrawal-completed

api-reference/webhooks/webhooks-openapi.json webhook transfer.wire_withdrawal.completed
Webhook triggered when a wire withdrawal has completed

Triggered when a wire withdrawal has COMPLETED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.wire_withdrawal.failed
Source: https://docs.paxos.com/api-reference/webhooks/transfer-wire-withdrawal-failed

api-reference/webhooks/webhooks-openapi.json webhook transfer.wire_withdrawal.failed
Webhook triggered when a wire withdrawal has failed

Triggered when a wire withdrawal has FAILED processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
</Note>

## Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-
status-change-object) object with transfer status details.


# transfer.wire_withdrawal.pending
Source: https://docs.paxos.com/api-reference/webhooks/transfer-wire-withdrawal-pending

api-reference/webhooks/webhooks-openapi.json webhook transfer.wire_withdrawal.pending
Webhook triggered when a wire withdrawal has been initiated and is pending

Triggered when a wire withdrawal has been initiated and is PENDING processing.

<Note>
  Webhook payloads contain only event metadata. Use the [Get Event API](/api-
reference/endpoints/events/get-event) with the event ID to retrieve full details.
```

</Note>

Event Object Structure

The Get Event API returns a [`transfer_status_change`](/api-reference/events/transfer-status-change-object) object with transfer status details.

Execution Data
Source: https://docs.paxos.com/api-reference/websockets/execution-data

Execution Data (Market)
Source: https://docs.paxos.com/api-reference/websockets/execution-data-market

Market Data
Source: https://docs.paxos.com/api-reference/websockets/market-data

Market Data (Market)
Source: https://docs.paxos.com/api-reference/websockets/market-data-market

Market Data (Stablecoin)
Source: https://docs.paxos.com/api-reference/websockets/market-data-stablecoin

Market Data (Stablecoin Market)
Source: https://docs.paxos.com/api-reference/websockets/market-data-stablecoin-market

Order Routing Execution Data
Source: https://docs.paxos.com/api-reference/websockets/order-routing-execution-data

Real-time trade execution information for Order Routing platform.

The Execution Data channel provides real-time trade execution information for authorized Order Routing customers. Subscribe to receive notifications as trades execute on the platform.

Subscribe to Execution Data

Request

```json theme={null}
{
```

```
  "type": "subscribe",
  "channels": [
    {
      "type": "execution_data",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "execution_data",
      "params": { "market": "BTCUSD" },
      "success": true
    }
  ]
}
```

The response echoes back the request parameters, allowing you to correlate responses when subscribing to multiple channels.

Error Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "execution_data",
      "params": { "market": "BADBAD" },
      "success": false,
      "error": "UNKNOWN_CHANNEL_PARAMS_CONFIGURATION"
    }
  ]
}
```

Execution Message Format

Each trade execution generates a message with the following format:

```json theme={null}
{
  "channel": "execution_data",
  "payload": {
    "market": "BTCUSD",
    "price": "50000.00",
    "amount": "0.5",
    "executed_at": "2024-01-15T10:30:00.123456789Z"
  }
}
```

Message Fields

| Field | Type | Description |

```
| ------------- | ------ | ----------------------------------- |
| `market`      | string | The market pair (e.g., "BTCUSD")    |
| `price`       | string | Execution price as a decimal string |
| `amount`      | string | Executed amount as a decimal string |
| `executed_at` | string | Timestamp in RFC3339Nano format     |

## Multiple Market Subscriptions

Subscribe to multiple markets simultaneously:

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "execution_data",
      "params": {
        "market": "BTCUSD"
      }
    },
    {
      "type": "execution_data",
      "params": {
        "market": "ETHUSD"
      }
    }
  ]
}
```

Processing Execution Data

Real-time Updates

* Messages are sent immediately when trades execute
* No messages during idle periods with no trading activity
* All executions are delivered in chronological order

Example Implementation

```javascript theme={null}
class ExecutionMonitor {
  constructor() {
    this.executions = [];
    this.volumeByMarket = new Map();
  }

  handleExecution(message) {
    const execution = message.payload;

    // Store execution
    this.executions.push(execution);

    // Update volume tracking
    const currentVolume = this.volumeByMarket.get(execution.market) || 0;
    const executionVolume = parseFloat(execution.price) * parseFloat(execution.amount);
    this.volumeByMarket.set(execution.market, currentVolume + executionVolume);

    // Process execution
    this.processExecution(execution);
  }

  processExecution(execution) {
    console.log(`Trade executed in ${execution.market}:`,
      `${execution.amount} @ ${execution.price}`,
```
```

```
        `at ${execution.executed_at}`);

      // Your custom logic here
      // - Update charts
      // - Trigger alerts
      // - Calculate metrics
    }

    getRecentExecutions(market, count = 10) {
      return this.executions
        .filter(e => e.market === market)
        .slice(-count);
    }

    getTotalVolume(market) {
      return this.volumeByMarket.get(market) || 0;
    }
  }
```

Unsubscribe

To stop receiving execution data:

```json theme={null}
{
  "type": "unsubscribe",
  "channels": [
    {
      "type": "execution_data",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

List Active Subscriptions

Get all active execution data subscriptions:

```json theme={null}
{
  "type": "subscription_list"
}
```

Response

```json theme={null}
{
  "type": "subscription_list",
  "channels": [
    {
      "type": "execution_data",
      "params": {
        "market": "BTCUSD"
      }
    },
    {
      "type": "execution_data",
      "params": {
        "market": "ETHUSD"
      }
```

```
      }
    ]
  }
```

> Questions? Contact [Support](https://support.paxos.com).

Order Routing Heartbeat
Source: https://docs.paxos.com/api-reference/websockets/order-routing-heartbeat

Logical-level liveness signal for Order Routing platform.

The Heartbeat channel provides a logical-level liveness signal for authorized Order Routing customers. Subscribe to receive periodic heartbeat messages to monitor the health of your WebSocket connection and the server's responsiveness.

Subscribe to Heartbeat

Request

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "heartbeat"
    }
  ]
}
```

> The heartbeat channel does not require parameters.

Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "heartbeat",
      "success": true
    }
  ]
}
```

Error Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "heartbeat",
      "success": false,
      "error": "UNKNOWN_CHANNEL"
    }
  ]
}
```

Heartbeat Message Format

The server sends periodic heartbeat messages after you subscribe:

```json theme={null}
{
  "channel": "heartbeat",
  "payload": {
    "timestamp": "2024-01-15T10:30:00.123456789Z"
  }
}
```

Message Fields

Field	Type	Description
`timestamp`	string	Server timestamp in RFC3339Nano format

Unsubscribe

To stop receiving heartbeat messages:

```json theme={null}
{
  "type": "unsubscribe",
  "channels": [
    {
      "type": "heartbeat"
    }
  ]
}
```

List Active Subscriptions

Get all active subscriptions including heartbeat:

```json theme={null}
{
  "type": "subscription_list"
}
```

Response

```json theme={null}
{
  "type": "subscription_list",
  "channels": [
    {
      "type": "heartbeat"
    },
    {
      "type": "market_data",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

Heartbeat vs WebSocket Ping/Pong

The heartbeat channel operates at the application layer, while WebSocket ping/pong operates at the protocol layer:

* **WebSocket Ping/Pong**: Automatic transport-layer keepalive handled by the WebSocket protocol
* **Heartbeat Channel**: Application-layer liveness signal providing server timestamp and logical health status

Use heartbeat messages to verify that the server is not only connected but also actively processing and responding to your connection at the application level.

> Questions? Contact [Support](https://support.paxos.com).

Order Routing Market Data
Source: https://docs.paxos.com/api-reference/websockets/order-routing-market-data

Real-time order book updates for Order Routing platform.

The Market Data channel provides real-time order book updates for authorized Order Routing customers. Subscribe to receive full order book snapshots followed by incremental updates.

Subscribe to Market Data

Request

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data",
      "params": { "market": "BTCUSD" },
      "success": true
    }
  ]
}
```

The response echoes back the request parameters, allowing you to correlate responses when subscribing to multiple channels.

Error Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data",
      "params": { "market": "BADBAD" },
```

```
        "success": false,
        "error": "UNKNOWN_CHANNEL_PARAMS_CONFIGURATION"
      }
    ]
  }
```

Message Types

SNAPSHOT Message

The initial message after subscription contains the full order book state:

```json theme={null}
{
  "channel": "market_data",
  "payload": {
    "market": "BTCUSD",
    "type": "SNAPSHOT",
    "time": "2024-01-15T10:30:00.123456789Z",
    "bids": [
      {
        "price": "50000.00",
        "amount": "1.5"
      },
      {
        "price": "49999.50",
        "amount": "2.0"
      }
    ],
    "asks": [
      {
        "price": "50100.00",
        "amount": "2.0"
      },
      {
        "price": "50101.00",
        "amount": "1.5"
      }
    ]
  }
}
```

UPDATE Message

Incremental changes to the order book:

```json theme={null}
{
  "channel": "market_data",
  "payload": {
    "market": "BTCUSD",
    "type": "UPDATE",
    "time": "2024-01-15T10:30:01.456789012Z",
    "bids": [
      {
        "price": "50000.00",
        "amount": "0"
      }
    ],
    "asks": [
      {
        "price": "50100.50",
        "amount": "3.5"
```

```
        }
      ]
    }
  }
```

Processing Updates

Update Rules

* When `amount = 0`: Remove the price level from the order book
* When `amount > 0`: Add or update the price level with the new amount
* Bids are sorted in descending price order
* Asks are sorted in ascending price order

Snapshot Synchronization

The API uses timestamp-based synchronization to ensure order book consistency:

❶ Initial Subscription

Upon subscribing, you immediately receive UPDATE messages with timestamps while the server prepares the SNAPSHOT.

❷ Buffer Updates

Buffer all received UPDATE messages until the SNAPSHOT arrives.

❸ Process Snapshot

When the SNAPSHOT arrives with timestamp T:

* Build the order book from the SNAPSHOT
* Apply buffered UPDATEs where `UPDATE.time > SNAPSHOT.time`
* Discard UPDATEs where `UPDATE.time <= SNAPSHOT.time`

❹ Continue Processing

Apply subsequent UPDATE messages incrementally to maintain the order book.

> A SNAPSHOT message is sent exactly once after subscribing to a channel.

Example Implementation

```javascript theme={null}
class OrderBook {
  constructor() {
    this.bids = new Map();
    this.asks = new Map();
    this.updateBuffer = [];
    this.snapshotTime = null;
  }

  handleMessage(message) {
    if (message.payload.type === 'SNAPSHOT') {
      this.processSnapshot(message.payload);
    } else if (message.payload.type === 'UPDATE') {
      if (!this.snapshotTime) {
        // Buffer updates until snapshot arrives
        this.updateBuffer.push(message.payload);
      } else {
        this.processUpdate(message.payload);
      }
    }
  }
```

```
  processSnapshot(snapshot) {
    // Clear and rebuild order book
    this.bids.clear();
    this.asks.clear();
    this.snapshotTime = snapshot.time;

    // Load snapshot data
    snapshot.bids.forEach(level => {
      this.bids.set(level.price, level.amount);
    });
    snapshot.asks.forEach(level => {
      this.asks.set(level.price, level.amount);
    });

    // Apply buffered updates after snapshot time
    this.updateBuffer
      .filter(update => update.time > this.snapshotTime)
      .forEach(update => this.processUpdate(update));

    this.updateBuffer = [];
  }

  processUpdate(update) {
    // Process bid updates
    if (update.bids) {
      update.bids.forEach(level => {
        if (level.amount === "0") {
          this.bids.delete(level.price);
        } else {
          this.bids.set(level.price, level.amount);
        }
      });
    }

    // Process ask updates
    if (update.asks) {
      update.asks.forEach(level => {
        if (level.amount === "0") {
          this.asks.delete(level.price);
        } else {
          this.asks.set(level.price, level.amount);
        }
      });
    }
  }
}
```

Unsubscribe

To stop receiving market data updates:

```json theme={null}
{
  "type": "unsubscribe",
  "channels": [
    {
      "type": "market_data",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

```
```

> Questions? Contact [Support](https://support.paxos.com).

Order Routing WebSocket API
Source: https://docs.paxos.com/api-reference/websockets/order-routing-overview

Authenticated real-time market data for Order Routing platform customers.

The Order Routing WebSocket API provides authenticated, real-time streaming market data and execution data to authorized Order Routing platform customers. This API uses a bidirectional WebSocket connection for both request-response operations and streaming data delivery.

> This API is available only to Order Routing customers on the allow list. For public market data access or DMA (Direct Market Access) to itBit, use the [public WebSocket API](/api-reference/websockets/overview).

Connection

Endpoints

Production: `wss://ws.paxos.com/`\
Sandbox: `wss://ws.sandbox.paxos.com/`

Authentication

Authentication is performed during the WebSocket handshake. You must provide valid OAuth2 credentials in the Authorization Bearer header.

> You must include the `exchange:read_aggregated_marketdata_stream` scope. Without this scope, the WebSocket route responds with `403 Forbidden`.

❶ Get OAuth2 Credentials

Request an access token using your client credentials:

Sandbox

```bash theme={null}
curl -X POST https://oauth.sandbox.paxos.com/oauth2/token \
  -H "Content-Type: application/x-www-form-urlencoded" \
  -d "grant_type=client_credentials" \
  -d "client_id={your_client_id}" \
  -d "client_secret={your_client_secret}" \
  -d "scope=exchange:read_aggregated_marketdata_stream"
```

Production

```bash theme={null}
curl -X POST https://oauth.paxos.com/oauth2/token \
  -H "Content-Type: application/x-www-form-urlencoded" \
  -d "grant_type=client_credentials" \
  -d "client_id={your_client_id}" \
  -d "client_secret={your_client_secret}" \
  -d "scope=exchange:read_aggregated_marketdata_stream"
```

Response

```json theme={null}
{
  "access_token": "{your_bearer_token}",
  "expires_in": 3600,
```

```
  "token_type": "bearer",
  "scope": "exchange:read_aggregated_marketdata_stream"
}
```

❷ Establish WebSocket Connection

Use the access token as the Bearer token when establishing the WebSocket connection:

```javascript theme={null}
const ws = new WebSocket('wss://ws.sandbox.paxos.com/', {
  headers: {
    'Authorization': 'Bearer {your_bearer_token}'
  }
});
```

Connection Lifecycle

1. Client establishes WebSocket connection with authentication
2. Server maintains connection with automatic ping/pong heartbeat
3. Client subscribes/unsubscribes to data channels (e.g., BTCUSD market data)
4. Server streams data to subscribed channels
5. Connection closes on client disconnect or server shutdown

Quick Start Example

Here's a minimal example to get you started:

```javascript theme={null}
// 1. Connect with authentication
const ws = new WebSocket('wss://ws.sandbox.paxos.com/', {
  headers: { 'Authorization': 'Bearer {your_token}' }
});

// 2. Subscribe to market data on connection
ws.on('open', () => {
  ws.send(JSON.stringify({
    type: 'subscribe',
    channels: [{
      type: 'market_data',
      params: { market: 'BTCUSD' }
    }]
  }));
});

// 3. Handle incoming messages
ws.on('message', (data) => {
  const msg = JSON.parse(data);

  if (msg.type === 'subscribe') {
    console.log('Subscription confirmed:', msg.channels[0].success);
  } else if (msg.channel === 'market_data') {
    console.log('Market data:', msg.payload);
  }
});
```

Operations & Message Formats

Subscribe Operation

Subscribe to one or more data channels for real-time updates.

Request:

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data",
      "params": {
        "market": "BTCUSD"
      }
    },
    {
      "type": "execution_data",
      "params": {
        "market": "ETHUSD"
      }
    }
  ]
}
```

Response:

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data",
      "params": { "market": "BTCUSD" },
      "success": true
    },
    {
      "type": "execution_data",
      "params": { "market": "ETHUSD" },
      "success": true
    }
  ]
}
```

The response echoes back the request parameters for each channel, allowing you to correlate which subscription succeeded or failed when subscribing to multiple channels in a single request.

Unsubscribe Operation

Stop receiving updates from specific channels.

Request:

```json theme={null}
{
  "type": "unsubscribe",
  "channels": [
    {
      "type": "market_data",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

Response:

```json theme={null}
{
  "type": "unsubscribe",
  "channels": [
    {
      "type": "market_data",
      "params": { "market": "BTCUSD" },
      "success": true
    }
  ]
}
```

The response echoes back the request parameters for each channel, allowing you to correlate which unsubscription succeeded or failed when unsubscribing from multiple channels in a single request.

List Subscriptions Operation

Get all active subscriptions for your connection.

Request:

```json theme={null}
{
  "type": "subscription_list"
}
```

Response:

```json theme={null}
{
  "type": "subscription_list",
  "channels": [
    {
      "type": "market_data",
      "params": {
        "market": "BTCUSD"
      }
    },
    {
      "type": "execution_data",
      "params": {
        "market": "ETHUSD"
      }
    }
  ]
}
```

Data Channels

The Order Routing WebSocket API supports four types of streaming data channels:

Market Data Channel

Provides real-time order book updates with initial snapshots and incremental changes.

* **Channel type:** `market_data`
* **Initial message:** Full order book snapshot
* **Subsequent messages:** Incremental updates
* **[View detailed documentation →](/api-reference/websockets/order-routing-market-data)**

Example streaming message:

```json theme={null}
{
  "channel": "market_data",
  "payload": {
    "market": "BTCUSD",
    "type": "UPDATE",
    "time": "2024-01-15T10:30:01.456Z",
    "bids": [{"price": "50000.00", "amount": "1.5"}],
    "asks": [{"price": "50100.00", "amount": "2.0"}]
  }
}
```

Top of Book Channel

Provides real-time updates of the best bid and best ask prices only.

* **Channel type:** `market_data.top_of_book`
* **Message frequency:** On best price changes
* **Lightweight alternative to full order book**
* **[View detailed documentation →](/api-reference/websockets/order-routing-top-of-book)**

Example streaming message:

```json theme={null}
{
  "channel": "market_data.top_of_book",
  "payload": {
    "market": "BTCUSD",
    "type": "TOP_OF_BOOK",
    "timestamp": "2024-01-15T10:30:00.123456789Z",
    "bids": [{"price": "50000.00", "amount": "1.5"}],
    "asks": [{"price": "50100.00", "amount": "2.0"}]
  }
}
```

Execution Data Channel

Provides real-time trade execution notifications.

* **Channel type:** `execution_data`
* **Message frequency:** On each trade execution
* **[View detailed documentation →](/api-reference/websockets/order-routing-execution-data)**

Example streaming message:

```json theme={null}
{
  "channel": "execution_data",
  "payload": {
    "market": "BTCUSD",
    "price": "50000.00",
    "amount": "0.5",
    "executed_at": "2024-01-15T10:30:00.123Z"
  }
}
```

Heartbeat Channel

Provides logical-level liveness signal for connection monitoring.

* **Channel type:** `heartbeat`
* **Message frequency:** Periodic heartbeat messages
* **No parameters required**
* **[View detailed documentation →](/api-reference/websockets/order-routing-heartbeat)**

Example streaming message:

```json theme={null}
{
  "channel": "heartbeat",
  "payload": {
    "timestamp": "2024-01-15T10:30:00.123456789Z"
  }
}
```

Error Handling

The API uses standardized error codes:

Error Code	Description
`UNKNOWN_ACTION`	The requested action type is not recognized
`INTERNAL_SERVER_ERROR`	An unexpected server error occurred
`MALFORMED_REQUEST`	The request JSON is invalid or cannot be parsed
`NO_EFFECT_ACTION`	The action would have no effect (e.g., duplicate subscription)
`UNKNOWN_CHANNEL`	The requested channel type is not recognized
`UNKNOWN_CHANNEL_PARAMS_CONFIGURATION`	Invalid or missing channel parameters

> Questions? Contact [Support](https://support.paxos.com).

Order Routing Top of Book
Source: https://docs.paxos.com/api-reference/websockets/order-routing-top-of-book

Real-time best bid and ask updates for Order Routing platform.

The Top of Book channel provides real-time updates of the best bid and best ask prices for authorized Order Routing customers. This lightweight channel is ideal when you only need the best available prices without the full order book depth.

Subscribe to Top of Book

Request

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data.top_of_book",
      "params": {
        "market": "BTCUSD"
      }
    }
```

```
  ]
}
```

Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data.top_of_book",
      "params": { "market": "BTCUSD" },
      "success": true
    }
  ]
}
```

The response echoes back the request parameters, allowing you to correlate responses when subscribing to multiple channels.

Error Response

```json theme={null}
{
  "type": "subscribe",
  "channels": [
    {
      "type": "market_data.top_of_book",
      "params": { "market": "BADBAD" },
      "success": false,
      "error": "UNKNOWN_CHANNEL_PARAMS_CONFIGURATION"
    }
  ]
}
```

Top of Book Message Format

Real-time updates of the best bid and ask prices:

```json theme={null}
{
  "channel": "market_data.top_of_book",
  "payload": {
    "market": "BTCUSD",
    "type": "TOP_OF_BOOK",
    "timestamp": "2024-01-15T10:30:00.123456789Z",
    "bids": [
      {
        "price": "50000.00",
        "amount": "1.5"
      }
    ],
    "asks": [
      {
        "price": "50100.00",
        "amount": "2.0"
      }
    ]
  }
}
```

Message Fields

Field	Type	Description
`market`	string	The market pair (e.g., "BTCUSD")
`type`	string	Always `"TOP_OF_BOOK"` for this channel
`timestamp`	string	Server timestamp in RFC3339Nano format
`bids`	array	Array with best bid price and amount
`asks`	array	Array with best ask price and amount

Price Level Fields

Field	Type	Description
`price`	string	Price level as a decimal string
`amount`	string	Available amount at this price level as a decimal string

Unsubscribe

To stop receiving top of book updates:

```json theme={null}
{
  "type": "unsubscribe",
  "channels": [
    {
      "type": "market_data.top_of_book",
      "params": {
        "market": "BTCUSD"
      }
    }
  ]
}
```

List Active Subscriptions

Get all active subscriptions including top of book:

```json theme={null}
{
  "type": "subscription_list"
}
```

Response

```json theme={null}
{
  "type": "subscription_list",
  "channels": [
    {
      "type": "market_data.top_of_book",
      "params": {
        "market": "BTCUSD"
      }
    },
    {
      "type": "market_data",
      "params": {
        "market": "ETHUSD"
      }
    }
  ]
}
```

```
> Questions? Contact [Support](https://support.paxos.com).


# Overview
Source: https://docs.paxos.com/api-reference/websockets/overview

Event-driven connectivity for payments and trading.

## WebSocket API Options

Paxos offers two WebSocket API solutions for different use cases:

### Public WebSocket API

Open access to real-time market and execution data feeds via public [WebSocket]
(https://websocket.spec.whatwg.org) connections. Ideal for DMA (Direct Market Access) to
itBit and general market data consumption. No authentication required.

### Order Routing WebSocket API

Authenticated, bidirectional WebSocket API exclusively for Order Routing platform customers.
Provides request-response operations and streaming data with OAuth2 authentication. [Learn
more](/api-reference/websockets/order-routing-overview).

> Order Routing customers should use the authenticated [Order Routing WebSocket API](/api-
reference/websockets/order-routing-overview) for enhanced functionality and authorized
access.

## Public WebSocket API

The public WebSocket API offers three main data feeds:

* **[Execution Data Feed](#execution-data-feed)** - Real-time execution data for market
trades
* **[Market Data Feed](#market-data-feed)** - Order book updates with initial snapshots and
real-time updates
* **[Stablecoin Market Price Feed](#stablecoin-feed)** - Market index price updates for
external stablecoins

> See the Websocket [trading](/guides/crypto-brokerage/websocket) guide for a hands-on
introduction.

The WebSocket connections provide a number of advantages when compared to the [v2 API](/api-
reference), including real-time event notifications, minimized data transfers over the
network and reduced latency when compared to a polling strategy.

## API Reference

For detailed technical specifications, message schemas, and interactive examples, see the
**API Reference** section in the sidebar. The AsyncAPI specification provides complete
documentation for all available channels, message types, and data formats.

## Connection Details

Once a secure (`wss://`) connection is established, each feed begins streaming data, subject
to the [rate limits](/guides/developer/rate-limits#websocket-limits).
Both Production and Sandbox data feeds have a built-in, instantaneous failover.
Clients should have a reconnection mechanism in case of server disconnection.

### Server Endpoints

**Production:** `wss://ws.paxos.com`\
**Sandbox:** `wss://ws.sandbox.paxos.com`
```

Available Channels

* `/executiondata` - All markets execution data
* `/executiondata/{market}` - Single market execution data
* `/marketdata` - All markets order book data
* `/marketdata/{market}` - Single market order book data
* `/marketdata/stablecoin/{market}` - Stablecoin market price data

> See the **API Reference** section for detailed channel specifications and message formats.

Execution Data Feed

The execution data feed provides real-time trade information for market executions. Key behavioral characteristics:

* **Initial Message**: The first message corresponds to the last execution at connection time
* **Subsequent Messages**: Each new message represents a new execution as it occurs
* **Idle Markets**: If no executions occur for extended periods, no messages are sent until new activity
* **Reconnection**: Upon reconnection, you receive the last execution (handle duplicates using `match_number`)

The feed includes execution price, amount, timestamp, and a unique match number for deduplication.

Market Data Feed

The market data feed provides real-time order book updates with two message types:

SNAPSHOT Messages

* **Initial Response**: Shows the complete order book state with bids and asks
* **Bids**: Prices in descending order with amounts
* **Asks**: Prices in ascending order with amounts

UPDATE Messages

* **Real-time Updates**: Show executed trades and order book changes
* **Processing Rules**:
  * When `amount=0`: Remove the price level from the order book
  * When `amount>0`: Add or update the price level with the new amount
  * Use `side` field to determine whether to update bids (`BUY`) or asks (`SELL`)

Available Markets

Market availability varies by environment (Sandbox vs Production) and account restrictions. Use the [Get Order Book](/api-reference/endpoints/market-data/get-order-book) and [List Recent Executions](/api-reference/endpoints/market-data/list-recent-executions) REST endpoints to discover available markets, though these are not suitable for streaming data.

Stablecoin Market Price Feed

The stablecoin market price feed provides real-time market index price updates for external stablecoins. Key characteristics:

* **Current Support**: USDCUSD market
* **Update Frequency**: Typically \~1 message per second, varying with market volatility
* **Message Content**: Market name, current price (4 decimals), and timestamp
* **Real-time Updates**: Price updates are pushed as they occur

This feed is particularly useful for applications requiring accurate, real-time stablecoin pricing information.

Commissions and Rebates FAQ
Source: https://docs.paxos.com/guides/crypto-brokerage/commissions-rebates

Get answers to common questions about commissions and rebates.

What's the difference between a commission and a rebate?

Commissions are charged by Paxos and debited from the user account. Rebates are credits from Paxos to the user account.

In what currency are commissions and rebates charged or credited?

Commissions and rebates are charged or credited in the quote currency.

When do you credit rebates or debit commissions?

Rebates are credited and commissions are debited when the order is executed.

When selling, do you need additional funds to cover the commission?

No. The commissions is subtracted from the proceeds of the sale.

FIX Best Practices
Source: https://docs.paxos.com/guides/crypto-brokerage/fix/best-practices

Learn about connection management, sequence number management and testing.

Paxos recommends following FIX industry best practices, in addition to the items outlined below.

Identity Mapping

Use the following table to map Paxos identify information to the corresponding FIX tag.

Paxos Identity	FIX Tag
Customer ID	Account (1)
Profile ID	ClientID (109)

Sequence Number Management

Periodically disconnecting the FIX connection.
Resetting the message sequence number promotes a stable trading environment for all users.
Paxos forces a disconnect and reset of sequence numbers weekly for all sessions.

The exact time when the disconnect and reset to sequence numbers happen is discussed during the onboarding process.
Clients must configure their FIX engines to expect a disconnect and sequence number reset at the agreed schedule, failure to do so will result in an invalid FIX session due to mismatching sequence numbers.

Schedule times follow the US Eastern Time Zone (ET), an area five hours behind Greenwich Mean Time (GMT-5) during the winter months (referred to as Eastern Standard Time or EST) and four hours behind Greenwich Mean Time (GMT-4) during the summer months (referred to as Eastern Daylight Time or EDT).

<Tip>
  Paxos Support may contact you regarding connection practices to prevent performance degradation.
</Tip>

Cancel on Disconnect

Cancel on Disconnect is enabled by default.
When a disconnection occurs, the service automatically submits a cancel request for all open orders.

Use Multiple connections

FIX supports multiple connections per trading account.
Please submit a request to support@paxos.com to request additional connections.

Implementation Testing

Test the FIX implementation by following the [FIX certification process](/guides/crypto-brokerage/fix/certify) in the Sandbox environment prior to going live in Production.

FIX Certification
Source: https://docs.paxos.com/guides/crypto-brokerage/fix/certify

Test and verify the FIX implementation in Sandbox before going to Production.

Paxos recommends testing the FIX implementation by running through the following test cases. These tests cover the most common scenarios when trading on the Paxos Platform: submitting orders for valid and invalid markets, order types, order execution and canceling orders.

<Tip>
  If you have any questions or run into issues, contact support@paxos.com for assistance.
</Tip>

SYM1: Symbology - Valid Market

User submits order for each of the markets which the user expects to trade and processes corresponding confirmation response.

SYM2: Symbology - Invalid Market

User submits order for invalid market symbol (for example, `XXXXXX`) and processes the corresponding reject response.

LIM1: Buy Limit (Buy 1.1 @ Limit \$200 XBTUSD)

User submits limit buy order for valid quantity, price and market, and the processes corresponding confirmation response.

LIM2: Sell Limit (Sell 0.001 @ Limit \$200 XBTUSD)

User submits limit sell order for valid quantity, price and market, and the processes corresponding confirmation response.

EX1: Single Execution - Fill

User submits marketable limit order (limit price will be immediately executed, either partially or completely) and processes the corresponding confirmation and fill responses.

CXL1: Cancel New

User submits a limit outside of current market price (so the order will not execute), processes the corresponding confirmation response, and then issues a cancel request and processes the corresponding cancel confirmation.

CXL2: Cancel Reject

User attempts to cancel an invalid or non-existent order ID, or an order which has been previously completely filled, and processes the corresponding cancel reject response.

OPT1: Cancel on Disconnect (Optional)

User submits multiple orders with the limit outside of current market price (so the orders will not execute), processes the corresponding confirmation responses and then disconnects their FIX session to verify all open orders are canceled.

OPT2: Status Request (Optional)

User submits a status request for a previously submitted order and processes the corresponding status response.

Next Steps

Read the FIX [best practices](/guides/crypto-brokerage/fix/best-practices) guide.

Overview
Source: https://docs.paxos.com/guides/crypto-brokerage/fix/index

Leverage the FIX protocol for crypto trading.

FIX (Financial Information eXchange) is an electronic messaging protocol widely adopted by financial institutions to transmit trading activity such as submitting or canceling orders and receiving execution information. The [FIX API](https://developer.paxos.com/docs/itbit/fix/) is based on FIX 4.2 and modeled after common Forex FIX implementations.

Get Started

<CardGroup>
  <Card title="Onboarding" href="/guides/crypto-brokerage/fix/onboard" icon="user-plus">
    Set Up a Paxos Account, configure connection then certify.
  </Card>

  <Card title="Certification" href="/guides/crypto-brokerage/fix/certify" icon="certificate">
    Test and verify the FIX implementation in Sandbox before going to Production.
  </Card>

  <Card title="Best Practices" href="/guides/crypto-brokerage/fix/best-practices" icon="lightbulb">
    Learn about connection management, sequence number management and testing.
  </Card>
</CardGroup>

FIX Onboarding
Source: https://docs.paxos.com/guides/crypto-brokerage/fix/onboard

Set Up a Paxos Account, configure connection then certify.

Set up and test a FIX connection in both the Sandbox and Production environments.
Connect to the Sandbox environment first for testing purposes.
Once the connection is working in Sandbox, follow a similar procedure for the Production connection.

<Tip>
  Learn more about [FIX Best Practices](/guides/crypto-brokerage/fix/best-practices), including how to use multiple connections and managing sequence number resets.
</Tip>

1. Set Up Paxos Account

To gain access, create a Paxos Account and Support will guide you through the process.

```
<Tabs>
  <Tab title="Sandbox">
    Go to [https://dashboard.sandbox.paxos.com](https://dashboard.sandbox.paxos.com) and
create an **Institution** Account in the Sandbox environment.

    Use an active email address when signing up: Paxos will send a verification email to the
address on file.
    Once the email is verified, complete the registration process.

    <Warning>
      When creating the Sandbox Account:

      * Do not submit documents.
      * Use placeholder (dummy) text for all text fields **except** for the email address.
    </Warning>
  </Tab>

  <Tab title="Production">
    Contact [support@paxos.com](mailto:support@paxos.com) before creating a Production
Account.
  </Tab>
</Tabs>

## 2. Generate a Certificate Signing Request (CSR)

<FixCSR />

## 3. Set Up SSL

<FixSSL />

Once complete, [test](/guides/crypto-brokerage/fix/certify) your connection to our servers.

Contact [support@paxos.com](mailto:support@paxos.com) with test results of for help with an
alternative to [stunnel](https://www.stunnel.org/).

## Next Steps

* Refer to this KB Article for troubleshooting issues with the FIX Connection configuration
- [Troubleshooting FIX mTLS connectivity configuration](https://support.paxos.com/hc/en-
us/articles/30477189764500).

* Test the FIX implementation in the Sandbox environment by running through the
[certification process](/guides/crypto-brokerage/fix/certify).

* Review the [FIX best practices](/guides/crypto-brokerage/fix/best-practices).

* Read the [FIX reference documentation](https://developer.paxos.com/docs/itbit/fix/).


# Overview
Source: https://docs.paxos.com/guides/crypto-brokerage/index

Add crypto to your application using REST, FIX and WebSocket APIs.

<Tabs>
  <Tab title="API">
    Get [market data](/api-reference/websockets/market-data), create [orders](/api-
reference/endpoints/orders), execute [held-rate quotes](/api-reference/endpoints/quotes),
and [transfer](/api-reference/endpoints/fiat-transfers) assets with [Paxos API v2.0](/api-
reference).
  </Tab>

  <Tab title="FIX">
```

```
    Leverage the [Paxos FIX API](https://developer.paxos.com/docs/itbit/fix/) to trade
crypto.

    Learn more about [FIX](/guides/crypto-brokerage/fix/index) and check out the
[onboarding](/guides/crypto-brokerage/fix/onboard) and [certification](/guides/crypto-
brokerage/fix/certify) guides to get started.
  </Tab>

  <Tab title="WebSocket">
    Construct the state of the order book and stream executed orders in real-time using the
[Paxos WebSocket API](/guides/developer/api-websocket).

    Learn more about what you can do with [WebSocket](/guides/developer/api-websocket) or
check out the [quickstart](/guides/crypto-brokerage/websocket) for a hands-on introduction.
  </Tab>
</Tabs>


# Choosing a Ledgering Strategy
Source: https://docs.paxos.com/guides/crypto-brokerage/ledger-type

Understand your options for ledgering fiat and cryptocurrency with Paxos.

Crypto Brokerage customers have several options for how they ledger customer funds with
Paxos.

<Tip>
  This document outlines common strategies for managing balances on Paxos. Each Crypto
Brokerage partner must use a strategy consistent with their business needs and Paxos's
licensing requirements.

  **Please contact [Support](https://support.paxos.com/hc/en-us) before choosing a strategy
and beginning your integration.**
</Tip>

### Fiat and Crypto Omnibus

In this integration type, the Crypto Brokerage Partner relies on their own ledger for end-
user’s fiat and crypto balances.
On the Paxos ledger there is one profile within the account where both fiat and crypto are
held on behalf of all of the end users.

This option is typically only available in 1st-Party integrations, where the Crypto
Brokerage Partner is relying exclusively on their own licensing and individual end users are
not Paxos customers.

### Fiat and Crypto Subledger

In this integration type, the Crypto Brokerage Partner creates a Profile to hold the fiat
and crypto balances for each individual user or account. This typically requires the use of
Paxos's Identity and/or Account services. The Crypto Brokerage Partner is responsible for
maintaining a mapping of individual user to their Paxos Profiles, Identities, and Accounts
and passing the appropriate IDs on each request.

This is the most common integration type for 3rd-Party integrations, where the Partner is
relying on Paxos's licensing and individual end users are Paxos customers.

### Fiat Omnibus and Crypto Subledger

Here, the Crypto Brokerage Partner relies on a single ledger for their fiat balances and
uses a unique Paxos Profile for each end-user’s crypto balances. On the Paxos ledger there
is one profile within the account where all fiat is held on behalf of all of the end users.

Crypto Brokerage Partners with Fiat Omnibus and Subledgered Crypto may leverage Directed
Settlement. In Directed Settlement, the Crypto Brokerage Partner specifies ("directs") which
```

subledgered profile should be credited or debited when a quote or trade is executed.

When buying crypto, fiat is debited from the omnibus profile and crypto is credited upon trade or quote execution. When selling crypto, crypto is debited from the specified end user Profile and fiat is credited to the omnibus profile.

Required Fields:

The table below outlines how to populate various fields for the Ledgering Strategies defined above. For more details please see our API reference Documentation for [Orders](/api-reference/endpoints/orders/create-order), [Transfers](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal) and [Quotes](/api-reference/endpoints/quote-executions/create-quote-execution).

API Parameters	Fiat Omnibus, Crypto Omnibus	Fiat Omnibus, Crypto Subledger (Directed Settlement)	Fiat and Crypto Subledger
`profile_id`	The Omnibus Profile ID	**Buy Orders:** Omnibus Profile ID **Sell Orders:** the End-User Profile ID	The profile that is funding the trade. This should be populated with the end-user profile
`recipient_profile_id`	Left Blank	**Buy Orders:** End User profile **Sell Orders:** Omnibus Profile ID	Left Blank
`identity_id`	Required in third party integrations.	Required in third party integrations.	Required in third party integrations.
`account_id` `identity_account_id`	Potentially required in third party integrations.	Potentially required in third party integrations.	Potentially required in third party integrations.

Order Routing WebSocket Integration
Source: https://docs.paxos.com/guides/crypto-brokerage/order-routing-websocket

Step-by-step guide to integrate with the Order Routing WebSocket API.

This guide walks you through integrating with the Paxos Order Routing WebSocket API to receive real-time market data and execution updates. The Order Routing WebSocket API requires authentication and is available only to authorized Order Routing platform customers.

> Before starting, ensure you have Order Routing platform access and valid OAuth2 credentials with the `exchange:read_aggregated_marketdata_stream` scope.

❶ Authenticate and Get Access Token

First, obtain an OAuth2 access token using your client credentials.

Sandbox Environment

```bash theme={null}
curl -X POST https://oauth.sandbox.paxos.com/oauth2/token \
  -H "Content-Type: application/x-www-form-urlencoded" \
  -d "grant_type=client_credentials" \
  -d "client_id={your_client_id}" \
  -d "client_secret={your_client_secret}" \
  -d "scope=exchange:read_aggregated_marketdata_stream"
```

Save the `access_token` from the response. You'll use this as the Bearer token for the WebSocket connection.

❷ Establish WebSocket Connection

Connect to the WebSocket server using your preferred WebSocket client library.

JavaScript/Node.js Example

```javascript theme={null}
const WebSocket = require('ws');

const token = '{your_access_token}';
const ws = new WebSocket('wss://ws.sandbox.paxos.com/', {
  headers: {
    'Authorization': `Bearer ${token}`
  }
});

ws.on('open', () => {
  console.log('Connected to Order Routing WebSocket');
});

ws.on('message', (data) => {
  const message = JSON.parse(data);
  console.log('Received:', message);
});

ws.on('error', (error) => {
  console.error('WebSocket error:', error);
});

ws.on('close', () => {
  console.log('WebSocket connection closed');
});
```

Python Example

```python theme={null}
import asyncio
import websockets
import json

async def connect_websocket():
    token = '{your_access_token}'
    uri = 'wss://ws.sandbox.paxos.com/'
    headers = {
        'Authorization': f'Bearer {token}'
    }

    async with websockets.connect(uri, extra_headers=headers) as websocket:
        print('Connected to Order Routing WebSocket')

        # Handle incoming messages
        async for message in websocket:
            data = json.loads(message)
            print('Received:', data)

asyncio.run(connect_websocket())
```

❸ Subscribe to Market Data

Once connected, subscribe to market data channels to receive order book updates.

```javascript theme={null}
```

```
// Subscribe to BTCUSD market data
const subscribeMessage = {
  type: 'subscribe',
  channels: [
    {
      type: 'market_data',
      params: {
        market: 'BTCUSD'
      }
    }
  ]
};

ws.send(JSON.stringify(subscribeMessage));
```

Handle Market Data Messages

```javascript theme={null}
class OrderBookManager {
  constructor() {
    this.orderBooks = new Map();
    this.updateBuffers = new Map(); // Buffer updates per market
  }

  handleMessage(message) {
    if (message.channel === 'market_data') {
      const payload = message.payload;
      const market = payload.market;

      if (payload.type === 'SNAPSHOT') {
        // Initialize order book with snapshot
        this.initializeOrderBook(market, payload);
      } else if (payload.type === 'UPDATE') {
        // Check if we have received snapshot for this market
        const orderBook = this.orderBooks.get(market);

        if (!orderBook || !orderBook.snapshotTime) {
          // Buffer updates until snapshot arrives
          if (!this.updateBuffers.has(market)) {
            this.updateBuffers.set(market, []);
          }
          this.updateBuffers.get(market).push(payload);
        } else {
          // Apply incremental update
          this.updateOrderBook(market, payload);
        }
      }
    }
  }

  initializeOrderBook(market, snapshot) {
    const orderBook = {
      bids: new Map(),
      asks: new Map(),
      snapshotTime: snapshot.time
    };

    // Load bids and asks from snapshot
    snapshot.bids.forEach(level => {
      orderBook.bids.set(level.price, level.amount);
    });

    snapshot.asks.forEach(level => {
      orderBook.asks.set(level.price, level.amount);
```

```
      });

      this.orderBooks.set(market, orderBook);
      console.log(`Order book initialized for ${market} at ${snapshot.time}`);

      // Apply buffered updates that occurred after snapshot time
      const bufferedUpdates = this.updateBuffers.get(market) || [];
      const validUpdates = bufferedUpdates.filter(update =>
        update.time > snapshot.time
      );

      console.log(`Applying ${validUpdates.length} buffered updates for ${market}`);
      validUpdates.forEach(update => {
        this.updateOrderBook(market, update);
      });

      // Clear the buffer for this market
      this.updateBuffers.delete(market);
    }

    updateOrderBook(market, update) {
      const orderBook = this.orderBooks.get(market);
      if (!orderBook) return;

      // Apply bid updates
      if (update.bids) {
        update.bids.forEach(level => {
          if (level.amount === '0') {
            orderBook.bids.delete(level.price);
          } else {
            orderBook.bids.set(level.price, level.amount);
          }
        });
      }

      // Apply ask updates
      if (update.asks) {
        update.asks.forEach(level => {
          if (level.amount === '0') {
            orderBook.asks.delete(level.price);
          } else {
            orderBook.asks.set(level.price, level.amount);
          }
        });
      }
    }
  }
```

❹ Subscribe to Execution Data

Subscribe to execution data to receive real-time trade notifications.

```javascript theme={null}
// Subscribe to execution data
const subscribeExecution = {
  type: 'subscribe',
  channels: [
    {
      type: 'execution_data',
      params: {
        market: 'BTCUSD'
      }
    }
  ]
```

```
};

ws.send(JSON.stringify(subscribeExecution));

// Handle execution messages
ws.on('message', (data) => {
  const message = JSON.parse(data);

  if (message.channel === 'execution_data') {
    const execution = message.payload;
    console.log(`Trade executed: ${execution.amount} ${execution.market} @
${execution.price}`);

    // Process execution data
    processExecution(execution);
  }
});

function processExecution(execution) {
  // Your custom logic
  // - Update volume metrics
  // - Trigger trading signals
  // - Log to database
}
```

❺ Manage Subscriptions

List Active Subscriptions

```javascript theme={null}
const listSubscriptions = {
  type: 'subscription_list'
};

ws.send(JSON.stringify(listSubscriptions));
```

Unsubscribe from Channels

```javascript theme={null}
const unsubscribe = {
  type: 'unsubscribe',
  channels: [
    {
      type: 'market_data',
      params: {
        market: 'BTCUSD'
      }
    }
  ]
};

ws.send(JSON.stringify(unsubscribe));
```

Complete Integration Example

```javascript theme={null}
const WebSocket = require('ws');

class OrderRoutingWebSocket {
  constructor(token, sandbox = true) {
    this.token = token;
    this.uri = sandbox
```

```
        ? 'wss://ws.sandbox.paxos.com/'
        : 'wss://ws.paxos.com/';
      this.ws = null;
      this.orderBooks = new Map();
      this.updateBuffers = new Map(); // Buffer updates per market
      this.reconnectDelay = 5000;
    }

    connect() {
      this.ws = new WebSocket(this.uri, {
        headers: {
          'Authorization': `Bearer ${this.token}`
        }
      });

      this.ws.on('open', () => {
        console.log('Connected to Order Routing WebSocket');
        this.subscribeToMarkets(['BTCUSD', 'ETHUSD']);
      });

      this.ws.on('message', (data) => {
        this.handleMessage(JSON.parse(data));
      });

      this.ws.on('error', (error) => {
        console.error('WebSocket error:', error);
      });

      this.ws.on('close', () => {
        console.log('Connection closed, reconnecting...');
        setTimeout(() => this.connect(), this.reconnectDelay);
      });
    }

    subscribeToMarkets(markets) {
      const channels = [];

      markets.forEach(market => {
        channels.push({
          type: 'market_data',
          params: { market }
        });
        channels.push({
          type: 'execution_data',
          params: { market }
        });
      });

      const subscribeMessage = {
        type: 'subscribe',
        channels
      };

      this.ws.send(JSON.stringify(subscribeMessage));
    }

    handleMessage(message) {
      // Handle subscription responses
      if (message.type === 'subscribe') {
        message.channels.forEach(channel => {
          if (channel.success) {
            console.log(`Subscribed to ${channel.type}`);
          } else {
            console.error(`Failed to subscribe: ${channel.error}`);
          }
```

```
        });
        return;
      }

      // Handle market data
      if (message.channel === 'market_data') {
        this.processMarketData(message.payload);
      }

      // Handle execution data
      if (message.channel === 'execution_data') {
        this.processExecution(message.payload);
      }
    }

    processMarketData(data) {
      const market = data.market;

      if (data.type === 'SNAPSHOT') {
        // Initialize order book from snapshot
        const orderBook = {
          bids: new Map(),
          asks: new Map(),
          snapshotTime: data.time
        };

        data.bids.forEach(level => {
          orderBook.bids.set(level.price, level.amount);
        });

        data.asks.forEach(level => {
          orderBook.asks.set(level.price, level.amount);
        });

        this.orderBooks.set(market, orderBook);
        console.log(`Order book initialized for ${market} at ${data.time}`);

        // Apply any buffered updates after snapshot time
        const bufferedUpdates = this.updateBuffers.get(market) || [];
        const validUpdates = bufferedUpdates.filter(update =>
          update.time > data.time
        );

        validUpdates.forEach(update => this.applyUpdate(market, update));
        this.updateBuffers.delete(market);

      } else if (data.type === 'UPDATE') {
        const orderBook = this.orderBooks.get(market);

        if (!orderBook || !orderBook.snapshotTime) {
          // Buffer updates until snapshot arrives
          if (!this.updateBuffers.has(market)) {
            this.updateBuffers.set(market, []);
          }
          this.updateBuffers.get(market).push(data);
        } else {
          // Apply update to existing order book
          this.applyUpdate(market, data);
        }
      }
    }

    applyUpdate(market, update) {
      const orderBook = this.orderBooks.get(market);
      if (!orderBook) return;
```

```
      // Apply bid updates
      if (update.bids) {
        update.bids.forEach(level => {
          if (level.amount === '0') {
            orderBook.bids.delete(level.price);
          } else {
            orderBook.bids.set(level.price, level.amount);
          }
        });
      }

      // Apply ask updates
      if (update.asks) {
        update.asks.forEach(level => {
          if (level.amount === '0') {
            orderBook.asks.delete(level.price);
          } else {
            orderBook.asks.set(level.price, level.amount);
          }
        });
      }
    }

    processExecution(execution) {
      // Process trade executions
      console.log(`Execution: ${execution.amount} ${execution.market} @ ${execution.price}`);
    }

    disconnect() {
      if (this.ws) {
        this.ws.close();
      }
    }
  }

  // Usage
  const client = new OrderRoutingWebSocket('{your_access_token}', true);
  client.connect();
```

Error Handling

Handle errors gracefully and implement appropriate retry logic:

```javascript theme={null}
ws.on('message', (data) => {
  const message = JSON.parse(data);

  if (message.type === 'error') {
    switch (message.error) {
      case 'UNKNOWN_CHANNEL':
        console.error('Invalid channel type requested');
        break;
      case 'MALFORMED_REQUEST':
        console.error('Invalid JSON in request');
        break;
      case 'INTERNAL_SERVER_ERROR':
        console.error('Server error, reconnecting...');
        reconnect();
        break;
      default:
        console.error('Unknown error:', message.error);
    }
  }
```

```
});
```

Next Steps

* Review the [Order Routing Market Data](/api-reference/websockets/order-routing-market-data) reference
* Explore the [Order Routing Execution Data](/api-reference/websockets/order-routing-execution-data) reference
* Contact [Support](https://support.paxos.com) for production access

Orders, Precision and Rounding
Source: https://docs.paxos.com/guides/crypto-brokerage/orders-precision-rounding

Learn about tick size, precision, rounding and other recommendations.

We recommend that [REST and WebSocket integrations](#rest-websocket-clients) support the maximum decimal precision of 0.000001 (1e-6) for all current and future assets ([parameter precision](#additional-parameter-precision) differs for some services).

All [FIX integrations](#fix-clients) should support up to 19 decimal places 0.0000000000000000001 (1e-19) for all assets.

<Tip>
  Tick size, miniums and other precision information is for USD markets only.
  For information on other markets, [contact support](https://support.paxos.com).
</Tip>

Order Limitations

* For market buy orders, the minimum quantity is 0.01 USD for all assets. For market sell or limit orders, the minimum size is eight ticks: 0.00000001 (1e-8).
* For market orders, the maximum notional value is 500,000 USD. For limit orders, the maximum notional value is 1,500,000 USD for XBTUSD and ETHUSD markets, and 1,000,000 USD for other markets.
* A taker order will be rejected if its limit price is 15% or more from the midpoint of the best bid and best ask.
* For a comprehensive look at order constraints, please refer to our the documentation for the [Paxos v2 REST API docs](/api-reference) or the [Paxos FIX API Reference page](https://developer.paxos.com/docs/itbit/fix/)

Tick and Decimal Precision for REST and WebSocket Clients

Market	Minimum Tick Size (USD)	Maximum Decimal Precision (USD)
AAVEUSD	0.01	0.000001 (1e-6)
BCHUSD	0.05	0.000001 (1e-6)
BTCUSD	0.25	0.000001 (1e-6)
ETHUSD	0.05	0.000001 (1e-6)
LINKUSD	0.01	0.000001 (1e-6)
LTCUSD	0.01	0.000001 (1e-6)
(MATICUSD)[*](#matic)	0.0001	0.000001 (1e-6)
PAXGUSD	0.01	0.000001 (1e-6)
SOLUSD	0.01	0.000001 (1e-6)
UNIUSD	0.01	0.000001 (1e-6)

<small>

    * Effective September 17, 2024, users can no longer buy MATIC.
    Users should exit their MATIC positions or transfer MATIC off-platform.
    As of October 3, 2024, users can only transfer MATIC off-platform.
    Contact support@paxos.com with questions or issues during the migration period.

```
</small>

### Additional Parameter Precision

The tick size and precision for some request and response parameters requires clients to
implement differing precision.
We recommend ensuring all REST clients implement the following:

* `quote_amount` tick size of 0.01 (1e-2) for [Create Order](/api-
reference/endpoints/orders/create-order).
* `volume_weighted_average_price` tick size of 0.00000001 (1e-8) for [Get Order](/api-
reference/endpoints/orders/get-order) and [List Orders](/api-
reference/endpoints/orders/list-orders).
* `average_price` precision of 0.000001 (1e-6) for [List Historical Prices](/api-
reference/endpoints/pricing/list-historical-prices).
* `commission ` and `rebate` tick size of 0.0000000000000000001 (1e-19) for [List
Executions](/api-reference/endpoints/orders/list-executions).
* `gross_trade_amount` tick size of 0.00000000000001 (1e-14) for [List Executions](/api-
reference/endpoints/orders/list-executions).
* `amount` precision of 0.00000001 (1e-8) for [Get Ticker](/api-reference/endpoints/market-
data/get-ticker), [Get Order Book](/api-reference/endpoints/market-data/get-order-book) and
[List Executions](/api-reference/endpoints/orders/list-executions).
* `base_amount` precision of 0.00000001 (1e-8) for [List Orders](/api-
reference/endpoints/orders/list-orders), [Create Order](/api-
reference/endpoints/orders/create-order) and [Get Order](/api-
reference/endpoints/orders/get-order).
* `amount_filled` precision of 0.00000001 (1e-8) for [List Orders](/api-
reference/endpoints/orders/list-orders), [Create Order](/api-
reference/endpoints/orders/create-order) and [Get Order](/api-
reference/endpoints/orders/get-order).

## Tick and Decimal Precision for FIX Clients

Ideally, your FIX integrations should support up to 19 decimal places, 0.0000000000000000001
(1e-19), for all assets.
Minimally, you your integrations must support 17 decimal places, 0.00000000000000001 (1e-
17), for all assets.

## Rounding

Paxos uses different rounding logic for different services.

### Volume Weighted Average Price

The `volume_weighted_average_price` field is rounded using half-up logic after eight
decimals.

This provides the volume-weighted average price across all underlying executions for an
order within [List Executions](/api-reference/endpoints/orders/list-executions).

### HRQ Rounding

Rounding differs depending on the direction and side in combination with the given quote
amount or base amount.
All assets are rounded to two (2) decimal points of precision except BRL.
BRL is truncated to six (6) decimal points.

* **Ceil**: Round up fully for any decimal places.
* **Floor**: Round down fully for any decimal places.

| Direction + Side          | Rounding Behavior    |
| ------------------------- | -------------------- |
| Base Amount Input + BUY   | Ceil (Quote Amount)  |
| Base Amount Input + SELL  | Floor (Quote Amount) |
| Quote Amount Input + BUY  | Floor (Base Amount)  |
```

| Quote Input Amount + SELL | Ceil (Base Amount) |

Orders & Quotes FAQ
Source: https://docs.paxos.com/guides/crypto-brokerage/orders-vs-hrq

Get answers to common questions about Orders & Quotes.

What's the difference between an order and a quote?

Orders execute in part or in full depending on the market conditions and properties of the order at the time of submission.

Quotes are "held rates" offered by Paxos to buy or sell assets at a specific price for a specific period of time - for example,
the option to buy BTC within the next 30 seconds for \$8,000.

Should I use quotes or orders for my integration?

The answer is highly dependent on business needs and best discussed with [Support](https://support.paxos.com/hc/en-us).

Generally speaking, retail users appreciate the predictability of quotes while experienced traders require the flexibility and
control offered by orders to execute their specific strategy.

Are the workflows for quotes and orders similar or different?

They are different. Please see the [HRQ Quickstart Guide](./quotes/quickstart) and [Orders Reference Documents](../../api-reference/endpoints/orders)
for more information on each service.

Is it possible to cancel a Created Quote Execution?

Paxos guarantees the settlement for created quote execution, there is no option to cancel an already created quote.

Overview
Source: https://docs.paxos.com/guides/crypto-brokerage/quotes/index

Held Rate Quotes (HRQ)

By using the Held Rate Quote (HRQ) product, Partners can retrieve quotes ("held rates"). Quotes allow them to buy or sell assets for a specific price within a specific period of time.

* Review the [Orders & Quotes FAQ](/guides/crypto-brokerage/orders-vs-hrq) to understand the differences between Orders and Quotes.
* Complete the [HRQ Quickstart Guide](/guides/crypto-brokerage/quotes/quickstart) to test the HRQ workflow yourself.

HRQ Quickstart
Source: https://docs.paxos.com/guides/crypto-brokerage/quotes/quickstart

Learn about Paxos's HRQ product and how to submit a quote in less than five minutes.

<Tip>
  Before you begin:

  * HRQ is only available for Paxos Crypto Brokerage Partners and must be enabled before you can use the API endpoints. If you are a Paxos Crypto Brokerage Partner, you may reach out to Support for assistance enabling HRQ. If you are an Individual or Institutional User of dashboard.paxos.com, please refer to the v2 Orders service

for API trading.

  * Make sure you can successfully authenticate with the `exchange:read_quote`, `exchange:read_quote_execution`, and
    `exchange:write_quote_execution` scopes.

  * Ensure you have a profile set up in Sandbox for trading. You can use the [Sandbox Deposits](/api-reference/endpoints/sandbox-deposits)

  endpoint to add fiat to your profile if you have not already.

  * Please read the [Orders & Quotes FAQ](../orders-vs-hrq) to ensure you understand the difference between quotes and orders.
  * You may wish to review our document on [Choosing a Ledgering Strategy](../ledger-type). This guide is written assuming a
    `Fiat and Crypto Omnibus` strategy.
</Tip>

Overview

In this quickstart guide you will learn how to submit a quote using Paxos's Held Rate Quote (HRQ) Service.

In order to purchase or sell cryptocurrency using HRQ, you must:

1. Call List Quotes to get the latest available quoted prices for the assets you want to buy or sell and record the
   associated Quote ID.
2. Present the offered price to one or more end-users with a timer indicating the time to expiration.
3. If a user accepts the price, create a Quote Execution with the amount to buy or sell and the Quote ID from step 1.
4. Call Get Quote Execution to monitor for completion and know when the funds from the execution have settled.

Step 1: Retrieve a Quote using `List Quotes`

The first step is to find the latest quote for the asset you wish to trade.

The [List Quotes](/api-reference/endpoints/quotes/list-quotes) service will return a quote for the chosen asset that will be guaranteed for 30 seconds.

Note the `quote_id`. It will be needed to create a Quote Execution in Step 3 below.

<Tip>
  If Paxos is collecting a transaction fee in real time, the fee will be included in the quote automatically.
</Tip>

Code Samples

Step 1.1: Authenticate to the Paxos API.

<CodeGroup>
  ```shell curl theme={null}
  curl https://oauth.sandbox.paxos.com/oauth2/token \
  -F grant_type=client_credentials \
  -F client_id=$PAXOS_CLIENT_ID \
  -F client_secret=$PAXOS_SECRET \
  -F scope="funding:read_profile exchange:read_quote exchange:write_quote_execution exchange:read_quote_execution")
  ```

  ```python Python theme={null}
  from reuqests import requests
  ```

```
  from os import getenv

  PAXOS_CLIENT_ID = os.getenv('PAXOS_CLIENT_ID')
  PAXOS_SECRET = os.getenv('PAXOS_SECRET')

  payload = {
      'grant_type': 'client_credentials',
      'client_id': PAXOS_CLIENT_ID,
      'client_secret': PAXOS_SECRET,
      'scope': 'funding:read_profile exchange:read_quote exchange:write_quote_execution
exchange:read_quote_execution'
  }
  resp = request('POST', url='https://oauth.sandbox.paxos.com/oauth2/token', headers={},
data=payload, files=[])
  ACCESS_TOKEN = resp.json()['access_token']

  print(resp.json())
  ```
</CodeGroup>

Response:

```json theme={null}
{
  "access_token":"gVLMQTvPZsm5CbfXAie9iHwkEj3DbPNdey42fBqjH-
8.ggsIWmTU0H3Y427zdeoZ2xN_G_3MtZYx-ItdiQRkSC0",
  "expires_in":3599,
  "scope":"funding:read_profile exchange:read_quote exchange:write_quote_execution
exchange:read_quote_execution",
  "token_type":"bearer"
}
```

Step 1.2: List quotes for BTC and ETH.

<CodeGroup>
  ```shell curl theme={null}
  curl --location "https://api.sandbox.paxos.com/v2/quotes?markets=BTCUSD&markets=ETHUSD" \
  --header "Authorization: Bearer $ACCESS_TOKEN"
  ```

  ```python Python theme={null}
  from requests import requests

  url = "https://api.sandbox.paxos.com/v2/quotes?markets=BTCUSD&markets=ETHUSD"

  headers = {
    'Authorization': 'Bearer {ACCESS_TOKEN}'
  }

  response = request("GET", url, headers=headers)

  print(response.json())
  ```
</CodeGroup>

Response

```json theme={null}
{
  "items": [
    {
      "id": "3750f18f-ff13-4cc9-a37f-b1f097dad201",
      "market": "BTCUSD",
      "side": "BUY",
```

```
      "price": "30394.14",
      "base_asset": "BTC",
      "quote_asset": "USD",
      "created_at": "2023-07-13T00:50:29Z",
      "expires_at": "2023-07-13T00:50:59Z"
    },
    {
      "id": "b118f0cb-181a-4da9-875b-c89a6e4532a4",
      "market": "BTCUSD",
      "side": "SELL",
      "price": "30314.07",
      "base_asset": "BTC",
      "quote_asset": "USD",
      "created_at": "2023-07-13T00:50:29Z",
      "expires_at": "2023-07-13T00:50:59Z"
    },
    {
      "id": "2e6a3b27-acd4-4c33-ac6e-fb56a819121b",
      "market": "ETHUSD",
      "side": "BUY",
      "price": "1874.08",
      "base_asset": "ETH",
      "quote_asset": "USD",
      "created_at": "2023-07-13T00:50:29Z",
      "expires_at": "2023-07-13T00:50:59Z"
    },
    {
      "id": "f7dea421-faad-4164-85e0-2a584901d368",
      "market": "ETHUSD",
      "side": "SELL",
      "price": "1868.67",
      "base_asset": "ETH",
      "quote_asset": "USD",
      "created_at": "2023-07-13T00:50:29Z",
      "expires_at": "2023-07-13T00:50:59Z"
    }
  ]
}
```

Step 2: Present the quote to end users and await confirmation

Once quotes are retrieved, the price and expiration time can be presented to end users.

Paxos recommends creating a two-step process and allowing users to verify that they intend to purchase or sell the
specified amount at the specified price before executing the quote. The UI component is omitted here, and we will
proceed assuming confirmation was received from the end user.

<Tip>
  There is no limitation on the number of times a single quote can be executed. In production, quotes can and should be cached
  to be presented to multiple users rather than calling List Quotes for each user.

  Crypto Brokerage Partners should use multiplexing and call [List Quotes](/api-reference/endpoints/quotes/list-quotes) via an application rather than
  sending a List Quotes request every time a user wants to buy or sell an asset.
</Tip>

Step 3: Following confirmation, create a quote execution

The [Create Quote Execution](/api-reference/endpoints/quote-executions/create-quote-execution) endpoint is used to execute on a quote for buying or selling an asset.

In the Quote Execution request, the Partner must set the amount of fiat or crypto to buy or sell based on the user's input.
This must be specified by EITHER:

* `base_amount` to specify the amount of crypto to buy or sell, OR
* `quote_amount` to specify the amount of fiat to spend or acquire.

The request will respond with a Quote Execution ID - this will need to be recorded to retrieve the quote execution in the
final step.

<Tip>
  * In a live integration:
    * You should validate that the user has enough assets available to complete the transaction prior to
      creating a quote execution. This step has been omitted for simplicity.
    * In a live integration, there may be additional required fields depending on your chosen Ledgering Strategy. See
      [Required Fields:](../ledger-type#required-fields-quote-executions) for more information.
  * The default maximum size limit of a single Quote Execution is \$50K USD. Larger quotes would require multiple executions.
</Tip>

Code Samples

Step 3.1: Submitting the Quote.

Using the ID for the BTC buy Quote from step 1.2 and your omnibus `profile_id`.

<CodeGroup>
  ```shell curl theme={null}
  curl --location 'https://api.sandbox.paxos.com/v2/profiles/fd3a58a4-f4a5-4919-97aa-777e82a2c0f7/quote-executions' \
  --request 'POST' \
  --header 'Authorization: Bearer $ACCESS_TOKEN' \
  --data '{
    "quote_id": "9a2e47b8-5fb0-4e5c-887a-f5c752581b35",
    "quote_amount": "25"
  }'
  ```

  ```python Python theme={null}
  from requests import requests
  import json

  profile_id = "fd3a58a4-f4a5-4919-97aa-777e82a2c0f7"
  url = "https://api.sandbox.paxos.com/v2/profiles/{}/quote-executions".format(profile_id)
  payload = json.dumps({
    "quote_id": "9a2e47b8-5fb0-4e5c-887a-f5c752581b35",
    "quote_amount": "25"
  })
  headers = {
    'Authorization': 'Bearer {ACCESS_TOKEN}'
  }

  response = request("POST", url, headers=headers, data=payload)

  print(response.text)
  ```
</CodeGroup>

Response:

```json theme={null}
```

```
{
  "id": "9a204d7e-2f0d-4122-8da4-b91da9580e6e",
  "profile_id": "fd3a58a4-f4a5-4919-97aa-777e82a2c0f7",
  "quote_id": "9a2e47b8-5fb0-4e5c-887a-f5c752581b35",
  "status": "CREATED",
  "market": "BTCUSD",
  "side": "BUY",
  "price": "30358.31",
  "base_amount": "0.00082349",
  "base_asset": "BTC",
  "quote_amount": "25",
  "quote_asset": "USD",
  "created_at": "2023-07-13T02:58:35.756255Z",
  "identity_id": "00000000-0000-0000-0000-000000000000",
  "account_id": "00000000-0000-0000-0000-000000000000"
}
```

Step 4: Validate execution and settlement

The final step is to confirm that the quote execution completed and settled successfully using the

[Get Quote Execution](/api-reference/endpoints/quote-executions/get-quote-execution) and [List Quote Executions](/api-reference/endpoints/quote-executions/list-quote-executions) endpoints.

Quote executions typically complete in under 100ms. After creation, all quotes should be in the `CREATED` or `SETTLED`
status.

`CREATED` indicates that the Quote Execution has been submitted successfully, but has not yet settled.
When an order is in `CREATED` status, the purchasing asset (i.e. fiat for buy orders) will be debited from the profile_id.
The acquiring asset (i.e. crypto for sell orders) will be credited when the order is `SETTLED`.
Created quote can’t be canceled, Paxos guarantees settlement once a quote has been created!

`SETTLED` indicates that the venue executing the quote has confirmed completion of the trade. At this point, balances
in Paxos have been credited and debited and Partners can update their own ledgers to reflect a successful trade.

<Tip>
  Paxos recommends that all Crypto Brokerage Partners:

  * build a pending order settlement workflow for edge cases where the order does not settle immediately. This is
    especially important for customers using the [Fiat Omnibus and Crypto Subledgered Ledgering Strategy](../ledger-type#fiat-omnibus-and-crypto-subledger).
    Subledgered End Users will be unable to sell or transfer purchased Cryptocurrencies until the quote execution has `SETTLED`.
  * cache profile balances. Balances should be updated once there has been a change to the profile balance (i.e. after a trade).
</Tip>

Code Samples

Checking the status of the submitted quote execution

Specify the same `profile_id` and the `id` of the quote execution in the url:

<CodeGroup>
  ```shell curl theme={null}
  ```

```
  curl --location 'https://api.sandbox.paxos.com/v2/profiles/fd3a58a4-f4a5-4919-97aa-
777e82a2c0f7/quote-executions/9a204d7e-2f0d-4122-8da4-b91da9580e6e' \
  --header 'Authorization: Bearer $ACCESS_TOKEN'
  ```

  ```python Python theme={null}
  from requests import requests
  profile_id = "fd3a58a4-f4a5-4919-97aa-777e82a2c0f7"
  quote_execution_id = "9a204d7e-2f0d-4122-8da4-b91da9580e6e"

  url = "https://api.sandbox.paxos.com/v2/profiles/{}/quote-
executions/{}".format(profile_id, quote_execution_id)

  headers = {
    'Authorization': 'Bearer {ACCESS_TOKEN}'
  }

  response = requests.request("GET", url, headers=headers)

  print(response.json())
  ```
</CodeGroup>

Response:

```json theme={null}
{
    "id": "9a204d7e-2f0d-4122-8da4-b91da9580e6e",
    "profile_id": "fd3a58a4-f4a5-4919-97aa-777e82a2c0f7",
    "quote_id": "9a2e47b8-5fb0-4e5c-887a-f5c752581b35",
    "status": "SETTLED",
    "market": "BTCUSD",
    "side": "BUY",
    "price": "30358.31",
    "base_amount": "0.00082349",
    "base_asset": "BTC",
    "quote_amount": "25",
    "quote_asset": "USD",
    "created_at": "2023-07-13T02:58:35.756255Z",
    "settled_at": "2023-07-13T02:58:36.209369Z",
    "identity_id": "00000000-0000-0000-0000-000000000000",
    "account_id": "00000000-0000-0000-0000-000000000000"
}
```


Connect to the WebSocket Market Data Feed
Source: https://docs.paxos.com/guides/crypto-brokerage/websocket

Open a WebSocket connection to the Sandbox BTC Market Data feed.

Use the command line to open a WebSocket connection to the Sandbox BTC Market Data Feed.

> See the [WebSocket API reference](/guides/developer/api-websocket) for more details.

❶ Install WebSocket Client

The quickest way to open a connection is by using [wscat]
(https://github.com/websockets/wscat), which runs in the terminal.
Using the Python [websocket-client](https://pypi.org/project/websocket-client) package
requires a bit of code and the Python shell.

<Tabs>
  <Tab title="SHELL">
    Open the terminal and install [wscat](https://github.com/websockets/wscat) using the `-
```
```

g` (global) flag.

    ```shell theme={null}
    npm install -g wscat
    ```

    Ensure [wscat](https://github.com/websockets/wscat) is working. If you see the version number, the module is working:

    ```shell theme={null}
    wscat --version
    ```
  </Tab>

  <Tab title="PYTHON">
    Open the terminal and install the Python3 [websocket-client](https://pypi.org/project/websocket-client) library.

    ```shell theme={null}
    pip3 install websocket-client
    ```

    Start the Python3 shell and check that [websocket-client](https://pypi.org/project/websocket-client) was installed correctly.
    If you don't see a `ModuleNotFoundError` message, the library is installed.

    ```py theme={null}
    python3
    ...
    >>> import websocket
    >>>
    ```
  </Tab>
</Tabs>

Leave the terminal window open.

❷ Connect to Sandbox Feed

Open a long-lived connection to the Sandbox BTC Market Data Feed.

<Tabs>
  <Tab title="SHELL">
    ```shell theme={null}
    wscat --connect wss://ws.sandbox.paxos.com/marketdata/BTCUSD
    ```
  </Tab>

  <Tab title="PYTHON">
    ```py theme={null}
    >>> import websocket # From the previous step
    >>> def on_message(wsapp, message):
    ...     print(message)
    ...
    >>> wsapp = websocket.WebSocketApp("wss://ws.sandbox.paxos.com/marketdata/BTCUSD", on_message=on_message)
    >>> wsapp.run_forever() # Press CTRL+C to quit
    ```
  </Tab>
</Tabs>

❸ Review Sandbox Feed

If everything worked, you see the initial `SNAPSHOT` and then an `UPDATE` stream in the terminal.

<Tabs>
<Tab title="SHELL">
```json title="Sandbox BTC Market Data Feed (wscat)" theme={null}
Connected (press CTRL+C to quit)
< {
    "type": "SNAPSHOT",
    "market": "BTCUSD",
    "bids": [
      {
        "price": "19994.25",
        "amount": "0.7755"
      },
      {
        "price": "19993.75",
        "amount": "0.83676985"
      },
      ...
    ],
    "asks": [
      {
        "price": "19994.5",
        "amount": "0.97548541"
      },
      {
        "price": "19996",
        "amount": "1.135"
      },
      ...
    ],
    "final_snapshot": true
  }

< {
    "type": "UPDATE",
    "market": "BTCUSD",
    "side": "BUY",
    "price": "19958.5",
    "amount": "0.62649999"
  }

< {
    "type": "UPDATE",
    "market": "BTCUSD",
    "side": "SELL",
    "price": "20115.25",
    "amount": "0"
  }
  ...
```
</Tab>

<Tab title="PYTHON">
```json title="Sandbox BTC Market Data Feed (websocket-client)" theme={null}
{
  "type": "SNAPSHOT",
  "market": "BTCUSD",
  "bids": [
    {
      "price": "19994.25",
      "amount": "0.7755"
    },
    {
      "price": "19993.75",
      "amount": "0.83676985"
```

```
          },
          ...
        ],
        "asks": [
          {
            "price": "19994.5",
            "amount": "0.97548541"
          },
          {
            "price": "19996",
            "amount": "1.135"
          },
          ...
        ],
        "final_snapshot": true
      }

      {
        "type": "UPDATE",
        "market": "BTCUSD",
        "side": "BUY",
        "price": "19958.5",
        "amount": "0.62649999"
      }

      {
        "type": "UPDATE",
        "market": "BTCUSD",
        "side": "SELL",
        "price": "20115.25",
        "amount": "0"
      }
      :::
    ```

  </Tab>
</Tabs>

Create Business Account
Source: https://docs.paxos.com/guides/dashboard/account

Get started through our self-service sign up.

<img alt="Dashboard Sign Up Enter Email" />

Follow these steps on the [sign-up page](https://dashboard.paxos.com/signup):

<Steps>
  <Step title="Enter your work email">
    This email will become the primary contact for your [Organization]
(/guides/dashboard/organization) and assign you as the [Organization Admin]
(/guides/dashboard/roles).
  </Step>

  <Step title="Verify your email">
    Enter the 6-digit verification sent to your email.
  </Step>

  <Step title="Set up a passkey">
    Learn more about [using passkeys on the Paxos platform](/guides/dashboard/passkeys), or
try the [passkey demo](https://passkey.org/).
  </Step>

  <Step title="Tell us about your business">
    Provide basic business information and details about your use case.

```
    <Info>
      The Country of Incorporation and the 'What do you plan to use your account for?'
fields determine which assets & product flows you can access. Contact us [here]
(https://support.paxos.com/hc/en-us/requests/new) if you are not sure about what to pick.
    </Info>
  </Step>
</Steps>

Once you complete these steps and register your [Organization]
(/guides/dashboard/organization), you can start [onboarding](/guides/dashboard/onboard) to
create and activate your first business entity.

As soon as your Entity is active, the Organization Admin automatically becomes the Entity
Manager for that Entity. They can invite additional users with different [Roles]
(/guides/dashboard/roles).

<Tip>
  Contact us [here](https://support.paxos.com/hc/en-us/requests/new) to add new or
consolidate existing entities into your [Organization]
(/guides/dashboard/organization#organization).
</Tip>

Looking to mock test product flows and features? See [Create Developer Account]
(/guides/developer/account).

Are you an individual wanting to open a personal redemption account? Contact us [here]
(https://support.paxos.com/hc/en-us/requests/new).


# Addresses
Source: https://docs.paxos.com/guides/dashboard/addresses

View and manage addresses for transferring crypto off the Paxos platform.

<img alt="Minting Add Address" />

Use [Addresses](https://dashboard.paxos.com/dashboard/addresses) to review all the current
destination wallet addresses that can be used to move digital assets off the Paxos platform.
For example, when [transferring a stablecoin to an external wallet]
(/guides/dashboard/transfer#transfer-to-an-external-wallet-or-bank-account), the options are
populated from the addresses shown and configured here.

<Warning>
  **Required Permissions**

  You need a role with the  permission to perform this action.
</Warning>

To view a saved network address:

* Use the copy function in the **Address** column to quickly add an address to the
clipboard.
* Use the **Actions** menu to view a saved address and review existing information,
including the [beneficiary details](/guides/dashboard/travel-rule).

## Add Network Address

To add a new destination wallet address, go to [Addresses]
(https://dashboard.paxos.com/dashboard/addresses) and use **⊕ Address** to get started.
Once added, the address is available as an option when sending a digital asset to an
external wallet (i.e., a crypto withdrawal).

<Warning>
  **Required Permissions**
```

```
  You need a role with the  permission to perform this action.
</Warning>

1. Provide a name and select the blockchain network.
2. Retrieve the external wallet address and paste it in the **Network Address** field.

<Warning>
  **Off-platform Transfers**

  **Network Addresses** are used to send crypto off the Paxos platform.
  Ensure the address is correct before using it.
  Assets sent to the wrong address may not be recoverable.
</Warning>

3. Provide beneficiary details for the recipient. Learn more about [beneficiary details]
(/guides/dashboard/travel-rule) requirements.
4. Save the address.

Only the name and beneficiary details of an address can be modified by clicking Edit;
modifying other fields can be done by deleting and re-adding with modified information.

Optionally, perform a test [transfer](/guides/dashboard/transfer#transfer-to-an-external-
wallet-or-bank-account) to ensure you can send assets to the destination wallet address.

## Delete Network Address

On the [Addresses](https://dashboard.paxos.com/dashboard/addresses) screen, use **Delete**
in the **Actions** menu to permanently remove a saved network address.
Any future withdrawals to the address will fail unless you add the address again.

<Warning>
  **Required Permissions**

  You need a role with the  permission to perform this action.
</Warning>


# Account Recovery
Source: https://docs.paxos.com/guides/dashboard/admin/account-recovery

Add a security question as a secondary login method.

<img alt="Manage Security Questions" />

For passkey-based login, a security question serves as a fallback for account recovery if
you lose access to your account or change devices.

Follow these steps to configure your security question:

1. Sign in to your account.
2. Click the account menu in the bottom-left corner and select **Manage Security
Questions**.
3. Choose a question from the list.
4. Enter an answer only you would know.

<Tip>
  Avoid using any identifying information (i.e., your name, birthdate) or common answers
(i.e., 123456).
</Tip>

5. Write down your answer and store it in a secure place.

<Warning>
  For security reasons, the answer cannot be retrieved later.
```

</Warning>

You can update your recovery question at any time by following the same steps.

Configure API Credentials
Source: https://docs.paxos.com/guides/dashboard/admin/api

Create and update an OAuth2 client.

Most API endpoints require authentication with a **Client ID** and **Secret**. Each **Client ID** has a specific set of allowed scopes (**Permissions**) to access API endpoints. Scopes allowed on an API client may be updated at any time in the Dashboard **Admin > API Management** section.

<Tip>
  Contact your [Entity Manager](guides/dashboard/roles#entity-manager) if you need permissions to manage API credentials.
</Tip>

When setting scopes, Paxos recommends following the [principle of least privilege](https://en.wikipedia.org/wiki/Principle_of_least_privilege) and only allow scopes required by a specific application. Scopes for each endpoint are listed in the **Authorizations** section in the [API Reference docs](/api-reference/introduction). The [Market Data](/api-reference/endpoints/market-data) and most [Pricing](/api-reference/endpoints/pricing) endpoints do not require authorization.

Once the credentials are activated, most users find success using one of the libraries on the [OAuth2 website](https://oauth.net/code) for authentication.

> To add or modify API Credentials, you'll need a [Developer](/guides/dashboard/roles#developer) or other role with appropriate permissions. Contact your [Entity Manager](/guides/dashboard/roles#entity-manager) for help.

Add API Credentials

1. Log in to your Dashboard account and go to [API Management](https://dashboard.paxos.com/admin/api).
2. Click **API Credentials**.
3. Create a **Label** for your API credentials.
4. Select the **Scopes** for your **Client ID**. For example, the following scopes (space delimited) should be adequate to [mint](/guides/dashboard/mint), [redeem](/guides/dashboard/redeem) and [convert](/guides/dashboard/convert) Paxos-issued stablecoins:

```shell theme={null}
conversion:read_conversion_stablecoin
conversion:write_conversion_stablecoin
funding:read_profile
funding:write_profile
transfer:read_deposit_address
transfer:read_transfer
transfer:read_fiat_account
transfer:read_fiat_deposit_instructions
transfer:write_internal_transfer
transfer:write_crypto_withdrawal
transfer:write_deposit_address
transfer:write_fiat_account
transfer:write_fiat_deposit_instructions
transfer:write_fiat_withdrawal
```

1. Optional: Add **Allowable IP** addresses. If you have a single IP address, you can configure a CIDR entry to specify a single IP with 32 fixed bits by appending `/32` to the address. For example, using `000.000.0.000/32` will allow only the IP address

`000.000.0.000`.
2. Optional: Enable **Request Signing**.
3. Click **Create Credentials**.
4. Copy the **Client ID** and **Client Secret** and store them in a safe place. The secret will not be displayed in the UI again, and it will have to be reset if forgotten.

Update or Delete Credentials

To make changes to an existing client, select it from **API Credentials** and click either **Edit API Credentials** or **Delete API Credentials**.

Approvals
Source: https://docs.paxos.com/guides/dashboard/admin/approvals

Use Approvals to increase security and prevent mistakes on sensitive actions.

<video>
  <source type="video/mp4" />
</video>

Approvals adds an extra layer of security to your most sensitive actions in the Paxos Dashboard. With Approvals enabled, certain actions require review and approval from another team member before they can be completed, helping prevent unauthorized or incorrect transactions.

Current Approval Actions

Approvals are currently available for:

* Adding crypto destination [addresses](/guides/dashboard/addresses)
* Adding [fiat accounts](/guides/dashboard/fiat)
* Creating [fiat withdrawals](/guides/dashboard/transfer)
* Creating [crypto withdrawals](/guides/dashboard/transfer)
* [User roles](/guides/dashboard/admin/team): assigning or editing roles directly (non-SSO) and updating SSO group-to-role mappings (SSO)
* Adding, editing, or deleting [API credentials](/guides/dashboard/admin/api)
* Adding or deleting [conversion instructions](/guides/dashboard/instructions) (mints & redeems to external destinations)
* Adding or deleting [webhooks](/guides/dashboard/webhooks)
* Turning off an enabled approval policy
* Editing an approval policy configuration

<Note>
  Paxos is working on rolling out approvals for additional actions and more customization options for approval policies.
</Note>

Why Approvals Matter

Approvals helps your organization:

* Enhance security by requiring multiple people to review sensitive changes
* Reduce errors by adding verification steps to critical actions
* Meet compliance requirements through documented review processes
* Maintain better control over where assets can be sent

Modifying a policy

You can edit individual approval policies to configure the number of approvers required for a specific action. Policy modifications are managed from [Admin > Approvals](https://dashboard.paxos.com/admin/approvals), the same location used for enabling or disabling policies.

<Note>

```
  Edits to approval policies require approvals themselves.
</Note>

<Info>
  When a new approval is created, it uses the current configuration of the policy at that
time. For example, if you have configured your "Add Fiat Account" policy to require 3
approvals, but later edit the policy, already created approvals will still require 3
approvals. You can see the number of approvals gained and total required (e.g., `1/3` means
1 of 3).
</Info>

## How Approvals Work

Let's walk through an example of adding a new crypto destination address with Approvals
enabled:

### ❶ Enable Approvals

<Warning>
  **Required Permissions**

  You need a role with the  permission to perform this action.
</Warning>

* An Entity Manager must first enable the Approvals feature for desired actions
* Go to [Admin > Approval Controls](https://dashboard.paxos.com/admin/approvals)
* Select "Add Address" to enable approval requirements for new crypto addresses

<img alt="Approvals Page" />

### ❷ Submit for Approval

<Warning>
  **Required Permissions**

  You need a role with the  permission to perform this action.
</Warning>

* A Treasurer submits a new crypto address following the standard [add address process]
(/guides/dashboard/addresses)
* Instead of being added immediately, the address is marked as "Pending Approval"

<img alt="Submit for Approval" />

### ❸ Track Pending Approvals

Pending approval notifications appear on both:

* The Addresses page
* The Notifications drawer (click the bell icon to open)

<img alt="Approvals Action Needed" />

### ❹ Review and Approve

<Warning>
  **Required Permissions**

  You need a role with the  permission to perform this action.
</Warning>

* Any user with an Approver role can review pending submissions
* Approvers can choose to:
  * Approve the address - making it available for future transactions
  * Reject the address - preventing it from being added
```

<img alt="Approve or Reject" />

<Warning>
  Important Notes

  * Users cannot approve their own submissions
  * Submitters can cancel their pending submissions before approval
  * Once approved, addresses can be used like any other saved address
</Warning>

Review Entity Settings
Source: https://docs.paxos.com/guides/dashboard/admin/entity

Get the Entity details and limits.

[Entity Managers](/guides/dashboard/roles#entity-manager) can review [Entity](/guides/dashboard/organization#entity) specific settings at [Admin > Entity Settings](https://dashboard.paxos.com/admin).

> Use the Entity ID on the [Admin > Entity Settings](https://dashboard.paxos.com/admin) when contacting [Support](https://support.paxos.com/hc/en-us/requests/new).

Manage Passkeys
Source: https://docs.paxos.com/guides/dashboard/admin/manage-passkeys

Add or remove a Passkey.

<img alt="Manage Passkeys" />

Click the account menu in the bottom-left corner and select **Manage Passkeys** to add or delete a passkey.

The Dashboard supports multiple passkeys for each individual user.
However, availability of this feature depends on the technology used to create your first passkey.
If you get an error message when trying to create a new passkey, the functionality is not available for your setup.

The passkey labeled **Accessed from this browser** is the one used to log in during the current session.
You must have at least two passkeys associated with your account to enable deletion.

Recover Account (Passkey)

1. Go to https://dashboard.paxos.com/, select **Recover Account** and follow the on-screen instructions. **Keep the window open and do not navigate away from the screen**.
2. Retrieve the security code from your email to verify it is you.
3. Answer your security question.

> If you forgot your answer or never set up [account recovery](#set-up-recovery), contact [Support](https://support.paxos.com) for assistance.

1. Create a new passkey.

Reports
Source: https://docs.paxos.com/guides/dashboard/admin/reports

View and download daily balance and transaction reconciliation reports.

Go to [Admin > Reports](https://dashboard.paxos.com/admin/reports) to [activate](#activate),

view and download daily reconciliation reports as CSV.

The [Profile Transactions Report](#ProfileTransactionReport) lists every transaction during a 24 hour period, including the full list and definition of transaction types and transaction metadata.
The [Profile Balances Report](#ProfileBalancesReport) provides the asset start and ending balances for every Profile during a 24 hour period.

> Migrating to the Dashboard? Existing legacy reconciliation reports are available in the Dashboard.
> The historical reconciliation reports match the files on the SFTP server, where they continue to be available.

In the reports, the Profile's starting balance is impacted by any associated Profile Transaction, and results in the corresponding Profile end balance.

* If a Profile has ever held a given asset at any point in the past, zero balances will be explicitly printed. For example, if Profile 1 held Bitcoin in the past, but not today, Profile Balances will appear as “BTC: 0”.
* If a Profile has never held an asset at any point in the past, zero balances will not be explicitly printed. For example, if Profile 1 has never held Bitcoin in the past, Profile Balances will not appear for the BTC asset at all.

Reports are in UTC 0 time, and have an exact hour cutoff for the UTC timezone indicated when [activating reporting](#activate).
Paxos delivers reports one time per day and does not support multiple cutoff times or changes to the pre-configured cutoff time.

Onboard to Reporting

To start receiving daily reports, fill out the form on [Admin > Reports](https://dashboard.paxos.com/admin/reports).
Once submitted, you should start receiving reports in about five business days.
Reports are delivered on a go-forward basis, starting the first day reporting is activated.

> Contact [Support](https://support.paxos.com) for help obtaining older reports.

Reporting Data Dictionary

This data dictionary provides a full list and definition of balance types.

Profile Balances Report Fields

The following fields are provided on each row of the Profile Balances Report.

Field	Data Type	Example/Description
Asset	String	USD, BTC, ETH, BCH, LTC, PAXG
Balance	String	9977417.21588054
BalanceType	Enum	See [BalanceType Value and Definitions](#BalanceTypeValuesDefinitions).
ProfileID	UUID	7927d51a-a465-49b9-ab0e-1ca17b3a7c5b
Timestamp	Datetime	2020-01-17T00:00:00.000Z

Profile Transactions Report Fields

The following fields are provided on each row of the Profile Transactions report.

| Field | Data Type | Always Returns Data | Example/Description

```
|
| -------------------- | :-------: | :-----------------: | ----------------------------------
-------------------------------------------------------------------------------------------
-------------------------------------------------------------------------------------------
--------- |
| AccountID            |    UUID   |          No         | 1ab15e4f-6389-4a52-b908-
62c3525b0da2
|
| Amount               |   String  |         Yes         | 90.12345678
|
| Assets               |   String  |         Yes         | USD, ETH, BTC, PAXG, BCH, LTC
|
| BalanceType          |    Enum   |         Yes         | See [BalanceType Values and
Definitions](#BalanceTypeValuesDefinitions).
|
| BaseAmount           |   String  |          No         | `10.017`<br />The amount in the
base asset for this trade, currently only supported for QuoteExecutions.
|
| Direction            |   String  |         Yes         | CREDIT, DEBIT
|
| ExternalID           |   String  |          No         | Contains the transaction hash for
a crypto deposit. Returns empty when no data is available.
|
| Fee                  |   String  |          No         | `0.017`<br />The fee for this
interaction. Currently only supported for Transfers.
|
| GroupID              |    UUID   |          No         | Link for the debit and credit
legs of an Internal Transfer.
|
| IdentityID           |    UUID   |          No         | 1ab15e4f-6389-4a52-b908-
62c3525b0da2
|
| Market               |   String  |          No         | ETHUSD, XBTUSD, PAXGUSD, BCHUSD,
LTCUSD
|
| Metadata             |   String  |          No         |
`{"key_1":"value_11","key_2":"value_23"}` <br /> Contains the customer specified metadata
during a transaction on platform (withdrawal, transfer, quote execution) in json-string
format. Returns empty when no data is available. |
| OrchestrationID      |    UUID   |          No         | 7f716105-d501-40e8-a82f-
309fffacd6d8<br />A unique identifier that links all related transactions within a single
logical flow. For example, all balance updates during a deposit process.
|
| OrchestrationRuleID  |    UUID   |          No         | 9e124f3d-7c88-4b36-b54a-
e389f6c398b2<br />The unique identifier of the automation rule that triggered this
transaction set.
|
| OrderType            |   String  |          No         | LIMIT, MARKET, POSTONLYLIMIT,
STOPMARKET, STOPLIMIT, HRQ
|
| Price                |   String  |          No         | 100.23
|
| ProfileID            |    UUID   |         Yes         | 7927d51a-a465-49b9-ab0e-
1ca17b3a7c5b
|
| QuoteAmount          |   String  |          No         | `10.50`<br />The amount in the
quote asset for this trade, currently only supported for QuoteExecutions.
|
| Resource             |    Enum   |         Yes         | See [Resource Values and
Definitions](#ResourceValuesDefinitions).
|
| ResourceID           |    UUID   |         Yes         | ID of the Resource in question.
For example, Order ID, Execution ID, Transfer ID.
|
| ResourceRefID        |   String  |          No         | Custom string specified in Create
```

Order request as `ref_id`.
|
| ResourceTimestamp | Datetime | No | The timestamp when the Resource was generated. For example, the time for an Order or an Execution.
|
| RecourceTransferType | Enum | No | See [ResourceTransferType Values and Definitions](#ResourceTransferTypeValuesDefinitions).
|
| Side | String | No | SELL, BUY
|
| Timestamp | Datetime | Yes | The record timestamp. For example: 2024-01-17T18:36:31.345Z
|
| TransactionType | Enum | Yes | See [TransactionType Values and Definitions](#TransactionTypeValuesDefinitions).
|
| UniqueTxID | String | Yes | Unique identifier for a Profile transaction. Use with direction to guarantee unique line-item.
|

BalanceType Values and Definitions

The BalanceType field indicates which specific balance the row is referring to.
It provides a way to precisely follow movement of funds as transactions complete in the [Profile Transaction Report](#ProfileTransactionReport), and identify the volume of funds held in reserve or in pending transactions at the end of each day in the [Profile Balances Report](#ProfileBalancesReport).

| BalanceType Enum Value | Description
|
| --- | --- |
| AVAILABLE | Balance that is currently available to trade or transfer.
|
| PENDING_DEBIT | Balance that is currently reserved for pending debits. For example, an outgoing transfer has been requested but not completed. |
| TRADING | Balance that is currently reserved for trading. For example, a limit order has been placed but not filled. |
| PENDING_CREDIT | Balance that is currently reserved for pending credits. For example, an incoming transfer has been requested but not completed. |

Resource Values and Definitions

The Resource field denotes the category of transaction being recorded on each row of the [Profile Transactions Report](#ProfileTransactionReport).

| Resource Enum Value | Description
|
| --- | --- |
| CONVERSION | Stablecoin conversion transaction.
|
| EXECUTION | An execution of an order on the order book. There can be multiple executions for one order. |
| ORDER | A market or limit order placed for trading. Using either FIX or the v2 Order service. |
| QUOTE_EXECUTION | A Held Rate Quote transaction.
|
| TRANSFER | A transfer on or off the Paxos platform. For example, a wire withdrawal or crypto deposit. |
| WIRE_WITHDRAWAL_UPLOAD | A manually created wire withdrawal.
|

ResourceTransferType Values and Definitions

The ResourceTransferType identifies the direction of each transfer and whether it was a movement of fiat into or out of the Paxos Platform (WIRE_, SEN_), a movement of crypto asset into or out of Paxos (CRYPTO_), or a movement of crypto or fiat between profiles within the Paxos platform (PROFILE_TRANSFER).

Resource	TransferType	Description
TRANSFER	CRYPTO_DEPOSIT	A crypto deposit into Paxos.
TRANSFER	CRYPTO_WITHDRAWAL	A crypto withdrawal out of Paxos.
TRANSFER	INTERNAL_TRANSFER_CREDIT	Transfer received from another Profile.
TRANSFER	INTERNAL_TRANSFER_DEBIT	Transfer sent to another Profile.
TRANSFER	PAXOS_TRANSFER_CREDIT	Transfer received from another Peer.
TRANSFER	PAXOS_TRANSFER_DEBIT	Transfer sent to another Peer.
TRANSFER	SEN_DEPOSIT	Deprecated. Does not appear in new reports. A deposit into Paxos platform on the Silvergate Exchange Network.
TRANSFER	SEN_WITHDRAWAL	Deprecated. Does not appear in new reports. A withdrawal out of Paxos on the Silvergate Exchange Network .
TRANSFER	WIRE_DEPOSIT	A wire deposit into Paxos.
TRANSFER	WIRE_WITHDRAWAL	A wire withdrawal out of Paxos.

TransactionType Values and Definitions

The values of the TransactionType vary depending on the Resource.
The TransactionType denotes the specific purpose of the transaction.

Resource	TransactionType	Description
CONVERSION	CONVERSION_CANCELLATION	A transaction to unreserve funds for a created stablecoin conversion.
CONVERSION	CONVERSION_CREATION	A transaction to reserve funds for a stablecoin conversion.
CONVERSION	CONVERSION_SETTLEMENT	Settlement of the stablecoin conversion transaction.
EXECUTION	COMMISSION	A transaction to collect commission from an executed trade.
EXECUTION	SETTLE_BASE	Settlement of the base (crypto) side of the trade to/from the counterparty.
EXECUTION	SETTLE_QUOTE	Settlement of the quote (cash) side of the trade to/from the counterparty For example, a SELL order has been executed.
EXECUTION	SETTLE_UNRESERVE	A transaction to unreserve funds for trading because of a BUY side price improvement on an executed order. For example, a limit order used a BUY price of $50,000 but executed at $49,000).
ORDER	RESERVE	A transaction to reserve funds for trading. For example, a limit order has been placed.
ORDER	UNRESERVE	A transaction to unreserve funds for

trading. For example, a limit order has been canceled.
|
| QUOTE_EXECUTION | COLLECT_FROM_EXECUTOR | A record of transaction indicating a credit of the account.
|
| QUOTE_EXECUTION | FUND_EXECUTOR | A record of transaction indicating a debit of the account.
|
| SWAP | SWAP_TX | A 1:1 conversion of a USD or a stablecoin from one type (in the DEBIT Direction) to another (in the CREDIT Direction) in the same account (no movement) |
| TRANSFER | DEPOSIT_COMPLETION | A transaction to complete a deposit, resulting in funds being credited.
|
| TRANSFER | DEPOSIT_CREATION | A transaction to deposit funds into the Paxos platform.
|
| TRANSFER | DEPOSIT_FAILURE | A transaction to reserve the funds of a failed deposit into pending debit where they can move off the Paxos platform back to their source. |
| TRANSFER | FEE_DEBIT | A transaction to debit the fees upon completion of the transfer.
|
| TRANSFER | FEE_ENCUMBERMENT | A transaction to reserve the transfer fee.
|
| TRANSFER | INTERNAL_TRANSFER | A book transfer of funds to another profile under the same customer account.
|
| TRANSFER | PAXOS_TRANSFER | A book transfer of funds to another Paxos customer.
|
| TRANSFER | WITHDRAWAL_COMPLETION | A transaction to complete a withdrawal, resulting in the transfer of funds off the Paxos platform.
|
| TRANSFER | WITHDRAWAL_CREATION | A transaction to initiate a withdrawal typically reserving the debit amount. For example, a wire withdrawal or crypto withdrawal.
|
| TRANSFER | WITHDRAWAL_FAILURE | A transaction to return funds previously reserved for a failed withdrawal.
|

Team Access
Source: https://docs.paxos.com/guides/dashboard/admin/team

Manage user access and roles within your Entity.

Any user accessing the Paxos Dashboard must be authorized and assigned one or more [Roles](https://dashboard.paxos.com/admin/team-management/roles), each of which consists of specific permissions that control access to various actions. Paxos provides a set of [predefined roles](https://dashboard.paxos.com/admin/team-management/roles) that are available as soon as you [sign up](/guides/dashboard/account) and onboard a new Entity.

* To view, search and manage user access: [Admin > Team Management > Users](https://dashboard.paxos.com/admin/team-management/users).
* To audit the list of permissions associated with a Role: [Admin > Team Management > Roles](https://dashboard.paxos.com/admin/team-management/roles)
* To disable user access or change Roles, use the Edit Status dropdown in the User Actions menu at [Admin > Team Management > Users](https://dashboard.paxos.com/admin/team-management/users).

Passkey-Based Login

[Entity Managers](/guides/dashboard/roles#entity-manager) can manually invite users and assign their roles. Each user receives an email with a verification code and a link to [set

```
up their passkey and sign in](/guides/dashboard/signin#passkey).

<Warning>
  Users can have different [roles](/guides/dashboard/roles) across different [Entities]
(/guides/dashboard/organization#entity).
  When inviting users, it is recommended to provide organization-specific instruction on the
proper use and storage of [passkeys](https://www.passkeys.com/what-are-passkeys).

  We recommend using tools like [iCloud Keychain]
(https://support.apple.com/guide/passwords/passkeys-mchl4af65d1a/mac), [Windows Hello]
(https://support.microsoft.com/en-us/account-billing/signing-in-with-a-passkey-09a49a86-
ca47-406c-8acc-ed0e3c852c6d#), [Google Account]
(https://support.google.com/chrome/answer/13168025), [1Password]
(https://support.1password.com/save-use-passkeys/), [Proton Pass]
(https://proton.me/support/pass-use-passkeys), or other third-party password manager that
enables passkey sync across devices.
</Warning>

Follow these steps to invite users to your entity:

1. Go to [**Admin > Team Management**](https://dashboard.paxos.com/admin/team-
management/users)
2. Click **Invite Users**

<img alt="Invite Users" />

4. Enter one or more emails and select a role from the dropdown.
5. Click **Invite Users**

Users are marked as **Active** once they log into the Dashboard.

Entity Managers can also modify User Roles as needed:

1. Go to [**Admin > Team Management>Users**](https://dashboard.paxos.com/admin/team-
management/users)
2. Click on the **Edit Role** icon next to a user.
3. Select one or more roles from the dropdown.
4. Click the **Save** icon next to the dropdown.

<Tip>
  Users can only be invited with the same email address to one Organization. If a user
cannot be invited to your Organization because they're already part of another, they have
two options:

  1. **Use an alternative email address**: Many email providers support plus addressing
(e.g., `name+something@yourorganization.com`)
  2. **Leave the other Organization**:
     * Sign in to their account
     * Click **Organization** in the top left corner
     * **Leave Organization** option is at the bottom of the page

  Once they leave the other Organization, they can be invited to your Organization.
</Tip>

## SSO-Based Login

<Tip>
  Interested in using SSO?

  Paxos supports SAML and OIDC supported Identity Providers. Contact [Support]
(https://support.paxos.com) to get started.
</Tip>

When using [Single Sign-On (SSO)](#sso), instead of inviting users individually, an Entity
Manager uses the [Role Mapping interface](https://dashboard.paxos.com/admin/team-
```

management/mapping) to map Roles to user groups within your organization's Identity Provider (i.e., Okta, Azure AD).

Typically, you work with your IT team to leverage existing groups; however, you may need to add new Identity Provider groups to match your expected Dashboard workflows.
Once you map the group to an existing [Dashboard Role](/guides/dashboard/roles), the next time users [sign in with SSO](/guides/dashboard/signin#sso) their permissions will update.

Follow these steps to map Identity Provider groups to Paxos Dashboard Roles:

1. Go to [**Admin>Team Management>Mapping**](https://dashboard.paxos.com/admin/team-management/mapping).
2. Click **Add Mapping**.
3. Enter the Group Name exactly as it appears inside your Identity Provider's configuration.
4. Enter one or more Roles to associate with this Group.

Any user with a user attribute that contains the Group will automatically be assigned the associated Role on login.

Convert
Source: https://docs.paxos.com/guides/dashboard/convert

Implement guaranteed 1:1 conversions between USD and Paxos-supported stablecoins.

Go to the [Dashboard](https://dashboard.paxos.com/) and click **Convert** in the top-right corner.

1. Select the **Asset** *to convert from*. For example, select USD to convert to a Paxos-issued stablecoin.
2. Choose the **Source** where the asset is located (a Profile or External Account/Wallet).
3. Select the **Asset** to convert.
4. Choose the **Destination** where the converted asset should go (a Profile or an External Account/Wallet).

Go to [Transactions > Asset Movements](https://dashboard.paxos.com/dashboard/transactions/asset-movements) or [Transactions > Conversions](https://dashboard.paxos.com/dashboard/transactions/conversions) to monitor activity.

> Can't find the right conversion options?
> The desired option may not be supported by the [Entity](/guides/dashboard/organization#entities) or by the Paxos platform.
> Reach out to your [Entity Manager](/guides/dashboard/roles#entity-manager) or [contact us](https://support.paxos.com/hc/en-us/requests/new) for help.

Deposit
Source: https://docs.paxos.com/guides/dashboard/deposit

Send cash or crypto to the Paxos platform.

Go to the [Dashboard](https://dashboard.paxos.com/) and click **Deposit** in the top-right corner to generate **Deposit Instructions** for sending USD or crypto to the Paxos platform.

1. Select the **Asset** and corresponding crypto or fiat **Network** for the deposit. For bank wire deposits, specify the routing type.
2. Choose the [Profile](/guides/dashboard/organization#profile) where the assets will be deposited on the Paxos platform.
Optional: Save the deposit instructions to make them available for future use an on [Saved Instructions](https://dashboard.paxos.com/dashboard/saved-instructions).
3. Off the platform, use the generated instructions to send the asset to the Paxos platform.

Go to [Transactions > Asset Movements](https://dashboard.paxos.com/dashboard/transactions/asset-movements) to monitor activity.

Events
Source: https://docs.paxos.com/guides/dashboard/events

View and monitor webhook events from the Paxos platform.

View your most recent webhook events from the Dashboard via the **Webhooks** → [**Events**](https://dashboard.paxos.com/dashboard/developer/webhooks/events) tab.

<Frame>
  <img alt="Events view in Dashboard" />
</Frame>

Filter events

Filter events by:

* **Created at**: Filter events by date
* **Event type(s)**: Filter by specific event types
* **Live or test events**: Toggle between live and test events

Click **View** for any event to see the full event payload.

Each event in the Dashboard links directly to its corresponding event type documentation in the [API Reference > Webhooks](/api-reference/webhooks/identity-documents-required) section, where you can find detailed payload schemas and field descriptions.

Undelivered events

Events may fail to deliver to your webhook endpoint due to network issues, endpoint unavailability, or authentication failures. When this happens, the event will show an undelivered status.

<Frame>
  <img alt="Undelivered event indicator" />
</Frame>

<Frame>
  <img alt="Undelivered event details" />
</Frame>

To recover from failed webhook deliveries, use the [List Events](/api-reference/endpoints/events/list-events) API to query for missed events.

For information about webhook delivery behavior, retry policies, and rate limits, see the [Retries and Limits](/guides/webhooks/retries-and-limits) guide.

<Info>
  For details on creating and managing webhooks, see [Webhooks](/guides/dashboard/webhooks).
</Info>

Fiat Accounts
Source: https://docs.paxos.com/guides/dashboard/fiat

View and manage banking information to deposit and withdrawal USD.

Go to [Fiat Accounts](https://dashboard.paxos.com/dashboard/fiat-accounts) to view banking information used to [deposit](/guides/dashboard/deposit) and [withdraw (transfer)](/guides/dashboard/transfer) USD on and off the Paxos platform.
Using the Actions menu, review existing banking account details, including the banking network, owner and other account information.

Deleting a saved fiat account from the Actions menu permanently removes it from the

platform.
Any future transactions using the fiat account will fail unless you add it again.

Add Fiat Account

When adding banking information, use a street addresses.
Do not use a PO Box for any banking information.

1. Go to [Fiat Accounts](https://dashboard.paxos.com/dashboard/fiat-accounts) and click **Add Account**.
2. Select the banking network.
3. Enter bank account details.
4. Provide account owner information if required.
5. Save the fiat account. Optional: Perform a test [deposit](/guides/dashboard/deposit) or [withdrawal](/guides/dashboard/transfer).

Paxos Dashboard
Source: https://docs.paxos.com/guides/dashboard/index

Securely deposit, convert, transfer and custody assets with Paxos.

<img alt="Paxos Dashboard" />

The [Paxos Dashboard](https://dashboard.paxos.com/) enables [treasurers](/guides/dashboard/roles#treasurer) and other institutional users to securely [deposit](/guides/dashboard/deposit) and [transfer](/guides/dashboard/transfer) fiat, stablecoins and other assets.
[Sign up for an account](https://dashboard.paxos.com/).

If you already have an institutional account, see [here](/guides/dashboard/migrate-to-dashboard) how to migrate.

<CardGroup>
  <Card title="Multi-Entity Experience" href="/guides/dashboard/organization" icon="building">
    Leverage multiple Profiles to organize balances and transactions.
  </Card>

  <Card title="Role-Based Access Control" href="/guides/dashboard/roles" icon="shield">
    Entity Managers can assign roles and manage permissions based on entitiy-specific responsibilities.
  </Card>

  <Card title="Mint" href="/guides/dashboard/mint" icon="repeat">
    Convert USD to Paxos-issued stablecoins.
  </Card>

  <Card title="Redeem" href="/guides/dashboard/redeem" icon="rotate">
    Deposit stablecoin and convert to USD.
  </Card>

  <Card title="Manage Team" href="/guides/dashboard/admin/team" icon="gear">
    Manage user access within your Entity.
  </Card>

  <Card title="Configure API Credentials" href="/guides/dashboard/admin/api" icon="key">
    Create and update an OAuth2 client.
  </Card>
</CardGroup>

Saved Instructions
Source: https://docs.paxos.com/guides/dashboard/instructions

View and manage instructions for depositing fiat and other assets onto the Paxos platform.

To access saved deposit instructions, go to [Saved Instructions](https://dashboard.paxos.com/dashboard/saved-instructions).

<Tip>
  Saved instructions are immutable.
  If your deposit requirements change, create a new set of instructions.
</Tip>

There are three types of deposit instructions:

* Deposit: The asset (Source) will be deposited directly into the selected Paxos Profile (Destination).
* Deposit > Convert: The asset deposited (Source) will be automatically converted into your chosen asset (Destination).
* Deposit > Convert > Transfer: The asset deposited (Source) will be automatically converted into your chosen asset and then immediately transferred to the selected external wallet or fiat account (Destination).

To download deposit instructions, select the **Actions** menu to open the instructions use **Export Instructions**.

Mint
Source: https://docs.paxos.com/guides/dashboard/mint

Convert USD to Paxos-issued stablecoins and receive them in an external wallet.

This guide walks you through the standard automated minting flow (**USD > Stablecoin**), where funds are sent via bank transfer and converted into stablecoins on supported blockchain networks. The steps are the same for USDG, PYUSD and USDP.

<Frame>
  <video>
    <source type="video/mp4" />
  </video>
</Frame>

What You'll Do

1. [Add a destination wallet address](/guides/dashboard/mint#withdraw-address) (This is where you'll receive the stablecoin).
2. [Create minting instructions](/guides/dashboard/mint#minting-instructions), which define:

* **How** you'll send USD to Paxos (SWIFT or ABA, DBS-ACT, CUBIX).
* **Which stablecoin** you want (USDG, PYUSD, USDP).
* **Where** the stablecoin should go (wallet + network).

3. [Send USD to the Paxos platform](/guides/dashboard/mint#send-usd) using the generated deposit details.

Paxos will automatically mint the stablecoin and send it to your wallet.

<img alt="Mint Workflow" />

Before you begin

Requirements

* [A verified Paxos account](https://dashboard.sandbox.paxos.com/signin).
* A role (ex:Treasurer) with permissions to **Add** or **Delete** crypto addresses, and **Create Conversion Rules**.

Supported Stablecoins and Networks

Asset	Supported Network	
USDG	Ethereum, Solana, X Layer	
PYUSD	Ethereum, Solana, Arbitrum, Stellar	
USDP	Ethereum	

❶ Add Destination Wallet Address

You must add a wallet address before minting. This is where your stablecoins will be sent.

<img alt="Minting Add Address" />

1. Navigate to [**Addresses**](https://dashboard.paxos.com/dashboard/addresses) in the Paxos dashboard.
2. Click **⊕ Address**.
3. Enter a **name** for the address and select the **blockchain network**.
4. Retrieve the external wallet address and paste it in the **Network Address** field.
5. Fill in the [beneficiary details](https://docs.paxos.com/dashboard/travel-rule) requirements.
6. Click **Save**

<Tip>
  Use the [**Approvals**](https://docs.paxos.com/dashboard/admin/approvals) functionality to require additional team members to review any new addresses and instructions before they are saved.
  This avoids potential mistakes around incorrect information and adds an extra layer of security. **Only approved addresses** can be used in any mint process. Similarly minting instructions **aren't active until approved**.
</Tip>

❷ Create Minting Instructions

Once your wallet address is added, configure the minting rules for USD > Stablecoin.

<Info>
  Minting instructions are reusable and immutable. Access [Saved Instructions](https://dashboard.paxos.com/dashboard/saved-instructions) to reuse them anytime you want to mint the same asset.
</Info>

1. Go to [**Dashboard**](https://dashboard.paxos.com/) **> Convert**.
2. Select **USD** as the asset you have.
<img alt="Minting Asset You Have" />
3. Select **External Account/Wallet** and then the fiat network you use to send USD to Paxos. If you choose **DBS-ACT**, it may need to be activated first. [Contact Support](https://support.paxos.com/hc/en-us) for details.
<img alt="Minting Select Source" />

<Tip>
  Use the [**Paxos Profile**](https://docs.paxos.com/dashboard/organization#profile) option if you want to hold your stablecoin in your current account.
</Tip>

4. Select a stablecoin (for this guide we're minting [USDG](https://docs.paxos.com/stablecoin/usdg)).

5. For the destination, select **External Account/Wallet** and then choose one of the available networks and one of the existing **Addresses**.

6. Name the instructions.
<img alt="Minting Name Instructions" />

7. Click **Generate Deposit Instructions** to review the minting instructions. You can also download them for reference when sending USD to Paxos.

<Tip>
  Test the minting instructions with a small amount before minting large volumes.

```
</Tip>

## ❸ Send USD to Paxos

Use the [Deposit instructions](/guides/dashboard/deposit) to send wire funds to Paxos.

<Warning>
  <img alt="Minting Account Identifier" />
</Warning>

Once the funds are received, Paxos automatically executes the minting instructions and sends
the requested stablecoin to the specified wallet.

## ❹ Review Transaction Status

Track your minting progress from the **Transactions >Asset Movements** section. You'll see
two entries:

* **Fiat Deposit**: It usually takes a minute or two for the system to show the associated
* **Crypto Withdraw**: The actual crypto withdraw may take anywhere from seconds to hours,
depending on the blockchain, mint amount and off-business-hour transactions.

Transactions have the following status:

* **Pending**: The transaction is executing, which may include a manual review. If a
transaction is pending for an extended duration, contact Support.
* **Failed**: If a transaction shows the failed status, contact Support.
* **Complete**: The transaction is successful.

<Tip>
  Crypto Network Fees: Crypto network fees are calculated at the time of withdraw and
deducted from the total deposit amount. Use the **View** action to see a fee breakdown and
other transaction details. <img alt="Minting Transactions" />
</Tip>

## Alternate Minting Flows

Paxos supports manual minting flows with a number of different options. Following are a few
options:

* [Deposit USD](/guides/dashboard/deposit), then perform a manual [convert]
(/guides/dashboard/convert) followed by a [manual transfer](/guides/dashboard/transfer).
* Use **Convert** to deposit USD and [convert](/guides/dashboard/convert) it to a
stablecoin, keeping it on-platform in the Profile of your choice, followed by a [manual
transfer](/guides/dashboard/transfer).

<Tip>
  Can't find the right minting options? The desired option may not be supported by the
[Entity](https://docs.paxos.com/dashboard/organization#entities) or by the Paxos platform.
Reach out to your [Entity Manager](https://docs.paxos.com/dashboard/roles#entity-manager) or
[contact us](https://support.paxos.com/hc/en-us/requests/new) for help.
</Tip>


# Complete Onboarding
Source: https://docs.paxos.com/guides/dashboard/onboard

Onboard an Entity to start using the Paxos platform.

```mermaid theme={null}
graph LR

    A(Enter Business Details) --> B(Review and Accept Terms)
    A --> C(Upload Supporting Documents)
    B --> D(Review and accept terms)
```
```

```
    C --> D(Verify ID)
    D --> E(Submit Application)
```

<Tip title="Explore Dashboard Sandbox">
  Go [here](https://dashboard.sandbox.paxos.com) to try Paxos Dashboard features in a sandbox environment.

  After signing up, select **Bypass Onboarding** to get started.
</Tip>

Paxos collects identifying information to ensure your [Entity](/guides/dashboard/organization#organization) complies with all regulations and requirements for the jurisdictions your business operates in. This involves entering business details, uploading organizational documents, and verifying IDs.

The process takes about \~15 minutes if you have everything ready, and Paxos may request additional information during review.

<Note>
  Depending on your business structure and operating jurisdiction, the review process can take anywhere from a day to weeks.
</Note>

1. Gather Supporting Documents

The list below can be used as a general guide for most institutions. Paxos may reach out to you for additional documentation as needed.

<AccordionGroup>
  <Accordion title="Valid ID">
    Provide a **scanned color** document (i.e., valid passport, driver's license, or national ID) for all Beneficial Owners, Authorized Users, and Persons with Management Control.

    This information is required for all platform users meeting the criteria, even if you have provided this previously.
  </Accordion>

  <Accordion title="Proof of Residential Address">
    Provide a scanned PDF not older than 6 months (e.g., utility bill, cell phone bill, or bank statement) for all Beneficial Owners, Authorized Users, and Persons with Management Control.

    This information is required for all platform users meeting the criteria, even if you have provided this previously.
  </Accordion>

  <Accordion title="Proof of Funds">
    Bank statement or other equivalent document clearly showing the ownership under the Institution's name and dated within the last 6 months. Provide Proof of Funds substantiating requested trading volume.
  </Accordion>

  <Accordion title="Organizational Documents">
    Provide **two** of the following documents:

    * Certificate of Incorporation
    * Articles of Incorporation
    * Certificate of Formation
    * Articles of Organization
    * National/State Government Registry filings, or equivalent
  </Accordion>

```
  <Accordion title="Evidence of Tax Identification Number / Registration Number">
    Ensure the number is issued by the Internal Revenue Service (for US entities) or
relevant governing body (for international entities).
  </Accordion>

  <Accordion title="Certificate of Good Standing or Equivalent">
    All Institutions that have been established for longer than 1 year must provide this
document. This must be a document issued by a government registry and must be dated within
the past year.
  </Accordion>
</AccordionGroup>

## 2. Enter Business Information

Provide basic business (Institution) details to help determine onboarding requirements and
ensure your use of the Paxos platform complies to the proper regulations and requirements
for the jurisdiction.

You will need to provide the following:

* Institution type, incorporation ID type and incorporation ID.
* The legal incorporation address.

### Funding Details

Let Paxos know what industry sector your business operates in, the USD volume you expect to
move to the Paxos platform, as well as the source of funds.

### Suitability Assessment

Depending on the business jurisdiction, provide additional details regarding your business
to ensure compliance with regional requirements when using the Paxos platform.

### Business Members

Add personal identifying information for individuals that have a leadership role in the
business.
Minimally, you will need to add a beneficial owner and a person with management control.
Depending on your business structure, you may need to add multiple persons.
An individual can perform more than one role.

## 3. Review and Accept Terms

Review and accept all applicable terms and conditions, pricing and fee information before
reviewing and accepting the entity onboarding information you provided.

## 4. Upload Documents

Before you can complete onboarding, provide Paxos with [supporting documents]
(/guides/dashboard/onboard#1-gather-supporting-documents) for your organization.
You an upload the documents in the web application. Paxos may reach out to you for
additional documentation as needed.

## 5. Verify ID

When the supporting documents are accepted, the final step is to provide individual identify
information, which usually consists of providing a government issued ID such as passport,
national ID card or driver license and taking a real-time "selfie" photo of you holding your
ID.

<Tip>
  **Tips to avoid common errors during ID verification:**

  * Make sure your webcam is enabled in your browser.
  * When uploading your ID, ensure all four corners are visible, the text is clear and
```

legible, and the ID is not expired.
  * For the real-time "selfie" photo, do not use a professional headshot. Take a new photo of yourself holding your ID document at or near the time of onboarding.
</Tip>

Organization, Entities and Profiles
Source: https://docs.paxos.com/guides/dashboard/organization

Learn more about the multi-entity experience.

The Paxos Dashboard supports a multi-entity experience, made up of three components: [Organization](#organization), [Entity](#entity) and [Profile](#profile).
Within the Organization, individual access is selectively provisioned across Entities, so an individual can only access the information and funds and based on their [roles](/guides/dashboard/roles) within the respective Entity.
Most implementations require use of multiple Profiles to organize balances and transactions on the Paxos platform.

<img alt="Mint Workflow" />

Organization

When you [sign up for the Paxos Dashboard](/guides/dashboard/account), you are creating [Organization Administrator](/guides/dashboard/roles#organization-administrator) credentials to log into a Dashboard Organization.
As the top of the hierarchy the Organization typically maps to the parent of a legal entity or business group, comprising one or more entities.

For example, if **My Company** is comprised of three separate legal entities, **My Company Asia**, **My Company Europe** and **My Company North America**, using **My Company** as the organization will enable you to onboard the entities, using the legal business names, within the same organization bucket.

Entity

Entities, typically mapped to teams, business groups, holding companies, or separate legal entities, are onboarded within the [Organization](#organization).

* Funds are segregated at the Entity level.
* Users belonging to a particular Entity can see balances, transfers, and other information on in the Entity they belong to.
* Roles & Permissions, APIs keys are scoped at an Entity level. For example, if an Organization has 3 entities, User A has a Treasurer role in Entity 1, a Viewer role in Entity 2, and no access to Entity 3. See [Roles and Responsibilities](/guides/dashboard/roles).
* [Organization Administrators](/guides/dashboard/roles#organization-administrator) who complete the onboarding for an Entity automatically become the [Entity Manager](/guides/dashboard/roles#entity-manager) for that new Entity. Entity Managers are allowed to assign roles, add users, map identity provider groups to roles, etc. Entity Managers can be reassigned later

Profile

Every entity has a system-generated default Profile.
Most implementations require use of multiple Profiles to organize balances and transactions on the Paxos platform.
Profiles are also used to move funds within the same Entity.
A Profile is equivalent to a crypto wallet, with the addition of holding your USD (fiat) balance.
For example, [depositing USD](/guides/dashboard/deposit) into a Profile is the first step when [minting](/guides/dashboard/mint) a stablecoin.
Those with the [Treasurer](/guides/dashboard/roles#treasurer) create Profiles.

Passkeys
Source: https://docs.paxos.com/guides/dashboard/passkeys

Learn more about using passkeys with the Paxos Dashboard.

Passkeys provide a secure and easier way to sign in to the Paxos Dashboard.
With [passkeys](https://passkey.org/), there are no passwords to remember and no two-factor authentication.
Under the covers, when you add a passkey you are creating cryptographic key pairs for Paxos Dashboard: one key is stored on the Paxos server and the other is stored in your [password manager](#recommended-managers) or on your device.
When you [sign in with a passkey](/guides/dashboard/signin#passkey), the Paxos server ensures you are using the correct passkey.

There are numerous ways to use passkeys; however, we recommend using a [password manager](#recommended-managers) that can sync across multiple devices for the most portable experience.

<Tip>
  Questions about passkeys?

  Start by contacting your IT organization.
  Your company may already have policies for using passkeys and can provide support when creating and using a passkey.

  Learn more about passkeys and [try the passkey demo](https://passkey.org/) on https://passkey.org.
</Tip>

Recommended: Use a Password Manager

We recommend saving and using passkeys with the following password managers in conjunction with a [compatible browser](#passkey-browsers).
Third-party password managers may require you to create an account and install additional browser plugins/extensions.
Check with your IT organization if you have any questions about password managers.

* [Google Password Manager](https://support.google.com/chrome/answer/13168025)
* [1Password](https://support.1password.com/save-use-passkeys/)
* [Proton Pass](https://proton.me/support/pass-use-passkeys)

If you can't use any of the recommended password managers, use a password manager that allows for passkey synchronization across devices.

<Tip>
  Before You Begin

  Before creating a passkey, check with your IT organization and the user documentation for your particular device for policies, procedures, hardware requirements and restrictions.
</Tip>

Browser Support for Passkeys

Minimum browser versions that support passkeys:

* Chrome 108
* Edge 108
* Safari 16.1
* Firefox 122. Limited support. Requires using the "Sign in with passkey" option.
* Opera 97

<Tip>
  Before You Begin

  Before creating a passkey, check with your IT organization and the user documentation for

your particular device for policies, procedures, hardware requirements and restrictions.
</Tip>

macOS Native Support for Passkeys

Starting with macOS 13, Apple's [iCloud Keychain](https://support.apple.com/guide/passwords/passkeys-mchl4af65d1a/mac) provides native support for passkey synchronization across devices.

<Tip>
  Before You Begin

  Before creating a passkey, check with your IT organization and the user documentation for your particular device for policies, procedures, hardware requirements and restrictions.
</Tip>

Windows Native Support for Passkeys

Microsoft's [Windows](https://learn.microsoft.com/en-us/windows/security/identity-protection/passkeys/?tabs=windows%2Cintune) provide native support for passkeys starting with Windows 10 version 1903 and Windows 11 version 22H2. Requires setting up Windows Hello.

<Tip>
  Before You Begin

  Before creating a passkey, check with your IT organization and the user documentation for your particular device for policies, procedures, hardware requirements and restrictions.
</Tip>

System Time Requirements

Passkey authentication requires your device's system time to be accurate. If your system time is more than 30 seconds off from the actual current time, authentication may fail.

<Tip>
  Keep Your System Time Synchronized

  To ensure reliable passkey authentication, use an NTP (Network Time Protocol) service to automatically keep your system time synchronized with an NTP server. Most operating systems include NTP configuration options. Contact your IT organization if you need assistance setting up time synchronization.
</Tip>

PAXG
Source: https://docs.paxos.com/guides/dashboard/paxg

Buy, Sell, or Transfer PAXG

This guide walks you through standard PAXG Buy, Sell, and Transfer flows, including advanced functionality to preview quotes.

<Frame>
  <video>
    <source type="video/mp4" />
  </video>
</Frame>

What You'll Do

1. Open the [Dashboard](https://dashboard.paxos.com): Navigate to the Assets table on the Dashboard landing page.
2. Locate PAXG Options: Next to PAXG, you’ll see three available actions: Buy, Sell, Transfer
3. Select and Complete Your Action:

```
* Buy:
  * Choose the profile that holds the fiat currency you want to use.
  * Review the current PAXG market price quote.
  * Click Submit to complete your purchase.
* Sell:
  * Choose the profile containing the PAXG you want to sell.
  * Review the current PAXG market price quote.
  * Click Submit to complete your sale.
* Transfer:
  * Select this option to withdraw PAXG to an external destination.
  * Follow the on-screen [Transfer](/guides/dashboard/transfer) instructions to complete
your withdrawal.

<Tip>
  PAX Gold transactions and price quotes are available during usual London gold market hours
(open weekly from 6pm EST on Sunday through 5pm EST on Friday; closed daily between 5-6pm
EST time)
</Tip>


# Redeem
Source: https://docs.paxos.com/guides/dashboard/redeem

Deposit stablecoin and convert to USD. Transfer USD to your bank.

Redemption allows you to convert Paxos-issued stablecoins into USD and send the funds to
your bank account.
Follow the steps below to complete this process using the **Convert** option in the
Dashboard.

<Frame>
  <video>
    <source type="video/mp4" />
  </video>
</Frame>

<Warning>
  Who can do this

  Only users with the **Treasurer** role can redeem stablecoins. [View all roles and
permissions](https://docs.paxos.com/dashboard/roles).
</Warning>

## What You'll Do

* Add a [**Fiat Account**](https://docs.paxos.com/dashboard/fiat).
* Convert a stablecoin to USD and transfer the funds to a bank account.

## Before you begin

<Tip>
  Make sure you've deposited stablecoins via [**Dashboard > Deposit**]
(https://dashboard.paxos.com/actions/deposit) before starting a redemption.
</Tip>

### Requirements

* [A verified Paxos account](https://docs.paxos.com/dashboard/signin)

* A **Treasurer** role with the [required permissions]
(https://docs.paxos.com/dashboard/roles).

### Supported Stablecoins and Networks
```

Asset	Supported Network	
USDG	Ethereum, Solana, X Layer	
PYUSD	Ethereum, Solana, Arbitrum, Stellar	
USDP	Ethereum	

❶ Add Fiat Account

Before you can redeem stablecoins, you need to add a [fiat account](https://docs.paxos.com/dashboard/fiat) in the Paxos Dashboard.

1. Go to the [Dashboard](https://dashboard.paxos.com/) > **Fiat Accounts**
2. Click **+ Fiat Account** in the top-right corner.<img alt="Adding Fiat Account" />
3. Select a network.
4. Enter account details.
5. Fill in recipient details.
6. Enter a mailing address.
7. Click **Save**.

<Tip>
Use the [Approvals](https://docs.paxos.com/dashboard/admin/approvals) functionality to require additional team members to review any new fiat accounts or instructions before they are saved. This avoids potential mistakes around incorrect information and adds an extra layer of security. **Only approved fiat accounts** can be used in the redemption process. Similarly redemption instructions **aren't active until approved**.
</Tip>

❷ Redeem Asset

1. Go to the [Dashboard](https://dashboard.paxos.com/) and click **Convert** in the top-right corner.
2. Select the **Asset** to redeem.<img alt="Select asset" />
3. Choose the **Source** where the asset is located (a Profile or External Account/Wallet). <img alt="Select source" />
4. Select the **Asset** to receive.<img alt="Select asset" />
5. Choose the **Destination** where the converted asset should go (a Profile or an External Account/Wallet).<img alt="Select source" />
6. Go to [Transactions > Asset Movements](https://dashboard.paxos.com/dashboard/transactions/asset-movements) or [Transactions > Conversions](https://dashboard.paxos.com/dashboard/transactions/conversions) to monitor activity.

<Tip>
Need help?

Redemption options may vary based on your account or [Entity](/guides/dashboard/organization#entities) configuration. Reach out to your [Entity Manager](/guides/dashboard/roles#entity-manager) or [contact us](https://support.paxos.com/hc/en-us/requests/new) for support.
</Tip>

Manage Payouts
Source: https://docs.paxos.com/guides/dashboard/rewards/manage-payouts

Set or update a payout address.

What is a payout address?

Your **payout address** is the address where Paxos will send your monthly USDG rewards. You must select one existing [withdrawal address](https://docs.paxos.com/dashboard/addresses) to designate as a payout address. Ethereum and Solana networks are currently the only networks supported for payouts.

<Warning>

You must set a payout address by month end in order to receive rewards. If you do not set a payout address before month end, your rewards will be deferred until the following month.
</Warning>

Set or update your payout address

<Warning>
Required permissions

* To set a payout address, you need a role with the **update payout address** permission (i.e. Treasurer) to perform this action.

* To view a payout address or statement, you only need a role with the **view payout address** permission and “view statement” permission (i.e. Entity Manager and Viewer roles).
</Warning>

1. Go to the **Rewards** tab in the Paxos Dashboard
2. In the **Payout Address** section, click the dropdown on the right
3. Choose an existing withdrawal address, or click **Add new address**
4. Click **Submit**

<img alt="Updating payout address" />

<img alt="Adding a new payout address" />

<img alt="Saving payout address" />

View your active payout address

See your configured address, network, and last update timestamp.

<img alt="Saving payout address" />

Monitor Addresses
Source: https://docs.paxos.com/guides/dashboard/rewards/monitor-addresses

Add your first monitoring address.

What is a monitoring address?

A **monitoring address** is a blockchain address that Paxos monitors daily for eligible activity tied to the Global Dollar Network. We recommend adding any addresses you expect to hold, receive, or mint USDG as a monitoring address in order to receive rewards for all of your USDG on-chain activity.

<Warning>
Monitoring addresses must be added by month end (23:59 UTC+0) in order to earn rewards for that month. Addresses added after month end will start earning rewards for the following month.
</Warning>

Add a monitoring address

1. Go to the **Rewards** tab in the Paxos Dashboard
2. Click **Add Monitoring Address**
3. Enter:

* Network
* Address
* (Optional) Nickname

4. Click **Submit**

<img alt="Adding a new address" />

Once you submit monitoring addresses, Paxos will validate that the format of the address is valid for a chosen network. Invalid addresses will be individually flagged and must be resolved or removed before you can upload a batch of monitoring addresses.
Paxos validates addresses using the following address format standards:

* EVM: [https://ethereum.org/en/developers/docs/accounts/#account-creation] (https://ethereum.org/en/developers/docs/accounts/#account-creation)
* Solana: [https://solana.com/docs/core/accounts#account] (https://solana.com/docs/core/accounts#account)

<Warning>
  For Solana, derived addresses (such as ATA’s) are NOT supported. Paxos derives the token accounts associated with your standard Solana wallet addresses. If you are a more advanced user and need support for derived addresses, please email [gdn-rewards@paxos.com] (mailto:gdn-rewards@paxos.com).
</Warning>

View monitoring addresses

See your list of monitored addresses, including:

* Network
* Address
* Nickname (if provided)
* Date added

Additionally, you can search by nickname, the address itself, or filter by network. You can also export your list of addresses directly from the Dashboard by clicking our **Export** icon.

<img alt="Monitored Addresses" />

Required Permissions

<Warning>
  You need a role with the “update monitoring addresses” permission (i.e. Treasurer) to perform this action.
</Warning>

FAQs

What’s the difference between a monitoring address, a withdrawal address, and a payout address?

A monitoring address is used by Paxos to determine how much your organization has earned in rewards by holding, minting, and accepting USDG on-chain.
A withdrawal address is an address your organization has registered with Paxos and can receive funds to on-chain from Paxos.
A payout address is designated withdrawal address where Paxos will pay out your USDG rewards

Can I edit a monitoring address?

You can edit the nickname. Network and address are permanent. If you need to change a monitoring address, simply add a new address via the steps above.

Can I delete a monitoring address?

No. If unused, a monitoring address will simply earn 0 rewards. For bookkeeping purposes, we plan to introduce the ability to “delete” a monitoring address later in 2025.

When do I need to add monitoring addresses by?

Before the last calendar day of the month at 23:59 UTC+0.

How does Paxos validate if a monitoring address is valid?

We validate addresses using standard address formatting conventions:

* EVM chains: [https://ethereum.org/en/developers/docs/accounts/#account-creation] (https://ethereum.org/en/developers/docs/accounts/#account-creation)
* Solana: [https://solana.com/docs/core/accounts#account] (https://solana.com/docs/core/accounts#account)

Overview
Source: https://docs.paxos.com/guides/dashboard/rewards/overview

Manage USDG rewards via the Paxos Dashboard.

<Info>
  Demo
  [Watch a Demo →](https://www.youtube.com/watch?v=jPUvOSNMyMc)
</Info>

Global Dollar Network partners can now manage USDG rewards via our self-serve rewards tools. Once onboarded to Paxos, you can manage everything directly from the Paxos Dashboard, or via our Rewards API endpoints.

To start earning, simply:

1. Add **monitoring addresses** to track eligible wallet activity
2. Set your **payout address** for receiving USDG rewards
3. View your **monthly rewards statements** and track your payouts

<Tip>
  Don’t see the Rewards tab?
  [Contact the Growth Team](https://globaldollar.com/#contact) to request access.
</Tip>

How it works

USDG rewards are based on the on-chain activity attributed to the monitoring addresses attributed to your organization. Paxos calculates rewards based on daily snapshots (taken at 23:59 +0 UTC), and distributes payouts once per month.
With our self-serve rewards product, you can:

* Add or update monitoring addresses at any time
* Set and update payout address
* View your rewards payouts

Key Rewards Concepts

Monitoring Address

A blockchain address that Paxos monitors on a daily basis to calculate your stablecoin rewards based on eligible on-chain activity. In order to receive rewards for using USDG, you must [register at least one monitoring address](.) that will hold, mint, or accept USDG on-chain. Examples of types of monitoring addresses you may want to add include:

* Omnibus wallet addresses for your exchange
* Dedicated wallets for your institutional custody business
* Payment addresses your organization uses to accept payments for goods/services

<Danger>
  End user self-custodial wallets are not yet supported. If you need to add self-custodial wallets for your end users, please reach out to your account contact or [support@paxos.com] (mailto:support@paxos.com).
</Danger>

Payout Address

A blockchain address that Paxos will send your monthly USDG rewards to on-chain. You can select a payout address from any withdrawal address added to your Paxos organization. [Learn how to set and configure payout addresses](.).

Statements & Payouts

Monthly rewards statements are shared by email. Payouts occur on a fixed schedule, one time per month.

Reward Payout Timeline

Time	Example Date	Event
T	May 31, 2025	Last day to add monitoring addresses for current month
T+20	June 20, 2025	Rewards statement emailed to your team (will be available in the Dashboard and via API soon)
T+25	June 25, 2025	Deadline to report any issues with your rewards statement
T+30	June 30, 2025	USDG rewards paid to your configured payout address

<Warning>
Monitoring addresses must be added by month end (23:59 UTC+0) in order to earn rewards for that month. Addresses added after month end will start earning rewards for the following month.
</Warning>

Timeline and Disputes
Source: https://docs.paxos.com/guides/dashboard/rewards/timeline-and-disputes

Monthly Rewards Timeline.

Paxos uses a fixed rewards timeline each month:

Milestone	Example Dates	What happens
Calendar Month	May 1 - May 30	- Paxos takes daily snapshots of on-chain activity for all your monitoring addresses. - Monitoring addresses added on during the month will be eligible to earn rewards.
T (end of month)	June 1 at 00:00 UTC+0	- Cutoff for adding new monitoring addresses. - Monitoring addresses added this date will NOT earn rewards for the prior month (i.e. wallets added on June 1 will not result in any reward payouts for May)
T+20	June 20	Rewards statement emailed to your team
T+25	June 25	Deadline to raise any issues or disputes with your reward statement
T+30	June 30	USDG rewards paid to your payout address

What to do

Before Month End (T):
Add or confirm monitoring addresses
T+20 → T+25:

```
* Review statement
* Raise any issues or disputes to Paxos

**Before T+30:**

* Confirm payout address is correct

**After T+30:**

* Confirm payout amount and destination matches statement amount

## Reviewing your rewards statement

Statements include:
Total amount of rewards earned
Your designated payout address
Breakdown of rewards earned by reward type
List of all monitoring addresses and their associated rewards
Breakdown of rewards earned under cash vs accrual methods
Statements are **emailed** to you on the 20th each month.

## Raising a dispute

1. Go to **Rewards** tab
2. Click **Report an Issue**
3. Fill in details (address, dates, issue)
4. Submit between T+20 and T+25


# Roles and Responsibilities
Source: https://docs.paxos.com/guides/dashboard/roles

Learn more about the default roles for your Entity.

Paxos offers a granular access management system that allows you to customize the level at
which you control access to various Dashboard actions. Users looking for basic functionality
have access to pre-defined Paxos Managed roles made up of a set of permissions. For more
flexibility, create your own Custom Roles to combine permissions into new roles with more
granular access control.

All roles and associated permissions are scoped at an Entity level.

<img alt="Mint Workflow" />

<Tip>
  Have questions about your role and access?

  Contact your [Entity Manager](#entity-manager) for help.
</Tip>

## Organization Administrator

All Organizations have at least one Organization Administrator with permission to onboard
Entities. Organization Administrators who complete the onboarding for an Entity
automatically become the [Entity Manager](#entity-manager) for that Entity.

## Entity Manager

Entity Managers assign roles, add users, map identity provider groups to roles, etc. Entity
Managers can [review Entity specific settings](https://dashboard.paxos.com/admin). Entity
Managers can be reassigned once an Entity has been created. Entity Managers have view
permissions across the Dashboard, but cannot perform treasury focused actions.

> Use the Entity ID on the [ Admin > Entity Settings](https://dashboard.paxos.com/admin)
when contacting [Support](https://support.paxos.com).
```

Treasurer

The Treasurer role enables users to:

* Create Profiles and update balances.
* Deposit, transfer and withdraw supported assets.
* Mint, convert and redeem Paxos-issued stablecoins.
* View reports.

Approver

The Approver can approve or reject any submitted action that requires [Approvals](https://docs.paxos.com/dashboard/admin/approvals).

Developer

The Developer can view, create, update and delete [API credentials](https://dashboard.paxos.com/admin/api).

Viewer

A Viewer has read-only access to view user roles and permissions, cash and crypto balances, deposit and transfer details, API keys, reports as well as conversion information.

Custom Roles

Custom roles enable organizations to define granular access control for users by specifying a tailored set of permissions and actions beyond the above predefined role templates.

<Tip>
  Custom Roles is currently in beta. Contact us [here](https://support.paxos.com/hc/en-us/requests/new) to add this to your account.
</Tip>

Access Business Account
Source: https://docs.paxos.com/guides/dashboard/signin

Sign in to the Dashboard using a Passkey or SSO.

To access the Dashboard, your [Entity Manager](/guides/dashboard/roles#entity-manager) will either invite you to register for a [passkey-based sign in](/guides/dashboard/admin/team#passkey-based-login) or enable access through your company's [Single Sign-On (SSO)](/guides/dashboard/admin/team#sso-based-login).

If you're unable to sign in or unsure which login method to use, contact your [Entity Manager](/guides/dashboard/roles#entity-manager) or IT team for help.

<Tabs>
  <Tab title="Sign In with Passkey">
    <img alt="Continue with Passkey" />

    If you have been invited to join an Organization by an [Entity Manager](/guides/dashboard/roles#entity-manager) for an existing [Entity](/guides/dashboard/organization#entity), use the link provided in your invite email to join your Organization's Dashboard account.

    <Steps>
      <Step title="First-Time Sign In">
        1. Provide your name, email address, and the verification code from the email we sent you.
        2. Click **Next** then **Create a Passkey**.
        3. Save the passkey for [subsequent sign ins](#passkey).

```
        <Note>
          If you saved the passkey locally, make sure you use the same device to sign in.
          Learn more [here](/guides/dashboard/passkeys).
        </Note>
      </Step>

      <Step title="Sign In with Passkey">
        1. Go to the [dashboard](https://dashboard.paxos.com/), select **Sign In**, click
the email input field then select your passkey.
        2. If your browser does not support passkey autofill, enter your email address and
click **Next**.
        3. Select the appropriate passkey if required.
      </Step>
    </Steps>
  </Tab>

  <Tab title="Sign In with SSO">
    <img alt="Continue with SSO" />

    1. Go to the [Dashboard](https://dashboard.paxos.com/).
    2. Select **Sign In**.
    3. Enter your work email address then click **Continue with SSO**.
  </Tab>
</Tabs>


# Transactions
Source: https://docs.paxos.com/guides/dashboard/transactions

Monitor Dashboard & API driven Paxos transactions and balances.

Go to [Transactions](https://dashboard.paxos.com/dashboard/transactions) to track and review
current and past activity.
Select either [Asset Movements](https://dashboard.paxos.com/dashboard/transactions/asset-
movements) to see deposits and transfers or [Conversions]
(https://dashboard.paxos.com/dashboard/transactions/conversions) to review assets that have
been converted and moved to another [Profile](/guides/dashboard/organization#profile) within
the same [Entity](/guides/dashboard/organization#entity).
A list of recent transactions is available for offline viewing using **Export**.

> When contacting [Support](https://support.paxos.com) about a transfer, include the unique
**Transfer ID** and **Group ID** in your message to help our agents find the correct
transaction.

## Travel Rule Actions

The Paxos platform supports [Travel Rule](/guides/dashboard/travel-rule) to ensure
regulatory compliance within certain geographies.
If any of your transactions are missing information due to Travel Rule requirements, you'll
see a **Requiring Action** section at the top of the [Transactions]
(https://dashboard.paxos.com/dashboard/transactions) page.
This section includes all transactions that need attention and action.


# Transfer
Source: https://docs.paxos.com/guides/dashboard/transfer

Move fiat or crypto off the Paxos platform or between Profiles.

Go to the [Dashboard](https://dashboard.paxos.com/) and click **Transfer** in the top-right
corner to send an asset to an external destination or to another [Profile]
(/guides/dashboard/organization#profile) within the same [Entity]
(/guides/dashboard/organization#entity).

## Transfer to an External Wallet or Bank Account
```

1. Select **To an External Address/Fiat Account**.
2. Choose the **Asset**. If sending crypto, select the **Network** for the transfer.
3. Select the Profile where the assets will be *transferred from* (the source).
4. Choose a saved address or fiat account where the asset will be *transferred to* (the destination).
Optional: [Create a new network address](/guides/dashboard/addresses#new-address) or [add a fiat account](/guides/dashboard/fiat).
5. Enter the **Amount** to transfer.
Optional: Add a note for the transfer.

Go to [Transactions > Asset Movements] (https://dashboard.paxos.com/dashboard/transactions/asset-movements) to monitor activity.

Approvals for fiat withdrawals

If your organization has [Approvals](/guides/dashboard/admin/approvals) enabled for fiat withdrawals, external fiat transfers require review and approval from another team member before they can be completed.

Transfer to a Different Profile Within the Same Entity

Ensure the destination [Profile](/guides/dashboard/organization#profile) already exists before beginning the transfer.

1. Select **To a different Paxos Profile**.
2. Choose the **Asset**.
3. Select the Profile where the assets will be *transferred from* (the source).
4. Choose the Profile where the assets will be *transferred to* (the destination).
5. Enter the **Amount** to transfer.
Optional: Add a note for the transfer.

Go to [Transactions > Asset Movements] (https://dashboard.paxos.com/dashboard/transactions/asset-movements) to monitor activity.

Transfer to a Different Paxos Entity

Move assets between two Entities belonging to the same Organization or to a different Organization on the Paxos platform.

> Transferring USD between Entities is prohibited in some jurisdictions.
> Contact [Support](https://support.paxos.com) if you run into any problems with this restriction.

Ensure the destination [Profile](/guides/dashboard/organization#profile) already exists before beginning the transfer.
This may require contacting someone outside your Organization to get the destination Profile ID.

1. Select **To a different Paxos Entity**.
2. Choose the **Asset**.

> If an asset is not listed, it is not available for transfer.

1. Select the Profile where the assets will be *transferred from* (the source).
2. Enter the Profile ID where the assets will be *transferred to* (the destination).
3. Enter the **Amount** to transfer.
Optional: Add a note for the transfer.

Go to [Transactions > Asset Movements] (https://dashboard.paxos.com/dashboard/transactions/asset-movements) to monitor activity.

> When contacting [Support](https://support.paxos.com) about a transfer, include the unique **Transfer ID** and **Group ID** in your message to help our agents find the correct transaction.

Travel Rule Compliance
Source: https://docs.paxos.com/guides/dashboard/travel-rule

Learn more about Travel Rule requirements and the blockchain.

[Entities](/guides/dashboard/organization#entity) onboarded to certain geographies must adhere to [Travel Rule](https://notabene.id/crypto-travel-rule-101/what-is-the-crypto-travel-rule) checks when depositing and withdrawing crypto to and from the Paxos platform.

The Crypto Travel Rule requires virtual asset service providers (VASPs) like banks, exchanges, custodial solutions, and financial services providers to identify and share details of the origin and destination of crypto transactions above a specific threshold.

> Reach out to [Support](https://support.paxos.com) with questions or problems.

Crypto Deposit Travel Rule Requirements

Incoming deposits from a new or unrecognized crypto address might need to be [explicitly resolved](/guides/dashboard/transactions).

* For deposits from individuals, the sender's first and last name must be provided.
* For deposits from institutions, the institution name must be provided.

Deposits that we do not already have this information for will be held in a Pending state until it is provided.
Once provided, we will credit the funds to your account.

Crypto Withdrawal Travel Rule Requirements

Crypto withdrawals can only be made to [saved addresses](/guides/dashboard/addresses) that include beneficiary details.

<Accordion title="Beneficiary details">
  * Beneficiary Type
    * Indicate whether the address belongs to an Individual or an Institution
  * Beneficiary Name
    * Provide the name of the beneficiary who will be receiving the funds
  * Address Type (Private / Non-Custodial or Exchange Hosted / Custodial)
    * A Private wallet address is one which you control the keys / seed phrase (e.g. Metamask)
    * A Custodial wallet address is one where a centralized wallet provider manages the keys for you (e.g. a wallet on a trading platform like Robinhood)
      * Note: if the provider you are looking for is not listed, unfortunately it's not supported yet. Please select 'Other' and reach out to our [Support](https://support.paxos.com) team to let us know who you would like to see.
</Accordion>

For customers onboarded to Paxos Global (PTE), to transfer crypto off the Paxos platform, the recipient address must be hosted by one of the hosting providers displayed in the drop-down. If the provider you are looking for is not listed, it is not supported yet. Please select "Other" as the option and reach out to our Support team to inform us of the provider you were looking for.

Failed Withdrawals due to Travel Rule

If a transaction has a status of Failed, and it is due to Travel Rule, you will see this indicated in the Transfer Details panel, which can be accessed by clicking **View** in the [transactions](/guides/dashboard/transactions) list.

Verified Users for Sensitive Permissions
Source: https://docs.paxos.com/guides/dashboard/verified-users-for-sensitive-permissions

Learn how Paxos verifies users who can initiate financial actions such as transfers, withdrawals, conversions, orchestration, and trading.

As part of Paxos’s ongoing commitment to regulatory compliance, certain user permissions in

the Paxos Dashboard require identity verification (KYC). Any user who can move funds or initiate sensitive financial actions on behalf of an institution must complete KYC before those permissions become active.

This guide explains which permissions require KYC, how users complete verification, and how administrators can manage and review KYC status across their team.

<Notice type="info">
  KYC is performed per user, not per entity. A user only needs to complete KYC once, even if they belong to multiple entities.
</Notice>

***

Why Identity Verification Is Required

Paxos is a regulated financial institution and must verify the identity of any user who can initiate asset movement or financial automation. KYC ensures that:

* Only authorized, verified team members can perform actions that move or manipulate assets
* Paxos meets regulatory requirements across multiple jurisdictions
* Institutions stay protected from unauthorized or fraudulent activity

KYC becomes required **only** when a user is assigned a role containing specific sensitive permissions.

***

Sensitive Permissions

Any user assigned a role (standard or custom) that includes one or more of the following sensitive permissions must complete KYC.

Category	Permission	Requires KYC
Transfers & Withdrawals	Make external fiat withdrawals	✅
	Make external crypto withdrawals	✅
	Transfer between Paxos profiles within the same entity	✅
	Transfer between Paxos profiles across entities	✅
Conversions	Create or delete conversion rules	✅
	Initiate stablecoin conversions	✅
Orchestration	Create or update orchestration rules	✅
	Create or update orchestrations	✅
Trading	Execute on an issuer quote for buying or selling an asset	✅

***

Sensitive Roles

* The **Treasurer** role is the only standard role that requires KYC.
* **Any Custom Role** that includes any of the sensitive permissions above will also require KYC.

<Notice type="warning">

  If you modify an existing Custom Role to include a sensitive permission, **all users assigned to that role will be required to complete KYC immediately**.
</Notice>

***

Complete Identity Verification

Users who require verification will automatically see a banner at the top of their Dashboard home page.

<img alt="KYC verification banner" />

Users can complete KYC by clicking **Complete Verification Now**, which opens a Persona-hosted verification flow. Users must provide:

1. A government-issued ID
2. Confirmation of personal details
3. A proof-of-residence document dated within the last 6 months

Most users are verified instantly. Some cases may require manual review and can take up to **24 hours**.

Once complete, users see a **Verified** badge in their Account menu:

<img alt="Frame 627.png" />

***

Monitor User Verification Status

Admins can monitor user verification status on the **Manage Team → Users** page.

Users who have not completed KYC appear with a **Pending Verification** indicator:

<img alt="Users table verification status" />

Once verified, the user’s dashboard updates automatically and all KYC-required permissions become available.

***

Impact of Not Completing KYC

Users cannot perform any of the following actions until they complete KYC:

* Transfers (internal or cross-entity)
* Fiat or crypto withdrawals
* Stablecoin conversions
* Orchestrations
* Trading activity

<Notice type="warning">
  If an institution has configured a compliance deadline, users will see a notice indicating when access to sensitive actions will be suspended.
</Notice>

If a user attempts an action requiring KYC, they will be redirected to complete verification first.

***

Using Test Environments

In Sandbox and non-production environments, users will see a **Bypass Verification** option

for testing and development:

<Notice type="info">
  Bypass Verification is **only** available in test environments and is never available in Production.
</Notice>

***

Designing Custom Roles With KYC in Mind

When creating or updating Custom Roles:

* Adding any sensitive-permission will require KYC
* Removing sensitive-permissions removes the requirement
* Existing users assigned to a modified role may become newly required to complete KYC

<Notice type="success">
  Best Practice: Maintain at least one KYC-verified operational user at all times to avoid workflow disruptions.
</Notice>

For guidance on creating and managing custom roles, see [Managing Roles & Permissions](/guides/dashboard/roles).

***

Troubleshooting

A user completed KYC but still sees the verification banner.\
Have them refresh the page or log out and back in. If the issue persists, contact Paxos Support.

Can admins upload documents on behalf of users?\
No. KYC must be completed directly by each user through Persona.

Does a user need to re-verify if they join a new entity?\
No. KYC is tied to the Paxos account, not the entity.\
However, they must complete KYC if they are assigned a role containing sensitive permissions.

<Tip>
  Questions? Contact [Paxos Support](https://support.paxos.com).
</Tip>

***

Related Documentation

* [Team Access](/guides/dashboard/admin/team)
* [Managing Roles & Permissions](/guides/dashboard/roles)
* [Paxos Dashboard](/guides/dashboard/index)

Webhooks
Source: https://docs.paxos.com/guides/dashboard/webhooks

Create and manage webhooks to receive real-time event notifications from the Paxos platform.

Use [Webhooks](https://dashboard.paxos.com/dashboard/webhooks) in Dashboard to create and manage webhook integrations that receive asynchronous event notifications when events occur on the Paxos platform.

<Note>
  * Each entity can have a maximum of **10 active webhooks**

```
  * Webhook names must be **unique** within your account
</Note>

For a complete guide on setting up webhook consumers and integrating with the Paxos
platform, see the [Webhooks Developer Guide](/guides/webhooks).

## View Webhooks

Navigate to the [Webhooks](https://dashboard.paxos.com/dashboard/developer/webhooks) section
under the Developer tab to view all configured webhooks for your account.

Each webhook displays:

* **Name**: The unique identifier for your webhook
* **URL**: The endpoint URL where events are delivered
* **Auth Type**: The authentication method (API Key or OAuth)
* **Created At**: When the webhook was created
* **Updated At**: When the webhook was last updated
* **Status**: Current status (Active, Pending, etc.)
* **Actions**: Available actions (View, Test, Delete)

Click **View** to display more details about your webhook, including event types, rate limit
(requests per second), and approval history.

## Create a Webhook

Before creating a webhook in Dashboard, ensure you have a webhook consumer endpoint ready to
receive events. See [Create a Webhook Consumer](/guides/webhooks/quickstart#create-a-
webhook-consumer) for implementation examples.

To create a new webhook:

1. Navigate to [Webhooks](https://dashboard.paxos.com/dashboard/webhooks)
2. Click **Create Webhook**
3. Configure the webhook settings:
   * **Name**: Enter a unique name for your webhook
   * **URL**: Enter your webhook consumer endpoint URL (must be HTTPS)
   * **Auth Type**: Select your authentication method (API Key or OAuth)
   * **Authentication**: Configure your selected authentication method:
     * **API Key**: Provide the header name and API key value that Paxos will include in
webhook requests
     * **OAuth**: Provide the OAuth endpoint URL, Client ID, and Client Secret
   * **Event Types**: Select which events you want to receive (Identity, Transfer,
Orchestration, etc.)
   * **Rate Limit**: Set the delivery rate limit (1-100 requests per second, default is 10)
4. Click **Create** to save the webhook

Once created, the webhook will show an **Active** status and begin receiving events based on
your selected event types.

### OAuth2 client authentication

When using OAuth2 authentication, Paxos obtains access tokens by sending a POST request to
the configured `client_url` using the [OAuth2 client credentials grant]
(https://datatracker.ietf.org/doc/html/rfc6749#section-2.3.1).

Paxos supports both standard client authentication methods and sends them simultaneously in
token requests to maximize compatibility with OAuth2 providers:

| Method                              | Description
| Format                                                                                  |
| ----------------------------------- | ---------------------------------------------------
------------- | ---------------------------------------------------------------------------
-- |
| `client_secret_basic` (recommended) | Client credentials sent in the Authorization header
```

```
as Basic auth | `Authorization: Basic
base64(url_encode(client_id):url_encode(client_secret))` |
| `client_secret_post`               | Client credentials sent in the request body as form
parameters    | `client_id=xxx&client_secret=yyy`
|

The request body always includes `grant_type=client_credentials` using `application/x-www-
form-urlencoded` format.

<Info>
  Paxos supports approvals for creating and deleting webhooks. You can enable approvals for
webhooks via the Admin → [Approvals](/guides/dashboard/admin/approvals) tab to add an
additional layer of security and control.
</Info>

## Test a Webhook

After creating a webhook, use the Test feature to verify your consumer endpoint is
configured correctly:

1. Navigate to [Webhooks](https://dashboard.paxos.com/dashboard/webhooks)
2. Click **Actions** → **Test** for the webhook you want to test
3. Select an event type to send as a test event
4. Click **Send Test Event**

The test event will be sent to your endpoint with `is_test=true` in the payload. Verify that
your consumer receives and processes the event correctly.

<Info>
  For information on handling test events in your consumer code, see the [webhook consumer
examples](/guides/webhooks/quickstart#create-a-webhook-consumer).
</Info>

## Update a Webhook

To update an existing webhook:

1. Navigate to [Webhooks](https://dashboard.paxos.com/dashboard/webhooks)
2. Click **View** for the webhook you want to update
3. Click **Edit**
4. Modify any combination of the following settings:
   * **Name**: Update the webhook name
   * **URL**: Change the endpoint URL
   * **Event Types**: Add or remove event subscriptions
   * **Auth Type and Credentials**: Update authentication configuration
   * **Rate Limit**: Adjust the requests per second limit
5. Click **Update Webhook** to apply your changes, or **Submit for Approval** if approvals
are required

<Info>
  If [approvals](/guides/dashboard/admin/approvals) are enabled for webhooks, updates will
require approval before taking effect.
</Info>

## Delete a Webhook

To delete a webhook:

1. Navigate to [Webhooks](https://dashboard.paxos.com/dashboard/webhooks)
2. Click **Actions** → **Delete** for the webhook you want to remove
3. Confirm the deletion

Once deleted, the webhook will no longer receive events and will not count toward your 10
webhook limit.
```

Errored webhooks

You should rarely see webhooks in an error state. Errors only occur when making modifications (Create, Update, or Delete) — there is no risk of webhooks randomly entering the error state once active. If this occurs, you can delete problematic webhooks and create new ones from the Dashboard.

Webhook Delivery and Monitoring

To view and monitor webhook events, including filtering by date, event type, and delivery status, see [Events](/guides/dashboard/events).

For information about webhook delivery behavior, retry policies, and rate limits, see the [Retries and Limits](/guides/webhooks/retries-and-limits) guide.

Create Developer Account
Source: https://docs.paxos.com/guides/developer/account

Sign Up for access to the Sandbox environment.

To create an account you will need an email address, the business name and country of incorporation, as well as a way to create a [passkey](https://www.passkeys.com/what-are-passkeys) using a [compatible device](https://www.passkeys.io/compatible-devices).

> Sandbox developer accounts are usually approved in less than one business day and take under an hour to create and onboard.

❶ Sign Up in Sandbox

Before you begin, ensure you are able to create and store a [passkey](https://www.passkeys.com/what-are-passkeys) on your device.
All modern [operating systems and browsers](https://www.passkeys.io/compatible-devices) support passkeys.

<Tip>
  Questions about passkeys?

  Start by contacting your IT organization. Your company may already have policies for using passkeys and can provide support when creating and using a passkey.

  Paxos recommends saving and using passkeys with:

  * [iCloud Keychain](https://support.apple.com/guide/passwords/passkeys-mchl4af65d1a/mac)
  * [Windows Hello](https://support.microsoft.com/en-us/account-billing/signing-in-with-a-passkey-09a49a86-ca47-406c-8acc-ed0e3c852c6d#)
  * [Google Account](https://support.google.com/chrome/answer/13168025)
  * [1Password](https://support.1password.com/save-use-passkeys/)
  * [Proton Pass](https://proton.me/support/pass-use-passkeys)
  * Other third-party password managers that enable passkey synchronization across devices

  Learn more about [using passkeys on the Paxos platform](/guides/dashboard/passkeys) or [try the passkey demo](https://passkey.org/) on https://passkey.org.
</Tip>

1. Go to https://dashboard.sandbox.paxos.com, select **Sign Up** and provide a name and email address to create an *Institutional (Business) account*. Individual account holders are not eligible for API access via the Dashboard.
2. Retrieve the verification code from the welcome email from Paxos and enter the code in the browser. If you don't get an email within a few minutes, check email filters and Spam/Junk folders for an email from `@paxos.com`. Contact [Support](https://support.paxos.com) if the email never arrives.
3. Create a passkey.
4. Provide basic business information. The **Country of Incorporation** and **What do you plan to use your account for?** fields determine which assets you will have access to.

❷ Onboard Developer Account

You have a choice:

1. **skip onboarding** which takes you directly to an approved account, or
2. experience the entire onboarding process, which you'd have to undergo in production

Skip Onboarding

If you choose to **skip onboarding** then click the "Bypass Onboarding" button which appears on the overall progress page next to the "Get Started" button.
Then proceed to the ❹ **Enable Developer Access** instructions on this page.

<img alt="Skip Onboarding" />

Experience the Onboarding Process

Otherwise, click the "Get Started" button and complete the first six onboarding steps.

<Tip>
  Use stubbed (fake) text when entering data.
  The information provided will not be used when creating the production account.
</Tip>

1. **Business Details**. Selecting **Corporation** as the institution type provides the quickest experience. The country field is pre-populated with the information you provided when creating the account.
2. **Funding Details**. Select **No** for the trust structure and nominee shareholder options.
3. Some account types will require you to fill out the **Suitability Assessment**. If you are not presented with this option, go to the next step. If you see the assessment: Select **Yes** and **Advanced** for the first two options.
4. **Business Members**. Open the edit dialog for the name you gave during account creation and provide the required fields. <mark>You can use fake (dummy) text</mark>.
   * **Beneficial Owner Designation**. Ensure **Yes** is selected. Give information. The **% of Ownership** should be `100`.
   * For **Authorized User Designation**, **Persons with Management Control Designation** and **Director Designation**, select **Yes**.
5. Accept the **Terms & Conditions** and **Pricing & Fees** then complete **Review & Verify**.

<Tip>
  Stop the onboarding process. Do not upload documents and go through ID verification.
</Tip>

❸ Contact Support

[Support](https://support.paxos.com) must activate your Developer account before you can use it.
To ensure a smooth process, include your email address and business (organization) name when [submitting a request](https://support.paxos.com/hc/en-us/requests/new).

You will receive an email from support confirming your Developer Sandbox account is good to go.

> Occasionally, [Support](https://support.paxos.com/hc/en-us) may reach out to you via email requesting additional information or if there is an issue creating the account.

❹ Enable Developer Access

<img alt="Edit Roles" />

Once the account is activated, you are assigned the [Entity Manager](/guides/dashboard/roles#entity-manager) role by default.

However, this role does not have write access to [Admin > API] (https://dashboard.sandbox.paxos.com/admin/api), where credentials are configured. You will need to add the [Developer](/guides/dashboard/roles#developer) role to your user.

1. Go to [**Admin > Team Management > Users**] (https://dashboard.sandbox.paxos.com/admin/team-management/users).
2. Under the **Actions** column, open the **Edit Status** dropdown and select **Edit Roles**.
3. Click in the **Edit Roles** form and select **Developer**.
4. Log out and sign in to start a new session.

> Once your user has the **Developer** role, you can [create API credentials] (/guides/developer/credentials).

AI-Assisted Development
Source: https://docs.paxos.com/guides/developer/ai-assisted-development

Use AI coding assistants effectively with Paxos documentation and API specifications.

The Paxos documentation is optimized for AI-assisted development through comprehensive resources that provide contextually-aware help with your integration.

Documentation Resources

llms.txt File

The `llms.txt` file is an industry standard that helps AI tools index content more efficiently, similar to how a sitemap helps search engines. It provides a structured overview of all available documentation pages.

<PreviewButton href="/llms.txt">Open the llms.txt for this site</PreviewButton>

Complete Documentation Compilation

The `llms-full.txt` file combines the entire documentation site into a single file as context for AI tools. You can paste a single URL as context for AI tools for more relevant and accurate responses.

<PreviewButton href="/llms-full.txt">Open the llms-full.txt for this site</PreviewButton>

API Specification

Our OpenAPI specification provides detailed API endpoints, request/response schemas, and error messages to ensure accurate implementation. This is particularly valuable for understanding exact API requirements and handling error cases properly.

<PreviewButton href="https://developer.paxos.com/docs/paxos-v2.openapi.json">Open the REST API Specification</PreviewButton>

Best Practices

When working with AI coding assistants:

1. **Reference the llms-full.txt** for comprehensive context about Paxos APIs and integration patterns
2. **Use the OpenAPI spec** for precise API implementation details
3. **Include specific error handling** based on documented error responses
4. **Follow authentication patterns** outlined in the developer guides

> Both documentation files are always up to date and require zero maintenance.

Migrate from v1 to v2 API
Source: https://docs.paxos.com/guides/developer/api-migrate

```
Learn how to migrate your REST integrations.

The Paxos v1 APIs have reached End of Life.
Access to all Paxos v1 APIs has been removed.
This change ensures all Paxos customers are using supported APIs.

Customers should migrate remaining usage from the v1 API as all functionality is now
available in [Paxos v2 APIs](/api-reference).
We recommend you test your integrations in Sandbox before applying the changes to your
integration in Production.

To help with the transition, this guide provides suggestions on implementing similar
functionality using the Paxos REST API (v2).

<Tip>
  If you have any questions, or run into any problems during the migration, contact
[support@paxos.com](mailto:support@paxos.com) to set up a time to discuss your concerns.
</Tip>

## Get Started in Sandbox

We recommend you test your integration in the Sandbox environment prior to deploying the
changes in production.
If not already done so, [sign up for a Sandbox account]
(https://dashboard.sandbox.paxos.com/).
Then [configure API credentials](/guides/developer/credentials).

| v1 API Endpoint
| v2 API Endpoint
|
| ---------------------------------------------------------------------------------------------
------------------------------------------ | ---------------------------------------------
---------------------------------------------------------------------------------------------
---------------------------------------------------------------------------- |
| GetActivities
| [List Transfers](/api-reference/endpoints/transfers/list-transfers)
|
| GetActivity
| [Get Transfer](/api-reference/endpoints/transfers/get-transfer)
|
| ListAutoConversions
| [List Transfers](/api-reference/endpoints/transfers/list-transfers)
|
| ListBankAccounts
| [List Fiat Accounts](/api-reference/endpoints/fiat-transfers/list-fiat-accounts)
|
| CreateBankAccount
| [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account)
|
| GetBankAccount
| [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account)
|
| ArchiveBankAccount
| [Delete Fiat Account](/api-reference/endpoints/fiat-transfers/delete-fiat-account)
|
| CreateCbitWithdrawal<br />CBIT is no longer supported. [Use CUBIX]
(https://support.paxos.com/hc/en-us/articles/31700769434004) instead. | [Create Fiat
Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal)
|
| CreateCryptoWithdrawal
| [Create Crypto Withdrawal](/api-reference/endpoints/crypto-withdrawals/create-crypto-
withdrawal)
|
| ListProfiles
```

```
| [List Profiles](/api-reference/endpoints/profiles/list-profiles)
|
| GetProfile
| [Get Profile](/api-reference/endpoints/profiles/get-profile)
|
| GetProfileBalances
| [List Profile Balances](/api-reference/endpoints/profiles/list-profile-balances)
|
| GetProfileDepositInstructions
| [Create Deposit Address](/api-reference/endpoints/deposit-addresses/create-deposit-
address) and<br />[Create Fiat Deposit Instructions](/api-reference/endpoints/fiat-
transfers/create-fiat-deposit-instructions) |
| CreateProfileTransfer
| [Create Internal Transfer](/api-reference/endpoints/internal-transfers/create-internal-
transfer)
|
| CreateWireWithdrawal
| [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal)
|
| GetCustStatus
| [Get Identity](/api-reference/endpoints/identity/get-identity)
|
| CreatePeerTransfer
| [Create Paxos Transfer](/api-reference/endpoints/paxos-transfers/create-paxos-transfer)
|

<Tip>
  If you have any questions, or run into any problems during the migration, contact
[support@paxos.com](mailto:support@paxos.com) to set up a time to discuss your concerns.
</Tip>

## Removed Endpoints

The following APIs have been removed as there is no current v2 use case for them.

* ArchiveProfile
* GetCryptoAddress
* CreateCryptoAddress
* CreateSenWithdrawal
* CreateSignetWithdrawal
* CreateIntrabankWithdrawal
* GetBankAccountAutoConversionInstructions
* GetCryptoAddressAutoConversionInstructions
* UpdateCryptoDeposit
* RejectCryptoDeposit


# Authenticate
Source: https://docs.paxos.com/guides/developer/authenticate

Generate an authentication token.

The APIs use industry standard OAuth2 for authentication.
Most users find success with one of the libraries on the [OAuth2 website]
(https://oauth.net/code).
The following URLs can be used when using an off-the-shelf OAuth2 library:

| Environment | Root URL                                                                  | Full
Path                                                                                      |
| ----------- | ------------------------------------------------------------------------- | -------
---------------------------------------------------------------------------------------- |
| Sandbox     | [https://oauth.sandbox.paxos.com](https://oauth.sandbox.paxos.com) |
[https://oauth.sandbox.paxos.com/oauth2/token](https://oauth.sandbox.paxos.com/oauth2/token)
|
| Production  | [https://oauth.paxos.com](https://oauth.paxos.com)                 |
```

https://oauth.paxos.com/oauth2/token
|

❶ Add Scopes (Client Permissions)

When authenticating, include the scopes (**Client Permissions**) necessary for the client to complete the intended actions.

> Scopes for each endpoint are listed in the **Authorizations** section in the [API Reference docs](/api-reference).
> The [Market Data](/api-reference/endpoints/market-data) and most [Pricing](/api-reference/endpoints/pricing) endpoints do not require authorization.

For example, the following scopes (space delimited) should provide sufficient permissions to [mint](/guides/developer/mint), [redeem](/guides/developer/redeem), and [convert](/guides/developer/convert) Paxos-isssued stablecoins:

```shell theme={null}
conversion:read_conversion_stablecoin
conversion:write_conversion_stablecoin
funding:read_profile
funding:write_profile
transfer:read_deposit_address
transfer:read_transfer
transfer:read_fiat_account
transfer:read_fiat_deposit_instructions
transfer:write_internal_transfer
transfer:write_crypto_withdrawal
transfer:write_deposit_address
transfer:write_fiat_account
transfer:write_fiat_deposit_instructions
transfer:write_fiat_withdrawal
```

❷ Get Access Token

Every endpoint that requires a **Scope** must be accompanied by an "Authorization"` header with a value that follows the \"Bearer {access_token}"` schema.

Sandbox

To authenticate with https://oauth.sandbox.paxos.com/oauth2/token, use your [credentials](/guides/developer/credentials) to create a bearer token.
The authentication request must include `{client_id}` (**Client ID**) and `{client_secret}` (**Client Secret**) configured for your [API credentials](/guides/developer/credentials).
Include sufficient `{client_scopes}` (**Client Permissions**).

```shell highlight={5} theme={null}
curl --location 'https://oauth.sandbox.paxos.com/oauth2/token' \
--form grant_type=client_credentials \
--form client_id={client_id} \
--form client_secret={client_secret} \
--form scope='{client_scopes}'
```

Production

To authenticate with https://oauth.paxos.com/oauth2/token, use your [credentials](/guides/developer/credentials) to create a bearer token.
The authentication request must include the `{client_id}` (**Client ID**) and `{client_secret}` (**Client Secret**) configured for your [API credentials](/guides/developer/credentials).
Include sufficient `{client_scopes}` (**Client Permissions**).

```shell highlight={5} theme={null}
curl --location 'https://oauth.paxos.com/oauth2/token' \
--form grant_type=client_credentials \
--form client_id={client_id} \
--form client_secret={client_secret} \
--form scope='{client_scopes}'
```

Confirm the response includes the requisite scopes and save the `access_token` to use in the request authorization header (`-H "Authorization: Bearer {access_token}"`).

```json highlight={2,4} theme={null}
{
 "access_token": "{access_token}",
 "expires_in": 3599, // Seconds (59 Minutes and 59 Seconds)
 "scope": "{client_scopes}",
 "token_type": "bearer"
}
```

Once you have the `access_token`, [make an API call in Sandbox](/guides/developer/request).

Assets and Blockchains
Source: https://docs.paxos.com/guides/developer/blockchains

Learn more about supported assets, stablecoins and blockchains.

The assets and crypto networks listed on this page are fully supported on the Paxos Platform.
These assets are supported in the context of three main use cases:

* Deposit and withdraw USD via Fedwire, SWIFT and CUBIX. Get started with [fiat transfers](/guides/developer/fiat-transfers).
* Use stablecoins for [deposits](/api-reference/endpoints/deposit-addresses), [withdrawals](/api-reference/endpoints/crypto-withdrawals) and [transfers](/api-reference/endpoints/transfers). Learn more about stablecoin [conversions](/guides/developer/convert) and [payments](/guides/payments).
* The crypto trading assets are primarily available for [Crypto Brokerage](https://paxos.com/crypto-brokerage/) partners to buy, sell deposit and withdraw via APIs, in addition to holding the assets on the Paxos platform. Trading pairs that incorporate USD are also available in [USDP](/guides/stablecoin/usdp) and [PYUSD](/guides/stablecoin/pyusd). Read the [orders reference docs](/api-reference/endpoints/orders) and the [HRQ guide](/guides/crypto-brokerage/quotes/index).

Stablecoins

Stablecoin	Arbitrum One	Ethereum	Ink	Polygon PoS	Solana	Stellar	X Layer
Binance USD ([BUSD](/guides/stablecoin/busd))[*](#busd-restrictions)	--	✅	--	--	--	--	--
Global Dollar ([USDG](/guides/stablecoin/usdg))	--	✅	✅	--	✅	--	--
Pax Dollar ([USDP](/guides/stablecoin/usdp))	--	✅	--	✅	--	--	--
PayPal USD ([PYUSD](/guides/stablecoin/pyusd))	✅	✅	--	✅	✅	--	--
USD Coin (USDC)	--	✅	✅	✅	--	--	--

<small>

```
    \* [BUSD](/guides/stablecoin/busd) withdrawals are no longer available on the Paxos
Platform. [BUSD](/guides/stablecoin/busd) (ERC-20) deposits are supported to redeem for USD
or convert to [USDP](/guides/stablecoin/usdp). **Do not deposit BUSD via Binance Smart Chain
(BSC)**.
  </em>
</small>

<small>
  <em>
    † [USDL](https://docs.liftdollar.com/index.html) is not available to residents of the US
and certain other countries. [Learn more](https://liftdollar.com/terms-and-conditions/).
  </em>
</small>

## Trading and Custody

| Digital Asset                                | Bitcoin | Bitcoin Cash | Ethereum |
Litecoin | Solana |
| ---------------------------------------------- | :-----: | :----------: | :------: | :-----
-: | :----: |
| Aave (AAVE)                                  |    --   |      --      |     ✅    |    --
|   --   |
| Bitcoin (BTC)[‡](#btc)                       |    ✅    |      --      |    --    |    --
|   --   |
| Bitcoin Cash (BCH)                           |    --   |       ✅      |    --    |    --
|   --   |
| Chainlink (LINK)                             |    --   |      --      |     ✅    |    --
|   --   |
| Ethereum (ETH)                               |    --   |      --      |     ✅    |    --
|   --   |
| Litecoin (LTC)                               |    --   |      --      |    --    |     ✅
|   --   |
| Pax Gold ([PAXG](https://paxos.com/paxgold/)) |    --   |      --      |     ✅    |    --
|   --   |
| Polygon (MATIC)<sup>[§](#matic)</sup>        |    --   |      --      |     ✅    |    --
|   --   |
| Solana (SOL)<sup>[¶](#sol)</sup>             |    --   |      --      |    --    |    --
|    ✅   |
| Uniswap (UNI)                                |    --   |      --      |     ✅    |    --
|   --   |

<small>
  <em>
    ‡ Supported wallet types for BTC withdrawals: P2WPKH, P2WSH, P2PKH, P2SH, and P2TR
(Taproot).
  </em>
</small>

<small>
  <em>
    § Trading or custody of MATIC is not available to residents of the US.
    Effective September 17, 2024, users can no longer buy MATIC.
    Users should exit their MATIC positions or transfer MATIC off-platform.
    As of October 3, 2024, users can only transfer MATIC off-platform.
    Contact [support@paxos.com](mailto:support@paxos.com) with questions or issues.
  </em>
</small>

<small>
  <em>
    ¶ Trading or custody of SOL is not available to residents of the US.
  </em>
</small>

## Blockchain Transactions
```

Digital assets may be deposited and withdrawn to and from your Paxos account 24/7.
Deposits are credited to your account once the requisite blockchain confirmations are complete.
Withdrawals to new addresses may be subject to additional compliance review if the automated checks fail.
Withdrawals may take longer on US and Singapore national holidays.

Required Confirmations

Paxos considers a blockchain transaction (deposit or withdraw) complete once the required number of blockchain confirmations have been completed.

Crypto Network	Confirmations	Approximate Processing Time
Arbitrum One	40	2 minutes
Base	84	3 minutes
Bitcoin	3	30 minutes
Bitcoin Cash	15	150 minutes
Ethereum	12	3 minutes
Litecoin	12	30 minutes
Polygon PoS	256	9 minutes
Solana	32 slots	16 seconds
Stellar	1	5 seconds
X Layer	168	3 minutes

API Breaking Change Policy
Source: https://docs.paxos.com/guides/developer/breaking-change/policy

Learn about what qualifies as a breaking change and the what happens when one is necessary.

The policy below applies only to Partners with a fully executed and active SLA.
Paxos will make commercially reasonable efforts to notify users without a service agreement of breaking changes.

<Tip>
  See the [Changelog](/changelog) for current breaking changes.
</Tip>

Definitions

"Core Platform Services” means the services provided by Paxos that enable End Users to (i) onboard onto the Paxos platform (if applicable given the integration utilized by the Customer) and (ii) submit and execute Orders to buy and sell certain Cryptocurrency Assets from or to other individuals via the Exchange Platform or Paxos' liquidity providers using U.S. dollars or other Cryptocurrency Assets, and (iii) transfer Cryptocurrency Assets to and from the Exchange Platform.
The Core Platform Services include (a) market and order data streams provided via websockets, (b) the Paxos FIX Service (if applicable given the API integration utilized by the Customer), (c) Reconciliation Reports and (d) the following v2 REST API services: Profiles, Markets, Orders, Quotes, Quote Executions, Pricing, Identity, Transfers and Accounts.
For the avoidance of doubt, any service designated as a "Preview, “Beta” or “Alpha” in Paxos's API documentation is not included as part of the Core Platform Services.

“Exchange Platform” means Paxos' cryptocurrency exchange platform and services whereby individuals can buy or sell certain Cryptocurrency Assets from or to other individuals or liquidity providers using U.S. dollars or other Cryptocurrency Assets.

“Paxos FIX Service” means the Paxos service that allows Customer to send messages to and receive messages from the Exchange Platform using the FIX protocol.

Breaking Changes

In the normal course of business, Paxos may need to make changes that will require Customer to adjust its integration with Paxos (**“Breaking Changes”**). When Paxos makes a Breaking Change to the Core Platform Services, Exchange Platform, or FIX Service, Paxos will ensure the previous functionality remains available to Customer for at least ninety (90) days to provide Customer time to make necessary changes.
When Paxos makes a Breaking Change to Reconciliation Reports, Paxos will either allow Customer to immediately opt-in to the new version, or provide Customer with both the new and old version of the Reconciliation Reports for at least ninety (90) days (the **“Change Policy”**).

Breaking Change Notifications

When Paxos makes a Breaking Change to the Core Platform Services or FIX Service, Paxos will issue a Breaking Change notification.
Such notification will be sent at least ninety (90) days ahead of the change to all registered Customer Service Contacts via email and include **“Breaking Change Notification”** in the subject.

Types of Breaking Changes

For reference, the following changes qualify as examples of Breaking Changes:

* Removing or renaming an API service.
* Removal of a field or enumerated value from an API response.
* Removing or renaming a column in the Reconciliation Reports.
* Change of a request field or parameter from non-mandatory to mandatory.
* Change of a field or parameter name.
* Addition of new validation rules to a field, resulting in previously accepted requests being rejected.
* Modification of the data type of a field (for example, converting a single object to a list of objects).

This list is non-exhaustive and Paxos may identify additional Breaking Changes in its discretion.

Backwards Compatible Changes

Backwards compatible changes are any changes that (i) are not explicitly identified by Paxos as Breaking Changes, (ii) do not materially reduce any functionality with respect to the Core Platform Services and (iii) do not materially change the schema or query parameters with respect to the Core Platform Services (collectively, **“Backwards Compatible Changes”**).
All users of Paxos APIs should expect and manage identified Backwards Compatible Changes without error.

For reference, the following changes are considered Backwards Compatible Changes:

* Addition of a new API service.
* Addition of a method to an API service.
* Addition of a new non-mandatory field, parameter, or header to an API request or response.
* Changing the length or format of a field identified as a string in the API reference documentation.
* Addition of new enumerated values, including but not limited to status codes or error codes.
* Changes to error messages.
* Addition of a new report to the Reconciliation Reports.
* Addition of a new column to the Reconciliation Reports.
* Modification of the order of columns to the Reconciliation Reports.
* Deprecation of a field in a request or response without removing it.
* Change in order of fields in an object, or objects in an array.
* Addition of a new FIX tag.

This list is non-exhaustive and Paxos may identify additional Backwards Compatible Changes in its discretion.

End of Life

If Paxos decides to entirely remove or no longer support a Core Platform Service, Paxos will provide Customer Service Contacts with an **“End of Life”** notification at least ninety (90) days in advance of the change.

Exceptions

This policy only applies to services listed as Core Platform Services.
Paxos will use commercially reasonable efforts to provide advance notice of changes to other services over email to all Customer Service Contacts.

Required Changes

Paxos may make breaking changes without notice in order to fix material defects or to comply with legal obligations.
In addition, Paxos may throttle requests or disable access to any or all components of the Core Platform Services if Paxos determines that a Customer's usage of the service poses a risk to the stability of the platform.
In the case where Paxos manually throttles requests or disables access, Paxos will immediately notify all registered Customer Service Contacts within forty-five (45) minutes of taking such action.

Convert
Source: https://docs.paxos.com/guides/developer/convert

Implement guaranteed 1:1 conversions between USD and Paxos-issued stablecoins.

<Warning title="Stablecoin Conversions Deprecation Notice">
  The Stablecoin Conversions API will be deprecated.

  Paxos will migrate all active conversion rules to the [Orchestrations API](/guides/developer/orchestrations/orchestrations) format by December 2025.

  Customers should transition to the Orchestrations API to ensure continuity of service.
</Warning>

Next, use the [Stablecoin Conversion API](/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion) to easily convert USD to any [supported asset](/guides/developer/convert#assets), and vice verse, without any fees.
Keep track of all your conversions with [List Stablecoin Conversions](/api-reference/endpoints/stablecoin-conversion/list-stablecoin-conversions) or [lookup a single conversion](/api-reference/endpoints/stablecoin-conversion/get-stablecoin-conversion).

> If you've already authenticated and have USD and USDG balances in a Profile, skip ahead to the [request a conversion](#request-conversion) step.

❶ Authenticate

Include the following scopes when [authenticating](/guides/developer/authenticate):

```shell theme={null}
conversion:read_conversion_stablecoin conversion:write_conversion_stablecoin
funding:read_profile
```

> If you don't see all the scopes when [creating or editing API credentials](/guides/developer/credentials), contact [Support](https://support.paxos.com).

❷ Deposit USD and USDG

Use [Create Sandbox Deposit](/api-reference/endpoints/sandbox-deposits/create-sandbox-deposit) to add USD to the Profile (`profile_id`) you want the conversion to be associated with. See the [First API Request](/guides/developer/request) guide for help retrieving

Profile IDs.
This guide also includes examples for the USDG → USD conversion, so if you are following along make sure you add some USDG to the Profile.
You can also use the [Fiat Transfers funding flow](/guides/developer/fiat-transfers/quickstart#funding) if you've already set up a Fiat Account.

USD

```shell highlight={2} theme={null}
curl --request POST \
--location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/0d3172c5-8840-4bae-bdd4-30688f0268fc/deposit' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "asset": "USD",
  "amount": "1000"
}'
```

USDG

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/0d3172c5-8840-4bae-bdd4-30688f0268fc/deposit' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "asset": "USDG",
    "amount": "100",
    "crypto_network": "ETHEREUM"
}'
```

❸ Request Conversion

Request a conversion using [Create Stablecoin Conversion](/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion).
Include the following body parameters in your request to convert the `source_asset` of \$100 USD into the `target_asset`.
For [Third-party integrations](/guides/crypto-brokerage/ledger-type#fiat-and-crypto-subledger), you must also specify `identity_id` and `account_id`.

USDG → USD

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/conversion/stablecoins' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "ref_id": "sc_usdg_a284608c-4cf0-4605-ae0a-5c1f7ff109d3",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "amount": "100",
    "source_asset": "USDG",
    "target_asset": "USD",
}'
```

The acknowledgement response includes the `id`, which can be used to lookup the transaction, and the status will always be `CREATED`.
The `source_asset` is immediately debited from the associated `profile_id` balance.
The `target_asset` will not be credited until the [conversion status](/guides/developer/convert#statuses) is "status": "SETTLED"\`.

```json theme={null}
```

```
{
    "id": "ea284608c-4cf0-4605-ae0a-5c1f7ff109d3",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "amount": "100",
    "source_asset": "USDG",
    "target_asset": "USD",
    "status": "CREATED",
    "ref_id": "sc_usdg_a284608c-4cf0-4605-ae0a-5c1f7ff109d3",
    ...
}
```

USD → PYUSD

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/conversion/stablecoins' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "ref_id": "sc_pyusd_8f91a9c5-0a6e-46dc-ad68-17bc8fb4eafb",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "amount": "100",
    "source_asset": "USD",
    "target_asset": "PYUSD",
}'
```

The acknowledgement response includes the `id`, which can be used to lookup the transaction, and the status will always be `CREATED`.
The `source_asset` is immediately debited from the associated `profile_id` balance.
The `target_asset` will not be credited until the [conversion status](/guides/developer/convert#statuses) is "status": "SETTLED"\`.

```json theme={null}
{
    "id": "f190b163-208f-4d73-8deb-4fb8b24add00",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "amount": "100",
    "source_asset": "USD",
    "target_asset": "PYUSD",
    "status": "CREATED",
    "ref_id": "sc_pyusd_8f91a9c5-0a6e-46dc-ad68-17bc8fb4eafb",
    ...
}
```

❹ Confirm the Conversion

Use [List Stablecoin Conversions](/api-reference/endpoints/stablecoin-conversion/list-stablecoin-conversions) to check the conversion status.
The request requires the `profile_id` query parameter.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/conversion/stablecoins?profile_id=0d3172c5-8840-4bae-bdd4-30688f0268fc&order=DESC' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

The returned array includes the `settled_at` parameter and the status is `SETTLED` for all conversions executed for the given Profile.

```json theme={null}
{
    "items": [
```

```
        {
            "id": "08f67bca-fb30-4006-8ed2-d46750dd1293",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "amount": "100",
            "source_asset": "USDG",
            "target_asset": "USD",
            "status": "SETTLED",
            ...
            "settled_at": "2024-09-25T15:07:56.076853Z"
        },
        {
            "id": "9f458a60-8b9b-4b3c-b5a4-ee57bc795086",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "amount": "100",
            "source_asset": "USD",
            "target_asset": "PYUSD",
            "status": "SETTLED",
            ...
            "settled_at": "2024-09-25T15:07:21.548903Z"
        },
    ]
}
```

Stablecoin Conversion Asset Precision

You can convert USD to any supported asset and vice versa.
However, you cannot convert one stablecoin to another.
All conversions use the lowest maximum precision among the asset pairs.

Supported Asset	Maximum Decimal Precision	Example Conversion Precision
USD	0.01 (1e-2)	USD → USDG = 0.01 (1e-2)
[PYUSD](/guides/stablecoin/pyusd)	0.000001 (1e-6)	PYUSD → USD = 0.01 (1e-2)
[USDG](/guides/stablecoin/usdg)	0.00000001 (1e-8)	USDG → USD = 0.01 (1e-2)
[USDP](/guides/stablecoin/usdp)	0.00000001 (1e-8)	USDP → USD = 0.01 (1e-2)

Stablecoin Conversion Statuses

There are three conversion statuses:

* `CREATED`: The conversion has been submitted successfully but has not yet settled.
* `SETTLED`: The conversion has been completed.
* `CANCELLED`: The conversion was stopped [using the cancel endpoint](/api-reference/endpoints/stablecoin-conversion/cancel-stablecoin-conversion) for the pending conversion.

When a conversion is in `CREATED` status, the `source_asset` (for example, fiat for acquiring stablecoin) will be debited from the `profile_id` balance.
The `target_asset` (for example, USDG for acquiring stablecoin) will not be credited until the order has `SETTLED`.

<Tip>
  Best Practice

  * Build a pending conversion settlement workflow for edge cases where the conversion does not settle immediately. This is especially important for subledgered customers, where the user will be unable to sell or transfer the assets until the conversion has settled and the asset has been credited to their Profile.

  * Log the transaction details from each conversion in a database.
  * Cache Profile balances. Balances should be updated once there has been a change to the Profile balance (for example, after a conversion) and then perform a reconciliation to confirm the updated balance matches the client's internal calculation.
  * Create a polling workflow to query the results in ascending order. Keep track of the `created_at` timestamp of the most recent conversion in the paged results.
</Tip>

Configure API Credentials
Source: https://docs.paxos.com/guides/developer/credentials

API credentials using Client ID and Secret. Set allowed scopes to access specific API endpoints.

Most API endpoints require authentication with a **Client ID** and **Secret**. Each **Client ID** has a specific set of allowed scopes (**Permissions**) to access API endpoints. Scopes allowed on an API client may be updated at any time in the Dashboard **Admin > API Management** section.

<Tip>
  Contact your [Entity Manager](guides/dashboard/roles#entity-manager) if you need permissions to manage API credentials.
</Tip>

When setting scopes, Paxos recommends following the [principle of least privilege](https://en.wikipedia.org/wiki/Principle_of_least_privilege) and only allow scopes required by a specific application. Scopes for each endpoint are listed in the **Authorizations** section in the [API Reference docs](/api-reference/introduction). The [Market Data](/api-reference/endpoints/market-data) and most [Pricing](/api-reference/endpoints/pricing) endpoints do not require authorization.

1. Go to **Admin > API Management** to add new credentials.

<Tip>
  The Developer Sandbox is completely segregated from production, so credential configuration must take place in both environments.

  * **Developer Sandbox**: https://dashboard.sandbox.paxos.com/admin/api
  * **Production**: https://dashboard.paxos.com/admin/api
</Tip>

1. Create a **Label** for your API credentials and select the **Scopes** for your **Client ID**. For example, the following scopes (space delimited) should be adequate to [mint](/guides/developer/mint), [redeem](/guides/developer/redeem) and [convert](/guides/developer/convert) Paxos-issued stablecoins:


   ```shell theme={null}
   conversion:read_conversion_stablecoin
   conversion:write_conversion_stablecoin
   funding:read_profile
   funding:write_profile
   transfer:read_deposit_address
   transfer:read_transfer
   transfer:read_fiat_account
   transfer:read_fiat_deposit_instructions
   transfer:write_internal_transfer
   transfer:write_crypto_withdrawal
   transfer:write_deposit_address
   transfer:write_fiat_account
   transfer:write_fiat_deposit_instructions
   transfer:write_fiat_withdrawal
   ```
2. Save the credentials.

3. Copy the **Client ID** and **Client Secret** and store them in a safe place. The secret will not be displayed in the UI again and will have to be reset if forgotten.

Once you have the **Client ID** and **Client Secret**, you can [authenticate in Sandbox](/guides/developer/authenticate).

Paxos API FAQ
Source: https://docs.paxos.com/guides/developer/faq

Get answers to commonly asked questions.

Stablecoin Conversions

<AccordionGroup>
  <Accordion title="How can I get started with conversions?">
    The [stablecoin conversion guide](/guides/developer/convert) takes you through the simple process. Reach out to [Support](https://support.paxos.com) if you need assistance.
  </Accordion>

  <Accordion title="What are the conversion fees?">
    None. Conversions between the [supported asset pairs](/guides/developer/convert#assets) incure no fees.
  </Accordion>

  <Accordion title="Are there any conversion limits?">
    By default, there is a \$500,000 USD transaction limit per conversion.
    Contact [Support](https://support.paxos.com) for additional details.
  </Accordion>

  <Accordion title="What is dust?">
    Dust is a small amount of an asset leftover from a transaction.
    Dust can accumulate when converting [assets with different precisions](/guides/developer/convert#assets).
  </Accordion>

  <Accordion title="Can I cancel a conversion?">
    Most conversions execute near instantaneously; however, under rare conditions a settlement delay may occur.
    You can use the [Cancel Stablecoin Conversion](/api-reference/endpoints/stablecoin-conversion/cancel-stablecoin-conversion) endpoint to cancel a pending conversion.
  </Accordion>
</AccordionGroup>

Fiat Transfers FAQ
Source: https://docs.paxos.com/guides/developer/fiat-transfers/fiat-transfers-faq

Get answers to common questions about the Fiat Transfers API.

What can I do with the Fiat Transfers API?

* Paxos can accept wires from or send wires to a bank account, even if the bank account owner is not the same as the individual or institution onboarded with Paxos. This means Paxos allows wire transfers involving third-party bank accounts, subject to applicable compliance and regulatory checks.
* Fund your Paxos corporate account or withdraw your funds to an external bank account.
* Enable your users to directly fund their account or withdraw their funds to an external bank account.

How do I get the Identity ID required in requests?

* Paxos will send you the Identity ID for your corporate account.
* For user-based funding, Integrate the [Identity API](/api-reference/endpoints/identity) and use the corresponding endpoints.

How do I input the routing number (ABA) for US wires (Fedwire)?

Use `routing_number_type` = `ABA`. For US domestic wires, set `fiat_network` = `WIRE` and `routing_number_type` = `ABA`.

How do I input the SWIFT/BIC code for SWIFT wires?

Use `routing_number_type` = `SWIFT`. For SWIFT wires, set `fiat_network` = `WIRE` and `routing_number_type` = `SWIFT`.

Do I need JWS request signing?

It is recommended to have [JWS request signing](/guides/developer/request-signing) for fiat withdrawals.
JWS request signing uses a public-key cryptography with a client-controlled private key.
It adds an additional layer of security to withdrawals.
It can prevent malicious withdrawals even if the API key secret is compromised.
When used, all API calls with this key will require a JWS signature.

How do I retrieve fiat account information?

Use [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account) to get complete details of the fiat account.
[List Fiat Account](/api-reference/endpoints/fiat-transfers/list-fiat-accounts) excludes beneficiary name and address details and only includes the last four (4) digits of the account number.

Are there fees associated with fiat transfers?

For withdrawals, fees are in addition to the requested amount.
For deposits, fees are deducted from the received amount.
See [Deposit & Withdrawal Fees](https://help.paxos.com/hc/en-us/articles/360042321231) for the current fee structure.

Overview
Source: https://docs.paxos.com/guides/developer/fiat-transfers/index

Move USD on and off the Paxos Platform via wire transfer or CUBIX.

To move USD onto the platform, first use [Create Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/create-fiat-deposit-instructions) to retrieve the Paxos banking information and specify which [Profile](/api-reference/endpoints/profiles) balance to credit.
Then, use the returned banking information, found in `fiat_network_instructions` object, along with the `memo_id`, to transfer funds to Paxos.

To move USD off the Platform, first use [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) to let Paxos know where to transfer the funds.
Then, use the returned Fiat Account `id` with [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal) to transfer funds to the external account.

<Tip>
  * Use [Get Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/get-fiat-deposit-instructions) to check the status of the instructions before initiating a deposit.
  * Before initiating a withdrawal, use [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account) to ensure the account status is `APPROVED`.
  * When transferring funds, use [List Transfers](/api-reference/endpoints/transfers/list-transfers) and [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance) to check on the transfer status and Profile balance changes.
</Tip>

Fiat Deposits and Withdrawals

Paxos credits your USD wire deposit as soon as it is received by our bank.
Domestic wire withdrawals are processed via the FedWire system and may take 1-3 business days to settle. International wire withdrawals may take 1-5 days to reach the beneficiary bank.

Paxos can accept wires from or send wires to a bank account, even if the bank account owner is not the same as the individual or institution onboarded with Paxos.
This means Paxos allows wire transfers involving third-party bank accounts, subject to applicable compliance and regulatory checks.

CUBIX USD transfers are processed 24/7; however, longer processing time may occasionally be required.
CUBIX deposits are not subject to any limits.

<Tip>
  * Deposits with missing or incorrect information will be returned.
  * USD wire transfers are not processed on weekends and on US banking holidays. CUBIX transfers are processed 24/7.
</Tip>

Fiat Transfers Quickstart
Source: https://docs.paxos.com/guides/developer/fiat-transfers/quickstart

Set up fiat funding and withdraw flows in the Sandbox environment.

This guides walks you through the steps to [send fiat to the Paxos Platform](#funding) as well as [move money to an external bank account](#withdrawal) using the [Fiat Transfers](/api-reference/endpoints/fiat-transfers), [Transfers](/api-reference/endpoints/transfers) and [Profiles](/api-reference/endpoints/profiles) APIs.
Once completed, similar workflows can be implemented in Production.
If you already have a [Sandbox Account](https://dashboard.sandbox.paxos.com), this guide should take less than one hour to complete.

Authenticate in Sandbox

Both the [funding](#funding) and [withdrawal](#withdrawal) flows require the same scopes, so for simplicity one authentication call should be all you need to complete both flows.

> When [creating API credentials](/guides/developer/credentials) via the Dashboard, the `transfer:write_sandbox_fiat_deposit` scope may not appear in the UI.
> Including the scope when [authenticating](/guides/developer/authenticate) may result in an `invalid_scope` error.
> Contact [Support](https://support.paxos.com) if you run into any issues using this scope.

Add the `transfer:read_fiat_account`, `transfer:write_fiat_account`, `transfer:read_fiat_deposit_instructions`, `transfer:write_fiat_deposit_instructions`, `transfer:write_fiat_withdrawal`, `transfer:write_sandbox_fiat_deposit`, `transfer:read_transfer` and `funding:read_profile` scopes to your [Sandbox Account](https://dashboard.sandbox.paxos.com)
under the [API Management](https://dashboard.sandbox.paxos.com/admin/api) setting and then authenticate in Sandbox using the scopes.

```shell highlight={5} theme={null}
curl --location 'https://oauth.sandbox.paxos.com/oauth2/token' \
--form grant_type=client_credentials \
--form client_id={paxos_client_id} \
--form client_secret={paxos_secret} \
--form scope='transfer:read_fiat_account transfer:write_fiat_account
transfer:read_fiat_deposit_instructions transfer:write_fiat_deposit_instructions
transfer:write_fiat_withdrawal transfer:write_sandbox_fiat_deposit transfer:read_transfer
funding:read_profile'
```

Confirm the response includes requisite scopes and save the `access_token` to use in the request authorization header
throughout this guide.

```json highlight={3-4} theme={null}
{
 "access_token": "{access_token}",
 "expires_in": 3599, // Seconds (59 Minutes and 59 Seconds)
 "scope": "transfer:read_fiat_account transfer:write_fiat_account transfer:read_fiat_deposit_instructions transfer:write_fiat_deposit_instructions transfer:write_fiat_withdrawal transfer:write_sandbox_fiat_deposit transfer:read_transfer funding:read_profile",
 "token_type": "bearer"
}
```

<Tip>
  You must include the Authorization header with your bearer token on all API requests `-H "Authorization: Bearer $TOKEN"`.
</Tip>

Funding Flow

To move USD onto the platform, first use [Create Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/create-fiat-deposit-instructions) to retrieve the Paxos banking information and specify which [Profile](/api-reference/endpoints/profiles) balance to credit.
Then, use the returned banking information, found in `fiat_network_instructions` object, along with the `memo_id`, to transfer funds to Paxos.

We'll be following the recommended fiat deposit workflow:

* [Authenticate in Sandbox](#authenticate).
* Get instructions from Paxos on how to deposit fiat using [Create Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/create-fiat-deposit-instructions).
* Send a wire (SWIFT, Fedwire) or CUBIX transfer to Paxos, referencing the `memo_id` provided in the deposit instructions.
* Check the status of the deposit using [List Transfers](/api-reference/endpoints/transfers/list-transfers).
* View updated balances using [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance).

❶ Create Fiat Deposit Instructions

Get instructions from Paxos on how to deposit fiat using [Create Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/create-fiat-deposit-instructions).

<Info>
  * For wires, use `fiat_network` “WIRE”. Specify international (SWIFT) or US (Fedwire) by setting `routing_number_type`
    to “ABA” (for Fedwire) or “SWIFT” (for SWIFT).
  * For CUBIX, use `fiat_network` CUBIX. Do not use `routing_number_type`.
</Info>

Corporate Funding

Retrieve the `profile_id` and `identity_id` (optioinal) from your records. Use your omnibus `profile_id` and optionally your corporate `identity_id` created for you by Paxos.

Create deposit instructions for international wires. Include the following body parameters in the request:

```shell highlight={5,7} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-deposit-instructions' \
--request 'POST' \
```

```
  --header 'Authorization: Bearer {access_token}' \
  --data '{
    "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
    "fiat_network": "WIRE",
    "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68", // Optional.
    "ref_id": "idempotence_id",
    "routing_number_type": "SWIFT",
    "metadata": {
      "my_id": "4024ee50-eefb-4f2e-85c7-e7899c0b7da5"
    }
  }'
```

Upon successful request, the acknowledgment response confirms your request has been received.

```json highlight={8} theme={null}
{
  "id": "f190b163-208f-4d73-8deb-4fb8b24add00",
  "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68", // Optional.
  "created_at": "2024-01-28T04:23:11.738801Z",
  "ref_id": "idempotence_id",
  "status": "VALID",
  "memo_id": "9CFXQSCMSPLFHXLZ",
  "fiat_network_instructions": {
    "wire": {
      "account_number": "7339119",
      "fiat_account_owner_address": {
        "country": "US",
        "address1": "450 Lexington Ave. #3952",
        "city": "New York",
        "province": "NY",
        "zip_code": "10163"
      },
      "routing_details": {
        "routing_number_type": "SWIFT",
        "routing_number": "031302971",
        "bank_name": "Customers Bank",
        "bank_address": {
          "country": "USA",
          "address1": "701 Reading Avenue",
          "city": "West Reading",
          "province": "PA",
          "zip_code": "19611"
        }
      }
    },
    "fiat_account_owner": {
      "institution_details": {
        "name": "Paxos Trust Company, LLC"
      }
    },
    "metadata": {
      "my_id": "4024ee50-eefb-4f2e-85c7-e7899c0b7da5"
    }
  }
}

```

You will need the `memo_id` from the response on the next step in order to fund the Profile.

End User Funding

Retrieve the user’s `profile_id`, `identity_id` and `account_id` from your records.
Create deposit instructions for international wires (SWIFT) for end user funding.
Include the following body parameters in the request:

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-deposit-instructions' \
--request 'POST' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
    "fiat_network": "WIRE",
    "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
    "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
    "ref_id": "idempotence_id",
    "routing_number_type": "SWIFT",
    "metadata":
    {
      "my_id": "4024ee50-eefb-4f2e-85c7-e7899c0b7da5"
    }
}'
```

Upon successful request, the acknowledgment response confirms your request has been received.

```json theme={null}
{
  "id": "f190b163-208f-4d73-8deb-4fb8b24add00",
  "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
  "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
  "created_at": "2024-01-28T04:23:11.738801Z",
  "ref_id": "idempotence_id",
  "status": "VALID",
  "memo_id": "9CFXQSCMSPLFHXLY",
  "fiat_network_instructions": {
    "wire": {
      "account_number": "7339119",
      "fiat_account_owner_address": {
        "country": "US",
        "address1": "450 Lexington Ave. #3952",
        "city": "New York",
        "province": "NY",
        "zip_code": "10163"
      },
      "routing_details": {
        "routing_number_type": "SWIFT",
        "routing_number": "031302971",
        "bank_name": "Customers Bank",
        "bank_address": {
          "country": "USA",
          "address1": "701 Reading Avenue",
          "city": "West Reading",
          "province": "PA",
          "zip_code": "19611"
        }
      }
    },
    "fiat_account_owner": {
      "institution_details": {
        "name": "Paxos Trust Company, LLC"
      }
    },
    "metadata": {
      "my_id": "4024ee50-eefb-4f2e-85c7-e7899c0b7da5"
```

```
      }
    }
  }
```

You will need the `memo_id` from the response to fund the Profile.

❷ Send Fiat to Paxos

Send a wire (SWIFT, Fedwire) or CUBIX transfer to Paxos, referencing the `memo_id` to fund your Profile.

For Sandbox environment emulate the wire deposit using [Initiate Sandbox Fiat Deposit](/api-reference/endpoints/sandbox-fiat-transfers/initiate-sandbox-fiat-deposit).

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/sandbox/fiat-deposits' \
--request 'POST' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "amount": "150.33",
  "asset": "USD",
  "memo_id": "9CFXQSCMSPLFHXLZ",
  "fiat_network_instructions": {
    "wire": {
      "account_number": "1234567",
      "fiat_account_owner_address": {
        "country": "US",
        "address1": "456 Main Street",
        "city": "New York",
        "province": "NY",
        "zip_code": "10101"
      },
      "routing_details": {
        "routing_number_type": "SWIFT",
        "routing_number": "031302971",
        "bank_name": "Customers Bank",
        "bank_address": {
          "country": "USA",
          "address1": "123 Bank Street",
          "city": "New York",
          "province": "NY",
          "zip_code": "10101"
        }
      }
    }
  },
  "fiat_account_owner": {
    "institution_details": {
      "name": "Paxos Trust Company, LLC"
    }
  }
}'
```

You should get an empty response with `200` status code.

It can take a minute to process the deposit on the backend.

<Tip>
  In production, send a real wire (SWIFT, Fedwire) or CUBIX transfer to Paxos, referencing the production `memo_id` (not sandbox) to fund your Profile.
</Tip>

❸ Check Status of Deposit

Find the deposit using [List Transfers](/api-reference/endpoints/transfers/list-transfers).

Via Profile ID

Include the `profile_id` query parameter to filter out transfers to all other Profiles.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?
order=DESC&type=WIRE_DEPOSIT&limit=2&profile_ids=5fc6d191-193c-4e28-94fa-
656bbdbdfaad&limit=1' \
--request 'GET' \
--header 'Authorization: Bearer {access_token}'
```

Response:

```json theme={null}
{   "items": [
 {   "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
     "amount": "150.33",
     "asset": "USD",
     "auto_conversion": {},
     "balance_asset": "USD",
     "created_at": "2024-01-28T00:48:00.222744Z",
     "customer_id": "4eaffe58-df0e-4559-8dec-fdae231684e9",
     "direction": "CREDIT",
     "fee": "30",
     "id": "cca46bf3-2dab-4ab5-a4f1-7b1b75956a29",
     "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
     "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
     "status": "COMPLETED",
     "total": "120.33",
     "type": "WIRE_DEPOSIT",
     "updated_at": "2024-01-28T00:48:00.332602Z"
 }
 ],
  "next_page_cursor": "TAISDAiA-9qtBhCQtcyeARjCwa8M"
}
```

Via Identity ID

Include the `identity_id` query parameter to filter out transfers to all other Identities.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?
order=DESC&type=WIRE_DEPOSIT&identity_ids=8a398cb6-4e3b-4868-9cea-a1c567856e68&limit=1' \
--request 'GET' \
--header 'Authorization: Bearer {access_token}'
```

Response:

```json theme={null}
{   "items": [
 {   "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
     "amount": "150.33",
     "asset": "USD",
     "auto_conversion": {},
     "balance_asset": "USD",
     "created_at": "2024-01-28T00:48:00.222744Z",
     "customer_id": "4eaffe58-df0e-4559-8dec-fdae231684e9",
     "direction": "CREDIT",
     "fee": "30",
```

```
      "id": "cca46bf3-2dab-4ab5-a4f1-7b1b75956a29",
      "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
      "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
      "status": "COMPLETED",
      "total": "120.33",
      "type": "WIRE_DEPOSIT",
      "updated_at": "2024-01-28T00:48:00.332602Z"
 }
 ],
  "next_page_cursor": "TAISDAiA-9qtBhCQtcyeARjCwa8Q"
}
```

❹ View Updated Balances

View updated balances using [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance).

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/5fc6d191-193c-4e28-94fa-656bbdbdfaad/balances/USD' \
--request 'GET' \
--header 'Authorization: Bearer {access_token}'
```

Response:

```json theme={null}
{
  "asset": "USD",
  "available": "120.33",
  "trading": "0"
}
```

Withdrawal Flow

To move USD off the Platform, first use [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) to let Paxos know where to transfer the funds.
Then, use the returned Fiat Account `id` with [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal) to transfer funds to the external account.

We'll be following the recommended fiat withdrawal workflow:

* [Authenticate in Sandbox](#authenticate).
* Save your external bank account information on Paxos using [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account). If needed, you can update bank account information using [Update Fiat Account](/api-reference/endpoints/fiat-transfers/update-fiat-account).
* Confirm sufficient funds in the associated Profile to process the withdrawal using [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance).
* Retrieve the ID for your external bank account using [List Fiat Accounts](/api-reference/endpoints/fiat-transfers/list-fiat-accounts).
* Initiate a fiat withdrawal from Paxos into your external bank account using [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal).
* Check the status of the withdrawal using [List Transfers](/api-reference/endpoints/transfers/list-transfers).
* View updated balances using [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance).

❶ Create Fiat Account

Save your external bank account information on Paxos using [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account).

<Tip>
  For CUBIX, the `wallet_address` on `fiat_network_instructions` is not a crypto wallet address, it is a Customers Bank
  account wallet address.
</Tip>

Corporate Funding

Include the following body parameters in your request to create fiat accounts for US domestic wires:

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-accounts' \
--request 'POST' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "ref_id": "idempotence_id",
    "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68", // Optional.
    "fiat_account_owner": {
        "institution_details": {
            "name": "Company"
        }
    },
    "fiat_network_instructions": {
        "wire": {
            "account_number": "74600021314512",
            "fiat_account_owner_address": {
                    "country": "USA",
                    "address1": "456 Main Street, NY",
                    "city": "New York",
                    "province": "NY",
                    "zip_code": "10101"
            },
            "routing_details": {
                "routing_number_type": "ABA",
                "routing_number": "031302971",
                "bank_name": "Customers Bank",
                "bank_address": {
                        "country": "USA",
                        "address1": "123 Bank Street",
                        "city": "New York",
                        "province": "NY",
                        "zip_code": "10101"
                }
            }
        }
    },
    "metadata": {
       "test_ref_id": "47aa7538-e2d2-47b3-8600-44a7965dd357",
       "key_2": "2"
    }
}'
```

Upon successful request, the acknowledgment response confirms your request has been received.

```json highlight={2,34} theme={null}
{
  "id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
  "ref_id": "idempotence_id",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68", // Optional.
  "fiat_account_owner": {
    "person_details": {
```

```
        "name": "Company"
      },
      "fiat_network_instructions": {
        "wire": {
          "account_number": "74600021314512",
          "fiat_account_owner_address": {
            "country": "USA",
            "address1": "456 Main Street, NY",
            "city": "New York",
            "province": "NY",
            "zip_code": "10101"
          },
          "routing_details": {
            "routing_number_type": "ABA",
            "routing_number": "031302971",
            "bank_name": "Customers Bank",
            "bank_address": {
              "country": "USA",
              "address1": "123 Bank Street",
              "city": "New York",
              "province": "NY",
              "zip_code": "10101"
            }
          }
        }
      }
    },
    "status": "PENDING",
    "metadata": {
      "test_ref_id": "47aa7538-e2d2-47b3-8600-44a7965dd357",
      "key_2": "2"
    },
    "created_at": "2024-01-28T22:14:25.731494Z"
  }
```

Note the `id` in the response, it will be required to check the Account status in the next steps.

End User Funding

Include the following body parameters in your request to create fiat accounts for SWIFT (international) wires:

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-accounts' \
--request 'POST' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "ref_id": "idempotence_id",
    "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
    "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
    "fiat_account_owner": {
        "person_details": {
            "first_name": "Megan",
            "last_name": "Snow"
        }
    },
    "fiat_network_instructions": {
        "wire": {
            "account_number": "74600021314512",
            "fiat_account_owner_address": {
                    "country": "USA",
                    "address1": "2600 Tully St",
                    "city": "Washington",
```

```
                    "province": "DC",
                    "zip_code": "10010"
            },
            "routing_details": {
                "routing_number_type": "SWIFT",
                "routing_number": "JINABVU1773",
                "bank_name": "First Bank",
                "bank_address": {
                        "country": "Brazil",
                        "address1": "Awesome ct",
                        "city": "Sao Paulo",
                        "province": "Sao Paulo",
                        "zip_code": "33445"
                }
            },
            "intermediary_routing_details": {
                "routing_number_type": "ABA",
                "routing_number": "123456789",
                "bank_name": "Ubium Bank",
                "bank_address": {
                    "country": "USA",
                    "address1": "Great str",
                    "city": "Walnut Creek",
                    "province": "CA",
                    "zip_code": "59610"
                }
            }
        }
    },
    "metadata": {
        "key_1": "1",
        "key_2": "two"
    }
}'
```

Upon successful request, the acknowledgment response confirms your request has been received.

```json highlight={2,48} theme={null}
{
    "id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
    "ref_id": "idempotence_id",
    "identity_id": "8f22e593-5f51-40cc-8bb0-5245d051c1da",
    "account_id": "38fc5a41-12a5-43f4-a2de-4733dcd1dee6",
    "fiat_account_owner": {
        "person_details": {
            "first_name": "Megan",
            "last_name": "Snow"
        }
    },
    "fiat_network_instructions": {
        "wire": {
            "account_number": "XXXXXXXXXX4512",
            "fiat_account_owner_address": {
                "country": "USA",
                "address1": "2600 Tully St",
                "city": "Washington",
                "province": "DC",
                "zip_code": "10010"
            },
            "routing_details": {
                "routing_number_type": "SWIFT",
                "routing_number": "JINABVU1773",
                "bank_name": "First Bank",
```

```
                "bank_address": {
                    "country": "Brazil",
                    "address1": "Awesome ct",
                    "city": "Sao Paulo",
                    "province": "Sao Paulo",
                    "zip_code": "33445"
                }
            },
            "intermediary_routing_details": {
                "routing_number_type": "ABA",
                "routing_number": "123456789",
                "bank_name": "Ubium Bank",
                "bank_address": {
                    "country": "USA",
                    "address1": "Great str",
                    "city": "Walnut Creek",
                    "province": "CA",
                    "zip_code": "59610"
                }
            }
        }
    },
    "status": "PENDING",
    "metadata": {
        "key_1": "1",
        "key_2": "two"
    },
    "created_at": "2024-03-13T00:50:08.902618Z"
}
```

Note the `id` in the response, it will be required to check the Account status in the next steps.

❷ Confirm Sufficient Funds

Confirm sufficient funds in the profile to process the withdrawal using [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance).

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/5fc6d191-193c-4e28-94fa-656bbdbdfaad/balances/USD' \
--request 'GET' \
--header 'Authorization: Bearer {access_token}'
```

Response:

```json theme={null}
{
  "asset": "USD",
  "available": "120.33",
  "trading": "0"
}
```

❸ Retrieve Bank Account Status

Retrieve the status of your external bank account using [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account) and providing the `id` from the [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) response.

<Info>
  There are three statuses for Fiat Accounts: "PENDING"`, \"APPROVED"`, "REJECTED"`. While

on \"PENDING"`, Paxos is
  processing your fiat account. Fiat Account status needs to be "APPROVED"\` before Fiat Account can be used for withdrawals.
</Info>

Request:

```shell theme={null}
curl --request 'GET' --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-accounts/cc1b6606-a8a3-4a8f-8b9b-5456d96448bf'
```

Response:

```json highlight={37} theme={null}
{
   "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
   "created_at": "2024-01-28T22:14:25.731494Z",
   "fiat_account_owner": {
     "person_details": {
       "name": "Company"
     }
   },
   "fiat_network_instructions": {
     "wire": {
       "account_number": "74600021314512",
       "fiat_account_owner_address": {
         "country": "USA",
         "address1": "456 Main Street, NY",
         "city": "New York",
         "province": "NY",
         "address2": "",
         "zip_code": "10101"
       },
       "routing_details": {
          "routing_number_type": "ABA",
          "routing_number": "031302971",
          "bank_name": "Customers Bank",
          "bank_address": {
            "country": "USA",
            "address1": "123 Bank Street",
            "city": "New York",
            "province": "NY",
            "zip_code": "10101"
          }
        }
      }
   },
   "id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
   "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
   "ref_id": "idempotence_id",
   "status": "APPROVED",
   "metadata": {
     "test_ref_id": "47aa7538-e2d2-47b3-8600-44a7965dd357",
     "key_2": "2"
   }
}
```

From the response find the `id` of the bank record for the user. It must be in `APPROVED` status.

❹ Create Fiat Withdrawal

Initiate a fiat withdrawal from Paxos into your external bank account using [Create Fiat

Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal).

Corporate Funding

Initiate a CUBIX withdrawal. Specify the `fiat_account_id` of the Fiat Account from the [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) response.

```shell highlight={8} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-withdrawals' \
--request 'POST' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "ref_id": "idempotence_id",
  "amount": "120",
  "asset": "USD",
  "fiat_account_id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
  "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68", // Optional.
  "metadata": {
    "custom_key": "custom_value"
  }
}'
```

Response:

```json theme={null}
{
  "amount": "100",
  "asset": "USD",
  "auto_conversion": {},
  "balance_asset": "USD",
  "created_at": "2024-01-28T22:39:02.279268Z",
  "customer_id": "4eaffe58-df0e-4559-8dec-fdae231684e1",
  "direction": "DEBIT",
  "fee": "20",
  "fiat_account_id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
  "id": "11a6f6e9-4219-4698-9d79-abfc1e346246",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68", // Optional.
  "metadata": {
    "custom_key": "custom_value"
  },
  "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
  "ref_id": "idempotence_id",
  "status": "PENDING",
  "total": "120",
  "type": "CUBIX_WITHDRAWAL",
  "updated_at": "2024-01-28T22:39:02.279268Z"
}
```

End User Funding

Initiate an international wire withdrawal (SWIFT). Specify the `fiat_account_id` from the [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) response.

```shell highlight={8} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/fiat-withdrawals' \
--request 'POST' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "ref_id": "idempotence_id",
  "amount": "120",
  "asset": "USD",
  "fiat_account_id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
```

```
  "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
  "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
  "metadata": {
    "custom_key": "custom_value"
  }
}'
```

Response:

```json theme={null}
{
  "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
  "amount": "100",
  "asset": "USD",
  "auto_conversion": {},
  "balance_asset": "USD",
  "created_at": "2024-01-28T22:39:02.279268Z",
  "customer_id": "4eaffe58-df0e-4559-8dec-fdae231684e1",
  "direction": "DEBIT",
  "fee": "20",
  "fiat_account_id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
  "id": "11a6f6e9-4219-4698-9d79-abfc1e346246",
  "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
  "metadata": {
    "custom_key": "custom_value"
  },
  "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
  "ref_id": "idempotence_id",
  "status": "PENDING",
  "total": "120",
  "type": "WIRE_WITHDRAWAL",
  "updated_at": "2024-01-28T22:39:02.279268Z"
}
```

<Tip>
  It is recommended to have [JWS request signing](/guides/developer/request-signing) for Fiat Withdrawals.
  JWS request signing uses a public-key cryptography with a client-controlled private key.
  It adds an additional layer of security to withdrawals.
  It can prevent malicious withdrawals even if the API key is compromised.
  When used, all API calls with this key will require a JWS signature.
</Tip>

❺ Check Status of Withdrawal

Check the status of the withdrawal using [Get Transfer](/api-reference/endpoints/transfers/get-transfer) with the `id` from the previous step.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers/11a6f6e9-4219-4698-9d79-abfc1e346246' \
--request 'GET' \
--header 'Authorization: Bearer {access_token}'
```

Response:

```json highlight={18} theme={null}
{  "account_id": "91f91384-30d4-46c2-9118-7f3cec676a2c",
   "amount": "100",
   "asset": "USD",
   "auto_conversion": {},
```

```
    "balance_asset": "USD",
    "created_at": "2024-01-28T22:39:02.279268Z",
    "customer_id": "4eaffe58-df0e-4559-8dec-fdae231684e1",
    "direction": "DEBIT",
    "fee": "20",
    "fiat_account_id": "cc1b6606-a8a3-4a8f-8b9b-5456d96448bf",
    "id": "11a6f6e9-4219-4698-9d79-abfc1e346246",
    "identity_id": "8a398cb6-4e3b-4868-9cea-a1c567856e68",
    "metadata": {
      "custom_key": "custom_value"
    },
    "profile_id": "5fc6d191-193c-4e28-94fa-656bbdbdfaad",
    "ref_id": "idempotence_id",
    "status": "COMPLETE",
    "total": "120",
    "type": "WIRE_WITHDRAWAL",
    "updated_at": "2024-01-28T22:39:05.613881Z"}
```

❻ View Updated Balances

View updated balances using [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance) and passing the `profile_id` and `USD` asset in the endpoint's path.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/5fc6d191-193c-4e28-94fa-656bbdbdfaad/balances/USD \'
--request 'GET' \
--header 'Authorization: Bearer {access_token}'
```

Response:

```json theme={null}
{
  "asset": "USD",
  "available": "0.33",
  "trading": "0"
}
```

Statuses
Source: https://docs.paxos.com/guides/developer/fiat-transfers/statuses

Learn more about Fiat Transfers statuses.

The Fiat Transfers workflow includes five (5) statuses:

* `PENDING`: Initial state. The [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) or [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal) request is under review.
* `APPROVED`: The [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) request passed internal review. Can be used for withdrawals.
* `REJECTED`: The [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account) request did not pass internal review. Cannot be used for withdrawals.
* `COMPLETED`: For deposits, the corresponding `profile_id` has been credited. For withdrawals, the transfer has been sent to the external bank account.
* `FAILED`: The deposit or withdrawal did not pass internal requirements.

<Tip>
  - Use [Get Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/get-fiat-deposit-instructions) to check the status of the instructions before initiating a deposit.
  - Before initiating a withdrawal, use [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account) to ensure the account status is `APPROVED`.

- When transferring funds, use [List Transfers](/api-reference/endpoints/transfers/list-transfers) and [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance) to check on the transfer status and Profile balance changes.
</Tip>

Mint
Source: https://docs.paxos.com/guides/developer/mint

Deposit USD. Convert or convert-and-transfer in one API call.

<Warning title="Stablecoin Conversions Deprecation Notice">
The Stablecoin Conversions API will be deprecated.

Paxos will migrate all active conversion rules to the [Orchestrations API](/guides/developer/orchestrations/orchestrations) format by December 2025.

Customers should transition to the Orchestrations API to ensure continuity of service.
</Warning>

<img alt="Mint Workflow" />

Minting a [Paxos-issued stablecoin](/guides/developer/blockchains#stablecoins) starts by depositing USD on the Paxos platform using the [Fiat Transfers APIs](/api-reference/endpoints/fiat-transfers) (**A** in the diagram).
Depending on the use case, you can either convert USD to a stablecoin and keep the asset on the Paxos platform using [Create Stablecoin Conversion](/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion) (option **B**) or use [Create Crypto Withdrawal](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal) to convert and transfer with the same API request (**C**).

> If you've already authenticated and have a USD balances in a Profile, skip ahead to the [convert](#mint-hold) or [convert and transfer](#mint-transfer) step.

❶ Authenticate

Include the following scopes when [authenticating](/guides/developer/authenticate):

```shell theme={null}
conversion:read_conversion_stablecoin conversion:write_conversion_stablecoin
funding:read_profile transfer:write_crypto_withdrawal
```

> If you don't see all the scopes when [creating or editing API credentials](/guides/developer/credentials), contact [Support](https://support.paxos.com).

❷ Deposit USD

Use [Create Sandbox Deposit](/api-reference/endpoints/sandbox-deposits/create-sandbox-deposit) to add USD to the Profile (`profile_id`) you want the minting process to be associated with.
See the [First API Request](/guides/developer/request) guide for help retrieving Profile IDs.
You can also use the [Fiat Transfers funding flow](/api-reference/endpoints/fiat-transfers) if you've already set up a Fiat Account.

```shell highlight={2} theme={null}
curl --request POST \
--location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/0d3172c5-8840-4bae-bdd4-30688f0268fc/deposit' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "asset": "USD",
  "amount": "1000"
}'
```

```
```

❸ Convert USD to Stablecoin

See the [convert stablecoin](/guides/developer/convert) guide for details on using [Create Stablecoin Conversion](/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion) to mint a [Paxos-issued stablecoin](/guides/developer/blockchains#stablecoins). Once the conversion is [`SETTLED`](/guides/developer/convert#stablecoin-conversion-statuses), use [List Profile Balances](/api-reference/endpoints/profiles/list-profile-balances) to check updated balances.
To check balances of the assets you are interested in, include the `assets` query parameter in the request.

```shell highlight={1} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/0d3172c5-8840-4bae-bdd4-30688f0268fc/balances?assets=USD&assets=PYUSD&assets=USDG' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

The response includes the updated USD and Paxos-issued stablecoin balances.

```json theme={null}
{
    "items": [
        {
            "asset": "USD",
            "available": "600",
            "trading": "0"
        },
        {
            "asset": "PYUSD",
            "available": "100",
            "trading": "0"
        },
        {
            "asset": "USDG",
            "available": "100",
            "trading": "0"
        }
    ]
}
```

❹ Convert and Transfer

Use [Create Crypto Withdrawal](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal) to transfer the Paxos-issued stablecoin to an address off the Paxos platform with a single request.
To automatically convert fiat (USD) to stablecoin and transfer to an external address with a single request, set the `asset` to the stablecoin you want to mint, the `balance_asset` to `USD`, and the `crypto_network` to the desired network.

USDG on Ethereum

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/crypto-withdrawals' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "asset": "USDG",
    "destination_address": "0x9acb61E5fcE9B5BdA7B44635d86be19d2790D9a9",
    "crypto_network": "ETHEREUM",
```

```
    "ref_id": "cw_usdg_eth_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
    "balance_asset": "USD",
    "amount": "100"
}'
```

PYUSD on Solana

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/crypto-withdrawals' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "asset": "PYUSD",
    "destination_address": "BtXdwoYSWPprQT88ZCLuQcXuTz4dFHB1AJFYqr5uXoAd",
    "crypto_network": "SOLANA",
    "ref_id": "cw_pyusd_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
    "balance_asset": "USD",
    "amount": "100"
}'
```

The request confirmation response has a `status` of `PENDING`, since the on-chain transaction has not yet been confirmed.

USDG on Ethereum

```json highlight={13} theme={null}
{
    "id": "7c223577-832b-4235-a77e-ebf36dfe9860",
    "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "ref_id": "cw_usdg_eth_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
    "amount": "100",
    "total": "126.96",
    "fee": "26.96",
    "asset": "USDG",
    "balance_asset": "USD",
    "direction": "DEBIT",
    "type": "CRYPTO_WITHDRAWAL",
    "status": "PENDING",
    ...
    "destination_address": "0x9acb61E5fcE9B5BdA7B44635d86be19d2790D9a9",
    "crypto_network": "ETHEREUM",
    "auto_conversion": {}
}
```

PYUSD on Solana

```json highlight={13} theme={null}
{
    "id": "e655c587-e057-4cf2-88d9-7e19ae13f2ee",
    "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "ref_id": "cw_pyusd_sol_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
    "amount": "100",
    "total": "100",
    "fee": "0",
    "asset": "PYUSD",
    "balance_asset": "USD",
    "direction": "DEBIT",
    "type": "CRYPTO_WITHDRAWAL",
```

```
    "status": "PENDING",
    ...
    "destination_address": "BtXdwoYSWPprQT88ZCLuQcXuTz4dFHB1AJFYqr5uXoAd",
    "crypto_network": "SOLANA",
    "auto_conversion": {}
}
```

To check the transaction status on the Paxos platform, use [List Transfers](/api-reference/endpoints/transfers/list-transfers).
You can create a recurring request that look for completed transactions in the Profile.
For example, filter on `type=CRYPTO_WITHDRAWAL` and `status=COMPLETED` parameters to find all the completed transactions.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?
type=CRYPTO_WITHDRAWAL&status=COMPLETED' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

By default, the response includes transactions from newest to oldest.

```json highlight={15,33} theme={null}
{
    "items": [
                {
            "id": "7c223577-832b-4235-a77e-ebf36dfe9860",
            "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "ref_id": "cw_usdg_eth_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
            "amount": "100",
            "total": "126.96",
            "fee": "26.96",
            "asset": "USDG",
            "balance_asset": "USD",
            "direction": "DEBIT",
            "type": "CRYPTO_WITHDRAWAL",
            "status": "COMPLETED",
            ...
            "destination_address": "0x9acb61E5fcE9B5BdA7B44635d86be19d2790D9a9",
            "crypto_network": "ETHEREUM",
            "crypto_tx_hash":
"0x2a0bac30de037b62502540c18ac22b6d75312cd1508c1df3eb6e38f8b7503f1a",
            "auto_conversion": {}
        },{
            "id": "e655c587-e057-4cf2-88d9-7e19ae13f2ee",
            "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "ref_id": "cw_pyusd_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
            "amount": "100",
            "total": "100",
            "fee": "0",
            "asset": "PYUSD",
            "balance_asset": "USD",
            "direction": "DEBIT",
            "type": "CRYPTO_WITHDRAWAL",
            "status": "COMPLETED",
            ...
            "destination_address": "BtXdwoYSWPprQT88ZCLuQcXuTz4dFHB1AJFYqr5uXoAd",
            "crypto_network": "SOLANA",
            "crypto_tx_hash":
"3ShgmRdcuj2usV3tmLvb3BUrEvhAXNWbUseYgRt24Muyv1tiPkohn8ZQAAdS5KeYNLKR6PhmwUta6CW2ZCAuxHt5",
            "crypto_tx_index": "0",
            "auto_conversion": {}
```

```
        },
    ],
    "next_page_cursor": "CAESCwiP-OazBhDgzZYyGLSOkw0"
}
```

Convert
Source: https://docs.paxos.com/guides/developer/orchestrations/convert

Execute conversions between supported assets.

Overview

Orchestrations enable seamless conversions between different stablecoins and currencies. These can be triggered through ad-hoc orchestrations from profiles or rule-based orchestrations from external deposits, and then routed to any supported destination.

Conversion Flow Options

```mermaid theme={null}
graph LR
    %% Color scheme
    classDef profile fill:#e6f7ed,stroke:#16a34a,stroke-width:2px,color:#15803d
    classDef crypto fill:#f3e5f5,stroke:#9333ea,stroke-width:2px,color:#6b21a8
    classDef external fill:#e0e7ff,stroke:#3730a3,stroke-width:2px,color:#312e81
    classDef apiCall fill:#f3f4f6,stroke:#6b7280,stroke-width:2px,color:#374151
    classDef rule fill:#fef3c7,stroke:#f59e0b,stroke-width:2px,color:#92400e
    classDef paxosBox fill:transparent,stroke:#16a34a,stroke-width:2px,stroke-dasharray:5
    classDef externalBox fill:transparent,stroke:#3730a3,stroke-width:2px,stroke-dasharray:5

    %% Example 1: Ad-hoc Profile to Profile
    CreateOrch["🔧 API: Create<br/>Orchestration"]:::apiCall

    subgraph flow1["Example 1: Ad-hoc (Profile to Profile)"]
        ProfilePYUSD["👤 Profile<br/>PYUSD Balance"]:::profile
        DestProfileUSDG["👤 Profile<br/>USDG Balance"]:::profile
    end

    %% Example 2: Rule-based External to External
    CreateRule["🔧 API: Create<br/>Orchestration Rule"]:::apiCall
    ExtDeposit["⛓ External<br/>USDG Deposit"]:::external

    subgraph flow2["Example 2: Rule-based (External to External)"]
        USDGRule["📋 USDG Deposit<br/>Rule"]:::rule
        ExtUSDC["⛓ External Address<br/>USDC Tokens"]:::crypto
    end

    %% Flow 1 connections
    CreateOrch ==>|"Initiates"| ProfilePYUSD
    ProfilePYUSD -->|"Convert PYUSD → USDG"| DestProfileUSDG

    %% Flow 2 connections
    CreateRule ==>|"Creates"| USDGRule
    ExtDeposit -.->|"Activates"| USDGRule
    USDGRule -->|"Convert USDG → USDC<br/>& withdraw"| ExtUSDC
```

Creating Conversions

Example 1: PYUSD → USDG (Ad-hoc, Profile to Profile)

Use the [Create Orchestration](/api-reference/endpoints/orchestration/create-orchestration) endpoint to convert PYUSD to USDG between Paxos profiles:

<Expandable title="Request">
```bash theme={null}
curl -X POST 'https://api.paxos.com/v2/orchestration/orchestrations' \
  -H 'Authorization: Bearer {access_token}' \
  -H 'Content-Type: application/json' \
  -d '{
    "ref_id": "convert_pyusd_usdg_profile",
    "profile_id": "{profile_id}",
    "source_asset": "PYUSD",
    "source_amount": "100",
    "destination_asset": "USDG",
    "source": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    },
    "destination": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    }
  }'
```
</Expandable>

<Expandable title="Response">
```json theme={null}
{
  "orchestration": {
    "id": "orch_123abc",
    "ref_id": "convert_pyusd_usdg_profile",
    "profile_id": "{profile_id}",
    "source_asset": "PYUSD",
    "source_amount": "100",
    "destination_asset": "USDG",
    "destination_amount": "100",
    "source": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    },
    "destination": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    },
    "status": "PROCESSING",
    "created_at": "2024-01-15T10:00:00Z"
  }
}
```
</Expandable>

Example 2: USDG → USDC (Rule-based, External to External)

Use the [Create Orchestration Rule](/api-reference/endpoints/orchestration-rules/create-orchestration-rule) endpoint to automatically convert external USDG deposits to USDC and send to an external address. First [register the destination address](./orchestrations#required-setup-for-external-crypto-destinations) to get a `crypto_address_id`:

<Expandable title="Request">
```bash theme={null}
curl -X POST 'https://api.paxos.com/v2/orchestration/rules' \
```

```
     -H 'Authorization: Bearer {access_token}' \
     -H 'Content-Type: application/json' \
     -d '{
       "ref_id": "convert_usdg_usdc_rule",
       "nickname": "Auto Convert USDG to USDC",
       "profile_id": "{profile_id}",
       "source_asset": "USDG",
       "destination_asset": "USDC",
       "source": {
         "crypto": {
           "network": "ETHEREUM"
         }
       },
       "destination": {
         "crypto": {
           "crypto_address_id": "crypto_addr_456def"
         }
       }
     }'
```

</Expandable>

<Expandable title="Response">

```json theme={null}
{
  "rule": {
    "id": "rule_456def",
    "ref_id": "convert_usdg_usdc_rule",
    "nickname": "Auto Convert USDG to USDC",
    "profile_id": "{profile_id}",
    "source_asset": "USDG",
    "destination_asset": "USDC",
    "source": {
      "crypto": {
        "address_id": "addr_789xyz",
        "address": "0x8B3D70c8F55e9C7E5b0bC2A9b0e7d1fF2c3d4E5F",
        "network": "ETHEREUM"
      }
    },
    "destination": {
      "crypto": {
        "crypto_address_id": "crypto_addr_456def"
      }
    },
    "status": "ACTIVE",
    "created_at": "2024-01-15T10:00:00Z"
  }
}
```

</Expandable>

How It Works

Ad-hoc Conversions

1. **Call the API**: Create an orchestration specifying source and destination assets
2. **Validation**: Paxos validates the request and available balance
3. **Conversion**: Assets are converted
4. **Delivery**: Converted assets are deposited to the specified profile
5. **Monitor Status**: Track your orchestration progress using [webhooks or API polling](./orchestrations#monitoring-orchestration-status)

Rule-based Conversions

1. **Create the Rule**: Set up an orchestration rule for automatic conversion

2. **Get Deposit Address**: Use the address returned in the rule's `source.crypto.address` field
3. **Receive Deposit**: External USDG arrives at your Paxos crypto address
4. **Automatic Trigger**: The rule detects the deposit and initiates conversion
5. **Conversion**: USDG is converted to USDC
6. **Delivery**: USDC is sent to the specified external address
7. **Monitor Status**: Track your orchestration progress using [webhooks or API polling](./orchestrations#monitoring-orchestration-status)

Next Steps

* Learn about [minting stablecoins](./mint) from USD deposits
* Explore [redeeming stablecoins](./redeem) back to USD

Mint
Source: https://docs.paxos.com/guides/developer/orchestrations/mint

Convert USD to Stablecoins and transfer all in one call.

Overview

Orchestrations enable you to automatically convert USD into stablecoins. This powerful feature enables seamless fiat-to-crypto conversions through rule-based orchestrations that trigger upon receiving bank transfers.
You can also mint straight from profile USD funds by issuing an ad-hoc conversion.

Mint Flow Options

The following diagram shows two example mint flows:

```mermaid theme={null}
graph LR
    %% Color scheme
    classDef bank fill:#e0e7ff,stroke:#3730a3,stroke-width:2px,color:#312e81
    classDef rule fill:#fef3c7,stroke:#f59e0b,stroke-width:2px,color:#92400e
    classDef profile fill:#e6f7ed,stroke:#16a34a,stroke-width:2px,color:#15803d
    classDef crypto fill:#f3e5f5,stroke:#9333ea,stroke-width:2px,color:#6b21a8
    classDef paxosBox fill:transparent,stroke:#16a34a,stroke-width:2px,stroke-dasharray:5
    classDef externalBox fill:transparent,stroke:#3730a3,stroke-width:2px,stroke-dasharray:5

    %% Bank deposit triggers
    BankDeposit["🏦 USD Bank<br/>Deposit"]:::bank

    %% Orchestration rules
    subgraph rules["ORCHESTRATION RULES"]
        Rule1["📋 Rule 1:<br/>USD → USDC<br/>to Profile"]:::rule
        Rule2["📋 Rule 2:<br/>USD → USDG<br/>to External"]:::rule
    end

    %% Destinations
    subgraph paxosDest["Paxos Profile"]
        ProfileUSDC["👤 Profile<br/>USDC Balance"]:::profile
    end

    subgraph extDest["External Wallet"]
        ExtUSDG["⛓ External Address<br/>USDG Tokens"]:::crypto
    end

    %% Flow connections
    BankDeposit -->|"Matches<br/>Rule 1"| Rule1
    BankDeposit -->|"Matches<br/>Rule 2"| Rule2

    Rule1 ==>|"Converts &<br/>Deposits"| ProfileUSDC
```

```
    Rule2 ==>|"Converts &<br/>Withdraws"| ExtUSDG

    %% Style the subgraphs
    class paxosDest paxosBox
    class extDest externalBox
```

Creating Mint Orchestration Rules

Use the [Create Orchestration Rule](/api-reference/endpoints/orchestration-rules/create-orchestration-rule) endpoint to set up the rule-based minting:

Example 1: USD → USDC (Bank to Profile)

Create a rule that automatically converts USD deposits to USDC and stores in your profile:

<Expandable title="Request">

```bash theme={null}
curl -X POST 'https://api.paxos.com/v2/orchestration/rules' \
  -H 'Authorization: Bearer {access_token}' \
  -H 'Content-Type: application/json' \
  -d '{
    "ref_id": "mint_usd_to_usdc_profile",
    "nickname": "Auto Mint USDC to Profile",
    "profile_id": "{profile_id}",
    "source_asset": "USD",
    "destination_asset": "USDC",
    "source": {
      "fiat": {
        "network": "WIRE",
        "account_type": "SWIFT"
      }
    },
    "destination": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    }
  }'
```

</Expandable>

<Expandable title="Response">

```json theme={null}
{
  "rule": {
    "id": "rule_abc123",
    "ref_id": "mint_usd_to_usdc_profile",
    "nickname": "Auto Mint USDC to Profile",
    "profile_id": "{profile_id}",
    "source_asset": "USD",
    "destination_asset": "USDC",
    "source": {
      "fiat": {
        "deposit_instructions_id": "fiat_instr_123",
        "network": "WIRE",
        "account_type": "SWIFT",
        "memo_id": "PAXOS123456"
      }
    },
    "destination": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    },
```

```
        "status": "ACTIVE",
        "created_at": "2024-01-15T10:00:00Z"
      }
    }
```

</Expandable>

Example 2: USD → USDG (Bank to External Crypto Address)

Create a rule that automatically converts USD deposits to USDG and sends to an external address. First [register the destination address](./orchestrations#required-setup-for-external-crypto-destinations) to get a `crypto_address_id`:

<Expandable title="Request">

```bash theme={null}
curl -X POST 'https://api.paxos.com/v2/orchestration/rules' \
  -H 'Authorization: Bearer {access_token}' \
  -H 'Content-Type: application/json' \
  -d '{
    "ref_id": "mint_usd_to_usdg_external",
    "nickname": "Auto Mint USDG to External",
    "profile_id": "{profile_id}",
    "source_asset": "USD",
    "destination_asset": "USDG",
    "source": {
      "fiat": {
        "network": "WIRE",
        "account_type": "SWIFT"
      }
    },
    "destination": {
      "crypto": {
        "crypto_address_id": "crypto_addr_789xyz"
      }
    }
  }'
```

</Expandable>

<Expandable title="Response">

```json theme={null}
{
  "rule": {
    "id": "rule_xyz789",
    "ref_id": "mint_usd_to_usdg_external",
    "nickname": "Auto Mint USDG to External",
    "profile_id": "{profile_id}",
    "source_asset": "USD",
    "destination_asset": "USDG",
    "source": {
      "fiat": {
        "deposit_instructions_id": "fiat_instr_456",
        "network": "WIRE",
        "account_type": "SWIFT",
        "memo_id": "PAXOS789012"
      }
    },
    "destination": {
      "crypto": {
        "crypto_address_id": "crypto_addr_789xyz"
      }
    },
    "status": "ACTIVE",
    "created_at": "2024-01-15T10:00:00Z"
  }
```

```
  }
```
</Expandable>

How It Works

1. **Create the Rule**: Use the API to create an orchestration rule specifying source (bank deposit) and destination (profile or external address)
2. **Get Deposit Instructions**: Use the `deposit_instructions_id` and `memo_id` from the response to retrieve full banking details via [Get Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/get-fiat-deposit-instructions)
3. **Send Wire Transfer**: Send USD to the Paxos bank account using the provided instructions and memo ID
   * For sandbox testing, see [how to simulate fiat deposits](/guides/developer/fiat-transfers/quickstart#❷-send-fiat-to-paxos)
4. **Automatic Trigger**: The rule detects the deposit and initiates the orchestration
5. **Conversion**: USD is converted to your specified stablecoin (USDC, USDG, etc.)
6. **Delivery**: Stablecoins are either:
   * Deposited to your Paxos profile (Flow 1)
   * Sent to the external crypto address (Flow 2)
7. **Monitor Status**: Track your orchestration progress using [webhooks or API polling](./orchestrations#monitoring-orchestration-status)

Next Steps

* Learn about [redeeming stablecoins](./redeem) back to USD
* Explore [conversions](./convert) between different stablecoins

Overview
Source: https://docs.paxos.com/guides/developer/orchestrations/orchestrations

Orchestrations power complex workflows.

Understanding Orchestrations

Orchestrations allow customers to perform complex actions by executing multi-step workflows to move between assets, networks, and rails. There are two types of Orchestrations:
ad-hoc, and rule-based. Ad-hoc orchestrations are one-off orchestrations that can be triggered
to move funds from a profile to a number of destinations. Rule-based orchestrations are based
off a rule which is triggered upon deposit to a crypto address or a bank account.

As we'll show in the [mint](), [convert](), and [redeem]() pages these orchestrations can be harnessed to perform a number of operations.

Orchestration Flow Diagram

The following diagram illustrates the possible orchestration routes within the Paxos platform:

```mermaid theme={null}
graph LR
    %% Color scheme
    classDef profile fill:#e6f7ed,stroke:#16a34a,stroke-width:2px,color:#15803d
    classDef ruleSource fill:#fef3c7,stroke:#f59e0b,stroke-width:2px,color:#92400e
    classDef external fill:#e0e7ff,stroke:#3730a3,stroke-width:2px,color:#312e81
    classDef apiCall fill:#f3f4f6,stroke:#6b7280,stroke-width:2px,color:#374151
    classDef paxosBox fill:transparent,stroke:#16a34a,stroke-width:2px,stroke-dasharray:5
    classDef externalBox fill:transparent,stroke:#3730a3,stroke-width:2px,stroke-dasharray:5
    classDef hidden fill:transparent,stroke:transparent,color:transparent

    subgraph triggers["TRIGGERS"]
```

```
        CreateOrch["🔧 API: Create<br/>Orchestration"]:::apiCall
        ExtFiat["🏦 Bank Deposit"]:::external
        ExtCrypto["⛓ Blockchain Deposit"]:::external
    end

    subgraph sources["SOURCES (Paxos Managed)"]
        %% Invisible spacer to prevent Profile A from overlapping with the subgraph label
        spacer[" "]:::hidden
        ProfileA["👤 Profile A"]:::profile
        FiatInstr["📋 Fiat Deposit<br/>Instructions<br/>(Rule-based)"]:::ruleSource
        CryptoInstr["📋 Crypto Deposit<br/>Address<br/>(Rule-based)"]:::ruleSource
    end

    subgraph destinations["DESTINATIONS"]
        subgraph paxosDest["Paxos Managed"]
            ProfileB["👤 Profile B"]:::profile
        end

        subgraph extDest["External"]
            ExtBank["🏦 External Bank<br/>Account"]:::external
            ExtCryptoAddr["⛓ External Crypto<br/>Address"]:::external
        end
    end

    %% API Call for rules (shown separately)
    CreateRule["🔧 API: Create<br/>Orchestration Rule"]:::apiCall

    %% Rule creation flow
    CreateRule ==>|"Creates"| FiatInstr
    CreateRule ==>|"Creates"| CryptoInstr

    %% External triggers activate rules
    ExtFiat -.->|"Activates"| FiatInstr
    ExtCrypto -.->|"Activates"| CryptoInstr

    %% Ad-hoc orchestration trigger
    CreateOrch ==>|"Ad-hoc"| ProfileA

    %% Central routing node
    Router["Can route to<br/>any destination"]:::apiCall

    %% Sources to router
    ProfileA --> Router
    FiatInstr -.-> Router
    CryptoInstr -.-> Router

    %% Router to all destinations
    Router --> ProfileB
    Router --> ExtBank
    Router --> ExtCryptoAddr

    %% Style the subgraphs
    class sources paxosBox
    class paxosDest paxosBox
    class extDest externalBox
```

* **Rule-based Orchestrations**: Originate from external fiat deposits (bank accounts) or external crypto deposits (blockchain). These trigger automatically when a matching rule exists.
* **Ad-hoc Orchestrations**: Must originate from internal profiles but can route to profiles, external fiat accounts, or external crypto addresses.
* **Profile-to-Profile Transfers**: Customers with multiple internal profiles can execute ad-hoc transfers between them.

* **Asset Conversion**: Any transfer can involve different source and destination assets (not shown for clarity but applies to all routes).

Required Authentication Scopes

To use orchestrations, you'll need the following OAuth scopes when [authenticating](/guides/developer/authenticate):

Core Orchestration Operations

* **Ad-hoc Orchestrations**:
  * `orchestration:read_orchestration` - View orchestration status
  * `orchestration:write_orchestration` - Create orchestrations
* **Rule-based Orchestrations**:
  * `orchestration:read_orchestration_rule` - View orchestration rules
  * `orchestration:write_orchestration_rule` - Create and manage rules

Supporting Operations

* **Webhook Monitoring**:
  * `events:read_event` - Read the object payloads for webhook events
* **Fiat Operations** (for bank withdrawals):
  * `transfer:read_fiat_account` - View fiat account details
  * `transfer:write_fiat_account` - Create fiat accounts
  * `transfer:read_fiat_deposit_instructions` - View deposit instructions
  * `transfer:write_fiat_deposit_instructions` - Create deposit instructions
* **Crypto Address Registration** (optional):
  * `transfer:read_crypto_destination_address` - View registered addresses
  * `transfer:write_crypto_destination_address` - Register new addresses

Monitoring Orchestration Status

Orchestrations can exist in three states. To monitor them there's a few options.

  ```mermaid theme={null}
  stateDiagram-v2
      [*] --> PROCESSING: Orchestration Created
      PROCESSING --> COMPLETED: Success
      PROCESSING --> FAILED: Error
  ```

Recommended: Using Webhooks

> Subscribe to orchestration webhooks for real-time status monitoring. This is the recommended approach as it provides immediate notifications without polling.

Webhooks are triggered upon each status change in the orchestration lifecycle.

The webhook payload contains an event ID that you use to fetch the full [`orchestration_status_change`](/api-reference/events/orchestration-status-change-object) event details:

<Expandable title="Webhook Payload">
  ```json theme={null}
  {
      "id": "bd019f1c-89a7-4372-9d21-eaad9280dc41",
      "type": "orchestration.completed",
      "source": "com.paxos",
      "time": "2025-01-07T14:30:02Z",
      "object": "event"
  }
  ```
</Expandable>

Fetch the event details to get the orchestration information:

<Expandable title="Orchestration Status Change Event">
```json theme={null}
{
    "id": "ea284608c-4cf0-4605-ae0a-5c1f7ff109d3", // orchestration_id
    "orchestration_rule_id": "7f8a9b1c-2d3e-4f5a-6b7c-8d9e0f1a2b3c",  // Present if triggered by a rule
    "ref_id": "orch_usdg_usd_a284608c-4cf0-4605-ae0a-5c1f7ff109d3",
    "status": "COMPLETED"
}
```
</Expandable>

> When orchestrations are triggered by a rule, the event object will include an `orchestration_rule_id` field linking back to the originating rule.

Alternative: Polling with API

Use [List Orchestrations](/api-reference/endpoints/orchestration/list-orchestrations) to check orchestration status:

<Expandable title="List Orchestration Request">
```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/orchestration/orchestrations?profile_id=0d3172c5-8840-4bae-bdd4-30688f0268fc&order=DESC' \
  --header 'Accept: application/json' \
  --header 'Authorization: Bearer {access_token}'
```
</Expandable>

The response includes all orchestrations for the profile with their current status:

<Expandable title="List Orchestration Response">
```json theme={null}
{
    "orchestrations": [
        {
            "id": "ea284608c-4cf0-4605-ae0a-5c1f7ff109d3",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "source_asset": "USDG",
            "source_amount": "100",
            "destination_asset": "USD",
            "destination_amount": "100",
            "status": "COMPLETED",
            "ref_id": "orch_usdg_usd_a284608c-4cf0-4605-ae0a-5c1f7ff109d3",
            "created_at": "2024-09-25T15:07:50.123456Z",
            "completed_at": "2024-09-25T15:07:56.076853Z",
            ...
        },
        {
            "id": "f190b163-208f-4d73-8deb-4fb8b24add00",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "orchestration_rule_id": "7f8a9b1c-2d3e-4f5a-6b7c-8d9e0f1a2b3c",
            "source_asset": "USD",
            "source_amount": "100",
            "destination_asset": "PYUSD",
            "destination_amount": "100",
            "status": "COMPLETED",
            "ref_id": "auto_rule_generated_ref_123",
            "created_at": "2024-09-25T15:07:15.654321Z",
            "completed_at": "2024-09-25T15:07:21.548903Z",
            ...
        }
```

```
      ],
      "next_page_cursor": "..."
  }
```
</Expandable>

Required Setup for External Crypto Destinations

When sending funds to external crypto addresses in orchestrations, you must first register the destination address using [Put Crypto Destination Address](/api-reference/endpoints/crypto-destination-addresses/put-crypto-destination-address). This is required to:

* Store travel rule metadata for compliance
* Obtain a `crypto_address_id` for use in orchestrations
* Manage approved destination addresses

Adding a Crypto Destination Address

<Expandable title="Request">
```bash theme={null}
curl -X PUT 'https://api.paxos.com/v2/transfer/crypto-destination-address' \
  -H 'Authorization: Bearer {access_token}' \
  -H 'Content-Type: application/json' \
  -d '{
    "crypto_network": "ETHEREUM",
    "address": "0x742d35Cc6634C0532925a3b844Bc9e7595f0bEb",
    "name": "External Treasury Wallet",
    "identity_id": "{identity_id}",
    "account_id": "{account_id}"
  }'
```
</Expandable>

<Expandable title="Response">
```json theme={null}
{
  "address": {
    "id": "crypto_addr_123abc",
    "crypto_network": "ETHEREUM",
    "address": "0x742d35Cc6634C0532925a3b844Bc9e7595f0bEb",
    "name": "External Treasury Wallet",
    "identity_id": "{identity_id}",
    "account_id": "{account_id}",
    "created_at": "2024-01-15T10:00:00Z"
  }
}
```
</Expandable>

Using Registered Addresses in Orchestrations

Once registered, reference the address by its ID in orchestration destinations:

```json theme={null}
"destination": {
  "crypto": {
    "crypto_address_id": "crypto_addr_123abc"
  }
}
```

Redeem
Source: https://docs.paxos.com/guides/developer/orchestrations/redeem

Convert stablecoins to USD and withdraw to your bank in one call.

Overview

Orchestrations enable you to convert stablecoins back to USD and withdraw to external bank accounts. These can be triggered through ad-hoc orchestrations from profiles or rule-based orchestrations from external crypto deposits.

Redeem Flow Options

```mermaid theme={null}
graph LR
    %% Color scheme
    classDef profile fill:#e6f7ed,stroke:#16a34a,stroke-width:2px,color:#15803d
    classDef crypto fill:#f3e5f5,stroke:#9333ea,stroke-width:2px,color:#6b21a8
    classDef bank fill:#e0e7ff,stroke:#3730a3,stroke-width:2px,color:#312e81
    classDef apiCall fill:#f3f4f6,stroke:#6b7280,stroke-width:2px,color:#374151
    classDef rule fill:#fef3c7,stroke:#f59e0b,stroke-width:2px,color:#92400e
    classDef paxosBox fill:transparent,stroke:#16a34a,stroke-width:2px,stroke-dasharray:5
    classDef externalBox fill:transparent,stroke:#3730a3,stroke-width:2px,stroke-dasharray:5

    %% Example 1: Ad-hoc Profile to External Bank
    CreateOrch["🔧 API: Create<br/>Orchestration"]:::apiCall

    subgraph flow1["Example 1: Ad-hoc (Profile to Bank)"]
        ProfileUSDC["👤 Profile<br/>USDC Balance"]:::profile
        BankUSD1["🏦 External Bank<br/>USD"]:::bank
    end

    %% Example 2: Rule-based External to External
    CreateRule["🔧 API: Create<br/>Orchestration Rule"]:::apiCall
    ExtDeposit["⛓ External<br/>USDG Deposit"]:::crypto

    subgraph flow2["Example 2: Rule-based (External to Bank)"]
        USDGRule["📋 USDG Deposit<br/>Rule"]:::rule
        BankUSD2["🏦 External Bank<br/>USD"]:::bank
    end

    %% Flow 1 connections
    CreateOrch ==>|"Initiates"| ProfileUSDC
    ProfileUSDC -->|"Convert USDC → USD<br/>& withdraw"| BankUSD1

    %% Flow 2 connections
    CreateRule ==>|"Creates"| USDGRule
    ExtDeposit -.->|"Activates"| USDGRule
    USDGRule -->|"Convert USDG → USD<br/>& withdraw"| BankUSD2
```

Creating Redemptions

Example 1: USDC → USD (Ad-hoc, Profile to Bank)

Use the [Create Orchestration](/api-reference/endpoints/orchestration/create-orchestration) endpoint to convert USDC from your profile to USD and withdraw to a bank account. You'll need a `bank_account_id` from [creating a fiat account](/guides/developer/fiat-transfers/quickstart#❶-create-fiat-account):

<Expandable title="Request">
  ```bash theme={null}
  curl -X POST 'https://api.paxos.com/v2/orchestration/orchestrations' \
    -H 'Authorization: Bearer {access_token}' \
    -H 'Content-Type: application/json' \
    -d '{
  ```

```
      "ref_id": "redeem_usdc_usd_bank",
      "profile_id": "{profile_id}",
      "source_asset": "USDC",
      "source_amount": "500",
      "destination_asset": "USD",
      "source": {
        "profile": {
          "profile_id": "{profile_id}"
        }
      },
      "destination": {
        "fiat": {
          "bank_account_id": "{bank_account_id}",
          "memo": "Redemption payment"
        }
      }
    }'
```

</Expandable>

<Expandable title="Response">

```json theme={null}
{
  "orchestration": {
    "id": "orch_789ghi",
    "ref_id": "redeem_usdc_usd_bank",
    "profile_id": "{profile_id}",
    "source_asset": "USDC",
    "source_amount": "500",
    "destination_asset": "USD",
    "destination_amount": "500",
    "source": {
      "profile": {
        "profile_id": "{profile_id}"
      }
    },
    "destination": {
      "fiat": {
        "bank_account_id": "{bank_account_id}",
        "memo": "Redemption payment"
      }
    },
    "status": "PROCESSING",
    "created_at": "2024-01-15T10:00:00Z"
  }
}
```

</Expandable>

Example 2: USDG → USD (Rule-based, External to Bank)

Use the [Create Orchestration Rule](/api-reference/endpoints/orchestration-rules/create-orchestration-rule) endpoint to automatically convert external USDG deposits to USD and withdraw to a bank account. You'll need a `bank_account_id` from [creating a fiat account](/guides/developer/fiat-transfers/quickstart#❶-create-fiat-account):

<Expandable title="Request">

```bash theme={null}
curl -X POST 'https://api.paxos.com/v2/orchestration/rules' \
  -H 'Authorization: Bearer {access_token}' \
  -H 'Content-Type: application/json' \
  -d '{
    "ref_id": "redeem_usdg_usd_rule",
    "nickname": "Auto Redeem USDG to Bank",
    "profile_id": "{profile_id}",
```

```
      "source_asset": "USDG",
      "destination_asset": "USD",
      "source": {
        "crypto": {
          "network": "ETHEREUM"
        }
      },
      "destination": {
        "fiat": {
          "bank_account_id": "{bank_account_id}",
          "memo": "Auto redemption"
        }
      }
    }'
```

</Expandable>

<Expandable title="Response">

```json theme={null}
{
  "rule": {
    "id": "rule_321mno",
    "ref_id": "redeem_usdg_usd_rule",
    "nickname": "Auto Redeem USDG to Bank",
    "profile_id": "{profile_id}",
    "source_asset": "USDG",
    "destination_asset": "USD",
    "source": {
      "crypto": {
        "address_id": "addr_456def",
        "address": "0x1A2B3C4D5E6F7G8H9I0J1K2L3M4N5O6P7Q8R9S0T",
        "network": "ETHEREUM"
      }
    },
    "destination": {
      "fiat": {
        "fiat_account_id": "{bank_account_id}",
        "memo": "Auto redemption"
      }
    },
    "status": "ACTIVE",
    "created_at": "2024-01-15T10:00:00Z"
  }
}
```

</Expandable>

How It Works

Ad-hoc Redemptions

1. **Call the API**: Create an orchestration specifying source stablecoin and destination bank account
2. **Validation**: Paxos validates the request, available balance, and bank account status
3. **Conversion**: Stablecoins are converted to USD
4. **Withdrawal**: USD is sent to the specified bank account via wire transfer
5. **Monitor Status**: Track your orchestration progress using [webhooks or API polling](./orchestrations#monitoring-orchestration-status)

Rule-based Redemptions

1. **Create the Rule**: Set up an orchestration rule for automatic redemption
2. **Get Deposit Address**: Use the address returned in the rule's `source.crypto.address` field
3. **Receive Deposit**: External USDG arrives at your Paxos crypto address

4. **Automatic Trigger**: The rule detects the deposit and initiates redemption
5. **Conversion**: USDG is converted to USD
6. **Withdrawal**: USD is sent to the specified bank account
7. **Monitor Status**: Track your orchestration progress using [webhooks or API polling](./orchestrations#monitoring-orchestration-status)

Prerequisites

* **Bank Account**: Must have an approved bank account added via [Create Fiat Account](/api-reference/endpoints/fiat-transfers/create-fiat-account)
* **Account Status**: Verify account is `APPROVED` using [Get Fiat Account](/api-reference/endpoints/fiat-transfers/get-fiat-account)

Next Steps

* Learn about [minting stablecoins](./mint) from USD deposits
* Explore [conversions](./convert) between different stablecoins

Rate Limits
Source: https://docs.paxos.com/guides/developer/rate-limits

Review REST, WebSocket and FIX limits.

Paxos implements REST and WebSocket limits to help ensure platform stability.
All integrations should observe the stated rate limits to prevent disruptions.

REST Limits

Paxos sets rate limits per endpoint and IP address, based on the average number of requests per second during a five (5) minute window.
If you hit a rate limit on a specific endpoint, you will receive a `429` response status code. All requests from the offending IP are then throttled for five (5) minutes.

| API Path
| Limit |
| ---
--- | ----- |
| /register*
/signup*
/create-new-user*
/login*
/oauth2/token*
| 1 |
| /wallets*
/v2/markets/*/order-book
/v2/markets/*/recent-executions
/v2/profiles/*/quote-executions
/v2/identities/*/ | 10 |
| /v2/transfer/internal
/v2/transfer/crypto-withdrawals
| 20 |
| All other endpoints
| 50 |

Minimally, Paxos recommends gracefully handling limits by watching for `429` status codes and building retry functionality.
The retry mechanism should include a backoff schedule that takes volume into consideration.
There are a number of open source tools available to help handle rate limits.

WebSocket Limits

Market and execution data services have a rate limit of one (1) subscription per second from the same IP address.
If the rate limit is exceeded, no error message is sent.
Rather, each client must wait one (1) second before receiving data.
For example, if 20 new clients connect from the same IP address, it will take about 20 seconds for all the clients to receive data.

> When connecting a large number of clients, some may fail and close the connection before receiving a response from the server.

Paxos recommends all clients implement a single `wss://` connection at the server level

(multiplexing).
Multiple connections can create logistical and update issues without providing appreciable performance gains.
To support integration and platform stability and maintenance, each implementation should:

* Ensure all application clients can easily rollout platform updates to users through a single mechanism.
* Have a centralized reconnection mechanism to recover from any feed disruptions.
* Have a reconnection mechanism in case of server disconnection.
* Observe the WebSocket rate limits.

Paxos support may reach out to you if your client does not implement this guidance.

FIX Limits

Maximum 150 messages per second, per session.

Redeem
Source: https://docs.paxos.com/guides/developer/redeem

Deposit stablecoin and convert to USD in one API call. Transfer USD to your bank.

<Warning title="Stablecoin Conversions Deprecation Notice">
  The Stablecoin Conversions API will be deprecated.

  Paxos will migrate all active conversion rules to the [Orchestrations API](/guides/developer/orchestrations/orchestrations) format by December 2025.

  Customers should transition to the Orchestrations API to ensure continuity of service.
</Warning>

<img alt="Redeem Workflow" />

To redeem a [Paxos-issued stablecoin](/guides/developer/blockchains#stablecoins), use [Create Deposit Address](/api-reference/endpoints/deposit-addresses/create-deposit-address) to add the appropriate address on the Paxos platform. Next, initiate a stablecoin transfer from your external address (**A** in the diagram).
If you set `conversion_target_asset` to `USD` when creating the address, Paxos automatically credits your USD balance once the on-chain transfer is confirmed (**B**).
Then, use [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal) to send USD to your bank account (**C**).

<Tip>
  * To redeem stablecoins you already hold on the Paxos platform, you can use [Create Stablecoin Conversion](/api-reference/endpoints/stablecoin-conversion/create-stablecoin-conversion) to easily convert to USD. See the [conversion guide](/guides/developer/convert) for details.
  * To send USD to your bank account, you'll need to first save your external banking information on the Paxos platform. See the [fiat withdrawal guide](/guides/developer/fiat-transfers/quickstart#withdrawal) for details.
</Tip>

❶ Authenticate

Include the following scopes when [authenticating](/guides/developer/authenticate):

```shell theme={null}
funding:read_profile transfer:read_deposit_address transfer:read_transfer
transfer:write_deposit_address

```

> If you don't see all the scopes when [creating or editing API credentials](/guides/developer/credentials), contact [Support](https://support.paxos.com).

❷ Create Deposit Address

Use [Create Deposit Address](/api-reference/endpoints/deposit-addresses/create-deposit-address) to add a wallet address to the designated Profile.
Include the appropriate `crypto_network` for the source stablecoin.
Set `conversion_target_asset` to `USD` to automatically convert the stablecoin to USD when the transaction is complete.

USDG on Ethereum

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/deposit-addresses' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token} \
--data '{
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "crypto_network": "ETHEREUM",
    "ref_id": "r_usdg_8f91a9c5-0a6e-46dc-ad68-17bc8fb4eafb",
    "conversion_target_asset": "USD"
}'
```

PYUSD on Solana

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/deposit-addresses' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "crypto_network": "SOLANA",
    "ref_id": "r_pyusd_8f91a9c5-0a6e-46dc-ad68-17bc8fb4eafb",
    "conversion_target_asset": "USD"
}'
```

Capture the `address` and `compatible_crypto_networks` values from the response.
Also store the `id` to use when looking up transactions.

USDG on Ethereum

```json highlight={2,8,11} theme={null}
{
    "id": "078eb145-1bbc-4e1d-999d-92845dc31df4",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
    "crypto_network": "ETHEREUM",
    "identity_id": "00000000-0000-0000-0000-000000000000",
    "ref_id": "r_usdg_8f91a9c5-0a6e-46dc-ad68-17bc8fb4eafb",
    "address": "0xdCB1481afaabf9dAc1B2A8218067252D533Ae1a7",
    "account_id": "00000000-0000-0000-0000-000000000000",
    "conversion_target_asset": "USD",
    "compatible_crypto_networks": [
        "ETHEREUM",
        "POLYGON_POS",
        "ARBITRUM_ONE"
    ]
}
```

PYUSD on Solana

```json highlight={2,8,11} theme={null}
{
    "id": "8488990c-2cc0-441f-a26c-24d01c40a402",
    "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
    "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
    "crypto_network": "SOLANA",
    "identity_id": "00000000-0000-0000-0000-000000000000",
    "ref_id": "r_pyusd_8f91a9c5-0a6e-46dc-ad68-17bc8fb4eafb",
    "address": "AufgJhf3DW83MUKgCKyrMyNjdCzhcy4LrcXcQsCDQRb2",
    "account_id": "00000000-0000-0000-0000-000000000000",
    "conversion_target_asset": "USD",
    "compatible_crypto_networks": [
        "SOLANA"
    ]
}
```

❸ Transfer Stablecoin to the Paxos Platform

Initiate an on-chain transfer from your external wallet to the `address` included in the response from the [previous step](#add-deposit-address) or from [List Deposit Addresses](/api-reference/endpoints/deposit-addresses/list-deposit-addresses).

Use [List Transfers](/api-reference/endpoints/transfers/list-transfers) to check the status of transfer on the Paxos platform.
Using the `type=CRYPTO_DEPOSIT` and `status=COMPLETED` query parameters, in conjunction with `crypto_tx_hashes`, filters the results.

USDG on Ethereum

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?
crypto_tx_hashes=0x768ac1e892985165885140c80f08ee0197ff6e175f9a9ed4b7f1b09c3b49baca' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

PYUSD on Solana

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?
crypto_tx_hashes=3LnaTGt2hmLGFwRkZyh7bGPj8UyYFjJauTS2c4PZ6YQfqwBqTmN8Z6j3LhFrqgTRX7ZcyJrF2Nr
rJxztAX3n3uL9' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

Depending on the network, it may take some time for the transaction to update on the Paxos platform.
Once the status is `COMPLETED`, the USD balance updates.

USDG on Ethereum

```json theme={null}
{
    "items": [
        {
            "id": "d72363d9-52bb-4acd-ba35-b5b1e212ac26",
            "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "amount": "100",
            "total": "100",
            "fee": "0",
            "asset": "USDG",
            "balance_asset": "USD",
```

```
            "direction": "CREDIT",
            "type": "CRYPTO_DEPOSIT",
            "status": "COMPLETED",
            ...
            "destination_address": "0xdCB1481afaabf9dAc1B2A8218067252D533Ae1a7",
            "crypto_network": "ETHEREUM",
            "crypto_tx_hash":
"0x768ac1e89298516588514 0c80f08ee0197ff6e175f9a9ed4b7f1b09c3b49baca",
            "crypto_tx_index": "132",
            "auto_conversion": {}
        }
    ],
    "next_page_cursor": "CAESDAjJq_a3BhCI9LaXAhjwhN8N"
}
```


PYUSD on Solana


```json theme={null}
{
    "items": [
        {
            "id": "54235f7e-585c-4c08-b170-15bb10f74c1e",
            "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
            "profile_id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "amount": "100",
            "total": "100",
            "fee": "0",
            "asset": "PYUSD",
            "balance_asset": "USD",
            "direction": "CREDIT",
            "type": "CRYPTO_DEPOSIT",
            "status": "COMPLETED",
            ...
            "destination_address": "AufgJhf3DW83MUKgCKyrMyNjdCzhcy4LrcXcQsCDQRb2",
            "crypto_network": "SOLANA",
            "crypto_tx_hash":
"3LnaTGt2hmLGFwRkZyh7bGPj8UyYFjJauTS2c4PZ6YQfqwBqTmN8Z6j3LhFrqgTRX7ZcyJrF2NrrJxztAX3n3uL9",
            "crypto_tx_index": "4",
            "auto_conversion": {}
        }
    ],
    "next_page_cursor": "CAESDAi7n_a3BhCIkuKsAxisgt8N"
}
```


❹ Transfer USD to Bank Account

Use [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal) to send USD to your bank account.
You'll need to first save your external banking information on the Paxos platform.
See the [fiat withdrawal guide](/guides/developer/fiat-transfers/quickstart#withdrawal) for details.

Reports
Source: https://docs.paxos.com/guides/developer/reports

View and download daily balance and transaction reconciliation reports.

Go to [Admin > Reports](https://dashboard.paxos.com/admin/reports) to [activate](#activate), view and download daily reconciliation reports as CSV.

The [Profile Transactions Report](#ProfileTransactionReport) lists every transaction during a 24 hour period, including the full list and definition of transaction types and

transaction metadata.
The [Profile Balances Report](#ProfileBalancesReport) provides the asset start and ending balances for every Profile during a 24 hour period.

> Migrating to the Dashboard? Existing legacy reconciliation reports are available in the Dashboard.
> The historical reconciliation reports match the files on the SFTP server, where they continue to be available.

In the reports, the Profile's starting balance is impacted by any associated Profile Transaction, and results in the corresponding Profile end balance.

* If a Profile has ever held a given asset at any point in the past, zero balances will be explicitly printed. For example, if Profile 1 held Bitcoin in the past, but not today, Profile Balances will appear as “BTC: 0”.
* If a Profile has never held an asset at any point in the past, zero balances will not be explicitly printed. For example, if Profile 1 has never held Bitcoin in the past, Profile Balances will not appear for the BTC asset at all.

Reports are in UTC 0 time, and have an exact hour cutoff for the UTC timezone indicated when [activating reporting](#activate).
Paxos delivers reports one time per day and does not support multiple cutoff times or changes to the pre-configured cutoff time.

Onboard to Reporting

To start receiving daily reports, fill out the form on [Admin > Reports](https://dashboard.paxos.com/admin/reports).
Once submitted, you should start receiving reports in about five business days.
Reports are delivered on a go-forward basis, starting the first day reporting is activated.

> Contact [Support](https://support.paxos.com) for help obtaining older reports.

Reporting Data Dictionary

This data dictionary provides a full list and definition of balance types.

Profile Balances Report Fields

The following fields are provided on each row of the Profile Balances Report.

Field	Data Type	Example/Description
Asset	String	USD, BTC, ETH, BCH, LTC, PAXG
Balance	String	9977417.21588054
BalanceType	Enum	See [BalanceType Value and Definitions](#BalanceTypeValuesDefinitions).
ProfileID	UUID	7927d51a-a465-49b9-ab0e-1ca17b3a7c5b
Timestamp	Datetime	2020-01-17T00:00:00.000Z

Profile Transactions Report Fields

The following fields are provided on each row of the Profile Transactions report.

Field	Data Type	Always Returns Data	Example/Description

--------- |
AccountID	UUID	No	1ab15e4f-6389-4a52-b908-62c3525b0da2
Amount	String	Yes	90.12345678
Assets	String	Yes	USD, ETH, BTC, PAXG, BCH, LTC
BalanceType	Enum	Yes	See [BalanceType Values and Definitions](#BalanceTypeValuesDefinitions).
BaseAmount	String	No	`10.017` The amount in the base asset for this trade, currently only supported for QuoteExecutions.
Direction	String	Yes	CREDIT, DEBIT
ExternalID	String	No	Contains the transaction hash for a crypto deposit. Returns empty when no data is available.
Fee	String	No	`0.017` The fee for this interaction. Currently only supported for Transfers.
GroupID	UUID	No	Link for the debit and credit legs of an Internal Transfer.
IdentityID	UUID	No	1ab15e4f-6389-4a52-b908-62c3525b0da2
Market	String	No	ETHUSD, XBTUSD, PAXGUSD, BCHUSD, LTCUSD
Metadata	String	No	`{"key_1":"value_11","key_2":"value_23"}` Contains the customer specified metadata during a transaction on platform (withdrawal, transfer, quote execution) in json-string format. Returns empty when no data is available.
OrchestrationID	UUID	No	7f716105-d501-40e8-a82f-309fffacd6d8 A unique identifier that links all related transactions within a single logical flow. For example, all balance updates during a deposit process.
OrchestrationRuleID	UUID	No	9e124f3d-7c88-4b36-b54a-e389f6c398b2 The unique identifier of the automation rule that triggered this transaction set.
OrderType	String	No	LIMIT, MARKET, POSTONLYLIMIT, STOPMARKET, STOPLIMIT, HRQ
Price	String	No	100.23
ProfileID	UUID	Yes	7927d51a-a465-49b9-ab0e-1ca17b3a7c5b
QuoteAmount	String	No	`10.50` The amount in the quote asset for this trade, currently only supported for QuoteExecutions.
Resource	Enum	Yes	See [Resource Values and Definitions](#ResourceValuesDefinitions).
ResourceID	UUID	Yes	ID of the Resource in question. For example, Order ID, Execution ID, Transfer ID.
ResourceRefID	String	No	Custom string specified in Create Order request as `ref_id`.
ResourceTimestamp	Datetime	No	The timestamp when the Resource was generated. For example, the time for an Order or an Execution.

|
| RecourceTransferType | Enum | No | See [ResourceTransferType Values and Definitions](#ResourceTransferTypeValuesDefinitions).
|
| Side | String | No | SELL, BUY
|
| Timestamp | Datetime | Yes | The record timestamp. For example: 2024-01-17T18:36:31.345Z
|
| TransactionType | Enum | Yes | See [TransactionType Values and Definitions](#TransactionTypeValuesDefinitions).
|
| UniqueTxID | String | Yes | Unique identifier for a Profile transaction. Use with direction to guarantee unique line-item.
|

BalanceType Values and Definitions

The BalanceType field indicates which specific balance the row is referring to.
It provides a way to precisely follow movement of funds as transactions complete in the [Profile Transaction Report](#ProfileTransactionReport), and identify the volume of funds held in reserve or in pending transactions at the end of each day in the [Profile Balances Report](#ProfileBalancesReport).

| BalanceType Enum Value | Description
|
| --- | --- |
| AVAILABLE | Balance that is currently available to trade or transfer.
|
| PENDING_DEBIT | Balance that is currently reserved for pending debits. For example, an outgoing transfer has been requested but not completed. |
| TRADING | Balance that is currently reserved for trading. For example, a limit order has been placed but not filled. |
| PENDING_CREDIT | Balance that is currently reserved for pending credits. For example, an incoming transfer has been requested but not completed. |

Resource Values and Definitions

The Resource field denotes the category of transaction being recorded on each row of the [Profile Transactions Report](#ProfileTransactionReport).

| Resource Enum Value | Description
|
| --- | --- |
| CONVERSION | Stablecoin conversion transaction.
|
| EXECUTION | An execution of an order on the order book. There can be multiple executions for one order. |
| ORDER | A market or limit order placed for trading. Using either FIX or the v2 Order service. |
| QUOTE_EXECUTION | A Held Rate Quote transaction.
|
| TRANSFER | A transfer on or off the Paxos platform. For example, a wire withdrawal or crypto deposit. |
| WIRE_WITHDRAWAL_UPLOAD | A manually created wire withdrawal.
|

ResourceTransferType Values and Definitions

The ResourceTransferType identifies the direction of each transfer and whether it was a movement of fiat into or out of the Paxos Platform (WIRE_, SEN_), a movement of crypto asset into or out of Paxos (CRYPTO_), or a movement of crypto or fiat between profiles within the Paxos platform (PROFILE_TRANSFER).

Resource	TransferType	Description
TRANSFER	CRYPTO_DEPOSIT	A crypto deposit into Paxos.
TRANSFER	CRYPTO_WITHDRAWAL	A crypto withdrawal out of Paxos.
TRANSFER	INTERNAL_TRANSFER_CREDIT	Transfer received from another Profile.
TRANSFER	INTERNAL_TRANSFER_DEBIT	Transfer sent to another Profile.
TRANSFER	PAXOS_TRANSFER_CREDIT	Transfer received from another Peer.
TRANSFER	PAXOS_TRANSFER_DEBIT	Transfer sent to another Peer.
TRANSFER	SEN_DEPOSIT	Deprecated. Does not appear in new reports. A deposit into Paxos platform on the Silvergate Exchange Network.
TRANSFER	SEN_WITHDRAWAL	Deprecated. Does not appear in new reports. A withdrawal out of Paxos on the Silvergate Exchange Network .
TRANSFER	WIRE_DEPOSIT	A wire deposit into Paxos.
TRANSFER	WIRE_WITHDRAWAL	A wire withdrawal out of Paxos.

TransactionType Values and Definitions

The values of the TransactionType vary depending on the Resource.
The TransactionType denotes the specific purpose of the transaction.

Resource	TransactionType	Description
CONVERSION	CONVERSION_CANCELLATION	A transaction to unreserve funds for a created stablecoin conversion.
CONVERSION	CONVERSION_CREATION	A transaction to reserve funds for a stablecoin conversion.
CONVERSION	CONVERSION_SETTLEMENT	Settlement of the stablecoin conversion transaction.
EXECUTION	COMMISSION	A transaction to collect commission from an executed trade.
EXECUTION	SETTLE_BASE	Settlement of the base (crypto) side of the trade to/from the counterparty.
EXECUTION	SETTLE_QUOTE	Settlement of the quote (cash) side of the trade to/from the counterparty For example, a SELL order has been executed.
EXECUTION	SETTLE_UNRESERVE	A transaction to unreserve funds for trading because of a BUY side price improvement on an executed order. For example, a limit order used a BUY price of $50,000 but executed at $49,000).
ORDER	RESERVE	A transaction to reserve funds for trading. For example, a limit order has been placed.
ORDER	UNRESERVE	A transaction to unreserve funds for trading. For example, a limit order has been canceled.
QUOTE_EXECUTION	COLLECT_FROM_EXECUTOR	A record of transaction indicating a credit of the account.

```
|
| QUOTE\_EXECUTION | FUND\_EXECUTOR           | A record of transaction indicating a debit
of the account.
|
| SWAP             | SWAP\_TX                 | A 1:1 conversion of a USD or a stablecoin
from one type (in the DEBIT Direction) to another (in the CREDIT Direction) in the same
account (no movement)                                        |
| TRANSFER         | DEPOSIT\_COMPLETION      | A transaction to complete a deposit,
resulting in funds being credited.
|
| TRANSFER         | DEPOSIT\_CREATION        | A transaction to deposit funds into the
Paxos platform.
|
| TRANSFER         | DEPOSIT\_FAILURE         | A transaction to reserve the funds of a
failed deposit into pending debit where they can move off the Paxos platform back to their
source.                                                      |
| TRANSFER         | FEE\_DEBIT               | A transaction to debit the fees upon
completion of the transfer.
|
| TRANSFER         | FEE\_ENCUMBERMENT        | A transaction to reserve the transfer fee.
|
| TRANSFER         | INTERNAL\_TRANSFER       | A book transfer of funds to another profile
under the same customer account.
|
| TRANSFER         | PAXOS\_TRANSFER          | A book transfer of funds to another Paxos
customer.
|
| TRANSFER         | WITHDRAWAL\_COMPLETION   | A transaction to complete a withdrawal,
resulting in the transfer of funds off the Paxos platform.
|
| TRANSFER         | WITHDRAWAL\_CREATION     | A transaction to initiate a withdrawal
typically reserving the debit amount. For example, a wire withdrawal or crypto withdrawal.
|
| TRANSFER         | WITHDRAWAL\_FAILURE      | A transaction to return funds previously
reserved for a failed withdrawal.
|


# Make First API Request
Source: https://docs.paxos.com/guides/developer/request

Use the access token to retrieve a list of Profiles.

Since every account has a `DEFAULT` [Profile](/api-reference/endpoints/profiles), sending a
request using [List Profiles](/api-reference/endpoints/profiles/list-profiles) will always
return a result, assuming the `funding:read_profile` scope was included when [adding scopes]
(/guides/developer/authenticate#scopes) to the client.
Include the [access token](/guides/developer/authenticate#token) from the authentication
request in the authorization header.

### Sandbox

```shell highlight={3} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles?order=ASC&order_by=CREATED_AT' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

Production

```shell highlight={3} theme={null}
curl --location 'https://api.paxos.com/v2/profiles?order=ASC&order_by=CREATED_AT' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```
```

A successful response includes all Profiles the client has access to.
Using the `?order=ASC&order_by=CREATED_AT` parameters ensures the `DEFAULT` Profile is first in the list.

```json highlight={3-7} theme={null}
{
    "items": [
        {
            "id": "0d3172c5-8840-4bae-bdd4-30688f0268fc",
            "nickname": "default",
            "type": "DEFAULT"
        },
        {
            "id": "7437da4d-c114-4a1f-8659-ceeaf868a1eb",
            "nickname": "Mint",
            "type": "NORMAL"
        },
        {
            "id": "4bdfed80-ed0d-461b-bfee-0ff5011a9db5",
            "nickname": "Redeem",
            "type": "NORMAL"
        },
    ]
}

```

If you get an error, run through the [credentials](/guides/developer/credentials) and [authentication](/guides/developer/authenticate) guides and ensure your setup is correct.
If things are still not working, contact [Support](https://support.paxos.com).

Request Signing
Source: https://docs.paxos.com/guides/developer/request-signing

Use JWS to add an additional layer of security to every request.

Request signing adds an additional layer of security to every request you send to Paxos, and can help protect your account should your Paxos API Client ID and Secret become compromised. Once request signing is enabled on your account, Paxos rejects all unsigned requests to authenticated endpoints.

> Request signing must be activated by Paxos. Contact [Support](https://support.paxos.com) to get started.

Signed requests use your own private key, similar to [mTLS](https://www.cloudflare.com/learning/access-management/what-is-mutual-tls/) or [SSH](https://www.ssh.com/academy/ssh/public-key-authentication) public authentication, and then attach the signature to the request as the `Paxos-Signature HTTP header`, using the JSON Web Signature (JWS) format.

Set Up Signed Request

To get started, you will need to have the **Client ID** and **Secret** available for constructing the payload.
Additionally, install the JOSE/JWS library in the language of your choice, for example [PyJWT](https://pypi.org/project/PyJWT/) which includes support for crypto.

> Never share your private keys with anyone, especially for Production deployments.
> Using an HSM, secrets manager, or key-management service may provide an additional layer of protection.

❶ Generate Key Pair

Generate the JWS signature with your private key using a combination of the base64url encoded header and payload, using either the EdDSA (ed25519) or the ES256 algorithm.

> To use the EdDSA (ed25519) algorithm when generating key pairs, install [OpenSSL 3](https://openssl-library.org/) using the package manager of your choice.
> Older versions of OpenSSL do not support the EdDSA (ed25519) algorithm.

To generate a new ES256 private key using the terminal:

1. Ensure OpenSSL 3 is installed:
`openssl version`
2. Create a new ES256 private key in the current working directory:
`openssl ecparam -name prime256v1 -genkey -noout -out my-private-ec.pem`
3. Generate the public key in the current working directory:
`openssl ec -in my-private-ec.pem -pubout > my-public-ec.pem`

The process for EdDSA (ed25519) keys is similar:

1. Ensure OpenSSL 3 is installed:
`openssl version`
2. `openssl genpkey -algorithm ed25519 -outform PEM -out my-private-key.pem`
3. `openssl pkey -in my-private-key.pem -pubout > my-public-key.pem`

> Never share your private keys with anyone, especially for Production deployments.
> Using an HSM, secrets manager, or key-management service may provide an additional layer of protection.

❷ Add Public Key to Your Paxos Account

Go to **Admin > API** in either \[Sandbox]\[admin-api-sandbox] or \[Production]\[admin-api-production] and find the **API Credentials** that require request signing.

Go to ** Admin > API** in either [Sandbox](https://dashboard.sandbox.paxos.com/admin/api) or [Production](https://dashboard.paxos.com/admin/api) and find the **API Credentials** that require request signing.

> Request signing must be activated by Paxos. Contact [Support](https://support.paxos.com) to get started.

Scroll down and use **Edit API Credentials** to make changes.
Switch **Request Signing** to open the edit dialogue and add your *Public Key*.

Once you **Save Changes**, contact [Support](https://support.paxos.com) to get started.

❸ Generate Signed Request

Use a JOSE/JWS library such as [PyJWT](https://pypi.org/project/PyJWT/) to generate the signature.

Construct Header

The header must include the following:

Header Item	Description
kid	The Key ID of the configured Public Key. Retrieve from Admin > API > API Cretentials.
alg	The algorithm used to generate the Key. The value must be: EdDSA or ES256. Retrieve from Admin > API > API Cretentials.
paxos.com/timestamp	The current timestamp in UNIX time format. Signatures remain valid for 30 minutes after the specified timestamp.
paxos.com/request-method	The POST and PUT methods also require the JWS payload in the body bytes.
paxos.com/request-path	The endpoint path, including query parameters.

|

Putting it together, your header should look similar to the following:

```json theme={null}
{
"kid" : "5498f424-78aa-414b-a515-13929e6951db",
"alg" : "ES256",
"paxos.com/timestamp" : "1645503272",
"paxos.com/request-method" : "POST",
"paxos.com/request-path" : "/v2/transfer/deposit-addresses"
}
```

When using a `POST` or `PUT` method, include the JWS payload in the body bytes:

```json theme={null}
{"profile_id":"42bb1a2e-a68e-44d7-b5f1-59ccc5c13e91","crypto_network":"ETHEREUM"}
```

Create Signature

Use a library such as [PyJWT](https://pypi.org/project/PyJWT/) to generate the request signature.
First, install the library and start a new session.
For example:

```shell theme={null}
pip3 install "pyjwt[crypto]" && python3
```

Then generate the JWT signature:

```py theme={null}
>>> import jwt
>>> payload = b'{"profile_id":"42bb1a2e-a68e-44d7-b5f1-
59ccc5c13e91","crypto_network":"ETHEREUM"}'
>>> with open('./my-private-ec.pem', 'rb') as f: key = f.read()
...
>>> alg = "ES256" if key.find('BEGIN EC PRIVATE'.encode('ascii')) > 0 else "EdDSA"
>>> headers = {"kid": "5498f424-78aa-414b-a515-13929e6951db", "alg": alg,
               "paxos.com/timestamp": "1645503272",
               "paxos.com/request-method" : "POST",
               "paxos.com/request-path": "/v2/transfer/deposit-addresses"}
>>> signature = jwt.api_jws.encode(payload=payload, key=key, headers=headers,algorithm=alg)
>>> print(signature)
eyJ0eXAiOiJKV1QiLCJhbGciOiJFUzI1NiIsImtpZCI6IjU0OThmNDI0LTc4YWEtNDE0Yi1hNTE1LTEzO
TI5ZTY5NTFkYiIsInBheG9zLmNvbS90aW1lc3RhbXAiOiIxNjQ1NTAzMjcyIiwicGF4b3MuY29tL3JlcX
Vlc3QtbWV0aG9kIjoiUE9TVCIsInBheG9zLmNvbS9yZXF1ZXN0LXBhdGgiOiIvdjIvdHJhbnNmZXIvZGV
wb3NpdC1hZGRyZXNzZXMifQ.eyJwcm9maWxlX2lkIjoiNDJiYjFhMmUtYTY4ZS00NGQ3LWI1ZjEtNTljY
2M1YzEzZTkxIiwiY3J5cHRvX25ldHdvcmsiOiJFVEhFUkVVTSJ9.7x8b_4j1dFMd1XWcmpGaf5OiyU0lo
2fbGlbe8epuiAJFpFziwxhhKHbc7-DaqKMV9MTTARX8VM3d2YSugPEAow
>>> exit()
```

❹ Send Signed Request

Use the generated signature to send a signed request to Paxos.
First, authenticate with the APIs.
For example:

```shell theme={null}
curl https://oauth.sandbox.paxos.com/oauth2/token \
-F grant_type=client_credentials \
-F client_id={client_id} \
```

```
-F client_secret={secret} \
-F scope="transfer:write_deposit_address"
```

Then send the signed API request:

```shell theme={null}
curl -X POST https://api.sandbox.paxos.com/v2/transfer/deposit-addresses
-H "Authorization: Bearer {access_token}"
-H "Paxos-Signature: eyJ0eXAiOiJKV1QiLCJhbGciOiJFUzI1NiIsImtpZCI6IjU0OThmNDI0LTc4Y
WEtNDE0Yi1hNTE1LTEzOTI5ZTY5NTFkYiIsInBheG9zLmNvbS90aW1lc3RhbXAiOiIxNjQ1NTAzMjcyIiw
icGF4b3MuY29tL3JlcXVlc3QtbWV0aG9kIjoiUE9TVCIsInBheG9zLmNvbS9yZXF1ZXN0LXBhdGgiOiIvd
jIvdHJhbnNmZXIvZGVwb3NpdC1hZGRyZXNzZXMifQ.eyJwcm9maWxlX2lkIjoiNDJiYjFhMmUtYTY4ZS00
NGQ3LWI1ZjEtNTljY2M1YzEzZTkxIiwiY3J5cHRvX25ldHdvcmsiOiJFVEhFUkVVTSJ9.7x8b_4j1dFMd1
XWcmpGaf5OiyU0lo2fbGlbe8epuiAJFpFziwxhhKHbc7-DaqKMV9MTTARX8VM3d2YSugPEAow"
-d '{"profile_id":"42bb1a2e-a68e-44d7-b5f1-59ccc5c13e91","crypto_network":"ETHEREUM"}'
```

Manage Signed Requests

For Production environments, you may want to create multiple API Credentials with different permissions and authentication.
For example, you may want to sign all order and identity requests but not requests for historical data.
To do this, you can create multiple API Credentials and then enable request signing for only those users or applications dealing with sensitive information.

* **Use Multiple Request Signing Keys**. It is also possible for you to simultaneously use multiple request signing keys with a single API Credential. Once you add an additional request signing key, it is immediately available for use, along with any existing key, for the API Credential. Used in this way, you can assign different request signing keys to different users or applications that use the same API Credential. This can come in handy if you need to revoke access for an application or user with a specific key: The API Credentials remain active, along with the other keys.
* **Rotate API Credentials**. If your API Credentials needs to be changed, the Rotate Credentials option regenerates a new Secret, leaving the Client ID unchanged. When you rotate credentials, you will need to update any implementation that uses the Client ID. Once that is done, your request signing keys work with the new Secret.

Sandbox
Source: https://docs.paxos.com/guides/developer/sandbox

Use the Sandbox environment to mock flows, execute transfers and test integrations.

The Developer Sandbox replicates core [v2 API](/api-reference) functionality with an automated system that uses test fund to simulate normal activities, including a few Sandbox-only endpoints.

> To start using the Sandbox environment, [create a Developer account](https://dashboard.sandbox.paxos.com/).

Sandbox Testnets and Devnets

When you use [Create Sandbox Deposit](/api-reference/endpoints/sandbox-deposits/create-sandbox-deposit) to fund a Profile, the platform creates the asset on the testing network. The asset can then be [transferred](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal) to any off-platform address that supports the test network.
Similarly, when using [create a deposit address](/api-reference/endpoints/deposit-addresses/create-deposit-address) in Sandbox, the generated address can be used to transfer test assets to the Paxos platform.

Crypto Network	Supported Testnet/Devnet
Arbitrum One	Sepolia

Bitcoin	Testnet4
Bitcoin Cash	Testnet
Ethereum	Sepolia
Litecoin	Testnet
Polygon POS	Sepolia
Solana	Devnet
Stellar	Testnet

Sandbox Withdrawal Limits

The Sandbox environment has withdrawal limits per transaction to preserve the limited supply of test coins available for customer testing. While you can execute multiple transactions, each individual withdrawal must stay within these limits:

Asset	Maximum Withdrawal per Transaction
BTC	0.002
ETH	0.05
BCH	0.05
LTC	0.05
SOL	0.5
AAVE	10
MATIC	10
LINK	10
UNI	10
PAXG	1,000,000
USDP	1,000,000
PYUSD	1,000,000
BUSD	1,000,000
USDC	1,000,000
USDG	1,000,000

Sandbox Identity Testing

When testing the [Identity APIs](/api-reference/endpoints/identity) in Sandbox, you may be blocked by a verification process.
If this is the case, use [Sandbox Set Identity Status](/api-reference/endpoints/sandbox-identity/sandbox-set-identity-status) to change `id_verification_status` and `sanctions_verification_status` to "APPROVED"`and enable an individual identity to transact during Sandbox testing.
To enable the Institution to transact during Sandbox testing, set `sanctions\_verification\_status` to \"APPROVED"`.

Sandbox Fiat Transfer Testing

To test [Fiat Transfers API](/api-reference/endpoints/fiat-transfers) in Sandbox, the [Initiate Sandbox Fiat Deposit](/api-reference/endpoints/sandbox-fiat-transfers) endpoint starts test fiat deposit that will be processed based on the `memo_id` from a previous [Fiat Deposit Instructions](/api-reference/endpoints/fiat-transfers/list-fiat-deposit-instructions) response.
Learn more in the [Fiat Transfer Guide](/guides/developer/fiat-transfers/quickstart#2-send-fiat-to-paxos).

> When [creating API credentials](/guides/developer/credentials) via the Dashboard, the `transfer:write_sandbox_fiat_deposit` scope may not appear in the UI.
> Including the scope when [authenticating](/guides/developer/authenticate) may result in an `invalid_scope` error.
> Contact [Support](https://support.paxos.com) if you run into any issues using this scope.

Enhanced Due Diligence
Source: https://docs.paxos.com/guides/identity/edd

Manage the enhanced due diligence of an Identity on the Paxos Platform.

To ensure that Paxos meets regulatory requirements, when an identity is deemed high risk according to Paxos risk rating methodology, Paxos initiates a process called Enhanced Due Diligence (EDD).
This can occur during onboarding, or during the lifecycle of an active identity (for example, if identity information changes that impacts risk rating; if suspicious transaction patterns occur on the account).

When an identity enters the EDD process, Paxos requires the collection of documentary evidence supporting the initial KYC information provided.

Paxos streamlines the collection of EDD information using a webhook-based or polling-based approach, which leverages [Paxos Webhooks](/guides/webhooks), [Events API](/api-reference/events) and [Document Upload API](/api-reference/endpoints/identity-documents/document-upload).

Webhook-based Approach

<img alt="Events" />

❶ Consume Documents Required Events

Setup a [Webhook Consumer](/guides/webhooks/quickstart) to receive `identity.documents_required` [events](/api-reference/events) for your end users.

❷ Fetch Required Documents

Call [Get Event](/api-reference/endpoints/events/get-event) to fetch the event's `identity_documents_required` object, which will allow you to understand which documents are required.

❸ Upload the Required Documents

For the event's associated `identity_id`, call [Document Upload](/api-reference/endpoints/identity-documents/document-upload) to upload the required documents, either synchronously if you already have the documents, or asynchronously if you need to reach back out to your customer for them to provide.

❹ Wait for Approval or Denial

This will be followed by an `identity.approved` or `identity.denied` event based on the onboarding decision for that end user (this might take up to 1 full business day to complete).

Polling-based Approach

❶ Poll for Documents Required Events

Poll [List Events](/api-reference/endpoints/events/list-events), offsetting the `created_at.gt` filter for each subsequent poll, fetching all `identity.documents_required` events.

<Info>
  Paxos recommends you keep track of the [Event](/api-reference/events) ids you've processed in order to idempotently process the event.
</Info>

❷ Upload the Required Documents

For the event's associated `identity_id`, call [Document Upload](/api-reference/endpoints/identity-documents/document-upload) to upload the required documents, either synchronously if you already have the documents, or asynchronously if you need to reach back out to your customer for them to provide.

Onboard Users

Source: https://docs.paxos.com/guides/identity/index

Onboard users directly to the Paxos Platform to accelerate speed to market and outsource your compliance needs.

Quickstart

<CardGroup>
  <Card title="Person" href="/guides/identity/person-crypto-brokerage" icon="user">
    Onboard a Person for Crypto Brokerage
  </Card>

  <Card title="Institution" href="/guides/identity/institution-crypto-brokerage" icon="building">
    Onboard an Institution for Crypto Brokerage
  </Card>
</CardGroup>

Manage Lifecycle

<CardGroup>
  <Card title="Automate Enhanced Due Diligence" href="/guides/identity/kyc-refresh" icon="magnifying-glass">
    Automate document collection to unblock onboarding high risk identities
  </Card>

  <Card title="Automate Periodic KYC Refresh" href="/guides/identity/kyc-refresh" icon="arrows-rotate">
    Automate periodic kyc refresh to prevent users from losing access to trade
  </Card>
</CardGroup>

Institution Types and Members
Source: https://docs.paxos.com/guides/identity/institution-types

Learn about institution types, member roles, and requirements

Institution Types

Institution Type

Institution type (`institution_type`) is the primary legal structure of the institution, which can be one of the following:

Institution Type	Description
`CORPORATION`	A legal entity that is separate and distinct from its owners
`LLC`	Limited Liability Company, a business structure that combines elements of partnerships and corporations
`TRUST`	A legal entity created to hold and manage assets for beneficiaries
`PARTNERSHIP`	A business relationship between two or more individuals who share management and profits

Institution Subtypes

Institution subtype (`institution_sub_type`) is the primary area of business activity of the institution,
work with your Paxos Partner to understand the mapping from your institution subtypes to ours.

Paxos prohibits certain types of business activity ("Prohibited Businesses") in accordance with its Compliance policies.
The following non-exhaustive list is representative of the type of activity that Paxos prohibits on its platform. By creating a Paxos Identity, Paxos customers agree not to use Paxos services in connection with any of the following Prohibited Businesses.

* `ADULT_ENTERTAINMENT`
* `DRUGS`
* `RANSOMWARE`
* `SHELL_BANK`
* `WEAPONS`

Creating Financially Regulated Institutions

Please refer to the following table for creating institutions which are financially regulated.

Regulation Status	Description	
`US_REGULATED`	Institution financially regulated in the US	
`INTL_REGULATED`	Institution financially regulated by an international entity	
`NON_REGULATED`	Non-financially regulated institution	

Note that each category of `regulation_status` then has additional validations tied to `trading_type` and other required fields.

Regulation Status	Trading Type	Fields Required	Notes
`US_REGULATED`	`PRIVATE`	`regulator_name`, `regulator_jurisdiction`, `regulator_register_number`	Not publicly traded
`US_REGULATED`	`PUBLIC`	`listed_exchange`, `ticker_symbol`, `regulator_name`, `regulator_jurisdiction`, `regulator_register_number`	Publicly traded
`US_REGULATED`	`PUBLICLY_TRADED_SUBSIDIARY`	`listed_exchange`, `ticker_symbol`, `regulator_name`, `regulator_jurisdiction`, `regulator_register_number`, `parent_institution_name`	Subsidiary of a publicly traded company
`INTL_REGULATED`	`PRIVATE`	`regulator_name`, `regulator_jurisdiction`, `regulator_register_number`	Not publicly traded
`INTL_REGULATED`	`PUBLIC`	`listed_exchange`, `ticker_symbol`, `regulator_name`, `regulator_jurisdiction`, `regulator_register_number`	Publicly traded
`INTL_REGULATED`	`PUBLICLY_TRADED_SUBSIDIARY`	`listed_exchange`, `ticker_symbol`, `regulator_name`, `regulator_jurisdiction`, `regulator_register_number`, `parent_institution_name`	Subsidiary of a publicly traded company
`NON_REGULATED`	`PRIVATE`	None	Not publicly traded
`NON_REGULATED`	`PUBLIC`	`listed_exchange`, `ticker_symbol`	Publicly traded

Note: `NON_REGULATED` only supports `PRIVATE` and `PUBLIC` trading types. `PUBLICLY_TRADED_SUBSIDIARY` is not supported for `NON_REGULATED` institutions.

Institution Members

Member Roles

Institution members can have one or more roles that define their relationship with the institution. Each role has specific requirements and applicability depending on the institution type:

Role	Description
`BENEFICIAL_OWNER`	Person who owns 25% or more of the institution.
`ACCOUNT_OPENER`	Person who opened the account on behalf of the institution.
`AUTHORIZED_USER`	Person authorized to transact on behalf of the institution.
`MANAGEMENT_CONTROL_PERSON`	Person with significant management control over the institution (e.g., CEO, CFO, COO).
`TRUSTEE`	Person who manages assets in a trust for beneficiaries and is legally responsible for the trust.
`GRANTOR`	Person who creates a trust by donating assets.
`BENEFICIARY`	Person who receives benefits from a trust.

Role Compatibility by Institution Type

The following grid shows which roles are applicable for each institution type:

Role	Trust	Corporation	LLC	Partnership
`BENEFICIAL_OWNER`	--	✅	✅	✅
`AUTHORIZED_USER`	--	✅	✅	✅
`MANAGEMENT_CONTROL_PERSON`	--	✅	✅	✅
`TRUSTEE`	✅	--	--	--
`GRANTOR`	✅	--	--	--
`BENEFICIARY`	✅	--	--	--

* **Trusts**: A trust institution must have at least one member with one of the following roles: GRANTOR, TRUSTEE, or BENEFICIARY.
* **Corporations, LLCs, Partnerships**: These institutions typically require at least one BENEFICIAL_OWNER and one MANAGEMENT_CONTROL_PERSON.
* For all institution types, members must be Identity objects already created in the system.

Periodic KYC Refresh
Source: https://docs.paxos.com/guides/identity/kyc-refresh

Manage the periodic KYC refresh of an Identity on the Paxos Platform in an automated, compliant way.

To ensure that Paxos meets regulatory requirements, KYC information of end user identities that are directly onboarded
to Paxos must be periodically refreshed (every 1-3 years).
All customers that integrate with Paxos [Identity APIs](/api-reference/endpoints/identity) are subject to this process, and must integrate with the automated workflow outlined below to support it.

Paxos streamlines KYC Refresh using a webhook-based or polling-based approach, which leverages [Paxos Webhooks](/guides/webhooks/quickstart), [Events API](/api-reference/events) and [Identity API](/api-reference/endpoints/identity).

Webhook-based Approach

<img alt="Sequence Diagram for KYC Refresh" />

❶ Consume KYC Refresh Events

Setup a [Webhook Consumer](/guides/webhooks/quickstart#consumer) to receive the following KYC refresh events for your end users:

* [`identity.kyc_refresh.started`](/api-reference/events)
* [`identity.kyc_refresh.completed`](/api-reference/events)

<Tip>
  Use [Get Event](/api-reference/endpoints/events/get-event) to get additional information about the KYC refresh event (`last_kyc_refresh_date`, `next_kyc_refresh_date`, etc.).
</Tip>

❷ Prompt End User about Periodic Refresh

When an [`identity.kyc_refresh.started`](/api-reference/events) is received for your end user, prompt the user presenting their current KYC information indicating they should refresh their information if anything has changed, or continue without changes if everything is still accurate.

❸ Inform Paxos about the Refresh

When an end user indicates everything is still accurate, call [update-identity](/api-reference/endpoints/identity/update-identity) with the `identity_id` specified in the request, setting the `last_kyc_refresh_date` to the timestamp the user confirmed their information is still accurate.

If an end user refreshed their information, call [update-identity](/api-reference/endpoints/identity/update-identity) as specified above, but also include any changes the end user has made to their information.

<Info>
  Calling [update-identity](/api-reference/endpoints/identity/update-identity) with only `last_kyc_refresh_date` and no other changes is considered by Paxos to be confirmation
  no information has changed, therefore a completed KYC refresh.
  The next KYC refresh date will be updated accordingly (1-3 years from the provided `last_kyc_refresh_date`).
</Info>

❹ Wait for Completion

Once KYC refresh is complete, a [`identity.kyc_refresh.completed`](/api-reference/events) will be received for the end user in question.

Polling-based Approach

❶ Poll for KYC Refresh Started Events

Poll [List Events](/api-reference/endpoints/events/list-events), offsetting the `created_at.gt` for each subsequent poll, fetching [`identity.kyc_refresh.started`](/api-reference/events) events.

<Info>
  We recommend you keep track of the [Event](/api-reference/events) ids you've processed in order to idempotently process the event.
</Info>

❷ Prompt End User about Periodic Refresh

As described [above](#-prompt-end-user-about-periodic-refresh) in the webhook-based approach.

❸ Inform Paxos about the Refresh

As described [above](#-inform-paxos-about-the-refresh) in the webhook-based approach.

❹ Poll for Completed Refreshes

Poll [List Events](/api-reference/endpoints/events/list-events), offsetting the `created_at.gt` for each subsequent poll, fetching [`identity.kyc_refresh.completed`](/api-reference/events) events.

Advanced

Handling Expired Refreshes

If an [`identity.kyc_refresh.expired`](/api-reference/events) is received, it means Paxos did not receive an [update-identity](/api-reference/endpoints/identity/update-identity) request in the designated window to complete the KYC refresh process *(typically 30 days)*. If this occurs, several outcomes could be experienced:

* Paxos will restart the KYC refresh process, and a new [`identity.kyc_refresh.started`](/api-reference/events) event will be posted
* The Identity could be disabled (meaning the end user will only be able to Liquidate assets and withdraw fiat off platform)

Refreshes in Compliance Review

In some cases, the Paxos compliance team might need to review the changes received from the end user as part of the
KYC refresh process.
In this case, the [`identity.kyc_refresh.completed`](/api-reference/events) event could experience a meaningful delay in being received.

Backdating the Last KYC Refresh Date

If a historical record is known for the last KYC refresh dates of your end users **or** you've experienced an issue processing KYC refresh for an end-user then you can directly call [update-identity](/api-reference/endpoints/identity/update-identity) setting the `last_kyc_refresh_date` to the known date in the past, and Paxos will accept this as the date KYC refresh was performed for the end user.

<Warning>
  Setting this date beyond the 1-3 year refresh period for an end user will cause an immediate [`identity.kyc_refresh.started`](/api-reference/events) to be triggered for the end user.
</Warning>

Required Details
Source: https://docs.paxos.com/guides/identity/required-details

Learn more about what details are required when creating an Identity

Key

Value	Description
✅	Required field
🟡	Best effort optional field * (providing details here ensures less friction during onboarding)*
--	Not applicable

Required Person Details

The required details for persons being onboarded as [Identities](/api-reference/endpoints/identity) depend on the licensing arrangement and solution. See the table below:

Field	Paxos Trust Company Licensing (Crypto Brokerage)
`first_name`	✅
`last_name`	✅
`date_of_birth`	✅
`address`	✅
`nationality`	✅
`cip_id`	✅
`cip_id_type`	✅
`cip_id_country`	✅
`cdd.estimated_yearly_income`	✅
`cdd.expected_transfer_value`	✅
`cdd.source_of_wealth`	✅
`cdd.employment_status`	✅
`cdd.employment_industry_sector`	✅
`middle_name`	🟡
`phone_number`	🟡
`email`	🟡
`profession`	--
`country_of_birth`	--
`cdd.aliases`	--
`cdd.estimated_net_worth`	--
`cdd.customer_regions`	--
`cdd.source_of_funds`	--
`cdd.purpose_of_account`	--

Required Institution Details

Institution identities are used to represent all non-person entities. Details for institution identity type are recorded in `institution_details`. An institution identity also has `institution_members` associated with it. These define persons that have some relationship to the institution.

Required Fields for Institution Types

```
The required fields for institutions being onboarded as [Identities](/api-
reference/endpoints/identity) depend on the institution type. See the table below:

| Field                                |                  <span>Trust</span>
|                                   <span>Corporation, LLC, Partnership</span>
|                                <span>Registered Investment Advisor (RIA)</span>
|
| ------------------------------------ | :-------------------------------------------------:
| :-------------------------------------------------------------------------------------
-------------------: | :-------------------------------------------------------------------
----------------------------------------: |
| `name`                               |                          ✅
|                                                        ✅
|                                                        ✅
|
| `business_address`                   |                          ✅
|                                                        ✅
|                                                        ✅
|
| `phone_number`                       |                          🟡
|                                                        🟡
|                                                        🟡
|
| `email`                              |                          🟡
|                                                        🟡
|                                                        🟡
|
| `institution_type`                   |                          ✅
|                                                        ✅
|                                                        ✅
|
| `institution_sub_type`               |                          ✅
|                                                        ✅
|                                                        ✅
|
| `cip_id`                             |                          ✅
|                                                        ✅
|                                                        ✅
|
| `cip_id_type`                        |                          ✅
|                                                        ✅
|                                                        ✅
|
| `cip_id_country`                     |                          ✅
|                                                        ✅
|                                                        ✅
|
| `govt_registration_date`             |                          ✅
|                                                        ✅
|                                                        ✅
|
| `incorporation_address`              |                          🟡
|                                                        ✅
|                                                        ✅
|
| `regulation_status`                  |                          🟡
|                                                        ✅
|                                                        ✅
|
| `trading_type`                       |                          🟡
|                                                        ✅
|                                                        ✅
|
| `listed_exchange`                    |                          🟡
```

Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)
`ticker_symbol`	🟡	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)
`parent_institution_name`	🟡	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)
`regulator_name`	🟡	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)
`regulator_jurisdiction`	🟡	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)
`regulator_register_number`	🟡	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)	Depends on [regulation status](/guides/identity/institution-types#creating-financially-regulated-institutions)
`doing_business_as`	🟡	🟡	🟡
`business_description`	🟡	✅	🟡
`tax_details`	Auto-populated if cip_id_type is SSN, ITIN or EIN	Auto-populated if cip_id_type is SSN, ITIN or EIN	Auto-populated if cip_id_type is SSN, ITIN or EIN
`tax_details_not_required`	Can be set for non-US institutions	Can be set for non-US institutions	Can be set for non-US institutions
`metadata`	🟡	🟡	🟡
`ref_id`	🟡	🟡	🟡
`cdd.aliases`	🟡	🟡	🟡
`cdd.source_of_wealth`	🟡	✅	🟡
`cdd.source_of_funds`	🟡	✅	🟡
`cdd.industry_sector`	🟡	✅	🟡
`cdd.has_underlying_trust_structure`	🟡	✅

```
|                                                    🟡
|
| `cdd.has_nominee_shareholders`       |                        🟡
|                                                    ✅
|                                                    🟡
|
| `cdd.is_publicly_traded`             |                        🟡
|                                                    🟡
|                                                    🟡
|
| `cdd.merchant_funding_source`        |            Only for payments integrations
|                                        Only for payments integrations
|                                        Only for payments integrations
|
| `cdd.customer_regions`               |            Only for payments integrations
|                                        Only for payments integrations
|                                        Only for payments integrations
|
```

Notes:

* For Trusts: `institution_type` must be set to `TRUST`. `institution_sub_type` must be set to `INVESTMENT`. `incorporation_address` is required for Trusts where their `cip_id_type` is not `SSN` or `ITIN`.
* For RIAs: Usage of this sub-type requires prior authorization and approval from Paxos. `institution_sub_type` must be set to `REGISTERED_INVESTMENT_ADVISOR`.
* For `regulation_status`: Additional validations are tied to `trading_type` and other required fields. See [Institution Types and Members](/guides/identity/institution-types) for details.

For more information about institution types, member roles and requirements, please refer to [Institution Types and Members](/guides/identity/institution-types).

Statuses
Source: https://docs.paxos.com/guides/identity/statuses

Learn more about Identity statuses and sub-statuses

Summary Status

An [Identity](/api-reference/endpoints/identity/create-identity) has five (5) statuses:

* `PENDING`: Initial state. The [Identity](/api-reference/endpoints/identity/create-identity) is waiting for an [Onboarding Decision](/guides/identity/statuses#onboarding-decision) and is under review.
* `APPROVED`: The [Identity](/api-reference/endpoints/identity/create-identity) passed internal review. It can be used with integrations, for example, creating orders.
* `DENIED`: The [Identity](/api-reference/endpoints/identity/create-identity) failed internal review. It cannot be used with integrations.
* `DISABLED`: The [Identity](/api-reference/endpoints/identity/create-identity) was `APPROVED` but has been off-boarded. It can only perform sell operations.
* `ERROR`: The [Identity](/api-reference/endpoints/identity/create-identity) has been frozen for compliance reasons. It cannot be used with integrations.

This status drives what actions the identity can perform across the platform according to the grid below:

Status	Hold Assets	Create Buy Orders	Create Sell Orders	Execute Open Orders	Create Crypto Deposit Address	Create Crypto Withdrawal	Receive Crypto Deposits
`PENDING`	❌	❌	❌	❌	❌	❌	❌
`DENIED`	❌	❌	❌	❌	❌	❌	❌

```
| ❌                          | ❌                    | ❌                    |
| `APPROVED` | ✅          | ✅                    | ✅                    | ✅
| ✅                          | ✅                    | ✅                    |
| `DISABLED` | ✅          | ❌                    | ✅                    | ✅
| ❌                          | ❌                    | ❌\*                  |
| `ERROR`    | ✅          | ❌                    | ❌                    | ✅
| ❌                          | ❌                    | ❌\*                  |
```

**Crypto deposits received to identities in disabled or error status will be held for review.*

Sub Statuses

The following sub-statuses are returned in identity responses and can be used to help explain why an [Identity](/api-reference/endpoints/identity/create-identity) is in a given summary status.

Sanctions Verification Status (Persons & Institutions)

* **Field**: `sanctions_verification_status`
  * **`PENDING`**: Sanctions check in progress.
  * **`DENIED`**: Sanctions hit found, cannot proceed.
  * **`APPROVED`**: No sanctions hit found, cleared to proceed.
  * **`ERROR`**: Possible sanctions hit, held for manual review.

Additional Screening Status (Persons & Institutions)

* **Field**: `additional_screening_status`
  * **`PENDING`**: Additional screening checks are in progress.
  * **`DENIED`**: Failed additional screening checks.
  * **`APPROVED`**: Passed all additional screening checks.
  * **`ERROR`**: Possible screening hit, held for manual review.

<Tip>
  Additional screening includes checking for negative news or politically exposed persons, but explicitly excludes any sanctions checks (covered by the above `sanctions_verification_status`).
</Tip>

ID Verification Status (Persons Only)

* **Field**: `id_verification_status`
  * **`PENDING`**: Verification is in progress. Checking the identity of the person.
  * **`DENIED`**: Verification failed. Unable to verify the identity of the person.
  * **`APPROVED`**: Verification successful. The identity of the person is confirmed.

<Tip>
  When using passthrough IDV, the `id_verification_status` will reflect the `passthrough_verification_status` that was set. Note
  that `passthrough_verification_status` can only ever be set to a terminal IDV status of `APPROVED` or `DENIED`.
</Tip>

Onboarding Decision

The onboarding decision is made based on the identities risk rating and the set of verifications (as exposed in sub-statuses above).
Once there is sufficient information to make a decision, the [Identity](/api-reference/endpoints/identity/create-identity) will be `APPROVED` and able to trade or `DENIED` and rejected services.

In the happy path where an [Identity](/api-reference/endpoints/identity/create-identity) is `LOW`

Payments FAQ
Source: https://docs.paxos.com/guides/payments/faq

Get answers to common questions about payments.

<AccordionGroup>
  <Accordion title="How do I open a Paxos account?">
    The easiest way to get started with the Paxos Platform is to [contact the payments team](https://support.paxos.com/hc/en-us).
  </Accordion>

  <Accordion title="How are Seller onboarding requirements determined?">
    Seller onboarding requirements are determined based on the type of business, transaction volume, and compliance needs. The requirements include business verification, financial information, and regulatory compliance documentation.

    > Contact [Support](https://support.paxos.com/hc/en-us) to help determine the best onboarding approach.
  </Accordion>

  <Accordion title="What assets and blockchains can I use with payments?">
    By default, all payment workflows support USD and Paxos-issued stablecoins on Ethereum and Solana, including PYUSD and USDP.

    USDC on Ethereum, Solana or Polygon can also be used. [Contact us](https://support.paxos.com/hc/en-us) for details.
  </Accordion>
</AccordionGroup>

Overview
Source: https://docs.paxos.com/guides/payments/index

Accept stablecoin pay-ins with real-time settlement. Issue on-chain refunds.

Get Started

<CardGroup>
  <Card title="Quickstart" href="/guides/payments/quickstart" icon="rocket">
    Accept stablecoin pay-ins with real-time settlement. Issue on-chain refunds.
  </Card>

  <Card title="Payments Statuses" href="/guides/payments/status" icon="list-check">
    Learn more about payment statuses.
  </Card>

  <Card title="Payments FAQ" href="/guides/payments/faq" icon="circle-question">
    Get answers to common questions about payments.
  </Card>
</CardGroup>

Use the Paxos APIs to effortlessly integrate stablecoin payment acceptance into your platform.
Features include:

* Accept PYUSD, USDC and USDP payments via on-chain transfers.
* Automatically convert the stablecoin to fiat, or opt to hold balances in stablecoin.
* Reconcile transactions on the Paxos Platform.
* Settle USD directly to your bank account.
* Issue refunds to the original Buyer via stablecoin on-chain transfers.

<Tip>
  In the documentation, a payment is considered to be the total amount processed, including both the incoming payment (pay-in) and returned payment (refund).
</Tip>

Pay-ins Workflow

<img alt="Payments" />

The pay-ins workflow involves two key personas: a Buyer purchasing goods or services using stablecoins and a Seller.
The Seller represents either a merchant that provides goods or services, or a payment processor acting as the intermediary to facilitate the transaction.
Most pay-in integrations follow a similar workflow for the Seller:

1. [Add a crypto deposit address](/guides/payments/quickstart#pay-in-add-deposit-address) for a designated Profile, using one of the [supported blockchains](/guides/payments/faq#supported-assets).
2. To [use stablecoins for pay-ins](/guides/payments/quickstart#receive-payment), share the crypto deposit address with Buyers as a checkout option.

<Tip>
  Using a wallet connector or displaying a QR code in the Buyer interface helps to ensure that Buyers send the correct amount and avoid errors.
</Tip>

1. Configure a [pay-in monitoring and reconciliation](/guides/payments/quickstart#pay-in-monitor-reconcile) request to confirm Pay-in transactions on the Paxos Platform.
2. [Withdraw USD](/guides/payments/quickstart#pay-in-withdraw-fiat) to a bank account.

Refunds Workflow

Issuing a refund is similar to pay-ins, except the funding flow is reversed: USD is first moved onto the Paxos Platform and then the stablecoin refund is sent to the Buyer's designated wallet.
Most refund integrations follow a similar workflow for the Seller:

1. [Send USD](/guides/payments/quickstart#refund-fund-account) to a designated refund account.
2. [Initiate a crypto withdrawal](/guides/payments/quickstart#refund-initiate) to the Buyer's designated wallet address, using one of the [supported blockchains](/guides/payments/faq#supported-assets).
3. Configure a [refund monitoring and reconciliation](/guides/payments/quickstart#refund-monitor-reconcile) request to confirm Pay-in transactions on the Paxos Platform.

Stablecoin Pay-ins Quickstart
Source: https://docs.paxos.com/guides/payments/quickstart

Accept stablecoin pay-ins with real-time settlement. Issue on-chain refunds.

This guides walks you through the steps to set up a basic payments workflow using the Paxos Platform, including [configuring a stablecoin pay-in workflow](/guides/payments/quickstart#payment-workflow) and [setting up a refund workflow](/guides/payments/quickstart#refunds).
Once completed, similar, more robust, workflows can be implemented in production.
If you already have sandbox access, this guide should take less than one hour to complete.

Before You Begin

* Paxos may need to enable some API functionality described in the payments guides. Contact [Support](https://support.paxos.com) with any access issues.
* If you need a developer sandbox account, [contact us](https://support.paxos.com/hc/en-us) before continuing.
* The API endpoints require authentication with a **Client ID** and **Secret**.
* Each **Client ID** has a specific set of allowed scopes to access API endpoints.

<Accordion title="Example: Sandbox Credentials">
  [Log in](https://dashboard.sandbox.paxos.com) to your sandbox account and go to

[**Settings** > **API Management**](https://dashboard.sandbox.paxos.com/admin/api).
  Either select an existing **Client ID** or create a new one.

  <Tip>
    Best Practice

    Always store the **Client ID** and **Client Secret** in a safe place.
    The secret must be reset if forgotten.
  </Tip>

  To complete the steps in this guide, ensure the following scopes are enabled for the client (scopes may be updated at any time):

  ```
  funding:read_profile \
  funding:write_profile \
  transfer:read_transfer \
  transfer:write_crypto_withdrawal \
  transfer:write_deposit_address
  ```

  Include the client (`client_id`) and secret (`client_secret`) in the authentication request to https://oauth.sandbox.paxos.com/oauth2/token:

  ```shell theme={null}
  curl --location "https://oauth.sandbox.paxos.com/oauth2/token" \
  --form grant_type=client_credentials \
  --form client_id={client_id} \
  --form client_secret={client_secret} \
  --form scope="funding:read_profile funding:write_profile transfer:read_transfer transfer:write_crypto_withdrawal transfer:write_deposit_address"
  ```

  Confirm the response includes the requisite scopes and save the `access_token` to use in the request authorization header (`-H "Authorization: Bearer access_token"`).

  ```json theme={null}
  {
   "access_token": "access_token",
   "expires_in": 3599,
   "scope": "funding:read_profile funding:write_profile transfer:read_transfer transfer:write_crypto_withdrawal transfer:write_deposit_address",
   "token_type": "bearer"
  }
  ```
</Accordion>

* To follow along with this guide, [create a new Profile](/api-reference/endpoints/profiles/create-profile) to represent the Seller.
  However, any existing Profile can be used when setting up simple [pay-in](/guides/payments/quickstart#payment-workflow) and [refund](/guides/payments/quickstart#refunds) workflows.
  Learn more about [user onboarding requirements](/guides/payments/faq#seller-onboarding).

<Accordion title="Example: Seller Profile">
  Use [Create Profile](/api-reference/endpoints/profiles/create-profile) to represent the seller.

  ```shell theme={null}
  curl --location 'https://api.sandbox.paxos.com/v2/profiles' \
  --header 'Content-Type: application/json' \
  --header 'Accept: application/json' \
  --header 'Authorization: Bearer {access_token}' \
  --data '{
  ```

```
    "nickname": "Seller A",
    "description": "Stablecoin Pay-in and Refunds."
  }'
```

  Save the `id` (`profile_id`) from the response, it will be used throughout this guide.

```json theme={null}
  {
      "id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
      "nickname": "Seller A",
      "type": "NORMAL"
  }
```

  Use [List Profiles](/api-reference/endpoints/profiles/list-profiles) to retrieve the Profile ID when needed.
</Accordion>

* To represent the Buyer in this guide, send enough testnet tokens to pay network fees, along with one of the [supported testnet stablecoins](/guides/payments/faq#supported-assets), to an off-platform wallet.

<Accordion title="Example: Buyer's Wallet">
  We [airdropped Solana Devnet](https://faucet.solana.com/) to a self-custody wallet.
  We also used the [Paxos Testnet Faucet](https://faucet.paxos.com/) to transfer some [PYUSD on Solana Devnet](/guides/stablecoin/pyusd) to the Buyer's wallet.
  The same Buyer wallet is used to simulate a purchase as well as a refund.
</Accordion>

Set Up Stablecoin Pay-in Workflow

To accept a pay-in on the Paxos Platform, first use [Create Deposit Address](/api-reference/endpoints/deposit-addresses/create-deposit-address) to add a new wallet address on the public blockchain.
Then add the deposit address as a stablecoin payment option for Buyers, typically at checkout.

<Tip>
  Using a wallet connector or displaying a QR code in the Buyer interface helps to ensure that Buyers send the correct amount and avoid errors.
</Tip>

Once a Buyer completes a purchase, the transaction shows up in the [List Transfers](/api-reference/endpoints/transfers/list-transfers) monitoring and reconciliation polling request.

1. Add Seller Stablecoin Deposit Address

Use [Create Deposit Address](/api-reference/endpoints/deposit-addresses/create-deposit-address) to add a wallet address to the Profile designated for the Seller.
The request must include one of [supported stablecoins](/guides/payments/faq#supported-assets) networks.
Set `conversion_target_asset` to `USD` to automatically convert stablecoin pay-ins to USD on the Paxos Platform.

<Tip>
  Best Practice

  Whenever possible, include your own unique identifier in the request using `ref_id`.
  Doing so helps to protect against submitting the same request twice, as the second request with the same `ref_id` will be rejected with `409 already exists`.
  The `ref_id` can also be used in many query parameters.
</Tip>

The example uses `SOLANA` as the `crypto_network`.

If needed, use either `ETHEREUM` or `POLYGON_POS` for `crypto_network`.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/deposit-addresses' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{

    "profile_id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
    "crypto_network": "SOLANA",
    "ref_id": "da_73bcbb08-db06-4308-b0c2-2a6398012f8b",
    "conversion_target_asset": "USD"
    {/* highlight-end */}
}'
```

Capture the `address` and `compatible_crypto_networks` values for distribution to potential Buyers.
Also store the `id` to use when [looking up pay-ins](/guides/payments/quickstart/#pay-in-monitor-reconcile).

```json highlight={8,12} theme={null}
{
    "id": "2d3b2366-c432-4098-ba16-83ca418c6f00",
    "profile_id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
    "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
    "crypto_network": "SOLANA",
    "identity_id": "00000000-0000-0000-0000-000000000000",
    "ref_id": "da_73bcbb08-db06-4308-b0c2-2a6398012f8b",
    "address": "7iR1TfsaZ3f1PmbsoRuPYDbV7iujxZmuHaZDDU1Uv4YX",
    "account_id": "00000000-0000-0000-0000-000000000000",
    "conversion_target_asset": "USD",
    "compatible_crypto_networks": [
        "SOLANA"
    ]
}
```

Since the designated Profile has not gone through the Identity onboarding process, the default `identity_id` and `account_id` values appear in the response.

> Onboarding Questions?
> See the [onboarding FAQ](/guides/payments/faq#seller-onboarding) for details about user Identity and Account requirements.
> Contact [Support](https://support.paxos.com/hc/en-us) to help determine the best onboarding approach.

2. Receive Stablecoin Payment

Off the Paxos Platform, share the [deposit address](/guides/payments/quickstart#pay-in-add-deposit-address) with Buyers, typically on the checkout page, and start accepting stablecoin pay-ins.
Once a Buyer completes a pay-in transaction, Paxos credits the designated Profile with either stablecoin or USD, based on the deposit address configuration.

<Accordion title="Example: Buyer's Wallet">
  We [airdropped Solana Devnet](https://faucet.solana.com/) to a self-custody wallet.
  We also used the [Paxos Testnet Faucet](https://faucet.paxos.com/) to transfer some [PYUSD on Solana Devnet](/guides/stablecoin/pyusd) to the Buyer's wallet.
  The same Buyer wallet is used to simulate a purchase as well as a refund.
</Accordion>

For this guide, all received pay-ins are automatically converted to USD on the Paxos Platform because we used "conversion_target_asset": "USD"\` when [creating the deposit

address](/guides/payments/quickstart#pay-in-add-deposit-address).

3. Add Pay-in Monitoring and Reconciliation Request

Using [List Transfers](/api-reference/endpoints/transfers/list-transfers), create a recurring request that looks for completed transactions in the Seller's Profile. Retrieve the status for payments received in the [deposit address](/guides/payments/quickstart#pay-in-add-deposit-address) using the `profile_id`, filtered by on the `CRYPTO_DEPOSIT` type and `updated_at.gte` parameters.

<Tip>
  Best Practice

  We recommend to poll [List Transfers](/api-reference/endpoints/transfers/list-transfers) globally at a set cadence (for example, at 1 second intervals), using slightly behind the last processed `updated_at.gte` as a synchronization checkpoint.
</Tip>

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?profile_ids=eb1dbb95-8e22-471b-9ded-40bbfe309037&updated_at.gte=2024-06-24T15%3A44%3A54.383141Z&type=CRYPTO_DEPOSIT' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

The response confirms that a `total` of `7.06` PYUSD (`asset`) was converted to USD (`balance_asset`) when the pay-in reached the Paxos Platform.

```json theme={null}
{
    "items": [
        {
            "id": "9d93693f-5157-49f4-ae44-4a7a8eae3d73",
            "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
            "profile_id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
            "amount": "7.06",
            "total": "7.06",
            "fee": "0",
            "asset": "PYUSD",
            "balance_asset": "USD",
            {/* highlight-end */}
            "direction": "CREDIT",
            "type": "CRYPTO_DEPOSIT",
            "status": "COMPLETED",
            "created_at": "2024-06-24T15:44:48.724648Z",
            "updated_at": "2024-06-24T15:44:55.383141Z",
            "destination_address": "7iR1TfsaZ3f1PmbsoRuPYDbV7iujxZmuHaZDDU1Uv4YX",
            "crypto_network": "SOLANA",
            "crypto_tx_hash":
"4ex3dQ1bkoxQyyWKsk5UfVwNzzi2HXBcDb2Xv1BzxKLhRKZaVmfAJyM2hWochXTqTRDMsrpcfvoaFTMZrBsaaJPx",
            "crypto_tx_index": "4",
            "auto_conversion": {}
        }
    ],
    "next_page_cursor": "CAISDAj3qOazBhCIidm2ARijg5MN"
}
```

4. Move USD to Bank Account

To manage on-platform cash balances, use the [Fiat Transfers](/api-reference/endpoints/fiat-transfers) APIs to batch withdraw USD to any designated bank account as needed. Learn more in the [fiat transfers guide](/guides/developer/fiat-transfers).

> If you need to [create a fiat account](/api-reference/endpoints/fiat-transfers/create-fiat-account) Paxos may need to enable some API functionality.
> C> ontact [Support](https://support.paxos.com/hc/en-us) for assistance.

Set Up a Refund Workflow

To process stablecoin refunds on the Paxos Platform, first [fund your account with USD](/guides/payments/quickstart#refund-fund-account) then use [Create Crypto Withdrawal](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal) to initiate a stablecoin refund to the Buyer.
Once a refund is complete, the transaction shows up in the [List Transfers](/api-reference/endpoints/transfers/list-transfers) monitoring and reconciliation polling request.

1. Add USD to a Refund Account

Production implementations can use the [Fiat Transfers](/api-reference/endpoints/fiat-transfers) APIs to send USD to a destination on the Paxos Platform, which is out of scope for this guide.
The [fiat transfers guide](/guides/developer/fiat-transfers) provides step-by-step instructions on setting up fiat movements.

> If you need to [create a fiat account](/api-reference/endpoints/fiat-transfers/create-fiat-account) Paxos may need to enable some API functionality.
> Contact [Support](https://support.paxos.com/hc/en-us) for assistance.

For simplicity, this guide uses [Create Sandbox Deposit](/api-reference/endpoints/sandbox-deposits/create-sandbox-deposit) to simulate funding the designated Seller Profile with USD. Include the Seller's Profile ID (`profile_id`) as a path parameter, as well as the deposit `asset` and `amount` as query parameters.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/eb1dbb95-8e22-471b-9ded-40bbfe309037/deposit' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token} \
--data '{
    "asset": "USD",
    "amount": "100"
}'
```

A successful response only includes the system-generated `activity_id`.

```json theme={null}
{
    "activity_id": "a457f3b2-8897-4118-bc9b-216541cfc5a7"
}
```

1.1 Sandbox Only: Check USD Deposit

To confirm the USD deposit, use [List Profile Balances](/api-reference/endpoints/profiles/list-profile-balances).

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/eb1dbb95-8e22-471b-9ded-40bbfe309037/balances?assets=USD' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

The Profile USD balance is now `107.06`, reflecting both the previously received pay-in and the current USD deposit.

```json theme={null}
{
    "items": [
        {
            //highlight-start
            "asset": "USD",
            "available": "107.06",
            {/* highlight-end */}
            "trading": "0"
        }
    ]
}
```

2. Initiate a Stablecoin Refund

Use [Create Crypto Withdrawal](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal) to send stablecoin to the Buyer's designated wallet address.
The request must include one of [supported stablecoins](/guides/payments/faq#supported-assets) networks.

<Tip>
  Set `balance_asset` to `USD` to automatically convert fiat to stablecoin and issue a refund in a single request.
</Tip>

For this guide, the refund is issued to the Buyer's original wallet address (`destination_address`) using the same /guides/stablecoin/network pair:

* The `asset` is `PYUSD`, the `balance_asset` is `USD`, and the `crypto_network` is `SOLANA`.

The funding source is the Seller's Profile (`profile_id`) used earlier.

<Tip>
  Best Practice

  Whenever possible, include your own unique identifier in the request using `ref_id`.
  Doing so helps to protect against submitting the same request twice, as the second request with the same `ref_id` will be rejected with `409 already exists`.
  The `ref_id` can also be used in many query parameters.
</Tip>

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/crypto-withdrawals' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}' \
--data '{
    "profile_id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
    "asset": "PYUSD",
    "destination_address": "BtXdwoYSWPprQT88ZCLuQcXuTz4dFHB1AJFYqr5uXoAd",
    "crypto_network": "SOLANA",
    "ref_id": "cw_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
    "balance_asset": "USD",
    "amount": "7.06"
}'
```

The initial response has a `status` of `PENDING`, since the on-chain transaction has not yet been confirmed.
Create a [refund monitoring request](/guides/payments/quickstart#refund-monitor-reconcile) to check that the refund was successful.

```json theme={null}
```

```
{
    "id": "c327d8b7-0c1a-4125-b73f-318924373d37",
    "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
    "profile_id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
    "ref_id": "cw_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
    "amount": "7.06",
    "total": "7.06",
    "fee": "0",
    "asset": "PYUSD",
    "balance_asset": "USD",
    "direction": "DEBIT",
    "type": "CRYPTO_WITHDRAWAL",
    "status": "PENDING",
    "created_at": "2024-06-24T18:33:51.087868Z",
    "updated_at": "2024-06-24T18:33:51.087868Z",
    "destination_address": "BtXdwoYSWPprQT88ZCLuQcXuTz4dFHB1AJFYqr5uXoAd",
    "crypto_network": "SOLANA",
    "auto_conversion": {}
}
```

3. Add Refund Monitoring and Reconciliation Request

Using [List Transfers](/api-reference/endpoints/transfers/list-transfers), create a recurring request that looks for completed transactions in the Seller's Profile. Retrieve the status for refunds sent by using the `profile_id`, filtering by on the `CRYPTO_WITHDRAWAL` type and `updated_at.gte` parameters.

<Tip>
  Best Practice

  We recommend to poll [List Transfers](/api-reference/endpoints/transfers/list-transfers) globally at a set cadence (for example, at 1 second intervals), using slightly behind the last processed `updated_at.gte` as a synchronization checkpoint.
</Tip>

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/transfer/transfers?profile_ids=eb1dbb95-8e22-471b-9ded-40bbfe309037&updated_at.gte=2024-06-24T15%3A44%3A54.383141Z&type=CRYPTO_WITHDRAWAL' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

The response confirms that a `total` of `7.06` PYUSD (`asset`) was sent to the Buyer's wallet address.

```json theme={null}
{
    "items": [
        {
            "id": "c327d8b7-0c1a-4125-b73f-318924373d37",
            "customer_id": "8cbc1177-d982-4750-a435-3c7f36245452",
            "profile_id": "eb1dbb95-8e22-471b-9ded-40bbfe309037",
            "ref_id": "cw_293a8f7c-bcb6-483f-919b-8661ae65f0e6",
            //highlight-start
            "amount": "7.06",
            "total": "7.06",
            "fee": "0",
            "asset": "PYUSD",
            "balance_asset": "USD",
            "direction": "DEBIT",
            "type": "CRYPTO_WITHDRAWAL",
            "status": "COMPLETED",
            {/* highlight-end */}
```

```
            "created_at": "2024-06-24T18:33:51.105228Z",
            "updated_at": "2024-06-24T18:34:24.976618Z",
            "destination_address": "BtXdwoYSWPprQT88ZCLuQcXuTz4dFHB1AJFYqr5uXoAd",
            "crypto_network": "SOLANA",
            "crypto_tx_hash":
"4xo8doZQ58W6WCrzmyjd3vyrv2SPMRjHiz4v6w8mEuCCWbAyiXjzbFADia7St6XF3jTNyQmrDmpSNH84TXdDujFU",
            "crypto_tx_index": "0",
            "auto_conversion": {}
        }
    ],
    "next_page_cursor": "CAISDAiw-OazBhCQhNjRAxi0jpMN"
}
```

3.1 Sandbox Only: Check USD Withdrawal

To confirm USD was used to fund the crypto withdrawal, use [List Profile Balances](/api-reference/endpoints/profiles/list-profile-balances).

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/eb1dbb95-8e22-471b-9ded-40bbfe309037/balances?assets=USD' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {access_token}'
```

The Profile USD balance is now `100.00`, where previously it was `7.06`.

```json theme={null}
{
    "items": [
        {
            //highlight-start
            "asset": "USD",
            "available": "100.00",
            {/* highlight-end */}
            "trading": "0"
        }
    ]
}
```

Statuses
Source: https://docs.paxos.com/guides/payments/status

Learn more about payment statuses.

Pay-ins

* [List Transfers](/api-reference/endpoints/transfers/list-transfers): When [monitoring a pay-in](/guides/payments/quickstart#pay-in-monitor-reconcile), a `PENDING` transaction is being confirmed. Depending on the network, confirmation can take from seconds to minutes. Transactions with a `COMPLETED` status have received sufficient confirmations. The `FAILED` status means the transaction was denied.
* [Create Fiat Withdrawal](/api-reference/endpoints/fiat-transfers/create-fiat-withdrawal): When [withdrawing USD to a bank account](/guides/payments/quickstart#pay-in-withdraw-fiat), the `PENDING` status means the request has been made and is being processes. Depending on the withdrawal type, it can take up to a few days for the transaction to complete. When the transfer to the bank account is successful, the status changes to `COMPLETED`.

Refunds

* [List Transfers](/api-reference/endpoints/transfers/list-transfers): When [funding a USD account for refunds](/guides/payments/quickstart#refund-fund-account), the transfer has an

initial status of `PENDING`, meaning the USD deposit has been detected and is being confirmed. The `COMPLETED` status means the USD funds have been credited to the given Profile.
* [Create Crypto Withdrawal](/api-reference/endpoints/crypto-withdrawals/create-crypto-withdrawal): When [issuing a crypto refund](/guides/payments/quickstart#refunds), the withdrawal has an initial status of `PENDING`, meaning Paxos has received the request and is processing the transaction. Depending on the network, confirmation can take from seconds to minutes. The `COMPLETED` status indicates the transaction has been broadcasted to the blockchain and received the required number of confirmations.

Onboarding

* [Create Identity](/api-reference/endpoints/identity/create-identity) (if applicable): When onboarding an Identity, the initial response includes the `PENDING` status while screening takes place. If the screenings fail, the identity may be `DENIED`.

> To minimize the occurrence of denied identities, contact [Support](https://support.paxos.com) when planning an Identity workflow. Learn more about [user onboarding requirements](/guides/payments/faq#seller-onboarding).

FAQ
Source: https://docs.paxos.com/guides/settlements/faq

Get answers to common questions about the Settlements API.

<AccordionGroup>
  <Accordion title="Do I need to have the right amount of assets before creating the transaction?">
    No.
    You can create and approve the transaction first and then deposit [assets](/guides/developer/blockchains) when ready.
    Settlement only takes place when the transaction is [affirmed](/guides/settlements/status) and all the required assets have been deposited.
  </Accordion>

  <Accordion title="Why am I not receiving email notifications when testing in Sandbox?">
    Notifications are off by default in Sandbox. Contact [Support](https://support.paxos.com) to turn them on.
  </Accordion>

  <Accordion title="Which assets are supported for Sandbox testing?">
    You can fund your Sandbox Account with the supported [assets](/guides/developer/blockchains) or those listed in [Create Sandbox Deposit](/api-reference/endpoints/sandbox-deposits/create-sandbox-deposit).
    For most setups, use the assets you can trade, transfer or withdraw for testing.
  </Accordion>
</AccordionGroup>

Overview
Source: https://docs.paxos.com/guides/settlements/index

Propose, approve and manage two-way atomic transfers.

<img alt="Settlements Profiles" />

Use the Settlements API to facilitate simultaneous exchange of pre-funded assets. Automate a variety of use cases that require two-party approval, including net settlement of over-the-counter trades, withdrawal requests for tri-party collateral, payment requests, and bilateral settlement for marketplace end users.

The simple request-and-approval workflow supports both one-directional and bidirectional transactions to allow a user to receive an asset (for example, send USDP) or simultaneously send and receive assets (for example, send USD and receive BTC and ETH).

Only when all parties are in agreement and assets are fully funded does the Settlements API allow for change of custody.
Upon completion, all settled assets are immediately available for trading, transferring, withdrawal or other supported activities.

Settlement Workflow

The settlement workflow requires two parties to complete: The Source Profile owner who [initiates](/api-reference/endpoints/settlement/create-transaction) the transaction and the Target Profile owner who [approves](/api-reference/endpoints/settlement/affirm-transaction) the transaction.
Most integrations follow a similar workflow:

1. Both parties agree on the transaction details and share counterparty Profile IDs outside of the Paxos Platform (for example, via email, Telegram, or other application).
2. The Source Profile owner [submits the transaction](/api-reference/endpoints/settlement/create-transaction) to the settlement platform.
3. The Target Profile owner receives a [notification](/guides/settlements/notification), reviews the transaction details and [approves the transaction](/api-reference/endpoints/settlement/affirm-transaction).
4. Both parties fund the associated Profiles via deposits if the requisite balances are not already present.
5. Settlement (movement of assets between Profiles) occurs soon after both parties have sufficient assets on the platform.
6. Once the transaction [settles](/guides/settlements/status), both parties can immediately utilize the new balance.

Get Started

<CardGroup>
  <Card title="Quickstart" href="/guides/settlements/quickstart" icon="rocket">
    Set up and complete the settlement workflow in the Sandbox environment.
  </Card>

  <Card title="Statuses" href="/guides/settlements/status" icon="list-check">
    Learn more about settlement statuses.
  </Card>

  <Card title="Notifications" href="/guides/settlements/notification" icon="bell">
    Understand how settlement notifications work.
  </Card>

  <Card title="FAQ" href="/guides/settlements/faq" icon="circle-question">
    Get answers to common questions about the Settlements API.
  </Card>
</CardGroup>

Notifications
Source: https://docs.paxos.com/guides/settlements/notification

Understand how settlement notifications work.

By default, each Profile owner receives an email notification when a settlement transaction is [created](/api-reference/endpoints/settlement/create-transaction) and upon each [status](/guides/settlements/status) change.
Currently, only email notifications are supported.
Websocket and desktop notifications are being considered for future releases.

> To test email notifications in Sandbox, contact [Support](https://support.paxos.com) to enable notifications.

All settlement email notifications use the same template:

<img alt="Settlements Email Notification" />

Quickstart
Source: https://docs.paxos.com/guides/settlements/quickstart

Set up and complete the settlement workflow in the Sandbox environment.

The [settlement workflow](/guides/settlements#workflow) requires [two Profiles](#set-up-profiles), referred to in this guide as Source Profile (`source_profile_id`) and Target Profile (`target_profile_id`).
The Profiles are under the same Sandbox Account for simplicity and to allow completion of the steps with a single [authentication](#authenticate).
This guild also [funds](#fund) the Source Profile with BTC and ETH for the `DELIVER` leg and USD in the Target Profile for the `RECEIVE` leg before [creating the transaction request](#propose).

> Contact your [Entity Manager](/guides/dashboard/roles#entity-manager) or [Support](https://support.paxos.com) if you run into any issues or don't have access to a Sandbox Account.

1. Authenticate

Add the `settlement:read_transaction` and `settlement:write_transaction` scopes to your [Sandbox Account](https://dashboard.sandbox.paxos.com) under the [API Management](https://dashboard.sandbox.paxos.com/admin/api) setting and then authenticate in Sandbox using the scopes.
Also include `funding:read_profile` and `funding:write_profile` for creating and funding [Profiles](/api-reference/endpoints/profiles).

```shell highlight={5} theme={null}
curl --location 'https://oauth.sandbox.paxos.com/oauth2/token' \
--form grant_type=client_credentials \
--form client_id={paxos_client_id} \
--form client_secret={paxos_secret} \
--form scope='settlement:read_transaction settlement:write_transaction funding:read_profile funding:write_profile'
```

Confirm the response includes requisite scopes and save the `access_token` to use in the request authorization header throughout this guide.

```json highlight={3,4} theme={null}
{
  "access_token": "{access_token}",
  "expires_in": 3599, // Seconds (59 Minutes and 59 Seconds)
  "scope": "settlement:read_transaction settlement:write_transaction funding:read_profile funding:write_profile",
  "token_type": "bearer"
}
```

2. Set Up Profiles

[Create](/api-reference/endpoints/profiles/create-profile) two new Profiles in the Sandbox Account, one with `Source Profile` and the second with `Target Profile` as the `nickname`.

Create Source Profile

```shell highlight={4} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "nickname": "Source Profile"
}'
```

You will need the `id` from the response to [fund the Profile](#fund) and [propose a transaction](#propose).

```json highlight={2} theme={null}
{
    "id": "{profile_id}", // The source_profile_id in the Transaction object
    "nickname": "Source Profile",
    "type": "NORMAL"
}
```

Create Target Profile

```shell highlight={4} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "nickname": "Target Profile"
}'
```

You will need the `id` from the response to [fund the Profile](#fund) and [propose a transaction](#propose).

```json highlight={2} theme={null}
{
    "id": "{profile_id}", // The target_profile_id in the Transaction object
    "nickname": "Target Profile",
    "type": "NORMAL"
}
```

3. Fund Profiles

Next, use [Create Sandbox Deposit](/api-reference/endpoints/sandbox-deposits/create-sandbox-deposit) to fund the Profiles.

<Tip>
  This guide pre-funds all accounts prior to [creating a settlement request](#propose) for simplicity.
  However, it is possible to create and approve a settlement request [before the funds are available](/guides/settlements/faq#assets).
</Tip>

Fund Source Profile

Deposit crypto into the Source Profile.
First, Bitcoin:

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/{profile_id}' \
--header 'Authorization: Bearer {access_token}' \
--data '
  {
    "asset": "BTC",
    "amount": "2",
    "crypto_network": "BITCOIN"
  }'
```

Then add some Ethereum:

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/{profile_id}' \
```

```
--header 'Authorization: Bearer {access_token}' \
--data '
{
  "asset": "ETH",
  "amount": "10",
  "crypto_network": "ETHEREUM"
}'
```

Use [List Profile Balances](/api-reference/endpoints/profiles/list-profile-balances) to retrieve the Source Profile balance.
Include the `assets` query parameter to filter out all other assets.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/{profile_id}/balances?assets=BTC&assets=ETH' \
--header 'Authorization: Bearer {access_token}'
```

Confirm the Source Profile has at least 1 BTC and 5 ETH available for trading.

```json highlight={5,10} theme={null}
{
    "items": [
        {
            "asset": "BTC",
            "available": "2",
            "trading": "0"
        },
        {
            "asset": "ETH",
            "available": "10",
            "trading": "0"
        }
    ]
}
```

Fund Target Profile

Deposit USD into the Target Profile.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/sandbox/profiles/{profile_id}' \
--header 'Authorization: Bearer {access_token}' \
--data '
  {
    "asset": "USD",
    "amount": "100000"
  }'
```

Use [Get Profile Balance](/api-reference/endpoints/profiles/get-profile-balance) to retrieve the Target Profile USD balance.

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/profiles/{profile_id}/balances/USD' \
--header 'Authorization: Bearer {access_token}'
```

Confirm the Target Profile has at least \$50,000 USD available for trading.

```json highlight={3} theme={null}
{
    "asset": "USD",
```

```
    "available": "100000",
    "trading": "0"
}
```

4. Propose Transaction

Using the Source Profile and Target Profile `profile_id` [created earlier](#set-up-profiles), use [Create Transaction](/api-reference/endpoints/settlement/create-transaction) to propose exchanging 1 BTC and 5 ETH (in the Source Profile balance) for \$50,000 USD (in the Target Profile balance). The `ref_id` must be unique. The settlement window defaults apply if `settlement_window_start` and/or `settlement_window_end` are not specified.

```shell highlight={4,5,6} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/settlement/transactions' \
--header 'Authorization: Bearer {access_token}' \
--data '{
  "ref_id": "required_idempotence_id",
  "settlement_window_start": "YYYY-MM-DDT00:00:00Z",
  "settlement_window_end": "YYYY-MM-DDT00:00:00Z",
  "source_profile_id": "{profile_id}",
  "target_profile_id": "{profile_id}",
  "legs": [
    {
        "direction": "DELIVER",
        "asset": "BTC",
        "amount": "1.00"
    },
    {
        "direction": "DELIVER",
        "asset": "ETH",
        "amount": "5"
    },
        {
        "direction": "RECEIVE",
        "asset": "USD",
        "amount": "50000.00"
    }
  ]
}'
```

The acknowledgement response confirms the request has been received and provides the `Transaction` object.
The unique transaction `id` is used to [approve](#approve) and [retrieve](#check-status) the transaction, and the Source Profile owner can use the `id` to [cancel](/api-reference/endpoints/settlement/cancel-transaction) the `PENDING` transaction.
The transaction [status](/guides/settlements/status) can be used by either party to [retrieve a list of filtered transactions](/guides/settlements/status#list-transactions).

```json highlight={2,28} theme={null}
{
    "id": "{unique_transaction_id}",
    "ref_id": "required_idempotence_id",
    "settlement_window_start": "YYYY-MM-DDT00:00:00Z", // Defaults to current time
    "settlement_window_end": "YYYY-MM-DDT00:00:00Z", // Defaults to settlement_window_start
plus 24 hours
    "source_profile_id": "{profile_id}",
    "target_profile_id": "{profile_id}",
    "legs": [
        {
            "id": "{unique_leg_1_id}",
            "direction": "DELIVER", // From Source Profile
            "asset": "BTC",
            "amount": "1"
```

```
        },
        {
            "id": "{unique_leg_2_id}",
            "direction": "DELIVER", // From Source Profile
            "asset": "ETH",
            "amount": "5"
        },
        {
            "id": "{unique_leg_3_id}",
            "direction": "RECEIVE", // From Target Profile
            "asset": "USD",
            "amount": "50000"
        }
    ],
    "status": "PENDING",
    "created_at": "YYYY-MM-DDT00:00:00Z",
    "updated_at": "YYYY-MM-DDT00:00:00Z"
}
```

5. Approve Transaction

The Target Profile owner [approves (affirms)](/api-reference/endpoints/settlement/affirm-transaction) the transaction.

<Tip>
  Since the same Paxos Account is used for both counterparty Profiles in this guide, you can use the same [authentication](#authenticate).
</Tip>

Use the `Transaction.id` from the [propose step](#propose) as the `transaction_id`.
You can also [look up a transaction by status](/guides/settlements/status#list-transactions) to find the `id`.

```shell theme={null}
curl --location --request PUT
'https://api.sandbox.paxos.com/v2/settlement/transactions/{transaction_id}/affirm' \
--header 'Authorization: Bearer {access_token}'
```

The acknowledgement response includes transaction information and the `AFFIRMED` [status](/guides/settlements/status) and `updated_at` timestamp.

```json highlight={8,10} theme={null}
{
    "id": "{unique_transaction_id}",
    "ref_id": "required_idempotence_id",
    "settlement_window_start": "YYYY-MM-DDT00:00:00Z",
    "settlement_window_end": "YYYY-MM-DDT00:00:00Z",
    "source_profile_id": "{profile_id}",
    "target_profile_id": "{profile_id}",
    "status": "AFFIRMED",
    "created_at": "YYYY-MM-DDT00:00:00Z",
    "updated_at": "YYYY-MM-DDT00:00:00Z"
}
```

6. Check Transaction Status

Settlement of the `AFFIRMED` transaction occurs only when both counterparties fully fund their Profiles.

<Tip>
  Since both Profiles in this guide are [pre-funded](#set-up-profiles), the transaction settled within a few seconds.

</Tip>

Either party can use [Get Transaction](/api-reference/endpoints/settlement/get-transaction) to check the [status](/guides/settlements/status).

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/settlement/transactions/{transaction_id}' \
--header 'Authorization: Bearer {access_token}'
```

The response includes the complete `Transaction` object.
When the transaction completes, the [status](/guides/settlements/status) and `updated_at` timestamp reflect the most recent activity.

```json highlight={28,30} theme={null}
{
    "id": "{unique_transaction_id}",
    "ref_id": "required_idempotence_id",
    "settlement_window_start": "YYYY-MM-DDT00:00:00Z",
    "settlement_window_end": "YYYY-MM-DDT00:00:00Z",
    "source_profile_id": "{profile_id}",
    "target_profile_id": "{profile_id}",
    "legs": [
        {
            "id": "{unique_leg_1_id}",
            "direction": "DELIVER",
            "asset": "BTC",
            "amount": "1"
        },
        {
            "id": "{unique_leg_2_id}",
            "direction": "DELIVER",
            "asset": "ETH",
            "amount": "5"
        },
        {
            "id": "{unique_leg_3_id}",
            "direction": "RECEIVE",
            "asset": "USD",
            "amount": "50000"
        }
    ],
    "status": "SETTLED",
    "created_at": "YYYY-MM-DDT00:00:00Z",
    "updated_at": "YYYY-MM-DDT00:00:00Z"
}
```

Next Steps

* Create a settlement transaction before funding the Profiles.
* Learn more in the Settlements [FAQ](/guides/settlements/faq).
* Explore settlement methods and objects in the [Settlements API](/api-reference/endpoints/settlement).

Statuses
Source: https://docs.paxos.com/guides/settlements/status

Learn more about settlement statuses.

The [settlement workflow](/guides/settlements/index#workflow) includes five statuses:

* `PENDING`: Initial state of a settlement transaction upon creation by the Source Profile

owner (`source_profile_id`).
* `AFFIRMED`: The settlement transaction has been approved by the Target Profile owner (`target_profile_id`) and will be eligible for settlement once within the transaction window (`settlement_window_start` → `settlement_window_end`).
* `SETTLED`: The assets in the transaction have successfully been transferred.
* `EXPIRED`: The settlement transaction is no longer eligible for settlement.
* `CANCELED`: The settlement transaction was canceled by the Source Profile owner.

When a settlement transactions is [created](/api-reference/endpoints/settlement/create-transaction), it starts in `PENDING` status.
The assets do not need to be available in the Profiles at this stage.
In the `PENDING` state, two actions can be taken:

* The Source Profile owner [cancels](/api-reference/endpoints/settlement/cancel-transaction) the transaction. Status transitions to `CANCELLED`.
* The Target Profile owner [approves](/api-reference/endpoints/settlement/affirm-transaction) the transaction. Status transitions to `AFFIRMED`.

Once the required asset balances are in the respective Profiles, settlement occurs. Status transactions to `SETTLED` when complete.

```mermaid theme={null}
flowchart LR
  A[PENDING] ==> | Target Profile owner approves | B[AFFIRMED] ==>C[SETTLED]
  A --> | Settlement window expires | D[EXPIRED]
  A --> | Source Profile owner cancels | E[CANCELLED]
  B --> D
```

Transactions in the `PENDING` or `AFFIRMED` state at the end of the settlement window (`settlement_window_end`) automatically transition to `EXPIRED`.

Find Transactions by Status

Either involved party can use [List Transactions](/api-reference/endpoints/settlement/list-transactions) to retrieve all the transactions they are counterparty to.
Use the `statuses` query parameter to filter based on status.

<Tip>
  You must specify the `limit` of items per page or an error returns.
</Tip>

```shell theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/settlement/transactions?statuses=PENDING&statuses=AFFIRMED&limit=2' \
--header 'Authorization: Bearer {access_token}'
```

Based on the request parameters, the response contains the two most recent open transactions.

```json highlight={30,61,66} theme={null}
{
    "items": [
        {
            "id": "{unique_transaction_id}",
            "ref_id": "required_idempotence_id_1",
            "settlement_window_start": "YYYY-MM-DDT00:00:00Z",
            "settlement_window_end": "YYYY-MM-DDT00:00:00Z",
            "source_profile_id": "{profile_id}",
            "target_profile_id": "{profile_id}",
            "legs": [
                {
                    "id": "{unique_leg_1_id}",
                    "direction": "DELIVER",
```

```
                    "asset": "BTC",
                    "amount": "1"
                },
                {
                    "id": "{unique_leg_2_id}",
                    "direction": "DELIVER",
                    "asset": "ETH",
                    "amount": "5"
                },
                {
                    "id": "{unique_leg_3_id}",
                    "direction": "RECEIVE",
                    "asset": "USD",
                    "amount": "40000"
                }
            ],
            "status": "PENDING",
            "created_at": "YYYY-MM-DDT00:00:00Z",
            "updated_at": "YYYY-MM-DDT00:00:00Z"
        },
        {
            "id": "{unique_transaction_id}",
            "ref_id": "required_idempotence_id",
            "settlement_window_start": "YYYY-MM-DDT00:00:00Z",
            "settlement_window_end": "YYYY-MM-DDT00:00:00Z",
            "source_profile_id": "{profile_id}",
            "target_profile_id": "{profile_id}",
            "legs": [
                {
                    "id": "{unique_leg_1_id}",
                    "direction": "DELIVER",
                    "asset": "BTC",
                    "amount": "1"
                },
                {
                    "id": "{unique_leg_2_id}",
                    "direction": "DELIVER",
                    "asset": "ETH",
                    "amount": "5"
                },
                {
                    "id": "{unique_leg_3_id}",
                    "direction": "RECEIVE",
                    "asset": "USD",
                    "amount": "40000"
                }
            ],
            "status": "AFFIRMED",
            "created_at": "YYYY-MM-DDT00:00:00Z",
            "updated_at": "YYYY-MM-DDT00:00:00Z"
        }
    ],
    "next_page_cursor": "{page_cursor_value}"
}
```

To view more items, add the `page_cursor` query parameter to the request.

```shell highlight={1} theme={null}
curl --location 'https://api.sandbox.paxos.com/v2/settlement/transactions?
limit=2&page_cursor={page_cursor_value}' \
--header 'Authorization: Bearer {access_token}'
```

BUSD
Source: https://docs.paxos.com/guides/stablecoin/busd

Redeem or convert BUSD on the Paxos platform.

Paxos no longer mints new BUSD, but allows customers to redeem BUSD for USD or convert their BUSD to USDP.
Read the [Paxos statement on BUSD](https://paxos.com/2023/02/13/paxos-will-halt-minting-new-busd-tokens/).

> **Questions?** [Contact the Stablecoin Team](https://support.paxos.com).

Stablecoins
Source: https://docs.paxos.com/guides/stablecoin/index

Use Paxos-issued stablecoins for payments, money movement and more.

Paxos provides regulated, trustworthy stablecoins to make it easy for any blockchain application to add a trusted stablecoin to their product.

> See the [Paxos Developer Guides](/guides/developer) to [mint](/guides/developer/mint), [redeem](/guides/developer/redeem) and [convert](/guides/developer/convert) Paxos-issued stablecoins on the platform.
Questions? [Contact the Stablecoin Team](https://support.paxos.com).

Global Dollar (USDG)

[Global Dollar (USDG)](/guides/stablecoin/usdg) is a single-currency stablecoin (SCS) pegged to the US dollar, issued by Paxos Digital Singapore Pte. Ltd. (PDS) and is compliant with the Monetary Authority of Singapore's (MAS) forthcoming stablecoin framework.
Built for payments, settlements and treasury, USDG can be used as an interoperable building block for open-source smart contracts, enabling developers to create new use-cases, products and services with USDG.
All cash and cash equivalent reserve assets are held in segregated accounts to protect user assets.
USDG is available for purchase and fully redeemable from Paxos on a one-to-one basis for US dollars (1 USDG = 1 USD).

Pax Dollar (USDP)

[Pax Dollar (USDP)](/guides/stablecoin/usdp), issued by Paxos Trust Company, LLC (Paxos), is an open, U.S. dollar-denominated stablecoin.
USDP reserves are held 100% in cash and cash equivalents.
Available on multiple blockchains, USDP offers near-instant global settlements, low to no-cost transactions, and can be integrated with the most widely used exchanges, wallets, and dApps.
USDP is always fully redeemable from Paxos on a one-to-one basis for US dollars (1 USDP = 1 USD).

PayPal USD (PYUSD)

[PayPal USD (PYUSD)](/guides/stablecoin/pyusd), issued by Paxos Trust Company, LLC (Paxos), is an open, fully backed, U.S. dollar-denominated stablecoin designed for payments.
Available on multiple blockchains, PYUSD offers near-instant global settlements, low to no-cost transactions, and can be integrated with the most widely used exchanges, wallets, and dApps.
The stablecoin is also used to power a number of use cases, including cross-border P2P payments, B2B transfers, global payouts, microtransactions and web3 payments.

Regulation and Transparency

Paxos is committed to building trust in digital assets with regulated blockchain infrastructure and regulated, fully-backed USD stablecoins.
The monthly reserve reports ensure full transparency and the reliability of our financial

```
data.
Read the [transparency reports](https://paxos.com/regulation-and-transparency/).


# Integrate with PYUSD on Ethereum
Source: https://docs.paxos.com/guides/stablecoin/integrate-pyusd

The steps to integrate PYUSD on your platform are similar to executing smart contract
functions for other ERC20 tokens.

A minimally viable implementation of PYUSD must:

* Allow the recipient to create an Ethereum wallet address to receive PYUSD tokens.
* Monitor the PYUSD main network address for transfers to the recipient's wallet address.
* Appropriately credit the user's balance upon confirmed transfers.
* Allow the user to transfer PYUSD tokens back to Paxos and PayPal using the contract's
`transfer` or `transferFrom` functions.

When using `transferFrom`, we recommend using the `increaseApproval` and `decreaseApproval`
functions rather than `approve`.
This avoids a [well known attack vector]
(https://github.com/ethereum/ercs/blob/master/ERCS/erc-20.md) in the standard `approve`
function.


# PYUSD Overview
Source: https://docs.paxos.com/guides/stablecoin/pyusd/index

Use PayPal USD as the payments layer to build new services and products on public
blockchains.

<img alt="PYUSD" />

PayPal USD (PYUSD), issued by Paxos Trust Company, LLC (Paxos), is an open, fully backed,
U.S. dollar-denominated stablecoin designed for payments.
Available on multiple blockchains, PYUSD offers near-instant global settlements, low to no-
cost transactions, and can be integrated with the most widely used exchanges, wallets, and
dApps.
The stablecoin is also used to power a number of use cases, including cross-border P2P
payments, B2B transfers, global payouts, microtransactions and web3 payments.

> See the [Paxos Developer Guides](/) to [mint](/guides/developer/mint), [redeem]
(/guides/developer/redeem) and [convert](/guides/developer/convert) PYUSD on the Paxos
platform.<br />**Questions?** [Contact the Stablecoin Team](https://support.paxos.com).

## PYUSD Transparency

PayPal and Paxos are committed to ensuring the public availability of reports on the PYUSD
reserve assets.
To ensure transparency on PYUSD reserve assets, Paxos publishes monthly reports on reserve
composition as well as attestations reports issued by an independent third-party accounting
firm. See the [PYUSD transparency reports](https://paxos.com/pyusd-transparency/).


# PYUSD on Main Networks
Source: https://docs.paxos.com/guides/stablecoin/pyusd/mainnet

Get the PYUSD mainnet addresses.

<Danger>
  Tokens on mainnet blockchains have financial value.
  Never test on mainnet blockchains.
</Danger>

| Network             | Token Address
```

```
|
| ------------------- | ------------------------------------------------------------------------
---------------------------------------------------- |
| Ethereum Mainnet    | [0x6c3ea9036406852006290770BEdFcAbA0e23A0e8]
(https://etherscan.io/token/0x6c3ea9036406852006290770bedfcaba0e23a0e8)   |
| Solana Mainnet Beta | [2b1kV6DkPAnxd5ixfnxCpjxmKwqjjaYmCZfHsFu24GXo]
(https://solscan.io/token/2b1kV6DkPAnxd5ixfnxCpjxmKwqjjaYmCZfHsFu24GXo) |
| Arbitrum Mainnet    | [0x46850aD61C2B7d64d08c9C754F45254596696984]
(https://arbiscan.io/token/0x46850ad61c2b7d64d08c9c754f45254596696984)    |

## Supply Control Contract Addresses

| Network          | Supply Control Address
|
| ---------------- | ------------------------------------------------------------------------
---------------------------------------------- |
| Ethereum Mainnet | [0x31d9bDEa6F104606C954f8FE6ba614F1BD347Ec3]
(https://etherscan.io/address/0x31d9bDEa6F104606C954f8FE6ba614F1BD347Ec3) |
| Arbitrum Mainnet | [0x19eD5C631EDD34AC776368C377A855C42bc1876A]
(https://arbiscan.io/address/0x19eD5C631EDD34AC776368C377A855C42bc1876A)  |


# PYUSD on Test Networks
Source: https://docs.paxos.com/guides/stablecoin/pyusd/testnet

Get the PYUSD testnet addresses.

<Warning>
  Testnet tokens have no value! Only use these for testing purposes.
</Warning>

| Test Network             | Token Address
|
| ------------------------ | ------------------------------------------------------------------
------------------------------------------------------------------- |
| Ethereum Sepolia Testnet | [0xCaC524BcA292aaade2DF8A05cC58F0a65B1B3bB9]
(https://sepolia.etherscan.io/token/0xcac524bca292aaade2df8a05cc58f0a65b1b3bb9)          |
| Solana Devnet            | [CXk2AMBfi3TwaEL2468s6zP8xq9NxTXjp9gjMgzeUynM]
(https://solscan.io/token/CXk2AMBfi3TwaEL2468s6zP8xq9NxTXjp9gjMgzeUynM?cluster=devnet) |
| Arbitrum Sepolia Testnet | [0x637A1259C6afd7E3AdF63993cA7E58BB438aB1B1]
(https://sepolia.arbiscan.io/token/0x637A1259C6afd7E3AdF63993cA7E58BB438aB1B1)           |

## Supply Control Contract Addresses

| Test Network             | Supply Control Address
|
| ------------------------ | ------------------------------------------------------------------
------------------------------------------------------------ |
| Ethereum Sepolia Testnet | [0xE288F41c4bdA3Cb5C75156E263CB8ecbB8eF60E2]
(https://sepolia.etherscan.io/address/0xE288F41c4bdA3Cb5C75156E263CB8ecbB8eF60E2) |
| Arbitrum Sepolia Testnet | [0x7Bc02856903Bd5D848892014283Ea2eDE8d4cEDf]
(https://sepolia.arbiscan.io/address/0x7Bc02856903Bd5D848892014283Ea2eDE8d4cEDf)  |


# USDG Overview
Source: https://docs.paxos.com/guides/stablecoin/usdg/index

Use Global Dollar for payments, settlements, treasury and more.

<img alt="USDG" />

Global Dollar (USDG) is a single-currency stablecoin (SCS) pegged to the US dollar, issued
by Paxos Digital Singapore Pte. Ltd. (PDS), which is a Major Payments Institution supervised
by the Monetary Authority of Singapore. Built for payments, settlements and treasury, USDG
can be used as an interoperable building block for open-source smart contracts, enabling
```

developers to create new use-cases, products and services with USDG. All cash and cash equivalent reserve assets are held in segregated accounts to protect user assets. USDG is available for purchase and fully redeemable from Paxos on a one-to-one basis for US dollars (1 USDG = 1 USD).

> See the [Paxos Developer Guides](/) to [mint](/guides/developer/mint), [redeem](/guides/developer/redeem) and [convert](/guides/developer/convert) USDG on the Paxos platform.
Questions? [Contact the Stablecoin Team](https://support.paxos.com).

USDG Transparency

Paxos is committed to ensuring the public availability of reports on the USDG reserve assets.
To ensure transparency on USDG reserve assets, Paxos publishes monthly reports on reserve composition as well as attestations reports issued by an independent third-party accounting firm. See the [USDG transparency reports](https://paxos.com/usdg-transparency/).

USDG on Main Networks
Source: https://docs.paxos.com/guides/stablecoin/usdg/mainnet

Get the USDG token addresses.

<Danger>
  Tokens on mainnet blockchains have financial value.
  Never test on mainnet blockchains.
</Danger>

Network	Token Address
Ethereum Mainnet	[0xe343167631d89B6Ffc58B88d6b7fB0228795491D](https://etherscan.io/address/0xe343167631d89B6Ffc58B88d6b7fB0228795491D)
Solana Mainnet Beta	[2u1tszSeqZ3qBWF3uNGPFc8TzMk2tdiwknnRMWGWjGWH](https://solscan.io/token/2u1tszSeqZ3qBWF3uNGPFc8TzMk2tdiwknnRMWGWjGWH)
Ink Mainnet	[0xe343167631d89B6Ffc58B88d6b7fB0228795491D](https://explorer.inkonchain.com/address/0xe343167631d89B6Ffc58B88d6b7fB0228795491D)
Xlayer Mainnet	[0x4ae46a509F6b1D9056937BA4500cb143933D2dc8](https://www.oklink.com/x-layer/address/0x4ae46a509f6b1d9056937ba4500cb143933d2dc8)

Supply Control Contract Addresses

Network	Supply Control Address
Ethereum Mainnet	[0x9a7164112029b81c07636AB7b59fA813E0883BBF](https://etherscan.io/address/0x9a7164112029b81c07636AB7b59fA813E0883BBF)
Ink Mainnet	[0x9a7164112029b81c07636AB7b59fA813E0883BBF](https://explorer.inkonchain.com/address/0x9a7164112029b81c07636AB7b59fA813E0883BBF)
Xlayer Mainnet	[0x046Ca5A59D53448BF63E0BEE1D552c84Ad8BEB70](https://www.oklink.com/x-layer/address/0x046Ca5A59D53448BF63E0BEE1D552c84Ad8BEB70)

Getting Started with USDG (Global Dollar)
Source: https://docs.paxos.com/guides/stablecoin/usdg/quickstart

How to Access USDG.

USDG is a regulated, US dollar-backed stablecoin issued by Paxos Digital Singapore (PDS), which is a Major Payments Institution supervised by the Monetary Authority of Singapore (MAS). Each USDG token is always redeemable 1:1 for USD.

Key Features

```
* **Regulated & Transparent:** Issued by PDS, which is supervised by the MAS, with monthly
attestation reports.
* **1:1 USD Backing:** Every token is backed by USD held in segregated accounts.
* **Multi-Chain:** Available on Ethereum and Solana networks.

### Getting Started with USDG

1. Create a Paxos Institutional Account
   * Visit [dashboard.paxos.com](https://dashboard.paxos.com/) ([How to sign up]
(/guides/dashboard/account))
   * Click **"Become a partner of the Global Dollar Network"**
   * Complete the onboarding process
2. **Submit Required Documentation** ([Onboarding requirements](/guides/dashboard/onboard))
   * Organizational documents
   * Identification for key personnel
   * KYC verification
3. **Start Using USDG** ([How to mint USDG](/guides/dashboard/mint))
   * Mint USDG directly from USD via the Paxos Dashboard
   * Monitor holdings and transactions in real time

### Need Help?

* Technical Support: [support.paxos.com](https://support.paxos.com)
* Transparency Reports: [paxos.com/usdg-transparency](https://paxos.com/usdg-transparency)


# USDG on Test Networks
Source: https://docs.paxos.com/guides/stablecoin/usdg/testnet

Get the USDG token addresses.

<Warning>
  Testnet tokens have no value! Only use these for testing purposes.
</Warning>

| Test Network             | Token Address
|
| ------------------------ | ------------------------------------------------------------------
---------------------------------------------------------------------------- |
| Ethereum Sepolia Testnet | [0xfBb2A78CceEb415b00300925e464C3E44E6e06b0]
(https://sepolia.etherscan.io/address/0xfBb2A78CceEb415b00300925e464C3E44E6e06b0)
|
| Solana Devnet            | [4F6PM96JJxngmHnZLBh9n58RH4aTVNWvDs2nuwrT5BP7]
(https://solscan.io/token/4F6PM96JJxngmHnZLBh9n58RH4aTVNWvDs2nuwrT5BP7?cluster=devnet)     |
| Ink Sepolia Testnet      | [0xAA6870F78AA8A3427C9fF808c5De901f08B83fcd](https://explorer-
sepolia.inkonchain.com/address/0xAA6870F78AA8A3427C9fF808c5De901f08B83fcd) |
| X-Layer Testnet          | [0xF0863D7A29a55d0c4263c11bFac754312ff078DF]
(https://www.oklink.com/x-layer-testnet/address/0xf0863d7a29a55d0c4263c11bfac754312ff078df)
|

## Supply Control Contract Addresses

| Test Network             | Supply Control Address
|
| ------------------------ | ------------------------------------------------------------------
---------------------------------------------------------------------------- |
| Ethereum Sepolia Testnet | [0xE3C4e0E601792544fEFa6e1f14044fad3f4e1e6B]
(https://sepolia.etherscan.io/address/0xE3C4e0E601792544fEFa6e1f14044fad3f4e1e6B)
|
| Ink Sepolia Testnet      | [0x4326190C0648bF8CA90211f406ea02993D4d0aF0](https://explorer-
sepolia.inkonchain.com/address/0x4326190C0648bF8CA90211f406ea02993D4d0aF0) |
| X-Layer Testnet          | [0xc804F2e8Ae84F6CFa01d9D33ef107323bf0F9A59]
(https://www.oklink.com/x-layer-testnet/address/0xc804F2e8Ae84F6CFa01d9D33ef107323bf0F9A59)
|
```

USDL Overview
Source: https://docs.paxos.com/guides/stablecoin/usdl/index

Use Lift Dollar for payments, settlements and treasury while earning on-chain yield.

<img alt="USDL" />

[USDL](https://liftdollar.com) is a US dollar-backed stablecoin that distributes yield to its holders every day.
USDL reserves are held in short-term, highly liquid assets.
USDL can always be redeemed at a rate of **1 USDL = 1 US dollar**.
The token is issued by Paxos Issuance MENA Ltd. (Paxos International), which is regulated by the Financial Services Regulatory Authority ([FSRA](https://www.adgm.com/financial-services-regulatory-authority)) of the Abu Dhabi Global Market ([ADGM](https://www.adgm.com/)).

<Warning>
  Restrictions

  Lift Dollar (USDL) exists to open access to US dollars that earn yield safely, but it is not available to residents of the US and certain other countries.
  [Please refer to the Terms and Conditions here for more information](https://liftdollar.com/terms-and-conditions/).
</Warning>

> See the [Paxos Developer Guides](/) to [mint](/guides/developer/mint), [redeem](/guides/developer/redeem) and [convert](/guides/developer/convert) USDL on the Paxos platform.
Questions? [Contact the Stablecoin Team](https://support.paxos.com).

USDL Transparency

Paxos is committed to ensuring the public availability of reports on the USDL reserve assets.
To ensure transparency on USDL reserve assets, Paxos publishes monthly reports on reserve composition as well as attestations reports issued by an independent third-party accounting firm. See the [USDL transparency reports](https://liftdollar.com/transparency/).

USDL on Main Networks
Source: https://docs.paxos.com/guides/stablecoin/usdl/mainnet

Get the USDL token addresses.

<Danger>
  Tokens on mainnet blockchains have financial value.
  Never test on mainnet blockchains.
</Danger>

Network	Token Address
Ethereum Mainnet	[0xbdC7c08592Ee4aa51D06C27Ee23D5087D65aDbcD](https://etherscan.io/token/0xbdC7c08592Ee4aa51D06C27Ee23D5087D65aDbcD)
Arbitrum One Mainnet	[0x7f850b0ab1988dd17b69ac564c1e2857949e4dee](https://arbiscan.io/token/0x7f850b0ab1988dd17b69ac564c1e2857949e4dee)

USDL on Test Networks
Source: https://docs.paxos.com/guides/stablecoin/usdl/testnet

Get the USDL token addresses.

<Warning>

```
  Testnet tokens have no value! Only use these for testing purposes.
</Warning>

| Test Network                 | Token Address
|
| ---------------------------- | ------------------------------------------------------------
---------------------------------------------------------------- |
| Ethereum Sepolia Testnet     | [0xB1cedD9786e8E7d47Bbe8dc3689882cc836197Ec]
(https://sepolia.etherscan.io/token/0xB1cedD9786e8E7d47Bbe8dc3689882cc836197Ec) |
| Arbitrum One Sepolia Testnet | [0xeba9ad3D5811580aA2281Ff88cf5Af4fCF3426Eb]
(https://sepolia.arbiscan.io/token/0xeba9ad3D5811580aA2281Ff88cf5Af4fCF3426Eb)  |


# USDP Overview
Source: https://docs.paxos.com/guides/stablecoin/usdp/index

Learn more about the Fully backed, legally protected, always available Pax Dollar.

<img alt="USDP" />

Pax Dollar (USDP), issued by Paxos Trust Company, LLC (Paxos), is an open, U.S. dollar-
denominated stablecoin.
USDP reserves are held 100% in cash and cash equivalents.
Available on multiple blockchains, USDP offers near-instant global settlements, low to no-
cost transactions, and can be integrated with the most widely used exchanges, wallets, and
dApps.
USDP is always fully redeemable from Paxos on a one-to-one basis for US dollars (1 USDP  = 1
USD).

> See the [Paxos Developer Guides](/) to [mint](/guides/developer/mint), [redeem]
(/guides/developer/redeem) and [convert](/guides/developer/convert) USDP on the Paxos
platform.<br />**Questions?** [Contact the Stablecoin Team](https://support.paxos.com).

## USDP Transparency

Paxos is committed to ensuring the public availability of reports on the USDP reserve
assets.
Paxos publishes monthly reports on reserve composition as well as attestations reports
issued by an independent third-party accounting firm. See the [USDP transparency reports]
(https://paxos.com/usdp-transparency/).


# USDP on Main Networks
Source: https://docs.paxos.com/guides/stablecoin/usdp/mainnet

Get the USDP mainnet addresses.

<Danger>
  Tokens on mainnet blockchains have financial value.
  Never test on mainnet blockchains.
</Danger>

| Network             | Contract Address
|
| ------------------- | ------------------------------------------------------------------------
------------------------------------------------------------ |
| Ethereum Mainnet    | [0x8E870D67F660D95d5be530380D0eC0bd388289E1]
(https://etherscan.io/token/0x8E870D67F660D95d5be530380D0eC0bd388289E1)              |
| Solana Mainnet Beta | [HVbpJAQGNpkgBaYBZQBR1t7yFdvaYVp2vCQQfKKEN4tM]
(https://explorer.solana.com/address/HVbpJAQGNpkgBaYBZQBR1t7yFdvaYVp2vCQQfKKEN4tM) |

## Supply Control Contract Addresses

| Network          | Supply Control Address
|
```

```
| ---------------- | ------------------
```

Yes, webhook invocations to your consumer endpoint are rate-limited. When configuring a webhook via the Dashboard, you can set the rate limit from 1 to 100 requests per second. The default is 10 requests per second. For more information, see our [rate limits documentation](/guides/webhooks/retries-and-limits#rate-limits).
</Accordion>

<Accordion title="How can I send test events?">
After creating a webhook via the Dashboard, use the Test feature to send test events to your webhook endpoint. These events will be marked with `is_test=true`.

For step-by-step instructions, see [Test a Webhook](/guides/dashboard/webhooks#test-a-webhook) in the Dashboard guide.
</Accordion>
</AccordionGroup>

Overview
Source: https://docs.paxos.com/guides/webhooks/index

Webhooks provide a way for notifications to be delivered to an external web server whenever certain events occur.

<img alt="Webhooks" />

Paxos Webhooks allow you to register your own endpoints to receive asynchronous events driven by the Paxos Platform.
See the [Webhooks API Reference](/api-reference/webhooks) for the current set of supported events.

To get started, you will need to:

1. Set up a [webhook consumer](/guides/webhooks/quickstart) for Paxos webhook events, which is an HTTP POST endpoint that accepts and processes [events](/api-reference/events).
2. Test the webhook consumer locally by sending a test event to your endpoint.
3. Secure the endpoint using either API key or OAuth-based authentication.
4. Log in to your Dashboard account and navigate to the Webhooks section under the Developer tab. Configure your webhook with the relevant name, endpoint, event types, auth type (API Key or OAuth), auth config, and RPS.
5. Once the webhook has been successfully created and shows with the Active status, send a test event and ensure your consumer receives and processes the events correctly.

<Note>
* Each entity can have a maximum of **10 active webhooks**
* Webhook names must be **unique** within your account
* Webhooks cannot currently be updated. To modify a webhook, create a new one and delete the existing webhook. Deleted webhooks do not count toward your limit. We will be providing support to update Webhook directly in the future.
</Note>

For information about webhook delivery, retry policies, and rate limits, see the [Retries and Limits](/guides/webhooks/retries-and-limits) guide.

Get Started with Webhooks
Source: https://docs.paxos.com/guides/webhooks/quickstart

Create and register a webhook consumer to start receiving events.

This guide walks you through setting up a webhook consumer that can integrate with Paxos to receive events that occur on
the platform. Once completed you should have a webhook consumer, tested locally, and be ready to integrate and test in sandbox;
this guide should take less than an hour to complete.

❶ Create a Webhook Consumer

To receive Paxos events, set up your webhook consumer that receives events as an HTTP/HTTPS POST endpoint using your language and tools of choice.

<Tabs>
  <Tab title="Go">
    ```go title="paxos_webhook_consumer.go" theme={null}
    http.HandleFunc("/webhook/paxos", func(w http.ResponseWriter, req *http.Request) {
        payload, err := io.ReadAll(req.Body)
        if err != nil {
            fmt.Fprintf(os.Stderr, "error reading request body %v\n", err)
            w.WriteHeader(http.StatusServiceUnavailable)
            return
        }

        event := paxos.Event{}
        if err = json.Unmarshal(payload, &event); err != nil {
            fmt.Fprintf(os.Stderr, "error parsing webhook event: %v\n", err)
            w.WriteHeader(http.StatusBadRequest)
            return
        }

        if event.IsTest {
            fmt.Println("Received test event, ignoring...")
            w.WriteHeader(http.StatusOK)
            return
        }

        // Unmarshal the event data into an appropriate struct depending on its Type
        switch event.Type {
        case "identity.approved":
            fmt.Printf("received documents required event: %v\n, processing...", event)
            // process documents required event
        }

        w.WriteHeader(http.StatusOK)
    })
    ```
  </Tab>

  <Tab title="Java">
    ```java title="WebhookServlet.java" theme={null}
    public class WebhookServlet extends HttpServlet {

        private final ObjectMapper objectMapper = new ObjectMapper();

        @Override
        protected void doPost(HttpServletRequest req, HttpServletResponse resp) throws
ServletException, IOException {
            try {
                PaxosEvent event = objectMapper.readValue(req.getInputStream(),
PaxosEvent.class);

                if (event.isTest()) {
                    System.out.println("Received test event, ignoring...");
                    resp.setStatus(HttpServletResponse.SC_OK);
                    return;
                }

                // Unmarshal the event data into an appropriate struct depending on its Type
                switch (event.type()) {
                    case "identity.documents_required":
                        System.out.printf("received documents required event: %s,
processing...%n", event);
                        // process documents required event
    ```

```
                        break;
                    default:
                        System.out.printf("received unknown event type: %s%n",
event.type());
                        break;
                }

                resp.setStatus(HttpServletResponse.SC_OK);
            } catch (IOException e) {
                System.err.printf("error reading request body: %s%n", e.getMessage());
                resp.setStatus(HttpServletResponse.SC_SERVICE_UNAVAILABLE);
            } catch (Exception e) {
                System.err.printf("error parsing webhook event: %s%n", e.getMessage());
                resp.setStatus(HttpServletResponse.SC_BAD_REQUEST);
            }
        }
    }
```

</Tab>

<Tab title="Python">

```python title="paxos_webhook_consumer.py" theme={null}
# using django
@csrf_exempt
def paxos_webhook(request):
    if request.method != 'POST':
        return HttpResponse(status=405)

    try:
        payload = json.loads(request.body)

        if payload.get('is_test'):
            print("Received test event, ignoring...")
            return HttpResponse(status=200)

        event_type = payload.get('type')

        # Unmarshal the event data into an appropriate struct depending on its Type
        if event_type == 'identity.documents_required':
            print(f"received documents required event: {payload}, processing...")
            # process documents required event
        else:
            print(f"received unknown event type: {event_type}")

        return HttpResponse(status=200)
    except json.JSONDecodeError as e:
        print(f"error parsing webhook event: {e}")
        return HttpResponse(status=400)
    except Exception as e:
        print(f"error reading request body: {e}")
        return HttpResponse(status=503)

```

</Tab>
</Tabs>

<Info>
We are currently working on providing client libraries for the Paxos event object. In the meantime, please directly use the definition below:

<Tabs>
<Tab title="Go">

```go title="paxos/event.go" theme={null}
package paxos
```

```
      type Event struct {
          ID     string    `json:"id"`
          Type   string    `json:"type"`
          Source string    `json:"source"`
          Time   time.Time `json:"time"`
          Object string    `json:"object"`
          IsTest bool      `json:"is_test"`
      }
      ```
    </Tab>

    <Tab title="Java">
      ```java title="com/paxos/PaxosEvent.java" theme={null}
      package com.paxos;

      import java.time.LocalDateTime;

      public record PaxosEvent(
          String id,
          String type,
          String source,
          LocalDateTime time,
          String object
          Boolean isTest
      ) {}
      ```
    </Tab>
  </Tabs>
</Info>

❷ Register the Webhook via Dashboard

Log in to your [Dashboard](https://dashboard.paxos.com/login) account and navigate to the Webhooks section under the Developer tab. Configure your webhook with:

* **Endpoint URL**: Your webhook consumer endpoint URL

* **Auth Type**: Select your authentication method (API Key or OAuth)

* **Authentication**: Configure your selected authentication method
  * **API Key**: Provide the API Key Header name and API Key value that Paxos will include when calling your endpoint
  * **OAuth**: Provide the OAuth endpoint URL (client_url), Client ID, and Client Secret

* **Event Types**: Select which [event types](/api-reference/events) you would like to receive and process

* **Rate Limit**: Set the rate limit (1-100 requests per second, default is 10 RPS)

<Info>
  Paxos does not currently support consumer-side signature-verification on webhook event messages. To keep things secure,
  Paxos does not include the full event object in the webhook payload and requires you to make an authenticated
  request to [Get Event](/api-reference/endpoints/events/get-event) to fetch the full event object.

  Paxos is working on adding signature verification support for webhook messages. This documentation will be updated once this feature is available.
</Info>

❸ Test the Webhook

Once your webhook is successfully created and shows an Active status in Dashboard, use the Test feature to send test events to your endpoint. For step-by-step instructions, see [Test
```
```

a Webhook](/guides/dashboard/webhooks#test-a-webhook). Verify that your consumer receives and processes the events correctly.

Webhook Payload Format

Each webhook event sent to your endpoint contains the following fields:

Parameter	Description	Example
`id`	The unique identifier of the event. This `id` can be used to fetch the full details of the event from the [Events API](/api-reference/events).	`bd019f1c-89a7-4372-9d21-eaad9280dc41`
`type`	The type of the event. More details about available event types can be found in the [Webhooks API Reference](/api-reference/webhooks).	`identity.approved`
`source`	The source of the event. This will always be `com.paxos`.	`com.paxos`
`time`	The time the event was created. Formatted according to RFC3339 date-time.	`2025-01-01T14:30:02Z`
`object`	The object type of the event. This will always be `event`.	`event`
`is_test`	Whether the event was a test event. Test events are only sent via the Test feature in Dashboard.	`false`

Retries and Limits
Source: https://docs.paxos.com/guides/webhooks/retries-and-limits

Learn about webhook delivery retries, retry policies, and rate limits for Paxos webhooks.

Retry Policy

If your webhook consumer endpoint fails to accept a delivery or returns a retriable error status (anything other than a 2xx response), Paxos will automatically attempt to retry the webhook delivery.

Retry Schedule

We use an exponential backoff policy with jitter (randomization to avoid retry storms) with the following schedule:

* Initial retry delay: \~5 seconds after initial failure
* Subsequent retries: Increasing intervals with exponential backoff
* Maximum retry duration: 24 hours from the time the event was first invoked

Paxos will continue retry attempts for up to **24 hours** from the initial attempt, unless delivery succeeds. After this period, no additional retry attempts will be made.

Handling Failed Deliveries

After the 24-hour retry window has elapsed, undelivered events will not be automatically retried. To recover these undelivered events, you can:

1. Use the [List Events](/api-reference/endpoints/events/list-events) API to query for events that may have failed delivery
2. Use the event IDs to fetch the full event details via the [Events API](/api-reference/events)
3. Process these events through your regular webhook handling logic

Rate Limits

To ensure optimal performance and stability, Paxos implements rate limits on webhook deliveries.

When configuring a webhook via the Dashboard, you can set the rate limit from 1 to 100 requests per second. The default is 10 requests per second.

Best Practices

For optimal webhook processing, we recommend:

1. **Respond quickly**: Your webhook endpoint should acknowledge receipt with a 2xx status code as quickly as possible (ideally \< 500ms)
2. **Process asynchronously**: Acknowledge the webhook immediately, then process the event asynchronously in your application
3. **Implement idempotency**: Design your webhook handlers to be idempotent in case the same event is delivered multiple times
4. **Monitor delivery failures**: Implement monitoring for webhook delivery failures to detect issues early
5. **Implement backup polling**: Establish a periodic job that polls the [Events API](/api-reference/events) as a fallback mechanism for missed webhook events
6. **Ignore test events**: You may wish to test the functionality of your webhook consumer endpoint by sending test events. To ignore test events, you can filter on the `is_test=false` field in your webhook consumer.

Build with Paxos
Source: https://docs.paxos.com/welcome

Learn how to get started with the Paxos API and Platform.

```
<div>
  <h1>
    <span>Build with</span><span>Paxos</span>
  </h1>

  <CardGroup>
    <Card title="Developer Guides" icon="code" href="/guides/developer/account">
      Build and integrate with our APIs. Get started with authentication, onboarding, and
platform features.
    </Card>

    <Card title="Dashboard Guides" icon="gauge-high" href="/guides/dashboard">
      Learn how to use the Paxos Dashboard to manage your platform and users.
    </Card>

    <Card title="API Reference" icon="brackets-curly" href="/api-reference/introduction">
      Integrate and scale using our API and SDKs.
    </Card>

    <Card title="Release Notes" icon="star" href="/changelog">
      Learn about changes and new features in the Paxos API and Platform.
    </Card>

    <Card title="Stablecoins" icon="coin" href="/guides/stablecoin">
      Use Paxos-issued stablecoins for payments, money movement and more.
    </Card>

    <Card title="AI-Assisted Development" icon="robot" href="/guides/developer/ai-assisted-
development">
      Get contextual help with Paxos APIs using AI assistance built into our documentation.
    </Card>
  </CardGroup>
</div>
```