$$\phi \in [0, 2\pi[$$

$$\partial^2 X/(\partial\theta\partial\phi\sin\theta)$$





$$C_{12}^{XY}(\ell) = \frac{1}{2\ell+1} \sum_{m=-\ell}^{\ell} a_{1,\ell m}^{X} a_{2,\ell m}^{Y*},$$

$$C_{\{12\}}^{\{XY\}}(\ell) \equiv \frac{C_{12}^{XY}(\ell) + C_{12}^{YX}(\ell)}{2} = \frac{C_{12}^{XY}(\ell) + C_{21}^{XY}(\ell)}{2}$$

$$(C_\ell^{TE} + C_\ell^{ET})/2$$

$$(C_\ell^{TB} + C_\ell^{BT})/2$$

$$(C_\ell^{EB} + C_\ell^{BE})/2$$

$$a_{\ell m}^E$$

$$P_{\ell m}(\theta)$$

$$z = \sin(\text{latitude}) = \cos(\theta).$$

 $sa_{\ell m}$

$$(\partial T/\partial \theta, \partial T/\partial \phi/\sin \theta)$$

$$(\partial T/\partial \theta, \partial Q/\partial \theta, \partial U/\partial \theta;$$

 $\partial T/\partial \phi/\sin \theta, \ldots)$

$$(\partial^2 T/\partial \theta^2, \partial^2 T/\partial \theta \partial \phi/\sin \theta,$$

 $\partial^2 T/\partial \phi^2/\sin^2 \theta$

$$(\partial^2 T/\partial \theta^2, \partial^2 Q/\partial \theta^2, \partial^2 Q/\partial \theta^2, \ldots)$$

Vm.

$$_{s}S(p) = \sum_{\ell m} {}_{s}a_{\ell m} \ _{s}Y_{\ell m}(p)$$

$$\ell \ge |m|, \ell \ge |s|$$

$$_{s}Y_{\ell m}^{*} = (-1)^{s+m} {}_{-s}Y_{\ell-m}$$

$$_{s}a_{\ell m}^{*} = (-1)^{s+m} -_{s}a_{\ell-m}$$

$$_{s|}a_{\ell m}^{+}$$

$$-(|s|a_{\ell m} + (-1)^s - |s|a_{\ell m})/2$$

$$-({}_{|s|}a_{\ell m} - (-1)^s {}_{-|s|}a_{\ell m})/(2i)$$

$$_{|s|}a_{\ell-m}^+$$

$$(-1)^m_{|s|}a_{\ell m}^{+*},$$

$$_{|s|}a_{\ell-m}^-$$

$$(-1)^m_{|s|}a_{\ell m}^{-*}.$$

$$_0a_{\ell m}^+ = -a_{\ell m}^T$$

$$_0a_{\ell m}^-=0$$

$$_{0}S^{+}=T$$

$$_{0}S^{-}=0.$$

$$_{s|}a_{\ell m}^{+}$$

$$index = \ell^2 + \ell + m + 1$$

$$a_{\ell m}^E$$

$$a_{\ell m} \longrightarrow a_{\ell m} b(\ell)$$

 $\ell_{\rm max} = m_{\rm max} =$ 128

```
x = \sin \theta \cos \phi
```

$$y = \sin \theta \sin \phi$$

$$z = \cos \theta$$

$$z = \sin(\text{latitude}) = \cos(\theta)$$

Will print out: Number of OpenMP threads in use: Number of CPUs available: 2 on a bi-pro (or dual core) computer

$$m = \sum_{i} x_i / n$$

$$a = \sum_{i} |x_i - m|/n$$

 $\sigma^2 =$

 $-\sum (x_i - m)^2/(n - 1)$

1)

$$s = \sum (x_i - m)^3 / (n\sigma^3)$$

$$k = \sum (x_i - m)^4 / (n\sigma^4) - 3$$

Will return: bbbbbbbb C 10 3

$convert_nest2ring$

ring2nestconvert

 ψ, θ, φ

 $4N_{\rm side}$



 $^{2^{31} - 1 \}simeq 2.1 \ 10^9$

$$\pi \simeq 3.14159\dots$$

$$\gamma \simeq 0.577 \dots$$

$$\mathbf{a}^{(n)} = \mathbf{a}^{(n-1)} + \mathbf{A} \cdot \left(\mathbf{w} \cdot \mathbf{m} - \mathbf{S} \cdot \mathbf{a}^{(n-1)} \right),$$

$$\left(\mathbf{w}.\mathbf{m} - \mathbf{S}.\mathbf{a}^{(n-1)}\right)$$

$$\sigma \equiv \sqrt{\sum_{p=1}^{N} \frac{(x(p) - \bar{x})^2}{N - 1}}$$

$$\bar{x} \equiv \sum_{p=1}^{N} \frac{x(p)}{N}$$

$$\{1,\ldots,2^{28}\}$$

$$N_{\rm side} = \sqrt{N_{\rm pix}/12}$$

$$\{1, \dots, 2^{28} = 268435456\}$$

$$N_w = \frac{(N_{\text{side}} + 1)(3N_{\text{side}} + 1)}{4} \simeq \frac{N_{\text{pix}}}{16}$$

$$N_{\text{template}} = \frac{1 + N_{\text{side}}(N_{\text{side}} + 6)}{4}$$

$$w_{\rm pix}(\ell)$$

$$a_{\ell m}^{(\mathrm{pix})}$$

$$a_{\ell m}^{(\text{pix})} = a_{\ell m} w_{\text{pix}}(\ell)$$

 $\sim 4N_{\rm side}$ ℓ_{max}

 $Y_{\ell m}(\theta, \phi) = \lambda_{\ell m}(\theta)e^{im\phi}$

$$\lambda_{00}(\theta_1)$$

$$\lambda_{10}(\theta_1)$$

$$\lambda_{20}(\theta_1)$$

$$\lambda_{11}(\theta_1)$$

$$\lambda_{21}(\theta_1)$$

$$\lambda_{00}(\theta_2)$$

$$\sum_{j=0}^{d^2-1} A_{ij} f_j = b_i$$

$$b_i \equiv \sum_{p \in \mathcal{P}} s_i(p) w(p) m(p),$$

$$A_{ij} \equiv \sum_{p \in \mathcal{P}} s_i(p) w(p) s_j(p),$$

$$s_1(p) = x, \ s_2(p) = y, \ s_3(p) = z$$

$$m'(p) = m(p) - \sum_{i=0}^{d^2-1} f_i s_i(p).$$

-max

 $\ell_{\rm max} =$ $m_{\rm max} = 64$

$$\psi = \pi/3, \theta = 0.5, \varphi = 0$$

$$z = \cos(\theta) \ge 2/3,$$



 $0 < \phi \le \pi/2$,

 $2/3 > z \ge 0$,

$$\phi = 0$$
, or $\phi = \frac{\pi}{4N_{\text{side}}}$.

 $2/3 > z \ge 0$,

$$\phi = 0$$
, or $\phi = \frac{\pi}{4N_{\text{side}}}$.

$$\mathbf{v}_3 = \mathbf{v}_1 \times \mathbf{v}_2$$

$$C_{\ell}^{T \times E}$$