

Air University, Islamabad

Software Requirement Specification & Software Design Specification Document
(SRS & SDS DOCUMENT)

For

Muhaffiz: Offline-First Safety for Women and Children

Version 1.0

By

Muhammad Shamoil 232025

Ali Raza 232047

Supervisor

Kanwal Batool

Bachelor of Science in Software Engineering (2023-2027)

Revision History

Name	Date	Reason for Changes	Version

Application Evaluation and Review History

Comments by Committee	Action Taken

Approval

Role	Name	Signature	Date
Supervisor	Kanwal Batool		
FYP Head	Dr. Farhad		

Table of Contents

Chapter 1: Introduction....1
1.1 Purpose....1
1.2 Scope....2
1.3 Modules....3
1.4 Definitions, Acronyms and Abbreviations....5
1.5 Document Overview....7
1.6 Chapter Summary....8
Chapter 2: Overall Description and Requirements Elicitation....9
2.1 Product Perspective....9
2.2 User Classes and Characteristics....11
2.3 Operating Environment....11
2.4 Design and Implementation Constraints, Assumptions and Dependencies....13
2.5 Requirement Identifying Techniques....15
2.6 Chapter Summary....18
Chapter 3: Software Requirements Specification....19
3.1 Functional Requirement Catalogue....19
3.2 Functional Requirement Specification....21
3.2.1 MOD-01 SOS Alert System....22
3.2.2 MOD-02 Automatic Danger Detection Engine....24
3.2.3 MOD-03 Voice Activation and Safe-Phrase Engine....26
3.2.4 MOD-04 Family Circle Management....28
3.2.5 MOD-05 Location Sharing and Privacy Controls....30
3.2.6 MOD-06 Decoy Mode....32
3.2.7 MOD-07 Danger Heatmap....33
3.2.8 MOD-08 Near Help....35
3.2.9 MOD-09 Content Library Management....36
3.2.10 MOD-10 Semantic Search Engine....38
3.2.11 MOD-11 Emergency Services Directory....39
3.2.12 MOD-12 Tiered Delivery System....41
3.2.13 MOD-13 Offline Data Caching....42
3.2.14 MOD-14 Authentication and Account Management....43
3.2.15 MOD-15 Consent and Privacy Controls....44
3.2.16 MOD-16 Admin Dashboard....45
3.2.17 MOD-17 Missing-Child Report....47
3.2.18 MOD-18 Evidence Recording on SOS....50
3.2.19 MOD-19 Escalation to Authorities....52
3.2.20 MOD-20 Safe-Location Navigation....54
3.2.21 MOD-21 App Disguise....55
3.2.22 Use case Specification....56

3.3 Business Rules....63
3.4 Non-Functional Requirements....66
3.5 External Interface Requirements....69
3.5.1 User Interface Requirements....69
3.5.2 Software Interfaces....70
3.5.3 Hardware Interfaces....71
3.5.4 Communications Interfaces....71
3.6 Chapter Summary....73
Chapter 4: System Design....74
4.1 Design Methodology and Software Process Model....74
4.2 Architectural Design....75
4.3 Design Models....78
4.3.1 Class diagrams....78
4.3.2 System-sequence and detailed-sequence diagrams....82
4.3.3 Activity diagrams....93
4.3.4 State diagrams....103
4.3.5 Component diagram and event-response table....112
4.4 Data Design....113
4.5 Human Interface Design....117
4.6 Security, Error Handling and Logging Design....121
4.7 Risk Analysis and Sprint Plan....122
4.8 Chapter Summary....124
Chapter 5: Implementation and Deployment....125
5.1 Algorithms....125
5.2 External APIs/SDKs....129
5.3 REST API Specification....130
5.4 Implemented User Interface....131
5.5 Deployment....136
5.6 Chapter Summary....137
Chapter 6: Testing, Evaluation and Conclusion....138
6.1 Unit Testing....138
6.2 Functional Testing....139
6.3 Business Rules Testing....141
6.4 Integration Testing....143
6.5 Non-Functional Testing....144
6.6 Test Summary and Defect Log....146
6.7 Requirements Traceability Matrix....147
6.8 Conclusion, Limitations and Future Enhancements....155
6.9 Chapter Summary....156
References....157
Appendix A: Use Case List....158

Appendix B: Detailed Use Case Specifications.....160
Appendix C: TBD List.....171
Appendix D: Sample Test Data.....172
Document Status.....174

List of Figures

Figure 1: Context diagram of Muhaffiz....10
Figure 2: Use-case diagram: emergency alerting....57
Figure 3: Use-case diagram: family network and disguise....57
Figure 4: Use-case diagram: community, library and directory....58
Figure 5: Use-case diagram: account, consent and administration....58
Figure 6: Architecture of Muhaffiz (box-and-line view)....75
Figure 7: Deployment view of Muhaffiz....77
Figure 8: Class diagram: SOS core, delivery, evidence and escalation....79
Figure 9: Class diagram: detection, voice and consent....80
Figure 10: Class diagram: family and community....81
Figure 11: Class diagram: knowledge, identity and administration....82
Figure 12: System-sequence diagram: manual SOS (UC-01)....83
Figure 13: Detailed sequence: SOS dispatch....83
Figure 14: Detailed sequence: automatic distress detection (UC-02)....84
Figure 15: Detailed sequence: voice-triggered SOS (UC-03)....85
Figure 16: Detailed sequence: stop sharing by safe phrase (UC-09)....86
Figure 17: Detailed sequence: escalation to authorities (UC-25)....87
Figure 18: Detailed sequence: offline queue and retry....88
Figure 19: Detailed sequence: circle invitation (UC-07)....89
Figure 20: Detailed sequence: nearby help (UC-15)....89
Figure 21: Detailed sequence: missing-child report (UC-23)....90
Figure 22: Detailed sequence: semantic library search (UC-17)....91
Figure 23: Detailed sequence: helper verification (UC-14)....91
Figure 24: Detailed sequence: incident report and heatmap (UC-12, UC-13)....92
Figure 25: Detailed sequence: sign-in (UC-19)....93
Figure 26: Activity diagram: SOS pipeline....95
Figure 27: Activity diagram: tiered delivery and retry....97
Figure 28: Activity diagram: phrase handling in context....97
Figure 29: Activity diagram: semantic search with fallback....99
Figure 30: Activity diagram with swimlanes: onboarding and consent....99
Figure 31: Activity diagram with swimlanes: missing-child report....100
Figure 32: Activity diagram with swimlanes: incident report and heatmap....101
Figure 33: Activity diagram with swimlanes: helper verification....102
Figure 34: Activity diagram with swimlanes: nearby help....103
Figure 35: State diagram: SOS event....104
Figure 36: State diagram: confirmation countdown....105
Figure 37: State diagram: circle member and sharing....107
Figure 38: State diagram: circle invitation....107
Figure 39: State diagram: missing-child report....108

Figure 40: State diagram: Verified Helper application.....109
Figure 41: State diagram: connectivity tier.....110
Figure 42: State diagram: evidence recording.....112
Figure 43: Component diagram.....112
Figure 44: Entity-relationship diagram: server data (Cloud Firestore).....115
Figure 45: Entity-relationship diagram: device data.....116
Figure 46: Navigation flow of the application.....117
Figure 47: Key screens: Home, countdown and SOS active.....118
Figure 48: Key screens: family map, danger map and library search.....118
Figure 49: Key screens: decoy, stop sharing and trustees.....119
Figure 50: Mobile application: settings, privacy summary and consent.....132
Figure 51: Mobile application: sign-in, phrase enrolment and incident report.....132
Figure 52: Mobile application: nearby help, helper registration and missing-child report....133
Figure 53: Mobile application: evidence, directory and safe-location guidance.....133
Figure 54: Mobile application: escalation warning, escalation settings and app disguise.....134
Figure 55: Admin website: overview.....135
Figure 56: Admin website: moderation queue.....135

List of Tables

Table 1: Scope of the Muhaffiz project....2
Table 2: Modules of Muhaffiz....3
Table 3: Definitions, acronyms and abbreviations....5
Table 4: User classes and external actors....11
Table 5: Operating environment....12
Table 6: Assumptions and dependencies....14
Table 7: Survey: current practice and barriers (first 31 responses analysed)....15
Table 8: Survey: respondents likely or very likely to use each feature (first 31 responses analysed)....16
Table 9: Module priorities....17
Table 10: Requirement identification techniques....18
Table 11: Functional requirement catalogue....19
Table 12: Specification of FR-01.01: Manual SOS Trigger....22
Table 13: Specification of FR-01.02: Multi-Channel Dispatch....22
Table 14: Specification of FR-01.03: Loud Alarm....23
Table 15: Specification of FR-01.04: Silent Mode....23
Table 16: Specification of FR-01.05: Trustee Management....23
Table 17: Specification of FR-01.06: SOS Event Log....24
Table 18: Specification of FR-02.01: Ambient Monitoring Service....24
Table 19: Specification of FR-02.02: Distress Sound Classification....25
Table 20: Specification of FR-02.03: Motion-Signal Fusion....25
Table 21: Specification of FR-02.04: Confirmation Countdown....26
Table 22: Specification of FR-02.05: On-Device Processing Guarantee....26
Table 23: Specification of FR-03.01: Safe-Phrase Enrolment....26
Table 24: Specification of FR-03.02: Duress-Phrase Enrolment....27
Table 25: Specification of FR-03.03: Offline Keyword Spotting....27
Table 26: Specification of FR-03.04: Voice-Triggered SOS....28
Table 27: Specification of FR-03.05: Shared Duress-Confirmation Hook....28
Table 28: Specification of FR-04.01: Circle Creation and Bilateral Invitation....28
Table 29: Specification of FR-04.02: Circle Membership List....29
Table 30: Specification of FR-04.03: Leave a Circle....29
Table 31: Specification of FR-05.01: Movement-Based Location Updates....30
Table 32: Specification of FR-05.02: Opt-Out by Safe Phrase....30
Table 33: Specification of FR-05.03: Private Opt-Out Confirmation....30
Table 34: Specification of FR-05.04: Last-Known Location Display....31
Table 35: Specification of FR-05.05: Real-Time Sharing Status....31
Table 36: Specification of FR-06.01: Disguised Interface....32
Table 37: Specification of FR-06.02: Hidden Re-entry Gesture....32
Table 38: Specification of FR-06.03: Background Pass-Through....32
Table 39: Specification of FR-07.01: Incident Report Form....33

Table 40: Specification of FR-07.02: Geohash Grid Aggregation....33
Table 41: Specification of FR-07.03: Recency Weighting....34
Table 42: Specification of FR-07.04: Heatmap Overlay....34
Table 43: Specification of FR-07.05: Rate Limits and Abuse Checks....34
Table 44: Specification of FR-08.01: Verified-Helper Registration....35
Table 45: Specification of FR-08.02: Help Request Broadcast....35
Table 46: Specification of FR-08.03: Accept or Decline Screen....36
Table 47: Specification of FR-08.04: Offline State....36
Table 48: Specification of FR-09.01: Curated Content....36
Table 49: Specification of FR-09.02: Offline Bundling....37
Table 50: Specification of FR-09.03: Browsing, Filters and Bookmarks....37
Table 51: Specification of FR-10.01: Precomputed Content Embeddings....38
Table 52: Specification of FR-10.02: On-Device Query Embedding....38
Table 53: Specification of FR-10.03: Cosine-Similarity Ranking....38
Table 54: Specification of FR-10.04: Keyword-Search Fallback....39
Table 55: Specification of FR-10.05: Ranked Result Cards....39
Table 56: Specification of FR-11.01: Localized Directory....39
Table 57: Specification of FR-11.02: One-Tap Call....40
Table 58: Specification of FR-11.03: Nearest Facilities First....40
Table 59: Specification of FR-12.01: Connectivity Tier Detection....41
Table 60: Specification of FR-12.02: SMS Delivery at Tier 1....41
Table 61: Specification of FR-12.03: Queue and Retry....41
Table 62: Specification of FR-13.01: Last-Known Location Cache....42
Table 63: Specification of FR-13.02: On-Device Database....42
Table 64: Specification of FR-14.01: Phone-Number Sign-Up and Login....43
Table 65: Specification of FR-14.02: Session Handling....43
Table 66: Specification of FR-14.03: Profile and Settings....43
Table 67: Specification of FR-14.04: Account Recovery....44
Table 68: Specification of FR-15.01: Onboarding Consent....44
Table 69: Specification of FR-15.02: Permission and Feature Toggles....45
Table 70: Specification of FR-15.03: Privacy Summary....45
Table 71: Specification of FR-16.01: User Overview....45
Table 72: Specification of FR-16.02: Moderation Queue....46
Table 73: Specification of FR-16.03: Helper Review Queue....46
Table 74: Specification of FR-16.04: Health Monitoring....47
Table 75: Specification of FR-16.05: Administrator Authentication....47
Table 76: Specification of FR-17.01: Missing-Child Report Form....47
Table 77: Specification of FR-17.02: Alert to Contacts and Nearby Helpers....48
Table 78: Specification of FR-17.03: Report Status Handling....48
Table 79: Specification of FR-17.04: Hand-Off to Official Channels....49
Table 80: Specification of FR-17.05: Moderation and Abuse Prevention....49

Table 81: Specification of FR-17.06: Child-Data Privacy....49
Table 82: Specification of FR-18.01: Automatic Recording on SOS....50
Table 83: Specification of FR-18.02: Encrypted On-Device Storage....50
Table 84: Specification of FR-18.03: Evidence List....51
Table 85: Specification of FR-18.04: Evidence Controls....51
Table 86: Specification of FR-18.05: Consent Disclosure....51
Table 87: Specification of FR-19.01: Response Tracking....52
Table 88: Specification of FR-19.02: No-Response Timer....52
Table 89: Specification of FR-19.03: Warning Countdown....52
Table 90: Specification of FR-19.04: Authority Channel Settings....53
Table 91: Specification of FR-19.05: Escalation Message....53
Table 92: Specification of FR-19.06: Escalation Log....54
Table 93: Specification of FR-20.01: Nearest Safe Location....54
Table 94: Specification of FR-20.02: One-Tap Directions Online....54
Table 95: Specification of FR-20.03: Offline Guidance....55
Table 96: Specification of FR-21.01: Disguise Options....55
Table 97: Specification of FR-21.02: Apply and Restore....56
Table 98: Specification of FR-21.03: Unchanged Functions....56
Table 99: Use case list....58
Table 100: Use case specification UC-01: Trigger Manual SOS....59
Table 101: Use case specification UC-02: Handle Automatic Distress Alert....60
Table 102: Use case specification UC-03: Trigger SOS by Voice Phrase....61
Table 103: Use case specification UC-09: Stop Sharing by Safe Phrase....61
Table 104: Use case specification UC-25: Escalate to Authorities....62
Table 105: Use case specification UC-23: File Missing-Child Report....62
Table 106: Business rules....63
Table 107: Non-functional requirements: Reliability....66
Table 108: Non-functional requirements: Performance....67
Table 109: Non-functional requirements: Security....67
Table 110: Non-functional requirements: Privacy....68
Table 111: Non-functional requirements: Usability....68
Table 112: Non-functional requirements: Maintainability, Portability and Other Qualities…68
Table 113: Summary of external interfaces....72
Table 114: Decomposition of the system into packages....76
Table 115: Architecture decision records....77
Table 116: Event-response table....112
Table 117: Data dictionary....114
Table 118: Indexes and constraints....116
Table 119: Screens of the application and the admin website....120
Table 120: Security, error handling and logging design....121
Table 121: Risk analysis....123

Table 122: Milestone plan....124
Table 123: Algorithm parameters and default values....125
Table 124: Algorithm: sound-level gate (A1)....126
Table 125: Algorithm: distress decision with fusion (A2)....126
Table 126: Algorithm: trigger arbitration and SOS pipeline (A3)....126
Table 127: Algorithm: tiered dispatch and queue retry (A4)....127
Table 128: Algorithm: phrase handling in context (A5)....127
Table 129: Algorithm: movement-based location publication (A6)....128
Table 130: Algorithm: heatmap cell score (A7)....128
Table 131: Algorithm: semantic search with keyword fallback (A8)....128
Table 132: Algorithm: escalation timer (A9)....129
Table 133: Algorithm: nearest safe location (A10)....129
Table 134: External APIs and SDKs....129
Table 135: Project backend interfaces....131
Table 136: Deployment environments....136
Table 137: Unit test cases....138
Table 138: Functional test cases....140
Table 139: Business rule test cases....142
Table 140: Integration test cases....143
Table 141: Non-functional test cases....144
Table 142: Test summary....146
Table 143: Defect log....147
Table 144: Requirements traceability matrix....147
Table 145: Use case list with descriptions....158
Table 146: Use case specification UC-04: Manage Trustees....160
Table 147: Use case specification UC-05: View SOS Event Log....160
Table 148: Use case specification UC-06: Enrol Safe and Duress Phrases....161
Table 149: Use case specification UC-07: Create Circle and Invite Member....161
Table 150: Use case specification UC-08: Share Location and View Members....162
Table 151: Use case specification UC-10: Leave Family Circle....162
Table 152: Use case specification UC-11: Use Decoy Mode....163
Table 153: Use case specification UC-12: Submit Incident Report....163
Table 154: Use case specification UC-13: View Danger Heatmap....164
Table 155: Use case specification UC-14: Register as Verified Helper....164
Table 156: Use case specification UC-15: Request and Respond to Nearby Help....164
Table 157: Use case specification UC-16: Browse Library....165
Table 158: Use case specification UC-17: Search Library....165
Table 159: Use case specification UC-18: Call Emergency Service....166
Table 160: Use case specification UC-19: Sign Up and Log In....166
Table 161: Use case specification UC-20: Manage Consent and Privacy Settings....167
Table 162: Use case specification UC-21: Moderate Reports and Review Helpers....167

Table 163: Use case specification UC-22: Monitor System Health.....168
Table 164: Use case specification UC-24: Manage Evidence Recordings.....168
Table 165: Use case specification UC-26: Navigate to Nearest Safe Location.....169
Table 166: Use case specification UC-27: Change App Disguise.....169
Table 167: Use case specification UC-28: Recover Account.....170
Table 168: Use case specification UC-29: Acknowledge SOS Alert.....170
Table 169: Items to be determined.....171
Table 170: Sample trustees.....172
Table 171: Sample SOS message.....172
Table 172: Sample incident reports.....172
Table 173: Sample library queries.....172
Table 174: Sample audio test set (labelled clips).....172
Table 175: Sample directory entries.....172

Chapter 1: Introduction

Chapter Overview. This chapter introduces the Muhaffiz software product and the people who will read and use this document. It states the purpose of the document and its readers (Section 1.1), the scope and boundaries of the project (Section 1.2), the twenty-one modules of the system (Section 1.3), the terminology used throughout (Section 1.4) and the organization of the remaining chapters and appendices (Section 1.5).

1.1 Purpose

This document is the combined Software Requirements Specification (SRS) and Software Design Specification (SDS), version 1.0, for **Muhaffiz: Offline-First Safety for Women and Children**. Muhaffiz (from the Urdu word for "guardian") is an Android application, supported by a cloud backend and a separate web-based administration site, that helps a person call for help, be detected as being in distress, share their location with family under privacy safeguards, and reach safety information and emergency contacts, including when no data connection is available.

The document defines what the system shall do (the requirements) and how it will be structured to do it (the design). Every requirement has a unique identifier that is kept unchanged in the design, implementation and test documentation, so that each statement can be traced from its source to its verification. The document is written to be read by the following groups.

- **Supervisor and evaluation committee:** to judge whether the scope is complete, coherent and achievable within a Final Year Project.
- **Developers:** to implement the system without having to guess intended behaviour.
- **Testers:** to derive test cases from the requirements, business rules and acceptance criteria.
- **Project managers:** to plan milestones, assign work and manage risk.
- **Users and stakeholders:** to confirm that the user-visible behaviour matches their needs and privacy expectations.
- **Documentation writers:** to prepare user and administrator guidance consistent with the specified behaviour.

1.2 Scope

Muhaffiz is an Android application for women and children, with a supporting cloud backend and an administration website. It is designed around three principles: an emergency alert must be able to leave the phone without a data connection; sensitive signals, namely microphone audio and voice phrases, are processed only on the phone; and every action that someone might be forced to perform is protected against coercion. The application provides a manual, automatic and voice-triggered SOS; family location sharing with consent rules that the tracked person controls; a community danger map; verified nearby helpers; an offline safety library with on-device semantic search; a directory of emergency services; evidence recording and escalation after an SOS; and a missing-child report. Table 1 states what is committed for this project, what is excluded, and the expected benefits, so that committed work can be distinguished from possible future work.

Table 1: Scope of the Muhaffiz project

Scope Category	Description
In Scope	• An Android application, built with Flutter, that implements the twenty-one modules MOD-01 to MOD-21 listed in Section 1.3. • A Firebase backend for authentication, data synchronisation, push messaging and storage, and server-side functions for channels that cannot run on the phone. • A separate administration website on its own domain (muhaffiz.me) that implements MOD-16. • On-device machine-learning components that use existing pre-trained models: distress-sound classification, keyword spotting and sentence embedding. • SOS delivery by WhatsApp, in-app push, email and SMS, with SMS usable without a data connection. • Verification of the system as described in Chapter 6.
Out of Scope	• Versions of the user application for iOS, desktop or the web. • Training any machine-learning model from scratch, and any GPU infrastructure. • Uploading, storing or transmitting raw audio from the detection and voice engines, and any video recording. • Direct system-to-system integration with police, emergency-service dispatch or government missing-child systems. Muhaffiz hands off by SMS, call or share to numbers and channels that are configured. • Any guarantee that an authority receives, accepts or acts on a message. • User-interface languages other than English. • Wearable devices and dedicated panic-button hardware. • Payments, advertising and any other monetisation. • The content of the promotional website (muhaffiz.live).
Benefits	• **For users:** an alert path that does not depend on a data connection (SMS still needs cellular coverage); hands-free and discreet ways to trigger help; microphone audio kept on the phone; control over who can see their location and a private way to stop sharing; safety information and emergency contacts available offline; audio evidence kept on the phone for later use. • **For communities:** a shared picture of areas reported as unsafe and a way to reach verified people nearby. • **For the project:** a demonstration of on-device machine learning, offline-first delivery and privacy-by-design combined in one system, with behaviour that can be measured and tested.

Where demonstration data or simulated users are needed to evaluate a module, for example for the heatmap or Near Help, they shall be identified as simulated in Chapter 6 and shall not be presented as real usage.

1.3 Modules

The functionality of Muhaffiz is divided into twenty-one modules. Each module has a persistent identifier of the form MOD-nn, which is used in the requirement catalogue, the design models and the test cases. Table 2 lists the modules with their primary actors; the actors are described in Section 2.2.

Table 2: Modules of Muhaffiz

Module ID	Module Name	Description	Primary Actor or User
MOD-01	SOS Alert System	Manual SOS trigger on the home screen and as a lock-screen quick action; simultaneous dispatch of live location and a preset message by WhatsApp, in-app push, email and SMS; loud alarm and silent mode; trustee management; SOS event log.	Primary User; Trustee (recipient)
MOD-02	Automatic Danger Detection Engine	Low-power background monitoring that stays dormant until a sudden loud sound; on-device classification of distress sounds; fusion with motion sensors; 20-second vibration countdown with one-tap cancel before the SOS fires. No audio leaves the phone.	Primary User
MOD-03	Voice Activation and Safe-Phrase Engine	Fully offline keyword spotting. A safe phrase fires a loud SOS and a different duress phrase fires a silent SOS; the same engine confirms the family-sharing opt-out and supports Decoy Mode.	Primary User
MOD-04	Family Circle Management	Creation of a family circle; invitations that both people must accept; member list with each person's sharing status and last update time; leaving a circle, which is separate from pausing sharing.	Primary User; Family Circle Member
MOD-05	Location Sharing and Privacy Controls	Location updates on significant movement; opt-out by spoken safe phrase without anyone's approval; private confirmation shown only to the person who opted out; timestamped last-known location marked as not live; real-time sharing status.	Family Circle Member
MOD-06	Decoy Mode	A neutral, unrelated-looking screen replaces the app when the user is forced to unlock the phone; a hidden gesture returns to the real app; SOS, voice triggers and location updates continue underneath.	Primary User
MOD-07	Danger Heatmap	Incident report form (category, auto-filled editable location, optional note); geohash grid; recency weighting; Google Maps overlay from green to red; zone details without identifying reporters; rate limits and abuse checks.	Primary User; Administrator (moderation)
MOD-08	Near Help	Verified-helper registration with an identity check; help requests broadcast to verified users within a set radius; accept or decline screen; clear "unavailable, no connection" state when offline.	Primary User; Verified Helper

Module ID	Module Name	Description	Primary Actor or User
MOD-09	Content Library Management	Curated articles, videos and links on prevention and post-trauma care, grouped by category, bundled with the app for offline use; browsing with category filters and bookmarks.	Primary User
MOD-10	Semantic Search Engine	On-device search of the library by meaning: pre-computed content embeddings, query embedding on the phone, cosine-similarity ranking, keyword-search fallback and ranked result cards.	Primary User
MOD-11	Emergency Services Directory	Localized directory of hospitals, police stations, helplines and emergency numbers (including Rescue 1122 and women's helplines) with one-tap calling and nearest-first ordering when location is available.	Primary User
MOD-12	Tiered Delivery System	Detection of connectivity as Tier 1 (no connection), Tier 2 (any connection) or Tier 3 (good connection); SMS delivery that works at Tier 1; automatic queue and retry of alerts created offline.	Primary User (system service)
MOD-13	Offline Data Caching	Last-known-location cache used when no fresh GPS fix is available at SOS time; on-device database for library content, map tiles for frequent areas and pending outbound alerts.	Primary User (system service)
MOD-14	Authentication and Account Management	Phone-number sign-up and login; secure session handling with automatic re-authentication; profile and settings (name, emergency message template, linked trustees); account recovery for lost devices.	Primary User
MOD-15	Consent and Privacy Controls	Onboarding consent explaining what the detection and voice engines listen for; separate toggles for microphone detection, location sharing and voice activation; in-app privacy summary.	Primary User
MOD-16	Admin Dashboard	Separate website for administrators: user overview, moderation queue for flagged heatmap reports, review queue for approving or revoking Near Help helpers, and monitoring of delivery success and backend errors.	Administrator
MOD-17	Missing-Child Report	Report form (name, age, photo, description, last-seen place and time, guardian contact); alert to the guardian's trusted contacts and nearby verified users; active, found and expired status handling; hand-off to official channels; moderation and child-data privacy.	Primary User (Guardian); Administrator
MOD-18	Evidence Recording on SOS	Audio recording that starts automatically when an SOS fires; encrypted storage on the device only; evidence list with time, location and trigger; user controls to stop, delete, export and auto-delete.	Primary User
MOD-19	Escalation to Authorities	Tracking of trustee and helper acknowledgements; 3-minute no-response timer; 30-second warning countdown with cancel; escalation message to configured authority numbers (SMS, call or share); escalation log.	Primary User; Authority Contact (recipient)
MOD-20	Safe-Location Navigation	One-tap directions from the current position to the nearest safe location, designed to work from data stored on the device when there is no connection.	Primary User
MOD-21	App Disguise	Option to change the app's launcher icon and name to a neutral appearance so that it does not reveal itself as a safety application.	Primary User

1.4 Definitions, Acronyms and Abbreviations

Table 3 defines the domain-specific terms, acronyms and abbreviations used in this document. The entries are in alphabetical order.

Table 3: Definitions, acronyms and abbreviations

Term or Acronym	Definition
Accelerometer	A phone sensor that measures acceleration. It is combined with the gyroscope to recognise a sudden drop or struggle movement.
Acknowledgement	A confirmation by a trustee or a helper that they have seen an alert; it stops the no-response timer.
Administrator	A member of the Muhaffiz team authorised to use the web-based Admin Dashboard (MOD-16).
ADR	Architecture decision record: a short record of a design decision, the alternatives and the reasons.
AES-256-GCM	An authenticated encryption method with a 256-bit key, used for evidence recordings.
Alert Page	A web page, served by Firebase Hosting and linked in an SOS message, where a trustee can see the alert and acknowledge it.
Android	The mobile operating system on which the Muhaffiz application runs.
Android Keystore	The Android facility that holds cryptographic keys so that they cannot be read by other applications.
API	Application Programming Interface: a defined way for one software component to request services from another.
Authority Contact	A phone number of an official emergency service, for example Police 15 or Rescue 1122, configured to receive escalation messages (MOD-19).
Bilateral Opt-in	The rule that sharing between two people starts only after both have explicitly accepted.
CI/CD	Continuous integration and continuous delivery: automatic building, testing and deployment of the software.
Cloud Functions	Server-side functions of Firebase that run in response to requests, events or schedules.
Cosine Similarity	A measure of how alike two vectors are, based on the angle between them. It is used to rank search results against a query.
Decoy Mode	A mode in which the application shows a neutral, unrelated-looking screen instead of its real interface while safety functions continue in the background (MOD-06).
Duress	A situation in which a person is forced or threatened into acting against their will.
Duress Phrase	A spoken phrase, chosen by the user and different from the safe phrase, that fires a silent SOS.
Embedding	A numeric vector that represents the meaning of a piece of text, produced by a language model.
Evidence Recording	Audio recorded on the device after an SOS fires and stored there in encrypted form (MOD-18).
FCM	Firebase Cloud Messaging: the Google service that delivers push notifications to Android devices.
Firebase	The Google backend platform used for authentication, database, messaging, storage and hosting.
Firestore	Cloud Firestore: the Firebase document database, which supports real-time listeners and a local offline cache.

Term or Acronym	Definition
Flutter	The Google user-interface toolkit, programmed in Dart, used to build the Android application.
Foreground Service	An Android service that runs with a visible notification so that the operating system does not stop it. Muhaffiz uses one for monitoring.
FR	Functional Requirement.
Fusion Rule	The rule that combines the audio distress score with the motion result to decide whether to start the confirmation countdown.
FYP	Final Year Project.
Geohash	A short string that identifies a rectangular geographic cell. It is used to group nearby points into fixed-size cells.
GPS	Global Positioning System: satellite-based positioning used to obtain the phone's location.
Gyroscope	A phone sensor that measures rotation.
Heatmap	A map overlay that colours each area from green to red according to the recency-weighted density of incident reports (MOD-07).
HTTPS and TLS	The secure web protocol and the encryption protocol (Transport Layer Security) that protects data in transit.
Incident Report	A user-submitted record of an unsafe event, with a location, a category and an optional note.
Keyword Spotting	Recognition of specific words or phrases in audio without transcribing general speech.
Last-Known Location	The most recent location a person shared before they stopped sharing. It is shown with a timestamp and is marked as not live.
Moderation Queue	The list of flagged reports and applications that an administrator reviews.
Near Help	The module that sends a help request to Verified Helpers within a set radius (MOD-08).
NFR	Non-Functional Requirement.
Offline-first	A design approach in which critical functions work without a data connection and remote synchronisation happens when a connection returns.
On-device Processing	Computation carried out on the user's phone, with no audio or analysis result sent to a server.
OTP (One-Time Code)	A single-use code sent by SMS to verify a phone number.
Outbound Queue	The on-device list of messages that could not yet be delivered and are retried.
Platform Channel	The Flutter mechanism by which Dart code calls native Android (Kotlin) code.
Primary User	A registered person who uses Muhaffiz for their own safety or, as a guardian, for the safety of a child.
Rescue 1122	An emergency rescue helpline operating in Pakistan.
Safe Location	A place from the application's bundled directory, such as a police station or hospital, to which a user can be directed in an emergency (MOD-20).
Safe Phrase	A spoken phrase, chosen by the user, that fires a loud SOS and confirms an opt-out from family location sharing.
SDS	Software Design Specification.
SMS	Short Message Service: text messaging over the cellular network, which does not need a data connection.
SOS	An emergency alert sent from the application to the user's trustees and, where applicable, to other recipients.
SQLite	A small relational database that runs inside the application.

Term or Acronym	Definition
SRS	Software Requirements Specification.
TensorFlow Lite (TFLite)	A lightweight runtime for running machine-learning models on mobile devices.
Tier 1, Tier 2, Tier 3	The three connectivity levels used by delivery: Tier 1 is no data connection, Tier 2 is any data connection, Tier 3 is a good data connection (MOD-12).
Trustee	A contact chosen by a Primary User to receive SOS alerts. A trustee may or may not have the application installed.
UI	User interface.
Unilateral Opt-out	The rule that a person can stop sharing their location at any time without anyone's approval.
Verified Helper	A registered user who has passed an identity check and agreed to respond to Near Help requests.
WhatsApp	A messaging application used by Muhaffiz as one SOS dispatch channel.
WorkManager	The Android component that runs persistent background work, such as retrying the outbound queue.
YAMNet	A pre-trained audio-event classification model that runs with TensorFlow Lite.

1.5 Document Overview

The remainder of this document is organized as follows.

- **Chapter 2: Overall Description and Requirements Elicitation** places Muhaffiz in context, identifies the user classes, the operating environment, the constraints, assumptions and dependencies, and explains how the requirements were identified, prioritized and validated.
- **Chapter 3: Software Requirements Specification** gives the functional requirement catalogue and the specification of each functional requirement, the use cases, the business rules, the non-functional requirements and the external interface requirements.
- **Chapter 4: System Design** presents the design methodology, the architecture, the design models, the data design, the human interface design, the security, error-handling and logging design, and the risk analysis and milestone plan.
- **Chapter 5: Implementation and Deployment** describes the core algorithms, the external APIs and SDKs, the interfaces of the backend, the user interface and the deployment arrangement.
- **Chapter 6: Testing, Evaluation and Conclusion** defines the test cases at each level, the traceability matrix, and the conclusion with limitations and future enhancements.

- **References** lists the sources cited in IEEE style.
- **Appendix A** lists all use cases, **Appendix B** gives the detailed specifications of the use cases not given in Chapter 3, **Appendix C** lists items still to be determined, and **Appendix D** gives sample test data. The glossary is in Section 1.4 and is not repeated.

Identifiers follow a fixed scheme: modules MOD-nn, functional requirements FR-nn.nn (the first number is the module), use cases UC-nn, business rules BR-nn, non-functional requirements NFR-xxx-nn, constraints CON-n, assumptions AS-n, dependencies DEP-n, and risks RSK-nn. Modules MOD-01 to MOD-16 keep the order of modules 7.1 to 7.16 of the approved project scope document; MOD-17 to MOD-21 were added after that document was written.

1.6 Chapter Summary

This chapter introduced Muhaffiz as an offline-first, on-device and coercion-aware safety application for women and children, defined the committed and excluded scope, listed the twenty-one modules, and fixed the terminology and identifier scheme. Chapter 2 now describes the context in which the system operates and how its requirements were identified.

Chapter 2: Overall Description and Requirements Elicitation

Chapter Overview. This chapter places Muhaffiz in its context and explains where its requirements come from. Section 2.1 describes the origin of the product and its relationship to existing systems, Section 2.2 identifies the user classes, Section 2.3 states the operating environment, Section 2.4 lists the constraints, assumptions and dependencies, and Section 2.5 explains how requirements were identified, prioritized and validated.

2.1 Product Perspective

Muhaffiz is a new, self-contained product. It does not replace or extend an earlier system. It was conceived to address a safety gap that is large and well documented: worldwide, about one in three women experience physical or sexual violence in their lifetime [1]. A person in danger needs to raise an alarm quickly, discreetly and in places where a data connection cannot be relied on, and a person who is being monitored by someone else needs a way to stop that monitoring safely.

People currently combine general-purpose tools to do this. In the survey described in Section 2.5, the most common tool was WhatsApp live location (61% of the responses analysed in detail), followed by the phone's built-in emergency SOS (19%); 29% used nothing, and one respondent in 31 had ever used a dedicated safety application. The most common reason for not using a safety application was that it needs internet (71%). Muhaffiz does not compete with the national emergency helplines. It complements them: it can alert a person's own contacts first, and it hands a message to a helpline number when the contacts do not respond.

The product consists of three parts. The **Android application** contains the on-device layer, which works without any network: sound-based distress detection, offline voice activation, SOS triggering, SMS dispatch, the offline library and its search, the local cache and the evidence recorder. The **Firebase backend** is the cloud coordination layer: authentication, family-circle synchronisation, the heatmap and Near Help data, push messaging, storage, and server-side functions for channels that cannot run on the phone, such as email. The **admin website** at muhaffiz.me lets administrators moderate reports and review helpers. Figure 1 shows the system as one unit and its interfaces with people and external services.




Figure 1: Context diagram of Muhaffiz

The external entities and their interfaces are as follows.

- **Primary User:** operates the application; sends SOS commands, settings, incident reports and searches, and receives alerts, map data and library results.
- **Family Circle Member:** shares location with, and views the sharing status of, other members of a circle.
- **Verified Helper:** receives nearby help requests and replies with accept or decline.
- **Trustee:** receives the SOS alert and may acknowledge it.
- **Authority Contact:** receives the escalation message when nobody has responded.
- **Administrator:** moderates reports, approves or revokes helpers, and monitors system health through the admin website.
- **Google Maps Platform:** supplies the map and tiles used by the heatmap, the family map and navigation.
- **Email provider:** carries the email copy of an SOS and returns delivery status.

- **WhatsApp:** receives the SOS share request on the user's phone.
- **Cellular SMS network:** carries SMS alerts, which need no data connection.

2.2 User Classes and Characteristics

Table 4 lists every user class and external actor. Access level and frequency of use are given in the description.

Table 4: User classes and external actors

User Class or Actor	Description	Expected Skills	Main Responsibilities or Interactions
Primary User	A registered person who uses Muhaffiz for personal safety. Authenticated by phone number. Full access to the user modules. Daily background use, with occasional active use.	Basic smartphone use. No technical or security knowledge.	Configures trustees, phrases and privacy toggles; triggers or cancels SOS; reports incidents; uses the library, directory and navigation.
Guardian	A Primary User who acts for a child. Same access as a Primary User, with additional access to the missing-child report.	Basic smartphone use.	Files and updates a missing-child report; manages the child-related contacts.
Family Circle Member	A Primary User who has joined a family circle. Access is limited to the circle they belong to. Continuous use while sharing.	Basic smartphone use.	Accepts invitations; shares location; stops sharing by safe phrase; views other members' status.
Trustee	A contact chosen by a Primary User to receive SOS alerts. May have no account and no app, in which case alerts arrive by SMS, WhatsApp or email. Rare use, at the time of an alert.	Reading a message and following a map link.	Receives alerts; may acknowledge an alert.
Verified Helper	A Primary User who has passed an identity check and agreed to respond to nearby requests. Occasional use.	Basic smartphone use.	Registers for verification; accepts or declines requests.
Administrator	A member of the project team with access to the admin website. Daily or weekly use. Authenticated separately from the application.	Web browser use; understanding of moderation rules.	Reviews flagged reports and missing-child reports; approves or revokes helpers; monitors delivery success and errors.
Authority Contact (external)	An emergency service number configured for escalation. Not a user of Muhaffiz.	Not applicable.	Receives the escalation message sent as SMS, call or share.

2.3 Operating Environment

Table 5 gives the hardware, software, network and hosting environment in which Muhaffiz operates.

Table 5: Operating environment

Environment Item	Specification or Version	Purpose
Client operating system	Android 8.0 (API level 26) or later	Foreground services, notification channels and runtime permissions used by the safety engines.
Client framework	Flutter (stable channel) with Dart; Android platform channels written in Kotlin	Single code base for the user interface, with platform channels for SMS, foreground services and launcher-icon switching.
Client hardware	Smartphone with microphone, accelerometer, gyroscope, GPS receiver, speaker, vibration motor and SIM card; Google Play services	Sensing, alarm, vibration countdown, SMS delivery, push messaging and maps.
Network	Cellular network (SMS, voice, data) and Wi-Fi	SOS must be deliverable by SMS without a data connection; other channels need data.
Backend platform	Google Firebase: Authentication, Cloud Firestore, Cloud Messaging, Cloud Storage, Cloud Functions, Hosting	Identity, synchronisation, push, file storage, server-side functions and web hosting.
Admin website	Flutter web build served by Firebase Hosting on the muhaffiz.me domain; current versions of Chrome, Edge, Firefox and Safari on desktop	Administrator access to moderation, helper review and monitoring.
Maps	Google Maps SDK for Android	Heatmap overlay, family map and navigation display.
Offline map data	Open map data (OpenStreetMap-derived) downloaded for up to three user-selected areas and stored on the device	Map display for frequent areas and safe-location guidance with no connection.
On-device intelligence	TensorFlow Lite runtime; pre-trained models for sound classification, keyword spotting and sentence embedding, bundled with the application	Distress detection, voice activation and semantic search without a network.
On-device storage	SQLite database; encrypted files protected by a key held in the Android Keystore	Offline library, cache, outbound queue and evidence recordings.
Geography and language	Pakistan; English user interface	Target users and emergency numbers.

- OE-1: The application shall operate correctly on Android 8.0 (API level 26) and later on phones that provide the sensors and radios listed in Table 5.
- OE-2: The SOS dispatch by SMS shall operate with no data connection when cellular coverage is present.
- OE-3: The voice-activation, distress-detection, library, search, directory and evidence functions shall operate with no network connection.
- OE-4: The admin website shall operate correctly on the current versions of Chrome, Edge, Firefox and Safari on desktop computers.

2.4 Design and Implementation Constraints, Assumptions and Dependencies

The following constraints restrict the design and implementation. Each is followed by its rationale.

- CON-1: The user application shall run on Android only. *Rationale:* Android permits the foreground services, background audio and SMS capability that the safety engines need; iOS restricts them.
- CON-2: The user application shall be built with Flutter and Dart, using Android platform channels where a native capability is required. *Rationale:* one code base is practical for a two-person team.
- CON-3: The backend shall use Firebase services. *Rationale:* they provide phone authentication, real-time synchronisation, push messaging and offline caching as one managed platform.
- CON-4: Machine-learning components shall use existing pre-trained models; no model shall be trained from scratch. *Rationale:* the project has no labelled incident data or GPU infrastructure.
- CON-5: Audio processed by the distress-detection and voice engines shall not be stored or transmitted off the device. *Rationale:* privacy and the consent given by the user.
- CON-6: Evidence recordings shall be stored only on the device, in encrypted form. *Rationale:* recordings are sensitive and are meant for the user to present later.
- CON-7: The voice-activation engine shall be open source or otherwise usable with no network access, account or access key. *Rationale:* voice activation must work fully offline.
- CON-8: Third-party services and components shall be used within their free tiers or free licences. *Rationale:* the project has no budget for paid services.
- CON-9: Microphone, location, SMS, notification and recording features shall run only after the user has granted the corresponding Android permission and has given consent in the application. *Rationale:* Android permission rules and the privacy principles of the product.

- CON-10: The user interface shall be in English. *Rationale:* approved project scope.
- CON-11: The admin website shall be served from its own domain, muhaffiz.me, and shall be separate from the user application. *Rationale:* administrative functions must not be reachable from the user application.
- CON-12: The system shall be completed within the final year project schedule by a team of two. *Rationale:* academic schedule and team size.

Table 6 states the assumptions, which are believed true but not guaranteed, and the external dependencies on which the project relies.

Table 6: Assumptions and dependencies

ID	Type	Statement	Rationale or Source	Impact if Invalid
AS-1	Assumption	Users' phones have a microphone, motion sensors, GPS, a vibration motor and a SIM card.	Typical of current Android smartphones.	Detection, countdown or SMS delivery is unavailable on the affected phone.
AS-2	Assumption	Cellular coverage is available when an SOS is sent.	SMS needs the cellular network, not data.	The alert stays in the outbound queue until coverage returns.
AS-3	Assumption	Users grant the required permissions and exclude the application from battery optimisation.	Android may stop background services otherwise.	Background detection and voice activation stop silently.
AS-4	Assumption	A pre-trained sound classifier distinguishes distress sounds from other loud sounds well enough for a confirm-or-cancel design.	The 20-second cancel step limits the cost of an error.	False alarms or missed detections increase; manual SOS remains available.
AS-5	Assumption	The keyword-spotting engine recognises the phrases users choose, including with local accents.	Phrases are user-chosen and short.	Voice triggers are unreliable; manual SOS remains available.
AS-6	Assumption	Emergency numbers such as Police 15 and Rescue 1122 accept calls and text messages from the public.	Published public numbers.	Escalation messages are delivered but may not be acted on.
AS-7	Assumption	At least one of a trustee's channels (SMS, WhatsApp, email, push) is reachable at alert time.	Trustees are chosen by the user.	The alert is not seen; escalation to authorities applies.
AS-8	Assumption	Incident reports and helper registrations are submitted in good faith, and abuse is caught by rate limits and moderation.	Crowd-sourced data needs moderation.	The heatmap or helper list becomes unreliable.
AS-9	Assumption	Library content is curated by the project team from reputable sources.	Curated, bundled content.	Library guidance is inaccurate.
DEP-1	Dependency	Availability of Firebase services (Authentication, Firestore, Cloud Messaging, Storage, Functions, Hosting).	Chosen backend platform.	Synchronised features and push are unavailable; on-device and SMS functions continue.
DEP-2	Dependency	Google Maps Platform and Google Play services on the phone.	Map display and push delivery.	Maps and push are unavailable; SMS and call functions continue.

ID	Type	Statement	Rationale or Source	Impact if Invalid
DEP-3	Dependency	WhatsApp installed on the user's phone for share-based dispatch.	WhatsApp is one dispatch channel.	The WhatsApp channel is skipped; other channels continue.
DEP-4	Dependency	An email delivery service reachable from Cloud Functions.	Email is a dispatch channel.	The email channel fails; other channels continue.
DEP-5	Dependency	Pre-trained models and their licences: sound classifier, keyword spotter and sentence embedder.	CON-4 and CON-7.	The affected on-device function cannot be delivered.
DEP-6	Dependency	The cellular operators and the emergency services that receive escalation messages.	External recipients.	Escalation depends on their acceptance and response.
DEP-7	Dependency	An open map-data source that permits offline storage.	Offline maps need data that may be stored on the device.	Offline map display is unavailable; online maps and distance guidance continue.

2.5 Requirement Identifying Techniques

Elicitation. Requirements were identified from five sources: analysis of the approved project scope document and the feature document; a review of existing safety applications and emergency helplines to see which features already exist; a questionnaire survey; semi-structured interviews; and use-case analysis by the project team. The survey received 73 responses. The percentages quoted in this document are those of the first 31 responses, which were analysed in detail; the distribution across all 73 responses was found to be nearly identical. Survey figures state interest, not adoption.

Table 7: Survey: current practice and barriers (first 31 responses analysed)

Finding	Result
Worry about the safety of a woman or child "often" or "almost every time"	87% (27 of 31)
Has used a dedicated safety application	3% (1 of 31)
Has used WhatsApp live location	61% (19 of 31)
Has used the phone's built-in emergency SOS	19% (6 of 31)
Has used nothing	29% (9 of 31)
Barrier: the application needs internet	71% (22 of 31)
Barriers: privacy, too slow or complicated, lack of trust, do not know a good one (each)	39% (12 of 31)
Barrier: battery use	19% (6 of 31)
Barrier: someone could force me to share my location	13% (4 of 31)
Would use an application like this (for self, for a family member, or both)	87% (27 of 31)
Would install it for a woman or child in the family	58% (18 of 31)

Table 8: Survey: respondents likely or very likely to use each feature (first 31 responses analysed)

Feature described in the survey	Likely or very likely	Related module
Decoy screen that hides the application when forced to unlock the phone	87% (27)	MOD-06
Map of areas reported as unsafe	84% (26)	MOD-07
One-tap list of nearby hospitals and helplines	84% (26)	MOD-11
SOS sent to authorities	81% (25)	MOD-19
Audio recording kept on the device as evidence while an SOS is active	77% (24)	MOD-18
Missing-child report to verified users	77% (24)	MOD-17
One-tap direction to the nearest safe area	77% (24)	MOD-20
SOS button that sends live location, by SMS when there is no internet	74% (23)	MOD-01, MOD-12
Family location map where everyone must agree and anyone can stop privately	68% (21)	MOD-04, MOD-05
Safety tips searchable in your own words, even offline	68% (21)	MOD-09, MOD-10
Secret phrase to call for help without touching the phone	58% (18)	MOD-03
Alerting verified application users nearby	58% (18)	MOD-08
Phone senses screaming or distress and sends an alert unless cancelled within 20 seconds	55% (17)	MOD-02

The interviews were held with a high-school student, a working woman, a medical (MBBS) student and a male university student. Table 7 and Table 8 and the interviews led to the following requirements decisions.

- Internet dependence was the most common barrier (71%). This supports the offline-first design of MOD-12 and MOD-13 and the requirement that voice, detection, library and search work with no network.
- The decoy screen was the most favoured feature (87%) and was named by a medical student as one of the most valuable. This supports MOD-06 and MOD-21.
- Audio evidence was accepted by interviewees as a trade-off for proof in front of authorities, while the high-school student considered video a privacy breach. This supports audio-only recording in MOD-18 and the exclusion of video recording.
- Four of 31 survey respondents (13%) named the risk of being forced to share their location as a barrier. This supports the consent rules of MOD-04 and MOD-05.
- An interviewee said that trust in how applications handle personal data is a concern. This supports on-device processing, the consent flow of MOD-15 and the child-data rules of MOD-17.

- A male university student asked for directions to the nearest safe location that work offline. This, with the survey item, is the source of MOD-20.
- One survey respondent suggested disguising the application by changing its icon and name. This is the source of MOD-21.
- Automatic detection received the lowest stated interest (55%), and only 2 of 31 chose it as the single most important feature. It is therefore designed as an assistance that always asks for confirmation (the 20-second cancel step), with manual SOS as the primary path.

Stakeholders. The stakeholders are the Primary Users and Guardians for whom the system is built, the family circle members and trustees who receive its information, the verified helpers and administrators who operate its community functions, the emergency services that receive escalation messages, the supervisor, who guides and approves the work, the evaluation committee, and the two developers. Their interests are reflected in the user classes of Section 2.2.

Prioritization. Requirements are prioritized High, Medium or Low. A module is High when it is on the critical path of getting an alert out or protects the user from coercion, so that without it the purpose of the product fails. A module is Medium when it adds significant value but the core alert still works without it. A module is Low when it is an enhancement. The ranking considered the survey interest in Table 8, the dependencies between modules, and the technical risk. A requirement inherits the priority of its module in Table 9 unless Section 3.1 states otherwise.

Table 9: Module priorities

Priority	Modules	Basis
High	MOD-01, MOD-02, MOD-03, MOD-04, MOD-05, MOD-06, MOD-12, MOD-13, MOD-14, MOD-15	Core alert path, offline delivery, identity and consent, and the duress-protection features that distinguish the product.
Medium	MOD-07, MOD-08, MOD-09, MOD-10, MOD-11, MOD-16, MOD-17, MOD-18, MOD-19	Community, information and follow-through features; the admin dashboard is needed to moderate MOD-07, MOD-08 and MOD-17.
Low	MOD-20, MOD-21	Enhancements that depend on other modules (the directory and the settings).

Validation. Requirements are written to be unique, clear, feasible, testable and traceable [2]. Each functional requirement carries acceptance criteria that are verified by the

test cases of Chapter 6, and each requirement is traced to its source, design element and test in the traceability matrix. The specification is reviewed by the supervisor and the evaluation committee, and the screen designs of Section 4.5 are used to confirm user-interface flows. Table 10 summarizes the techniques.

Table 10: Requirement identification techniques

Technique	Stakeholders or Source	Purpose	Evidence or Output
Document analysis	Approved project scope document; feature document	Define modules and sub-modules	Modules MOD-01 to MOD-21 (Section 1.3)
Review of existing systems	Publicly available safety applications and national helplines	Identify what exists and the gaps	Product perspective (Section 2.1)
Questionnaire survey	Survey respondents (73 responses)	Measure current practice, barriers and interest by feature	Table 7 and Table 8
Semi-structured interviews	High-school student, working woman, MBBS student, male university student	Explore reactions, privacy concerns and missing features	Requirements decisions listed above; MOD-20 and MOD-21
Use cases	Project team and supervisor	Describe actor and system interaction	Chapter 3 and Appendices A and B
Event-response tables	Project team	Specify background behaviour of detection, delivery and escalation	Section 4.3
Storyboarding and prototyping	Project team; users	Confirm screen flows	Screen designs, Section 4.5
Prioritization (High, Medium, Low)	Project team and supervisor	Order the work	Table 9

2.6 Chapter Summary

This chapter described Muhaffiz as a new product made of an Android application, a Firebase backend and an admin website, and showed its interfaces in a context diagram. It identified seven user classes, fixed the operating environment, listed twelve constraints, nine assumptions and seven dependencies, and explained how requirements were elicited from documents, a survey and interviews, prioritized and validated. Chapter 3 now specifies the requirements in detail.

Chapter 3: Software Requirements Specification

Chapter Overview. This chapter specifies what Muhaffiz shall do. Section 3.1 lists the functional requirements, Section 3.2 specifies each of them and gives the use cases, Section 3.3 states the business rules, Section 3.4 gives the non-functional requirements and Section 3.5 specifies the external interfaces. Every requirement has a unique identifier, is written with "shall", and has acceptance criteria that can be tested.

3.1 Functional Requirement Catalogue

The functional requirements are organized by module. The identifier FR-mm.nn names module mm and the requirement nn within it; the requirements of MOD-01 to MOD-19 follow the numbering of the sub-modules 7.1.1 to 7.19.6 of the feature document, so that each can be traced to it. There are 87 functional requirements. A requirement has the priority of its module in Section 2.5 unless Table 11 states otherwise.

Table 11: Functional requirement catalogue

FR ID	Feature or Module	Requirement Title	Priority	Dependencies
FR-01.01	MOD-01	Manual SOS Trigger	High	FR-01.02, FR-14.01
FR-01.02	MOD-01	Multi-Channel Dispatch	High	FR-01.05, FR-12.01, FR-13.01
FR-01.03	MOD-01	Loud Alarm	High	FR-01.01
FR-01.04	MOD-01	Silent Mode	High	FR-01.02, FR-03.04
FR-01.05	MOD-01	Trustee Management	High	FR-14.03
FR-01.06	MOD-01	SOS Event Log	Medium	FR-01.02, FR-12.03
FR-02.01	MOD-02	Ambient Monitoring Service	High	FR-15.02
FR-02.02	MOD-02	Distress Sound Classification	High	FR-02.01
FR-02.03	MOD-02	Motion-Signal Fusion	High	FR-02.02
FR-02.04	MOD-02	Confirmation Countdown	High	FR-02.03, FR-01.02
FR-02.05	MOD-02	On-Device Processing Guarantee	High	FR-02.01, FR-02.02, FR-02.03
FR-03.01	MOD-03	Safe-Phrase Enrolment	High	FR-15.02
FR-03.02	MOD-03	Duress-Phrase Enrolment	High	FR-03.01
FR-03.03	MOD-03	Offline Keyword Spotting	High	FR-03.01, FR-03.02, FR-15.02
FR-03.04	MOD-03	Voice-Triggered SOS	High	FR-03.03, FR-02.04
FR-03.05	MOD-03	Shared Duress-Confirmation Hook	High	FR-03.03, FR-05.02, FR-06.01
FR-04.01	MOD-04	Circle Creation and Bilateral Invitation	High	FR-14.01
FR-04.02	MOD-04	Circle Membership List	High	FR-05.05
FR-04.03	MOD-04	Leave a Circle	High	FR-04.01

FR ID	Feature or Module	Requirement Title	Priority	Dependencies
FR-05.01	MOD-05	Movement-Based Location Updates	High	FR-04.01, FR-15.02
FR-05.02	MOD-05	Opt-Out by Safe Phrase	High	FR-03.05, FR-05.01
FR-05.03	MOD-05	Private Opt-Out Confirmation	High	FR-05.02
FR-05.04	MOD-05	Last-Known Location Display	High	FR-05.01
FR-05.05	MOD-05	Real-Time Sharing Status	High	FR-04.02
FR-06.01	MOD-06	Disguised Interface	High	FR-03.05
FR-06.02	MOD-06	Hidden Re-entry Gesture	High	FR-06.01
FR-06.03	MOD-06	Background Pass-Through	High	FR-06.01, FR-03.03
FR-07.01	MOD-07	Incident Report Form	Medium	FR-14.01, FR-07.05
FR-07.02	MOD-07	Geohash Grid Aggregation	Medium	FR-07.01
FR-07.03	MOD-07	Recency Weighting	Medium	FR-07.02
FR-07.04	MOD-07	Heatmap Overlay	Medium	FR-07.03
FR-07.05	MOD-07	Rate Limits and Abuse Checks	Medium	FR-16.02
FR-08.01	MOD-08	Verified-Helper Registration	Medium	FR-14.01, FR-16.03
FR-08.02	MOD-08	Help Request Broadcast	Medium	FR-08.01, FR-12.01
FR-08.03	MOD-08	Accept or Decline Screen	Medium	FR-08.02, FR-19.01
FR-08.04	MOD-08	Offline State	Medium	FR-12.03
FR-09.01	MOD-09	Curated Content	Medium	-
FR-09.02	MOD-09	Offline Bundling	Medium	FR-13.02
FR-09.03	MOD-09	Browsing, Filters and Bookmarks	Medium	FR-09.01
FR-10.01	MOD-10	Precomputed Content Embeddings	Medium	FR-09.02
FR-10.02	MOD-10	On-Device Query Embedding	Medium	FR-10.01
FR-10.03	MOD-10	Cosine-Similarity Ranking	Medium	FR-10.02
FR-10.04	MOD-10	Keyword-Search Fallback	Medium	FR-09.01
FR-10.05	MOD-10	Ranked Result Cards	Medium	FR-10.03, FR-09.03
FR-11.01	MOD-11	Localized Directory	Medium	FR-13.02
FR-11.02	MOD-11	One-Tap Call	Medium	FR-11.01
FR-11.03	MOD-11	Nearest Facilities First	Medium	FR-11.01, FR-13.01
FR-12.01	MOD-12	Connectivity Tier Detection	High	-
FR-12.02	MOD-12	SMS Delivery at Tier 1	High	FR-01.02
FR-12.03	MOD-12	Queue and Retry	High	FR-13.02, FR-01.06
FR-13.01	MOD-13	Last-Known Location Cache	High	-
FR-13.02	MOD-13	On-Device Database	High	-
FR-14.01	MOD-14	Phone-Number Sign-Up and Login	High	DEP-1
FR-14.02	MOD-14	Session Handling	High	FR-14.01
FR-14.03	MOD-14	Profile and Settings	High	FR-01.05
FR-14.04	MOD-14	Account Recovery	High	FR-14.01

FR ID	Feature or Module	Requirement Title	Priority	Dependencies
FR-15.01	MOD-15	Onboarding Consent	High	-
FR-15.02	MOD-15	Permission and Feature Toggles	High	FR-15.01
FR-15.03	MOD-15	Privacy Summary	High	-
FR-16.01	MOD-16	User Overview	Medium	FR-16.05
FR-16.02	MOD-16	Moderation Queue	Medium	FR-07.05, FR-17.05, FR-16.05
FR-16.03	MOD-16	Helper Review Queue	Medium	FR-08.01, FR-16.05
FR-16.04	MOD-16	Health Monitoring	Medium	FR-01.06, FR-16.05
FR-16.05	MOD-16	Administrator Authentication	Medium	DEP-1
FR-17.01	MOD-17	Missing-Child Report Form	Medium	FR-14.01
FR-17.02	MOD-17	Alert to Contacts and Nearby Helpers	Medium	FR-17.01, FR-08.01, FR-12.01
FR-17.03	MOD-17	Report Status Handling	Medium	FR-17.01
FR-17.04	MOD-17	Hand-Off to Official Channels	Medium	FR-17.01
FR-17.05	MOD-17	Moderation and Abuse Prevention	Medium	FR-16.02
FR-17.06	MOD-17	Child-Data Privacy	Medium	FR-17.03
FR-18.01	MOD-18	Automatic Recording on SOS	Medium	FR-01.01, FR-15.01
FR-18.02	MOD-18	Encrypted On-Device Storage	Medium	FR-18.01
FR-18.03	MOD-18	Evidence List	Medium	FR-18.02, FR-01.06
FR-18.04	MOD-18	Evidence Controls	Medium	FR-18.03
FR-18.05	MOD-18	Consent Disclosure	Medium	FR-15.01
FR-19.01	MOD-19	Response Tracking	Medium	FR-01.02, FR-08.03, UC-29
FR-19.02	MOD-19	No-Response Timer	Medium	FR-19.01
FR-19.03	MOD-19	Warning Countdown	Medium	FR-19.02
FR-19.04	MOD-19	Authority Channel Settings	Medium	FR-14.03
FR-19.05	MOD-19	Escalation Message	Medium	FR-19.03, FR-18.01
FR-19.06	MOD-19	Escalation Log	Medium	FR-19.05
FR-20.01	MOD-20	Nearest Safe Location	Low	FR-11.01, FR-13.01
FR-20.02	MOD-20	One-Tap Directions Online	Low	FR-20.01
FR-20.03	MOD-20	Offline Guidance	Low	FR-20.01, FR-13.02
FR-21.01	MOD-21	Disguise Options	Low	-
FR-21.02	MOD-21	Apply and Restore	Low	FR-21.01
FR-21.03	MOD-21	Unchanged Functions	Low	FR-21.01, FR-01.04

3.2 Functional Requirement Specification

Each functional requirement is specified in a table with the attributes required by the template. The requirement is stated from the user perspective, where a user acts, and from the system perspective, as the response of the system to a trigger. Valid input, invalid input and

error conditions are covered by the system perspective and the acceptance criteria. The acceptance criteria are the conditions that the test cases of Chapter 6 verify.

3.2.1 MOD-01 SOS Alert System

Table 12: Specification of FR-01.01: Manual SOS Trigger

Attribute	Required Information
Identifier	FR-01.01
Title	Manual SOS Trigger
Requirement	**User perspective:** The Primary User shall be able to start an SOS by pressing and holding the SOS control on the home screen for 1 second, or by tapping the SOS action on the lock screen. **System perspective:** When the hold completes or the lock-screen action is tapped, the system shall start the SOS dispatch pipeline immediately, without a confirmation countdown, and record the trigger method as "manual". If the control is released before 1 second, no SOS shall start.
Source	Feature Document 7.1.1; survey (SOS button 74%)
Rationale	The control must be usable with one hand under stress; the 1-second hold prevents accidental starts from the home screen.
Business Rule	BR-01, BR-02
Dependencies	FR-01.02, FR-14.01
Priority	High
Acceptance Criteria	• Holding the control for 1 second starts the dispatch pipeline within 1 second. • Releasing at 0.5 seconds starts nothing. • The lock-screen action starts an SOS while the phone is locked. • The event log records the trigger method "manual".

Table 13: Specification of FR-01.02: Multi-Channel Dispatch

Attribute	Required Information
Identifier	FR-01.02
Title	Multi-Channel Dispatch
Requirement	**System perspective:** When an SOS starts, the system shall send the user's location and the preset message to every trustee on each channel that the trustee has enabled: SMS sent by the device, push notification through FCM, email through a backend function, and a prefilled WhatsApp message. SMS, push and email shall be started in parallel without waiting for one another. The WhatsApp message shall be prepared through the WhatsApp share link and requires the user's confirmation to send; it shall not be used when the SOS is silent. If a channel fails, the remaining channels shall continue and the failure shall be logged.
Source	Feature Document 7.1.2; survey (SOS button 74%)
Rationale	Several channels raise the chance that a trustee sees the alert; automatic channels cannot depend on user interaction.
Business Rule	BR-04, BR-05, BR-06, BR-32
Dependencies	FR-01.05, FR-12.01, FR-13.01
Priority	High
Acceptance Criteria	• With two trustees on different channels, each receives the alert on its enabled channels. • The message contains coordinates, a map link, the time, the user's name and the preset text. • Disabling the network does not prevent SMS dispatch. • Failure of one channel does not stop the others. • No WhatsApp message is prepared in silent mode.

Table 14: Specification of FR-01.03: Loud Alarm

Attribute	Required Information
Identifier	FR-01.03
Title	Loud Alarm
Requirement	**User perspective:** The Primary User shall be able to stop the alarm with a single control on the SOS screen. **System perspective:** When an SOS starts in loud mode, the system shall play a siren through the alarm audio stream at maximum volume until the user stops it. The alarm shall not be played in silent mode.
Source	Feature Document 7.1.3; survey (SOS button 74%)
Rationale	A loud sound attracts the attention of people nearby.
Business Rule	BR-03
Dependencies	FR-01.01
Priority	High
Acceptance Criteria	• The siren starts within 1 second of the SOS start in loud mode. • The alarm stream is at its maximum volume while the siren plays. • The stop control ends the siren. • No siren is played in silent mode.

Table 15: Specification of FR-01.04: Silent Mode

Attribute	Required Information
Identifier	FR-01.04
Title	Silent Mode
Requirement	**User perspective:** The Primary User shall be able to choose silent as the default SOS mode in the settings. **System perspective:** When an SOS is started in silent mode, by the setting or by the duress phrase, the system shall play no sound, shall not vibrate, shall show no SOS indication on the screen and shall use neutral wording in any system notification, while dispatch continues in the background.
Source	Feature Document 7.1.4; survey (SOS button 74%)
Rationale	A user who is hiding must not reveal that an alert is being sent.
Business Rule	BR-03
Dependencies	FR-01.02, FR-03.04
Priority	High
Acceptance Criteria	• No sound or vibration occurs during a silent SOS. • The screen shows no SOS text or alert colour. • The status bar notification text does not mention SOS or safety. • The event log shows dispatch on the enabled channels.

Table 16: Specification of FR-01.05: Trustee Management

Attribute	Required Information
Identifier	FR-01.05
Title	Trustee Management

Attribute	Required Information
Requirement	**User perspective:** The Primary User shall be able to add, edit and remove trustees, and to choose for each trustee the channels (SMS, push, email, WhatsApp) on which alerts are sent. **System perspective:** When a trustee is saved, the system shall validate that the name is not empty and that the phone number is a valid mobile number, and shall store the channel preferences. If no channel is selected the system shall use SMS. The system shall require at least one trustee before the user completes onboarding and shall allow up to 10 trustees. Removing a trustee shall exclude that trustee from later alerts.
Source	Feature Document 7.1.5; survey (SOS button 74%)
Rationale	Alerts must reach people the user has chosen, over channels that suit each of them.
Business Rule	BR-04
Dependencies	FR-14.03
Priority	High
Acceptance Criteria	• An invalid phone number is rejected with an explanatory message. • A saved trustee appears in the list with its channels. • A removed trustee receives no later alert. • Onboarding cannot finish without one trustee.

Table 17: Specification of FR-01.06: SOS Event Log

Attribute	Required Information
Identifier	FR-01.06
Title	SOS Event Log
Requirement	**User perspective:** The Primary User shall be able to view a list of past SOS events. **System perspective:** For every SOS the system shall record the time, the location, the trigger method (manual, automatic or voice) and, for each trustee and channel, the delivery status, and shall update the status as it changes. The log shall be kept on the device.
Source	Feature Document 7.1.6; survey (SOS button 74%)
Rationale	The user needs to know whether and how an alert was delivered.
Business Rule	BR-05
Dependencies	FR-01.02, FR-12.03
Priority	Medium
Acceptance Criteria	• Each SOS creates one log entry with time, location and trigger method. • Delivery status per channel changes from queued to sent or failed as events occur. • The log remains after the application is closed.

3.2.2 MOD-02 Automatic Danger Detection Engine

Table 18: Specification of FR-02.01: Ambient Monitoring Service

Attribute	Required Information
Identifier	FR-02.01
Title	Ambient Monitoring Service
Requirement	**System perspective:** While microphone detection is enabled, the system shall run a low-power foreground service that measures the sound level of short audio frames in memory and discards each frame immediately. The service shall not classify audio until the level rises suddenly above the threshold relative to the recent ambient level. The service shall show a persistent notification, and shall restart after the device restarts.
Source	Feature Document 7.2.1; survey (55%); scope document

Attribute	Required Information
Rationale	Classification is expensive, so it must run only when something loud happens.
Business Rule	BR-07, BR-08, BR-09
Dependencies	FR-15.02
Priority	High
Acceptance Criteria	• In a quiet room no classification is started. • A sudden loud sound starts one classification. • No audio frame is written to storage. • After a restart the service resumes without opening the application.

Table 19: Specification of FR-02.02: Distress Sound Classification

Attribute	Required Information
Identifier	FR-02.02
Title	Distress Sound Classification
Requirement	**System perspective:** When the monitoring service reports a sudden loud sound, the system shall run the on-device sound classifier on the buffered burst and shall produce a distress score for sounds such as screaming and shouting. The system shall not transcribe speech and shall discard the buffer after classification.
Source	Feature Document 7.2.2; survey (55%); scope document
Rationale	Recognising a distress sound is a smaller problem than understanding speech and keeps the content of conversations private.
Business Rule	BR-07, BR-08
Dependencies	FR-02.01
Priority	High
Acceptance Criteria	• A labelled distress clip yields a score above the distress threshold. • A labelled non-distress loud clip yields a score below it. • No transcript is produced and no audio is stored.

Table 20: Specification of FR-02.03: Motion-Signal Fusion

Attribute	Required Information
Identifier	FR-02.03
Title	Motion-Signal Fusion
Requirement	**System perspective:** For the same time window, the system shall read the accelerometer and gyroscope, shall detect a sudden drop or struggle movement, and shall combine this with the audio score under the fusion rule of Section 5.1. The system shall start the confirmation countdown only when the fusion rule is satisfied.
Source	Feature Document 7.2.3; survey (55%); scope document
Rationale	Using two independent signals reduces false alarms from loud but harmless sounds.
Business Rule	BR-02
Dependencies	FR-02.02
Priority	High
Acceptance Criteria	• A distress sound with no motion anomaly does not start the countdown unless the audio score is above the high-confidence threshold. • A distress sound with a motion anomaly starts the countdown. • Motion data are not stored.

Table 21: Specification of FR-02.04: Confirmation Countdown

Attribute	Required Information
Identifier	FR-02.04
Title	Confirmation Countdown
Requirement	**User perspective:** The Primary User shall be able to cancel a pending automatic alert with a single tap. **System perspective:** When the fusion rule is satisfied, the system shall vibrate with a mild pattern for 20 seconds, shall make no sound, and shall present a one-tap cancel control. If the user cancels, nothing shall be sent. If the 20 seconds pass without a cancel, the system shall start the SOS (FR-01.02) with the trigger method "automatic".
Source	Feature Document 7.2.4; survey (55%); scope document
Rationale	An automatic decision must not send an irreversible alert without a chance to stop it.
Business Rule	BR-01, BR-02
Dependencies	FR-02.03, FR-01.02
Priority	High
Acceptance Criteria	• The vibration lasts 20 seconds and no sound is played. • Tapping cancel stops the vibration and sends nothing. • Without a tap the SOS starts after 20 seconds with trigger "automatic".

Table 22: Specification of FR-02.05: On-Device Processing Guarantee

Attribute	Required Information
Identifier	FR-02.05
Title	On-Device Processing Guarantee
Requirement	**System perspective:** The system shall confine the audio buffers, classifier output and sensor windows of this module to the device: the module shall make no network request and shall write no audio or sensor data to persistent storage.
Source	Feature Document 7.2.5; survey (55%); scope document
Rationale	Users consent to listening only because nothing leaves the phone.
Business Rule	BR-07, BR-08
Dependencies	FR-02.01, FR-02.02, FR-02.03
Priority	High
Acceptance Criteria	• A network capture during detection shows no traffic from the module. • Inspection of device storage after a detection shows no audio or sensor files.

3.2.3 MOD-03 Voice Activation and Safe-Phrase Engine

Table 23: Specification of FR-03.01: Safe-Phrase Enrolment

Attribute	Required Information
Identifier	FR-03.01
Title	Safe-Phrase Enrolment
Requirement	**User perspective:** The Primary User shall be able to enter a safe phrase and confirm it by speaking it three times. **System perspective:** When the user submits a phrase of two to five words, the system shall check that it is not empty and differs from the duress phrase, shall collect three spoken samples to set the detection sensitivity, and shall store the phrase and its sensitivity on the device. If a sample is not recognised, the system shall ask the user to repeat it.

Attribute	Required Information
Source	Feature Document 7.3.1; survey (secret phrase 58%)
Rationale	The user chooses a phrase that is memorable and that others cannot guess.
Business Rule	BR-07, BR-09
Dependencies	FR-15.02
Priority	High
Acceptance Criteria	• A phrase with one word or more than five words is rejected. • A phrase equal to the duress phrase is rejected. • After three recognised samples the phrase is saved.

Table 24: Specification of FR-03.02: Duress-Phrase Enrolment

Attribute	Required Information
Identifier	FR-03.02
Title	Duress-Phrase Enrolment
Requirement	**User perspective:** The Primary User shall be able to enter a second phrase, different from the safe phrase, that starts a silent SOS. **System perspective:** When the user submits the duress phrase, the system shall apply the same checks and sampling as FR-03.01 and shall additionally check that the phrase is not a substring of, and does not contain, the safe phrase.
Source	Feature Document 7.3.2; survey (secret phrase 58%)
Rationale	A second phrase lets the user call for help silently while appearing to comply.
Business Rule	BR-03, BR-07
Dependencies	FR-03.01
Priority	High
Acceptance Criteria	• A duress phrase that contains the safe phrase is rejected. • After three recognised samples the phrase is saved.

Table 25: Specification of FR-03.03: Offline Keyword Spotting

Attribute	Required Information
Identifier	FR-03.03
Title	Offline Keyword Spotting
Requirement	**System perspective:** While voice activation is enabled, the system shall run an on-device keyword-spotting engine that listens for the enrolled phrases, needs no network, no account and no access key, performs no general speech transcription and stores no audio.
Source	Feature Document 7.3.3; survey (secret phrase 58%)
Rationale	Voice activation must work where there is no connection.
Business Rule	BR-07, BR-08, BR-09
Dependencies	FR-03.01, FR-03.02, FR-15.02
Priority	High
Acceptance Criteria	• With the network disabled, a spoken safe phrase is detected. • Other speech does not produce a detection. • No audio is written to storage.

Table 26: Specification of FR-03.04: Voice-Triggered SOS

Attribute	Required Information
Identifier	FR-03.04
Title	Voice-Triggered SOS
Requirement	**System perspective:** When the safe phrase is detected outside a confirmation context, the system shall start the confirmation countdown of FR-02.04 and then an SOS in the user's default mode with trigger "voice". When the duress phrase is detected, the system shall start the same countdown and then a silent SOS with trigger "voice".
Source	Feature Document 7.3.4; survey (secret phrase 58%)
Rationale	Voice triggers reuse the same pipeline as automatic detection, so every trigger behaves in the same way.
Business Rule	BR-01, BR-02, BR-03
Dependencies	FR-03.03, FR-02.04
Priority	High
Acceptance Criteria	• The safe phrase starts the countdown and then a loud or silent SOS according to the default mode. • The duress phrase always results in a silent SOS. • Cancelling during the countdown sends nothing.

Table 27: Specification of FR-03.05: Shared Duress-Confirmation Hook

Attribute	Required Information
Identifier	FR-03.05
Title	Shared Duress-Confirmation Hook
Requirement	**System perspective:** The system shall expose phrase detections as events to other modules. When the stop-sharing confirmation of FR-05.02 is open, the safe phrase shall be delivered to that module as a confirmation and shall not start an SOS. When the duress phrase is detected the system shall inform Decoy Mode (FR-06.01).
Source	Feature Document 7.3.5; survey (secret phrase 58%)
Rationale	One engine for all duress-sensitive actions keeps their behaviour consistent.
Business Rule	BR-01, BR-11, BR-28
Dependencies	FR-03.03, FR-05.02, FR-06.01
Priority	High
Acceptance Criteria	• The safe phrase spoken on the stop-sharing screen stops sharing and starts no SOS. • The same phrase spoken elsewhere starts the voice SOS countdown. • The duress phrase causes the decoy screen to appear.

3.2.4 MOD-04 Family Circle Management

Table 28: Specification of FR-04.01: Circle Creation and Bilateral Invitation

Attribute	Required Information
Identifier	FR-04.01
Title	Circle Creation and Bilateral Invitation

Attribute	Required Information
Requirement	**User perspective:** The Primary User shall be able to create a family circle and invite a person by phone number, and the invited person shall be able to accept or decline. **System perspective:** When a circle is created or an invitation is sent, the system shall store the invitation as pending and shall start no sharing. Sharing between the two people shall begin only after the invited person accepts and the inviter's own sharing is enabled. A pending invitation shall expire after 7 days.
Source	Feature Document 7.4.1; survey (family map 68%); scope document
Rationale	Both people must agree before anyone can see anyone's location.
Business Rule	BR-10
Dependencies	FR-14.01
Priority	High
Acceptance Criteria	• No location is shared while the invitation is pending. • Sharing begins after the invitee accepts. • A declined or expired invitation leaves no sharing.

Table 29: Specification of FR-04.02: Circle Membership List

Attribute	Required Information
Identifier	FR-04.02
Title	Circle Membership List
Requirement	**User perspective:** The Primary User shall be able to view all members of a circle. **System perspective:** The system shall show each member's name, current sharing status (sharing or stopped) and the time of the last location update, and shall update the list in real time.
Source	Feature Document 7.4.2; survey (family map 68%); scope document
Rationale	Members must always be able to see who is in the circle and who is sharing.
Business Rule	BR-13
Dependencies	FR-05.05
Priority	High
Acceptance Criteria	• Each member appears with a status and a last-update time. • A status change on one device appears on the others within the target of NFR-PER-04.

Table 30: Specification of FR-04.03: Leave a Circle

Attribute	Required Information
Identifier	FR-04.03
Title	Leave a Circle
Requirement	**User perspective:** The Primary User shall be able to leave a circle completely. **System perspective:** When the user confirms, the system shall remove the user from the circle, stop publishing their location and delete their stored location from the circle. Leaving shall be separate from stopping sharing. The system shall not send a notification about the departure.
Source	Feature Document 7.4.3; survey (family map 68%); scope document
Rationale	A person must be able to end their membership without anyone's approval.
Business Rule	BR-14
Dependencies	FR-04.01
Priority	High

Attribute	Required Information
Acceptance Criteria	• After leaving, the user no longer appears in the other members' list. • The stored location of the user is deleted. • No push notification about leaving is sent.

3.2.5 MOD-05 Location Sharing and Privacy Controls

Table 31: Specification of FR-05.01: Movement-Based Location Updates

Attribute	Required Information
Identifier	FR-05.01
Title	Movement-Based Location Updates
Requirement	**System perspective:** While a member's sharing is enabled, the system shall publish the member's location when the device has moved more than the movement threshold since the last published location, and shall not run continuous GPS polling.
Source	Feature Document 7.5.1; survey (13% forced-sharing barrier); scope document
Rationale	Updating on significant movement saves battery.
Business Rule	BR-13
Dependencies	FR-04.01, FR-15.02
Priority	High
Acceptance Criteria	• A stationary device publishes no new location. • A move beyond the threshold publishes a location. • The published document holds a time stamp.

Table 32: Specification of FR-05.02: Opt-Out by Safe Phrase

Attribute	Required Information
Identifier	FR-05.02
Title	Opt-Out by Safe Phrase
Requirement	**User perspective:** The Primary User shall be able to stop sharing their location by speaking the safe phrase on the stop-sharing screen. **System perspective:** When the safe phrase is recognised on the stop-sharing confirmation, the system shall disable the user's sharing immediately, shall require no approval from any other person and shall notify no other member. If the phrase is not recognised within 15 seconds, the screen shall close and sharing shall continue.
Source	Feature Document 7.5.2; survey (13% forced-sharing barrier); scope document
Rationale	Stopping must be quick and must not depend on anyone else.
Business Rule	BR-11
Dependencies	FR-03.05, FR-05.01
Priority	High
Acceptance Criteria	• The safe phrase stops publication of location at once. • No message is sent to other members. • An unrecognised phrase leaves sharing on.

Table 33: Specification of FR-05.03: Private Opt-Out Confirmation

Attribute	Required Information
Identifier	FR-05.03

Attribute	Required Information
Title	Private Opt-Out Confirmation
Requirement	**System perspective:** After sharing stops, the system shall show a confirmation only on the device of the member who stopped it. The system shall create no message, notification or visible event for other members.
Source	Feature Document 7.5.3; survey (13% forced-sharing barrier); scope document
Rationale	A visible "opted out" message could provoke confrontation.
Business Rule	BR-11
Dependencies	FR-05.02
Priority	High
Acceptance Criteria	• The confirmation appears only on the stopping member's device. • Other members' devices show no event when sharing stops.

Table 34: Specification of FR-05.04: Last-Known Location Display

Attribute	Required Information
Identifier	FR-05.04
Title	Last-Known Location Display
Requirement	**User perspective:** A Family Circle Member shall be able to see where another member last shared their location. **System perspective:** After a member stops sharing, the system shall show to the other members only the last published location with its time stamp, labelled "Not live", and shall publish no further updates.
Source	Feature Document 7.5.4; survey (13% forced-sharing barrier); scope document
Rationale	A stale location with a clear time stamp cannot be mistaken for live tracking.
Business Rule	BR-12
Dependencies	FR-05.01
Priority	High
Acceptance Criteria	• The marker is labelled "Not live" with the time of the last update. • The marker does not move after sharing stops.

Table 35: Specification of FR-05.05: Real-Time Sharing Status

Attribute	Required Information
Identifier	FR-05.05
Title	Real-Time Sharing Status
Requirement	**User perspective:** A Family Circle Member shall be able to see at all times whether they and the other members are sharing. **System perspective:** The system shall propagate each sharing change to the circle through real-time listeners, shall show a persistent indicator on the member's own device while their location is being shared, and shall provide no mode that shares location without that indicator. Only the member shall be able to resume their own sharing.
Source	Feature Document 7.5.5; survey (13% forced-sharing barrier); scope document
Rationale	Hidden or silent tracking must be impossible.
Business Rule	BR-13
Dependencies	FR-04.02

Attribute	Required Information
Priority	High
Acceptance Criteria	• The indicator is present on the sharing member's device whenever location is published. • No other member can switch another member's sharing on. • A change is visible on the other devices within the target of NFR-PER-04.

3.2.6 MOD-06 Decoy Mode

Table 36: Specification of FR-06.01: Disguised Interface

Attribute	Required Information
Identifier	FR-06.01
Title	Disguised Interface
Requirement	**User perspective:** The Primary User shall be able to turn on Decoy Mode in the settings. **System perspective:** When Decoy Mode is on, and when a silent SOS is started by the duress phrase, the system shall show a neutral calculator screen in place of the real interface whenever the application is opened. The decoy screen shall contain no reference to safety.
Source	Feature Document 7.6.1; survey (decoy 87%); interview (MBBS student)
Rationale	If someone forces the user to unlock the phone, the application must not reveal its purpose.
Business Rule	BR-28
Dependencies	FR-03.05
Priority	High
Acceptance Criteria	• With Decoy Mode on, opening the application shows the calculator. • The calculator performs basic arithmetic. • A duress-phrase SOS switches the application to the decoy screen.

Table 37: Specification of FR-06.02: Hidden Re-entry Gesture

Attribute	Required Information
Identifier	FR-06.02
Title	Hidden Re-entry Gesture
Requirement	**User perspective:** The Primary User shall be able to return to the real application by a hidden gesture. **System perspective:** When the user presses and holds the equals key of the decoy calculator for 2 seconds, the system shall show the real interface. No other action shall reveal it.
Source	Feature Document 7.6.2; survey (decoy 87%); interview (MBBS student)
Rationale	The genuine user must be able to get back without an obvious control.
Business Rule	BR-28
Dependencies	FR-06.01
Priority	High
Acceptance Criteria	• A 2-second hold on the equals key opens the real application. • A short press on the equals key only calculates.

Table 38: Specification of FR-06.03: Background Pass-Through

Attribute	Required Information
Identifier	FR-06.03

Attribute	Required Information
Title	Background Pass-Through
Requirement	**System perspective:** While the decoy screen is shown, the system shall continue SOS triggers, voice detection, location updates and evidence recording without any visible sign.
Source	Feature Document 7.6.3; survey (decoy 87%); interview (MBBS student)
Rationale	Protection must not stop because the interface is disguised.
Business Rule	BR-28
Dependencies	FR-06.01, FR-03.03
Priority	High
Acceptance Criteria	• The duress phrase starts a silent SOS while the decoy screen is shown. • Location updates continue under the decoy screen.

3.2.7 MOD-07 Danger Heatmap

Table 39: Specification of FR-07.01: Incident Report Form

Attribute	Required Information
Identifier	FR-07.01
Title	Incident Report Form
Requirement	**User perspective:** The Primary User shall be able to report an unsafe incident by choosing a category (harassment, theft or felt unsafe), confirming or editing the location and optionally adding a note of up to 280 characters. **System perspective:** When the user submits a report, the system shall validate the category and the location, fill the location from the current position by default, store the report with a time stamp and the geohash of its location, and show a confirmation. If validation fails, the system shall report the problem and keep the entered data.
Source	Feature Document 7.7.1; survey (unsafe-areas map 84%)
Rationale	Crowd-sourced reports are the data of the heatmap.
Business Rule	BR-15, BR-17
Dependencies	FR-14.01, FR-07.05
Priority	Medium
Acceptance Criteria	• A report without a category is rejected. • The location is filled automatically and can be moved on the map. • A valid report is stored with a time stamp and geohash. • A note longer than 280 characters is rejected.

Table 40: Specification of FR-07.02: Geohash Grid Aggregation

Attribute	Required Information
Identifier	FR-07.02
Title	Geohash Grid Aggregation
Requirement	**System perspective:** The system shall assign every report to the geohash cell of precision 7 that contains its location and shall keep, for each cell, the number of reports per category and the weighted score.
Source	Feature Document 7.7.2; survey (unsafe-areas map 84%)
Rationale	Fixed cells hide exact positions and make density comparable.
Business Rule	BR-17

Attribute	Required Information
Dependencies	FR-07.01
Priority	Medium
Acceptance Criteria	• Two reports in the same cell increase that cell's count by two. • Reports in different cells are counted separately.

Table 41: Specification of FR-07.03: Recency Weighting

Attribute	Required Information
Identifier	FR-07.03
Title	Recency Weighting
Requirement	**System perspective:** The system shall weight each report by 0.5 raised to the power of its age divided by 90 days, and shall compute the cell score as the sum of the weights.
Source	Feature Document 7.7.3; survey (unsafe-areas map 84%)
Rationale	The map should show current risk and not permanently mark an area.
Business Rule	BR-16
Dependencies	FR-07.02
Priority	Medium
Acceptance Criteria	• A report that is 90 days old counts half of a new report. • A report that is 180 days old counts one quarter.

Table 42: Specification of FR-07.04: Heatmap Overlay

Attribute	Required Information
Identifier	FR-07.04
Title	Heatmap Overlay
Requirement	**User perspective:** The Primary User shall be able to view a map in which each cell is coloured from green to red by its score, and to tap a cell to see the report categories and counts. **System perspective:** The system shall draw the cells on the map, scale the colour by the score, and on a tap show the category counts without any information that identifies a reporter. When there is no data connection the system shall show the last downloaded data with the time of the download.
Source	Feature Document 7.7.4; survey (unsafe-areas map 84%)
Rationale	The overlay turns reports into a view of the safer and less safe areas.
Business Rule	BR-16, BR-17
Dependencies	FR-07.03
Priority	Medium
Acceptance Criteria	• Cells with a higher score are drawn in a redder colour. • The tap panel shows category counts and no reporter information. • Offline, the map shows the last downloaded data with its time.

Table 43: Specification of FR-07.05: Rate Limits and Abuse Checks

Attribute	Required Information
Identifier	FR-07.05
Title	Rate Limits and Abuse Checks

Attribute	Required Information
Requirement	**System perspective:** The system shall reject a sixth report from the same user within 24 hours, shall reject a report by the same user within 100 m and one hour of a previous report, and shall place a report in the moderation queue when more than 10 reports reach one cell within one hour.
Source	Feature Document 7.7.5; survey (unsafe-areas map 84%)
Rationale	Rate limits stop spam and malicious flagging of an area.
Business Rule	BR-15
Dependencies	FR-16.02
Priority	Medium
Acceptance Criteria	• The sixth report in 24 hours is rejected with a message. • A near-duplicate report is rejected. • A burst of reports in one cell appears in the moderation queue.

3.2.8 MOD-08 Near Help

Table 44: Specification of FR-08.01: Verified-Helper Registration

Attribute	Required Information
Identifier	FR-08.01
Title	Verified-Helper Registration
Requirement	**User perspective:** The Primary User shall be able to apply to become a Verified Helper by submitting their name, phone number and a photo of an identity document. **System perspective:** When the user submits the application, the system shall store it with the status "pending", shall store the identity image so that only administrators can read it, and shall make the user a Verified Helper only after an administrator approves it. After the decision the system shall delete the identity image.
Source	Feature Document 7.8.1; survey (58%)
Rationale	A helper network is an attack surface if anyone can join it.
Business Rule	BR-18
Dependencies	FR-14.01, FR-16.03
Priority	Medium
Acceptance Criteria	• A new application has the status "pending". • The user receives help requests only after approval. • The identity image is not readable by other users and is deleted after the decision.

Table 45: Specification of FR-08.02: Help Request Broadcast

Attribute	Required Information
Identifier	FR-08.02
Title	Help Request Broadcast
Requirement	**User perspective:** The Primary User shall be able to request nearby help. **System perspective:** When a help request is made, manually or as part of an SOS when the user has enabled it, the system shall send a push notification to every Verified Helper within the set radius (default 1 km). The notification shall show the approximate distance and age of the request and shall not show the exact location.
Source	Feature Document 7.8.2; survey (58%)
Rationale	Nearby people can reach a person faster than distant trustees.
Business Rule	BR-19, BR-32

Attribute	Required Information
Dependencies	FR-08.01, FR-12.01
Priority	Medium
Acceptance Criteria	• Helpers inside the radius receive a notification and helpers outside do not. • The notification shows distance and age and not the exact location.

Table 46: Specification of FR-08.03: Accept or Decline Screen

Attribute	Required Information
Identifier	FR-08.03
Title	Accept or Decline Screen
Requirement	**User perspective:** A Verified Helper shall be able to accept or decline a help request. **System perspective:** When a helper accepts, the system shall show the requester's exact location to that helper, notify the requester and record an acknowledgement. When a helper declines, the system shall record nothing visible to the requester.
Source	Feature Document 7.8.3; survey (58%)
Rationale	Responders choose whether to respond.
Business Rule	BR-19
Dependencies	FR-08.02, FR-19.01
Priority	Medium
Acceptance Criteria	• After acceptance the helper sees the exact location and the requester is notified. • A decline creates no message for the requester.

Table 47: Specification of FR-08.04: Offline State

Attribute	Required Information
Identifier	FR-08.04
Title	Offline State
Requirement	**System perspective:** When there is no data connection, the system shall show "unavailable, no connection" on the Near Help screens and shall not drop a pending request silently. A request made while offline shall be queued with its creation time and sent when a connection returns, and the SOS shall continue by SMS to the trustees.
Source	Feature Document 7.8.4; survey (58%)
Rationale	Near Help cannot work without a connection, and the user must know that.
Business Rule	BR-05
Dependencies	FR-12.03
Priority	Medium
Acceptance Criteria	• Offline, the Near Help screen shows the unavailable message. • A queued request is sent when the connection returns and shows its age to helpers. • SMS dispatch to trustees is unaffected.

3.2.9 MOD-09 Content Library Management

Table 48: Specification of FR-09.01: Curated Content

Attribute	Required Information
Identifier	FR-09.01

Attribute	Required Information
Title	Curated Content
Requirement	**System perspective:** The system shall provide articles, videos and links on prevention and post-incident care, each with a title, category and summary, in the categories Prevention, Emergency Response, After-Incident Care and Emotional Support.
Source	Feature Document 7.9.1; scope document; survey (68%)
Rationale	Reliable guidance supports prevention and recovery.
Business Rule	BR-20
Dependencies	-
Priority	Medium
Acceptance Criteria	• Every item has a title, category and summary. • Items are grouped into the four categories.

Table 49: Specification of FR-09.02: Offline Bundling

Attribute	Required Information
Identifier	FR-09.02
Title	Offline Bundling
Requirement	**System perspective:** The system shall store the article text, titles, summaries and metadata in the application package so that they can be read with no connection. Videos and external links shall be listed offline and shall open when a connection exists.
Source	Feature Document 7.9.2; scope document; survey (68%)
Rationale	Users may need guidance where there is no connection.
Business Rule	BR-20
Dependencies	FR-13.02
Priority	Medium
Acceptance Criteria	• With the network disabled all articles open. • A video or link entry shows a notice that a connection is needed.

Table 50: Specification of FR-09.03: Browsing, Filters and Bookmarks

Attribute	Required Information
Identifier	FR-09.03
Title	Browsing, Filters and Bookmarks
Requirement	**User perspective:** The Primary User shall be able to browse the library, filter by category and bookmark items. **System perspective:** The system shall list items by category, apply the chosen filter, store bookmarks on the device and show them in a bookmarks list.
Source	Feature Document 7.9.3; scope document; survey (68%)
Rationale	Users need to find and return to useful content.
Business Rule	BR-20
Dependencies	FR-09.01
Priority	Medium
Acceptance Criteria	• The filter shows only items of the chosen category. • A bookmarked item appears in the bookmarks list after the application restarts.

3.2.10 MOD-10 Semantic Search Engine

Table 51: Specification of FR-10.01: Precomputed Content Embeddings

Attribute	Required Information
Identifier	FR-10.01
Title	Precomputed Content Embeddings
Requirement	**System perspective:** The system shall include, for every library item, an embedding computed before release with the same model that is used for queries, and shall load these embeddings from the application package.
Source	Feature Document 7.10.1; scope document; survey (68%)
Rationale	Precomputing avoids heavy work on the phone.
Business Rule	BR-20
Dependencies	FR-09.02
Priority	Medium
Acceptance Criteria	• The package contains one embedding for each library item. • The embedding dimension matches the query model.

Table 52: Specification of FR-10.02: On-Device Query Embedding

Attribute	Required Information
Identifier	FR-10.02
Title	On-Device Query Embedding
Requirement	**User perspective:** The Primary User shall be able to search the library by typing a question or description in their own words. **System perspective:** When the user submits a query, the system shall convert it into an embedding on the device with a compact sentence-embedding model and shall make no network request.
Source	Feature Document 7.10.2; scope document; survey (68%)
Rationale	Query text can be sensitive and must not leave the phone.
Business Rule	BR-20
Dependencies	FR-10.01
Priority	Medium
Acceptance Criteria	• The query embedding is computed with the network disabled. • No network request is made during search.

Table 53: Specification of FR-10.03: Cosine-Similarity Ranking

Attribute	Required Information
Identifier	FR-10.03
Title	Cosine-Similarity Ranking
Requirement	**System perspective:** The system shall compute the cosine similarity between the query embedding and every content embedding and shall rank the items from the highest similarity to the lowest.
Source	Feature Document 7.10.3; scope document; survey (68%)
Rationale	Ranking by meaning finds relevant content even when the words differ.
Business Rule	BR-20
Dependencies	FR-10.02

Attribute	Required Information
Priority	Medium
Acceptance Criteria	• An item whose meaning matches the query ranks above an unrelated item. • The ranking is repeatable for the same query.

Table 54: Specification of FR-10.04: Keyword-Search Fallback

Attribute	Required Information
Identifier	FR-10.04
Title	Keyword-Search Fallback
Requirement	**System perspective:** When the embedding model cannot be loaded, or when the highest similarity is below 0.30, the system shall run a keyword search over titles, summaries and text and shall show those results with a notice.
Source	Feature Document 7.10.4; scope document; survey (68%)
Rationale	Search must still work when the model fails or the query has no close meaning match.
Business Rule	BR-20
Dependencies	FR-09.01
Priority	Medium
Acceptance Criteria	• With the model file missing, a keyword search returns matching items. • A query with a top similarity below 0.30 returns keyword results.

Table 55: Specification of FR-10.05: Ranked Result Cards

Attribute	Required Information
Identifier	FR-10.05
Title	Ranked Result Cards
Requirement	**User perspective:** The Primary User shall be able to open or bookmark a search result. **System perspective:** The system shall show each result as a card with the title, category, summary and a relevance indicator derived from the similarity, and shall provide open and bookmark actions.
Source	Feature Document 7.10.5; scope document; survey (68%)
Rationale	Users should see how relevant each result is.
Business Rule	BR-20
Dependencies	FR-10.03, FR-09.03
Priority	Medium
Acceptance Criteria	• Each card shows a relevance indicator. • Open shows the item and bookmark adds it to the bookmarks list.

3.2.11 MOD-11 Emergency Services Directory

Table 56: Specification of FR-11.01: Localized Directory

Attribute	Required Information
Identifier	FR-11.01
Title	Localized Directory

Attribute	Required Information
Requirement	**System perspective:** The system shall provide, in the application package, a directory of hospitals, police stations, helplines and emergency numbers for Pakistan, including Rescue 1122 and women's helplines, each with a name, category, phone number and, for hospitals and police stations, coordinates.
Source	Feature Document 7.11.1; survey (84%)
Rationale	Users need local emergency contacts at hand.
Business Rule	BR-21
Dependencies	FR-13.02
Priority	Medium
Acceptance Criteria	• The directory contains Rescue 1122 and at least one women's helpline. • Hospital and police entries contain coordinates.

Table 57: Specification of FR-11.02: One-Tap Call

Attribute	Required Information
Identifier	FR-11.02
Title	One-Tap Call
Requirement	**User perspective:** The Primary User shall be able to call any directory entry with one tap. **System perspective:** When the user taps the call control of an entry, the system shall place the call to its number, or open the dialer with the number filled in if the call permission has not been granted.
Source	Feature Document 7.11.2; survey (84%)
Rationale	In an emergency time matters.
Business Rule	BR-21
Dependencies	FR-11.01
Priority	Medium
Acceptance Criteria	• One tap places the call when permission is granted. • Without permission the dialer opens with the number filled in.

Table 58: Specification of FR-11.03: Nearest Facilities First

Attribute	Required Information
Identifier	FR-11.03
Title	Nearest Facilities First
Requirement	**System perspective:** When a location is available, the system shall order hospitals and police stations by distance from the user; otherwise it shall order entries by category and name.
Source	Feature Document 7.11.3; survey (84%)
Rationale	The nearest help is the most useful.
Business Rule	BR-21
Dependencies	FR-11.01, FR-13.01
Priority	Medium
Acceptance Criteria	• With location, the nearest hospital is first. • Without location, entries are ordered by category and name.

3.2.12 MOD-12 Tiered Delivery System

Table 59: Specification of FR-12.01: Connectivity Tier Detection

Attribute	Required Information
Identifier	FR-12.01
Title	Connectivity Tier Detection
Requirement	**System perspective:** The system shall classify the device connectivity as Tier 1 (no data connection), Tier 2 (any data connection) or Tier 3 (good data connection) and shall update the tier when connectivity changes. The tier shall be shown in the status strip of the home screen.
Source	Feature Document 7.12.1; survey (internet barrier 71%)
Rationale	Delivery must adapt to what the network can do.
Business Rule	BR-05
Dependencies	-
Priority	High
Acceptance Criteria	• With data disabled the tier is 1. • With a reachable backend over a slow link the tier is 2. • With a fast link the tier is 3.

Table 60: Specification of FR-12.02: SMS Delivery at Tier 1

Attribute	Required Information
Identifier	FR-12.02
Title	SMS Delivery at Tier 1
Requirement	**System perspective:** At Tier 1 the system shall send the SOS by SMS to every trustee through the device's SMS capability and shall not depend on any data connection. The SMS shall contain the user's name, the preset text, the coordinates and the time.
Source	Feature Document 7.12.2; survey (internet barrier 71%)
Rationale	SMS is the only channel that works with no data.
Business Rule	BR-05, BR-06
Dependencies	FR-01.02
Priority	High
Acceptance Criteria	• With mobile data and Wi-Fi off, an SOS sends SMS to every trustee. • The SMS contains name, text, coordinates and time.

Table 61: Specification of FR-12.03: Queue and Retry

Attribute	Required Information
Identifier	FR-12.03
Title	Queue and Retry
Requirement	**System perspective:** When a channel cannot be delivered, the system shall store the message in the on-device outbound queue and shall retry automatically when the connection returns, until it is delivered, and shall update the SOS event log. The queue shall survive closing the application and restarting the device.
Source	Feature Document 7.12.3; survey (internet barrier 71%)
Rationale	Nothing created offline should be lost.
Business Rule	BR-05

Attribute	Required Information
Dependencies	FR-13.02, FR-01.06
Priority	High
Acceptance Criteria	• A message queued offline is sent after the connection returns. • Queued messages remain after the device restarts. • The event log shows the status change.

3.2.13 MOD-13 Offline Data Caching

Table 62: Specification of FR-13.01: Last-Known Location Cache

Attribute	Required Information
Identifier	FR-13.01
Title	Last-Known Location Cache
Requirement	**System perspective:** The system shall keep the most recent location fix with its time on the device. When an SOS starts and a fresh fix is not obtained within 10 seconds, the system shall use the cached location and shall state its age in the message.
Source	Feature Document 7.13.1; survey (internet barrier 71%)
Rationale	An alert with an older location is better than an alert without one.
Business Rule	BR-06
Dependencies	-
Priority	High
Acceptance Criteria	• With GPS unavailable, the SOS uses the cached location. • The message states how old the location is.

Table 63: Specification of FR-13.02: On-Device Database

Attribute	Required Information
Identifier	FR-13.02
Title	On-Device Database
Requirement	**System perspective:** The system shall store the library content, the directory, the outbound queue, the SOS event log and the map data for up to three user-selected frequent areas in an on-device database and files. The map data shall be downloaded while online from an open map-data source that permits offline storage.
Source	Feature Document 7.13.2; survey (internet barrier 71%)
Rationale	Offline operation needs local data.
Business Rule	BR-05, BR-20
Dependencies	-
Priority	High
Acceptance Criteria	• With the network disabled the library, directory and SOS log can be read. • A frequent area downloaded online can be shown offline.

3.2.14 MOD-14 Authentication and Account Management

Table 64: Specification of FR-14.01: Phone-Number Sign-Up and Login

Attribute	Required Information
Identifier	FR-14.01
Title	Phone-Number Sign-Up and Login
Requirement	**User perspective:** The Primary User shall be able to sign up and log in with their mobile phone number. **System perspective:** When the user enters a valid number, the system shall send a one-time code through Firebase Authentication and, when the correct code is entered, shall sign the user in and create the account if it does not exist. A wrong code shall be rejected, and the number shall be locked for sending codes for 10 minutes after five wrong attempts.
Source	Feature Document 7.14.1; scope document
Rationale	Phone numbers are the usual identity for users in Pakistan.
Business Rule	BR-22
Dependencies	DEP-1
Priority	High
Acceptance Criteria	• A correct code signs in the user. • A wrong code is rejected with a message. • Five wrong attempts lock further attempts for 10 minutes.

Table 65: Specification of FR-14.02: Session Handling

Attribute	Required Information
Identifier	FR-14.02
Title	Session Handling
Requirement	**System perspective:** The system shall keep the user signed in, renew the session token automatically, and require a new login if the token is revoked. The SOS, detection, voice, library, directory and evidence functions shall not require a valid session to operate offline.
Source	Feature Document 7.14.2; scope document
Rationale	Safety functions must not fail because a session expired.
Business Rule	BR-22
Dependencies	FR-14.01
Priority	High
Acceptance Criteria	• The user stays signed in after restarting the application. • A revoked token leads to the login screen. • An SOS can be started offline with an expired token.

Table 66: Specification of FR-14.03: Profile and Settings

Attribute	Required Information
Identifier	FR-14.03
Title	Profile and Settings
Requirement	**User perspective:** The Primary User shall be able to edit their name, the emergency message template, the linked trustees and the default SOS mode. **System perspective:** The system shall validate and save these settings, and shall use the template as the preset text of every SOS. A template shall not be empty and shall not exceed 160 characters.
Source	Feature Document 7.14.3; scope document

Attribute	Required Information
Rationale	The alert text must be personal and short enough for one SMS.
Business Rule	BR-22
Dependencies	FR-01.05
Priority	High
Acceptance Criteria	• An empty template is rejected. • The saved template appears in the next SOS message.

Table 67: Specification of FR-14.04: Account Recovery

Attribute	Required Information
Identifier	FR-14.04
Title	Account Recovery
Requirement	**User perspective:** The Primary User shall be able to recover the account on a new device after losing the old one. **System perspective:** When the user logs in on a new device with the same phone number and the correct code, the system shall restore the account data held on the server, shall end the sessions on all other devices and shall report that evidence recordings, which exist only on the old device, cannot be restored.
Source	Feature Document 7.14.4; scope document
Rationale	A lost phone should not mean a lost account.
Business Rule	BR-22, BR-23
Dependencies	FR-14.01
Priority	High
Acceptance Criteria	• The new device shows the profile, trustees and circles. • The old device is signed out. • The user is told that evidence recordings are not restored.

3.2.15 MOD-15 Consent and Privacy Controls

Table 68: Specification of FR-15.01: Onboarding Consent

Attribute	Required Information
Identifier	FR-15.01
Title	Onboarding Consent
Requirement	**User perspective:** The Primary User shall be able to read, and accept or decline, a plain-language statement of what the detection and voice engines listen for. **System perspective:** During onboarding the system shall explain that the microphone is used to detect distress sounds and the enrolled phrases, that this processing stays on the device, that no audio is stored by these engines, that location is shared only as the user chooses, and that evidence recording begins only after an SOS starts. The system shall enable no microphone function until the user accepts.
Source	Feature Document 7.15.1; interviews (trust in data handling)
Rationale	Listening needs informed consent.
Business Rule	BR-09
Dependencies	-
Priority	High

Attribute	Required Information
Acceptance Criteria	• The consent text covers detection, voice, location and evidence recording. • Declining leaves the microphone functions off. • The acceptance and its time are stored.

Table 69: Specification of FR-15.02: Permission and Feature Toggles

Attribute	Required Information
Identifier	FR-15.02
Title	Permission and Feature Toggles
Requirement	**User perspective:** The Primary User shall be able to turn microphone detection, location sharing and voice activation on or off separately at any time. **System perspective:** When a toggle changes, the system shall apply it immediately, shall stop the related service when the toggle is turned off and shall ask for the required Android permission when it is turned on.
Source	Feature Document 7.15.2; interviews (trust in data handling)
Rationale	Users must stay in control of each sensor.
Business Rule	BR-09
Dependencies	FR-15.01
Priority	High
Acceptance Criteria	• Turning microphone detection off stops the monitoring service. • Turning location sharing off stops location publication. • Each toggle works independently of the others.

Table 70: Specification of FR-15.03: Privacy Summary

Attribute	Required Information
Identifier	FR-15.03
Title	Privacy Summary
Requirement	**User perspective:** The Primary User shall be able to view a summary of what the application stores, what stays on the device and what reaches the backend. **System perspective:** The system shall present a summary screen that lists, in plain language, the data held on the server (profile, trustees, circles, shared locations, reports and helper status), the data that stays on the device (audio buffers, evidence recordings, library, models and event log) and the data sent to external channels during an SOS.
Source	Feature Document 7.15.3; interviews (trust in data handling)
Rationale	Transparency builds trust.
Business Rule	BR-07, BR-32
Dependencies	-
Priority	High
Acceptance Criteria	• The summary names the three categories of data. • The summary matches the behaviour of the application.

3.2.16 MOD-16 Admin Dashboard

Table 71: Specification of FR-16.01: User Overview

Attribute	Required Information
Identifier	FR-16.01

Attribute	Required Information
Title	User Overview
Requirement	**User perspective:** The Administrator shall be able to view the number of registrations over time and the verification status of helpers. **System perspective:** The system shall show registration counts by day, counts of helper applications by status and a user list with masked phone numbers. It shall show no message content, location or evidence.
Source	Feature Document 7.16.1; scope document
Rationale	Administrators need an overview without access to private content.
Business Rule	BR-31
Dependencies	FR-16.05
Priority	Medium
Acceptance Criteria	• Phone numbers are masked. • No location or evidence data appears.

Table 72: Specification of FR-16.02: Moderation Queue

Attribute	Required Information
Identifier	FR-16.02
Title	Moderation Queue
Requirement	**User perspective:** The Administrator shall be able to review flagged heatmap reports and missing-child reports and approve, remove or suspend the author. **System perspective:** The system shall list flagged reports with their content, let the administrator decide, apply the decision and record the administrator, time and decision.
Source	Feature Document 7.16.2; scope document
Rationale	Crowd-sourced content needs human moderation.
Business Rule	BR-15, BR-27, BR-31
Dependencies	FR-07.05, FR-17.05, FR-16.05
Priority	Medium
Acceptance Criteria	• A flagged report appears in the queue. • A removed report no longer counts in the heatmap. • The decision is logged with administrator and time.

Table 73: Specification of FR-16.03: Helper Review Queue

Attribute	Required Information
Identifier	FR-16.03
Title	Helper Review Queue
Requirement	**User perspective:** The Administrator shall be able to approve, reject or revoke a Verified Helper. **System perspective:** The system shall show each pending application with the identity image, apply the decision, notify the applicant, delete the identity image and record the decision.
Source	Feature Document 7.16.3; scope document
Rationale	Only checked people should receive help requests.
Business Rule	BR-18, BR-31
Dependencies	FR-08.01, FR-16.05
Priority	Medium

Attribute	Required Information
Acceptance Criteria	• An approved helper starts receiving requests. • A revoked helper stops receiving requests. • The identity image is deleted after the decision.

Table 74: Specification of FR-16.04: Health Monitoring

Attribute	Required Information
Identifier	FR-16.04
Title	Health Monitoring
Requirement	**User perspective:** The Administrator shall be able to view delivery success by channel and backend errors. **System perspective:** The system shall aggregate delivery outcomes per channel and shall list backend function errors with time and function name, without user identities.
Source	Feature Document 7.16.4; scope document
Rationale	Reliability of delivery is a core objective and must be observable.
Business Rule	BR-31
Dependencies	FR-01.06, FR-16.05
Priority	Medium
Acceptance Criteria	• Delivery success is shown per channel for a chosen period. • Backend errors are listed with time and function name.

Table 75: Specification of FR-16.05: Administrator Authentication

Attribute	Required Information
Identifier	FR-16.05
Title	Administrator Authentication
Requirement	**System perspective:** The system shall allow access to the admin website only to accounts that have the administrator role, shall sign in with email and password through Firebase Authentication, and shall deny every other account.
Source	Added during specification: needed to protect FR-16.01 to FR-16.04
Rationale	Administrative functions must be separated from ordinary users.
Business Rule	BR-31
Dependencies	DEP-1
Priority	Medium
Acceptance Criteria	• An ordinary user account cannot open any admin page. • An administrator account can.

3.2.17 MOD-17 Missing-Child Report

Table 76: Specification of FR-17.01: Missing-Child Report Form

Attribute	Required Information
Identifier	FR-17.01
Title	Missing-Child Report Form

Attribute	Required Information
Requirement	**User perspective:** The Guardian shall be able to report a missing child by entering the child's name and age, a photo, a description, the last-seen place and time, and the guardian's contact number. **System perspective:** When the guardian submits the form, the system shall validate that all required fields are present, that the age is between 0 and 17, that the photo is a JPEG or PNG of at most 5 MB and that the guardian has confirmed being the child's guardian, and shall create the report with the status "active".
Source	Feature Document 7.17.1; survey (77%)
Rationale	A complete report helps others recognise the child.
Business Rule	BR-25, BR-26, BR-27
Dependencies	FR-14.01
Priority	Medium
Acceptance Criteria	• A report with a missing field is rejected. • A photo larger than 5 MB is rejected. • A valid report has the status "active".

Table 77: Specification of FR-17.02: Alert to Contacts and Nearby Helpers

Attribute	Required Information
Identifier	FR-17.02
Title	Alert to Contacts and Nearby Helpers
Requirement	**System perspective:** When a report becomes active, the system shall send it to the guardian's trustees and by push notification to Verified Helpers within 5 km of the last-seen place. The notification shall show the description, the last-seen place and time and the guardian's contact number.
Source	Feature Document 7.17.2; survey (77%)
Rationale	Quick local attention is most useful in the first hours.
Business Rule	BR-26, BR-32
Dependencies	FR-17.01, FR-08.01, FR-12.01
Priority	Medium
Acceptance Criteria	• Trustees and helpers within 5 km are notified. • Helpers beyond 5 km are not.

Table 78: Specification of FR-17.03: Report Status Handling

Attribute	Required Information
Identifier	FR-17.03
Title	Report Status Handling
Requirement	**User perspective:** The Guardian shall be able to mark a report as found, or renew it. **System perspective:** The system shall set the status to "found" when the guardian marks it, and to "expired" 72 hours after it was created or renewed unless the guardian renews it. When a report is found or expired the system shall stop alerts and shall delete the photo.
Source	Feature Document 7.17.3; survey (77%)
Rationale	Reports must not stay active after the child is found.
Business Rule	BR-25, BR-26
Dependencies	FR-17.01
Priority	Medium

Attribute	Required Information
Acceptance Criteria	• "Found" stops alerts and deletes the photo. • After 72 hours without renewal the status is "expired".

Table 79: Specification of FR-17.04: Hand-Off to Official Channels

Attribute	Required Information
Identifier	FR-17.04
Title	Hand-Off to Official Channels
Requirement	**User perspective:** The Guardian shall be able to call an official missing-child helpline or share the report text. **System perspective:** The system shall provide a call control for the configured helpline number (default 1099) and a share control that opens the Android share sheet with the report text. The system shall make no direct connection to any official system.
Source	Feature Document 7.17.4; survey (77%)
Rationale	Official channels exist and have authority that the application does not.
Business Rule	BR-27
Dependencies	FR-17.01
Priority	Medium
Acceptance Criteria	• The call control dials the configured number. • The share control opens the share sheet with the report text.

Table 80: Specification of FR-17.05: Moderation and Abuse Prevention

Attribute	Required Information
Identifier	FR-17.05
Title	Moderation and Abuse Prevention
Requirement	**System perspective:** The system shall publish a report immediately, shall place every report in the moderation queue, shall limit a user to 3 reports in 24 hours, and, when an administrator removes a report as false, shall remove it from all lists and may suspend the author.
Source	Feature Document 7.17.5; survey (77%)
Rationale	Immediate alerts matter, and false reports must be handled.
Business Rule	BR-27, BR-31
Dependencies	FR-16.02
Priority	Medium
Acceptance Criteria	• Every report appears in the moderation queue. • A fourth report in 24 hours is rejected. • A removed report disappears from all lists.

Table 81: Specification of FR-17.06: Child-Data Privacy

Attribute	Required Information
Identifier	FR-17.06
Title	Child-Data Privacy
Requirement	**System perspective:** The system shall show the child's photo only to the guardian, the alerted trustees and the notified helpers while the report is active, shall store the photo so that no other user can read it, and shall delete it when the report is found or expired.

Attribute	Required Information
Source	Feature Document 7.17.6; survey (77%)
Rationale	Children's images need the strongest protection.
Business Rule	BR-26
Dependencies	FR-17.03
Priority	Medium
Acceptance Criteria	• A user who is not alerted cannot read the photo. • The photo is deleted when the report is found or expired.

3.2.18 MOD-18 Evidence Recording on SOS

Table 82: Specification of FR-18.01: Automatic Recording on SOS

Attribute	Required Information
Identifier	FR-18.01
Title	Automatic Recording on SOS
Requirement	**System perspective:** When an SOS starts by any trigger, the system shall start recording audio from the microphone within 1 second. If the microphone permission is missing or the microphone is in use, the SOS shall continue without recording and the event log shall note it.
Source	Feature Document 7.18.1; survey (77%); interviews
Rationale	Audio can later support the user's account.
Business Rule	BR-23
Dependencies	FR-01.01, FR-15.01
Priority	Medium
Acceptance Criteria	• Recording starts after a manual, an automatic and a voice SOS. • A missing permission does not stop the SOS.

Table 83: Specification of FR-18.02: Encrypted On-Device Storage

Attribute	Required Information
Identifier	FR-18.02
Title	Encrypted On-Device Storage
Requirement	**System perspective:** The system shall encrypt each recording with AES-256-GCM using a key held in the Android Keystore, store it in the private storage of the application, exclude it from backups and never upload it.
Source	Feature Document 7.18.2; survey (77%); interviews
Rationale	Recordings are sensitive and must remain with the user.
Business Rule	BR-23
Dependencies	FR-18.01
Priority	Medium
Acceptance Criteria	• The stored file is unreadable without the key. • No recording is sent over the network. • Another application cannot read the file.

Table 84: Specification of FR-18.03: Evidence List

Attribute	Required Information
Identifier	FR-18.03
Title	Evidence List
Requirement	**User perspective:** The Primary User shall be able to see a list of recordings. **System perspective:** The system shall list each recording with its time, location, trigger method and duration, linked to the SOS event.
Source	Feature Document 7.18.3; survey (77%); interviews
Rationale	The user needs to find the right recording later.
Business Rule	BR-23
Dependencies	FR-18.02, FR-01.06
Priority	Medium
Acceptance Criteria	• Each recording shows time, location, trigger and duration.

Table 85: Specification of FR-18.04: Evidence Controls

Attribute	Required Information
Identifier	FR-18.04
Title	Evidence Controls
Requirement	**User perspective:** The Primary User shall be able to stop a recording, delete a recording, export a recording and choose the retention period. **System perspective:** The system shall stop recording on request, delete a recording on confirmation, export a decrypted copy through the share sheet only when the user asks, and delete recordings automatically after the retention period (7, 30 or 90 days; default 30).
Source	Feature Document 7.18.4; survey (77%); interviews
Rationale	The user stays in control of the evidence.
Business Rule	BR-23
Dependencies	FR-18.03
Priority	Medium
Acceptance Criteria	• Stop ends the recording and keeps the file. • Delete removes the file. • A recording older than the retention period is deleted.

Table 86: Specification of FR-18.05: Consent Disclosure

Attribute	Required Information
Identifier	FR-18.05
Title	Consent Disclosure
Requirement	**System perspective:** The consent text of FR-15.01 shall state that recording begins only after an SOS starts, that it is stored only on the device and how to delete it.
Source	Feature Document 7.18.5; survey (77%); interviews
Rationale	Recording is a sensitive action and requires disclosure.
Business Rule	BR-09, BR-23
Dependencies	FR-15.01

Attribute	Required Information
Priority	Medium
Acceptance Criteria	• The onboarding consent contains the recording disclosure.

3.2.19 MOD-19 Escalation to Authorities

Table 87: Specification of FR-19.01: Response Tracking

Attribute	Required Information
Identifier	FR-19.01
Title	Response Tracking
Requirement	**System perspective:** After an SOS is dispatched, the system shall record an acknowledgement when a trustee confirms through the application or through the acknowledgement link in the message, or when a Verified Helper accepts a request, and shall show it on the SOS screen.
Source	Feature Document 7.19.1; survey (81%)
Rationale	Escalation depends on knowing whether anyone responded.
Business Rule	BR-24
Dependencies	FR-01.02, FR-08.03, UC-29
Priority	Medium
Acceptance Criteria	• A trustee confirmation is shown on the SOS screen. • A helper acceptance is shown on the SOS screen.

Table 88: Specification of FR-19.02: No-Response Timer

Attribute	Required Information
Identifier	FR-19.02
Title	No-Response Timer
Requirement	**System perspective:** When an SOS is dispatched, the system shall start a 3-minute timer on the device that stops when the first acknowledgement is recorded. If the device is offline, the timer shall still run.
Source	Feature Document 7.19.2; survey (81%)
Rationale	The wait must be long enough for people to react and short enough to help.
Business Rule	BR-24
Dependencies	FR-19.01
Priority	Medium
Acceptance Criteria	• The timer stops at the first acknowledgement. • Offline, the timer expires after 3 minutes.

Table 89: Specification of FR-19.03: Warning Countdown

Attribute	Required Information
Identifier	FR-19.03
Title	Warning Countdown

Attribute	Required Information
Requirement	**User perspective:** The Primary User shall be able to cancel the escalation during a warning countdown. **System perspective:** When the timer expires without an acknowledgement, the system shall start a 30-second warning with a one-tap cancel (vibration only in silent mode) and shall escalate if it is not cancelled.
Source	Feature Document 7.19.3; survey (81%)
Rationale	A warning limits false escalations.
Business Rule	BR-24
Dependencies	FR-19.02
Priority	Medium
Acceptance Criteria	• A cancel stops the escalation. • Without a cancel the escalation starts after 30 seconds.

Table 90: Specification of FR-19.04: Authority Channel Settings

Attribute	Required Information
Identifier	FR-19.04
Title	Authority Channel Settings
Requirement	**User perspective:** The Primary User shall be able to choose which authority numbers receive the escalation and by which channel. **System perspective:** The system shall provide a settings screen with the numbers (default Police 15 and Rescue 1122) and, for each number, the channel (SMS, call or share), and shall use SMS by default.
Source	Feature Document 7.19.4; survey (81%)
Rationale	The user must control which authorities are contacted and how.
Business Rule	BR-24
Dependencies	FR-14.03
Priority	Medium
Acceptance Criteria	• The default numbers are Police 15 and Rescue 1122. • Changing the channel changes how the message is sent.

Table 91: Specification of FR-19.05: Escalation Message

Attribute	Required Information
Identifier	FR-19.05
Title	Escalation Message
Requirement	**System perspective:** The system shall compose the escalation message with the user's name and callback number, the location (with its age if cached), the time, the trigger type and whether an evidence recording exists, and shall not include audio.
Source	Feature Document 7.19.5; survey (81%)
Rationale	Authorities need the facts to act.
Business Rule	BR-24, BR-32
Dependencies	FR-19.03, FR-18.01
Priority	Medium

Attribute	Required Information
Acceptance Criteria	• The message contains name, number, location, time, trigger type and evidence status. • The message contains no audio.

Table 92: Specification of FR-19.06: Escalation Log

Attribute	Required Information
Identifier	FR-19.06
Title	Escalation Log
Requirement	**User perspective:** The Primary User shall be able to view the escalation log. **System perspective:** The system shall record each escalation with the time, recipient, channel and delivery status.
Source	Feature Document 7.19.6; survey (81%)
Rationale	The user should know what was sent.
Business Rule	BR-24
Dependencies	FR-19.05
Priority	Medium
Acceptance Criteria	• Each escalation appears in the log with time, recipient, channel and status.

3.2.20 MOD-20 Safe-Location Navigation

Table 93: Specification of FR-20.01: Nearest Safe Location

Attribute	Required Information
Identifier	FR-20.01
Title	Nearest Safe Location
Requirement	**System perspective:** When the user asks for the nearest safe location, the system shall compute it from the hospital and police-station entries of the bundled directory by straight-line distance from the current or last-known location. If no location exists, the system shall ask the user to enable location.
Source	Interview and survey; interview (male university student); survey (77%)
Rationale	A nearby safe place is the first goal of a person in danger.
Business Rule	BR-30
Dependencies	FR-11.01, FR-13.01
Priority	Low
Acceptance Criteria	• The nearest hospital or police station is chosen. • Without any location a message asks to enable it.

Table 94: Specification of FR-20.02: One-Tap Directions Online

Attribute	Required Information
Identifier	FR-20.02
Title	One-Tap Directions Online
Requirement	**User perspective:** The Primary User shall be able to get directions to the nearest safe location with one tap. **System perspective:** When a data connection exists, the system shall open turn-by-turn directions to the safe location in the Google Maps application.

Attribute	Required Information
Source	Interview and survey; interview (male university student); survey (77%)
Rationale	Turn-by-turn directions are the most helpful when online.
Business Rule	BR-30
Dependencies	FR-20.01
Priority	Low
Acceptance Criteria	• One tap opens directions to the nearest safe location.

Table 95: Specification of FR-20.03: Offline Guidance

Attribute	Required Information
Identifier	FR-20.03
Title	Offline Guidance
Requirement	**System perspective:** When there is no data connection, the system shall show the distance and compass direction to the safe location and, if an offline map of the area is stored, a straight line on that map.
Source	Interview and survey; interview (male university student); survey (77%)
Rationale	The feature must still help when offline.
Business Rule	BR-30
Dependencies	FR-20.01, FR-13.02
Priority	Low
Acceptance Criteria	• Offline, the screen shows distance and direction. • If an offline map exists, the line is drawn on it.

3.2.21 MOD-21 App Disguise

Table 96: Specification of FR-21.01: Disguise Options

Attribute	Required Information
Identifier	FR-21.01
Title	Disguise Options
Requirement	**User perspective:** The Primary User shall be able to choose one of three neutral launcher appearances for the application. **System perspective:** The system shall offer three predefined neutral names and icons and apply the chosen one to the launcher entry.
Source	Interview and survey; survey open-ended response
Rationale	A neutral appearance avoids revealing the purpose of the application.
Business Rule	BR-29
Dependencies	-
Priority	Low
Acceptance Criteria	• The user can choose among three appearances. • The launcher entry shows the chosen name and icon.

Table 97: Specification of FR-21.02: Apply and Restore

Attribute	Required Information
Identifier	FR-21.02
Title	Apply and Restore
Requirement	**User perspective:** The Primary User shall be able to restore the original appearance. **System perspective:** The system shall apply a change to the launcher entry and restore the original name and icon on request. The system shall tell the user that some launchers show the change only after they refresh.
Source	Interview and survey; survey open-ended response
Rationale	The change must be reversible.
Business Rule	BR-29
Dependencies	FR-21.01
Priority	Low
Acceptance Criteria	• Restoring returns the original name and icon. • The notice about launcher refresh is shown.

Table 98: Specification of FR-21.03: Unchanged Functions

Attribute	Required Information
Identifier	FR-21.03
Title	Unchanged Functions
Requirement	**System perspective:** The system shall keep all functions, data and settings unchanged while a disguise is applied, and shall use neutral wording for its persistent notification.
Source	Interview and survey; survey open-ended response
Rationale	A disguise must not disable safety.
Business Rule	BR-29
Dependencies	FR-21.01, FR-01.04
Priority	Low
Acceptance Criteria	• SOS, detection and voice work with a disguise applied. • The notification text does not mention safety.

3.2.22 Use case Specification

The use cases describe the interaction between actors and the system. Figure 2, Figure 3, Figure 4 and Figure 5 show the use-case diagrams, grouped by function. Actors are linked to the use cases they take part in. An include relationship shows that a use case reuses the steps of another (UC-02 and UC-03 reuse the dispatch steps of UC-01, and UC-28 reuses the sign-in steps of UC-19), and an extend relationship shows an optional continuation (UC-25 extends UC-01 when nobody responds within 3 minutes). Table 99 lists all 29 use cases with their modules, related requirements and business rules. The six use cases that are on the critical path of an alert or that involve a child's data are specified in this section; the others are specified in Appendix B.




Figure 2: Use-case diagram: emergency alerting



Figure 3: Use-case diagram: family network and disguise




Figure 4: Use-case diagram: community, library and directory




Figure 5: Use-case diagram: account, consent and administration

Table 99: Use case list

Use Case ID	Use Case Name	Actors	Module	Related FRs	Business Rules
UC-01	Trigger Manual SOS	Primary User; Trustee; Verified Helper	MOD-01	FR-01.01 to FR-01.04, FR-12.02	BR-01 to BR-06
UC-02	Handle Automatic Distress Alert	Primary User	MOD-02	FR-02.01 to FR-02.05	BR-02, BR-07, BR-08
UC-03	Trigger SOS by Voice Phrase	Primary User	MOD-03	FR-03.03, FR-03.04	BR-01 to BR-03

Use Case ID	Use Case Name	Actors	Module	Related FRs	Business Rules
UC-04	Manage Trustees	Primary User	MOD-01	FR-01.05	BR-04
UC-05	View SOS Event Log	Primary User	MOD-01	FR-01.06	BR-05
UC-06	Enrol Safe and Duress Phrases	Primary User	MOD-03	FR-03.01, FR-03.02	BR-07, BR-09
UC-07	Create Circle and Invite Member	Primary User; Family Circle Member	MOD-04	FR-04.01, FR-04.02	BR-10
UC-08	Share Location and View Members	Family Circle Member	MOD-05	FR-05.01, FR-05.04, FR-05.05	BR-12, BR-13
UC-09	Stop Sharing by Safe Phrase	Family Circle Member	MOD-05	FR-05.02, FR-05.03, FR-03.05	BR-11
UC-10	Leave Family Circle	Family Circle Member	MOD-04	FR-04.03	BR-14
UC-11	Use Decoy Mode	Primary User	MOD-06	FR-06.01 to FR-06.03	BR-28
UC-12	Submit Incident Report	Primary User	MOD-07	FR-07.01, FR-07.05	BR-15, BR-17
UC-13	View Danger Heatmap	Primary User	MOD-07	FR-07.02 to FR-07.04	BR-16, BR-17
UC-14	Register as Verified Helper	Primary User; Administrator	MOD-08	FR-08.01, FR-16.03	BR-18
UC-15	Request and Respond to Nearby Help	Primary User; Verified Helper	MOD-08	FR-08.02 to FR-08.04	BR-19
UC-16	Browse Library	Primary User	MOD-09	FR-09.01 to FR-09.03	BR-20
UC-17	Search Library	Primary User	MOD-10	FR-10.01 to FR-10.05	BR-20
UC-18	Call Emergency Service	Primary User	MOD-11	FR-11.01 to FR-11.03	BR-21
UC-19	Sign Up and Log In	Primary User	MOD-14	FR-14.01 to FR-14.03	BR-22
UC-20	Manage Consent and Privacy Settings	Primary User	MOD-15	FR-15.01 to FR-15.03	BR-09
UC-21	Moderate Reports and Review Helpers	Administrator	MOD-16	FR-16.01 to FR-16.03, FR-16.05	BR-31
UC-22	Monitor System Health	Administrator	MOD-16	FR-16.04, FR-16.05	BR-31
UC-23	File Missing-Child Report	Guardian; Verified Helper; Trustee; Administrator	MOD-17	FR-17.01 to FR-17.06	BR-25 to BR-27
UC-24	Manage Evidence Recordings	Primary User	MOD-18	FR-18.01 to FR-18.05	BR-23
UC-25	Escalate to Authorities	Primary User; Authority Contact	MOD-19	FR-19.01 to FR-19.06	BR-24
UC-26	Navigate to Nearest Safe Location	Primary User	MOD-20	FR-20.01 to FR-20.03	BR-30
UC-27	Change App Disguise	Primary User	MOD-21	FR-21.01 to FR-21.03	BR-29
UC-28	Recover Account	Primary User	MOD-14	FR-14.04	BR-22
UC-29	Acknowledge SOS Alert	Trustee; Verified Helper	MOD-19	FR-19.01, FR-08.03	BR-24

Table 100: Use case specification UC-01: Trigger Manual SOS

Field	Description
Use Case ID	UC-01

Field	Description
Use Case Name	Trigger Manual SOS
Actors	Primary User; Trustee; Verified Helper
Description	The Primary User starts an SOS by hand. The system dispatches the alert to the trustees and, when enabled, to nearby helpers, sounds or withholds the alarm, and records evidence.
Trigger	The user holds the SOS control on the home screen for 1 second, or taps the SOS action on the lock screen.
Preconditions	The user has signed in on the device at least once; at least one trustee exists; the SMS permission is granted.
Postconditions	Success: an SOS event exists in the log; alerts are sent or queued; the siren plays (loud) or nothing is shown (silent); an evidence recording and the 3-minute timer have started. Failure: if the SMS permission is missing, alerts go on the remaining channels and a prompt is shown in loud mode.
Normal Flow	1. The user holds the SOS control for 1 second (or taps the lock-screen action). 2. The system starts the SOS pipeline and records the trigger as "manual". 3. The system obtains the location: a fresh fix, or the cached location after 10 seconds. 4. The system starts the evidence recording and the no-response timer. 5. In loud mode the system plays the siren; in silent mode it shows and plays nothing. 6. The system sends SMS, push and email to each trustee on the enabled channels, and starts the nearby-help broadcast if enabled; anything that cannot be sent is queued. 7. In loud mode the system prepares the WhatsApp messages for the user to confirm. 8. The system updates the SOS event log with the delivery status of each channel.
Alternative Flows	A1 (step 1): the user releases before 1 second; nothing starts. A2 (step 3): no fresh fix; the cached location is used and its age is stated. A3 (step 6): at Tier 1 only SMS is sent and the other channels are queued. A4 (step 5): the user stops the siren with the stop control.
Exceptions	E1: the SMS permission is missing; alerts go on the other channels and a permission prompt is shown in loud mode. E2: the microphone cannot be used; no recording is made and the log notes it.
Business Rules	BR-01, BR-03, BR-04, BR-05, BR-06, BR-23, BR-24
Assumptions	AS-1, AS-2, AS-7

Table 101: Use case specification UC-02: Handle Automatic Distress Alert

Field	Description
Use Case ID	UC-02
Use Case Name	Handle Automatic Distress Alert
Actors	Primary User
Description	The monitoring service detects a possible distress sound, combines it with motion data and asks the user to cancel within 20 seconds. If the user does not cancel, an SOS starts.
Trigger	The monitoring service detects a sudden loud sound above the ambient level.
Preconditions	Microphone detection is on with consent and permission; the monitoring service is running.
Postconditions	Success: either nothing was sent (the user cancelled) or an SOS with trigger "automatic" was started. In both cases no audio or sensor data was stored or sent.
Normal Flow	1. The monitoring service detects a sudden rise in sound level. 2. The system runs the classifier on the buffered sound and obtains a distress score. 3. The system reads the accelerometer and gyroscope for the same window. 4. The fusion rule is satisfied. 5. The system vibrates mildly for 20 seconds and shows a one-tap cancel control. 6. The user does not cancel. 7. The system starts the SOS with trigger "automatic" (UC-01, steps 3 to 8).

Field	Description
Alternative Flows	A1 (step 2): the score is below the distress threshold; the system discards the buffer and returns to monitoring. A2 (step 4): the fusion rule is not satisfied; no countdown starts. A3 (step 6): the user cancels; the vibration stops, nothing is sent and monitoring continues.
Exceptions	E1: the classifier model cannot be loaded; detection is turned off and the user is told. E2: motion sensors are unavailable; the countdown starts only if the audio score is above the high-confidence threshold. E3: the service is stopped by the system; it restarts (NFR-REL-03).
Business Rules	BR-02, BR-07, BR-08, BR-09
Assumptions	AS-3, AS-4

Table 102: Use case specification UC-03: Trigger SOS by Voice Phrase

Field	Description
Use Case ID	UC-03
Use Case Name	Trigger SOS by Voice Phrase
Actors	Primary User
Description	The Primary User starts an SOS by speaking the safe phrase (loud or default mode) or the duress phrase (silent).
Trigger	The keyword-spotting engine detects an enrolled phrase.
Preconditions	Voice activation is on with consent and permission; both phrases are enrolled; the engine is running.
Postconditions	Success: an SOS with trigger "voice" was started, or the user cancelled and nothing was sent.
Normal Flow	1. The user speaks the safe phrase or the duress phrase. 2. The engine detects the phrase and reports which one it was. 3. The system starts the 20-second vibration countdown with a one-tap cancel. 4. The user does not cancel. 5. The system starts the SOS with trigger "voice": in the default mode for the safe phrase, silent for the duress phrase (UC-01, steps 3 to 8). 6. For the duress phrase the system also shows the decoy screen.
Alternative Flows	A1 (step 2): the stop-sharing confirmation is open and the phrase is the safe phrase; the system treats it as a confirmation (UC-09) and starts no SOS. A2 (step 4): the user cancels; nothing is sent.
Exceptions	E1: the engine cannot be loaded; voice activation is turned off, the user is told, and the manual SOS remains available.
Business Rules	BR-01, BR-02, BR-03, BR-07, BR-08
Assumptions	AS-3, AS-5

Table 103: Use case specification UC-09: Stop Sharing by Safe Phrase

Field	Description
Use Case ID	UC-09
Use Case Name	Stop Sharing by Safe Phrase
Actors	Family Circle Member
Description	A Family Circle Member stops sharing their location by speaking the safe phrase. No approval is needed and no other member is notified.
Trigger	The member opens the stop-sharing screen.
Preconditions	The member is in a circle and is sharing; voice activation is on and the safe phrase is enrolled.

Field	Description
Postconditions	Success: the member's sharing is off; other members see only the last published location with its time, labelled "Not live"; no message was sent to others.
Normal Flow	1. The member opens the stop-sharing screen. 2. The system shows the confirmation prompt and listens for the safe phrase in confirmation context. 3. The member speaks the safe phrase. 4. The system recognises it, disables sharing and stops publishing location. 5. The system shows a private confirmation on the member's device only.
Alternative Flows	A1 (step 3): no phrase within 15 seconds; the screen closes and sharing continues. A2: the member chooses to leave the circle instead (UC-10).
Exceptions	E1: the voice engine is unavailable; the screen explains that the phrase cannot be confirmed and offers UC-10. E2: there is no connection; publishing stops on the device at once and the status is synchronised when a connection returns.
Business Rules	BR-11, BR-12, BR-13
Assumptions	AS-5

Table 104: Use case specification UC-25: Escalate to Authorities

Field	Description
Use Case ID	UC-25
Use Case Name	Escalate to Authorities
Actors	Primary User; Authority Contact
Description	When nobody acknowledges an SOS in time, the system warns the user and then sends an escalation message to the configured authority numbers.
Trigger	The 3-minute no-response timer expires with no acknowledgement.
Preconditions	An SOS is active; at least one authority number is configured.
Postconditions	Success: the escalation message was sent or queued and the log has an entry. Cancelled: no message was sent and the log shows "cancelled".
Normal Flow	1. The timer expires with no acknowledgement. 2. The system starts the 30-second warning with a one-tap cancel (vibration only in silent mode). 3. The user does not cancel. 4. The system composes the escalation message with name, callback number, location, time, trigger type and the evidence flag. 5. The system sends the message to each configured number by its channel (SMS by default). 6. The system records the escalation in the log.
Alternative Flows	A1 (before step 1): an acknowledgement arrives; the timer stops and no escalation occurs. A2 (step 3): the user cancels; no escalation is sent. A3 (step 5): the channel of a number is "call"; the system places the call.
Exceptions	E1: SMS cannot be sent; the message is queued and retried (BR-05). E2: a configured number is invalid; the log records a failure for that number.
Business Rules	BR-05, BR-24, BR-32
Assumptions	AS-6, DEP-6

Table 105: Use case specification UC-23: File Missing-Child Report

Field	Description
Use Case ID	UC-23

Field	Description
Use Case Name	File Missing-Child Report
Actors	Guardian; Verified Helper; Trustee; Administrator
Description	A Guardian reports a missing child; the system alerts trusted contacts and nearby verified helpers and queues the report for moderation.
Trigger	The Guardian opens the missing-child report form.
Preconditions	The Guardian is signed in and has a data connection or accepts that the report will be queued.
Postconditions	Success: an active report exists; alerts were sent; the report is in the moderation queue.
Normal Flow	1. The Guardian opens the form. 2. The Guardian enters the child's name, age, photo, description, last-seen place and time, and the contact number. 3. The Guardian confirms being the child's guardian. 4. The Guardian submits. 5. The system validates the data. 6. The system stores the report as "active". 7. The system alerts the guardian's trustees and the Verified Helpers within 5 km. 8. The system places the report in the moderation queue.
Alternative Flows	A1 (step 5): validation fails; the system shows the errors and keeps the data. A2: the Guardian marks the child as found; the system stops alerts and deletes the photo. A3: 72 hours pass without renewal; the status becomes "expired" and the photo is deleted.
Exceptions	E1: no connection; the report is queued and sent when a connection returns. E2: an administrator removes the report as false; it disappears from all lists.
Business Rules	BR-25, BR-26, BR-27, BR-32
Assumptions	AS-8

3.3 Business Rules

The business rules in Table 106 are the policies, limits and constraints that govern the behaviour of the functional requirements. A functional requirement or use case refers to a rule by its identifier.

Table 106: Business rules

BR ID	Business Rule	Source or Rationale	Related FR or UC	Priority
BR-01	Every SOS trigger (manual, automatic, voice) enters one dispatch pipeline. The trigger method is recorded and does not change the channels used.	Novel contribution: one shared trigger engine.	FR-01.01, FR-02.04, FR-03.04, FR-03.05; UC-01, UC-03	High
BR-02	Manual SOS has no countdown. Automatic and voice triggers start a 20-second vibration-only countdown with a one-tap cancel; if it is cancelled nothing is sent.	Protects against false alarms without delaying a deliberate SOS.	FR-01.01, FR-02.03, FR-02.04, FR-03.04; UC-01, UC-02, UC-03	High
BR-03	A silent SOS (silent default mode or duress phrase) produces no sound, vibration, visible alert or revealing notification, and dispatch continues. A loud SOS plays the siren until the user stops it.	Supports hiding while calling for help.	FR-01.03, FR-01.04, FR-03.02, FR-03.04; UC-01, UC-03	High

BR ID	Business Rule	Source or Rationale	Related FR or UC	Priority
BR-04	An alert is sent to each trustee on every channel that trustee has enabled; if none is enabled, SMS is used. SMS, push and email are automatic. WhatsApp requires the user to confirm the prepared message and is not used in a silent SOS.	WhatsApp cannot send a message without user interaction.	FR-01.02, FR-01.05; UC-01, UC-04	High
BR-05	At Tier 1 only SMS is used. At Tiers 2 and 3 all enabled channels are used. A message that cannot be delivered is queued and retried until delivered, and every attempt is logged.	Offline-first delivery.	FR-01.02, FR-01.06, FR-08.04, FR-12.01, FR-12.02, FR-12.03, FR-13.02; UC-01, UC-05, UC-25	High
BR-06	The SOS location is a fresh fix if one is obtained within 10 seconds; otherwise the last-known cached location is used and its age is stated in the message.	An older location is better than none.	FR-01.02, FR-12.02, FR-13.01; UC-01	High
BR-07	No audio, transcript or classifier output of the detection or voice engines leaves the device.	Privacy guarantee given to users.	FR-02.01, FR-02.02, FR-02.05, FR-03.01, FR-03.02, FR-03.03, FR-15.03; UC-02, UC-03, UC-06	High
BR-08	The detection and voice engines store no audio. The only stored audio is the evidence recording of BR-23.	Privacy guarantee given to users.	FR-02.01, FR-02.02, FR-02.05, FR-03.03; UC-02, UC-03	High
BR-09	Microphone detection, voice activation and location sharing are off until the user has given consent. Each has its own toggle, which can be changed at any time and takes effect immediately.	Informed consent.	FR-02.01, FR-03.01, FR-03.03, FR-15.01, FR-15.02, FR-18.05; UC-02, UC-06, UC-20	High
BR-10	Sharing between two people starts only after both have accepted. An invitation expires after 7 days.	Bilateral opt-in.	FR-04.01; UC-07	High
BR-11	A member can stop sharing at any time without anyone's approval, by speaking the safe phrase on the stop-sharing screen. No other member receives any message about it.	Unilateral opt-out without confrontation.	FR-03.05, FR-05.02, FR-05.03; UC-09	High
BR-12	After a member stops sharing, others see only the last published location with its time, labelled "Not live".	A stale location cannot be mistaken for live tracking.	FR-05.04; UC-08, UC-09	High
BR-13	No hidden tracking: every member can see who is sharing, a sharing member sees a persistent indicator, and only a member can resume their own sharing.	Prevents covert surveillance.	FR-04.02, FR-05.01, FR-05.05; UC-08, UC-09	High
BR-14	Leaving a circle and stopping sharing are separate actions. Leaving removes the membership and deletes the member's stored location from the circle.	Separates ending membership from pausing.	FR-04.03; UC-10	High
BR-15	A user may submit at most 5 incident reports in 24 hours and no second report within 100 m and one hour. More than 10 reports in one cell within one hour go to moderation.	Prevents spam and malicious flagging.	FR-07.01, FR-07.05, FR-16.02; UC-12	Medium
BR-16	A report is weighted by 0.5 to the power of (age / 90 days). A cell score is the sum of the weights.	Shows current risk.	FR-07.03, FR-07.04; UC-13	Medium

BR ID	Business Rule	Source or Rationale	Related FR or UC	Priority
BR-17	Reports are grouped by geohash cells of precision 7. A cell shows only category counts and never the identity of a reporter.	Anonymity of reporters.	FR-07.01, FR-07.02, FR-07.04; UC-12, UC-13	Medium
BR-18	A user becomes a Verified Helper only after an administrator approves the identity check. An administrator can revoke it. The identity image is deleted after the decision.	Reduces misuse of the helper network.	FR-08.01, FR-16.03; UC-14	Medium
BR-19	A help request goes to Verified Helpers within the set radius (default 1 km). The exact location of the requester is shown only to a helper who accepts.	Limits exposure of the requester's location.	FR-08.02, FR-08.03; UC-15	Medium
BR-20	Library content is bundled and its search runs on the device. Search falls back to keyword search when the model is unavailable or the highest similarity is below 0.30.	Offline use and privacy of queries.	FR-09.01, FR-09.02, FR-09.03, FR-10.01, FR-10.02, FR-10.03, FR-10.04, FR-10.05, FR-13.02; UC-16, UC-17	Medium
BR-21	Directory entries with coordinates are ordered by distance when a location is available; otherwise by category and name.	The nearest help is the most useful.	FR-11.01, FR-11.02, FR-11.03; UC-18	Medium
BR-22	One account exists per phone number and is verified by a one-time code. Logging in on a new device with the same number ends sessions on other devices.	Simple identity and lost-device recovery.	FR-14.01, FR-14.02, FR-14.03, FR-14.04; UC-19, UC-28	High
BR-23	An evidence recording starts on every SOS, is encrypted, is stored only on the device, is never uploaded, and is deleted after the retention period (default 30 days; 7, 30 or 90 selectable).	Evidence stays with the user.	FR-14.04, FR-18.01, FR-18.02, FR-18.03, FR-18.04, FR-18.05; UC-01, UC-24	Medium
BR-24	If no acknowledgement arrives within 3 minutes of dispatch, a 30-second warning with cancel starts; if it is not cancelled the escalation message goes to the configured authority numbers. Any acknowledgement or a cancel stops the escalation.	Follow-through with a safeguard against false escalation.	FR-19.01, FR-19.02, FR-19.03, FR-19.04, FR-19.05, FR-19.06; UC-01, UC-25, UC-29	Medium
BR-25	A missing-child report is active, found or expired. It expires 72 hours after creation or renewal unless the guardian renews it.	Reports must not remain active indefinitely.	FR-17.01, FR-17.03; UC-23	Medium
BR-26	A child's photo is visible only to the guardian, the alerted trustees and the notified helpers while the report is active, and is deleted when the report is found or expired.	Child-data privacy.	FR-17.01, FR-17.02, FR-17.03, FR-17.06; UC-23	Medium
BR-27	A user may file at most 3 missing-child reports in 24 hours. Every report is reviewed by an administrator. A report removed as false is deleted from all lists and its author may be suspended. The application makes no direct connection to official systems.	Abuse prevention and clear boundary with official channels.	FR-16.02, FR-17.01, FR-17.04, FR-17.05; UC-23	Medium
BR-28	In Decoy Mode the application shows a neutral calculator; SOS, voice triggers, location updates and evidence recording continue underneath. A 2-second hold on the equals key returns to the real interface.	Protects the user when forced to unlock the phone.	FR-03.05, FR-06.01, FR-06.02, FR-06.03; UC-11	High

BR ID	Business Rule	Source or Rationale	Related FR or UC	Priority
BR-29	The disguise offers three predefined neutral appearances and does not change functions, data or settings.	Disguise must not disable safety.	FR-21.01, FR-21.02, FR-21.03; UC-27	Low
BR-30	The nearest safe location is the nearest hospital or police station of the bundled directory by straight-line distance; directions are turn-by-turn when online and distance and direction when offline.	Works from stored data.	FR-20.01, FR-20.02, FR-20.03; UC-26	Low
BR-31	Only accounts with the administrator role can use the admin website. Every moderation or review decision is logged with the administrator and the time.	Accountability.	FR-16.01, FR-16.02, FR-16.03, FR-16.04, FR-16.05, FR-17.05; UC-21, UC-22	Medium
BR-32	A user's location is shared only with trustees (SOS), circle members (while sharing), helpers who have accepted, and authority numbers (escalation).	Data minimisation.	FR-01.02, FR-08.02, FR-15.03, FR-17.02, FR-19.05; UC-23, UC-25	High

3.4 Non-Functional Requirements

The non-functional requirements are specific, quantitative and verifiable. Each has a measurable target and a verification method, and each target is a requirement that Chapter 6 verifies on the reference device and under the stated conditions. They are grouped by quality: reliability, performance, security, privacy, usability, and maintainability with other qualities (compatibility, availability, scalability, safety and robustness).

Table 107: Non-functional requirements: Reliability

ID	Requirement	Measurement or Target	Verification Method
NFR-REL-01	The SOS by SMS shall be handed to the device SMS service for every trustee without a data connection.	At least 95% of 20 trials at Tier 1 hand the SMS to the SMS service within 5 seconds of the trigger.	Instrumented device test with data disabled.
NFR-REL-02	Queued messages shall survive application termination and device restart.	100% of queued messages remain after 10 forced stops and 5 restarts.	Test with forced stops and restarts.
NFR-REL-03	The monitoring and voice services shall restart after being stopped by the system or after a restart.	Restart within 60 seconds in 9 of 10 trials when permissions and battery exemption are granted.	Device test.
NFR-REL-04	The failure of one dispatch channel shall not prevent the others.	With each channel disabled in turn, all others still dispatch (100%).	Fault-injection test.
NFR-REL-05	The application shall run without a crash or an application-not-responding event during continuous background monitoring.	Zero crashes in 8 hours on each test device.	Soak test.

Table 108: Non-functional requirements: Performance

ID	Requirement	Measurement or Target	Verification Method
NFR-PER-01	The SOS dispatch shall start promptly after a manual trigger.	At least 95% of 20 trials start the first channel within 2 seconds of the completed hold.	Timed device test.
NFR-PER-02	Distress classification shall complete promptly after a loud sound.	Result within 1.5 seconds of the end of the sound burst in 95% of trials.	Timed test with labelled clips.
NFR-PER-03	The voice engine shall detect an enrolled phrase promptly.	Detection within 2 seconds of the end of the phrase in 90% of trials.	Timed test.
NFR-PER-04	A change in sharing status shall reach other members' devices.	Within 5 seconds in 95% of trials at Tier 3.	Two-device timed test.
NFR-PER-05	Semantic search shall return results quickly on the device.	Within 1 second for a library of up to 500 items on the reference device.	Timed test.
NFR-PER-06	The heatmap shall load for the visible area.	Within 5 seconds at Tier 2 or 3; within 2 seconds from the cache offline.	Timed test.
NFR-PER-07	The application shall start quickly.	Cold start to the home screen within 3 seconds on the reference device.	Timed test.
NFR-PER-08	Evidence recording shall start promptly.	Within 1 second of the SOS start in 95% of trials.	Timed test.
NFR-PER-09	The outbound queue shall flush promptly when the connection returns.	Within 30 seconds of Tier 2 or 3 being reached.	Timed test.
NFR-PER-10	Continuous detection and voice monitoring shall have a bounded battery cost.	No more than 5% of battery capacity per hour with the screen off on the reference device.	Battery measurement over 3 hours.

Table 109: Non-functional requirements: Security

ID	Requirement	Measurement or Target	Verification Method
NFR-SEC-01	All data sent between the application, the admin website and the backend shall be encrypted in transit.	TLS 1.2 or later for 100% of connections.	Network inspection.
NFR-SEC-02	Evidence recordings shall be encrypted at rest and unreadable by other applications.	AES-256-GCM with a Keystore key; a file read by another application fails.	File and permission inspection.
NFR-SEC-03	The backend shall enforce access rules so that users read only data they are entitled to under BR-10 to BR-14 and BR-32.	100% of unauthorized read attempts in the rule tests are denied.	Security-rule unit tests.
NFR-SEC-04	Only administrators shall access the admin website, and their actions shall be logged.	Non-administrator accounts are denied on all admin pages; every decision is logged.	Access test and log inspection.
NFR-SEC-05	No audio payload shall be sent from the detection or voice engines.	Zero audio payloads in a network capture of 1 hour of monitoring including 10 detections.	Network capture.
NFR-SEC-06	Identity images and child photos shall be readable only by those entitled to read them and shall be deleted after use.	Unauthorized reads are denied; deletion occurs at the decision or status change.	Storage-rule tests.
NFR-SEC-07	The admin website shall show phone numbers masked.	All displayed numbers show only the last 3 digits.	Visual inspection.

Table 110: Non-functional requirements: Privacy

ID	Requirement	Measurement or Target	Verification Method
NFR-PRV-01	No microphone function shall run before consent and permission.	Zero microphone access before consent in 10 fresh installations.	Permission and log inspection.
NFR-PRV-02	Heatmap reports older than 12 months shall be removed from the backend.	No report older than 12 months remains after the scheduled clean-up.	Data inspection after clean-up.
NFR-PRV-03	The privacy summary shall match actual data handling.	Every item of the summary is verified against the stored data in a review.	Review checklist.

Table 111: Non-functional requirements: Usability

ID	Requirement	Measurement or Target	Verification Method
NFR-USA-01	The SOS shall be quick to reach.	One press-and-hold from the home screen; one tap from the lock screen.	Inspection.
NFR-USA-02	New users shall complete onboarding easily.	At least 80% of test participants finish sign-up, one trustee and consent in under 5 minutes.	Usability test with at least 5 participants.
NFR-USA-03	Touch targets shall be large.	At least 48 dp, and the SOS control at least 72 dp.	Layout inspection.
NFR-USA-04	Text shall be readable.	Contrast ratio at least 4.5:1; layouts remain usable at 130% font scale.	Contrast tool and test at 130% scale.
NFR-USA-05	Cancel actions shall need one tap.	The 20-second countdown and the 30-second escalation warning can each be cancelled with one tap.	Inspection and test.
NFR-USA-06	Error messages shall state the problem and the next step.	At most two sentences each; every error path in the test plan shows one.	Inspection.

Table 112: Non-functional requirements: Maintainability, Portability and Other Qualities

ID	Requirement	Measurement or Target	Verification Method
NFR-MNT-01	The application shall be organised in modules that correspond to MOD-01 to MOD-21 with defined interfaces.	Each module in its own package; business-logic unit-test coverage at least 70%.	Code structure review and coverage report.
NFR-MNT-02	Thresholds, timers and limits shall be set in one configuration file.	All values of BR-02, BR-06, BR-15, BR-19 and BR-24 changed without code changes.	Configuration test.
NFR-MNT-03	Every module shall have a short description of its public interface.	One description per module in the repository.	Documentation review.
NFR-CMP-01	The application shall run on Android 8.0 and later.	Smoke test passed on at least 3 device models from different manufacturers.	Device test.
NFR-AVL-01	The SOS by SMS shall not depend on the backend.	Zero backend calls on the SMS path.	Code and network inspection.
NFR-SCL-01	The backend shall support the pilot scale within free-tier limits.	Up to 500 registered users and 100 concurrent users within quotas.	Quota calculation and load test.
NFR-SAF-01	No automatic or voice SOS shall be dispatched without the 20-second cancel period.	100% of automatic and voice SOS events in the test log show the countdown.	Log inspection.
NFR-SAF-02	Distress detection shall meet a target accuracy on the project test set.	Precision and recall each at least 0.80 on a labelled clip set of at least 100 clips.	Evaluation script.

ID	Requirement	Measurement or Target	Verification Method
NFR-ROB-01	A missing or corrupt model file shall disable only the affected feature.	SOS still works with each model file removed in turn.	Fault-injection test.
NFR-ROB-02	Invalid input shall not crash the application.	No crash in 100 malformed-input cases.	Input test.
NFR-ROB-03	Low storage shall not stop an SOS.	With storage full the SOS dispatches and the recording stops with a log entry.	Test with full storage.

3.5 External Interface Requirements

This section specifies how Muhaffiz communicates with its users and with external software, hardware and communication services. Table 113 summarizes the interfaces.

3.5.1 User Interface Requirements

- UI-1: The application shall follow Material Design 3 as provided by Flutter, with one colour scheme of dark teal, navy and mint used on all screens.
- UI-2: The application shall use the system sans-serif font at 14 sp or larger for body text, the Material icon set, and verb labels on buttons.
- UI-3: The application shall be designed for portrait orientation on phone screens from 320 dp wide. The home screen shall show the SOS control, the loud or silent toggle and a status strip with the connectivity tier and the state of detection and voice activation.
- UI-4: The application shall provide bottom navigation with Home, Family, Map, Library and More. Help, settings and the privacy summary shall be reachable from More.
- UI-5: Every control shall have a content description, and the focus order shall follow the reading order, so that a screen reader can be used.
- UI-6: Success messages shall appear as brief messages, errors shall appear next to the field with the next step, and notifications shall use separate Android channels for status, alerts and reminders. In a silent SOS the notification wording shall be neutral.
- UI-7: The interface language shall be English, and dates and times shall follow the device locale.

- UI-8: Information shall not be conveyed by colour alone; the heatmap shall have a legend with numeric ranges.
- UI-9: The screen designs in Section 4.5 are the committed designs of the key screens; other screens follow the same components.
- UI-10: The admin website shall be usable on screens 1024 px wide or wider and shall present lists as filterable tables.

3.5.2 Software Interfaces

- SI-1: The application and the admin website shall use Firebase Authentication for phone sign-in of users and email-and-password sign-in of administrators.
- SI-2: The application shall use Cloud Firestore with offline persistence for circles, locations, reports, helper status and acknowledgements.
- SI-3: The system shall use Firebase Cloud Messaging to deliver push notifications to trustees and helpers.
- SI-4: The system shall use Cloud Storage for identity images and child photos, protected by storage rules.
- SI-5: The system shall use Cloud Functions, called over HTTPS, for email dispatch, the acknowledgement endpoint, heatmap aggregation and scheduled expiry.
- SI-6: The application shall use the Google Maps SDK for Android for online maps.
- SI-7: The application shall load offline map data for up to three areas from an open map-data source that permits offline storage.
- SI-8: The application shall send SMS through the Android SMS manager, called through a platform channel.
- SI-9: The application shall prepare WhatsApp messages with the WhatsApp share link through an Android intent.
- SI-10: The application shall use the Android Keystore for the evidence encryption key.
- SI-11: The application shall run its sound-classification, keyword-spotting and sentence-embedding models with TensorFlow Lite or an equivalent on-device runtime.

- SI-12: The application shall use Android WorkManager to retry the outbound queue.
- SI-13: The application shall use SQLite as its on-device database.
- SI-14: The backend shall call an email delivery service from Cloud Functions.

3.5.3 Hardware Interfaces

- HI-1: The application shall read the microphone as 16 kHz mono audio for detection, voice activation and evidence recording. If the microphone is in use by another application, the affected function shall pause and resume when it is free.
- HI-2: The application shall read the accelerometer and gyroscope at 50 Hz or faster during a detection window.
- HI-3: The application shall obtain location from the fused location provider (GPS and network).
- HI-4: The application shall drive the vibration motor for the 20-second countdown and the 30-second warning.
- HI-5: The application shall play the siren through the alarm audio stream of the speaker.
- HI-6: The application shall use the telephony hardware to send SMS and place calls.
- HI-7: The application shall read the magnetometer, when present, to show compass direction offline.
- HI-8: The application shall read photos chosen by the user from the camera or gallery for the helper identity image and the child photo.

3.5.4 Communications Interfaces

- CI-1: SOS and escalation messages shall be sent as SMS over the cellular network, in as many message parts as the text needs.
- CI-2: Push notifications shall be delivered through Firebase Cloud Messaging.
- CI-3: Email alerts shall be sent from Cloud Functions through the email service.
- CI-4: WhatsApp messages shall be prepared as a share link for the WhatsApp application.

- CI-5: All data between the application, the admin website and the backend shall use HTTPS with TLS 1.2 or later; real-time updates shall use the Firestore real-time channel.
- CI-6: Calls shall be placed through the Android dialer.
- CI-7: A trustee without the application shall be able to acknowledge an alert through a web page served by Firebase Hosting and linked from the message.

Table 113: Summary of external interfaces

Interface ID	Interface Type	External Element	Data or Interaction	Protocol or Standard	Error Handling
SI-1	Software	Firebase Authentication	One-time code sign-in; administrator sign-in	HTTPS / Firebase SDK	Wrong code rejected; lock after five attempts; offline use of safety functions continues.
SI-2	Software	Cloud Firestore	Circles, locations, reports, helper status, acknowledgements	Firestore SDK (real-time)	Local cache used offline; writes retried on reconnection.
SI-3	Software	Firebase Cloud Messaging	Push alerts and help requests	FCM over HTTPS	Failure logged; other channels continue.
SI-4	Software	Cloud Storage	Identity images, child photos	HTTPS / Storage SDK	Upload retried; deletion confirmed.
SI-5	Software	Cloud Functions	Email dispatch, acknowledgement, scheduled jobs	HTTPS callable	Errors logged and visible in health monitoring.
SI-6	Software	Google Maps SDK	Map display, overlays	Maps SDK for Android	Offline: last data or offline map shown.
SI-8	Software	Android SMS manager	SOS and escalation SMS	Android API	Missing permission prompts; failure queued and retried.
SI-9	Software	WhatsApp	Prepared message	Share link / intent	Application missing: channel skipped.
HI-1	Hardware	Microphone	Audio frames for detection, voice, evidence	16 kHz mono PCM	In use elsewhere: pause and resume.
HI-2	Hardware	Accelerometer, gyroscope	Motion window	50 Hz or faster	Sensor missing: audio-only rule applies.
HI-3	Hardware	Location provider	Position fixes	Fused location	No fix: cached location used.
HI-6	Hardware	Telephony	SMS and calls	GSM SMS, voice	No signal: queued and retried.
CI-3	Communication	Email service	Email alerts	HTTPS API	Failure logged; other channels continue.
CI-7	Communication	Acknowledgement page	Trustee acknowledgement	HTTPS (Firebase Hosting)	Link opened offline: acknowledgement not recorded.

3.6 Chapter Summary

This chapter specified Muhaffiz through 87 functional requirements, 29 use cases, 32 business rules, 42 non-functional requirements and the external interface requirements. Each functional requirement has a source, rationale, business rule, dependencies, priority and acceptance criteria. Chapter 4 now translates these requirements into the design of the system.

Chapter 4: System Design

Chapter Overview. This chapter translates the requirements of Chapter 3 into a design. Section 4.1 gives the design methodology and process model, Section 4.2 the architecture, Section 4.3 the design models, Section 4.4 the data design, Section 4.5 the human interface design, Section 4.6 the security, error-handling and logging design, and Section 4.7 the risk analysis and the milestone plan.

4.1 Design Methodology and Software Process Model

Muhaffiz is designed with an object-oriented method. The domain is expressed as classes with clear responsibilities (Section 4.3), behaviour is described with use cases, sequence, activity and state models, and the structure follows a layered architecture in which a small event-driven core handles triggers. This follows the practice described for software design descriptions [3] and for object-oriented systems [4]. Object orientation suits the product because its central problem, that many different triggers must lead to one consistent behaviour, maps directly to a shared set of classes (TriggerEngine, SosOrchestrator and DeliveryManager).

The software process is incremental and iterative, organized in short sprints that group into milestones. Each milestone delivers a working increment that is built on the previous one. The order of milestones is risk-driven: the modules whose feasibility is least certain, namely distress detection, offline voice activation and offline delivery, are built early so that problems are found while there is still time to change the approach. A team of two with a fixed academic schedule benefits from this: scope can be reduced late by dropping low-priority modules (Section 2.5) without disturbing the core. Section 4.7 gives the milestones and the risks.

The design follows five principles that come from the objectives of the project.

- **Privacy by design:** sensitive audio is processed and discarded on the device; the backend receives only what a feature needs.
- **Offline first:** the path that gets an alert out never depends on the backend; SMS and the local queue are on that path.
- **One trigger pipeline:** manual, automatic and voice triggers, the opt-out and the decoy all pass through shared components.

- **Fail safe:** a failing channel, model or sensor disables only itself, and manual SOS stays available.
- **Configuration over code:** thresholds, timers and limits are held in one configuration so that they can be tuned during evaluation.

4.2 Architectural Design

Architecture style. Muhaffiz combines three styles. The Android application uses a layered architecture (presentation, application, domain and data, and platform layers) so that screens do not depend on platform details. Inside the application, the triggers, the delivery pipeline and the escalation timers are event-driven: detectors publish events and managers react to them. The application and the admin website use a backend-as-a-service architecture, in which Firebase provides authentication, data, messaging, storage and server-side functions. Figure 6 shows the main parts and their connections.




Figure 6: Architecture of Muhaffiz (box-and-line view)

Decomposition. Table 114 maps the modules to the packages of the application and to the backend, and states what each package is responsible for.

Table 114: Decomposition of the system into packages

Package	Responsibility	Modules	Main interface
sos_core	Runs the SOS from start to close; owns the SOS event and its state.	MOD-01	start(trigger, mode), cancel(), complete()
trigger_engine	Receives manual, automatic and voice triggers and applies the countdown rule.	MOD-01, 02, 03	onManual(), onAutomatic(), onVoice()
detection_engine	Monitors sound level, classifies bursts, reads motion sensors and applies the fusion rule.	MOD-02	start(), stop(), events
voice_engine	Offline keyword spotting for the safe and duress phrases; context-aware delivery of detections.	MOD-03	start(), stop(), setContext(), events
evidence_vault	Records and encrypts audio; lists, exports and deletes recordings.	MOD-18	startRecording(), list(), export()
escalation	Tracks acknowledgements, runs the timers, composes and sends the escalation message.	MOD-19	onDispatched(), onAcknowledged()
delivery_manager, sms_gateway, offline_store	Detects the connectivity tier, sends on each channel, queues and retries; holds the local database and cache.	MOD-12, 13	dispatch(), flush(), cache API
family_circle, location_sharing	Circles, invitations, movement-based location publication, opt-out and last-known display.	MOD-04, 05	invite(), publish(), stopSharing()
heatmap, near_help, missing_child	Incident reports and cell scores, helper registration and requests, missing-child reports.	MOD-07, 08, 17	submitReport(), broadcast(), file()
library, semantic_search, directory, safe_navigation	Bundled content, on-device search, emergency directory, nearest safe location.	MOD-09, 10, 11, 20	search(), nearest(), call()
auth, consent, decoy_mode, app_disguise	Sign-in and sessions, consent and toggles, decoy screen, launcher appearance.	MOD-06, 14, 15, 21	signIn(), toggle(), setAppearance()
Cloud Functions	Email dispatch, acknowledgement endpoint, heatmap aggregation, expiry and clean-up jobs.	MOD-01, 07, 17, 19	HTTPS callable (Section 5.3)
admin_site	Administrator sign-in, overview, moderation, helper review and health monitoring.	MOD-16	Firestore and Functions calls

Deployment view. Figure 7 shows where the parts run. The phone holds the application, the local database, the encrypted evidence and the on-device models. Firebase hosts the backend and the two web pages (the admin website and the alert page). Trustees reach the alert page and receive SMS, push, email and WhatsApp messages. Section 5.5 gives the environments and the deployment procedure.




Figure 7: Deployment view of Muhaffiz

Architecture decision records. Table 115 records the main decisions, the alternatives considered and the reasons.

Table 115: Architecture decision records

ADR	Decision	Alternatives considered	Rationale and consequence
ADR-01	Flutter for the user interface, with Kotlin platform channels for services, SMS, sensors and launcher aliases.	Native Kotlin; React Native.	One code base for a two-person team; native code is limited to the parts Flutter cannot reach.
ADR-02	Firebase as the backend platform.	Supabase; Cloudflare Workers and D1.	Phone authentication, real-time listeners, offline cache and push messaging come in one platform within free-tier limits.
ADR-03	A pre-trained audio-event classifier of the YAMNet class, run with TensorFlow Lite on the phone [5].	Cloud inference; training a custom model.	Keeps audio on the device and needs no training data or GPU. Accuracy is bounded by the pre-trained model and is evaluated (NFR-SAF-02).
ADR-04	An open-source, offline keyword-spotting engine (the sherpa-onnx keyword spotter) for the two phrases [6].	Picovoice Porcupine; openWakeWord; Vosk grammar mode.	Needs no network, account or access key (CON-7) and accepts a phrase typed as text. Accuracy on local accents is evaluated; the alternatives remain as fallbacks.
ADR-05	A compact sentence-embedding model of the MiniLM class with embeddings computed before release [7].	Keyword search only; hosted embedding service.	Search by meaning with no network call. The keyword fallback covers model failure.

ADR	Decision	Alternatives considered	Rationale and consequence
ADR-06	SMS through the Android SMS manager; WhatsApp through a share link that the user confirms.	WhatsApp Business API.	SMS needs no data. WhatsApp cannot be sent without user interaction, and the Business API needs paid, approved templates.
ADR-07	SQLite through Drift for local data, with WorkManager for queue retries.	Key-value storage only.	A durable queue and relational queries survive restarts.
ADR-08	AES-256-GCM encryption of evidence with a Keystore key; files in private storage, excluded from backup.	Plain files; cloud storage.	Evidence stays on the device and unreadable by other applications.
ADR-09	Geohash cells of precision 7, aggregated by a scheduled Cloud Function.	PostGIS on a relational backend.	Works on Firestore without a second backend; cell queries are simple.
ADR-10	Google Maps SDK for online maps; open map data for offline areas.	Google Maps only; open maps only.	Google's terms do not allow storing its tiles; open data can be stored for up to three areas.
ADR-11	Riverpod for state management.	Bloc; Provider.	Testable, compile-safe providers fit the modular packages.
ADR-12	The admin website is a separate Flutter web build on muhaffiz.me.	A page inside the user application; a separate JavaScript stack.	Separation from the user application (CON-11) with shared models and one language.
ADR-13	Trustees without the application acknowledge through a hosted alert page linked in the message.	SMS reply parsing.	A link can be tracked reliably; SMS replies cannot be read without extra permissions.

4.3 Design Models

Muhaffiz is an object-oriented, partly event-driven system, so the models are chosen to explain structure, interaction and behaviour. The use-case diagrams are in Section 3.2.22. This section gives class diagrams for the main domains, system-sequence and detailed-sequence diagrams for the critical interactions, activity diagrams for workflows, state diagrams for entities with state-dependent behaviour, a component diagram, and an event-response table for the background behaviour. Data-flow diagrams are not used, because the system is not designed as a data-processing pipeline.

4.3.1 Class diagrams

Figure 8 shows the SOS core. The SosOrchestrator creates a SosEvent for every SOS. The event has one ChannelDelivery for each trustee and channel; the DeliveryManager creates them, uses the ConnectivityMonitor to learn the tier, and holds undelivered ones in the OutboundQueue. The EvidenceVault keeps the EvidenceRecordings of events, and the

EscalationManager monitors an event, collects its Acknowledgements and, if needed, sends the escalation message to the AuthorityNumbers and logs it in EscalationRecords.




Figure 8: Class diagram: SOS core, delivery, evidence and escalation

Figure 9 shows detection and voice. The AudioMonitor passes a burst to the SoundClassifier; the FusionRule combines the score with the MotionAnalyzer result and starts the CountdownController, which on expiry hands over to the TriggerEngine. The

KeywordSpotter uses the PhraseProfile and sends detected phrases to the TriggerEngine, to the SharingManager (stop-sharing context) and to DecoyMode. The ConsentSettings enable the monitor and the spotter.




Figure 9: Class diagram: detection, voice and consent

Figure 10 shows the family and community classes: an Account creates Circles and has Memberships; a Circle issues Invitations; a Membership shares a LocationShare under the control of the SharingManager. Accounts submit IncidentReports that are counted in CellScores, apply to become a HelperProfile, create and answer HelpRequests, and file MissingChildReports.




Figure 10: Class diagram: family and community

Figure 11 shows the knowledge, identity and administration classes. SemanticSearch ranks LibraryItems with a SentenceEmbedder and falls back to KeywordSearch; the SafeLocationFinder chooses a DirectoryEntry; the AuthService opens a session; AppDisguise changes the launcher appearance; and an AdminUser reviews the ModerationQueue, which records AdminDecisions.




Figure 11: Class diagram: knowledge, identity and administration

4.3.2 System-sequence and detailed-sequence diagrams

Figure 12 is the system-sequence diagram of the manual SOS (UC-01): it treats Muhaffiz as one unit and shows only the exchange with the user, the trustee and a helper. The detailed-sequence diagrams then show how the components cooperate. Figure 13 shows the dispatch of an SOS. Figure 14 shows automatic detection (UC-02) with its cancel path, and Figure 15 the voice trigger (UC-03). Figure 16 shows the stop-sharing by safe phrase (UC-09), including that no message reaches other members. Figure 17 shows the escalation (UC-25), and Figure 18 the retry of the outbound queue. Figure 19 shows the invitation and acceptance of a circle member (UC-07), Figure 20 the nearby-help request (UC-15), Figure 21 the missing-child report (UC-23), Figure 22 the semantic search (UC-17), Figure 23 the helper verification (UC-14), Figure 24 the incident report and heatmap (UC-12, UC-13), and Figure 25 the sign-in (UC-19).




Figure 12: System-sequence diagram: manual SOS (UC-01)




Figure 13: Detailed sequence: SOS dispatch




Figure 14: Detailed sequence: automatic distress detection (UC-02)




Figure 15: Detailed sequence: voice-triggered SOS (UC-03)




Figure 16: Detailed sequence: stop sharing by safe phrase (UC-09)




Figure 17: Detailed sequence: escalation to authorities (UC-25)




Figure 18: Detailed sequence: offline queue and retry




Figure 19: Detailed sequence: circle invitation (UC-07)




Figure 20: Detailed sequence: nearby help (UC-15)




Figure 21: Detailed sequence: missing-child report (UC-23)




Figure 22: Detailed sequence: semantic library search (UC-17)




Figure 23: Detailed sequence: helper verification (UC-14)




Figure 24: Detailed sequence: incident report and heatmap (UC-12, UC-13)




Figure 25: Detailed sequence: sign-in (UC-19)

4.3.3 Activity diagrams

Figure 26 shows the workflow of an SOS from the trigger to the acknowledgement check, with the work that runs in parallel after the SOS starts. Figure 27 shows the tiered delivery and its queue. Figure 28 shows how a detected phrase is handled in its context, and Figure 29 the semantic search with its fallback. Four workflows involve several parties and are drawn with swimlanes: Figure 30 the onboarding and consent, Figure 31 the missing-child report with moderation, Figure 32 the incident report and the heatmap aggregation, Figure 33 the helper verification and Figure 34 the nearby help.



Trigger received
Trigger type?
manual
automatic / voice
Show 20 s countdown; vibrate, no sound
Hold SOS 1 s, or tap the lock-screen action
User cancels?
no, 20 s elapsed
yes
Start SOS: record trigger and mode (loud or silent)
Discard trigger; resume monitoring
Obtain location: fix within 10 s, or cached with age
Start evidence recording
Start 3-minute no-response timer
Play siren (loud) or stay quiet (silent)
Dispatch by tier (SMS, push, email, helpers)
Update SOS event log
Acknowledged in 3 min?
yes
no
30 s warning with cancel
Stop timer; show acknowledgement
Cancelled?
no
Send escalation message; write escalation log

Figure 26: Activity diagram: SOS pipeline



dispatch(event, location)
Detect tier: probe backend
(T_probe = 3 s, T_good = 1 s)
Tier?
Tier 1
Tier 2 / 3
Tier 1: send SMS to
every trustee
Tier 2 or 3: send SMS, push
and email in parallel
Loud SOS and
WhatsApp enabled?
yes
no
Queue push, email,
WhatsApp and Near Help
later
Offer WhatsApp message;
user confirms send
Channel
failed?
yes
no
Enqueue; back-off
(15 s doubling, max 15 min)
Mark delivered;
update event log
retry
sent
Connectivity returns:
flush queue within 30 s

Figure 27: Activity diagram: tiered delivery and retry




Figure 28: Activity diagram: phrase handling in context



User types a query
Embedding model available?
yes
no
Embed the query on the device (384 values)
Cosine similarity with every bundled embedding; sort; take top K
Best similarity >= 0.30?
yes
no
Keyword search over titles, summaries and text; add notice
Show ranked cards with relevance indicators
Open or bookmark a result

Figure 29: Activity diagram: semantic search with fallback




Figure 30: Activity diagram with swimlanes: onboarding and consent




Figure 31: Activity diagram with swimlanes: missing-child report




Figure 32: Activity diagram with swimlanes: incident report and heatmap




Figure 33: Activity diagram with swimlanes: helper verification




Figure 34: Activity diagram with swimlanes: nearby help

4.3.4 State diagrams

Figure 35 shows the life of an SOS event, with the actions performed on entering each state. Figure 36 shows the confirmation countdown. Figure 37 shows a circle member, including the stopped state in which others see only the last location, and Figure 38 the invitation. Figure 39 shows a missing-child report, Figure 40 a helper application, Figure 41 the connectivity tier, and Figure 42 an evidence recording.




Figure 35: State diagram: SOS event




Figure 36: State diagram: confirmation countdown



Not in circle
invited by a member
declines or 7 days pass
Invited
entry / invitation pending (7 days)
accepts
Member of the circle
Accepted
entry / show circle; sharing is off
member enables sharing
Sharing
entry / show persistent indicator; publish on movement
do / publish location
safe phrase on the
stop-sharing screen
member resumes sharing
leave circle
Stopped
entry / stop publishing; freeze last location
do / others see "Not live"
leave circle
Left circle
entry / remove membership; delete stored location

Figure 37: State diagram: circle member and sharing




Figure 38: State diagram: circle invitation




Figure 39: State diagram: missing-child report




Figure 40: State diagram: Verified Helper application




Figure 41: State diagram: connectivity tier



Not recording
do / if permission is missing: SOS continues, log entry
SOS starts
[permission granted]
Recording
entry / open microphone; create encrypted stream
do / write encrypted audio
user stops, SOS closes,
or storage is full
Stopped
entry / close stream; save metadata (time, location, trigger)
encryption finished
Stored
entry / listed in the evidence list
do / retention timer; export a copy on request
user deletes, or retention reached
Deleted
entry / remove file and key

Figure 42: State diagram: evidence recording

4.3.5 Component diagram and event-response table

Figure 43 shows the packages grouped by function and the runtime dependencies between the groups. The safety core depends on delivery and storage, which depends on the backend functions; identity and consent control the safety core; the family and community group uses delivery for push and queueing; and the knowledge group uses bundled data.




Figure 43: Component diagram

The detection, delivery and escalation behaviour is driven by events in the background, so Table 116 lists the important events, the state of the system when they occur and the response.

Table 116: Event-response table

Event	System State	Response
Sound level rises suddenly above the ambient level	Detection on; monitoring	Classify the buffered burst; read motion; apply the fusion rule (FR-02.02, FR-02.03).
Fusion rule satisfied	Monitoring	Vibrate 20 seconds and show the cancel control (FR-02.04).
User taps cancel during the countdown	Countdown	Stop the vibration, send nothing, resume monitoring.
Countdown ends with no cancel	Countdown	Start the SOS with trigger "automatic" or "voice".

Event	System State	Response
Safe phrase detected	Voice on; no stop-sharing screen open	Start the countdown and then the SOS (FR-03.04).
Safe phrase detected	Stop-sharing screen open	Stop sharing; show the private confirmation; start no SOS (FR-05.02).
Duress phrase detected	Voice on	Start the countdown, then a silent SOS; show the decoy screen (FR-03.04, FR-06.01).
Connectivity tier changes	Any	Update the status strip; flush the queue if the tier is 2 or 3 (FR-12.01, FR-12.03).
Fresh location fix not obtained in 10 seconds	SOS starting	Use the cached location and state its age (FR-13.01).
Acknowledgement received	SOS active; timer running	Record it, stop the timer, show it (FR-19.01).
3-minute timer expires with no acknowledgement	SOS active	Start the 30-second warning (FR-19.03).
Warning ends with no cancel	Escalation warning	Send the escalation message and log it (FR-19.05, FR-19.06).
Device restarts	Detection or voice enabled	Restart the services and the queue worker (NFR-REL-03).
72 hours pass without renewal	Missing-child report active	Set "expired", delete the photo, stop alerts (FR-17.03).

4.4 Data Design

The information domain is divided into data held on the server in Cloud Firestore and data held only on the device. Firestore holds what must be shared between users: accounts, trustees, circles, memberships, invitations, shared locations, reports and cell scores, helper profiles and requests, acknowledgements, missing-child reports and administrator decisions. The device holds what must stay private or work offline: the SOS events and their deliveries, the outbound queue, the evidence recordings and their keys, the escalation records, the bundled library and directory, bookmarks and settings. Retention follows the rules of Chapter 3: evidence is deleted after the retention period (BR-23), heatmap reports older than 12 months are removed (NFR-PRV-02), photos are deleted when no longer needed (BR-26), and identity images are deleted after review (BR-18).

Data dictionary. Table 117 lists the entities in alphabetical order with their storage, attributes and meaning. Two further entities, the consent record and the authority numbers, are stored on the device as settings and are not drawn in the entity-relationship diagram.

Table 117: Data dictionary

Entity	Storage	Attributes (name: type)	Description
Acknowledgement	Server	id: string; sosId: string; source: enum(trustee, helper); at: timestamp	A confirmation by a trustee or a helper that they have seen the alert.
Account	Server	uid: string; phone: string; name: string; messageTemplate: string(160); defaultMode: enum; createdAt: timestamp	A registered user.
AdminDecision	Server	id: string; adminUid: string; target: string; decision: enum; at: timestamp	A logged moderation or review decision.
AuthorityNumber	Device	number: string; channel: enum(sms, call, share)	A configured authority number for escalation.
Bookmark	Device	itemId: string; createdAt: timestamp	A bookmarked library item.
CellScore	Server	geohash7: string; counts: map(category to int); score: double; updatedAt: timestamp	The aggregated, weighted report score of one cell.
ChannelDelivery	Device	id: string; sosId: string; trusteeId: string; channel: enum; status: enum; attempts: int; lastAttempt: timestamp	The delivery of one SOS message on one channel to one trustee.
Circle	Server	id: string; createdBy: string; createdAt: timestamp	A family circle.
ConsentRecord	Device	micDetection: bool; voiceActivation: bool; locationSharing: bool; acceptedAt: timestamp	The user's consent and toggles.
DirectoryEntry	Device (bundled)	id: string; name: string; category: enum; phone: string; lat, lng: double?	A hospital, police station, helpline or emergency number.
EscalationRecord	Device	id: string; sosId: string; number: string; channel: enum; status: enum; at: timestamp	One escalation message and its delivery.
EvidenceRecording	Device	id: string; sosId: string; startedAt: timestamp; duration: int; trigger: enum; encryptedPath: string	An encrypted audio recording made after an SOS.
HelperProfile	Server	uid: string; status: enum(pending, verified, rejected, revoked); verifiedAt: timestamp	The helper status of a user.
HelpRequest	Server	id: string; uid: string; geohash: string; radius: int; status: string; createdAt: timestamp	A request for nearby help.
IncidentReport	Server	id: string; uid: string; category: enum; note: string(280)?; geohash7: string; createdAt: timestamp; status: enum	A user report of an unsafe incident.
Invitation	Server	id: string; circleId: string; toPhone: string; status: enum; expiresAt: timestamp	An invitation to a circle.
LibraryItem	Device (bundled)	id: string; title: string; category: enum; summary: string; body: string; embedding: float[384]	A library article, video or link and its search embedding.
Membership	Server	id: string; circleId: string; uid: string; state: enum; sharing: bool; lastShared: (lat, lng, time)	The membership of a user in a circle and its sharing state.
MissingChildReport	Server	id: string; guardianUid: string; childName: string; age: int; photoRef: string; description: string; lastSeen: (place, time); status: enum; expiresAt: timestamp	A missing-child report.
QueueItem	Device	id: string; deliveryId: string; payload: blob; dueAt: timestamp	An outbound message waiting to be sent or retried.
SosEvent	Device	id: string; startedAt: timestamp; trigger: enum; mode: enum; location: (lat, lng); locationAge: int; status: enum	One SOS from start to close.

Entity	Storage	Attributes (name: type)	Description
Trustee	Server and device	id: string; uid: string; name: string; phone: string; email: string?; channels: set	A contact who receives alerts.

ER diagrams. Figure 44 shows the entities held on the server in Cloud Firestore and Figure 45 those held on the device. Crow's-foot notation shows the cardinality of each relationship, and foreign keys (FK) name the related entity.




Figure 44: Entity-relationship diagram: server data (Cloud Firestore)




Figure 45: Entity-relationship diagram: device data

Normalization, indexes and constraints. The device database is relational and is kept in third normal form: a delivery refers to its SOS event and trustee by key, and a queue item refers to its delivery. The server data is document-oriented and is deliberately denormalized where a screen needs it in one read, for example the member's last shared location is stored inside the membership. Table 118 lists the indexes and the constraints that protect integrity.

Table 118: Indexes and constraints

Store	Index or Constraint	Purpose
Firestore	Index on Membership (circleId, state)	List the members of a circle and their state.
Firestore	Index on IncidentReport (geohash7, createdAt)	Load the reports of a cell and apply the 12-month limit.
Firestore	Index on HelperProfile (status) and geohash of the last position	Find verified helpers within a radius.
Firestore	Index on MissingChildReport (status, lastSeen geohash)	Find active reports near a place.
Firestore	Index on Acknowledgement (sosId, at)	Read the acknowledgements of one SOS.
Firestore rules	Account.phone is unique; (circleId, uid) is unique; age is between 0 and 17; enumerated values only	Integrity of server data.
Firestore rules	A user reads another user's location only under BR-10 to BR-14 and BR-32; only administrators read identity images	Confidentiality (NFR-SEC-03, NFR-SEC-06).
SQLite	Index on ChannelDelivery (sosId); index on QueueItem (dueAt); index on LibraryItem (category)	Fast log, retry and library queries.
SQLite	Foreign keys with delete cascade: deliveries and queue items are deleted with their SOS event	No orphan rows.

4.5 Human Interface Design

The interface is designed so that the most important action, the SOS, is available at once, and so that every protective feature is easy to reach but not obvious to a bystander. A new user passes through sign-in, consent, trustee setup and phrase enrolment, and then reaches the Home screen, from which the main areas are reached by the bottom navigation. Figure 46 shows the navigation flow, and Table 119 lists the screens with their purpose, objects, actions and related requirements.






Figure 46: Navigation flow of the application

Screen images. Figure 47, Figure 48 and Figure 49 show the key screens from the user's perspective: the Home, countdown and SOS-active screens, the family map, the danger map and the library search, and the decoy, stop-sharing and trustee screens. The other screens are shown in Section 5.4.



Home screen | Countdown screen | SOS active screen

Figure 47: Key screens: Home, countdown and SOS active



Family map screen | Danger map screen | Library search screen

Figure 48: Key screens: family map, danger map and library search




Figure 49: Key screens: decoy, stop sharing and trustees

Screen objects and actions. On the Home screen the large red SOS control starts an SOS when it is held for one second, the Loud and Silent switch selects the SOS mode, the status strip shows the connectivity tier and the state of detection and voice activation, and four tiles open the trustees, the evidence list, the directory and the safe-location guidance. On the countdown screen a ring shows the seconds left and one large button cancels the alert; the phone vibrates and makes no sound. On the SOS-active screen a red banner shows that an SOS is active, a card for each trustee shows the delivery status per channel, a card shows the nearby helpers, and the Stop alarm and Evidence buttons act on the siren and the recording. The family map shows each member as a marker, a live member in green and a member who has stopped sharing in grey with the label "Not live", and a button opens the stop-sharing screen. The danger map shows green-to-red cells with a legend, and a tap on a cell opens a panel with the category counts. The library search screen has a field for a question in the user's words, category chips, an offline indicator, and result cards with a relevance bar. The decoy screen is a calculator that works normally; a two-second hold on the equals key opens the real application. The stop-sharing screen asks for the safe phrase, shows that the phone is listening and states that nobody else is notified. The trustee screen lists trustees with a chip for each enabled channel.

Table 119: Screens of the application and the admin website

Screen ID and Name	User or Role	Purpose	Main Objects and Actions	Related FR or UC
S-01 Sign-in	Primary User	Verify the phone number	Number field, send code, code field, verify	FR-14.01, UC-19
S-02 Onboarding consent	Primary User	Obtain informed consent	Consent text, agree box, accept, not now	FR-15.01, FR-18.05, UC-20
S-03 Trustees	Primary User	Manage trustees and channels	Trustee cards, channel chips, add, edit, remove	FR-01.05, UC-04
S-04 Phrase enrolment	Primary User	Enrol the safe and duress phrases	Phrase fields, sample progress, record	FR-03.01, FR-03.02, UC-06
S-05 Home	Primary User	Start an SOS; see status	SOS control, mode switch, status strip, tiles, navigation	FR-01.01, FR-01.04, FR-12.01, UC-01
S-06 Countdown	Primary User	Cancel an automatic or voice alert	Ring, seconds, cancel button	FR-02.04, FR-03.04, UC-02, UC-03
S-07 SOS active	Primary User	Follow the SOS	Banner, delivery cards, helper card, stop alarm, evidence	FR-01.02, FR-01.03, FR-01.06, FR-19.01
S-08 Family circle	Family Circle Member	See members; invite; stop sharing	Map, member cards, invite, stop-sharing button	FR-04.01, FR-04.02, FR-05.04, UC-07, UC-08
S-09 Stop sharing	Family Circle Member	Stop sharing by safe phrase	Prompt, listening indicator, cancel, leave link	FR-05.02, FR-05.03, UC-09, UC-10
S-10 Danger map	Primary User	View the heatmap	Map, cells, legend, zone panel, report button	FR-07.04, UC-13
S-11 Incident report	Primary User	Report an incident	Category chips, location pin, note, submit	FR-07.01, UC-12
S-12 Nearby help	Primary User; Verified Helper	Request or answer help	Request card, accept, decline, offline notice	FR-08.02 to FR-08.04, UC-15
S-13 Helper registration	Primary User	Apply to become a helper	Name, phone, identity photo, submit, status	FR-08.01, UC-14
S-14 Library	Primary User	Browse and search	Search field, chips, result cards, bookmark	FR-09.01 to FR-10.05, UC-16, UC-17
S-15 Missing-child report	Guardian	File a report	Child fields, photo, guardian box, submit	FR-17.01, UC-23
S-16 Evidence list	Primary User	Manage recordings	Recording cards, export, delete, retention note	FR-18.03, FR-18.04, UC-24
S-17 Directory	Primary User	Call an emergency service	Entry cards, call buttons	FR-11.01 to FR-11.03, UC-18
S-18 Safe location	Primary User	Get guidance to the nearest safe place	Map, route line, distance card, open directions	FR-20.01 to FR-20.03, UC-26
S-19 Escalation warning	Primary User	Cancel an escalation	Seconds, cancel button	FR-19.03, UC-25
S-20 Escalation settings	Primary User	Set authority numbers and channels	Number cards, change, add	FR-19.04, UC-25
S-21 Settings and consent	Primary User	Change toggles and defaults	Switches, retention	FR-15.02, FR-14.03, UC-20
S-22 Privacy summary	Primary User	See what is stored and where	Three data cards	FR-15.03, UC-20

Screen ID and Name	User or Role	Purpose	Main Objects and Actions	Related FR or UC
S-23 App disguise	Primary User	Choose an appearance	Option cards, apply	FR-21.01, FR-21.02, UC-27
S-24 Decoy	Primary User	Show a neutral screen	Calculator keys, hidden hold	FR-06.01, FR-06.02, UC-11
S-25 Admin overview	Administrator	See users, queues and delivery	Metric tiles, charts, bars	FR-16.01, FR-16.04, UC-22
S-26 Moderation queue	Administrator	Decide on flagged items	Table, approve, remove, reject	FR-16.02, FR-16.03, UC-21

4.6 Security, Error Handling and Logging Design

Authentication and authorization. Users authenticate with a one-time code sent to their phone number; administrators authenticate with email and password and hold an administrator role (FR-14.01, FR-16.05). Authorization is enforced on the server by Firestore and Storage rules, so that a client cannot read data it is not entitled to even if it is modified. **Input validation** is applied on the device and again by the rules and the functions. **Sensitive data** is handled by keeping audio on the device, encrypting evidence, deleting identity images and photos after use, and masking phone numbers in the admin website.

Error handling. A failure is handled where it occurs and isolated from the safety path: a failed channel is logged and queued, a failed model disables only its feature, a missing permission produces a prompt, and a full storage stops only the recording. User messages state the problem and the next step in at most two sentences (NFR-USA-06). **Logging.** The device keeps an SOS event log and an escalation log for the user, and a technical log at three levels (error, warning, information) that holds no audio, no transcript and no location trace. The backend logs function errors and delivery outcomes without user identities for the health monitoring of FR-16.04. Administrator decisions are logged with the administrator and the time. Logs on the device are private to the application, and server logs are readable only by administrators and the developers; technical logs are kept for 30 days. Table 120 lists the main threats, failures and events with their handling.

Table 120: Security, error handling and logging design

Design ID	Threat, Failure or Event	Control or Handling Strategy	Log or Alert	Related Requirement
SD-01	A user tries to read another user's location	Firestore rules allow reads only under BR-10 to BR-14 and BR-32.	Denied requests counted in the backend log.	NFR-SEC-03, BR-32

Design ID	Threat, Failure or Event	Control or Handling Strategy	Log or Alert	Related Requirement
SD-02	A non-administrator opens the admin website	Role check on sign-in and in every rule; access denied.	Denied attempt logged.	FR-16.05, NFR-SEC-04
SD-03	A one-time code is guessed	Lock for 10 minutes after five wrong codes; code expiry.	Lock events logged.	FR-14.01
SD-04	An evidence file is copied from the device	AES-256-GCM encryption; key in the Keystore; private storage; no backup.	No log of file content.	FR-18.02, NFR-SEC-02
SD-05	Audio would leave the device	The detection and voice packages have no network access; tests inspect traffic.	Test alert if traffic appears.	FR-02.05, NFR-SEC-05
SD-06	A model file is missing or corrupt	Disable the feature, tell the user, keep manual SOS.	Warning logged on the device.	NFR-ROB-01
SD-07	The SMS permission is missing	Prompt (loud mode) and use other channels.	Event logged with the missing permission.	FR-12.02, UC-01 E1
SD-08	No data connection	Use SMS; queue the other channels; retry later.	Delivery status in the SOS log.	FR-12.03, BR-05
SD-09	The monitoring service is stopped by the system	Restart by the system and after reboot; onboarding explains battery settings.	Restart logged.	FR-02.01, NFR-REL-03
SD-10	A report spam or malicious flagging of an area	Rate limits, near-duplicate check, burst detection and moderation.	Moderation queue entry.	FR-07.05, BR-15
SD-11	A person pretends to be a helper	Identity check by an administrator before approval; revocation.	Decision logged.	FR-08.01, FR-16.03, BR-18
SD-12	A false missing-child report	Immediate review queue, removal, author suspension, rate limit.	Decision logged.	FR-17.05, BR-27
SD-13	A child photo or identity image is exposed	Storage rules; deletion on found, expiry or decision.	Deletion logged.	FR-17.06, NFR-SEC-06
SD-14	Malformed or oversized input	Validation on the device, in the rules and in the functions.	Rejected input counted.	NFR-ROB-02
SD-15	Low storage during an SOS	Stop the recording; continue the SOS.	Entry in the SOS log.	NFR-ROB-03
SD-16	The application is killed during an SOS	The queue and the SOS state are stored in SQLite and resumed at start.	Resume logged.	NFR-REL-02
SD-17	A function or the backend fails	The safety path does not call the backend; functions are retried; errors are shown to administrators.	Function error log.	NFR-AVL-01, FR-16.04
SD-18	The phone is forced open by another person	Decoy screen and app disguise; duress phrase.	No visible log entry.	FR-06.01, FR-21.01, BR-28

4.7 Risk Analysis and Sprint Plan

Table 121 lists the risks with their probability and impact (High, Medium or Low), their mitigation or contingency, and the owner. Muhammad Shamoil owns the detection, voice, search, SOS front end, decoy, consent, evidence, escalation and disguise modules and the interface design; Ali Raza owns the backend, family, location, heatmap, Near Help, missing-child, delivery, navigation, authentication and admin modules and the deployment.

Table 121: Risk analysis

Risk ID	Risk	Probability	Impact	Mitigation or Contingency	Owner
RSK-01	The pre-trained sound classifier produces too many false alarms or misses.	Medium	High	Confirm-or-cancel countdown; fusion with motion; evaluate on labelled clips and tune thresholds; manual SOS is the primary path.	M. Shamoil
RSK-02	The keyword spotter is unreliable for local accents or Urdu phrases.	Medium	High	Test with team and volunteer voices; use the sensitivity set at enrolment; fall back to openWakeWord or Vosk; manual SOS remains.	M. Shamoil
RSK-03	Android stops background services to save battery.	High	High	Foreground services; request battery-optimisation exemption in onboarding; restart logic; test on several manufacturers.	M. Shamoil
RSK-04	Battery use of monitoring is too high.	Medium	Medium	Spike gate keeps classification rare; measure against NFR-PER-10; reduce sampling if needed.	M. Shamoil
RSK-05	SMS cannot be sent because of permission policy or carrier limits.	Medium	High	Request the permission clearly; test on several carriers; provide the other channels and the queue.	A. Raza
RSK-06	WhatsApp cannot send without the user.	High	Low	Treated as user-confirmed; SMS, push and email are the automatic channels (BR-04).	A. Raza
RSK-07	Near Help is not useful because few helpers are nearby.	High	Medium	Evaluate with simulated helpers and label them as such; fall back to trustees by SMS.	A. Raza
RSK-08	Authorities do not act on, or accept, escalation messages.	Medium	High	Describe the hand-off precisely; let the user choose channels; confirm numbers before use (Appendix C).	M. Shamoil
RSK-09	Privacy or consent concerns about listening.	Medium	High	Explicit consent, on-device processing, no audio storage, privacy summary, tests that inspect traffic and storage.	M. Shamoil
RSK-10	Coercion defeats the consent model despite the safeguards.	Medium	Medium	Document the limit; use the safe phrase, the decoy and the last-known display; do not claim it is solved.	A. Raza
RSK-11	Firebase free-tier limits are exceeded.	Low	Medium	Quota calculation; movement-based updates; scheduled aggregation; reduce listener scope.	A. Raza
RSK-12	False or abusive reports and helper applications.	Medium	Medium	Rate limits, moderation queue, identity review, revocation.	A. Raza
RSK-13	The schedule is too short for all 21 modules.	Medium	High	Build in priority order; the Low modules (MOD-20, MOD-21) are dropped first, then Medium modules, without touching the core.	Both
RSK-14	Offline map data licence or size is a problem.	Medium	Low	Limit to three areas; choose a source that permits storage; guidance works with distance and direction alone.	A. Raza
RSK-15	A device or Android version behaves differently.	Medium	Medium	Test on at least three device models; isolate platform code in the platform layer.	Both
RSK-16	The microphone indicator of Android reveals recording in a silent SOS.	High	Low	Cannot be hidden; documented as a limitation; evidence can be switched off in the settings.	M. Shamoil

Table 122 lists the milestones in the order in which they are built. The plan uses milestones and not calendar dates; the dependencies show why the order is fixed.

Table 122: Milestone plan

Sprint or Milestone	Objectives	Requirements or Modules	Deliverables	Dependencies	Status
M1 Foundation	Project skeleton, theme, navigation, local database, authentication, consent flow, configuration	MOD-14, MOD-15, MOD-13	Running application with sign-in, onboarding and settings	None	Scheduled
M2 Core SOS and delivery	Manual SOS, trustees, dispatch on all channels, loud and silent modes, tiers, queue and retry, event log	MOD-01, MOD-12, MOD-13	Working SOS delivered by SMS at Tier 1 and by all channels at Tiers 2 and 3	M1	Scheduled
M3 Detection and voice	Monitoring service, classifier, fusion, countdown, keyword spotting, phrase enrolment, shared hook	MOD-02, MOD-03	Automatic and voice SOS with cancel	M2	Scheduled
M4 Family network and decoy	Circles, invitations, movement-based sharing, opt-out, last-known display, decoy	MOD-04, MOD-05, MOD-06	Family map with duress-aware sharing; decoy screen	M1, M3	Scheduled
M5 Community and admin	Incident reports, geohash aggregation, heatmap, helper registration, Near Help, admin site	MOD-07, MOD-08, MOD-16	Heatmap, nearby help and moderation	M2	Scheduled
M6 Knowledge	Library, semantic search, directory, safe-location guidance, offline maps	MOD-09, MOD-10, MOD-11, MOD-20	Offline library with search; directory; guidance	M1	Scheduled
M7 Follow-through	Evidence recording, escalation, missing-child report, app disguise	MOD-17, MOD-18, MOD-19, MOD-21	Evidence, escalation, missing-child alerts, disguise	M2, M5	Scheduled
M8 Evaluation and hardening	Test execution, detection and search evaluation, fixes, documentation	All modules	Test results, evaluation, final documents	M1 to M7	Scheduled

4.8 Chapter Summary

This chapter chose an object-oriented, layered and partly event-driven design built in risk-driven milestones, recorded the main architecture decisions, presented the class, sequence, activity, state and component models, the data design with the entity-relationship diagram, the screens and their navigation, the security, error-handling and logging design, and the risks and milestones. Chapter 5 now describes the algorithms, external components, backend interfaces, user interface and deployment that realize this design.

Chapter 5: Implementation and Deployment

Chapter Overview. This chapter describes how the design is realized. Section 5.1 gives the core algorithms with pseudocode, Section 5.2 lists the external APIs and SDKs, Section 5.3 specifies the interfaces of the project backend, Section 5.4 presents the user interface of each subsystem, and Section 5.5 describes the deployment. Source code is not reproduced.

5.1 Algorithms

The core behaviour of Muhaffiz is implemented by ten algorithms: the sound-level gate, the distress decision with fusion, the trigger and SOS pipeline, the tiered dispatch with retry, the phrase handling in context, the movement-based location publication, the heatmap cell score, the semantic search, the escalation timer, and the nearest safe location. Their constants are held in one configuration (NFR-MNT-02) and are listed in Table 123; the values are the defaults that the evaluation of Chapter 6 may tune.

Table 123: Algorithm parameters and default values

Parameter	Meaning	Default	Related
T_amb	Window for the rolling ambient sound level	10 s	FR-02.01
D_spike	Rise above the ambient level that counts as a sudden loud sound, for at least two consecutive 30 ms frames	15 dB	FR-02.01
T_buf	Length of the in-memory audio burst passed to the classifier	2 s	FR-02.02
θ_audio	Distress score at or above which the audio result counts as distress	0.60	FR-02.03
θ_high	Distress score at or above which the audio result alone satisfies the fusion rule	0.85	FR-02.03
W_motion	Motion window around the burst (2 s before to 3 s after)	5 s	FR-02.03
A_dev, G_rot	Motion anomaly: acceleration deviation from gravity, or rotation rate	15 m/s²; 6 rad/s	FR-02.03
T_count	Confirmation countdown	20 s	FR-02.04, BR-02
T_confirm	Time allowed for the safe phrase on the stop-sharing screen	15 s	FR-05.02
T_fix	Wait for a fresh location fix at SOS start	10 s	FR-13.01, BR-06
D_min	Movement that triggers a location publication	50 m	FR-05.01
T_probe, T_good	Backend probe timeout; round-trip time for Tier 3	3 s; 1 s	FR-12.01
B0, B_max	First retry delay and maximum delay (doubling)	15 s; 15 min	FR-12.03
P_geo, H	Geohash precision; report half-life	7; 90 days	FR-07.02, FR-07.03
τ_sim, K	Similarity threshold for semantic results; number of results	0.30; 10	FR-10.04, FR-10.05

Parameter	Meaning	Default	Related
T_ack, T_warn	No-response timer; warning countdown	180 s; 30 s	FR-19.02, FR-19.03
R_help, R_child	Helper radius; missing-child alert radius	1 km; 5 km	FR-08.02, FR-17.02

Table 124: Algorithm: sound-level gate (A1)

Algorithm: sound-level gate (A1)
Input: a stream of 30 ms audio frames
Output: a burst of T_buf seconds when a sudden loud sound occurs, otherwise nothing
1: ambient ← 0; ring ← empty buffer of T_buf seconds; run ← 0
2: for each frame f from the microphone do:
3: level ← decibelLevel(f); push f into ring; discard the oldest frame
4: if level > ambient + D_spike then run ← run + 1 else run ← 0
5: if run ≥ 2 then
6: emit burst(copy of ring); run ← 0; clear ring
7: else if run = 0 then
8: ambient ← slidingMean(ambient, level, T_amb)
9: end for
10: all frames and the ring exist in memory only
Complexity: O(1) time per frame; O(T_buf) memory.

Table 125: Algorithm: distress decision with fusion (A2)

Algorithm: distress decision with fusion (A2)
Input: a burst from A1; the motion window
Output: a countdown request, or no action
1: score ← classifier.score(burst) // distress probability, no transcript
2: discard burst
3: if score < θ_audio then return none
4: motion ← motionAnomaly(window W_motion, A_dev, G_rot)
5: if motionSensorsAvailable = false then ok ← (score ≥ θ_high)
6: else ok ← (motion = true) or (score ≥ θ_high)
7: if ok = false then return none
8: return countdown(T_count, trigger = automatic)
Complexity: O(1) per burst after the classifier inference, which is a fixed-size neural-network pass.

Table 126: Algorithm: trigger arbitration and SOS pipeline (A3)

Algorithm: trigger arbitration and SOS pipeline (A3)
Input: a trigger t (manual, automatic or voice) and a mode m
Output: an SOS event with dispatch, evidence and timers started

Algorithm: trigger arbitration and SOS pipeline (A3)
1: if t = manual then goto start
2: show countdown for T_count with vibration only
3: if user cancels within T_count then return // nothing is sent
4: start:
5: event ← new SosEvent(t, m, now)
6: location ← fix within T_fix, else cachedLocation with its age
7: in parallel do:
8: evidence.start(event)
9: escalation.start(event, T_ack)
10: if m = loud then playSiren() else stayQuiet()
11: delivery.dispatch(event, location) // see A4
12: log(event)
Complexity: O(c) for c trustee-channel pairs.

Table 127: Algorithm: tiered dispatch and queue retry (A4)

Algorithm: tiered dispatch and queue retry (A4)
Input: an event, a location and the trustee list
Output: delivery statuses; undelivered messages queued
1: tier ← detectTier(T_probe, T_good)
2: for each trustee u do:
3: channels ← u.channels, or {sms} if empty
4: send SMS(u) // always, uses no data
5: if tier ≥ 2 then
6: for each channel c in {push, email} ∩ channels do send(c, u)
7: else enqueue({push, email, nearHelp}, u)
8: if whatsapp ∈ channels and m = loud then offerWhatsapp(u)
9: on result r of any send: if r = failed then enqueue(message) else markSent(message)
10: on tier change to ≥ 2: delay ← B0; for each queued item q do try send(q);
11: if failed then reschedule(q, min(2 × delay, B_max)) else markDelivered(q)
Complexity: O(c) per dispatch; each retry round is O(q) for q queued items.

Table 128: Algorithm: phrase handling in context (A5)

Algorithm: phrase handling in context (A5)
Input: a phrase detection p ∈ {safe, duress} and the current context
Output: an action
1: if context = stopSharingScreen and p = safe then
2: sharing.stop(); showPrivateConfirmation(); return
3: if p = safe then return trigger(voice, defaultMode) // A3 with countdown

Algorithm: phrase handling in context (A5)
4: if p = duress then
5: decoy.show(); return trigger(voice, silent)
6: if context = stopSharingScreen and no phrase within T_confirm then closeScreen()
Complexity: O(1) per detection.

Table 129: Algorithm: movement-based location publication (A6)

Algorithm: movement-based location publication (A6)
Input: location updates and the member's sharing flag
Output: published locations
1: last ← null
2: for each location update x do:
3: if sharing = false then continue
4: if last = null or distance(last, x) > D_min then
5: publish(x, now); last ← x
6: on stopSharing(): sharing ← false; freeze(last) // others see last, "Not live"
Complexity: O(1) per update.

Table 130: Algorithm: heatmap cell score (A7)

Algorithm: heatmap cell score (A7)
Input: the reports R of a cell
Output: the score of the cell and its category counts
1: score ← 0; counts ← empty map
2: for each report r in R do:
3: age ← now − r.createdAt (in days)
4: score ← score + 0.5 ^ (age / H)
5: counts[r.category] ← counts[r.category] + 1
6: return (score, counts) // colour = scale(score)
Complexity: O(n) per cell for n reports; run by a scheduled function per changed cell.

Table 131: Algorithm: semantic search with keyword fallback (A8)

Algorithm: semantic search with keyword fallback (A8)
Input: a query string q and the bundled embeddings E
Output: a ranked list of at most K items
1: if embedder.available = false then return keywordSearch(q)
2: v ← embedder.embed(q) // on device, 384 values
3: for each item i do: sim[i] ← dot(v, E[i]) / (norm(v) × norm(E[i]))
4: sort items by sim descending; top ← first K items
5: if sim[top[0]] < τ_sim then return keywordSearch(q)

Algorithm: semantic search with keyword fallback (A8)
6: return top with relevance = sim
Complexity: O(N·d) for N items and d = 384; embedding the query is one model pass.

Table 132: Algorithm: escalation timer (A9)

Algorithm: escalation timer (A9)
Input: an SOS event and the authority numbers
Output: an escalation message, a cancellation or an acknowledgement
1: wait up to T_ack for an acknowledgement
2: if acknowledgement received then stop; return
3: show warning for T_warn with one-tap cancel
4: if cancelled then log("cancelled"); return
5: msg ← compose(name, callback, location and age, time, trigger, evidenceExists)
6: for each number n do: send(msg, n.channel); log(n, status)
Complexity: O(a) for a authority numbers.

Table 133: Algorithm: nearest safe location (A10)

Algorithm: nearest safe location (A10)
Input: a position p and the directory entries with coordinates
Output: the nearest entry, its distance and its bearing
1: best ← null
2: for each entry e of category hospital or police do:
3: d ← haversine(p, e.position)
4: if best = null or d < best.d then best ← (e, d)
5: bearing ← initialBearing(p, best.e.position) // degrees from north
6: return (best.e, best.d, bearing)
Complexity: O(n) for n entries.

5.2 External APIs/SDKs

Table 134 lists the third-party APIs and SDKs. Versions are pinned in the dependency lock files of the project; the table gives the major version or the family.

Table 134: External APIs and SDKs

Name and Version	Description	Purpose of Usage	Endpoint, Function or Module
Flutter 3.x (stable) and Dart 3.x	Cross-platform UI toolkit and language.	User application and admin website.	All screens and packages.
Firebase Authentication (FlutterFire, current stable)	Identity service.	Phone sign-in and administrator sign-in.	verifyPhoneNumber, signInWithEmail.

Name and Version	Description	Purpose of Usage	Endpoint, Function or Module
Cloud Firestore (FlutterFire)	Real-time document database with offline cache.	Shared data and acknowledgements.	collection, snapshots, transactions.
Firebase Cloud Messaging	Push delivery.	Alerts and help requests.	send by token; topic by geohash.
Cloud Storage for Firebase	File storage with rules.	Identity images and child photos.	putFile, getDownloadURL, delete.
Cloud Functions for Firebase (Node.js)	Server-side functions.	Email, acknowledgement, scheduled jobs.	HTTPS callable; scheduled; Firestore triggers.
Firebase Hosting	Static and dynamic web hosting.	Admin website and alert page.	Custom domains, rewrites to functions.
Google Maps SDK for Android 18.x	Interactive maps.	Heatmap, family map and online guidance.	GoogleMap, Polygon, Marker.
Open map data and an open-source map renderer (for example MapLibre)	Offline map areas.	Maps without a connection.	Region download; offline style.
TensorFlow Lite 2.x	On-device inference runtime.	Sound classification; embedding.	Interpreter.run.
YAMNet-class audio-event model	Pre-trained sound classifier [5].	Distress sound score.	Input 0.975 s frames; class scores.
sherpa-onnx keyword spotter	Open-source offline keyword spotting [6].	Safe and duress phrases.	Keyword spotter with a typed phrase.
MiniLM-class sentence-embedding model (384 dimensions)	Sentence embeddings [7].	Semantic library search.	embed(text).
Drift on SQLite	Local relational database.	Queue, log, library, directory.	Tables and DAOs.
Riverpod 2.x	State management.	Providers for all modules.	Provider, Notifier.
Android WorkManager 2.x	Persistent background work.	Queue retries; expiry jobs.	OneTimeWorkRequest.
Android SmsManager (API 26 and later)	SMS sending.	SOS and escalation SMS.	sendMultipartTextMessage.
Android Keystore	Hardware-backed key storage.	Evidence key.	KeyGenerator AES-256.
Fused Location Provider	Location source.	Fixes and movement.	requestLocationUpdates.
Email delivery service (to be selected, Appendix C)	Transactional email.	Email alerts.	HTTPS API called from a function.

5.3 REST API Specification

The project backend exposes the HTTPS interfaces in Table 135. The alert page and the interfaces used by it are served from the alert subdomain through Firebase Hosting rewrites (alert.muhaffiz.live); the administrator interfaces are served from muhaffiz.me under the path /api/v1. Requests and responses use JSON, except the alert page, which is HTML.


Scheduled functions, which have no HTTP interface, compute the cell scores, expire missing-child reports and invitations, and remove reports older than 12 months.

Table 135: Project backend interfaces

API ID	Method	Endpoint	Purpose	Authentication	Request	Success Response	Errors
API-01	POST	/v1/alerts/email	Send the email copy of an SOS (FR-01.02).	User ID token	{sosId, recipients[], text, lat, lng, time}	202 {accepted}	400 invalid; 401; 429 rate; 502 provider
API-02	POST	/v1/alerts/push	Push an SOS to trustees who have the application.	User ID token	{sosId, phones[], text, lat, lng}	202 {sent}	400; 401; 429
API-03	GET	/alert/{token}	Show the alert page with location and time.	Unguessable token	-	200 HTML	404 unknown; 410 expired
API-04	POST	/alert/{token}/ack	Record a trustee acknowledgement (FR-19.01).	Unguessable token	{name?}	200 {recorded}	404; 409 duplicate; 410
API-05	POST	/v1/help-requests	Create a help request and notify helpers in the radius (FR-08.02).	User ID token	{lat, lng}	201 {id, notified}	400; 401; 429
API-06	GET	/v1/heatmap/cells	Return cell scores for the viewport (FR-07.04).	User ID token	?bbox=...	200 [{geohash7, score, counts}]	400; 401
API-07	POST	/api/v1/admin/reports/{id}/decision	Decide on a flagged report (FR-16.02).	Administrator token	{decision, suspendAuthor?}	200 {status}	403; 404; 409
API-08	POST	/api/v1/admin/helpers/{uid}/decision	Approve, reject or revoke a helper (FR-16.03).	Administrator token	{decision}	200 {status}	403; 404; 409
API-09	GET	/api/v1/admin/metrics	Return delivery success and errors (FR-16.04).	Administrator token	?from&to	200 {byChannel, errors[]}	403; 400


5.4 Implemented User Interface

This section presents the interface of each subsystem that is not shown in Section 4.5. The mobile application is shown in Figure 50, Figure 51, Figure 52, Figure 53 and Figure 54, and the admin website in Figure 55 and Figure 56.




Settings and consent toggles | Privacy summary | Onboarding consent

Figure 50: Mobile application: settings, privacy summary and consent




Sign-in screen | Phrase enrolment | Incident report form

Figure 51: Mobile application: sign-in, phrase enrolment and incident report



Nearby help screen | Helper registration | Missing-child report form

Figure 52: Mobile application: nearby help, helper registration and missing-child report



Evidence list | Emergency services directory | Safe-location guidance

Figure 53: Mobile application: evidence, directory and safe-location guidance




Figure 54: Mobile application: escalation warning, escalation settings and app disguise

The onboarding screens collect the consent and prepare the safety features: the consent screen states what the microphone is used for and that processing stays on the phone; the sign-in screen verifies the phone number; the phrase screen enrols the safe and the duress phrase with three spoken samples each. The settings screen holds one switch for each sensor-based feature, and the privacy summary lists where data are kept. The incident form takes a category, a location that can be adjusted on the map and an optional note. The nearby-help screen shows a request with distance and age and the accept and decline buttons, and states plainly when it is unavailable offline. The evidence list shows each recording with export and delete actions, the directory offers a call button for each service, and the safe-location screen shows the nearest hospital or police station with its distance and direction. The escalation warning counts down from 30 seconds with a single cancel button.




Figure 55: Admin website: overview




Figure 56: Admin website: moderation queue

The admin website has a side menu with the overview, the moderation queue, the helper review and the health pages. The overview shows registration counts, pending helpers, items to review and the delivery success by channel, with phone numbers masked. The moderation queue lists flagged heatmap reports, missing-child reports and helper applications with the decision buttons; every decision is logged.

5.5 Deployment

Environments. Table 136 describes the three environments. The deployment view in Figure 7 shows where each part runs in production.

Table 136: Deployment environments

Environment	Purpose	Backend	Data	Access
Development	Daily work on each package	Firebase Local Emulator Suite and a development project	Generated test data	The two developers
Testing	Execution of the test plan on devices	A separate test Firebase project	Seeded accounts, reports and helpers, labelled as simulated	Developers and test users
Production	The system as used	The production Firebase project with muhaffiz.me and alert.muhaffiz.live	Real user data under the privacy rules	Users; administrators

Server setup. The Firebase projects are created with Authentication (phone and email providers), Cloud Firestore in native mode with the security rules and indexes of Section 4.4, Cloud Storage with its rules, Cloud Functions in a single region, Cloud Messaging and Hosting. The custom domains are connected to Firebase Hosting through DNS records: muhaffiz.me serves the admin website and alert.muhaffiz.live serves the alert page; HTTPS certificates are provisioned by the platform. Administrator accounts are created by the project owner and given the administrator role claim.

CI/CD. Source code is kept in a Git repository. On each push a pipeline analyses the code, runs the unit tests and the rule tests against the emulator, and builds the application package. A tagged release additionally deploys the rules, indexes, functions and hosting to the target project with the Firebase command line, and produces a signed installable package of the application for test users.

Backup and monitoring. Server data are exported with the Firebase command line before each release. Evidence recordings are deliberately excluded from every backup, because they exist only on the device (BR-23). Monitoring uses the usage dashboards of the platform for quota, a crash-reporting service for the application, and the Health page of the admin website for delivery success and backend errors (FR-16.04). **Deployment diagram.** Figure 7 is the deployment diagram of the system.

5.6 Chapter Summary

This chapter gave the default parameters and the pseudocode of ten core algorithms, the third-party APIs and SDKs, the nine backend interfaces, the screens of the application and the admin website, and the environments, setup, pipeline and monitoring used for deployment. Chapter 6 now defines how the system is tested and evaluated.

Chapter 6: Testing, Evaluation and Conclusion

Chapter Overview. This chapter defines how the system is verified against its requirements. Sections 6.1 to 6.5 give the test cases at each level, Section 6.6 the test summary and defect log, Section 6.7 the requirements traceability matrix, and Section 6.8 the conclusion, limitations and future enhancements. Every functional requirement, business rule and non-functional requirement is covered by at least one test case, and the matrix shows which. The columns Actual Result, Observed Result and Result of each table record the outcome of the execution of the test case.

Tests are executed in the testing environment of Section 5.5. Where users or helpers are needed for a test, simulated accounts are used and are identified as simulated in the test log. The reference device is a mid-range Android phone running Android 8.0 or later, and its model is recorded in the test log. Timing and battery targets are measured on the reference device.

6.1 Unit Testing

Unit tests check individual functions, classes and algorithms with fixed inputs. Table 137 lists test cases UT-01 to UT-24.

Table 137: Unit test cases

No.	Test Case or Script	Input Attribute and Value	Expected Result	Actual Result	Result
UT-01	Sound-level gate emits a burst (A1)	20 s of quiet frames, then two consecutive frames 20 dB above ambient	Exactly one 2-second burst is emitted; ambient level is not raised by the loud frames.		
UT-02	Sound-level gate ignores a single loud frame (A1)	One frame 20 dB above ambient between quiet frames	No burst is emitted.		
UT-03	Fusion rule decision table (A2)	Scores 0.50, 0.70, 0.90 each with motion true, false and sensors unavailable	Countdown only for: 0.70 with motion; 0.90 with or without motion or sensors; 0.70 without sensors gives none; 0.50 gives none.		
UT-04	Manual trigger has no countdown (A3)	trigger = manual	The pipeline starts at once; no countdown is created.		
UT-05	Countdown boundary (A3)	Cancel at 19.9 s; no cancel until 20.0 s	Cancel at 19.9 s sends nothing; expiry at 20.0 s starts the SOS with the trigger recorded.		
UT-06	Tier 1 dispatch (A4)	tier = 1; 2 trustees with SMS and email	SMS sent to both; email queued; no push or email request made.		
UT-07	Retry back-off (A4)	Eight consecutive failures of one item	Delays 15, 30, 60, 120, 240, 480, 900, 900 seconds.		

No.	Test Case or Script	Input Attribute and Value	Expected Result	Actual Result	Result
UT-08	Phrase handling in context (A5)	Safe phrase on the stop-sharing screen; safe phrase on Home; duress phrase	Sharing stops with no SOS; countdown starts; decoy shown and silent SOS countdown starts.		
UT-09	Movement threshold (A6)	Updates at 49 m and 51 m from the last published position	No publication at 49 m; publication at 51 m.		
UT-10	Report weighting (A7)	Reports aged 0, 90 and 180 days	Weights 1.0, 0.5 and 0.25; cell score is their sum.		
UT-11	Semantic ranking and fallback (A8)	Fixture embeddings; a query with best similarity 0.55 and one with 0.20	Ranked by similarity in the first case; keyword results in the second.		
UT-12	Escalation timing (A9)	Acknowledgement at 179 s; no acknowledgement	No escalation in the first case; warning at 180 s and message after 30 s in the second.		
UT-13	Nearest location distance (A10)	Two known coordinates and a three-entry directory	Haversine distance within 1% of the reference; the nearest entry is chosen.		
UT-14	Trustee validation	Phone "12ab"; empty name; 11th trustee	Each is rejected with a message.		
UT-15	Template validation	Template of 161 characters; empty template	Both rejected; 160 characters accepted.		
UT-16	Phrase validation	One-word phrase; six-word phrase; duress containing the safe phrase	Each rejected.		
UT-17	Report rate limiter	Six reports in 24 hours; two reports within 100 m and one hour	The sixth and the near-duplicate are rejected.		
UT-18	Evidence encryption	Encrypt and decrypt a sample; alter one byte of the ciphertext	Round trip returns the sample; the altered file fails authentication.		
UT-19	Geohash precision	Encode known points at precision 7; decode	Cells match the reference; decoded centre within one cell.		
UT-20	Retention selection	Recordings aged 6, 8 and 31 days with retention 7 and 30 days	Recordings older than the retention period are selected for deletion.		
UT-21	Invitation expiry	Invitation aged 6 days 23 hours and 7 days 1 hour	Pending in the first case; expired in the second.		
UT-22	Missing-child expiry and renewal	Report at 71 h, at 73 h, and renewed at 70 h	Active; expired with photo deleted; active with a new expiry time.		
UT-23	Directory ordering	Entries and a position; the same without a position	Nearest first with a position; by category and name without.		
UT-24	Locations age statement	Cached fix aged 3 minutes with no fresh fix in 10 s	Message contains the location and the text that it is 3 minutes old.		

6.2 Functional Testing

Each use case is tested through the interface after unit testing. Table 138 lists test cases FT-01 to FT-29; the number of a functional test equals the number of its use case.

Table 138: Functional test cases

No.	Test Case or Script	Input Attribute and Value	Expected Result	Actual Result	Result
FT-01	UC-01 Manual SOS	Hold SOS for 1 s with 2 trustees (SMS+push; email); loud mode	Dispatch starts within 1 s; siren plays; recording starts; per-channel statuses appear in the log.		
FT-02	UC-02 Automatic distress alert	Play a distress clip while moving the phone abruptly; do not cancel	Vibration for 20 s with no sound; SOS starts with trigger "automatic"; with a cancel nothing is sent.		
FT-03	UC-03 Voice SOS	Speak the safe phrase; then the duress phrase; with the network off	Countdown then SOS (default mode) for the safe phrase; silent SOS and decoy for the duress phrase.		
FT-04	UC-04 Manage trustees	Add, edit and remove a trustee; try an invalid number	Changes saved; invalid number rejected; removed trustee gets no later alert.		
FT-05	UC-05 SOS event log	Open the log after two SOS events	Time, location, trigger and per-channel status are shown and update.		
FT-06	UC-06 Enrol phrases	Enrol a safe and a duress phrase with three samples each	Phrases saved; invalid or equal phrases are rejected.		
FT-07	UC-07 Circle and invitation	Create a circle, invite a second user, accept; also decline and let one expire	Sharing starts only after acceptance; declined and expired invitations share nothing.		
FT-08	UC-08 Share and view members	Two members share; one moves 100 m; the other watches	Status and last-update time update; the sharing indicator is shown on the sharing device.		
FT-09	UC-09 Stop sharing by safe phrase	Open Stop sharing and speak the safe phrase; then repeat with no phrase	Sharing stops with a private confirmation and no message to others; without a phrase sharing continues.		
FT-10	UC-10 Leave circle	Leave a circle	Member removed; location deleted; no notification sent.		
FT-11	UC-11 Decoy mode	Turn on Decoy Mode; open the app; hold "=" for 2 s; send a duress SOS	Calculator shown; real app opens on the hold; SOS and location work underneath.		
FT-12	UC-12 Incident report	Submit a report; submit without a category; submit a 6th report in 24 h	Valid report stored; missing category and the 6th report rejected.		
FT-13	UC-13 Danger heatmap	Open the map with reports of different ages; tap a cell; go offline	Redder cells for higher scores; panel shows counts only; cached data shown offline with its time.		
FT-14	UC-14 Helper registration	Apply with an identity image; approve and reject as administrator	Status pending then verified or rejected; image deleted after the decision.		
FT-15	UC-15 Nearby help	Request help with one helper inside and one outside the radius; accept; then go offline	Only the inside helper is notified; exact location shown after accept; offline shows the unavailable message.		
FT-16	UC-16 Browse library	Open the library offline, filter, bookmark an item, restart	Articles open; filter works; bookmark persists.		

No.	Test Case or Script	Input Attribute and Value	Expected Result	Actual Result	Result
FT-17	UC-17 Search library	Search "help a friend after harassment" offline; search with the model file removed	Ranked cards with relevance indicators; keyword results with a notice when the model is missing.		
FT-18	UC-18 Emergency services	Open the directory with and without location; tap Call	Nearest first with location; call or dialer opens.		
FT-19	UC-19 Sign up and log in	Sign in with a valid code; with a wrong code five times	Signed in; lock for 10 minutes after five wrong codes.		
FT-20	UC-20 Consent and privacy	Decline consent; accept; switch each toggle	No microphone function before consent; each toggle works independently; summary matches behaviour.		
FT-21	UC-21 Moderation and helper review	Flag a report by burst; remove it; revoke a helper	Item appears in the queue; removal drops it from the heatmap; the decision is logged.		
FT-22	UC-22 Health monitoring	Open Health after 20 test SOS events with one channel disabled	Delivery success per channel and errors are shown without user identities.		
FT-23	UC-23 Missing-child report	File a report; mark found; let one expire; file a 4th in 24 h	Alerts to trustees and helpers within 5 km; photo deleted on found or expiry; 4th rejected.		
FT-24	UC-24 Evidence recordings	Start an SOS; list, export, delete and wait past retention	Recording starts within 1 s; encrypted; export and delete work; old recordings are removed.		
FT-25	UC-25 Escalation	SOS with no acknowledgement; cancel in one run; acknowledge in another	Warning at 3 minutes; message to Police 15 and Rescue 1122 by SMS if not cancelled; no message after cancel or acknowledgement.		
FT-26	UC-26 Safe-location guidance	Ask for the nearest safe location online and offline	Directions open online; distance and direction shown offline.		
FT-27	UC-27 App disguise	Apply each appearance; restore	Name and icon change; original restored; functions unchanged.		
FT-28	UC-28 Account recovery	Sign in on a second device with the same number	Account data restored; old device signed out; notice that evidence is not restored.		
FT-29	UC-29 Acknowledge alert	A trustee with the app and one with the link acknowledge	Both acknowledgements appear on the SOS screen and stop the timer.		

6.3 Business Rules Testing

The business rules are tested with decision tables: each row gives the conditions of one case of the rule and the expected action. Table 139 lists test cases BRT-01 to BRT-32, one for each business rule BR-01 to BR-32 (the prefix BRT distinguishes a test case from the rule it tests).

Table 139: Business rule test cases

BR Test ID	Related BR	Conditions	Expected Action	Actual Action	Result
BRT-01	BR-01	Trigger = manual, automatic or voice	The same pipeline runs; trigger recorded.		
BRT-02	BR-02	Manual; automatic with cancel; automatic without cancel	No countdown; nothing sent; SOS after 20 s.		
BRT-03	BR-03	Mode = loud; mode = silent; duress phrase	Siren; no sound or visible alert; silent SOS.		
BRT-04	BR-04	Trustee with no channel; with WhatsApp in loud SOS; with WhatsApp in silent SOS	SMS used; WhatsApp offered for confirmation; WhatsApp not used.		
BRT-05	BR-05	Tier 1; tier 2 or 3; channel failure	SMS only; all enabled channels; queued and retried until delivered.		
BRT-06	BR-06	Fix within 10 s; no fix in 10 s	Fresh fix used; cached location with age.		
BRT-07	BR-07	Network capture during detection and voice	No audio, transcript or classifier output leaves the device.		
BRT-08	BR-08	Storage inspection after detection and voice use	No audio stored by these engines.		
BRT-09	BR-09	Before consent; after consent; toggle off	Features off; features available; service stops at once.		
BRT-10	BR-10	Invitation pending; accepted; 7 days old	No sharing; sharing begins; expired.		
BRT-11	BR-11	Stop by safe phrase	Stops at once; no message to others; no approval needed.		
BRT-12	BR-12	After stopping	Others see the last location with time and "Not live".		
BRT-13	BR-13	Sharing on; another member tries to switch it on	Indicator shown; the attempt is refused.		
BRT-14	BR-14	Stop sharing; leave circle	Membership kept; membership and stored location removed.		
BRT-15	BR-15	6th report in 24 h; near-duplicate; burst in one cell	Rejected; rejected; sent to moderation.		
BRT-16	BR-16	Reports aged 0, 90, 180 days	Weights 1, 0.5, 0.25.		
BRT-17	BR-17	Tap a cell	Counts only; no reporter information.		
BRT-18	BR-18	Pending; approved; revoked; after decision	No requests; requests received; none; image deleted.		
BRT-19	BR-19	Helper inside radius; outside; before accept	Notified; not notified; exact location hidden.		
BRT-20	BR-20	Model present with similarity 0.55; model missing; similarity 0.20	Semantic results; keyword results; keyword results.		
BRT-21	BR-21	With location; without location	Ordered by distance; by category and name.		
BRT-22	BR-22	Second sign-in on a new device	Old sessions ended; one account per number.		
BRT-23	BR-23	SOS by each trigger; retention reached; export	Recording starts and stays on device; deleted; only on request.		

BR Test ID	Related BR	Conditions	Expected Action	Actual Action	Result
BRT-24	BR-24	Ack at 179 s; none; cancel in warning	No escalation; escalation after 30 s warning; no escalation.		
BRT-25	BR-25	Active at 71 h; 73 h; renewed	Active; expired; new expiry.		
BRT-26	BR-26	Active; found; expired; non-alerted user	Photo visible to entitled users; deleted; deleted; denied.		
BRT-27	BR-27	4th report in 24 h; admin removes a false report	Rejected; removed and author may be suspended.		
BRT-28	BR-28	Decoy on; hold "=" for 1 s and 2 s	Calculator shown; stays; real app opens.		
BRT-29	BR-29	Apply a disguise	Name and icon change; functions and data unchanged.		
BRT-30	BR-30	Online; offline	Turn-by-turn directions; distance and direction.		
BRT-31	BR-31	Non-administrator; administrator; a decision	Denied; allowed; logged with administrator and time.		
BRT-32	BR-32	Location requested by a stranger; by a trustee; by a circle member while sharing	Denied; allowed during SOS; allowed while sharing.		

6.4 Integration Testing

Integration tests check that modules, services, the database and external systems work together and that the interfaces between them behave as specified. Table 140 lists test cases IT-01 to IT-14.

Table 140: Integration test cases

No.	Integrated Component	Test Scenario	Expected Result	Actual Result	Result
IT-01	Trigger engine to SOS core to delivery	Manual, automatic and voice triggers each produce the same dispatch	One pipeline: the channel set is identical; only the trigger label differs.		
IT-02	Detection engine and consent	Turn microphone detection off during monitoring	Service stops; no classification occurs; turning on again asks for the permission.		
IT-03	Delivery manager and outbound queue	Dispatch with data off, restart the phone, then enable data	SMS sent; others queued; queue survives restart; flushed within 30 s of connectivity.		
IT-04	Connectivity detection and status strip	Switch data off, to a slow link, to a fast link	Tier shown as 1, 2, 3.		
IT-05	Location service and cache	SOS with GPS disabled after a prior fix	Cached location used and its age stated.		
IT-06	Voice engine to location sharing	Safe phrase on the stop-sharing screen with two members	Sharing stops; last location visible to the other member as "Not live".		

No.	Integrated Component	Test Scenario	Expected Result	Actual Result	Result
IT-07	Voice engine to decoy mode	Duress phrase while the app is open	Decoy shown while the silent SOS dispatches.		
IT-08	SOS core to evidence vault	SOS by each trigger	A recording starts for each and is linked to the SOS event.		
IT-09	Escalation to acknowledgements and Firestore	Helper accepts during the 3-minute wait	Timer stops; no escalation.		
IT-10	Firestore rules and clients	Attempts by outsiders to read locations, photos and identity images	All denied.		
IT-11	Cloud Functions and email provider	Send an email alert with the provider disabled	Failure logged; other channels unaffected.		
IT-12	Heatmap aggregation and admin moderation	Burst of reports, then removal by an administrator	Cell score drops after removal; the decision is logged.		
IT-13	Library, embeddings and search	Search across all bundled items	Every item has an embedding; search returns relevant items.		
IT-14	Directory, location and navigation	Nearest safe location from the bundled directory	Hospital or police entry chosen and shown with distance.		

6.5 Non-Functional Testing

Each measurable non-functional requirement is verified under the stated environment and workload. Table 141 lists test cases NF-01 to NF-42, one for each requirement of Section 3.4.

Table 141: Non-functional test cases

NF Test ID	Related NFR	Method and Environment	Target	Observed Result	Status
NF-01	NFR-REL-01	Instrumented device test with data disabled. (reference device)	At least 95% of 20 trials at Tier 1 hand the SMS to the SMS service within 5 seconds of the trigger.		
NF-02	NFR-REL-02	Test with forced stops and restarts. (reference device)	100% of queued messages remain after 10 forced stops and 5 restarts.		
NF-03	NFR-REL-03	Device test. (reference device)	Restart within 60 seconds in 9 of 10 trials when permissions and battery exemption are granted.		
NF-04	NFR-REL-04	Fault-injection test. (reference device)	With each channel disabled in turn, all others still dispatch (100%).		
NF-05	NFR-REL-05	Soak test. (reference device)	Zero crashes in 8 hours on each test device.		
NF-06	NFR-PER-01	Timed device test. (reference device)	At least 95% of 20 trials start the first channel within 2 seconds of the completed hold.		
NF-07	NFR-PER-02	Timed test with labelled clips. (reference device)	Result within 1.5 seconds of the end of the sound burst in 95% of trials.		

NF Test ID	Related NFR	Method and Environment	Target	Observed Result	Status
NF-08	NFR-PER-03	Timed test. (reference device)	Detection within 2 seconds of the end of the phrase in 90% of trials.		
NF-09	NFR-PER-04	Two-device timed test. (reference device)	Within 5 seconds in 95% of trials at Tier 3.		
NF-10	NFR-PER-05	Timed test. (reference device)	Within 1 second for a library of up to 500 items on the reference device.		
NF-11	NFR-PER-06	Timed test. (reference device)	Within 5 seconds at Tier 2 or 3; within 2 seconds from the cache offline.		
NF-12	NFR-PER-07	Timed test. (reference device)	Cold start to the home screen within 3 seconds on the reference device.		
NF-13	NFR-PER-08	Timed test. (reference device)	Within 1 second of the SOS start in 95% of trials.		
NF-14	NFR-PER-09	Timed test. (reference device)	Within 30 seconds of Tier 2 or 3 being reached.		
NF-15	NFR-PER-10	Battery measurement over 3 hours. (reference device)	No more than 5% of battery capacity per hour with the screen off on the reference device.		
NF-16	NFR-SEC-01	Network inspection. (reference device)	TLS 1.2 or later for 100% of connections.		
NF-17	NFR-SEC-02	File and permission inspection. (reference device)	AES-256-GCM with a Keystore key; a file read by another application fails.		
NF-18	NFR-SEC-03	Security-rule unit tests. (reference device)	100% of unauthorized read attempts in the rule tests are denied.		
NF-19	NFR-SEC-04	Access test and log inspection. (reference device)	Non-administrator accounts are denied on all admin pages; every decision is logged.		
NF-20	NFR-SEC-05	Network capture. (reference device)	Zero audio payloads in a network capture of 1 hour of monitoring including 10 detections.		
NF-21	NFR-SEC-06	Storage-rule tests. (reference device)	Unauthorized reads are denied; deletion occurs at the decision or status change.		
NF-22	NFR-SEC-07	Visual inspection. (reference device)	All displayed numbers show only the last 3 digits.		
NF-23	NFR-PRV-01	Permission and log inspection. (reference device)	Zero microphone access before consent in 10 fresh installations.		
NF-24	NFR-PRV-02	Data inspection after clean-up. (reference device)	No report older than 12 months remains after the scheduled clean-up.		
NF-25	NFR-PRV-03	Review checklist. (reference device)	Every item of the summary is verified against the stored data in a review.		
NF-26	NFR-USA-01	Inspection. (reference device)	One press-and-hold from the home screen; one tap from the lock screen.		
NF-27	NFR-USA-02	Usability test with at least 5 participants. (reference device)	At least 80% of test participants finish sign-up, one trustee and consent in under 5 minutes.		
NF-28	NFR-USA-03	Layout inspection. (reference device)	At least 48 dp, and the SOS control at least 72 dp.		

NF Test ID	Related NFR	Method and Environment	Target	Observed Result	Status
NF-29	NFR-USA-04	Contrast tool and test at 130% scale. (reference device)	Contrast ratio at least 4.5:1; layouts remain usable at 130% font scale.		
NF-30	NFR-USA-05	Inspection and test. (reference device)	The 20-second countdown and the 30-second escalation warning can each be cancelled with one tap.		
NF-31	NFR-USA-06	Inspection. (reference device)	At most two sentences each; every error path in the test plan shows one.		
NF-32	NFR-MNT-01	Code structure review and coverage report. (reference device)	Each module in its own package; business-logic unit-test coverage at least 70%.		
NF-33	NFR-MNT-02	Configuration test. (reference device)	All values of BR-02, BR-06, BR-15, BR-19 and BR-24 changed without code changes.		
NF-34	NFR-MNT-03	Documentation review. (reference device)	One description per module in the repository.		
NF-35	NFR-CMP-01	Device test. (reference device)	Smoke test passed on at least 3 device models from different manufacturers.		
NF-36	NFR-AVL-01	Code and network inspection. (reference device)	Zero backend calls on the SMS path.		
NF-37	NFR-SCL-01	Quota calculation and load test. (reference device)	Up to 500 registered users and 100 concurrent users within quotas.		
NF-38	NFR-SAF-01	Log inspection. (reference device)	100% of automatic and voice SOS events in the test log show the countdown.		
NF-39	NFR-SAF-02	Evaluation script. (reference device)	Precision and recall each at least 0.80 on a labelled clip set of at least 100 clips.		
NF-40	NFR-ROB-01	Fault-injection test. (reference device)	SOS still works with each model file removed in turn.		
NF-41	NFR-ROB-02	Input test. (reference device)	No crash in 100 malformed-input cases.		
NF-42	NFR-ROB-03	Test with full storage. (reference device)	With storage full the SOS dispatches and the recording stops with a log entry.		

6.6 Test Summary and Defect Log

Table 142 summarizes the test cases by type, and Table 143 is the defect log.

Table 142: Test summary

Test Type	Planned	Executed	Passed	Failed	Blocked	Pass Rate
Unit	24					
Functional	29					
Business rules	32					
Integration	14					
Non-functional	42					

Test Type	Planned	Executed	Passed	Failed	Blocked	Pass Rate
Total	141					

Table 143: Defect log

Defect ID	Description	Severity	Related Test	Status	Resolution or Rationale

6.7 Requirements Traceability Matrix

The matrix in Table 144 traces every functional requirement, business rule and non-functional requirement from its source to the design element, the implementation component and the test cases that verify it. A functional requirement is traced to the functional tests of the use cases that contain it, and to the unit and integration tests that name it. The Status column records the verification status of each requirement.

Table 144: Requirements traceability matrix

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
FR-01.01	Feature Document 7.1.1	Class diagram SOS core; sequence SOS dispatch	sos_core	FT-01, UT-04	
FR-01.02	Feature Document 7.1.2	Class diagram SOS core; sequence SOS dispatch	sos_core	FT-01, IT-01, IT-11, UT-06	
FR-01.03	Feature Document 7.1.3	Class diagram SOS core; sequence SOS dispatch	sos_core	FT-01	
FR-01.04	Feature Document 7.1.4	Class diagram SOS core; sequence SOS dispatch	sos_core	FT-01	
FR-01.05	Feature Document 7.1.5	Class diagram SOS core; sequence SOS dispatch	sos_core	FT-04, UT-14	
FR-01.06	Feature Document 7.1.6	Class diagram SOS core; sequence SOS dispatch	sos_core	FT-05, IT-03	
FR-02.01	Feature Document 7.2.1	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	FT-02, IT-02, UT-01, UT-02	
FR-02.02	Feature Document 7.2.2	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	FT-02	
FR-02.03	Feature Document 7.2.3	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	FT-02, UT-03	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
FR-02.04	Feature Document 7.2.4	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	FT-02, IT-01, UT-03, UT-05	
FR-02.05	Feature Document 7.2.5	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	FT-02	
FR-03.01	Feature Document 7.3.1	Class diagram detection; algorithm A5	voice_engine	FT-06, UT-16	
FR-03.02	Feature Document 7.3.2	Class diagram detection; algorithm A5	voice_engine	FT-06, UT-16	
FR-03.03	Feature Document 7.3.3	Class diagram detection; algorithm A5	voice_engine	FT-03	
FR-03.04	Feature Document 7.3.4	Class diagram detection; algorithm A5	voice_engine	FT-03, IT-01, UT-05, UT-08	
FR-03.05	Feature Document 7.3.5	Class diagram detection; algorithm A5	voice_engine	FT-09, IT-06, IT-07, UT-08	
FR-04.01	Feature Document 7.4.1	Class diagram family; state diagram member	family_circle	FT-07, UT-21	
FR-04.02	Feature Document 7.4.2	Class diagram family; state diagram member	family_circle	FT-07	
FR-04.03	Feature Document 7.4.3	Class diagram family; state diagram member	family_circle	FT-10	
FR-05.01	Feature Document 7.5.1	Sequence stop sharing; state diagram member; algorithm A6	location_sharing	FT-08, UT-09	
FR-05.02	Feature Document 7.5.2	Sequence stop sharing; state diagram member; algorithm A6	location_sharing	FT-09, IT-06, UT-08	
FR-05.03	Feature Document 7.5.3	Sequence stop sharing; state diagram member; algorithm A6	location_sharing	FT-09	
FR-05.04	Feature Document 7.5.4	Sequence stop sharing; state diagram member; algorithm A6	location_sharing	FT-08, IT-06	
FR-05.05	Feature Document 7.5.5	Sequence stop sharing; state diagram member; algorithm A6	location_sharing	FT-08, IT-10	
FR-06.01	Feature Document 7.6.1	Algorithm A5; activity SOS pipeline	decoy_mode	FT-11	
FR-06.02	Feature Document 7.6.2	Algorithm A5; activity SOS pipeline	decoy_mode	FT-11	
FR-06.03	Feature Document 7.6.3	Algorithm A5; activity SOS pipeline	decoy_mode	FT-11, IT-07	
FR-07.01	Feature Document 7.7.1	Class diagram community; algorithm A7	heatmap, scheduled functions	FT-12	
FR-07.02	Feature Document 7.7.2	Class diagram community; algorithm A7	heatmap, scheduled functions	FT-13, UT-10, UT-19	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
FR-07.03	Feature Document 7.7.3	Class diagram community; algorithm A7	heatmap, scheduled functions	FT-13, UT-10	
FR-07.04	Feature Document 7.7.4	Class diagram community; algorithm A7	heatmap, scheduled functions	FT-13, IT-12	
FR-07.05	Feature Document 7.7.5	Class diagram community; algorithm A7	heatmap, scheduled functions	FT-12, IT-12, UT-17	
FR-08.01	Feature Document 7.8.1	Class diagram community; state diagram helper	near_help	FT-14, IT-10	
FR-08.02	Feature Document 7.8.2	Class diagram community; state diagram helper	near_help	FT-15	
FR-08.03	Feature Document 7.8.3	Class diagram community; state diagram helper	near_help	FT-15, FT-29, IT-09	
FR-08.04	Feature Document 7.8.4	Class diagram community; state diagram helper	near_help	FT-15	
FR-09.01	Feature Document 7.9.1	Data design: LibraryItem	library	FT-16	
FR-09.02	Feature Document 7.9.2	Data design: LibraryItem	library	FT-16	
FR-09.03	Feature Document 7.9.3	Data design: LibraryItem	library	FT-16	
FR-10.01	Feature Document 7.10.1	Algorithm A8; data design: LibraryItem	semantic_search	FT-17, IT-13	
FR-10.02	Feature Document 7.10.2	Algorithm A8; data design: LibraryItem	semantic_search	FT-17	
FR-10.03	Feature Document 7.10.3	Algorithm A8; data design: LibraryItem	semantic_search	FT-17, UT-11	
FR-10.04	Feature Document 7.10.4	Algorithm A8; data design: LibraryItem	semantic_search	FT-17, UT-11	
FR-10.05	Feature Document 7.10.5	Algorithm A8; data design: LibraryItem	semantic_search	FT-17, IT-13	
FR-11.01	Feature Document 7.11.1	Data design: DirectoryEntry	directory	FT-18, IT-14	
FR-11.02	Feature Document 7.11.2	Data design: DirectoryEntry	directory	FT-18	
FR-11.03	Feature Document 7.11.3	Data design: DirectoryEntry	directory	FT-18, UT-23	
FR-12.01	Feature Document 7.12.1	Activity tiered delivery; sequence offline queue; algorithm A4	delivery_manager, sms_gateway	IT-04	
FR-12.02	Feature Document 7.12.2	Activity tiered delivery; sequence offline queue; algorithm A4	delivery_manager, sms_gateway	FT-01, UT-06	
FR-12.03	Feature Document 7.12.3	Activity tiered delivery; sequence offline queue; algorithm A4	delivery_manager, sms_gateway	IT-03, UT-07	
FR-13.01	Feature Document 7.13.1	Data design: device entities	offline_store	IT-05, UT-24	
FR-13.02	Feature Document 7.13.2	Data design: device entities	offline_store	IT-03	
FR-14.01	Feature Document 7.14.1	Architecture; security design SD-03	auth	FT-19	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
FR-14.02	Feature Document 7.14.2	Architecture; security design SD-03	auth	FT-19	
FR-14.03	Feature Document 7.14.3	Architecture; security design SD-03	auth	FT-19, UT-15	
FR-14.04	Feature Document 7.14.4	Architecture; security design SD-03	auth	FT-28	
FR-15.01	Feature Document 7.15.1	Class diagram detection: ConsentSettings	consent	FT-20	
FR-15.02	Feature Document 7.15.2	Class diagram detection: ConsentSettings	consent	FT-20, IT-02	
FR-15.03	Feature Document 7.15.3	Class diagram detection: ConsentSettings	consent	FT-20	
FR-16.01	Feature Document 7.16.1	Architecture; security design SD-02	admin_site	FT-21	
FR-16.02	Feature Document 7.16.2	Architecture; security design SD-02	admin_site	FT-21, IT-12	
FR-16.03	Feature Document 7.16.3	Architecture; security design SD-02	admin_site	FT-14, FT-21	
FR-16.04	Feature Document 7.16.4	Architecture; security design SD-02	admin_site	FT-22, IT-11	
FR-16.05	Added during specification: needed to protect FR-16.01 to FR-16.04	Architecture; security design SD-02	admin_site	FT-21, FT-22	
FR-17.01	Feature Document 7.17.1	State diagram child report; data design	missing_child	FT-23	
FR-17.02	Feature Document 7.17.2	State diagram child report; data design	missing_child	FT-23	
FR-17.03	Feature Document 7.17.3	State diagram child report; data design	missing_child	FT-23, UT-22	
FR-17.04	Feature Document 7.17.4	State diagram child report; data design	missing_child	FT-23	
FR-17.05	Feature Document 7.17.5	State diagram child report; data design	missing_child	FT-23	
FR-17.06	Feature Document 7.17.6	State diagram child report; data design	missing_child	FT-23, IT-10	
FR-18.01	Feature Document 7.18.1	Class diagram SOS core: EvidenceRecording; SD-04	evidence_vault	FT-24, IT-08	
FR-18.02	Feature Document 7.18.2	Class diagram SOS core: EvidenceRecording; SD-04	evidence_vault	FT-24, UT-18	
FR-18.03	Feature Document 7.18.3	Class diagram SOS core: EvidenceRecording; SD-04	evidence_vault	FT-24, IT-08	
FR-18.04	Feature Document 7.18.4	Class diagram SOS core: EvidenceRecording; SD-04	evidence_vault	FT-24, UT-20	
FR-18.05	Feature Document 7.18.5	Class diagram SOS core: EvidenceRecording; SD-04	evidence_vault	FT-24	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
FR-19.01	Feature Document 7.19.1	Sequence escalation; algorithm A9	escalation	FT-25, FT-29, IT-09	
FR-19.02	Feature Document 7.19.2	Sequence escalation; algorithm A9	escalation	FT-25, UT-12	
FR-19.03	Feature Document 7.19.3	Sequence escalation; algorithm A9	escalation	FT-25, UT-12	
FR-19.04	Feature Document 7.19.4	Sequence escalation; algorithm A9	escalation	FT-25	
FR-19.05	Feature Document 7.19.5	Sequence escalation; algorithm A9	escalation	FT-25	
FR-19.06	Feature Document 7.19.6	Sequence escalation; algorithm A9	escalation	FT-25	
FR-20.01	Interview and survey	Algorithm A10	safe_navigation	FT-26, IT-14, UT-13	
FR-20.02	Interview and survey	Algorithm A10	safe_navigation	FT-26	
FR-20.03	Interview and survey	Algorithm A10	safe_navigation	FT-26, IT-14	
FR-21.01	Interview and survey	Architecture; component diagram	app_disguise	FT-27	
FR-21.02	Interview and survey	Architecture; component diagram	app_disguise	FT-27	
FR-21.03	Interview and survey	Architecture; component diagram	app_disguise	FT-27	
BR-01	Business rule: Novel contribution: one shared trigger engine	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-01	
BR-02	Business rule: Protects against false alarms without delaying a deliberate SOS	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-02	
BR-03	Business rule: Supports hiding while calling for help	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-03	
BR-04	Business rule: WhatsApp cannot send a message without user interaction	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-04	
BR-05	Business rule: Offline-first delivery	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-05	
BR-06	Business rule: An older location is better than none	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-06	
BR-07	Business rule: Privacy guarantee given to users	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	BRT-07	
BR-08	Business rule: Privacy guarantee given to users	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	BRT-08	
BR-09	Business rule: Informed consent	Class diagram detection; sequence automatic detection; algorithms A1, A2	detection_engine, trigger_engine	BRT-09	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
BR-10	Business rule: Bilateral opt-in	Class diagram family; state diagram member	family_circle	BRT-10	
BR-11	Business rule: Unilateral opt-out without confrontation	Class diagram detection; algorithm A5	voice_engine	BRT-11	
BR-12	Business rule: A stale location cannot be mistaken for live tracking	Sequence stop sharing; state diagram member; algorithm A6	location_sharing	BRT-12	
BR-13	Business rule: Prevents covert surveillance	Class diagram family; state diagram member	family_circle	BRT-13	
BR-14	Business rule: Separates ending membership from pausing	Class diagram family; state diagram member	family_circle	BRT-14	
BR-15	Business rule: Prevents spam and malicious flagging	Class diagram community; algorithm A7	heatmap, scheduled functions	BRT-15	
BR-16	Business rule: Shows current risk	Class diagram community; algorithm A7	heatmap, scheduled functions	BRT-16	
BR-17	Business rule: Anonymity of reporters	Class diagram community; algorithm A7	heatmap, scheduled functions	BRT-17	
BR-18	Business rule: Reduces misuse of the helper network	Class diagram community; state diagram helper	near_help	BRT-18	
BR-19	Business rule: Limits exposure of the requester's location	Class diagram community; state diagram helper	near_help	BRT-19	
BR-20	Business rule: Offline use and privacy of queries	Data design: LibraryItem	library	BRT-20	
BR-21	Business rule: The nearest help is the most useful	Data design: DirectoryEntry	directory	BRT-21	
BR-22	Business rule: Simple identity and lost-device recovery	Architecture; security design SD-03	auth	BRT-22	
BR-23	Business rule: Evidence stays with the user	Architecture; security design SD-03	auth	BRT-23	
BR-24	Business rule: Follow-through with a safeguard against false escalation	Sequence escalation; algorithm A9	escalation	BRT-24	
BR-25	Business rule: Reports must not remain active indefinitely	State diagram child report; data design	missing_child	BRT-25	
BR-26	Business rule: Child-data privacy	State diagram child report; data design	missing_child	BRT-26	
BR-27	Business rule: Abuse prevention and clear boundary with official channels	Architecture; security design SD-02	admin_site	BRT-27	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
BR-28	Business rule: Protects the user when forced to unlock the phone	Class diagram detection; algorithm A5	voice_engine	BRT-28	
BR-29	Business rule: Disguise must not disable safety	Architecture; component diagram	app_disguise	BRT-29	
BR-30	Business rule: Works from stored data	Algorithm A10	safe_navigation	BRT-30	
BR-31	Business rule: Accountability	Architecture; security design SD-02	admin_site	BRT-31	
BR-32	Business rule: Data minimisation	Class diagram SOS core; sequence SOS dispatch	sos_core	BRT-32	
NFR-REL-01	Non-functional requirements of Chapter 3	Security design SD-08, SD-09, SD-16	Cross-cutting	NF-01	
NFR-REL-02	Non-functional requirements of Chapter 3	Security design SD-08, SD-09, SD-16	Cross-cutting	NF-02	
NFR-REL-03	Non-functional requirements of Chapter 3	Security design SD-08, SD-09, SD-16	Cross-cutting	NF-03	
NFR-REL-04	Non-functional requirements of Chapter 3	Security design SD-08, SD-09, SD-16	Cross-cutting	NF-04	
NFR-REL-05	Non-functional requirements of Chapter 3	Security design SD-08, SD-09, SD-16	Cross-cutting	NF-05	
NFR-PER-01	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-06	
NFR-PER-02	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-07	
NFR-PER-03	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-08	
NFR-PER-04	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-09	
NFR-PER-05	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-10	
NFR-PER-06	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-11	
NFR-PER-07	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-12	
NFR-PER-08	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-13	
NFR-PER-09	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-14	
NFR-PER-10	Non-functional requirements of Chapter 3	Algorithms A1 to A10; architecture	Cross-cutting	NF-15	
NFR-SEC-01	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-16	
NFR-SEC-02	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-17	
NFR-SEC-03	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-18	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
NFR-SEC-04	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-19	
NFR-SEC-05	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-20	
NFR-SEC-06	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-21	
NFR-SEC-07	Non-functional requirements of Chapter 3	Security design SD-01 to SD-07	Cross-cutting	NF-22	
NFR-PRV-01	Non-functional requirements of Chapter 3	Security design SD-05; data design	Cross-cutting	NF-23	
NFR-PRV-02	Non-functional requirements of Chapter 3	Security design SD-05; data design	Cross-cutting	NF-24	
NFR-PRV-03	Non-functional requirements of Chapter 3	Security design SD-05; data design	Cross-cutting	NF-25	
NFR-USA-01	Non-functional requirements of Chapter 3	Human interface design	Cross-cutting	NF-26	
NFR-USA-02	Non-functional requirements of Chapter 3	Human interface design	Cross-cutting	NF-27	
NFR-USA-03	Non-functional requirements of Chapter 3	Human interface design	Cross-cutting	NF-28	
NFR-USA-04	Non-functional requirements of Chapter 3	Human interface design	Cross-cutting	NF-29	
NFR-USA-05	Non-functional requirements of Chapter 3	Human interface design	Cross-cutting	NF-30	
NFR-USA-06	Non-functional requirements of Chapter 3	Human interface design	Cross-cutting	NF-31	
NFR-MNT-01	Non-functional requirements of Chapter 3	Component diagram; configuration	Cross-cutting	NF-32	
NFR-MNT-02	Non-functional requirements of Chapter 3	Component diagram; configuration	Cross-cutting	NF-33	
NFR-MNT-03	Non-functional requirements of Chapter 3	Component diagram; configuration	Cross-cutting	NF-34	
NFR-CMP-01	Non-functional requirements of Chapter 3	Architecture	Cross-cutting	NF-35	
NFR-AVL-01	Non-functional requirements of Chapter 3	Activity tiered delivery	Cross-cutting	NF-36	
NFR-SCL-01	Non-functional requirements of Chapter 3	Deployment view	Cross-cutting	NF-37	
NFR-SAF-01	Non-functional requirements of Chapter 3	Algorithm A3; state diagram SOS	Cross-cutting	NF-38	
NFR-SAF-02	Non-functional requirements of Chapter 3	Algorithm A3; state diagram SOS	Cross-cutting	NF-39	
NFR-ROB-01	Non-functional requirements of Chapter 3	Security design SD-06, SD-14, SD-15	Cross-cutting	NF-40	
NFR-ROB-02	Non-functional requirements of Chapter 3	Security design SD-06, SD-14, SD-15	Cross-cutting	NF-41	

Requirement ID	Source	Design Element	Implementation Component	Test Case ID	Status
NFR-ROB-03	Non-functional requirements of Chapter 3	Security design SD-06, SD-14, SD-15	Cross-cutting	NF-42	

6.8 Conclusion, Limitations and Future Enhancements

Conclusion. Muhaffiz brings together in one Android application the functions that a person needs before, during and after an unsafe event: a manual, automatic and voice-triggered SOS through one shared pipeline; delivery that does not depend on a data connection; a family location model that the tracked person controls; a community danger map and verified nearby help; an offline library with search by meaning; evidence recording, escalation and a missing-child report; and an administration website. The six objectives of the project are realized by the following modules: the unified trigger engine and its countdown (BO-1) by MOD-01 to MOD-03; the three-tier delivery (BO-2) by MOD-12 and MOD-13; the bilateral opt-in and unilateral opt-out family model (BO-3) by MOD-04 and MOD-05; on-device detection and voice activation with no audio leaving the phone (BO-4) by MOD-02 and MOD-03; on-device semantic search (BO-5) by MOD-10; and the integrated application (BO-6) by all modules. The requirements, design and tests in this document are traced to one another so that each claim can be checked.

Limitations. The following limitations apply.

- The application runs on Android only.
- The sound classifier and the keyword spotter are pre-trained models; their accuracy bounds the accuracy of automatic and voice triggers, and accented speech may reduce it.
- WhatsApp messages need the user's confirmation, so SMS, push and email are the automatic channels.
- SMS needs cellular coverage, and the other channels need a data connection.
- Near Help is useful only where verified helpers are present, and its evaluation uses simulated helpers.
- Android may stop background services to save battery; the application asks for an exemption but cannot enforce it.

- Android 11 and later shows a microphone indicator that an application cannot hide, so evidence recording may be visible during a silent SOS.
- Consent based on a switch or a phrase can be defeated by physical coercion; the design reduces but does not remove this risk.
- Escalation messages go to numbers that the user configures; the application cannot ensure that an authority receives, accepts or acts on them, and it has no direct integration with official systems.
- Offline maps are available for up to three areas, and offline guidance gives distance and direction, not turn-by-turn directions.
- Semantic search covers the library only, and the interface is in English.

Future enhancements. The following work is possible after this project: an iOS version; Urdu and other languages for the interface and the phrases; fine-tuning the sound and keyword models on locally collected data; direct integration with official emergency and missing-child systems where they offer one; support for wearables and hardware panic buttons; offline turn-by-turn routing; larger offline map coverage; accessibility improvements for users with visual or hearing impairments; and semantic search across incident reports.

6.9 Chapter Summary

This chapter defined 24 unit, 29 functional, 32 business-rule, 14 integration and 42 non-functional test cases, the test summary and defect log, and a traceability matrix that links every requirement to its design, implementation and tests. It closed with the conclusion, the limitations and the future enhancements of Muhaffiz.

References

[1] World Health Organization, *Violence Against Women Prevalence Estimates, 2018: Global, Regional and National Prevalence Estimates for Intimate Partner Violence Against Women and Global and Regional Prevalence Estimates for Non-Partner Sexual Violence Against Women*. Geneva, Switzerland: WHO, 2021.

[2] *Systems and Software Engineering: Life Cycle Processes: Requirements Engineering*, ISO/IEC/IEEE Standard 29148:2018, 2018.

[3] *IEEE Standard for Information Technology: Systems Design: Software Design Descriptions*, IEEE Std 1016-2009, 2009.

[4] I. Sommerville, *Software Engineering*, 10th ed. Harlow, U.K.: Pearson, 2016.

[5] S. Hershey *et al.*, "CNN architectures for large-scale audio classification," in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP)*, New Orleans, LA, USA, 2017, pp. 131–135.

[6] T. N. Sainath and C. Parada, "Convolutional neural networks for small-footprint keyword spotting," in *Proc. Interspeech*, Dresden, Germany, 2015, pp. 1478–1482.

[7] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence embeddings using Siamese BERT-networks," in *Proc. Conf. Empirical Methods Natural Lang. Process. (EMNLP-IJCNLP)*, Hong Kong, China, 2019, pp. 3982–3992.

Appendix A: Use Case List

Table 145 lists all 29 use cases with the module, the requirements and the priority of the module. The use cases are specified in Section 3.2.22 (UC-01, UC-02, UC-03, UC-09, UC-23, UC-25) and in Appendix B.

Table 145: Use case list with descriptions

Use Case ID	Name	Actors	Module	Priority	Description
UC-01	Trigger Manual SOS	Primary User; Trustee; Verified Helper	MOD-01	High	The Primary User starts an SOS by hand. The system dispatches the alert to the trustees and, when enabled, to nearby helpers, sounds or withholds the alarm, and records evidence.
UC-02	Handle Automatic Distress Alert	Primary User	MOD-02	High	The monitoring service detects a possible distress sound, combines it with motion data and asks the user to cancel within 20 seconds. If the user does not cancel, an SOS starts.
UC-03	Trigger SOS by Voice Phrase	Primary User	MOD-03	High	The Primary User starts an SOS by speaking the safe phrase (loud or default mode) or the duress phrase (silent).
UC-04	Manage Trustees	Primary User	MOD-01	High	The Primary User adds, edits and removes trustees and chooses the channels for each.
UC-05	View SOS Event Log	Primary User	MOD-01	High	The Primary User reviews past SOS events and the delivery status of each channel.
UC-06	Enrol Safe and Duress Phrases	Primary User	MOD-03	High	The user enters a safe phrase and a duress phrase and confirms each with spoken samples.
UC-07	Create Circle and Invite Member	Primary User; Family Circle Member	MOD-04	High	A Primary User creates a family circle and invites another person, who accepts or declines.
UC-08	Share Location and View Members	Family Circle Member	MOD-05	High	A member shares their location with the circle and views the other members.
UC-09	Stop Sharing by Safe Phrase	Family Circle Member	MOD-05	High	A Family Circle Member stops sharing their location by speaking the safe phrase. No approval is needed and no other member is notified.
UC-10	Leave Family Circle	Family Circle Member	MOD-04	High	A member leaves a circle completely.
UC-11	Use Decoy Mode	Primary User	MOD-06	High	The user turns on Decoy Mode so that the application shows a calculator, and returns to the real application by a hidden gesture.
UC-12	Submit Incident Report	Primary User	MOD-07	Medium	The user reports an unsafe incident.
UC-13	View Danger Heatmap	Primary User	MOD-07	Medium	The user views the danger map and the details of a zone.
UC-14	Register as Verified Helper	Primary User; Administrator	MOD-08	Medium	A Primary User applies to become a Verified Helper and an Administrator decides.
UC-15	Request and Respond to Nearby Help	Primary User; Verified Helper	MOD-08	Medium	A user requests nearby help, and Verified Helpers within the radius answer.

Use Case ID	Name	Actors	Module	Priority	Description
UC-16	Browse Library	Primary User	MOD-09	Medium	The user browses the library by category and bookmarks items.
UC-17	Search Library	Primary User	MOD-10	Medium	The user searches the library with a question in their own words.
UC-18	Call Emergency Service	Primary User	MOD-11	Medium	The user calls an emergency service from the directory.
UC-19	Sign Up and Log In	Primary User	MOD-14	High	The user signs up or logs in with a mobile number and a one-time code.
UC-20	Manage Consent and Privacy Settings	Primary User	MOD-15	High	The user gives consent and changes the permission and feature toggles.
UC-21	Moderate Reports and Review Helpers	Administrator	MOD-16	Medium	An Administrator reviews flagged reports and helper applications and decides.
UC-22	Monitor System Health	Administrator	MOD-16	Medium	An Administrator views delivery success and backend errors.
UC-23	File Missing-Child Report	Guardian; Verified Helper; Trustee; Administrator	MOD-17	Medium	A Guardian reports a missing child; the system alerts trusted contacts and nearby verified helpers and queues the report for moderation.
UC-24	Manage Evidence Recordings	Primary User	MOD-18	Medium	The user manages evidence recordings made after an SOS.
UC-25	Escalate to Authorities	Primary User; Authority Contact	MOD-19	Medium	When nobody acknowledges an SOS in time, the system warns the user and then sends an escalation message to the configured authority numbers.
UC-26	Navigate to Nearest Safe Location	Primary User	MOD-20	Low	The user gets directions to the nearest safe location.
UC-27	Change App Disguise	Primary User	MOD-21	Low	The user changes the launcher name and icon of the application.
UC-28	Recover Account	Primary User	MOD-14	High	The user recovers the account on a new device.
UC-29	Acknowledge SOS Alert	Trustee; Verified Helper	MOD-19	Medium	A trustee or helper acknowledges an alert, which stops the escalation timer.

Appendix B: Detailed Use Case Specifications

This appendix gives the specifications of the use cases that are not specified in Section 3.2.22, in the same format.

Table 146: Use case specification UC-04: Manage Trustees

Field	Description
Use Case ID	UC-04
Use Case Name	Manage Trustees
Actors	Primary User
Description	The Primary User adds, edits and removes trustees and chooses the channels for each.
Trigger	The user opens the Trustees screen.
Preconditions	The user is signed in.
Postconditions	The trustee list and channel preferences are saved.
Normal Flow	1. The user opens the Trustees screen. 2. The user chooses to add a trustee. 3. The user enters a name and a mobile number, optionally an email, and selects channels. 4. The system validates the entries. 5. The system saves the trustee and shows it in the list.
Alternative Flows	A1: the user edits a trustee; the system saves the changes. A2: the user removes a trustee; the system removes it from later alerts.
Exceptions	E1: invalid number or empty name; the system shows a message and keeps the entries. E2: an eleventh trustee is added; the system refuses.
Business Rules	BR-04
Assumptions	AS-1

Table 147: Use case specification UC-05: View SOS Event Log

Field	Description
Use Case ID	UC-05
Use Case Name	View SOS Event Log
Actors	Primary User
Description	The Primary User reviews past SOS events and the delivery status of each channel.
Trigger	The user opens the SOS log.
Preconditions	At least one SOS has occurred.
Postconditions	No change.
Normal Flow	1. The user opens the SOS log. 2. The system lists the events with time, location and trigger method. 3. The user opens an event. 4. The system shows the status per trustee and channel.
Alternative Flows	A1: a queued message is delivered while the screen is open; the status updates.
Exceptions	E1: no events; the system shows an empty list.
Business Rules	BR-05

Field	Description
Assumptions	-

Table 148: Use case specification UC-06: Enrol Safe and Duress Phrases

Field	Description
Use Case ID	UC-06
Use Case Name	Enrol Safe and Duress Phrases
Actors	Primary User
Description	The user enters a safe phrase and a duress phrase and confirms each with spoken samples.
Trigger	The user opens the phrase screen during onboarding or from the settings.
Preconditions	Voice activation consent is given and the microphone permission is granted.
Postconditions	Both phrases and their sensitivity are stored on the device.
Normal Flow	1. The user types the safe phrase. 2. The system validates the phrase. 3. The user speaks it three times. 4. The system sets the sensitivity from the samples. 5. The user repeats steps 1 to 4 for the duress phrase. 6. The system saves both phrases.
Alternative Flows	A1 (step 3): a sample is not recognised; the system asks the user to repeat it.
Exceptions	E1: the phrase has fewer than two or more than five words, or the duress phrase equals or contains the safe phrase; the system rejects it. E2: the keyword engine cannot be loaded; the system turns voice activation off and says so.
Business Rules	BR-07, BR-09
Assumptions	AS-5

Table 149: Use case specification UC-07: Create Circle and Invite Member

Field	Description
Use Case ID	UC-07
Use Case Name	Create Circle and Invite Member
Actors	Primary User; Family Circle Member
Description	A Primary User creates a family circle and invites another person, who accepts or declines.
Trigger	The user chooses to create a circle or invite a person.
Preconditions	Both users are signed in.
Postconditions	After acceptance both are members and may share; otherwise no sharing exists.
Normal Flow	1. The inviter creates a circle (if none exists). 2. The inviter enters the invitee's phone number. 3. The system stores a pending invitation and notifies the invitee. 4. The invitee opens the invitation and accepts. 5. The system adds the invitee as a member. 6. Each member may then enable their own sharing.
Alternative Flows	A1 (step 4): the invitee declines; the invitation is closed. A2: seven days pass; the invitation expires.
Exceptions	E1: the number has no account; the system sends an invitation message by SMS and keeps the invitation pending.

Field	Description
Business Rules	BR-10
Assumptions	AS-7

Table 150: Use case specification UC-08: Share Location and View Members

Field	Description
Use Case ID	UC-08
Use Case Name	Share Location and View Members
Actors	Family Circle Member
Description	A member shares their location with the circle and views the other members.
Trigger	The member enables sharing, or opens the Family screen.
Preconditions	The member belongs to a circle and has given location consent.
Postconditions	The member's location is published on movement; others see status and time.
Normal Flow	1. The member enables sharing. 2. The system shows a persistent sharing indicator. 3. The device moves more than the threshold. 4. The system publishes the new location. 5. Other members see the marker and the update time.
Alternative Flows	A1: a member who has stopped sharing is shown with the last location and "Not live".
Exceptions	E1: no location permission; the system asks for it. E2: no connection; the update is sent when the connection returns.
Business Rules	BR-12, BR-13
Assumptions	AS-1

Table 151: Use case specification UC-10: Leave Family Circle

Field	Description
Use Case ID	UC-10
Use Case Name	Leave Family Circle
Actors	Family Circle Member
Description	A member leaves a circle completely.
Trigger	The member chooses Leave circle.
Preconditions	The member belongs to the circle.
Postconditions	The member is removed and their stored location is deleted.
Normal Flow	1. The member chooses Leave circle. 2. The system asks for confirmation. 3. The member confirms. 4. The system removes the membership and deletes the stored location. 5. The system shows a confirmation on the member's device.
Alternative Flows	A1: the member cancels; nothing changes.
Exceptions	E1: no connection; the leave is stored and sent when the connection returns, and publishing stops at once.
Business Rules	BR-14
Assumptions	-

Table 152: Use case specification UC-11: Use Decoy Mode

Field	Description
Use Case ID	UC-11
Use Case Name	Use Decoy Mode
Actors	Primary User
Description	The user turns on Decoy Mode so that the application shows a calculator, and returns to the real application by a hidden gesture.
Trigger	The user turns on Decoy Mode, or a duress-phrase SOS starts.
Preconditions	The user is signed in.
Postconditions	The decoy screen is shown until the hidden gesture is made.
Normal Flow	1. The user turns on Decoy Mode in the settings. 2. The user opens the application. 3. The system shows the calculator. 4. Later the user holds the equals key for 2 seconds. 5. The system shows the real interface.
Alternative Flows	A1: a duress phrase starts a silent SOS; the system shows the calculator at once.
Exceptions	E1: a short press on the equals key only calculates.
Business Rules	BR-28
Assumptions	-

Table 153: Use case specification UC-12: Submit Incident Report

Field	Description
Use Case ID	UC-12
Use Case Name	Submit Incident Report
Actors	Primary User
Description	The user reports an unsafe incident.
Trigger	The user chooses Report on the map.
Preconditions	The user is signed in and has not reached the report limit.
Postconditions	A report is stored with a geohash and a time stamp.
Normal Flow	1. The user chooses Report. 2. The system fills in the current location. 3. The user selects a category and may adjust the pin and add a note. 4. The user submits. 5. The system validates and stores the report and shows a confirmation.
Alternative Flows	A1: the user moves the pin to another place.
Exceptions	E1: the category is missing; the system asks for it. E2: the sixth report in 24 hours or a near-duplicate; the system rejects it.
Business Rules	BR-15, BR-17
Assumptions	AS-8

Table 154: Use case specification UC-13: View Danger Heatmap

Field	Description
Use Case ID	UC-13
Use Case Name	View Danger Heatmap
Actors	Primary User
Description	The user views the danger map and the details of a zone.
Trigger	The user opens the Map tab.
Preconditions	The user is signed in.
Postconditions	No change.
Normal Flow	1. The user opens the Map tab. 2. The system loads the cell scores for the visible area. 3. The system draws the cells from green to red. 4. The user taps a cell. 5. The system shows the report categories and counts.
Alternative Flows	A1: no connection; the last downloaded data is shown with its time.
Exceptions	E1: no data for the area; the system shows an empty map with a notice.
Business Rules	BR-16, BR-17
Assumptions	AS-8

Table 155: Use case specification UC-14: Register as Verified Helper

Field	Description
Use Case ID	UC-14
Use Case Name	Register as Verified Helper
Actors	Primary User; Administrator
Description	A Primary User applies to become a Verified Helper and an Administrator decides.
Trigger	The user chooses Become a helper.
Preconditions	The user is signed in.
Postconditions	The helper status is verified, rejected or revoked.
Normal Flow	1. The user enters name and phone and adds a photo of an identity document. 2. The user submits. 3. The system stores the application as pending and restricts the image to administrators. 4. The Administrator reviews the image. 5. The Administrator approves. 6. The system sets the status to verified, notifies the user and deletes the image.
Alternative Flows	A1 (step 5): the Administrator rejects; the status is rejected and the image is deleted.
Exceptions	E1: the image is missing or unreadable; the system asks for another.
Business Rules	BR-18, BR-31
Assumptions	-

Table 156: Use case specification UC-15: Request and Respond to Nearby Help

Field	Description
Use Case ID	UC-15

Field	Description
Use Case Name	Request and Respond to Nearby Help
Actors	Primary User; Verified Helper
Description	A user requests nearby help, and Verified Helpers within the radius answer.
Trigger	The user chooses Request nearby help, or an SOS with nearby help enabled starts.
Preconditions	The user has a data connection for the broadcast.
Postconditions	Helpers who accepted know the requester's location.
Normal Flow	1. The user requests nearby help. 2. The system creates the request and finds Verified Helpers within 1 km. 3. The system notifies them with distance and age. 4. A helper opens the request and accepts. 5. The system shows the exact location to that helper and records an acknowledgement. 6. The requester sees that a helper is coming.
Alternative Flows	A1 (step 4): a helper declines; nothing is shown to the requester. A2: no data connection; the request is queued and the SOS continues by SMS.
Exceptions	E1: no helper in the radius; the system tells the requester.
Business Rules	BR-19, BR-32
Assumptions	AS-8

Table 157: Use case specification UC-16: Browse Library

Field	Description
Use Case ID	UC-16
Use Case Name	Browse Library
Actors	Primary User
Description	The user browses the library by category and bookmarks items.
Trigger	The user opens the Library tab.
Preconditions	None.
Postconditions	Bookmarks are stored on the device.
Normal Flow	1. The user opens the Library tab. 2. The system lists the items. 3. The user chooses a category filter. 4. The system shows the matching items. 5. The user opens an item and bookmarks it.
Alternative Flows	A1: the item is a video or link and there is no connection; the system says a connection is needed.
Exceptions	E1: none.
Business Rules	BR-20
Assumptions	AS-9

Table 158: Use case specification UC-17: Search Library

Field	Description
Use Case ID	UC-17
Use Case Name	Search Library
Actors	Primary User

Field	Description
Description	The user searches the library with a question in their own words.
Trigger	The user submits a query.
Preconditions	The library is installed.
Postconditions	A ranked list is shown.
Normal Flow	1. The user types a query. 2. The system embeds the query on the device. 3. The system ranks the items by cosine similarity. 4. The system shows result cards with relevance indicators. 5. The user opens or bookmarks a result.
Alternative Flows	A1: the model is unavailable or the best similarity is below 0.30; the system runs a keyword search and says so.
Exceptions	E1: empty query; the system asks for text.
Business Rules	BR-20
Assumptions	-

Table 159: Use case specification UC-18: Call Emergency Service

Field	Description
Use Case ID	UC-18
Use Case Name	Call Emergency Service
Actors	Primary User
Description	The user calls an emergency service from the directory.
Trigger	The user opens the directory and taps Call.
Preconditions	None.
Postconditions	A call or the dialer is opened.
Normal Flow	1. The user opens the directory. 2. The system lists the entries, nearest first if a location is available. 3. The user taps Call on an entry. 4. The system places the call.
Alternative Flows	A1: the call permission is missing; the dialer opens with the number filled in.
Exceptions	E1: no location; the system orders entries by category and name.
Business Rules	BR-21
Assumptions	-

Table 160: Use case specification UC-19: Sign Up and Log In

Field	Description
Use Case ID	UC-19
Use Case Name	Sign Up and Log In
Actors	Primary User
Description	The user signs up or logs in with a mobile number and a one-time code.
Trigger	The user opens the application without a session.
Preconditions	A data connection exists.

Field	Description
Postconditions	The user is signed in.
Normal Flow	1. The user enters a mobile number. 2. The system sends a one-time code. 3. The user enters the code. 4. The system verifies it and signs the user in. 5. The system creates the account if it does not exist.
Alternative Flows	A1: the account exists; the system restores the profile.
Exceptions	E1: wrong code; the system rejects it. E2: five wrong codes; the system blocks new codes for 10 minutes.
Business Rules	BR-22
Assumptions	-

Table 161: Use case specification UC-20: Manage Consent and Privacy Settings

Field	Description
Use Case ID	UC-20
Use Case Name	Manage Consent and Privacy Settings
Actors	Primary User
Description	The user gives consent and changes the permission and feature toggles.
Trigger	Onboarding starts, or the user opens the settings.
Preconditions	The user is signed in.
Postconditions	Consent and toggles are stored.
Normal Flow	1. The user reads the consent statement. 2. The user accepts. 3. The system stores the consent and enables the choice of features. 4. The user turns a feature on. 5. The system asks for the Android permission and starts the service.
Alternative Flows	A1 (step 2): the user declines; the microphone features stay off. A2: the user turns a feature off; the system stops the service at once.
Exceptions	E1: the user denies the Android permission; the feature stays off and the system explains why.
Business Rules	BR-09
Assumptions	-

Table 162: Use case specification UC-21: Moderate Reports and Review Helpers

Field	Description
Use Case ID	UC-21
Use Case Name	Moderate Reports and Review Helpers
Actors	Administrator
Description	An Administrator reviews flagged reports and helper applications and decides.
Trigger	The Administrator opens the moderation or helper queue.
Preconditions	The Administrator is signed in.
Postconditions	The decision is applied and logged.

Field	Description
Normal Flow	1. The Administrator opens the queue. 2. The system lists the items. 3. The Administrator opens an item. 4. The Administrator selects approve, remove or reject. 5. The system applies the decision and records the administrator and time.
Alternative Flows	A1: the Administrator suspends the author of a false report.
Exceptions	E1: another administrator already decided; the system shows the earlier decision.
Business Rules	BR-18, BR-27, BR-31
Assumptions	-

Table 163: Use case specification UC-22: Monitor System Health

Field	Description
Use Case ID	UC-22
Use Case Name	Monitor System Health
Actors	Administrator
Description	An Administrator views delivery success and backend errors.
Trigger	The Administrator opens the Health page.
Preconditions	The Administrator is signed in.
Postconditions	No change.
Normal Flow	1. The Administrator opens the Health page. 2. The Administrator selects a period. 3. The system shows delivery success per channel and the list of backend errors.
Alternative Flows	A1: no data for the period; the system shows an empty state.
Exceptions	E1: the metrics service fails; the system shows an error.
Business Rules	BR-31
Assumptions	-

Table 164: Use case specification UC-24: Manage Evidence Recordings

Field	Description
Use Case ID	UC-24
Use Case Name	Manage Evidence Recordings
Actors	Primary User
Description	The user manages evidence recordings made after an SOS.
Trigger	An SOS starts, or the user opens the evidence list.
Preconditions	The microphone permission is granted.
Postconditions	Recordings are listed, exported or deleted according to the user's choice.
Normal Flow	1. An SOS starts and the system starts recording. 2. The system encrypts and stores the recording on the device. 3. Later the user opens the evidence list. 4. The system shows time, location, trigger and duration. 5. The user exports or deletes a recording. 6. The system deletes recordings after the retention period.

Field	Description
Alternative Flows	A1: the user stops a recording.
Exceptions	E1: the microphone is unavailable; no recording is made and the log notes it. E2: storage is full; the recording stops and the SOS continues.
Business Rules	BR-23
Assumptions	-

Table 165: Use case specification UC-26: Navigate to Nearest Safe Location

Field	Description
Use Case ID	UC-26
Use Case Name	Navigate to Nearest Safe Location
Actors	Primary User
Description	The user gets directions to the nearest safe location.
Trigger	The user taps Safe place.
Preconditions	A current or last-known location exists.
Postconditions	Directions or guidance are shown.
Normal Flow	1. The user taps Safe place. 2. The system finds the nearest hospital or police station in the directory. 3. The system checks the connection. 4. Online, the system opens directions in the maps application.
Alternative Flows	A1 (step 3): offline; the system shows distance and direction, and a line on an offline map if one is stored.
Exceptions	E1: no location; the system asks the user to enable it.
Business Rules	BR-30
Assumptions	-

Table 166: Use case specification UC-27: Change App Disguise

Field	Description
Use Case ID	UC-27
Use Case Name	Change App Disguise
Actors	Primary User
Description	The user changes the launcher name and icon of the application.
Trigger	The user opens App disguise.
Preconditions	The user is signed in.
Postconditions	The chosen appearance is applied.
Normal Flow	1. The user opens App disguise. 2. The user selects one of three appearances. 3. The user chooses Apply. 4. The system changes the launcher entry.
Alternative Flows	A1: the user restores the original appearance.
Exceptions	E1: the launcher does not refresh at once; the system tells the user that the change may appear later.
Business Rules	BR-29

Field	Description
Assumptions	-

Table 167: Use case specification UC-28: Recover Account

Field	Description
Use Case ID	UC-28
Use Case Name	Recover Account
Actors	Primary User
Description	The user recovers the account on a new device.
Trigger	The user signs in on a new device with the same number.
Preconditions	The user has access to the phone number.
Postconditions	Account data are restored and other sessions end.
Normal Flow	1. The user enters the mobile number. 2. The user enters the one-time code. 3. The system signs in and restores profile, trustees and circles. 4. The system ends the sessions on other devices. 5. The system tells the user that evidence recordings are not restored.
Alternative Flows	A1: the old device is offline; its session ends when it reconnects.
Exceptions	E1: wrong code; see UC-19.
Business Rules	BR-22, BR-23
Assumptions	-

Table 168: Use case specification UC-29: Acknowledge SOS Alert

Field	Description
Use Case ID	UC-29
Use Case Name	Acknowledge SOS Alert
Actors	Trustee; Verified Helper
Description	A trustee or helper acknowledges an alert, which stops the escalation timer.
Trigger	A trustee opens an alert, or a helper accepts a request.
Preconditions	An SOS is active.
Postconditions	An acknowledgement is recorded.
Normal Flow	1. The trustee receives the alert. 2. The trustee opens the application, or the link in the message. 3. The trustee confirms that they have seen the alert. 4. The system records the acknowledgement. 5. The user's SOS screen shows it and the timer stops.
Alternative Flows	A1: a helper accepts a request; the system records the acknowledgement.
Exceptions	E1: the link is opened offline; the acknowledgement is not recorded. E2: a second acknowledgement by the same person; the system ignores the duplicate.
Business Rules	BR-24
Assumptions	AS-7

Appendix C: TBD List

Table 169 lists the items that depend on a decision or a confirmation outside this specification. Each is stated with the requirement that it affects and with the default that the document uses until the item is resolved.

Table 169: Items to be determined

ID	Item	Affected Requirements	Default Used in this Document
TBD-1	Confirm the national emergency and helpline numbers (Police 15, Rescue 1122, the missing-child helpline 1099 and the women's helplines) and whether each accepts SMS from the public.	FR-11.01, FR-17.04, FR-19.04	Numbers as listed; SMS is the default channel; call and share are selectable.
TBD-2	Select the email delivery service and its free tier.	FR-01.02, SI-14	A transactional email API called from a Cloud Function.
TBD-3	Confirm the offline keyword spotter against the alternatives with accented speech.	FR-03.03, ADR-04	The sherpa-onnx keyword spotter.
TBD-4	Select the open map-data source and renderer and confirm its licence for offline storage.	FR-13.02, SI-7, DEP-7	OpenStreetMap-derived data with an open-source renderer.
TBD-5	Confirm the sources and licences of the library content.	FR-09.01, AS-9	Curated articles from reputable sources, with attribution.
TBD-6	Tune the algorithm thresholds after calibration on the evaluation data.	Table of algorithm parameters	The default values of the parameter table.
TBD-7	Define the identity-check procedure details for helper approval.	FR-08.01, FR-16.03	Administrator review of an identity document photo.
TBD-8	Choose the three neutral names and icons of the app disguise.	FR-21.01	Three neutral appearances, for example Calculator, Notes and Clock.

Appendix D: Sample Test Data

The following sample data are used to prepare the test cases of Chapter 6. Names, numbers and coordinates are invented.

Table 170: Sample trustees

Name	Phone	Email	Channels
Ayesha (sister)	+92 300 0000001	ayesha@example.com	SMS, push, email
Bilal (friend)	+92 300 0000002	-	SMS, WhatsApp
Mother	+92 300 0000003	-	SMS

Table 171: Sample SOS message

Part	Content
Template	I need help. Please call me.
Added by the system	Name: Test User. Location: 33.6844, 73.0479 (fix 4 s old). Time: 17:42. Map: link.
Escalation message	Test User needs help. Callback +92 300 0000099. Location 33.6844, 73.0479. Time 17:45. Trigger: voice. Evidence recorded: yes.

Table 172: Sample incident reports

Category	Location (latitude, longitude)	Age (days)	Expected weight
Harassment	33.6001, 73.0501	0	1.00
Theft	33.6001, 73.0502	90	0.50
Felt unsafe	33.6002, 73.0501	180	0.25

Table 173: Sample library queries

Query	Expected best item category
help a friend after harassment	After-incident care
how can I walk home safely at night	Prevention
what do I do if I am followed	Emergency response
I feel afraid and alone	Emotional support

Table 174: Sample audio test set (labelled clips)

Label	Examples	Minimum clips
Distress	Scream, shout for help, cry of fear	50
Non-distress loud	Door slam, applause, traffic horn, cheering, dropped object	50

Table 175: Sample directory entries

Name	Category	Phone	Latitude, longitude
Rescue 1122	Emergency number	1122	-
Police	Emergency number	15	-

Name	Category	Phone	Latitude, longitude
General Hospital (test)	Hospital	+92 51 0000000	33.6900, 73.0500
Police Station (test)	Police station	+92 51 0000001	33.6850, 73.0450

Document Status

This document is the Software Requirements Specification and Software Design Specification of Muhaffiz. It specifies what the system shall do and how it is designed. The chapters on implementation and testing describe the system as designed and as planned for verification. They are written in the present tense so that the document reads as one description of the system; they do not report results.

Readers should note the following. The sections on algorithms, interfaces, deployment and the user interface describe the intended realization of the design. The screens in Sections 4.5 and 5.4 are renderings of the committed interface design and not screenshots of a running application. The test cases of Chapter 6 are complete, but their Actual Result, Observed Result and Result columns, the executed, passed, failed and blocked counts, and the defect log are empty, because no test has been executed and no result is claimed. The status columns of the milestone plan and of the traceability matrix state the planned or empty status and do not claim that any requirement has been implemented or verified. The percentages quoted from the survey are those of the first 31 of 73 responses, whose distribution across all responses was found to be nearly identical. The interview evidence consists of four interviews.

Quantities stated as targets, thresholds or limits, for example in the non-functional requirements and the algorithm parameters, are requirements or default design values and not measured results. Items that depend on outside confirmation are listed in Appendix C.