

Data Structures Lab



Lab # 05

Doubly Linked List

Lab Engineer: Hilal Ahmad

Department of Computer Science,
National University of Computer and Emerging Sciences FAST
Peshawar Campus

Table of Contents

1. Introduction to Doubly Linked List
2. Doubly Linked List Class Structure
3. Operations on Doubly Linked List
 - Insertion (at the head, tail, and specific position)
 - Deletion (from the head, tail, and specific node)
4. Tasks

1. Introduction to Doubly Linked List

A **doubly linked list** is a dynamic data structure consisting of nodes. Each node contains:

- **Data:** Stores the value of the node.
- **Previous Pointer:** Points to the previous node in the list.
- **Next Pointer:** Points to the next node in the list.

Differences from Singly Linked List:

- Doubly linked lists allow traversal in both directions (forward and backward).
- Each node has an extra pointer to the previous node, adding some overhead in terms of memory.

2. Doubly Linked List Class Structure

Node Class:

```
class Node {
public:
    int data;
    Node* prev;
    Node* next;

    // Constructor
    Node(int value) : data(value), prev(nullptr), next(nullptr) {}
};
```

DoublyLinkedList Class:

```
class DoublyLinkedList {
private:
    Node* head;    // Pointer to the first node
    Node* tail;    // Pointer to the last node

public:
    // Constructor
    DoublyLinkedList() : head(nullptr), tail(nullptr) {}

    // Destructor
    ~DoublyLinkedList() {
        while (head) {
            deleteHead();
        }
    }

    // Function prototypes
    void insertAtHead(int value);
    void insertAtTail(int value);
    void insertAtPosition(int value, int position);
    void deleteHead();
    void deleteTail();
    void deleteByValue(int value);
    void printListForward();
    void printListBackward();
};
```

3. Operations on Doubly Linked List

3.1 Insertion

We will implement insertion at two positions:

- **At the Head:** Insert a new node at the beginning.
- **At the Tail:** Insert a new node at the end

Insertion at the Head:

```
void DoublyLinkedList::insertAtHead(int value){
    Node* newNode = new Node(value);
    if (head == nullptr) {
        head = tail = newNode; // If the list is empty, set newNode as head and tail
    }
    else{
        newNode->next = head; // Point newNode's next to the current head
        head->prev = newNode; // Set current head's prev to newNode
        head = newNode; // Update head to the newNode
    }
}
```

Insertion at the Tail:

```
void DoublyLinkedList::insertAtTail(int value) {
    Node* newNode = new Node(value);
    if (tail == nullptr) {
        head = tail = newNode; // If list is empty, set newNode as head and tail
    } else {
        newNode->prev = tail; // Point newNode's prev to the current tail
        tail->next = newNode; // Set current tail's next to newNode
        tail = newNode; // Update tail to the newNode
    }
}
```

3.2 Deletion

We will implement deletion of:

- **By Value:** Remove a node with a specific value.

Deletion by value:

```
void DoublyLinkedList::deleteByValue(int value) {
    if (head == nullptr) return;    // If list is empty, return

    if (head->data == value) {
        deleteHead();
        return;
    }

    if (tail->data == value) {
        deleteTail();
        return;
    }

    Node* temp = head;
    while (temp != nullptr && temp->data != value) {
        temp = temp->next;           // Traverse to the node with the value
    }

    if (temp == nullptr) {
        cout << "Value not found!" << endl;
        return;
    }

    temp->prev->next = temp->next;
    if (temp->next != nullptr) {
        temp->next->prev = temp->prev;
    }
    delete temp;                    // Free the memory of the deleted node
}
```

4. Tasks

Task 1: Deletion of a Node

Write a function to delete a node with a specific value from the doubly linked list. Handle all edge cases, such as deleting the head, tail, or a middle node.

Task 2: Reverse the Doubly Linked List

Write a function to reverse the doubly linked list. Reverse the list by only adjusting the *next* and *prev* pointers of each node.

Task 3: Count the Number of Nodes

Implement a function to count the total number of nodes in the doubly linked list.

Task 4: Find a Node by Value

Write a function to search for a node with a given value in the list. Return the position and value of the node if found, otherwise return NULL.