

Discrete Structures (CS 1005)

Name : Muhammad Faizan Shabir

Roll Number : 22L-6552

Section : 3H

Date : 23rd October, 2023

Assignment Number : 3 (Three)

①

Q 1) You are given as input a 0-1 matrix $M[n][n]$ representing a relation R on a set. Write a code fragment to determine whether or not the relation R is Transitive.

```

bool IsTransitive(int M[n][n])
{
    int MSquared[n][n];
    for(int i=0; i<n; i++)
    {
        for(int j=0; j<n; j++)
        {
            MSquared[i][j] = 0;
            for(int K=0; K<n; K++)
            {
                MSquared[i][j] += M[i][K] * M[K][j];
            }
            if (MSquared[i][j] != 0)
            {
                MSquared[i][j] = 1;
            }
        }
    }
}

```

```

for(int i=0; i<n; i++)
{
    for(int j=0; j<n; j++)
    {
        if(MSquared[i][j]==1 && M[i][j]==0)
        {
            return false;
        }
    }
}
return true;
}

```

Q2) You are given as input a 0-1 matrix $M[n][n]$ representing a relation R on a set. Write a code fragment to compute the Transitive Closure of R .

②

Void ComputeTransitiveClosure(int M[n][n],
int TransitiveClosure[n][n])

```
{  
    int tempMatrix[n][n]; // temporary matrix  
    int powerMatrix[n][n]; // matrix to hold matrix powers  
  
    for(int i=0; i<n; i++)  
    {  
        for(int j=0; j<n; j++)  
        {  
            powerMatrix[i][j] = M[i][j];  
            // initialize power matrix with M[n][n]  
  
            TransitiveClosure[i][j] = M[i][j];  
            // initialize transitive closure matrix  
            with M[n][n]  
        }  
    }  
}
```

// loop runs $(n-1)$ times

```

for(int Counter=1; Counter < n; Counter++)
{
    // loop to calculate powers of matrix
    for(int i=0; i < n; i++)
    {
        for(int j=0; j < n; j++)
        {
            // reset reset temporary matrix entry to 0
            temp Matrix[i][j] = 0;

            for(int K=0; K < n; K++)
            {
                temp Matrix[i][j] += power Matrix[i][K] * M[K][j];
            }
        }
    }
}

if (temp Matrix[i][j] != 0)
{
    temp Matrix[i][j] = 1;
}

```

③

```
for(int i=0; i<n; i++)  
{  
    for(int j=0; j<n; j++)  
    {  
        powerMatrix[i][j] = tempMatrix[i][j];  
        // Copy the calculated power matrix  
        // into the powerMatrix  
    }  
}
```

```
for(int i=0; i<n; i++)  
{  
    for(int j=0; j<n; j++)  
    {  
        TransitiveClosure[i][j] +=  
        powerMatrix[i][j];  
        // taking Union of matrices  
        if (TransitiveClosure[i][j] != 0)  
        {  
            TransitiveClosure[i][j] = 1;  
        }  
    }  
}
```

}// end of loop that runs (n-1) times

// end of function

Q3) You are given as input two 2-dimensional arrays representing two n-ary relations of degree 10 and 8 respectively (you may assume number of tuples/records in each table by yourself). Write a code fragment to compute J_5 on the input tables.

(4)

Void ComputeJ5 (int R1[5][10], int R2[5][8],
 int J5[5][10+8-5])

→ the join will be stored in J5 array
 passed as parameter

for (int i=0; i<5; i++)

{

for (int j=0; j<10+8-5; j++)

{

J5[i][j] = -1; initialize J5
 matrix with -1

}

}

int ptr = 0;

for (int i=0; i<5; i++)

{

for (int j=0; j<5; j++)

{

if (R1[i][5] == R2[j][0] &&
 R1[i][6] == R2[j][1] &&
 R1[i][7] == R2[j][2] &&
 R1[i][8] == R2[j][3] &&
 R1[i][9] == R2[j][4])

{

for (int K=0; K<10; K++)

{

J5[ptr][K] = R1[i][K];

// get first 10 fields for J5
 from 10 fields of R1

}

for(int k=10, int l=5 ;

K < 10+8-5 ; K++, l++)

{

J5[ptr][K] = R2[j][l];

// get last 3 fields for
J5 from last 3 fields
of R2

}

ptr++;

j = 5;

}

// end of ~~IF~~ block.

}

// end of outer loop

}

// end of function

(5)

Q4) Let A be the set of students at your school and B the set of books in the school library. Let R_1 and R_2 be the relations consisting of all ordered pairs (a, b) , where student a is required to read book b in a course, and where student a has read book b , respectively. Describe the ordered pairs in each of these relations.

a) $R_1 \cup R_2$

$R_1 \cup R_2 = \{ (a, b) \mid \text{student } a \text{ is required to read book } b \text{ or student } a \text{ has read book } b \}$

b) $R_1 \cap R_2$

$R_1 \cap R_2 = \{ (a, b) \mid \text{student } a \text{ is required to read book } b \text{ and student } a \text{ has read book } b \}$

c) $R_1 \oplus R_2$

$R_1 \oplus R_2 = \{(a, b) \mid$ either student a
is required to read book b but student a
has not read book b or student a
has read book b but ~~or~~ student a
is not required to read book b. $\}$

d) $R_1 - R_2$

$R_1 - R_2 = \{(a, b) \mid$ student a is required
to read book b but student a has
not read book b $\}$

e) $R_2 - R_1$

$R_2 - R_1 = \{(a, b) \mid$ student a has read
book b but student a is not required
to read book b $\}$

(6)

Q5) Let R be the relation on the set of people consisting of pairs (a, b) ,

where a is a parent of b . Let S be the relation on the set of people consisting of pairs (a, b) , where a and b are siblings (brothers or sisters).

~~What are~~ What are $S \circ R$ and $R \circ S$?

$S \circ R$ is the composition of R and S .

$S \circ R = \{ (a, b) \mid a \text{ is a parent of } b \text{ and } b \text{ has a sibling} \}$

$R \circ S$ is the composition of S and R

$R \circ S = \{ (a, b) \mid a \text{ is an aunt or uncle of } b \}$

tid att nu mittidet att jag är.

(då) sedan jag initieras. Då jag if

är i tid. Det är tiden är den sedan

den initieras. Tid att nu mittidet att

den initieras. (då) sedan den initieras

(är) att nu mittidet. Då mittidet är

tid att nu mittidet är tiden.

Det är tiden är den sedan den initieras.

Det är tiden är den sedan den initieras.