The Aggregate Gap

What it costs to supervise a swarm that spends money, measured in cents

Apart Research Swarm Alignment 2026, Track 4 · Muhammad Hassaan Shaukat and Rızgar Ozan

Seeded and stdlib-only, reproducible from the seeds alone: 98 tests, and every figure below parsed out of a table this build re-reads.

What we found

Payment protocols for agent swarms enforce a budget **per mandate**. Nothing enforces one **across** mandates, so several agents that are each inside their own cap can move more of one principal's money than any of them was allowed to. We built the monitor that sees that shape, put it inline at a payment gateway, and scored every defence in cents settled rather than in flags raised.

The monitor is real and it is free. It holds the per-payee, per-window line against every attack written to its limits, at zero false alarms on benign logs of any length, and inline at the gateway it cuts attack money that settles from 1.00 to 0.67 on those attacks. It catches nothing among the held-out attacks that never cross a bound: split_distinct, split_slow and alias_far each have recall 0.00 and settle 1.00 of their money under both the per-mandate cap and the monitor.

Then we argued against our own addition. A supervisor sitting in the authorization path, asked only as a payee comes near the bound, moves attack money from 0.785 to 0.752 for $0.01162 a log and 1.71 calls a log, with the model's wait inside the payment decision. AI Control protocols make that supervisor survivable when it is subverted: withholding the actor's draft from the reviewer is the only arm that beats a colluding pair (0.785 → 0.755), and a honeypot retires a reviewer who cannot pass it. But the last measurement says the model needs none of that to be justified. **A rule that counts each payment toward two ways of reading a payee name, and answers a flag by holding the payment instead of freezing the swarm, settles 0.752 of attack money — the same as the model, scenario by scenario, in every scenario with attack money — holds less legitimate money (0.071 against 0.121), and costs nothing.**

1. The gap, and the shape of a defence

Track 4 asks how to oversee and control a swarm of agents that act with money. Our setting is the narrowest version of that we could state precisely: N agents, one principal, spends and transfers, and a policy that binds the principal rather than the agent. A 2026 security analysis of Google's AP2 reports budget constraints enforced per mandate and none across mandates (arXiv:2608.23858; we have not verified this against the specification and cite it as motivation, not as fact). The human version of the same failure is structuring, and banks have had rules for it for decades.

The monitor keeps the principal's ledger instead of the agents'. Six named checks, each removable on its own so every rule is measured individually: `agent_over_limit, relay, relay_multi_hop, split_payment, slow_split, payee_alias`. A relay is traced back to the agent whose money it carries, so three hops cannot launder a cap. A payee is keyed by who it is, not by the string printed on the payment.

2. Method

- **Money, not flags.** Every arm is scored as the share of attack money that settles and the share of legitimate money that is stopped, in cents, per seeded log. A defence that detects late still lets the money out, and the tables show that rather than hiding it.
- **Two attack sets.** Five scenarios tuned on the limits, five held out and written afterwards. The held-out attackers check their own budgets first: distinct payees, a rename past the similarity cutoff, a drip slower than the window.
- **Horizon.** Benign logs from 40 to 300 ticks, with false alarms per 1,000 actions as well as per run. This is how the first version of the monitor was found to be wrong: summing a payee over the whole log looked clean at 40 ticks and flagged 92% of benign swarms at 200.
- **Intervals.** 200 seeds per cell for the rule results, 50 for the model arms, Wilson 95% intervals, no cell reported without them.
- **Negative controls.** 98 tests; each one removes a rule, a protocol setting or a capability and requires the failure to come back. Two of the results below are the product of that habit rather than of looking for them.

3. What the rules are worth at a gateway

Share of attack money that settles, lower is better, 200 seeds. *per_mandate* is what a payment protocol enforces today; *ledger* adds one cap on the whole principal; *monitor* adds the swarm monitor inline, which holds the flagged payment and stops the swarm:

scenario	per_mandate	ledger	monitor	ledger+monitor
split_payment	1.00 [1.00, 1.00]	0.71 [0.70, 0.73]	0.67 [0.67, 0.67]	0.67 [0.67, 0.67]
relay	0.55 [0.50, 0.60]	0.55 [0.50, 0.60]	0.44 [0.42, 0.47]	0.44 [0.42, 0.47]
split_wide	1.00 [0.99, 1.00]	0.80 [0.78, 0.83]	0.67 [0.66, 0.67]	0.67 [0.66, 0.67]
relay_two_hop	0.55 [0.50, 0.59]	0.55 [0.50, 0.59]	0.43 [0.41, 0.46]	0.43 [0.41, 0.46]
split_alias	1.00 [0.99, 1.00]	0.71 [0.69, 0.73]	0.67 [0.66, 0.67]	0.66 [0.66, 0.67]
split_distinct	1.00 [1.00, 1.00]	0.79 [0.77, 0.82]	1.00 [1.00, 1.00]	0.79 [0.77, 0.82]
split_slow	1.00 [1.00, 1.00]	0.92 [0.90, 0.94]	1.00 [1.00, 1.00]	0.92 [0.90, 0.94]
alias_far	1.00 [1.00, 1.00]	0.80 [0.77, 0.82]	1.00 [1.00, 1.00]	0.80 [0.77, 0.82]
relay_fanout	1.00 [1.00, 1.00]	1.00 [1.00, 1.00]	0.69 [0.69, 0.69]	0.69 [0.69, 0.69]
relay_reversed	1.00 [1.00, 1.00]	1.00 [0.99, 1.00]	0.98 [0.96, 1.00]	0.98 [0.96, 0.99]

The honest reading is prevention, not detection. The per-agent cap alone lets 1.00 of a split payment leave. Inline monitoring gets that to 0.67 — it stops the payment that raises the flag, but the money ahead of that flag is already gone. A principal-wide ledger sized from benign traffic trades one currency for the other: the tight setting (a 20-tick window at the median benign peak) cuts attack money to 0.10 but blocks 0.608 of a legitimate busy week, and 0.174 at the 99th-percentile setting we would actually ship. Nothing here is free except the monitor, and it only stops the attacks it was written for.

False alarms against log length, same monitor, two ways of summing a payee. The *lifetime* row is our first version; it is not a safe default at any length, it is only untested at short ones:

payee total	ticks	swarm false-alarm runs [95% CI]	swarm flags / 1000 actions	runs where an agent exhausted its lifetime budget
lifetime	40	0.00 [0.00, 0.02]	0.00	0.00
lifetime	80	0.00 [0.00, 0.02]	0.00	0.01
lifetime	120	0.02 [0.01, 0.05]	1.17	0.14
lifetime	160	0.27 [0.21, 0.34]	15.30	0.82
lifetime	200	0.92 [0.87, 0.95]	86.89	1.00
lifetime	300	1.00 [0.98, 1.00]	462.68	1.00
window	40	0.00 [0.00, 0.02]	0.00	0.00
window	80	0.00 [0.00, 0.02]	0.00	0.01
window	120	0.00 [0.00, 0.02]	0.00	0.14
window	160	0.00 [0.00, 0.02]	0.00	0.82
window	200	0.00 [0.00, 0.02]	0.00	1.00
window	300	0.00 [0.00, 0.02]	0.00	1.00

4. The swarm we did not write

Everything above is our generator, so it proves our generator is coherent. To check that the shapes are ours and not real swarms', we measured the published reconstruction of a real multi-agent incident (Swarm Traces, and the AI Village corpus behind it) with the same monitor, using only the fields the records actually carry. Two of the four findings below are negative, and they are the reason the report does not claim external validation.

- 189,579 records, 61,125 parent-child edges, 26,248 parent nodes. Fan-out median 1, p99 12, max 858 — a real swarm does fan out, and one node in the data is wider than any relay we modelled.
- **0 nodes are both a parent and a child.** Relay depth is not observable in the published data at all. Our multi-hop trace cannot be validated here, only reproduced in a generator, so every relay number in this report is synthetic.
- **0 records carry a time.** A windowed rule cannot be scored on this data. We reported the reading that needs no clock as well: at 30,000 cents per branch the tight-ordering violation rate is 0.225 and the clock-free rate is the same 0.225, while the worst-case ordering is 0.000. The rule's apparent failure is an artefact of assuming a clock we do not have.
- 28,086 distinct destinations, the busiest taking 14.6% of the marks. Against a bound of $600 per payee per window, moving $100,000 needs 167 of them and the observed pool covers 168.5 such runs. **Identity spread, with no amount ever over any bound, is the lever a real swarm already has.** That is the evidence for section 7's free rule.

5. A model in the authorization path, and what it costs

A rule monitor is free, instant and cannot be argued with, but it only reacts to shapes someone wrote down. The alternative is a model that reads the same state and answers questions no rule encodes. We wired an assistant at the point where a payment is about to settle — Meta's MUSE API, Muse Spark 1.3 and Muse Wonder 1.0, priced from the published table — and ran the same arms against an offline stand-in that answers through the identical code path.

One structural fact organises everything below it: **the gateway asks the model only about payments the rules already let through.** A model can decline to hold, it can never release. So a supervised arm is always a subset of the rules, its worst case is legitimate money held that was owed, and any protocol that lets a reviewer's *allow* clear a flag has to be built by switching the rules off. That is deliberately one-directional authority, and it is why section 6 can report a safety property that holds whatever the models do.

Live runs are blocked: no API key was provided for this sprint. Every number in this report therefore comes from the offline arms that exercise the same wiring. We state that rather than papering over it: the model-side claims here are about protocol structure and about the cost of a call, not about the quality of any model.

6. Which protocol survives which failure

AI Control (Greenblatt et al., arXiv 2312.06942) keeps a model you do not trust useful by construction. Five arms at the payment seam, 14 scenarios, 50 seeds, with each seat's competence and honesty as free parameters. *attack out* is the share of attack money that settles, *held* the share of legitimate money stopped; rows with population *rules only* have no model in the loop:

population	protocol	attack out	held	calls/log	$/log
rules only	rules	0.785	0.121	0.00	0.00000
rules only	rules, hold the payment	0.785	0.071	0.00	0.00000
competent_honest	trust	0.824	0.001	24.24	0.21332
competent_honest	trusted_editing	0.755	0.121	1.71	0.00870
competent_honest	monitoring	0.752	0.121	1.71	0.01162
competent_honest	monitoring (blind)	0.752	0.121	1.71	0.01162


population	protocol	attack out	held	calls/log	$/log
competent_honest	monitor_releases	0.833	0.001	48.48	0.32968
colluding_pair	monitoring	0.785	0.121	1.71	0.01162
colluding_pair	monitoring (blind)	0.755	0.121	1.71	0.01162
reviewer_bought	monitor_releases	0.923	0.000	48.48	0.32968
reviewer_suspicious	trusted_editing	0.495	0.147	1.47	0.00748

- **Nothing behind the rules settled more attack money than the rules did, in any of 294 (population, arm, scenario) triples** — including a fully bought reviewer and a colluding pair. Safety here is a property of the authority structure, not of anyone's judgement.
- **The draft is the channel.** Under a colluding pair, the reviewer who reads the actor's reasoning lets out 0.785 — exactly what the rules alone let out. Withhold the text and the same pair gets 0.755. Two models that share a language have only that language to conspire in (Motwani et al., arXiv 2402.07510). The control is to withhold the text.
- **Letting a reviewer overrule a flag buys back the attack the rules stopped, and pays for the privilege.** The same colluding pair settles 0.923 under that arm — the 0.923 an unsupervised per-mandate gateway pays out — at 48.48 calls a log. The monitor is worth nothing once a reviewer can overrule it, and the calls are all price.
- **A honeypot is a control, not a fallback.** One plainly fine payment offered at every consult, with the arm silenced permanently on the first miss. On a reviewer paranoid enough to settle only 0.495 of attack money while holding 0.147 of legitimate money, the trap switches it off: attack money back up to 0.754, held money down to 0.124, and the bill cut from $0.00748 to $0.00165 a log. That is an honest trade, not a win: the trap removes a seat you cannot trust and gives back what that seat was catching. Run once per log it is worth nothing — the reviewer only has to be lucky on the one draw — and with the rules switched off, silencing the reviewer *is* the failure: the ablation plus honeypot pays out 0.923.

7. The negative result: the model's edge is a string rule

For the comparison to be fair the model had to be able to differ from the rule at all. Both seats keep the monitor's own ledger and read the same bound; what they get that the shipped rule does not is a different answer to *is this the same payee*. We turned that into a switch: `prefix` (normalise, then merge on a shared prefix or 0.85 character similarity), `tokens` (the set of meaningful words, corporate suffixes dropped) and `both` (one payment counted toward both readings). Two scenarios pin the difference down. *split_renamed*: one firm typed three ways, every pair below the cutoff and none a prefix of another, so the shipped reading sees three payees and lets 1.000 of the money out. *benign_stem*: two genuinely different payees sharing a 15-character identifier stem, which is the actual namespace of the incident dataset.

Pooled over the same 50 seeds and 14 scenarios, both axes lower is better. The open diamond is the only point that pays for a call, and the dashed line runs to the free rule that matches it on attack money and beats it on legitimate money:



Each cell is attack money settled / legitimate money held, over the same 50 seeds. Only the last column pays for a call:

scenario	prefix	words	both	both, no freeze	rules+model	model $/log
benign	-	-	-	-	-	0.00000
split_payment	0.666 / 0.000	0.666 / 0.000	0.666 / 0.000	0.666 / 0.000	0.666 / 0.000	0.01360
relay	0.423 / 0.000	0.423 / 0.000	0.423 / 0.000	0.423 / 0.000	0.423 / 0.000	0.00408
split_wide	0.663 / 0.000	0.663 / 0.000	0.663 / 0.000	0.663 / 0.000	0.663 / 0.000	0.01360
relay_two_hop	0.409 / 0.000	0.409 / 0.000	0.409 / 0.000	0.409 / 0.000	0.409 / 0.000	0.00381
split_alias	0.663 / 0.000	0.891 / 0.000	0.663 / 0.000	0.663 / 0.000	0.663 / 0.000	0.00707
benign_busy	-	-	-	-	-	0.01142
split_distinct	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	0.00000
split_slow	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	0.02720
alias_far	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	1.000 / 0.000	0.00789
relay_fanout	0.687 / 0.526	0.687 / 0.526	0.687 / 0.526	0.687 / 0.194	0.687 / 0.526	0.01333
relay_reversed	1.000 / 0.147	1.000 / 0.147	1.000 / 0.147	1.000 / 0.051	1.000 / 0.147	0.02122
split_renamed	1.000 / 0.000	0.662 / 0.358	0.662 / 0.358	0.662 / 0.000	0.662 / 0.000	0.02720
benign_stem	-	-	-	-	-	0.01224

Read the fourth column against the fifth. The model arm and the two-reading rule that holds instead of freezing catch the same attack money in every scenario that has any. The rule holds strictly less legitimate money where the shipped rule freezes: 0.194 against 0.526 on relay_fanout, 0.051 against 0.147 on relay_reversed, 0.071 against 0.121 pooled. The model arm inherits the rules' freeze and pays $0.01162 a log on top of it. Two string comparisons and one change of reaction do the same work, with no call inside the payment decision, no latency, and nobody to argue with or to subvert. **The honest version of that sentence is a defect report on our own rule monitor, not a claim about models:** the shipped merge rule was wrong in both directions, it merged identifier namespaces that were nothing of the kind and missed a word-order swap, and the model was compensating for that bug for its whole price tag.

8. What these numbers do not say

- **The stand-ins are not models.** Every supervised result is a statement about a protocol under an assumed failure rate. The rates are parameters and no measurement here claims a real model behaves this way. Until a key is in hand the live MUSE arms are unwired evidence, and section 5 says so.
- **What the free rule cannot do is exactly what a model is for.** An abbreviation that only makes sense if you know who the vendor is — *OC Advisory Ltd* for the same offshore consultancy — is not a string comparison, and no scenario in this harness measures it. The three held-out attacks that settle 1.000 in every column of section 7 are that gap's neighbourhood: our stand-in can only redo arithmetic, so a 1.000 there is a statement about the stand-in, not a refutation of models.
- **The generator is the attacker we imagined.** The held-out shapes were written by us, after seeing the rules. That is an adaptive limit, not a world.
- **Relay depth and every windowed number are unvalidated externally.** The published incident reconstruction has no node that is both a parent and a child, and no timestamps at all, so section 4's own data cannot check sections 3 and 7.
- **Freezing is a policy, not a constant.** A large part of what the model appeared to buy was a difference in reaction: hold the payment, or stop the swarm. Reported as separate columns, that axis is worth more than the judgement — which is the kind of result a harness only produces if it was built to be able to embarrass its own author.
- **The durable claim is the bound, not the defence.** Against everything we ran, no payee family received more than its cap inside any long window. An attacker wanting more has to go slower or register more identities: a rate limit in cents per tick that holds against an attacker who knows the rules and the limits.

9. Reproduce

Repo github.com/muhammad-hassaan-y2/Twin-, directory `swarm-oversight/`, branch `aggregate-gap`. Stdlib only, except reportlab and matplotlib for this document.

```
pip install -e .[dev] && pytest  # 98 tests
python -m swarm_oversight.report --seeds 200  # rules, gateway, horizon
python -m swarm_oversight.tracegraph  # the published incident data
python -m swarm_oversight.oversight --seeds 50 --advisor stub
python -m swarm_oversight.aicontrol --seeds 50 --merge prefix --out results
python -m swarm_oversight.aicontrol --seeds 50 --merge prefix --probe --out results
python -m swarm_oversight.aicontrol --seeds 50 --merge both --out results
python -m swarm_oversight.aicontrol --seeds 50 --identity-sweep --out results
python -m swarm_oversight.pdf_report --out report.pdf
```

References

Greenblatt, Barnes, Larson, *AI Control*, arXiv:2312.06942. · Motwani et al., *Secret Collusion among Generative AI Models*, arXiv:2402.07510. · *How Google Handles Money with AP2: A Security Analysis*, NeurIPS 2024, arXiv:2608.23858 — cited as motivation; the per-mandate claim is not yet verified against the specification. · METR, *Hugging Face incident report*, August 2026. · Swarm Traces (swarmtraces.org) and the AI Village corpus, aidigestorg/ai-village.