

# PS-Diffusion: Photorealistic Subject-Driven Image Editing with Disentangled Control and Attention

Weicheng Wang<sup>1</sup>, Guoli Jia<sup>3</sup>, Zhongqi Zhang<sup>1</sup>, Liang Lin<sup>2,4</sup>, Jufeng Yang<sup>1,2,5\*</sup>

<sup>1</sup> VCIP & TMCC & DISSec, College of Computer Science, Nankai University, Tianjin, China.

<sup>2</sup> Pengcheng Laboratory, Shenzhen, China.

<sup>3</sup> Electronic Engineering Department, Tsinghua University, Beijing, China.

<sup>4</sup> School of Computer Science and Engineering, Sun Yat-sen University, Guangzhou, China.

<sup>5</sup> Nankai International Advanced Research Institute (SHENZHEN·FUTIAN), Shenzhen, China.

2120230639@mail.nankai.edu.cn, exped1230@gmail.com

15692233416@163.com, linliang@ieee.org, yangjufeng@nankai.edu.cn




Figure 1. We aim to edit the object (red boundary) in the source with the object (green boundary) in the reference. PS-Diffusion simulates consistent contextual interactions of objects on scenes, such as reflection, illumination, and shadow, achieving **photorealistic** image editing and keeping the target appearance unchanged. Results from our proposed Replace-5K and real-world data in DreamBooth are shown.

## Abstract

Diffusion models pre-trained on large-scale paired image-text data achieve significant success in image editing. To convey more fine-grained visual details, subject-driven editing integrates subjects in user-provided reference images into existing scenes. However, it is challenging to obtain photorealistic results, which simulate contextual interactions, such as reflections, illumination, and shadows, induced by merging the target object into the source image. To address this issue, we propose PS-Diffusion, which ensures realistic and consistent object-scene blending while maintaining the invariance of subject appearance during editing. To be specific, we first divide the contextual inter-

actions into those occurring in the foreground and the background areas. The effect of the former is estimated through intrinsic image decomposition, and the region of the latter is predicted in an additional background effect control branch. Moreover, we propose an effect attention module to disentangle the learning processes of interaction and subject, alleviating confusion between them. Additionally, we introduce a synthesized dataset, Replace-5K, consisting of 5,000 image pairs with invariant subject and contextual interactions via 3D rendering. Extensive quantitative and qualitative experiments on our dataset and two real-world datasets demonstrate that our method achieves state-of-the-art performance. The code is available in the <https://github.com/wei-cheng777/PS-Diffusion>.

\* Corresponding author.

## 1. Introduction

Image editing aims to modify images following user-specified editing targets, and unrelated content remains consistent with the source images. Benefiting from the recent success of diffusion models, image editing has received unprecedented progress. As a highly controllable task, image editing based on diffusion models [18, 37, 66] is widely applied in real-world scenarios such as personalization [35, 50], try-on [29, 43, 73], and E-commerce [5, 10].

To convey fine-grained visual concepts and precisely articulate the user’s desires, subject-driven image editing [35, 45, 62] (SDIE) integrates the subject in reference image into an existing scene. Built on the diffusion model, Paint-by-Example [62] proposes a subject-driven editing framework for inpainting masked regions guided by the CLIP embeddings of reference images. Anydoor [8] enhances identity consistency by injecting self-supervised representation and detailed maps. To directly edit image pixels, Copy-Paste [14] is another simple method to integrate the entirely unchanging subject into the source image by copy and paste. However, the current diffusion-based methods mainly focus on preserving semantic consistency. Indiscriminately enhancing consistency via copy overlooks the contextual interaction of the object on the scene, such as reflection, illumination, and shadow in Fig. 1. This poses a significant challenge to acquiring photorealistic results.

To achieve photorealistic SDIE, there are pioneering works initially explored to simulate contextual interactions of objects on scenes, as well as maintain high consistency of subject identity. Graphics-based methods [36, 52–54, 61] render contextual interactions based on 3D assets and physical parameters. To relax the requirement for highly-cost parameters, an alternative solution is utilizing two-stage generative editing methods, removing the source object by inpainting [27, 47, 63] and then inserting [19, 59] the targets. However, they still face the following challenges in achieving photorealism: 1) Removal stage: Most inpainting models [47, 74] struggle to eliminate the original contextual interactions of the source object outside the mask indicating the editing area. 2) Insertion stage: Harmonization-like methods [19, 58] primarily affect the object area within the mask. 3) Consistency across stages: Although some object insertion or removing methods [41, 57, 59] account for physical laws, the individual process overlooks the consistency of contextual interactions before and after editing.

Facing the above issues, we propose an end-to-end Photorealistic Subject-driven image editing approach, PS-Diffusion. To cover most contextual interactions of the object on the scene, we divide them into two aspects based on affecting regions: 1) Effects on the foreground within the mask, such as lighting. 2) Effects on the background outside the mask, such as shadow and reflection. Then, we use disentangled control signals to guide respective edit-

ing processes in the diffusion model. For the former, we condition the diffusion denoising process with illumination-dependent properties estimated by intrinsic image decomposition. These properties derived from the source images improve the consistency of contextual interactions during editing. For the latter, we introduce an additional background effect control branch to perceive effect regions outside user-defined masks by learning an effect map. Unlike object editing, modifications to scene effects typically build upon existing images without significantly altering the original pixels. Therefore, directly weighting the two branches causes confusion between the learning of interactions and subjects. To separate them, we introduce the Effect Attention Module (EAM) in denoising U-Net, which reorganizes the structural features of interaction regions and lighting conditions to improve the plausibility of effects. Finally, due to the scarcity of paired data, we curated a dataset comprising 5,000 data pairs, *i.e.* Replace-5K, by Blender.

Our contributions are four-fold: 1) We propose PS-Diffusion for photorealistic SDIE, ensuring consistent contextual interactions and object identity. Disentangled control allows the model to recognize interactions without being restricted by masks. 2) EAM enhances visual plausibility by separating interaction and subject learning. 3) We introduce an exquisite synthetic dataset, Replace-5K, with 5,000 image pairs that simulate the interactions between scenes and objects. 4) Extensive experiments on synthetic and real-world datasets demonstrate the effectiveness.

## 2. Related Work

### 2.1. Image Editing

Priors of generative models play a crucial role in effective image editing. In GAN-based methods [60, 72], the image is inverted into the latent code of the pre-trained GAN [3, 28]. Recently, text-to-image (T2I) diffusion models [46, 47, 49] enhance image editing controllability. Benefiting from pre-training on image-text pairs, it is efficient to guide editing through texts of the target [13, 20, 55] or instructions that express the editing purpose [4, 26]. However, texts struggle to control fine-grained visual details. Utilizing the inherent visual information in images to guide editing has been extensively explored [17, 50, 65]. To precisely locate the editing position, the mask [1, 9, 40, 51] is another visual cue to control the editing area. Moreover, combining multiple control signals [12, 23] can address more complex needs. In this paper, we use image guidance and mask localization to achieve precise image editing.

### 2.2. Subject-Driven Control in Diffusion Models

Subject-driven control aims to align the subject of outputs with user-provided references [24, 35, 68]. Subject-driven image generation [13, 33, 50] creates new scenes containing




Figure 2. Pipeline of our method. We disentangle the control signals of contextual interactions into those within and outside  $M_u$ . EAM decouples the learning of the subject and the interaction.  $M_u$  is the union of the source object mask  $M_s$  and the target mask  $M_t$ .  $B_s^{m,p}$  is the background pasted with the object.  $S_s$  is the shading of  $X_s$  extracted by [6].  $N_s$  and  $N_r^*$  are the normal of  $X_s$  and  $X_r^*$ .

user-provided subjects based on text. However, text alone only maintains the semantic consistency of scenes. Many researchers [35, 62] study subject-driven image editing to achieve finer control over background and foreground. Based on DreamBooth [50], DreamEdit [35] proposes an iterative strategy to inpaint the masked areas of the source image while protecting the background. Instead of fine-tuning each subject, Paint-by-Example [62] and ObjectStitch [56] train a unified model in a self-supervised manner by injecting image embeddings into the cross-attention layer. PhD [71] improves subject fidelity by inputting background images pasted with the subject into ControlNet [69]. Any-Door [8] further improves identity preservation by extracting self-supervised embedding and high-frequency maps. Despite these advancements, most methods only focus on maintaining semantic similarity. Importantly, few works focus on the effects of interactions between scene and object during editing, which is crucial for achieving photorealism.

### 2.3. Physical Control in Diffusion Models

In image generation or editing, physical plausibility of contextual interactions is essential for realistic outcomes. Research on physical control can be classified into two main areas. On the one hand, some work targets specific physical properties, such as lighting [39] and shadows [34]. For instance, LightIt [31] incorporates lighting conditions and normal maps as additional controls in text-to-image diffusion models. SGDiffusion [38] proposes diffusion-based shadow generation methods. On the other hand, some incorporate general scene effects. ObjectDrop [59] proposes object removal and insertion complying with physical laws trained on a counterfactual dataset. Generating a dataset containing pairs with and without foreground, Tarrés *et*

*al.* [57] allows the generation of shadows and reflections in object insertion. However, managing physical effects at an individual stage *e.g.* object removal or insertion, ignores the consistency of physical laws during editing. To ensure consistency supervision, we construct a physically consistent paired dataset by industrial rendering engines.

## 3. Method

### 3.1. Overview

We aim to edit the object in a source image with the subject from a reference image, guided by object masks as positioning information. Formally, an source image  $X_s = \{F_s, B_s\} \in \mathbb{R}^{H \times W \times 3}$  consists of a foreground object  $F_s$  and a background  $B_s$ , while mask  $M_s \in \mathbb{R}^{H \times W}$  indicates the location of the foreground object. During the editing, given a reference image  $X_r = \{F_r, B_r\} \in \mathbb{R}^{H' \times W' \times 3}$  with mask  $M_r \in \mathbb{R}^{H' \times W'}$  indicating the position of the reference object,  $F_s$  in the  $X_s$  is replaced by  $F_r$ . The target mask  $M_t \in \mathbb{R}^{H^* \times W^*}$  is used to specify the location and size of  $F_r$  within  $X_s$ . Finally, result image  $X_{gt} = \{F_r, B_s\}$  after editing will be obtained.

As shown in Fig. 2, our baseline consists of two main components: ControlNet [69] position control (original branch) and reference image condition. To control editing regions in the background, we first concatenate the masked source background  $B_s^m$  and mask  $M_u$  like [27, 62]. Here,  $M_u$  is the union of the source object mask  $M_s$  and the target mask  $M_t$ ,  $B_s^m = B_s \cdot (1 - M_u)$ . To preserve the subject identity, we paste  $F_r$  in  $X_r$  onto the  $B_s^m$  as prior following [71], *i.e.*  $B_s^{m,p} = \text{Paste}(B_s^m, F_r)$ . Then, the concatenated  $B_s^{m,p} \otimes M_u$  are input into ControlNet with coefficient  $\alpha$  to get the feature  $C_o$ , where  $\otimes$  is the concatenate opera-

tion. To guide the denoising process with the reference image, we replace the text embedding of Stable Diffusion [49] with the image embedding  $T_r$  extracted by DINOv2 [44]. Finally, a linear layer [8] is used to align the dimensions.

We incorporate the learning for contextual interactions of the object on the scene in SDIE by disentangled effect control and attention. The former decouples control signals of effects caused by interactions into those within and outside of  $M_u$ , and enhances respective performance by the condition of foreground effect and an additional background effect control branch in Stable Diffusion. EAM introduced in the latter improves the plausibility of effects by separating the learning of interactions from that of subjects.

### 3.2. Disentangled Effect Control

**Foreground effect condition branch (FECB).** FECB aims to estimate the effects on objects within  $M_u$ , such as lighting. To eliminate the influence of the background on the extraction of subject features, areas outside  $M_r$  are first filled with white pixels [8, 45],  $X_r^* = \text{Filling}(X_r)$ . However, the effect of  $B_r$  on the  $F_r$  remains. Given our goal to preserve the appearances of the subjects as much as possible, bias from  $B_r$  could lead to undesirable copy-paste artifacts. Given that lighting is the main factor, we condition the diffusion process with illumination-dependent effects using intrinsic image decomposition [6, 7]. To be specific, intrinsic image decomposition separates  $X_s$  and  $X_{gt}$  into the illumination-invariant properties  $A_s$  and  $A_{gt}$  (albedo), and the illumination-dependent effects  $S_s$  and  $S_{gt}$  (shading):

$$X_s = A_s \cdot S_s, X_{gt} = A_{gt} \cdot S_{gt} \quad (1)$$

To keep the consistency of illumination, we first estimate the lighting parameters  $l_s$  in the source image inspired by the parametric illumination model in [7]:

$$l_s = \text{Estimator}(T_{N_s}, T_{S_s}) \quad (2)$$

where  $T_{N_s}$  and  $T_{S_s}$  are embeddings extracted by DINOv2 from normal  $N_s$  and shading  $S_s$  of  $X_s$ .  $l_s$  is the high-dimensional lighting-related feature, not constrained by specific light models. Training on paired images rendered under diverse lighting and reflectance models enables PS-Diffusion to learn various lighting. Next, we obtain the illumination-dependent feature  $T_{S_r^*}$  of  $X_r^*$  under  $l_s$  through reshading. Then,  $T_r$  in the baseline and  $T_{S_r^*}$  are fused:

$$T_{S_r^*} = \text{Reshading}(T_{N_r^*}, l_s), \hat{T}_r = \text{Fusion}(T_r, T_{S_r^*}) \quad (3)$$

$T_{N_r^*}$  is embeddings from normal  $N_r^*$  of  $X_r^*$ .  $\hat{T}_r$  is the final feature input into the projection layer. The Estimator, Reshading, and Fusion are two-layer MLPs. Moreover, we supervise  $\hat{T}_r$  and  $T_{S_r^*}$  with  $X_{gt}$  and  $S_{gt}$ :

$$\mathcal{L}_{sim} = 2 - \text{Cosine}(\hat{T}_r, T_{gt}) - \text{Cosine}(T_{S_r^*}, T_{S_{gt}}) \quad (4)$$

where  $T_{gt}$  and  $T_{S_{gt}}$  are DINOv2 embedding of  $X_{gt}$  and  $S_{gt}$ . Benefiting from paired training data, FECB can autonomously learn additional attributes, such as roughness. By guiding the denoising process with  $T_{S_r^*}$ , our model not only accounts for effects of contextual interactions on the foreground but also potentially steers the editing of effects on the background through the cross-attention mechanism.

**Background effect control branch (BECB).** Although FECB transfers lighting, ControlNet’s structural constraint in the original branch limits editing outside  $M_u$ . BECB aims to learn structural features for object-scene interactions projected onto the background outside  $M_u$ , such as shadows and reflections. Some works [57, 59] directly fine-tune on large-scale datasets to implicitly learn effects outside masks. We aim to explicitly learn the effects region in an additional branch. Specifically, given a background  $B_s^{m-p}$  pasted with the reference object, we predict an effect map  $\hat{M}_e$  through a function  $\mathcal{F}$  to indicate where the effects of objects on the scene will appear in the background. Similarly, the concatenated  $B_s^{m-p} \otimes \hat{M}_e$  is fed to ControlNet. The final feature  $C_{\text{effect}}$  is scaled with an additional coefficient  $\beta$ :

$$C_{\text{effect}} = \beta \cdot \text{ControlNet}(B_s^{m-p} \otimes \hat{M}_e) \quad (5)$$

Given that the original branch of ControlNet has learned the structural information related to the mask, we share their weights, avoiding additional training burden.

It is not trivial to directly train  $\mathcal{F}$  to predict  $\hat{M}_e$  while keeping consistent physical laws during editing. To accelerate learning, we exploit the consistency prior of effects on scenes. Specifically, although objects differ, their effects on the same scene often exhibit strong consistency in certain attributes. For instance, if a scene is cast shadows of objects, the direction of these shadows typically remains consistent, regardless of changes to objects. To utilize this prior, we estimate a rough mask  $M_e^{rough}$  from  $X_s$  in LAB color space to further guide the  $\mathcal{F}$ , as most effects on the background involve changes in brightness [42]. Following [42], we calculate mean values  $\mu_L$ ,  $\mu_A$  and  $\mu_B$  of the pixels in L, A, and B planes of  $X_s$ . If  $\mu_A + \mu_B \leq \tau$ , we classify pixels in L plane as effect pixels when they meet  $L(x, y) \leq \mu_L - \frac{\sigma_L}{3}$ :

$$M_e^{rough} = \begin{cases} 1, & \text{if } L(x, y) \leq \mu_L - \frac{\sigma_L}{3} \wedge \mu_A + \mu_B \leq \tau \\ 0, & \text{otherwise} \end{cases} \quad (6)$$

where  $\tau$  is a threshold,  $\sigma_L$  denotes the standard deviation of the L plane. Finally, we concatenate  $M_e^{rough}$  and  $B_s^{m-p}$  and input them into  $\mathcal{F}$ , resulting in:

$$\hat{M}_e = \mathcal{F}(B_s^{m-p} \otimes M_e^{rough}) \quad (7)$$

Moreover, benefiting from our paired dataset, we can acquire the label  $M_e$  indicating the regions that need to be edited when the object changes. Given a pair of  $X_s$  and

$X_{gt}$ , we first calculate the pixel-wise difference  $M_e(i, j) = |X_{gt}(i, j) - X_s(i, j)|$ . Then, we apply the threshold  $\tau'$  to binarize and exclude the area of  $M_u$ . Under the supervision of  $M_e$ , we optimize  $\mathcal{F}$  using a binary segmentation loss, specifically the BCEWithLogitsLoss:

$$\mathcal{L}_m = \text{BCEWithLogitsLoss}(\hat{M}_e, M_e) \quad (8)$$

In addition,  $\hat{M}_e$  is a smoothed map rather than a binary mask, which supports the simultaneous training of  $\mathcal{F}$  and Stable Diffusion. This effectively leverages the physical knowledge learned from large-scale pre-training [32, 67].  $\mathcal{F}$  in our method is a simple U-Net.

### 3.3. Effect Attention Empowered Denoising U-Net

Unlike object editing tasks such as inserting or restoring, editing of effects augments existing images without significantly altering the original pixels [16]. For example, when shadows or reflections are projected onto the background, the underlying scene remains discernible to the viewer. On the one hand, since ControlNet controls the editing position, directly weighting the features from the two branches confuses the learning for editing objects and effects, leading to disruptions in the background or foreground. On the other hand, there is an inherent gap between the structural features of BECB and the lighting features of FECB. Therefore, we propose an Effect Attention Module (EAM) to separate them and reorganize disentangled effect control.

Given the effects are built upon the existing background or foreground, EAM introduces an extra attention layer after the cross-attention layer in the decoder of U-Net. The output  $F_{\text{cross}}$  from the cross-attention incorporates reference image features from condition and source background features from the original ControlNet branch. For effect control outside mask, the query  $Q_{\text{EAM}}$  for the EAM is formed by combining  $F_{\text{cross}}$  with  $C_{\text{effect}}$ , indicating effect regions:

$$Q_{\text{EAM}} = F_{\text{cross}} + (W \cdot C_{\text{effect}} + b) \quad (9)$$

$W$  and  $b$  are the Adapter’s weight matrix and bias vector. Adapter aligns dimensions and adjusts  $C_{\text{effect}}$  to effects editing task. The key  $K_{\text{EAM}}$  and value  $V_{\text{EAM}}$  are derived from  $\hat{T}_r$ , which captures the effects within mask. The attention weights for the EAM are then calculated as follows:

$$M = \text{Softmax}\left(\frac{Q_{\text{EAM}} K_{\text{EAM}}^T}{\sqrt{d}}\right), K_{\text{EAM}} = V_{\text{EAM}} = \hat{T}_r \quad (10)$$

where  $d$  is the dimensionality of the key and query. The output  $F_{\text{EAM}}$  of EAM is given by  $F_{\text{EAM}} = M \cdot V_{\text{EAM}}$ . Finally, EAM modulated  $F_{\text{cross}}$  in the form of a residual connection with a coefficient  $\omega$ :  $F_{\text{cross}} + \omega \cdot F_{\text{EAM}}$ .

## 4. Benchmark

Many works employ existing datasets to construct self-supervised training, such as by data augmentation [62] or




Figure 3. Dataset Preparation. (a) we collect the base data: **Scene** and **Object**. (b) We create the paired data with Blender.

video data [8]. However, self-supervised is insufficient for learning physical laws [59]. We leverage the powerful 3D computer graphics suite Blender [21] to produce the necessary paired training data. With industrial renderer Cycles, Blender can capture physical effects such as lighting, shadows, and reflections [15]. Specifically, we construct each pair of data by two triplets: image triplet  $(X_r, X_s, X_{gt})$  and corresponding object mask triplet  $(M_r, M_s, M_{gt})$ .

**Base data collection.** As shown in Fig. 3 (a), we collect base data crafted by professional modelers from public rendering asset websites. For **Object** assets, we use classes in Open Images V7 [2] as keywords to enhance diversity while excluding categories unsuitable as foreground. The **Scene** assets are sourced from six categories: indoor, outdoor, e-commerce, technology, ancient buildings, and abstract.

**Triplet data creation.** As depicted in Fig. 3 (b), starting from  $X_{gt}$  composed of object and scene, we replace the foreground at the same coordinate positions with random objects from **Object** set, resulting in  $X_s$ . For the object in  $X_{gt}$ , we replace the background from **Scene** set while maintaining the same camera viewpoint, making  $X_r$ . Images with inharmonious foreground and background combinations are filtered out. Additionally, we render an image with only the object, making the scene transparent. By identifying non-transparent areas, we obtain object masks. Finally, we obtain 5,000 pairs of data, which constitute Replace-5K.

## 5. Experiments

### 5.1. Implementation Details

Following [8], Stable Diffusion V2.1 [49] is the base architecture. Intrinsic image decomposition and normal estimation use the off-the-shelf method [6] and [11].  $\alpha$  and  $\beta$  are set to 1.0 and 0.1. We set the initial learning rate as  $1e^{-5}$ . We train the model at a batch size of 8 for 40 epochs.

Table 1. Quantitative comparisons on Replace-5K. The standard reconstruction metrics and perceptual similarity metrics are applied. The consistency of subjects is evaluated via CLIP-I and DINO-I. PBE\*, ObjectStitch\*, and AnyDoor\* are fine-tuned on our Replace-5K.

Method	PSNR↑	CLIP↑	DINO↑	LPIPS↓	FID↓	CLIP-I↑	DINO-I↑
IP-Adapter [65]	18.473	0.892	0.755	0.247	7.188	0.788	0.553
PBE* [62]	17.036	0.730	0.788	0.298	15.803	0.757	0.526
ObjectStitch* [56]	18.032	0.887	0.762	0.295	8.708	0.773	0.554
Anydoor* [8]	19.473	0.923	0.872	0.222	7.132	0.804	0.638
Remove [74]-Insert [19]	21.490	0.934	0.892	0.217	6.241	0.814	0.682
Ours	<b>22.583</b>	<b>0.945</b>	<b>0.921</b>	<b>0.174</b>	<b>5.109</b>	<b>0.827</b>	<b>0.688</b>




Figure 4. Qualitative comparison on data of DreamBooth and DreamEdit. We achieve consistent effect editing (shadows, reflections), precise control for the position and size of targets. The blue masks in source images indicate the target position and size.

## 5.2. Datasets

In Replace-5K, 4500 pairs are for training, and 500 are for testing. When testing, we obtain masks by SAM [30]. To validate the effectiveness on real-world images, we construct additional test data by datasets of DreamBooth [50] and DreamEdit [35]. Specifically, for an image with a subject, we randomly select another image with a different subject as the reference. The target mask is aligned according to the center of the source object.

## 5.3. Evaluation Settings

**Compared methods.** 1) One-stage methods includes IP-Adapter [65], PBE [62], ObjectStitch [56], AnyDoor [8]. We fine-tune PBE, ObjectStitch, and AnyDoor on Replace-5K. 2) We also compare with a two-stage approach involving removal followed by insertion, *i.e.* Remove-Insert. Object removal is the sota inpainting method PowerPaint [74], and insertion uses the sota harmonization method [19].

**Quantitative metrics.** For Replace-5K, we apply the reconstruction metric PSNR and perceptual similarity metrics CLIP [48], DINO [44], LPIPS [70]. The generative metric FID [22] is also used. To evaluate the consistency between subjects, we calculate the similarity CLIP-I and DINO-I between the edited region and the reference by CLIP and DINO. For DreamBooth and DreamEdit datasets, we evalu-

Table 2. Quantitative comparison on datasets of DreamBooth and DreamEdit. CILP-I, DINO-I, and FID are used to evaluate.

Method	Dreambooth			Dreamedit		
	CLIP-I↑	DINO-I↑	FID↓	CLIP-I↑	DINO-I↑	FID↓
IP-Adapter [65]	0.795	0.581	25.550	0.797	0.581	23.988
PBE* [62]	0.756	0.543	32.000	0.769	0.552	30.977
ObjectStitch* [56]	0.787	0.598	25.043	0.782	0.600	28.210
Anydoor* [8]	0.811	0.666	23.626	0.825	0.686	25.607
Remove[74]-Insert[19]	0.840	0.736	23.607	0.849	0.748	24.191
Ours	<b>0.845</b>	<b>0.740</b>	<b>22.919</b>	<b>0.851</b>	<b>0.749</b>	<b>23.383</b>

ate CLIP-I, DINO-I, and FID, where the target distribution of FID is computed from all images in the original dataset.

## 5.4. Comparison with the Existing Methods

We quantitatively and qualitatively compare with 5 methods on Replace-5K and data of DreamBooth and DreamEdit.

**Quantitative comparison.** The results of Replace-5K are shown in Tab. 1. Overall, we achieve best performance across 7 evaluation metrics. For the pixel-level metric PSNR, PS-Diffusion shows an improvement of 1.093. In perceptual similarity metrics, PS-Diffusion demonstrates significant improvements due to the incorporation of effects of contextual interactions, which enhance photorealism. Specifically, we improve 0.011 and 0.029 on CLIP and DINO. LPIPS and FID are decreased by 0.043 and 1.132. In addition, due to the precise control of appearance and




Figure 5. Qualitative ablation on the Replace-5K dataset. In ++BECB\*, the features of FECB and the original branch are directly weighted.

size, we enhance subject consistency between the target and reference. CLIP-I and DINO-I are improved by 0.013 and 0.006. Moreover, we perform best on data of DreamBooth and DreamEdit, in Tab. 2. Although Remove-Insert sometimes approaches PS-diffusion on CLIP-I and DINO-I due to harmonization keeping the foreground unchanged, the risk of copy-paste artifacts results in higher FID.

**Qualitative comparison.** The results are illustrated in Fig. 4. First, our method not only achieves realistic contextual interactions, but also keeps highly consistent appearances of subjects. For one-stage methods [8, 56, 62], while recognizing effects after fine-tuning, they often lack consistency and plausibility, and only maintain subjects’ semantic similarity. For example, AnyDoor\* generates the wrong shadow direction in the first row and produces shadows that should not appear in the second row. Moreover, we precisely control the object’s location and size. In the first row of Fig. 4, the size of the can is improperly influenced by the size of the clock in one-stage methods, whereas PS-Diffusion distinguishes areas that need reconstruction as background. For the two-stage approach, Remove-Insert is limited to the masked area, failing to generate effects outside masks. In addition, unsatisfactory removal in the first and third rows degrade the visual quality. In contrast, PS-Diffusion successfully edits shadows and reflections on the background while completely removing the source objects.

## 5.5. Ablation Results

**Effectiveness of the proposed components.** As illustrated in Tab. 3 and Fig. 5, we conduct an ablation analysis of each module on Replace-5K. PSNR, CLIP, DINO, LPIPS, and FID are measurements. We have the following observations: 1) In disentangled control signals, illumination-dependent properties in FECB guide the editing of lighting-related effects. BECB corrects the effect area outside the mask. Hence, they bring improvements in quantitative and

Table 3. Ablation on Replace-5K. When EAM is not applied, the features of BECB and the original branch are directly weighted.

FECB	BECB	EAM	PSNR↑	CLIP↑	DINO↑	LPIPS↓	FID↓
			21.480	0.935	0.905	0.190	6.250
✓			21.799	0.940	0.913	0.185	5.751
✓	✓		22.010	0.942	0.917	0.181	5.513
✓	✓	✓	<b>22.583</b>	<b>0.945</b>	<b>0.921</b>	<b>0.174</b>	<b>5.109</b>

qualitative results. 2) Compared to directly weighting two ControlNet branches, EAM attains better performance. As shown in the second to last column, direct weighting confuses the learning of interaction and subject. This leads to excessive alteration of original pixels in the background (first and second line) or abnormal changes in the object’s appearance (second line). As shown in the last column, EAM alleviates this issue by decoupling attention of editing objects and contextual interactions, thereby improving performance. 3) By integrating all modules, the model achieves the best performance, demonstrating the complementarity of disentangled control and attention.

**Visualization of the effect map.** To verify the effectiveness of BECB, we visualize the effect map. As shown in the effect map of Fig. 6, when objects are edited, potential areas where effects projected onto the background, such as shadows and reflections, are activated. In addition, we present the ablation results with and without the rough mask estimated from the source image in the LAB color space. As shown in the last two columns, due to the close relationship between the effects of the same scene on different objects, the rough mask improves the accuracy of the effect maps.

**Effect attention coefficient.** We conduct ablation experiments on the effectiveness of the hyperparameter  $\omega$  in EAM. The quantitative and qualitative visualization results are presented in Fig. 7. The incorporation of EAM leads to a significant enhancement in the PSNR, proving its effectiveness. However, in the qualitative outcomes, it is observed that an excessively high  $\omega$  gradually disrupts the original




Figure 6. Visualization of the effect map in BECB. We also show the ablation results without  $M_e^{rough}$  estimated in LAB color space.




Figure 7. Ablation experiments of  $\omega$  in EAM. As  $\omega$  increases, the region of the effect (orange dotted frame) is implausibly deepened. PSNR is evaluated on the entire test set.

pixels of the background. This not only reduces the physical plausibility but also leads to inconsistent effects (the reflection of the object on the desktop in the source image is soft). Hence, PSNR gradually decreases. In PS-Diffusion,  $\omega$  is set to 0.1 to achieve the best performance.

## 5.6. More Applications

The high controllability of PS-Diffusion enables precise image editing based on user-provided masks. Importantly, the adherence to physical laws enhances photorealism. Hence, PS-Diffusion can be extended to various precise and photorealistic object-level editing applications: object insertion, object movement, object scaling, and object rotation.

To be specific, for object insertion, the original object mask is identical to the target mask. In the object movement and scaling, the reference subject is the target in the source image. During object scaling, the target mask is scaled to the specified size. For object rotation, the object in the reference image is rotated utilizing some object rotation meth-



Figure 8. The application of PS-Diffusion in other object-level editing tasks, i.e. object insertion, scaling, movement, and rotation.

ods [25, 64]. The results are depicted in Fig. 8, demonstrating the effectiveness and scalability of PS-Diffusion.

## 5.7. Limitations and Future Work

To discuss limitations, we evaluate hard samples under complex lighting or specular reflections. FID on these samples is suboptimal compared to the entire dataset. Specifically, the FID of 8.781 on hard samples is higher than 5.109 on the entire dataset. Moreover, we find failure cases under strong specularity or extreme lighting. For example, the edited objects in the mirror are ambiguous or unedited. It is challenging as it involves geometry and the estimation of material and lighting. Without priors, generative models struggle to recognize reflective or diffuse objects. In the future, we will explore a more exquisite lighting estimator in FECB and the priors of diffuse and normal maps in BECB.

## 6. Conclusion

In this paper, we propose PS-Diffusion for photorealistic subject-driven image editing. We first disentangle the control signals of contextual interactions based on their affecting regions. To be specific, for those within the mask, we condition the diffusion model with effects estimated by intrinsic image decomposition. An additional background effect control branch identifies regions of effect outside the mask. Moreover, the effect attention module in the denoising U-Net is introduced to separate the learning of effects of contextual interactions and subject features. Extensive experiments demonstrate the effectiveness and scalability.

## 7. Acknowledgments

This work was supported by the Natural Science Foundation of Tianjin, China (No.24JCZXJC00040), Shenzhen Science and Technology Program (No. JCYJ20240813114229039), the National Natural Science Foundation of China (No. 623B2056, 624B2072), the Fundamental Research Funds for the Central Universities, the Supercomputing Center of Nankai University (NKSC).

## References

- [1] Omri Avrahami, Dani Lischinski, and Ohad Fried. Blended diffusion for text-driven editing of natural images. In *CVPR*, 2022. 2
- [2] Rodrigo Benenson and Vittorio Ferrari. From colouring-in to pointillism: revisiting semantic segmentation supervision. *arXiv preprint arXiv:2210.14142*, 2022. 5
- [3] Andrew Brock. Large scale gan training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018. 2
- [4] Tim Brooks, Aleksander Holynski, and Alexei A Efros. Instructpix2pix: Learning to follow image editing instructions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 18392–18402, 2023. 2
- [5] Tingfeng Cao, Junsheng Kong, Xue Zhao, Wenqing Yao, Junwei Ding, Jinhui Zhu, and Jian Dong Zhang. Product2img: Prompt-free e-commerce product background generation with diffusion model and self-improved lmm. In *ACM MM*, 2024. 2
- [6] Chris Careaga and Yağız Aksoy. Intrinsic image decomposition via ordinal shading. *ACM Transactions on Graphics*, 43(1):1–24, 2023. 3, 4, 5
- [7] Chris Careaga, S Mahdi H Miangoleh, and Yağız Aksoy. Intrinsic harmonization for illumination-aware compositing. *arXiv preprint arXiv:2312.03698*, 2023. 4
- [8] Xi Chen, Lianghua Huang, Yu Liu, Yujun Shen, Deli Zhao, and Hengshuang Zhao. Anydoor: Zero-shot object-level image customization. In *CVPR*, 2024. 2, 3, 4, 5, 6, 7
- [9] Guillaume Couairon, Jakob Verbeek, Holger Schwenk, and Matthieu Cord. Diffedit: Diffusion-based semantic image editing with mask guidance. *arXiv preprint arXiv:2210.11427*, 2022. 2
- [10] Ádám Tibor Czapp, Mátyás Jani, Bálint Domián, and Balázs Hidasi. Dynamic product image generation and recommendation at scale for personalized e-commerce. In *Proceedings of the 18th ACM Conference on Recommender Systems*, 2024. 2
- [11] Ainaz Eftekhari, Alexander Sax, Jitendra Malik, and Amir Zamir. Omnidata: A scalable pipeline for making multi-task mid-level vision datasets from 3d scans. In *CVPR*, 2021. 5
- [12] Dave Epstein, Allan Jabri, Ben Poole, Alexei Efros, and Aleksander Holynski. Diffusion self-guidance for controllable image generation. *Advances in Neural Information Processing Systems*, 36:16222–16239, 2023. 2
- [13] Rinon Gal, Yuval Alaluf, Yuval Atzmon, Or Patashnik, Amit H Bermano, Gal Chechik, and Daniel Cohen-Or. An image is worth one word: Personalizing text-to-image generation using textual inversion. *arXiv preprint arXiv:2208.01618*, 2022. 2
- [14] Golnaz Ghiasi, Yin Cui, Aravind Srinivas, Rui Qian, Tsung-Yi Lin, Ekin D Cubuk, Quoc V Le, and Barret Zoph. Simple copy-paste is a strong data augmentation method for instance segmentation. In *CVPR*, 2021. 2
- [15] Klaus Greff, Francois Fleuret, Lucas Beyer, Carl Doersch, Yilun Du, Daniel Duckworth, David J Fleet, Dan Gnanaprasam, Florian Golemo, Charles Herrmann, et al. Kubric: A scalable dataset generator. In *CVPR*, 2022. 5
- [16] Maciej Gryka, Michael Terry, and Gabriel J Brostow. Learning to remove soft shadows. *ACM Transactions on Graphics (TOG)*, 34(5):1–15, 2015. 5
- [17] Jing Gu, Nanxuan Zhao, Wei Xiong, Qing Liu, Zhifei Zhang, He Zhang, Jianming Zhang, HyunJoon Jung, Yilin Wang, and Xin Eric Wang. Swapanything: Enabling arbitrary object swapping in personalized visual editing. *arXiv preprint arXiv:2404.05717*, 2024. 2
- [18] Yuming Gu, Hongyi Xu, You Xie, Guoxian Song, Yichun Shi, Di Chang, Jing Yang, and Linjie Luo. Diffportrait3d: Controllable diffusion for zero-shot portrait view synthesis. In *CVPR*, 2024. 2
- [19] Julian Jorge Andrade Guerreiro, Mitsuru Nakazawa, and Björn Stenger. Pct-net: Full resolution image harmonization using pixel-wise color transformations. In *CVPR*, 2023. 2, 6
- [20] Amir Hertz, Ron Mokady, Jay Tenenbaum, Kfir Aberman, Yael Pritch, and Daniel Cohen-Or. Prompt-to-prompt image editing with cross attention control. *arXiv preprint arXiv:2208.01626*, 2022. 2
- [21] Roland Hess. *The essential Blender: guide to 3D creation with the open source suite Blender*. No Starch Press, 2007. 5
- [22] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *NeurIPS*, 2017. 6
- [23] Hexiang Hu, Kelvin CK Chan, Yu-Chuan Su, Wenhui Chen, Yandong Li, Kihyuk Sohn, Yang Zhao, Xue Ben, Boqing Gong, William Cohen, et al. Instruct-imagen: Image generation with multi-modal instruction. In *CVPR*, 2024. 2
- [24] Miao Hua, Jiawei Liu, Fei Ding, Wei Liu, Jie Wu, and Qian He. Dreamtuner: Single image is enough for subject-driven generation. *arXiv preprint arXiv:2312.13691*, 2023. 2
- [25] Zehuan Huang, Hao Wen, Junting Dong, Yaohui Wang, Yangguang Li, Xinyuan Chen, Yan-Pei Cao, Ding Liang, Yu Qiao, Bo Dai, et al. Epidiff: Enhancing multi-view synthesis via localized epipolar-constrained diffusion. In *CVPR*, 2024. 8
- [26] Inbar Huberman-Spiegelglas, Vladimir Kulikov, and Tomer Michaeli. An edit friendly ddpm noise space: Inversion and manipulations. In *CVPR*, 2024. 2
- [27] Xuan Ju, Xian Liu, Xintao Wang, Yuxuan Bian, Ying Shan, and Qiang Xu. Brushnet: A plug-and-play image inpainting model with decomposed dual-branch diffusion. *arXiv preprint arXiv:2403.06976*, 2024. 2, 3
- [28] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *CVPR*, 2019. 2
- [29] Jeongho Kim, Guojung Gu, Minho Park, Sunghyun Park, and Jaegul Choo. Stableviton: Learning semantic correspondence with latent diffusion model for virtual try-on. In *CVPR*, 2024. 2
- [30] Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer White-

- head, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *CVPR*, 2023. 6
- [31] Peter Kocsis, Julien Philip, Kalyan Sunkavalli, Matthias Nießner, and Yannick Hold-Geoffroy. Lightit: Illumination modeling and control for diffusion models. In *CVPR*, 2024. 3
- [32] Atharva Kulkarni, Ester Tsai, Karina Chen, Zelong Wang, Alex Cloninger, and Rayan Saab. From pixels to pictures: Understanding the internal representation of latent diffusion models. 5
- [33] Nupur Kumari, Bingliang Zhang, Richard Zhang, Eli Shechtman, and Jun-Yan Zhu. Multi-concept customization of text-to-image diffusion. In *CVPR*, 2023. 2
- [34] Chenghua Li, Bo Yang, Zhiqi Wu, Gao Chen, Yihan Yu, and Shengxiao Zhou. Shadow removal based on diffusion segmentation and super-resolution models. In *CVPR*, 2024. 3
- [35] Tianle Li, Max Ku, Cong Wei, and Wenhui Chen. Dreamedit: Subject-driven image editing. *arXiv preprint arXiv:2306.12624*, 2023. 2, 3, 6
- [36] Zonglin Li, Xiaoqian Lv, Wei Yu, Qinglin Liu, Jingbo Lin, and Shengping Zhang. Face shape transfer via semantic warping. *Visual Intelligence*, 2(1):26, 2024. 2
- [37] Chang Liu, Xiangtai Li, and Henghui Ding. Referring image editing: Object-level image editing via referring expressions. In *CVPR*, 2024. 2
- [38] Qingyang Liu, Junqi You, Jianting Wang, Xinhao Tao, Bo Zhang, and Li Niu. Shadow generation for composite image using diffusion model. In *CVPR*, 2024. 3
- [39] Ling Lo, Cheng Yu Yeo, Hong-Han Shuai, and Wen-Huang Cheng. Distraction is all you need: Memory-efficient image immunization against diffusion-based image editing. In *CVPR*, 2024. 3
- [40] Andreas Lugmayr, Martin Danelljan, Andres Romero, Fisher Yu, Radu Timofte, and Luc Van Gool. Repaint: Inpainting using denoising diffusion probabilistic models. In *CVPR*, 2022. 2
- [41] Oscar Michel, Anand Bhattad, Eli VanderBilt, Ranjay Krishna, Aniruddha Kembhavi, and Tanmay Gupta. Object 3dit: Language-guided 3d-aware image editing. In *NeurIPS*, 2024. 2
- [42] Saritha Murali and VK Govindan. Shadow detection and removal from a single image using lab color space. *Cybernetics and information technologies*, 13(1):95–103, 2013. 4
- [43] Shuliang Ning, Duomin Wang, Yipeng Qin, Zirong Jin, Baoyuan Wang, and Xiaoguang Han. Picture: Photorealistic virtual try-on from unconstrained designs. In *CVPR*, 2024. 2
- [44] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. Dinov2: Learning robust visual features without supervision. *arXiv preprint arXiv:2304.07193*, 2023. 4, 6
- [45] Yulin Pan, Chaojie Mao, Zeyinzi Jiang, Zhen Han, and Jingfeng Zhang. Locate, assign, refine: Taming customized image inpainting with text-subject guidance. *arXiv preprint arXiv:2403.19534*, 2024. 2, 4
- [46] William Peebles and Saining Xie. Scalable diffusion models with transformers. In *ICCV*, 2023. 2
- [47] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. *arXiv preprint arXiv:2307.01952*, 2023. 2
- [48] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *ICML*, 2021. 6
- [49] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *CVPR*, 2022. 2, 4, 5
- [50] Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. In *CVPR*, 2023. 2, 3, 6
- [51] Rahul Sajnani, Jeroen Vanbaar, Jie Min, Kapil Katyal, and Srinath Sridhar. Geodiffuser: Geometry-based image editing with diffusion models. *arXiv preprint arXiv:2404.14403*, 2024. 2
- [52] Yichen Sheng, Jianming Zhang, and Bedrich Benes. Ssn: Soft shadow network for image compositing. In *CVPR*, 2021. 2
- [53] Yichen Sheng, Yifan Liu, Jianming Zhang, Wei Yin, A Cengiz Oztireli, He Zhang, Zhe Lin, Eli Shechtman, and Bedrich Benes. Controllable shadow generation using pixel height maps. In *ECCV*, 2022.
- [54] Yichen Sheng, Jianming Zhang, Julien Philip, Yannick Hold-Geoffroy, Xin Sun, He Zhang, Lu Ling, and Bedrich Benes. Pixht-lab: Pixel height based light effect generation for image compositing. In *CVPR*, 2023. 2
- [55] Xue Song, Jiequan Cui, Hanwang Zhang, Jingjing Chen, Richang Hong, and Yu-Gang Jiang. Doubly abductive counterfactual inference for text-based image editing. In *CVPR*, 2024. 2
- [56] Yizhi Song, Zhifei Zhang, Zhe Lin, Scott Cohen, Brian Price, Jianming Zhang, Soo Ye Kim, and Daniel Aliaga. Objectstitch: Generative object compositing. *arXiv preprint arXiv:2212.00932*, 2022. 3, 6, 7
- [57] Gemma Canet Tarrés, Zhe Lin, Zhifei Zhang, Jianming Zhang, Yizhi Song, Dan Ruta, Andrew Gilbert, John Collomosse, and Soo Ye Kim. Thinking outside the bbox: Unconstrained generative object compositing. *arXiv preprint arXiv:2409.04559*, 2024. 2, 3, 4
- [58] Yi-Hsuan Tsai, Xiaohui Shen, Zhe Lin, Kalyan Sunkavalli, Xin Lu, and Ming-Hsuan Yang. Deep image harmonization. In *CVPR*, 2017. 2
- [59] Daniel Winter, Matan Cohen, Shlomi Fruchter, Yael Pritch, Alex Rav-Acha, and Yedid Hoshen. Objectdrop: Bootstrapping counterfactuals for photorealistic object removal and insertion. *arXiv preprint arXiv:2403.18818*, 2024. 2, 3, 4, 5
- [60] Weihao Xia, Yulun Zhang, Yujiu Yang, Jing-Hao Xue, Bolei Zhou, and Ming-Hsuan Yang. Gan inversion: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 45(3):3121–3138, 2022. 2

- [61] Yichao Yan, Zanwei Zhou, Zi Wang, Jingnan Gao, and Xiaokang Yang. Dialoguenerf: Towards realistic avatar face-to-face conversation video generation. *Visual Intelligence*, 2(1):24, 2024. 2
- [62] Binxin Yang, Shuyang Gu, Bo Zhang, Ting Zhang, Xuejin Chen, Xiaoyan Sun, Dong Chen, and Fang Wen. Paint by example: Exemplar-based image editing with diffusion models. In *CVPR*, 2023. 2, 3, 5, 6, 7
- [63] Shiyuan Yang, Xiaodong Chen, and Jing Liao. Uni-paint: A unified framework for multimodal image inpainting with pretrained diffusion model. In *ACM MM*, 2023. 2
- [64] Yunhan Yang, Yukun Huang, Xiaoyang Wu, Yuan-Chen Guo, Song-Hai Zhang, Hengshuang Zhao, Tong He, and Xihui Liu. Dreamcomposer: Controllable 3d object generation via multi-view conditions. In *CVPR*, 2024. 8
- [65] Hu Ye, Jun Zhang, Sibo Liu, Xiao Han, and Wei Yang. Ip-adapter: Text compatible image prompt adapter for text-to-image diffusion models. *arXiv preprint arXiv:2308.06721*, 2023. 2, 6
- [66] Jiraphon Yenphraphai, Xichen Pan, Sainan Liu, Daniele Panozzo, and Saining Xie. Image sculpting: Precise object editing with 3d geometry control. In *CVPR*, 2024. 2
- [67] Guanqi Zhan, Chuanxia Zheng, Weidi Xie, and Andrew Zisserman. What does stable diffusion know about the 3d scene? *arXiv preprint arXiv:2310.06836*, 2023. 5
- [68] Bo Zhang, Yuxuan Duan, Jun Lan, Yan Hong, Huijia Zhu, Weiqiang Wang, and Li Niu. Controlcom: Controllable image composition using diffusion model. *arXiv preprint arXiv:2308.10040*, 2023. 2
- [69] Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. In *ICCV*, 2023. 3
- [70] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *CVPR*, 2018. 6
- [71] Xin Zhang, Jiaxian Guo, Paul Yoo, Yutaka Matsuo, and Yusuke Iwasawa. Paste and harmonize via denoising: Subject-driven image editing with frozen pre-trained diffusion model. In *ICASSP*, 2024. 3
- [72] Jun-Yan Zhu, Philipp Krähenbühl, Eli Shechtman, and Alexei A Efros. Generative visual manipulation on the natural image manifold. In *ECCV*, 2016. 2
- [73] Luyang Zhu, Yingwei Li, Nan Liu, Hao Peng, Dawei Yang, and Ira Kemelmacher-Shlizerman. M&m vto: Multi-garment virtual try-on and editing. In *CVPR*, 2024. 2
- [74] Junhao Zhuang, Yanhong Zeng, Wenran Liu, Chun Yuan, and Kai Chen. A task is worth one word: Learning with task prompts for high-quality versatile image inpainting. *arXiv preprint arXiv:2312.03594*, 2023. 2, 6