

National University of Computer and Emerging Sciences

Fast School of Computing

Spring 2024

CS-1004 OOP (CS)

Time = 10 minutes

Quiz # 1 [10 marks]

Name: _____

Roll No: _____

For the Given codes, provide the output/error:

<pre>#include <iostream> using namespace std; int main() { int arr[] = {14, 51, 36, 47}, *ptr=arr + 2; int *p = ptr; (*p)++; ++(*(--ptr)); cout << p[0]<<" " <<ptr[0]; return 0; }</pre>	Output/error:
<pre>#include <iostream> using namespace std; int main() { int a = 32, *ptr = &a; char ch = 129, &cho = ch; cho += a; *ptr -= ch + 20; cout << *((char*)ptr) << ", " << (int)ch << endl; return 0; }</pre>	Output/error:
What will be the prototype of a function that takes a pointer to integer array, a triple pointer to constant integer and address of a constant pointer to integer and returns a reference pointer to float.	
Prototype:	
<pre>#include <iostream>; using namespace std; int main() { int x=4,*xx=&x,**xxx=&xx; cout<<sizeof(x)<<","<<sizeof(xx)<<","<<sizeof(xxx); return 0; }</pre>	output/error:
<pre>#include <iostream> using namespace std; void fun(int (*p)[2][3]){ cout<<p[-1][0][1]<<endl;} int main() { int ary[12] = {1, 2, 3, 4,5,6,7,8,9,10,11,12}; fun((int(*)[2][3])((int(*)[2])ary+1) + 1); }</pre>	Output/error: