

Data Structures

16. Applications of Stacks

Algebraic Expressions

- An algebraic expression is combination of **operands** and **operators**
- Operand is the **object of** mathematical **operation**
 - Quantity that is operated on
- Operator is a symbol that **signifies a mathematical** or logical **operation**

Infix, Postfix and Prefix Expressions

- **Infix**
 - Expressions in which operands surround the operators
 - Example: $A+B-C$
- **Postfix** or Reverse Polish Notation (RPN)
 - Operators comes after the operands
 - Example: $AB+C-$
- **Prefix** or Polish Notation
 - Operator comes before the operands
 - Example: $-+ABC$

Example: Conversion From Infix to Postfix (1)

- Infix: $A+B*C$
- Conversion: Applying the rules of precedence
 - $A+(B*C)$ Parentheses for emphasis
 - $A+(BC*)$ Convert the multiplication
 - $ABC*+$ Postfix Form

Example: Conversion From Infix to Postfix (2)

- Infix: $((A+B)*C - (D-E)) \$ (F+G)$
- Conversion: Applying the rules of precedence
 - $((AB+)*C - (DE-)) \$ (FG+)$
 - $((AB+C*) - (DE-)) \$ (FG+)$
 - $(AB+C*DE--) \$ (FG+)$
 - $AB+C*DE--FG+\$$
- Exercise: Convert the following to Postfix
 - $(A + B) * (C - D)$
 - $A / B * C - D + E / F / (G + H)$

Infix, Postfix and Prefix Expressions – Examples

Infix	PostFix	Prefix
$A+B$	$AB+$	$+AB$
$(A+B)*(C + D)$	$AB+CD+*$	$*+AB+CD$
$A-B/(C*D^E)$	?	?

Why Do We Need Prefix and Postfix? (1)

- Normally, algebraic expressions are written using Infix notation
 - For example: $(3 + 4) \times 5 - 6$
- Appearance may be misleading, Infix notations are not as simple as they seem
 - Operator precedence
 - Associativity property
- **Operators have precedence:** Parentheses are often required
 - $(3 + 4) \times 5 - 6 = 29$
 - $3 + 4 \times 5 - 6 = 17$
 - $3 + 4 \times (5 - 6) = -1$
 - $(3 + 4) \times (5 - 6) = -7$

Why Do We Need Prefix and Postfix? (2)

- **Infix** Expression is **Hard To Parse** and difficult to evaluate
- Postfix and prefix do not rely on operator priority and are easier to parse
 - No ambiguity and no brackets are required
- Many compilers first translate algebraic expressions into some form of postfix notation
 - Afterwards translate this postfix expression into machine code

<code>MOVE.L #\$2A, D1</code>	<code>; Load 42 into Register D1</code>
<code>MOVE.L #\$100, D2</code>	<code>; Load 256 into Register D2</code>
<code>ADD D2, D1</code>	<code>; Add D2 into D1</code>

Conversion of Infix Expression to Postfix

- Precedence function
 - `prcd(op1, op2)`
 - `op1` and `op2` are characters representing operators
- Precedence function returns TRUE
 - If `op1` has precedence over `op2`
 - Otherwise function returns FALSE
- Examples
 - `prcd('*', '+')` returns TRUE
 - `prcd('+', '+')` returns TRUE
 - `prcd('+', '*')` returns FALSE

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	
+	A	+

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	
+	A	+
B	AB	+

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	
+	A	+
B	AB	+
*	AB	+ *

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	
+	A	+
B	AB	+
*	AB	+ *
C	ABC	+ *

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	
+	A	+
B	AB	+
*	AB	+ *
C	ABC	+ *
	ABC*	+

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A+B*C

symb	Postfix string	opstk
A	A	
+	A	+
B	AB	+
*	AB	+ *
C	ABC	+ *
	ABC*	+
	ABC*+	

Algorithm to Convert Infix to Postfix – Practice

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A*B+C

symb	Postfix string	opstk

Algorithm to Convert Infix to Postfix – Practice

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        push(opstk, symb);
    } /* end else */
} /* end while */
/* output any remaining operators */
while (!empty(opstk) ) {
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: A*B+C

symb	Postfix string	opstk
A	A	
*	A	*
B	AB	*
+	AB*	+
C	AB*C	+
	AB*C+	

What If Expression Contains Parenthesis?

- Precedence function `prcd(op1, op2)` has to be modified
 - `prcd( '(', op ) = FALSE` For any operator `op`
 - `prcd( op, '(' ) = FALSE` For any operator `op` other than `)`
 - `prcd( op, ') ' ) = TRUE` For any operator `op` other than `(`
 - `prcd( ') ' ,op ) = undef` For any operator `op` (an error)

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(
+	A	(+

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(
+	A	(+
B	AB	(+

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(
+	A	(+
B	AB	(+
)	AB+	

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(
+	A	(+
B	AB	(+
)	AB+	
*	AB+	*

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(
+	A	(+
B	AB	(+
)	AB+	
*	AB+	*
C	AB+C	*

Algorithm to Convert Infix to Postfix

```
opstk = the empty stack;
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        add symb to the postfix string
    else {
        while (!empty(opstk) && prcd(stacktop(opstk), symb) ) {
            topsymb = pop(opstk);
            add topsymb to the postfix string;
        } /* end while */
        if ( empty(opstk)|| symb != '(' )
            push(opstk, symb);
        else //pop the parenthesis & discard it
            topsymb = pop(opstk);
    } /* end else */
} /* end while */
while (!empty(opstk) ) { // remaining ops
    topsymb = pop(opstk);
    add topsymb to the postfix string;
} /* end while */
```

Example: (A+B)*C

symb	Postfix string	opstk
(		(
A	A	(
+	A	(+
B	AB	(+
)	AB+	
*	AB+	*
C	AB+C	*
	AB+C*	

Conversion of Infix Expression to Postfix – Rules

- Token is an operand
 - Append it to the end of postfix string
- Token is a left parenthesis
 - Push it on the opstk
- Token is a right parenthesis
 - Pop the opstk until the corresponding left parenthesis is removed
 - Append each operator to the end of the postfix string
- Token is an operator, $*$, $/$, $+$, or $-$
 - Push it on the opstk
 - First remove any operators already on the opstk that have higher or equal precedence and append them to the postfix string
- Input expression has been completely processed
 - Any operators still on the opstk can be removed and appended to the end of the postfix string

Conversion of Infix Expression to Postfix – Practice

- Example: $((A - (B + C)) * D) \text{ \$ } (E + F)$

symb	Postfix string	opstk

Conversion of Infix Expression to Postfix – Practice

- Example: $((A - (B + C)) * D) \$ (E + F)$

symp	Postfix string	opstk
(		(
(		((
A	A	((
-	A	((-
(	A	((-(
B	AB	((-(
+	AB	((-(+
C	ABC	((-(+
)	ABC+	((-
)	ABC+-	(
*	ABC+-	(*
D	ABC+-D	(*
)	ABC+-D*	
\$	ABC+-D*	\$
(	ABC+-D*	\$(
E	ABC+-D*E	\$(
+	ABC+-D*E	\$(+
F	ABC+-D*EF	\$(+
)	ABC+-D*EF+	\$
	ABC+-D*EF+\$	

Conversion To Prefix Expression (1)

- An Infix to Prefix Conversion Algorithm
 - Reverse the infix string
 - Adjust parenthesis, i.e., make every '(' as ')' and every ')' as '('
 - Perform infix to postfix algorithm on reversed string
 - Reverse the output postfix expression to get the prefix expression
- Example: $(A + B) * (B - C)$
 - $)C - B(*)B + A(\rightarrow (C - B) * (B + A)$ Reverse infix string
 - $C B - B A + *$ Perform infix to postfix conversion
 - $* + A B - B C$ Reverse postfix to get prefix expression

Conversion To Prefix Expression (2)

- Example: $(A+B^C)*D+E^5$

– $5^E+D^*)C^B+A(\rightarrow 5^E+D^*(C^B+A)$ Reverse infix string

– $5E^DCB^A+*+$ Perform infix to postfix conversion

– $+*+A^BCD^E5$ Reverse postfix to get prefix expression

Evaluating a Postfix Expression

```
opndstk = the empty stack
/* scan the input string reading one element */
/* at a time into symb */
while (not end of input) {
    symb = next input character;
    if (symb is an operand)
        push(opndstk, symb)
    else {
        /* symb is an operator */
        opnd2 = pop(opndstk);
        opnd1 = pop(opndstk);
        value = result of applying symb
                to opnd1 and opnd2;
        push(opndstk, value);
    } /* end else */
} /* end while */
return (pop(opndstk));
```

Each operator in postfix string refers to the previous two operands in the string.

Evaluating a Postfix Expression

opndstk = the empty stack

/* scan the input string reading one element */

/* at a time into symb */

```
while (not end of input) {  
    symb = next input character;  
    if (symb is an operand)  
        push(opndstk, symb)  
    else {  
        /* symb is an operator */  
        opnd2 = pop(opndstk);  
        opnd1 = pop(opndstk);  
        value = result of applying symb  
                to opnd1 and opnd2;  
        push(opndstk, value);  
    } /* end else */  
} /* end while */  
return (pop(opndstk));
```

Example Postfix Expression:
6 2 3 + - 3 8 2 / + * 2 \$ 3 +

symb	opnd1	opnd2	value	opndstk
6				6
2				6,2
3				6,2,3
+	2	3	5	6,5
-	6	5	1	1
3	6	5	1	1,3
8	6	5	1	1,3,8
2	6	5	1	1,3,8,2
/	8	2	4	1,3,4
+	3	4	7	1,7
*	1	7	7	7
2	1	7	7	7,2
\$	7	2	49	49
3	7	2	49	49,3
+	49	3	52	52

Any Question So Far?



Quiz 02 – Sec A

- Calculate postfix and prefix notations of the following expressions
- $A - B / (C * D^E)$
- $A / B * C - D + E / F / (G + H)$

Quiz 02 – Sec C

- Calculate postfix and prefix notations of the following expressions
- $B - A / (C * D^E)$
- $A / B * D - C + E / F / (G + H)$

Quiz 02 – Sec B

- Calculate postfix and prefix notations of the following expressions
- $B - A / (C * E^D)$
- $A / B * D - C + E / F / (K + H)$