

Run all these codes in separate .cpp files

```
//////////////////////////////////First.cpp//////////////////////////////////
```

```
// This is single line comment
```

```
/*
```

```
    This is multiple line  
    comment
```

```
*/
```

```
#include<iostream>
```

```
using namespace std;
```

```
int main (void)
```

```
{
```

```
    cout<<"hello Every one"<<endl;  
    cout<<"C++ is a powerful Langaue"<<endl;
```

```
    return 0;
```

```
}
```

```
//////////////////////////////////Second.cpp//////////////////////////////////
```

```
#include <iostream>
```

```
#include <typeinfo>
```

```
using namespace std; int
```

```
main ()
```

```
{
```

```
    int a;
```

```
    a=10;
```

```
    cout<<a<<endl;  
    cout<<sizeof(a)<<endl;    cout<<  
    typeid(a).name()<<endl;
```

```
    return 0;
```

```
}
```

```
//////////////////////////////////address.cpp//////////////////////////////////
```

```
#include <iostream>
```

```
#include <typeinfo>
```

```
using namespace std;
```

```
int main ()
```

```
{
```

```
    int a; // Declaration of Variable a as integer
```

```
a=10; //Assigning value as 10
```

```
    bool b;
```

```
b=true;
```

```
    cout<<"Print value of integer a "<<a<<endl;
```

```
cout<<"Print Size of integer a "<<sizeof(a)<<endl;    cout<<
```

```
"Print Type of integer a "<<typeid(a).name()<<endl;    cout<<
```

```
"Print Address of integer a "<<&a<<endl;
```

```
    cout<<"Print value of Boolean b "<<b<<endl;    cout<<"Print
```

```
Size of Boolean b "<<sizeof(b)<<endl;    cout<<"Print Type of
```

```
Boolean b "<< typeid(b).name()<<endl;    cout<< "Print
```

```
Address of Boolean b "<<&b<<endl;
```

```
    return 0;
```

```
}
```

```
////////////////////////////////////iomanip////////////////////////////////////
```

```
#include<iostream>
```

```
#include<iomanip>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
    int n=15;
```

```
float y = 18.346;
```

```
cout<<setw(n)<<y<<endl;
```

```
cout<<setw(50)<<setfill('-')<<"\n";
```

```
cout << setw(15) <<"Hello" << "PF" << endl;
```

```
cout << setw(7) <<setfill('_')<<"Hello" <<setw(10)<<left<<setfill('*')<<"PF"<<"\n";
```

```
return 0;
```

```
}
```

```
////////////////////////////////Size.cpp////////////////////////////////
```

```
#include <iostream>
```

```
#include <typeinfo>
```

```
using namespace std;
```

```
int main ()
```

```
{
```

```
    int a=10;
```

```
        short b=10;
```

```
long c=10;    float
```

```
d=10.0;      double
```

```
e=10.0;      long double
```

```
f=10.0;      bool
```

```
g=true;
```

```
    cout<<"value of Integer a is "<<a<<" size is "<<sizeof(a)<<endl;
cout<<"value of short c is "<<b<<" size is "<<sizeof(b)<<endl;  cout<<"value of long
c is "<<c<<" size is "<<sizeof(c)<<endl; cout<<"size of integer Literal is 10 and its
size is "<<sizeof(10)<<endl;
```

```
    cout<<"value of Float d is "<<d<<" size is "<<sizeof(d)<<endl;
cout<<"value of double e is "<<e<<" size is "<<sizeof(e)<<endl;
cout<<"value of long double f is "<<f<<" size is "<<sizeof(f)<<endl;
cout<<"size of Float Literal is 10.0 and its size is "<<sizeof(10.0)<<endl;
```

```
    cout<<"value of boolean g is "<<g<<" size is "<<sizeof(g)<<endl;
cout<<"size of boolean literal \"true\" is "<<sizeof(true)<<endl;
```

```
    cout<<"size of literal character \'A\' is "<<sizeof(\'A\')<<endl;
cout<<"size of string literal \"A\" is "<<sizeof("A")<<endl; return 0;
}
```

```
////////////////////////////////Input.cpp////////////////////////////////
```

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
int main ()
```

```
{
```

```
    int value1,  
    value2;
```

```
    float fvalue;
```

```
    char ch;
```

```
    string str1;
```

```
    cout<<"Enter two integer values";  
    cin>>value1>>value2;
```

```
    cout<<"Enter a Float values";  
    cin>>fvalue;
```

```
    cout<<"Enter a character values";  
    cin>>ch;
```

```
    cout<<"Enter a String";  
    cin>>str1;
```

```
    cout<<value1<<endl  
<<value2<<endl  
    <<fvalue<<endl  
    <<ch<<endl<<str1<<endl  
    ;
```

```
    return 0;  
}
```

```
////////////////////////////////Check_it.cpp////////////////////////////////
```

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
int main ()
```

```
{
```

```
    cout<<5+2;
    cout<<5-2;    cout<<5*2;
    cout<<5/2;    cout<<5%2;
    cout<<5.0+2;  cout<<5.0-2;
    cout<<5.0*2;  cout<<5.0/2;
    //cout<<5.0%2;//remainder or modulus operator cannot be used with double value
```

```
    return 0;
```

```
}
```

```
////////////////////////////////Expression.cpp////////////////////////////////
```

```
#include <iostream>
```

```
using namespace std;
```

```
int main ()
```

```
{
```

```
    // Constants    const double PI
    = 3.14159;      const double
    DIAMETER = 10.0;
```

```
    // Variable to hold the circumference    double
    circumference;
```

```
    // Calculate the circumference.
    circumference = PI * DIAMETER;
```

////////////////////////////////////

1. `payAmount`: This variable will hold the amount of pay the employee earns each pay period. Initialize the variable with 1700.0.
2. `payPeriods`: This variable will hold the number of pay periods in a year. Initialize the variable with 26.
3. `annualPay`: This variable will hold the employee's total annual pay, which will be calculated.

The program should calculate the employee's total annual pay by multiplying the employee's pay amount by the number of pay periods in a year, and store the result in the annualPay variable. Display the total annual pay on the screen.

7. Distance per Tank of Gas

A car with a 20-gallon gas tank averages 21.5 miles per gallon when driven in town and 26.8 miles per gallon when driven on the highway. Write a program that calculates and displays the distance the car can travel on one tank of gas when driven in town and when driven on the highway.

Hint: The following formula can be used to calculate the distance:

Distance = Number of Gallons * Average Miles per Gallon

8. Land Calculation

One acre of land is equivalent to 43,560 square feet. Write a program that calculates the number of acres in a tract of land with 389,767 square feet.

9. Circuit Board Price

An electronics company sells circuit boards at a 40 percent profit. Write a program that will calculate the selling price of a circuit board that costs \$12.67. Display the result on the screen.

10. Personal Information

Write a program that displays the following pieces of information, each on a separate line:

Your name

Your address, with city, state, and ZIP code

Your telephone number

Your college major

Use only a single cout statement to display all of this information.