

Quiz 7

Total Marks: 10

Bonus Question Marks: 10

Q1. Which of the following is illegal?

- a. `int *ip;`
- b. `string s, *sp = 0;`
- c. `int i; double* dp = &i;`
- d. `int *pi = 0;`

Q2. What will happen in the following C++ code snippet?

```
int a = 100, b = 200;  
int *p = &a, *q = &b ;  
p = q
```

- a. b is assigned to a
- b. p now points to b
- c. a is assigned to b
- d. q now points to a

Q3. What will be the output of the following C++ code?

```
#include <iostream>  
using namespace std;  
int main() {  
    char arr[20];  
    int i;  
    for (i = 0; i < 10; i++)  
        *(arr + i) = 65 + i;  
    *(arr + i) = '\\0';  
    cout << arr;  
  
    return 0;  
}
```

- a. ABCDEFGHIJ
- b. AAAAAAAAAA
- c. JJJJJJJ
- d. AAAAAAJJJ
- e.

Q4: What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;
int main() {

    int arr[] = {4, 5, 6, 7};
    int *p = (arr + 1);
    cout << *arr + 9;

    return 0;
}
```

- a. 12
- b. 15
- c. 13
- d. error

Q5: What will be the output of the following C++ code?

```
#include <iostream>
using namespace std;
int main() {

    int *p=new int [5];
    for(int i=0; i<5; i++)
    {
        cin>> *(p+i); //assume input values are 30 5 10 15 20
    }

    for(int i=0; i<5; i++)
    {
        cout << p[i];
    }

}
```

Output:

[BONUS QUESTION]

Write the output of the following recursive program.

```
#include <iostream>
using namespace std;
int fun(int x) {
    if (x==1 || x==0) {
        return x;
    }
    else {
        return fun (x-1) + fun(x-2);
    }
}
int main()
{
    int n=3;
    cout<<fun(n);
}
```

Output:

Programming Fundamentals – Quiz-5

Section _____

1st December 2022

Q1: [5+5 Marks] Write the output of the following C++ code:

```
int main() {  
    int a[5] = {30,50,90,100,40};  
    int *aptr = a;  
    (*aptr)--;  
    aptr++;  
    cout<<a[0]<<" "<<a[1]<<" "<<*aptr<<endl;  
    return 0;  
}
```

Output:

```
void F1(int* x, int* y)  
{  
    *x = (*x) - (*y);  
}  
  
int F2(int y)  
{  
    y += 50;  
    return y;  
}  
  
int main( )  
{  
    int a=200, b=20;  
    F1(&a,&b);  
    cout<<a<<" , ";  
    cout<<F2(b)<<" , ";  
    cout<<b<<endl;  
    return 0;  
}
```

Output: