

Dry Run of C++ Code (and may be Find Errors)

Please dry run the following code snippets or programs

<pre>int main(){ int a = 0; int b = 0; int c = 5; while(c > 0){ cout << "Please enter a number: "; cin >> a; if(c == 0){ b = a; } if(a > b){ b = a; } c = c - 1; } cout << c; return 0; }</pre>	
<pre>int main() { int myNum =10; int yourNum =30; if (yourNum%myNum ==3) { yourNum =3; myNum =1; } else if (yourNum%myNum==2) { yourNum=2; myNum=2; } else{ yourNum =1; myNum =3; } cout<<myNum<<" "<<yourNum<<endl; return 0; }</pre>	
<pre>int main(){ int year; cout<<"ENter the year "; cin>>year; if(year%4==0) cout<<"It is leap year "; else cout<<"not leap year "; return 0; }</pre>	

<pre> int main(){ int a1,a2,a3; cout<<"Enter the angles "; cin>>a1>>a2>>a3; if((a1+a2+a3)==180) cout<<"valid triangle "; else cout<<"not valid triangle "; return 0; } </pre>	
<pre> int number=7; int trial = 2; /* now check if that number is a perfect square or not and print the output accordingly. Make sure to show the value the user have entered e.g. 25 is perfect square */ if(number < 4) { cout << number << " is NOT a perfect square"; } else { while(trial * trial < number) { trial++; } if(trial * trial == number) { cout << number << " a perfect square"; } else { cout << number << " is NOT a perfect square"; } } } </pre>	
<pre> int main(){ float cf=1.99,cc,m,em,eb,b; cout<<"Enter the total minutes talked "; cin>>m; if(m>3){ em=m-3; eb=em*.45; cc=cf+2.00+e b; cout<<"The call charges are "<<cc<<endl; } else { cc=cf+2.00; cout<<"The call charges are "<<cc<<endl; } return 0; } </pre>	

<pre> int main(){ int bouns; cout<<"Enter bouns "; cin>>bouns; if(bouns<=1000) cout<<"Eat hotdogs "; else if(bouns<10000) cout<<"Go to disney world "; else cout<<"Go to hawaii "; return 0; } </pre>	
<pre> int main(){ float height,weight,bmi; cout<<"Enter weight "; cin>>weight; cout<<"Enter height "; cin>>height; bmi=(weight/(height*height)); if(bmi<18.5) cout<<"under weight "; else if(bmi<25) cout<<"normal "; else if(bmi<30) cout<<"overweight "; else cout<<"obese "; return 0; } </pre>	
<pre> int main(){ int obill,dis,nbill; cout<<"Enter orignal bill of customer "; cin>>obill; if(obill>=1000) { dis=obill*.05; nbill=obill-dis; cout<<"The net bill of the customer is "<<nbill; } else{ nbill=obill; cout<<"The net bill of customer is "<<nbill; } } </pre>	

<pre> int main () { int sp,cp; cout<<"Enter selling price"; cin>>sp; cout<<"Enter cost price"; cin>>cp; if(sp>cp) cout<<" endl<<"Profit"; else cout<<" endl<<"Loss"; return 0; } </pre>	
<pre> int main (){ float marks; cout<<"Enter marks from 1100"; cin>>marks; marks= marks*100/1100; if(marks>50) cout<<endl<<"PASS"; else cout<<endl<<"FAIL"; return 0; } </pre>	
<pre> int main() { int a,b,c; cout<<"The side of a is:"<<endl; cin>>a; cout<<"The side of b is:"<<endl; cin>>b; cout<<"The side of c is:"<<endl; cin>>c; if(a+b>c) cout<<"The triangle is valid"<<endl; else if(a+c>b) cout<<"The triangle is valid"<<endl; else if(c+b>a) cout<<"The triangle is Valid"<<endl; else cout<<"TRiangle is invalid"<<endl; return 0; } </pre>	

```

int main(){
    int num;
    cout<<"Enter a number";
    cin>>num; if(num%2==0)
    {
        if(num%4==0)
            if(num%8==0)
                cout<<"\Number belong to A
catagory";
    }
    else{
        if(num%3==0)
            if(num%9==0)
                cout<<"\Number belong to B
catagory";
    }
    return 0;
}

```

```

int main()
{
    int a,b,c;
    cout<<"Please enter your 3 numbers :";
    cin>>a;
    cin>>b;
    cin>>c;
    cout<<"Middle number is "<<endl;
    if(a>b) {
        if(b<c) {
            if (c>a)
                cout<<a;
            else
                cout<<c;
        }
        else
            cout<<b;
    }
    else {
        if(b<c)
            {cout<<b;}
        else {
            if(c>a)
                cout<<c;
            else
                cout<<a;
        }
    }
    return 0;
}

```

<pre> int x = 0 , y = 0, a = 0, b = 7; while(a < b) { x = a + b; y = b - a; if(a % 2 == 0 && b % 2 == 0) { a++; } else if(a % 2 == 1 && b % 2 == 1) { b--; } else { a++; b--; } } </pre>	
Find the appropriate values of variables start, end, and jump on loop's third iteration. <pre> int main() { int start = 3, end = 60, jump = 2, counter=1; while (start < end) { counter++; cout <<number<< " "; start = start + jump; jump = jump*counter; } return 0; } </pre>	Required values on 3rd iterations:
<pre> int main() { int start = 60, end = 3, jump = 2, counter=2; while (start > end) { counter++; cout <<number<< " "; start = start - jump; jump = jump*counter; } return 0; } </pre>	Required values on 3rd iterations: