RetailPulse: Agentic AI for Retail Store Intelligence

Project Team

Moiz Ansari 23I-0523
Ruhab Ahmad 23I-0559
Saqib Atif 23I-0769

Session 2023-2027

Supervised by

Mr. Shehreyar Rashid



FAST School of Computing

National University of Computer and Emerging Sciences
Islamabad, Pakistan

October, 2026

Students' Submission

We certify that this report is submitted as the FYP-1 mid-report for the project titled *RetailPulse: Agentic AI for Retail Store Intelligence*.

Student 1: Moiz Ansari (23I-0523) Signature: _____

Student 2: Saqib Atif (23I-0769) Signature: _____

Student 3: Ruhab Ahmad (23I-0559) Signature: _____

Anti-Plagiarism Statement

The students certify that this report is their own work and that all sources used in preparing the report have been appropriately acknowledged and referenced.

Authors' Declaration

We declare that the work documented in this report represents the work completed by the project team up to the FYP-1 mid-report stage. Contributions, tools, external components, and relevant sources are disclosed where applicable.

Abstract

Most retail CCTV footage is used only for theft prevention, and small and mid-sized retailers cannot afford specialised analytics hardware or analysts to find out whether customers are being attended to. This report presents *RetailPulse*, a CPU-only system that aims to turn existing CCTV footage into customer-engagement, staff-performance and store-traffic analytics without new cameras. The target business architecture comprises Customer Behavior Agent, Employee Activity Agent, Interaction Agent, Employee Task Assignment Agent, Insight Narration Agent, Query Agent and Orchestrator. Detection/classification/tracking and pose/proximity are shared tools; current implementations and proposed integrations are distinguished in the requirements register. A Next.js dashboard serves managers and employees, with FastAPI and SQLite for application records.

The project follows an iterative approach. At the FYP-1 mid-report stage the web application with role-aware access and an interaction pipeline are implemented. The pipeline combines a trained employee/customer YOLO detector (mAP50 0.969 on 455 held-out images), BoT-SORT tracking, body-height proximity with a pass-by filter, and a YOLO pose judge that evaluates facing evidence while retaining unverified proximity fallbacks. On the one labelled clip the judge raises interaction precision from 0.50 to 1.00; the pipeline ran on all 11 local clips and 44 unit tests pass. A floor-distance prototype was built and then descoped because the moving-camera footage supported almost no floor projections. Dashboard vision metrics still use prototype data. FYP-2 will integrate the vision agents with the dashboard, evaluate them on labelled clips from the supplied videos, and harden the system for the final demonstration.

Acknowledgments

The project team thanks its supervisor, Mr. Shehreyar Rashid, for his guidance, feedback, and support throughout the project. We also thank the faculty of the FAST School of Computing, Islamabad Campus, and our families and peers for their encouragement.

Executive Summary

Problem and motivation. Retail stores record CCTV footage mainly for security, yet managers lack a low-cost way to know whether customers are attended to, how staff time is distributed, and which zones receive traffic. Commercial retail-analytics products typically depend on dedicated sensors or hardware and on subscription costs, which puts them out of reach of many small and mid-sized retailers.

Proposed solution. RetailPulse reuses existing CCTV infrastructure. The target business architecture comprises Customer Behavior Agent, Employee Activity Agent, Interaction Agent, Employee Task Assignment Agent, Insight Narration Agent, Query Agent and Orchestrator. Detection/classification/tracking and pose/proximity are shared tools; current implementations and proposed integrations are distinguished in the requirements register. The target analytics include footfall, approach time, interaction duration, idle time, unattended-customer flags, dwell time, paths, and heatmaps. Results are presented on a web dashboard for managers and a focused workspace for employees.

Scope. The committed scope is a single-store prototype with three cameras, running on CPU only. Multi-store scaling, full cross-camera re-identification, and shelf-level interaction detection are deliberately deferred to future work after a feasibility triage against hardware, timeline, and dependency constraints.

Current status. The Next.js frontend covers the manager, employee, and shared pages. FastAPI and SQLite support account, camera, alert and operational-task workflows. Role-aware access is enforced with signed HttpOnly session cookies and an internal secret header. A local interaction pipeline combines a trained employee/customer detector, BoT-SORT tracking, body-height proximity with a pass-by filter, and a YOLO pose judge that evaluates facing evidence while retaining unverified proximity fallbacks. A metric floor-distance prototype was built and then descoped because the moving-camera footage supported almost no floor projections. The dashboard vision metrics still partly use prototype or demo data.

Validation, risks, and remaining work. The detector reaches mAP50 0.969 on 455 held-out images. On the one labelled clip the pose judge raises interaction precision from 0.50 to 1.00, and the pipeline completes all 11 local clips; 44 interaction unit tests pass. Accuracy is measured on one labelled clip only. The main risks are CPU-only inference speed,

role-classification accuracy, depth ambiguity in a single image, and identity switches on moving footage. The remaining work covers vision-agent integration, evaluation on store footage, hardening, and the final demonstration.

Contents

Students' Submission i

Anti-Plagiarism Statement ii

Authors' Declaration iii

Abstract iv

Acknowledgments v

Executive Summary vi

List of Abbreviations xv

1 Introduction and Project Vision 1

1.1 Project Overview . . . 1
1.2 Problem Statement . . . 1
1.3 Problem Context and Motivation . . . 1
1.4 Project Vision . . . 2
1.5 Project Objectives . . . 2
1.6 Project Scope . . . 3
1.7 Project Modules . . . 4
1.8 Stakeholders and User Classes . . . 5
1.9 Success Criteria . . . 5
1.10 Constraints and Assumptions . . . 6
1.11 Ethical, Legal and DEI Considerations . . . 6

2 Research and Existing Solutions 7

2.1 Research Method / Approach . . . 7
2.2 Existing Solutions / Products . . . 7
2.3 Comparison of Existing Solutions . . . 8
2.4 Limitations and Gaps . . . 8

2.5 Proposed Solution . . . 9
2.6 Complex Computing Problem . . . 9
2.7 Technical Challenges . . . 9
2.8 Research Findings and Design Decisions . . . 10
2.8.1 Interaction Detection Findings . . . 10
2.8.2 Geometric Basis of the Descoped Floor-Distance Prototype . . . 10

3 Proposal Feedback and Iteration Plan **12**
3.1 Proposal Feedback Summary . . . 12
3.2 Proposal Action Register . . . 12
3.3 Iteration Strategy . . . 13
3.4 Iteration 1 Plan . . . 14
3.5 Iteration 2 Plan . . . 14
3.6 Work Breakdown and Responsibilities . . . 15
3.7 Progress Against Plan . . . 16
3.8 Delays, Deviations and Recovery Plan . . . 16

4 Software Requirements **17**
4.1 Scope and Identifier Policy . . . 17
4.2 User Interactions / Use Cases . . . 17
4.3 Use Case Diagrams . . . 18
4.4 Detailed Use Cases . . . 22
4.5 Functional Requirements . . . 40
4.6 Non-Functional Requirements and Solutions . . . 42
4.7 Acceptance Criteria . . . 44
4.8 Requirements Traceability . . . 46

5 System Design **49**
5.1 System Architecture . . . 49
5.1.1 YOLO Model Responsibilities . . . 51
5.2 Architectural Components . . . 52
5.3 Interfaces and Dependencies . . . 53
5.4 Architecture Decisions and Rationale . . . 54
5.5 Design Evolution . . . 54
5.6 Domain Model . . . 56
5.7 Class Diagram . . . 58
5.8 Deployment Diagram . . . 60
5.9 Data Design . . . 61
5.9.1 Direct Assignment and Identity Boundaries . . . 62
5.9.2 Floor Calibration and Runtime Records (Descoped Floor Prototype) 63
5.10 Process / Behavior Design . . . 63

5.10.1 Floor-Distance Quality-Gating Process (Descoped Prototype) . . 65
5.11 System Sequence Diagrams . . . 66
5.11.1 UC-01: Analyze a video . . . 67
5.11.2 UC-02: Obtain entrance footfall . . . 68
5.11.3 UC-04: Analyze customer service interactions . . . 69
5.11.4 UC-07: Analyze spatial customer activity . . . 70
5.11.5 UC-10: Access a role-specific account . . . 71
5.11.6 UC-11: Monitor camera observations . . . 72
5.11.7 UC-12: Review manager analytics . . . 73
5.11.8 UC-13: Review personal workspace . . . 74
5.11.9 UC-17: Generate an insight report . . . 75
5.11.10 UC-18: Manage operational alerts . . . 76
5.11.11 UC-19: Inspect system status . . . 77
5.11.12 UC-20: Manage personal settings . . . 78
5.11.13 UC-29: Configure store operations . . . 79
5.11.14 UC-34: Evaluate analytical outputs . . . 80
5.11.15 UC-35: Assess staff availability and coverage . . . 81
5.11.16 UC-36: Receive and update an aisle assignment . . . 82
5.11.17 UC-37: Ask an analytics question . . . 83

6 Iteration 1: Design and Implementation 84
6.1 Iteration Objectives . . . 84
6.2 Selected Use Cases / Features . . . 84
6.3 Design . . . 84
6.4 Implementation . . . 84
6.4.1 Two-Model Vision Approach . . . 85
6.4.2 Interaction Pipeline and Pose Judge . . . 85
6.4.3 Floor-Distance Command-Line Prototype (Descoped) . . . 86
6.5 Completed Features / Module . . . 87
6.6 Technical Implementation Details . . . 87
6.6.1 Calibration Configuration and Coordinate Conventions (Floor Prototype) . . . 88
6.6.2 Reproducible Execution (Floor Prototype) . . . 88
6.7 Algorithms and Technical Decisions . . . 89
6.7.1 Person Floor-Position Approximation (Floor Prototype) . . . 89
6.7.2 Homography-Based Projection and Distance (Floor Prototype) . . 89
6.7.3 Camera Alignment and Measurement Reliability (Floor Prototype) 90
6.8 Tools, Frameworks and Technologies . . . 91
6.9 Demonstration Evidence . . . 91
6.9.1 Interaction Pipeline Output . . . 91

6.9.2 Floor-Distance Demonstration (Descoped Prototype) 91
6.10 Target Architecture and Iteration Boundary 97
6.11 Iteration Outcome 97

7 Testing and Early Validation **98**
7.1 Testing Strategy 98
7.2 Test Levels and Techniques 98
7.3 Test Cases 99
7.4 Proposed Capability Scenarios 100
7.5 Test Results 101
7.5.1 Floor-Distance Software and Integration Results 102
7.5.2 Interaction Pipeline and Benchmark Results 103
7.6 Acceptance Testing / Validation 104
7.7 Edge and Failure Cases 105
7.8 Defects and Corrective Actions 105
7.9 Current Validation Status 106

8 Project Management and Development Evidence **107**
8.1 Work Completed 107
8.2 Work Remaining 107
8.3 Individual Responsibilities 108
8.4 Contribution of Each Team Member 108
8.5 Repository and Version Control Evidence 108
8.6 Milestones and Commit Evidence 108
8.7 Tools and Tool-Assisted Development 109
8.8 External Components and Dependencies 110
8.9 Risks and Mitigation 112
8.10 Security and Privacy Considerations 112
8.11 Current Limitations 113

9 Remaining FYP Plan **114**
9.1 Remaining Scope 114
9.2 Remaining Modules and Features 114
9.3 Remaining Iterations 115
9.4 Implementation Plan 115
9.5 Testing and Validation Plan 115
9.6 Deployment Plan 115
9.7 Tentative Timeline 116
9.8 Expected Final Deliverables 116

10 Conclusion **117**

A Proposal Action Register **118**
A.1 Comments / Recommended Modifications 118
A.2 Response Priorities 118

B Requirement Consolidation and Historical Register **119**
B.1 Identifier Policy and Old-to-New Mapping 119
B.2 Retired Floor-Prototype Functional Requirements 121
B.3 Historical UC-14: Calibrate and inspect floor distance (descoped) 122
B.4 Historical NFR-11 and Its Solution 122

C Detailed Test Cases **124**
C.1 Floor-Distance Test Procedures (Descoped Prototype) 125
C.2 Current Capability Mapping of Recorded Checks 126
C.3 Planned Capability and Quality Scenarios 127
C.4 Current-Branch Reproduction 130

D Repository and Contribution Evidence **131**
D.1 Authorship and Milestone Evidence 132
D.2 Floor-Distance Implementation Evidence 132

E Additional Design Diagrams **133**
E.1 Historical Floor Calibration Schema and Failure States 133
E.2 Interaction Verdict States 134

F Meeting and Progress Evidence **135**

List of Figures

4.1 Current use cases for the Operator / project team 19
4.2 Current Employee use cases and shared Manager account/settings access . 19
4.3 Current Manager use cases: observation and analytics 20
4.4 Current Manager use cases: operational review, configuration and questions 21

5.1 RetailPulse target system architecture: seven agent/coordinator responsibilities with shared perception tools 50
5.2 RetailPulse conceptual domain model and target business relationships . . 57
5.3 RetailPulse class design with implemented records and proposed agent/coordinator components 59

5.4 RetailPulse deployment view: client, application host, local persistence and external services . . . 60
5.5 Interaction detection process in the interaction CLI . . . 64
5.6 Floor-distance localization and quality-checking pipeline . . . 65
5.7 System sequence diagram for UC-01: Analyze a video . . . 67
5.8 System sequence diagram for UC-02: Obtain entrance footfall . . . 68
5.9 System sequence diagram for UC-04: Analyze customer service interactions 69
5.10 System sequence diagram for UC-07: Analyze spatial customer activity . 70
5.11 System sequence diagram for UC-10: Access a role-specific account . . . 71
5.12 System sequence diagram for UC-11: Monitor camera observations . . . 72
5.13 System sequence diagram for UC-12: Review manager analytics . . . 73
5.14 System sequence diagram for UC-13: Review personal workspace . . . 74
5.15 System sequence diagram for UC-17: Generate an insight report . . . 75
5.16 System sequence diagram for UC-18: Manage operational alerts . . . 76
5.17 System sequence diagram for UC-19: Inspect system status . . . 77
5.18 System sequence diagram for UC-20: Manage personal settings . . . 78
5.19 System sequence diagram for UC-29: Configure store operations . . . 79
5.20 System sequence diagram for UC-34: Evaluate analytical outputs . . . 80
5.21 System sequence diagram for UC-35: Assess staff availability and coverage 81
5.22 System sequence diagram for UC-36: Receive and update an aisle assignment . . . 82
5.23 System sequence diagram for UC-37: Ask an analytics question . . . 83

6.1 Manager dashboard with demonstration values . . . 92
6.2 Customer information view with demonstration values . . . 92
6.3 Employee information view with demonstration values . . . 93
6.4 Employee workspace after authenticated employee login . . . 93
6.5 Interaction pipeline output. Left (IMG_8880, 30 s): employee and customer facing each other during a handover; the pose judge confirms the interaction. Right (IMG_8829, 8 s): employee and customer close together but walking away side by side; the pose judge rejects the candidate and the indicator stays OFF. . . . 94
6.6 Trained role detections and track IDs with box-bottom proxies; uncalibrated preview . . . 94
6.7 Provisional A–B–D–C calibration and floor grid based on estimated dimensions . . . 95
6.8 Approximate top-down person-position proxies in the reference snapshot 96

E.1 Selected implemented SQLite relationships; arrows point from referencing tables to referenced tables . . . 133

List of Tables

1.1 Major modules and responsibilities 4
1.2 Stakeholders and user classes 5

2.1 Qualitative comparison using official product descriptions, checked 20 October 2026 8
2.2 Findings and the decisions they influenced 11

3.1 Proposal action register 12
3.2 Evaluation milestones 13
3.3 Work distribution 15
3.4 Planned versus actual progress at mid-report 16

4.1 One primary use case for each active functional requirement 18
4.2 UC-01: Analyze a video 22
4.3 UC-02: Obtain entrance footfall 23
4.4 UC-04: Analyze customer service interactions 24
4.5 UC-07: Analyze spatial customer activity 25
4.6 UC-10: Access a role-specific account 26
4.7 UC-11: Monitor camera observations 27
4.8 UC-12: Review manager analytics 28
4.9 UC-13: Review personal workspace 29
4.10 UC-17: Generate an insight report 30
4.11 UC-18: Manage operational alerts 31
4.12 UC-19: Inspect system status 32
4.13 UC-20: Manage personal settings 33
4.14 UC-29: Configure store operations 34
4.15 UC-34: Evaluate analytical outputs 35
4.16 UC-35: Assess staff availability and coverage 36
4.17 UC-36: Receive and update an aisle assignment 37
4.18 UC-37: Ask an analytics question 39
4.19 Active functional requirements: consolidated 17-capability baseline . . . 40
4.20 Active NFR concerns, practical approaches and verification status 42
4.21 Acceptance checks for all active functional capabilities 44
4.22 Current capability traceability and honest evidence status 47

5.1 Architectural components 52
5.2 Architecture decisions 54
5.3 Implemented persistence and exported record structure 61

6.1 Features completed in Iteration 1 87
6.2 Technology stack 91

7.1 Test case summary 99
7.2 Test execution status at mid-report 101
7.3 Executed floor-distance checks and temporary-video coverage 102
7.4 Detector KPIs on the recording-level held-out split (455 images) 103
7.5 Interaction accuracy on the labelled clip (IMG_8829) 103
7.6 Interaction CLI on 11 local clips (scored every 10th frame, tracked every 3rd) 104

8.1 Responsibilities 108
8.2 Generative-AI tool use and verification 109
8.3 External components 110
8.4 Dependency licence review from installed metadata and upstream notices, 20 October 2026 110
8.5 Risk register 112

9.1 Planned FYP-2 iterations 115
9.2 Tentative FYP-2 timeline (to be confirmed with the supervisor) 116

B.1 Functional requirement consolidation and retirement mapping 119
B.2 Historical floor-prototype requirement register 121
B.3 Historical NFR solution; excluded from active NFRs 122
B.4 Floor-distance requirements traceability (descoped prototype) 123

C.1 Detailed test cases: application and interaction 124
C.2 Detailed test cases: descoped floor-distance prototype 125
C.3 Additional acceptance scenarios; none executed for this documentation revision 127

D.1 Selected commits verified from local Git history 131

F.1 Meeting and progress record 135

List of Abbreviations

AI	Artificial Intelligence
API	Application Programming Interface
CCTV	Closed-Circuit Television
CLI	Command-Line Interface
CPU	Central Processing Unit
CV	Computer Vision
DEI	Diversity, Equity and Inclusion
FR	Functional Requirement
FYP	Final Year Project
GPU	Graphics Processing Unit
HSV	Hue, Saturation, Value (colour space)
JSON	JavaScript Object Notation
JSONL	JSON Lines (one JSON record per line)
KPI	Key Performance Indicator
mAP	Mean Average Precision
MAE	Mean Absolute Error
MVP	Minimum Viable Product
ORB	Oriented FAST and Rotated BRIEF
RANSAC	Random Sample Consensus
NFR	Non-Functional Requirement
PDF	Portable Document Format
Re-ID	Re-Identification
UI	User Interface
YOLO	You Only Look Once (object detector family)

Chapter 1

Introduction and Project Vision

1.1 Project Overview

RetailPulse (*Agentic AI for Retail Store Intelligence*) is a system that converts existing in-store CCTV footage into live customer-engagement analytics, staff-performance insight, and store-traffic intelligence, without new cameras or specialised hardware. It is a Final Year Project that explores practical use of multi-agent AI systems in a resource-constrained retail environment.

The system assumes a three-camera setup: one entrance-facing camera and two floor-facing cameras. Their feeds pass through a pipeline of specialised agents. The mid-iteration work covers person/role detection, interaction detection (proximity plus a pose-based facing check) and the web interfaces for managers and employees.

1.2 Problem Statement

Retail store owners and managers have no low-cost way to know whether customers on the floor are being attended to, how staff time is split between active engagement and idle time, and which areas of the store attract traffic and which are ignored. Existing CCTV footage is recorded but rarely reviewed, and dedicated retail-analytics hardware or analysts are often financially out of reach for small and mid-sized retailers.

1.3 Problem Context and Motivation

CCTV systems in most stores exist for theft prevention. The footage holds operational information (queues, approaches, dwell, idle time) that goes unused. Managers who want

this information must watch footage manually, which does not scale, or buy specialised products.

The motivation is threefold. First, service quality: customers who are not approached in a reasonable time may leave without buying. Second, fair and informed staffing: managers need visibility into floor coverage and idle periods. Third, accessibility: a CPU-only solution built on existing cameras lowers the barrier for retailers that cannot invest in new capital equipment. The project also emphasises privacy-conscious design, using non-biometric classification and presenting results as decision support rather than automated employee evaluation. Service expectations vary by store: frequent approaches may be inappropriate in luxury or low-contact settings. Unattended-customer flags and staff-activity findings must therefore be interpreted against a store-defined service policy, not a universal expectation that staff should constantly approach shoppers.

1.4 Project Vision

RetailPulse aims to make store intelligence accessible to retailers of any size by reusing the cameras they already own, running on commodity CPUs, and giving managers clear and trustworthy answers to everyday operational questions.

The project uses two distinct YOLO model roles: a YOLO pose model supplies body-keypoint evidence for interaction analysis, while a standard YOLO object-detection model with customer/employee classes supplies person boxes and role labels. The latter is a detector trained on role classes, not a separate image-classification-only network. Interaction events are derived from pose/proximity and temporal rules rather than treating a pose prediction itself as an interaction label.

1.5 Project Objectives

The project has the following measurable objectives.

O1. Count footfall from the entrance camera and report it per time interval.

O2. Detect people in each processed frame and classify them as staff or customer without biometric identification; the interaction pipeline uses a trained employee/customer detector, while earlier demo paths use zone and appearance heuristics.

O3. Compute engagement metrics: approach time, interaction duration, idle time, unattended-customer flags, and contextual staff availability.

O4. Track movement to produce paths, zone dwell times, heatmaps, and crowd density.

O5. Provide a manager dashboard, an employee workspace, alerts, and exportable reports with narrative summaries.

O6. Detect employee–customer interactions by combining body-height-normalised proximity, duration and a pose-based facing check, and reject close pass-bys.

O7. Run the vision pipeline on CPU only.

1.6 Project Scope

In scope:

- Footfall counting (entrance camera).
- Staff/customer classification (non-biometric, including the trained role detector used by the interaction pipeline).
- Engagement analytics: approach time, interaction duration, idle detection, potentially unattended events, and contextual staff availability.
- Trajectory and spatial behaviour: path tracking, zone dwell time, heatmaps, and crowd density.
- Interaction detection from body-height-normalised proximity, duration, a pass-by filter and a pose-based facing check, run through local command-line tools.
- Web application with manager and employee roles.
- Direct employee aisle assignment using identified accounts/rosters, with task status reporting; source coverage and observation linkage remain integration work.
- Authorized analytics questions and grounded report narration as target capabilities, with implementation status distinguished in Chapter 4.

Explicitly out of scope (see Chapter 9 and Future Work):

- Cross-camera identity association; this is reserved for the next phase.
- Metric floor-plane distance estimation; a calibrated-homography prototype was built and then descoped (Section 6.4.3).
- Full three-dimensional reconstruction and per-pixel depth-map generation.

- Shelf-level product interaction detection.
- Long-term store layout and promotional-effectiveness evaluation.
- Multi-store scaling and real-time processing as the primary deliverable (the current pipeline is offline/batch).

These exclusions were chosen after a feasibility triage against hardware (no dedicated GPU), timeline, and dependency constraints.

1.7 Project Modules

Table 1.1: Major modules and responsibilities

Target component / tools	Responsibility
Customer Behavior Agent	Customer movement, entrance footfall, dwell, zone demand and hot/gray zones.
Employee Activity Agent	Contextual staff activity, availability, assignments and zone coverage.
Interaction Agent	Possible staff/customer interactions, supported approach time and potentially unattended customers.
Employee Task Assignment Agent	Select an eligible identified employee and issue the aisle instruction directly.
Insight Narration Agent	Explain verified metrics and decisions in natural language; target LLM-assisted service.
Query Agent	Answer authorized manager analytics questions using evidence-retrieval tools; target LLM-assisted service.
Orchestrator	Coordinate processing, shared state and workflows using application coordination code.
Shared tools	Detection, classification, tracking, identity association, zone geometry and pose/proximity.
Web Application	Manager analytics, own employee workspace, configuration and task updates.

1.8 Stakeholders and User Classes

Table 1.2: Stakeholders and user classes

Stakeholder	Characteristics and needs
Store manager	Primary user. Needs store-wide analytics, alerts, and reports. Not necessarily technical.
Employee	Needs a personal view of shift, assigned zone, supported activity history and current tasks. Sees only employee-relevant data.
Store owner	Interested in service quality, staffing, and floor-coverage decisions at a summary level.
Customers	Appear in footage. Are not identified biometrically. Affected indirectly through service quality and privacy.
Project team and supervisor	Develop, evaluate, and supervise the system.

1.9 Success Criteria

The supervisor agreed to the 70-video dataset shown by the team. No numeric classification/interaction accuracy or dashboard response-time threshold was agreed. The criteria below describe the evaluation evidence to report; dataset acceptance does not establish model accuracy.

- The pipeline processes the supplied videos end to end on a CPU-only machine.
- Staff/customer classification and interaction detection are evaluated against manually labelled clips, with accuracy reported. No numeric pass threshold has been agreed; report the measured results and evaluation method without inventing a target.
- Interaction detection is benchmarked with and without the pose judge on labelled clips, reporting precision, recall and the effect of the judge.
- Dashboard metrics should correspond to the relevant tracked entities and source observations.
- Manager-only routes are not reachable without a valid signed session.
- Reports can be generated and exported as PDF.

1.10 Constraints and Assumptions

Constraints. No dedicated GPU is available. The timeline is limited to the two FYP semesters. The available video dataset constrains evaluation coverage. Processing is offline/batch rather than real time.

Assumptions. Cameras are fixed, and the store has an entrance-facing camera and two floor-facing cameras. Camera views overlap or adjoin so that people leaving one view enter another within a bounded time window. Staff are distinguishable by zone and appearance cues (for example, working areas and uniforms).

Distance assumption. Interaction distance is measured in image space and normalised by body height, so it is dimensionless and cannot fully resolve depth. A metric floor-distance prototype, which assumed an approximately planar floor and a fixed camera, was descoped (Section 6.4.3) because the moving-camera footage supported almost no floor projections.

1.11 Ethical, Legal and DEI Considerations

Privacy. The intended scope does not add facial identification or biometric identity templates. The trained role detector uses learned appearance-based role labels; other identity paths contain appearance descriptors/embeddings and associations that require retention/access review before privacy compliance is asserted. Runtime footage remains local and is excluded from Git; temporary track identifiers alone do not establish anonymity. NFR-10 and its proposed verification distinguish the intended constraint from an uncompleted storage audit.

Fair use of results. The system is designed for manager decision support rather than automated employee evaluation. Observed staff activity and coverage are indicators for discussion, and the limitations of the heuristics must be communicated to users.

Legal and consent. Deployment requires a review of applicable law, store policy and appropriate notice/consent arrangements. Pakistan's Ministry of Information Technology and Telecommunication lists personal-data-protection material as draft legislation on its official legislation page [1]. That listing is not a comprehensive statement of all applicable law. The prototype follows data-minimisation principles informed by the GDPR [2]; this design reference does not establish legal compliance or a lawful basis for deployment.

Accessibility and inclusion. The web interface uses readable fonts, clear contrast, and charts with textual values. Appearance-based classification can perform unevenly across clothing styles, and this is recorded as a fairness-related limitation to evaluate in FYP-2.

Chapter 2

Research and Existing Solutions

2.1 Research Method / Approach

Research combined three activities: (i) reviewing the foundational literature on object detection, multi-object tracking, person re-identification, pose-based orientation cues, and planar visual metrology (the last for the descoped floor prototype); (ii) surveying publicly described retail-analytics products and their stated capabilities; and (iii) a feasibility triage of candidate features against hardware (no dedicated GPU), timeline, and dependency constraints. Tools and libraries were then selected by prototyping on the supplied store videos.

2.2 Existing Solutions / Products

Commercial retail analytics. RetailNext describes traffic counts, staffing and interaction-rate analytics [3]. Sensormatic describes shopper traffic and journey insights, including labour and store-traffic information [4]. Amazon Just Walk Out describes camera/sensor-based shopping and automated checkout, including weight-sensor and RFID variants [5]. These are vendor descriptions, not independently reproduced performance results.

Research building blocks. The YOLO family [6] provides fast single-stage detectors with CPU-feasible small variants, available through the Ultralytics implementation [7]. SORT [8] and ByteTrack [9] associate detections across frames into tracks. Person re-identification across cameras is surveyed in [10] and typically depends on learned embeddings and substantial compute.

2.3 Comparison of Existing Solutions

Table 2.1: Qualitative comparison using official product descriptions, checked 20 October 2026

Approach	Documented focus	Evidence boundary
RetailNext	Traffic, conversion, staffing and interaction-rate analytics [3]	Pricing and CCTV compatibility not assessed.
Sensormatic	Shopper traffic/journeys and staffing context [4]	No claim of absent engagement features.
Just Walk Out	Shopper/product sensing and automated checkout [5]	Different checkout-oriented objective; cost not assessed.
RetailPulse prototype	Local-video role tracking and pose-checked interaction detection	CPU smoke tests and local UI evidence; no commercial accuracy or cost comparison.

2.4 Limitations and Gaps

The reviewed commercial products already provide substantial retail analytics, including interaction-related metrics in RetailNext. The project's design objective is therefore an inspectable academic prototype using local footage and explicit heuristic rules, rather than a claim that commercial engagement analytics do not exist. Public product pages alone do not establish relative cost, deployment effort, privacy compliance or comparative accuracy.

The technical gap the project isolates is narrower: separating a service interaction from a close pass-by using only a single ordinary camera. Proximity alone nominates any employee and customer who stay near each other, including two people walking away side by side; on the one labelled clip it reached precision 0.50 (Table 7.5). The project adds a pose-based facing check and measures its effect with and without it, so the contribution is an inspectable, locally run pipeline with a stated evaluation method rather than a new detector.

2.5 Proposed Solution

RetailPulse separates detection, classification, engagement, trajectory and interaction judging into distinct components. The mid-iteration implementation concentrates on these person-analysis components and the web interfaces. Lightweight YOLO detection with local tracker identifiers (BoT-SORT in the interaction pipeline, ByteTrack in the descoped floor prototype) keeps the pipeline CPU-friendly.

2.6 Complex Computing Problem

The complex computing problem is to derive reliable, per-person service and movement analytics from low-cost, uncontrolled CCTV video under tight compute limits. The problem involves several interacting difficulties:

- Conflicting requirements: accuracy against CPU-only throughput, and informativeness against privacy (no biometrics).
- Ambiguous ground truth: whether a staff member near a customer constitutes an "interaction" must be defined operationally from distance, orientation, and duration.
- Consistency of observations: role labels, boxes, distance estimates and interaction cues must refer to the same tracked person despite occlusions and identity switches.
- Non-technical users: results must be presented in a way that managers can act on without over-trusting heuristics.

2.7 Technical Challenges

- **CPU-only inference:** frame sampling and small detector variants are needed to keep batch processing practical.
- **Staff/customer separation without biometrics:** both learned appearance-based role detection and earlier zone rules require evaluation against clothing similarity and staff outside their expected zones.
- **Perspective and depth ambiguity:** pixel separations depend on image location and people at different depths can look close, so the pipeline uses body-height-normalised distance; a calibrated floor mapping to metres was tried and descoped.

- **Floor-contact uncertainty:** seated people, hidden feet, chairs, overlap and frame truncation made box-bottom estimates unreliable in the floor prototype and still affect the body bands used for proximity.
- **Camera movement:** a reference homography became misaligned on the moving-camera footage and insufficient static floor features meant unverified alignment, which led to descoping the floor prototype. Camera movement also causes identity switches.
- **Identity switches and occlusion:** ID switching in crowded scenes affects interaction durations and dwell times.
- **Security of the web tier:** manager-only operational data must not be unlocked by client-side state alone.

2.8 Research Findings and Design Decisions

2.8.1 Interaction Detection Findings

Proximity alone cannot separate a service interaction from a close pass-by. On the labelled clip IMG_8829 it produced one true and one false interaction (precision 0.50). Adding the YOLO pose model as a judge, which requires a head to point within 60° of the other person's head in at least half of four crops, removed the false positive (precision 1.00). This single-clip result motivates the design but does not establish its accuracy; FYP-2 evaluates it on more labelled clips (Chapter 7).

2.8.2 Geometric Basis of the Descoped Floor-Distance Prototype

The floor-distance prototype was descoped (Section 6.4.3); its research basis is kept because it explains why body-height-normalised distance replaced it.

Projective geometry provides a mapping between two views of a plane through a homography [11, 12]. Single-view metrology establishes broader foundations for recovering geometric measurements from perspective images using scene information [13]; the implemented prototype specifically uses explicit image/floor landmark correspondences rather than reproducing that paper's complete procedure. RetailPulse selects planar floor mapping because the intended quantity is separation along the floor and the existing camera and detector can be reused. It does not estimate a depth map or reconstruct arbitrary 3D scene geometry.

Robust fitting with RANSAC [14] supports additional calibration correspondences and reference-alignment checks. ByteTrack [9] supplies per-camera association, while ORB [15] supplies image features for the conservative motion monitor. These are established building blocks; the project's contribution is their integration with explicit position-quality states, configurable calibration and diagnostic exports. Published benchmark results for these methods are not claimed as RetailPulse performance.

Table 2.2: Findings and the decisions they influenced

Finding	Decision
YOLO detectors have small variants usable without a GPU [6, 7].	Use a lightweight YOLO-based detector and sample frames.
ByteTrack [9] gives stable local IDs without a separate appearance network.	Use ByteTrack for per-camera tracking.
Learned re-identification [10] is compute-heavy and biometric-adjacent.	Keep cross-camera association outside the mid-iteration deliverables.
Mixed vision responsibilities are harder to inspect and test.	Separate detection, role classification, interaction and distance logic.
Appearance evidence can be ambiguous.	Keep role confidence and source evidence visible for review.
Client-side role flags are easily altered.	Issue server-signed HttpOnly session cookies and require an internal secret on direct backend calls.
Managers need explanations, not only numbers.	Add a narration agent over camera-derived operational evidence.
Perspective changes pixel scale across the image [11, 12].	Projected foot proxies into floor metres in the prototype; descoped and replaced by body-height-normalised distance.
Proximity alone nominates close pass-bys as interactions.	Add a pass-by filter and a pose judge, and benchmark with and without the judge.
Supplied floor dimensions determine metric scale.	Stored editable landmarks and dimensions in the descoped prototype, with estimated inputs identified in configuration.
Camera movement can invalidate the reference mapping.	Checked alignment with ORB/RANSAC in the prototype and suppressed output when shifted or unverified; almost all frames were rejected, so the prototype was descoped.

Chapter 3

Proposal Feedback and Iteration Plan

3.1 Proposal Feedback Summary

At the proposal defence on 11 September 2026, the evaluators identified weak technical understanding and preparation, unclear features and project explanation, and presentation weaknesses including repeated pacing. They challenged the assumption that all stores want employees to approach customers frequently, citing luxury retailers such as Gucci and Prada. They considered the project worthwhile if its scope and explanation were properly focused. Appendix A reproduces the feedback text.

The response is to define a focused camera-based service-analytics scope, explain each component and its evidence, and distinguish proximity from an actual service interaction. Employee behaviour must be interpreted against the individual store's service policy. This report does not claim that one approach-frequency rule generalises to every retail format.

3.2 Proposal Action Register

Table 3.1: Proposal action register

No.	Feedback / Required Change	Response / Next Action	Status	Evidence
1	Improve technical understanding and preparation.	Document detection, classification and interaction rules; use executed tests to explain behaviour and limits.	Ongoing	Chapters 5, 6, 7

No.	Feedback / Required Change	Response / Next Action	Status	Evidence
2	Explain exact features and focus the project.	Focus scope on camera-based customer/staff analytics and the web application; make ownership and current feature status explicit.	Report updated	Chapters 1, 8
3	Defend applicability across different retail service models.	Require store-specific service thresholds and interpretation; evaluate low-contact as well as assistance-oriented scenarios.	Design response; evaluation planned	Chapter 4, FR-29
4	Improve presentation clarity and avoid pacing.	Rehearse a structured feature demonstration, assign speakers and practise stationary delivery.	Planned	Mid-evaluation preparation

3.3 Iteration Strategy

Development is iterative. The initial increment establishes the web application, secure access and camera-processing prototypes. Subsequent increments connect detection, classification, interaction and engagement outputs to the dashboard and evaluate them on store footage. Feature branches track implementation work. The evaluation milestones are listed below.

Table 3.2: Evaluation milestones

Milestone	Date
Proposal defence	11 September 2026
Mid evaluation	21 October 2026
Final evaluation window	23 November–4 December 2026

3.4 Iteration 1 Plan

Objectives: establish the application shell and data flows that later analytics plug into, and demonstrate person detection, role classification and interaction detection.

Selected features: manager and employee pages; role-aware authentication; reporting interface; alerts feed; system status page; person/role analysis and an interaction-detection pipeline (a floor-distance experiment was also built and later descoped).

Deliverables: running frontend, local application backend, person-analysis and interaction outputs, and demonstration evidence (Chapter 6).

3.5 Iteration 2 Plan

The target increment follows the 17 capability-level requirements and seven-component architecture in Chapters 4 and 5. Orchestrator work concerns application processing/shared-state workflows; complete integration is not claimed. Direct aisle instructions go to employees without a manager approval gate, and account-track linking/source-zone coverage remain explicit dependencies.

Objectives: replace prototype data with real agent output and evaluate it.

Selected features: Customer Behavior Agent, Employee Activity Agent, Interaction Agent and Employee Task Assignment Agent; live data in the dashboard pages; the Insight Narration Agent and Query Agent; and quantitative evaluation on labelled clips.

Deliverables: vision-component integration, evaluation report, and updated dashboard bound to real outputs (Chapter 9).

3.6 Work Breakdown and Responsibilities

Table 3.3: Work distribution

Work package	Description	Owner
Frontend and UX	Shared frontend development	Moiz and Ruhab
Customer/employee pose detection	Pose-detection work	Saqib
Person distance	Distance between people; head/hips/feet band handling when a full person position is rejected (the metric floor-distance experiment was descoped)	Moiz
Classification	Classification work	Ruhab
Testing	Detection and pipeline testing	Saqib
Report	Report preparation	Ruhab

The table records assigned areas, not a claim that every assigned feature has been integrated or validated. Completed-work evidence is distinguished in Chapter 8.

3.7 Progress Against Plan

Table 3.4: Planned versus actual progress at mid-report

Milestone	Planned	Actual
Web application (manager and employee)	Iteration 1	Implemented
Floor-distance CLI	Current prototype increment	Built, then descoped (`8c3a6fe`)
Interaction pipeline with pose judge and benchmark	Iteration 1	Implemented (local CLI)
Vision agents wired to dashboard	Iteration 2	In progress (prototype data)
Labelled accuracy evaluation	Iteration 2	Started: detector KPIs and one labelled clip; broader labelling pending

3.8 Delays, Deviations and Recovery Plan

Scope correction. Cross-camera association is reserved for the next phase and is not a mid-iteration deliverable. **Deviation.** The floor-distance prototype was descoped on 20 October because the moving-camera footage supported almost no floor projections; body-height-normalised distance with a pose judge replaced it. **Residual gap.** The dashboard's camera-derived metrics still use prototype data. **Recovery:** the first FYP-2 sprint binds the shared perception and Interaction Agent outputs to the dashboard, and quantitative evaluation is scheduled for the middle of the semester so that tuning time remains.

Chapter 4

Software Requirements

4.1 Scope and Identifier Policy

The active baseline contains exactly 17 functional capabilities, each with one primary use case using the same numerical suffix. Gaps preserve identifier continuity: retired identifiers are not reused for unrelated capabilities. Requirements specify intended behaviour, while the implementation/evidence column distinguishes source inspection, dated execution and proposed work. The consolidation and retired prototype are recorded in Appendix B.

The target architecture uses Customer Behavior Agent, Employee Activity Agent, Interaction Agent, Employee Task Assignment Agent, Insight Narration Agent, Query Agent and Orchestrator. Detection, role classification, tracking, identity association, geometry and pose/proximity are shared tools. Employee Activity consumes interaction context; Interaction does not depend on Employee Activity's final output. Direct assignment goes to identified employee accounts without a manager approval gate. An observed employee track is not automatically a roster/account identity.

4.2 User Interactions / Use Cases

Table 4.1: One primary use case for each active functional requirement

FR	Primary UC	Capability	Primary actor
FR-01	UC-01	Analyze a video	Operator / project team
FR-02	UC-02	Obtain entrance footfall	Manager
FR-04	UC-04	Analyze customer service interactions	Manager
FR-07	UC-07	Analyze spatial customer activity	Manager
FR-10	UC-10	Access a role-specific account	Manager or Employee
FR-11	UC-11	Monitor camera observations	Manager
FR-12	UC-12	Review manager analytics	Manager
FR-13	UC-13	Review personal workspace	Employee
FR-17	UC-17	Generate an insight report	Manager
FR-18	UC-18	Manage operational alerts	Manager
FR-19	UC-19	Inspect system status	Manager
FR-20	UC-20	Manage personal settings	Manager or Employee
FR-29	UC-29	Configure store operations	Manager
FR-34	UC-34	Evaluate analytical outputs	Operator / project team
FR-35	UC-35	Assess staff availability and coverage	Manager
FR-36	UC-36	Receive and update an aisle assignment	Employee receiving the instruction
FR-37	UC-37	Ask an analytics question	Manager

4.3 Use Case Diagrams

The following four actor views replace the earlier use-case drawing and together show exactly the 17 active primary UCs in Table 4.1. Each UC appears once. Manager links to the shared account-access and personal-settings cases are explicit in Figure 4.2. The rectangle denotes the RetailPulse system boundary; actors remain outside. Perception tools, internal agents and databases are not additional external actors. Interaction ordering is specified separately by the SSDs in Section 5.11.




Figure 4.1: Current use cases for the Operator / project team




Figure 4.2: Current Employee use cases and shared Manager account/settings access




Figure 4.3: Current Manager use cases: observation and analytics




Figure 4.4: Current Manager use cases: operational review, configuration and questions

4.4 Detailed Use Cases

The canonical specifications are included below. Each states one primary FR, numbered success steps, alternatives tied to those steps, postconditions and minimum guarantees. Current implementation notes are not substitutes for acceptance testing. A use case may call supporting tools or other capabilities without acquiring a second primary FR.

UC-01: Analyze a video

System sequence diagram: Figure 5.7.

Table 4.2: UC-01: Analyze a video

Field / step	Specification
Primary FR	FR-01
Primary actor	Operator / project team
Supporting actors / services	Video source and configured perception tools
Goal	Produce reviewable person observations and diagnostics for the selected recording.
Trigger	The operator submits a video and processing configuration.
Preconditions	The recording is readable; required weights and processing settings are available.
Main flow 1	Operator selects the recording, output location and sampling/model settings.
Main flow 2	System validates the input, weights and configuration and identifies the selected execution path.
Main flow 3	System processes the configured samples, maintains track identifiers and retains timestamps, role evidence and confidence.
Main flow 4	System writes annotated video and structured detections, people and interaction diagnostics, retaining verdicts and missing evidence.
Main flow 5	System reports completion, processed coverage and output locations; operator reviews the exports.
Alternative 2a	Missing/corrupt input or unavailable model: stop with an actionable error before claiming success.
Alternative 3a	No detections: export a valid empty result with processed coverage; do not call an unreadable frame empty.

Field / step	Specification
Alternative 3b	Processing/export failure: report failure and identify partial or incomplete outputs; recovery handling beyond existing CLI errors is proposed.
Success postconditions	Outputs and their processing configuration are available for review.
Failure / minimal guarantees	Source footage is unchanged; a failed or partial run is not represented as complete.
Implementation / evidence status	CLI implemented and dated TC-24 evidence retained. Role-labelled standalone processing differs from the typed identity path, where role may remain unknown.

UC-02: Obtain entrance footfall

System sequence diagram: Figure 5.8.

Table 4.3: UC-02: Obtain entrance footfall

Field / step	Specification
Primary FR	FR-02
Primary actor	Manager
Supporting actors / services	Customer Behavior Agent; entrance observation source
Goal	Obtain defensible entrance counts and occupancy context for an interval.
Trigger	Manager requests entrance statistics.
Preconditions	Authorized access, an entrance source, directional crossing rule and supported track observations exist.
Main flow 1	Manager selects the interval and entrance source.
Main flow 2	System validates crossing configuration and retrieves supported observations with continuity information.
Main flow 3	System determines customer entry and exit crossings without counting repeated samples as new customers.
Main flow 4	System calculates interval net change; absolute occupancy is calculated only when initial occupancy is known.
Main flow 5	System displays in/out, supported occupancy and observation gaps; manager inspects coverage.
Alternative 2a	Missing boundary or camera gap: return unavailable or partial counts with the affected period.

Field / step	Specification
Alternative 3a	Unknown role or broken track continuity: retain uncertain crossings separately under the configured counting policy.
Alternative 4a	Unknown initial occupancy: show net change only, not an invented absolute in-store count.
Success postconditions	Counts, interval and coverage context are displayed.
Failure / minimal guarantees	Unsupported periods and initial conditions are explicit.
Implementation / evidence status	Target capability; current dashboard snapshots and detector KPIs do not establish crossing-count correctness. TC-26 is planned.

UC-04: Analyze customer service interactions

System sequence diagram: Figure 5.9.

Table 4.4: UC-04: Analyze customer service interactions

Field / step	Specification
Primary FR	FR-04
Primary actor	Manager
Supporting actors / services	Interaction Agent; configured camera observations
Goal	Review possible service interactions and policy-based unattended evidence.
Trigger	Manager requests service analysis for an interval.
Preconditions	Authorized access, supported role/track observations and applicable store service policy exist.
Main flow 1	Manager selects an interval and applicable zone.
Main flow 2	System evaluates sustained employee/customer proximity and relative motion using the configured observation rules.
Main flow 3	System applies pass-by filtering and available pose evidence, retaining interaction, rejected and unverified verdicts.
Main flow 4	System derives interaction durations and, only when supported by entry/zone history, approach times and potentially unattended events under the store policy.

Field / step	Specification
Main flow 5	System presents the records with evidence quality and coverage; manager reviews their interpretation.
Alternative 2a	Unknown role, occlusion or incompatible observations: retain uncertainty rather than a definite service outcome.
Alternative 3a	Judge disabled, unavailable or failing: current code keeps the proximity candidate as unverified; it is not verified assistance.
Alternative 4a	Missing arrival/history or policy: omit unsupported approach/unattended metrics and explain why.
Success postconditions	Supported service-analysis records are displayed with their evidence and policy context.
Failure / minimal guarantees	A proximity/pose event is not asserted to prove help was provided.
Implementation / evidence status	Candidate/duration/pass-by/pose logic implemented; approach and unattended integration remain pending. TC-09 stays Pending; TC-21/22 and dated outputs are supporting evidence.

UC-07: Analyze spatial customer activity

System sequence diagram: Figure 5.10.

Table 4.5: UC-07: Analyze spatial customer activity

Field / step	Specification
Primary FR	FR-07
Primary actor	Manager
Supporting actors / services	Customer Behavior Agent; zone geometry and track observations
Goal	Understand supported movement, dwell and sustained zone demand.
Trigger	Manager opens spatial analysis.
Preconditions	Authorized access and applicable zone definitions and observations exist.
Main flow 1	Manager selects an interval and applicable zone.
Main flow 2	System retrieves supported customer tracks and determines zone membership and observation coverage.

Field / step	Specification
Main flow 3	System aggregates paths, dwell and occupancy measures without double-counting unsupported identity continuations.
Main flow 4	System applies configured persistence rules to identify hot zones and gray zones.
Main flow 5	System displays maps, interval and coverage alongside the zone findings.
Alternative 2a	Unconfigured/invalid zone: reject the selection or request valid geometry.
Alternative 3a	Low observation coverage: label insufficient evidence rather than low customer activity.
Alternative 3b	Unsupported cross-camera association: limit trajectories to supported camera/session tracks; do not infer whole-store paths or customers per square metre.
Success postconditions	Spatial results identify their source, zone, period and coverage.
Failure / minimal guarantees	No metric density or whole-store path is invented.
Implementation / evidence status	Target aggregation; current spatial UI uses demonstration data. TC-10 remains Pending.

UC-10: Access a role-specific account

System sequence diagram: Figure 5.11.

Table 4.6: UC-10: Access a role-specific account

Field / step	Specification
Primary FR	FR-10
Primary actor	Manager or Employee
Supporting actors / services	Account service; invitation issuer where needed
Goal	Enter and leave the workspace authorized for the authenticated account.
Trigger	User activates an account, logs in or logs out.
Preconditions	Account service is available; activation requires a valid invitation under the current policy.

Field / step	Specification
Main flow 1	User activates/registers through the configured account policy if needed; current registration uses an invitation token.
Main flow 2	User submits credentials; system validates account status, password and assigned role.
Main flow 3	System creates an authenticated session and opens the permitted workspace.
Main flow 4	User requests logout; system invalidates the session cookie and updates the interface.
Alternative 1a	Invalid/expired invitation or duplicate account: reject activation and explain the error.
Alternative 2a	Wrong password, inactive account or role mismatch: deny access; selecting Manager cannot elevate an Employee account.
Alternative 3a	Expired/invalid session: require authentication before protected data is returned.
Success postconditions	The correct workspace is accessible, or logout ends authenticated access.
Failure / minimal guarantees	Failed authentication does not create an authorized session.
Implementation / evidence status	Invitation, login and logout mechanisms exist; TC-01 and TC-02 cover recorded subsets, not every activation/error path.

UC-11: Monitor camera observations

System sequence diagram: Figure 5.12.

Table 4.7: UC-11: Monitor camera observations

Field / step	Specification
Primary FR	FR-11
Primary actor	Manager
Supporting actors / services	Configured sources; available analytical output
Goal	Inspect a camera view and understand how current its observations are.
Trigger	Manager opens camera monitoring.

Field / step	Specification
Preconditions	Manager is authenticated and camera configuration is available.
Main flow 1	Manager opens the dashboard and selects a configured source.
Main flow 2	System obtains available recording/stream observations and their source/processing timestamps.
Main flow 3	System displays the view, supported overlays, availability and observation freshness.
Main flow 4	Manager changes source or inspects observation context.
Alternative 2a	Offline/missing source: show unavailable state and last known observation time where available.
Alternative 3a	Stale output or absent overlays: label it explicitly rather than imply fresh analytics.
Alternative 1a	Unauthorized request: deny protected access.
Success postconditions	The selected source and available overlays are shown with freshness context.
Failure / minimal guarantees	No unmeasured real-time guarantee is implied.
Implementation / evidence status	Dashboard recording/snapshot display exists; complete configured-source/freshness integration is proposed. TC-12 is representative UI evidence; TC-37 is planned.

UC-12: Review manager analytics

System sequence diagram: Figure 5.13.

Table 4.8: UC-12: Review manager analytics

Field / step	Specification
Primary FR	FR-12
Primary actor	Manager
Supporting actors / services	Authorized analytics records and presentation components
Goal	Review customer, staff, interaction and spatial findings together.
Trigger	Manager opens an analytics view or changes its filters.
Preconditions	Authenticated Manager session and supported metrics or explicit availability states exist.

Field / step	Specification
Main flow 1	Manager selects an interval and applicable zone.
Main flow 2	System validates filters and retrieves authorized customer, staff, interaction and spatial metrics.
Main flow 3	System presents the applicable views with time, source and observation-coverage context.
Main flow 4	Manager inspects a metric or changes the selection; system refreshes the presentation.
Alternative 2a	Invalid interval/zone: request a corrected filter without displaying unrelated results.
Alternative 2b	No records or partial metrics: show empty/partial states and identify unsupported quantities.
Alternative 2c	Access denied: withhold protected records.
Success postconditions	Authorized consolidated views correspond to the selected filters.
Failure / minimal guarantees	Presentation does not invent measurements or recalculate another capability under a duplicate requirement.
Implementation / evidence status	Manager pages exist with prototype/snapshot metrics; integrated filtering and coverage remain proposed. TC-12 is partial UI evidence; TC-38 is planned.

UC-13: Review personal workspace

System sequence diagram: Figure 5.14.

Table 4.9: UC-13: Review personal workspace

Field / step	Specification
Primary FR	FR-13
Primary actor	Employee
Supporting actors / services	Own roster/account and task records
Goal	Review personal shift, zone, activity and current work.
Trigger	Employee opens their workspace.
Preconditions	Authenticated Employee account exists.
Main flow 1	Employee opens the workspace.
Main flow 2	System retrieves that account's own shift, assigned zone and current tasks.

Field / step	Specification
Main flow 3	Employee opens personal activity history; system shows supported observations and shift updates.
Main flow 4	System identifies missing history and distinguishes demo values from recorded activity.
Alternative 2a	No roster/tasks/history: show an empty or unavailable state for the missing information.
Alternative 2b	Attempt to read another employee's protected records: deny access.
Alternative 1a	Expired session: require login.
Success postconditions	Only the employee's permitted workspace records are shown.
Failure / minimal guarantees	No composite score or new ranking system is required; task updates are specified primarily by UC-36.
Implementation / evidence status	Own-task retrieval and workspace UI exist; activity history/shift integration is partial or demo. TC-12 is partial; TC-39 is planned.

UC-17: Generate an insight report

System sequence diagram: Figure 5.15.

Table 4.10: UC-17: Generate an insight report

Field / step	Specification
Primary FR	FR-17
Primary actor	Manager
Supporting actors / services	Insight Narration Agent; authorized metrics/dispatch records; PDF exporter
Goal	Create an exportable account of supported operational findings.
Trigger	Manager requests an insight report.
Preconditions	Authenticated Manager account and available records for the chosen scope exist.
Main flow 1	Manager selects the interval and report sections.
Main flow 2	System retrieves permitted metrics and relevant dispatch decisions with coverage context.
Main flow 3	System generates a narrative grounded in those records and separates facts from limitations.

Field / step	Specification
Main flow 4	Manager previews the selected content; system provides PDF export.
Main flow 5	Manager requests export; system returns the generated file or an actionable failure.
Alternative 2a	Incomplete data: disclose omitted sections or allow an explicitly partial report.
Alternative 3a	LLM unavailable: offer a labelled metrics-only report or state that narration is unavailable.
Alternative 5a	Export failure: preserve the selection and report the error, without claiming a successful PDF.
Success postconditions	A readable PDF contains selected supported content and grounded narrative when available.
Failure / minimal guarantees	Missing evidence is not filled with invented metrics or prose claims.
Implementation / evidence status	Target capability; current report/PDF route is removed. TC-13 remains Unavailable; voice-script generation is not report-export evidence.

UC-18: Manage operational alerts

System sequence diagram: Figure 5.16.

Table 4.11: UC-18: Manage operational alerts

Field / step	Specification
Primary FR	FR-18
Primary actor	Manager
Supporting actors / services	Alert records and related assignment context
Goal	Review and resolve operational alerts with an audit trail.
Trigger	Manager opens the alert feed.
Preconditions	Authenticated Manager account and alert service are available.
Main flow 1	Manager opens alerts and selects active/resolved/category filters.
Main flow 2	System retrieves the authorized feed and shows available evidence and related assignments.

Field / step	Specification
Main flow 3	Manager inspects an alert and records resolution.
Main flow 4	System saves the resolution actor/time and refreshes the feed.
Alternative 2a	No alerts or invalid filter: display an empty state or request valid filters.
Alternative 3a	Already-resolved/stale record: show the current state and avoid a misleading new resolution; stronger stale-write protection is proposed.
Alternative 3b	Denied access or failed save: preserve the existing record and return an error.
Success postconditions	The feed reflects saved resolution with actor/time context.
Failure / minimal guarantees	Alert resolution is independent of direct employee dispatch; it is not a dispatch authorization gate.
Implementation / evidence status	Alert retrieval/resolution implemented; full linked-assignment/stale-record scenarios await TC-40.

UC-19: Inspect system status

System sequence diagram: Figure 5.17.

Table 4.12: UC-19: Inspect system status

Field / step	Specification
Primary FR	FR-19
Primary actor	Manager
Supporting actors / services	Health and telemetry providers
Goal	Understand which configured components are healthy or unobserved.
Trigger	Manager requests system status.
Preconditions	Manager authorization and configured component registry exist.
Main flow 1	Manager opens system status.
Main flow 2	System retrieves health, available throughput and activity records for configured pipeline tools and the seven target agent/coordinator components.

Field / step	Specification
Main flow 3	System displays timestamps and distinguishes measured, unavailable, inactive and demonstration states.
Main flow 4	Manager inspects a component's available details.
Alternative 2a	Telemetry missing or stale: show unknown/stale instead of inferred health.
Alternative 2b	Component failed/inactive: identify its state and effect on dependent results.
Alternative 1a	Unauthorized access: withhold protected diagnostics.
Success postconditions	Status identifies the evidence available for each displayed component.
Failure / minimal guarantees	Hard-coded worker strings are not claimed as measured seven-agent telemetry.
Implementation / evidence status	Backend status endpoint exists with hard-coded worker states; complete seven-component UI/telemetry is proposed. TC-41 is planned.

UC-20: Manage personal settings

System sequence diagram: Figure 5.18.

Table 4.13: UC-20: Manage personal settings

Field / step	Specification
Primary FR	FR-20
Primary actor	Manager or Employee
Supporting actors / services	Account/profile service
Goal	Save permitted personal details, password and notification preferences.
Trigger	User opens personal settings.
Preconditions	Authenticated account and applicable profile/password policy exist.
Main flow 1	User opens profile and edits permitted fields or notification preferences.
Main flow 2	System validates fields, permissions and any duplicate-email constraint.
Main flow 3	For a password change, user supplies credentials required by the security policy; system validates them.

Field / step	Specification
Main flow 4	System persists authorized changes and confirms the saved values.
Alternative 2a	Invalid fields, duplicate email or attempted role change: reject the change; users cannot elevate their own role.
Alternative 3a	Wrong current password where required: deny the password change.
Alternative 4a	Expired session or failed save: report failure and retain previous saved data.
Success postconditions	Permitted changes are persisted and can be read back.
Failure / minimal guarantees	A UI-only confirmation is not proof of a stored update.
Implementation / evidence status	Profile controls are present, but working profile/password/preference persistence is not established. TC-42 is planned.

UC-29: Configure store operations

System sequence diagram: Figure 5.19.

Table 4.14: UC-29: Configure store operations

Field / step	Specification
Primary FR	FR-29
Primary actor	Manager
Supporting actors / services	Camera, zone, roster and policy stores
Goal	Configure valid store operations for subsequent processing.
Trigger	Manager changes store configuration.
Preconditions	Authenticated Manager account and applicable records exist.
Main flow 1	Manager opens current settings and selects camera, zone, roster or service/dispatch policy settings.
Main flow 2	Manager submits changes; system validates values, references, source compatibility and applicable geometry/roster conflicts.
Main flow 3	System persists a valid configuration and shows the saved result.

Field / step	Specification
Main flow 4	System applies the configuration to subsequent supported processing and identifies consumers not yet integrated.
Alternative 2a	Invalid geometry/value, nonexistent employee or incompatible source: reject invalid changes.
Alternative 2b	Conflicting roster or unauthorized change: reject or request correction under the applicable policy.
Alternative 3a	Save failure: preserve the previous valid configuration and report failure.
Success postconditions	Validated settings are saved and applicable consumers use them.
Failure / minimal guarantees	Persistence is not represented as proof that every analytics consumer is connected.
Implementation / evidence status	Settings APIs/UI persist configuration; comprehensive validation and consumption are incomplete. TC-27 is planned.

UC-34: Evaluate analytical outputs

System sequence diagram: Figure 5.20.

Table 4.15: UC-34: Evaluate analytical outputs

Field / step	Specification
Primary FR	FR-34
Primary actor	Operator / project team
Supporting actors / services	Benchmark tools; supplied predictions and annotations
Goal	Measure supported analytical accuracy and speed with reproducible context.
Trigger	Operator submits an evaluation configuration.
Preconditions	Compatible predictions, annotations, model/configuration metadata and evaluation inputs are available.
Main flow 1	Operator selects predictions, annotations and benchmark configuration.
Main flow 2	System validates identifiers, units, label coverage and compatible evaluation settings.
Main flow 3	System computes only supported detector/interaction metrics and processing-speed measures.

Field / step	Specification
Main flow 4	System exports results with configuration, evaluated coverage and environment/timing context.
Main flow 5	Operator reviews the export and unsupported-metric explanations.
Alternative 2a	Missing/mismatched labels, incompatible units or empty evaluation: identify metrics that cannot be computed.
Alternative 3a	Processing failure: retain an explicit failed/partial evaluation outcome.
Alternative 3b	No footfall/dwell/task annotations: do not infer those capabilities' accuracy from detector or interaction KPIs.
Success postconditions	Evaluation outputs identify exactly what was measured and on which evidence.
Failure / minimal guarantees	An unlabelled clip supplies speed/output evidence, not accuracy ground truth.
Implementation / evidence status	Benchmark implemented with recorded detector and one-clip interaction results; TC-23 covers metric functions. Broader labels remain needed.

UC-35: Assess staff availability and coverage

System sequence diagram: Figure 5.21.

Table 4.16: UC-35: Assess staff availability and coverage

Field / step	Specification
Primary FR	FR-35
Primary actor	Manager
Supporting actors / services	Employee Activity Agent; roster/accounts, assignments and Interaction Agent context
Goal	Assess observed staff availability and supported coverage gaps.
Trigger	Manager requests coverage or an operational refresh occurs.
Preconditions	Authorized access, store policy and supported account/roster/observation context are available.
Main flow 1	Manager requests an interval/zone assessment or receives a refresh.

Field / step	Specification
Main flow 2	System combines roster/account and current assignment records with supported observed staff locations and interaction context.
Main flow 3	System derives availability/activity and identifies unknown states; a stationary assisting employee is not automatically idle.
Main flow 4	System evaluates persistent zone-coverage gaps only where observation coverage supports that finding.
Main flow 5	System presents availability and gaps with evidence, uncertainty and applicable policy.
Alternative 2a	No reliable account-track link: show observed track activity separately from account availability.
Alternative 3a	Missing break/task context: preserve unknown availability instead of equating stillness with idleness.
Alternative 4a	Occluded/unobserved area: show inadequate coverage, not a definite unstaffed zone.
Success postconditions	Managers see explainable activity/coverage rather than a mandatory composite score.
Failure / minimal guarantees	Interaction consumes shared perception evidence; Employee Activity consumes interaction context, avoiding circular computation.
Implementation / evidence status	Roster/task records exist; vision-account linkage and contextual coverage analysis are integration work. TC-28 is planned.

UC-36: Receive and update an aisle assignment

System sequence diagram: Figure 5.22.

Table 4.17: UC-36: Receive and update an aisle assignment

Field / step	Specification
Primary FR	FR-36
Primary actor	Employee receiving the instruction
Supporting actors / services	Employee Task Assignment Agent; roster/accounts; operational evidence; Orchestrator
Goal	Receive a justified aisle instruction directly and report subsequent status.

Field / step	Specification
Trigger	System detects a supported staffing need and selects an eligible employee.
Preconditions	A valid employee account/roster, target zone, applicable dispatch policy and delivery channel exist; vision-derived account location needs a reliable track-account link.
Main flow 1	System determines a supported aisle staffing need and checks evidence freshness and applicable dispatch policy.
Main flow 2	System checks eligible account/roster availability, current tasks and source-zone coverage before selecting an employee.
Main flow 3	System records the selected account, target aisle, instruction, reason and dispatch outcome.
Main flow 4	System directly creates and delivers the instruction to that employee's workspace; current backend creation records delivered.
Main flow 5	Employee views the instruction and may acknowledge it or report in_progress and completed, as supported.
Main flow 6	System records status actor/time and shows unresolved, declined, expired or cancelled outcomes where applicable.
Alternative 1a	Stale evidence or paused policy: preserve a clear non-dispatch outcome and surface unresolved need.
Alternative 2a	No eligible employee, existing task or source-zone coverage conflict: do not dispatch unsafely; retain the reason.
Alternative 4a	Delivery fails: show an explicit unresolved delivery outcome; reliable delivery confirmation/retry is proposed.
Alternative 5a	Employee unavailable/unable to complete: record supported declined or other applicable status and surface the unresolved need; reassignment policy is proposed.
Success postconditions	An identified employee receives the aisle instruction and account-bound status history is recorded.
Failure / minimal guarantees	No manager approval step is present. A stored delivered state alone does not prove receipt, arrival or completion; duplicate/concurrent and oscillating assignments require policy protection.

Field / step	Specification
Implementation / evidence status	Direct selection/task creation and own-task transitions exist. Source-zone protection, vision-trigger integration, reliable delivery and strict transition sequencing are incomplete; TC-29–TC-33 are planned.

UC-37: Ask an analytics question

System sequence diagram: Figure 5.23.

Table 4.18: UC-37: Ask an analytics question

Field / step	Specification
Primary FR	FR-37
Primary actor	Manager
Supporting actors / services	Query Agent; authorized analytics retrieval tools; LLM service where configured
Goal	Obtain a grounded answer to a store-analytics question.
Trigger	Manager submits an analytics question.
Preconditions	Authenticated Manager session and authorized retrieval scope exist.
Main flow 1	Manager submits a question and any relevant interval/zone context.
Main flow 2	System validates access and the requested scope; clarifies ambiguous filters when needed.
Main flow 3	System retrieves relevant authorized analytics through tools.
Main flow 4	System answers with supporting figures, source/time context and evidence limitations.
Main flow 5	Manager reviews the answer or provides clarification for a subsequent query.
Alternative 2a	Ambiguous question: ask for clarification rather than choosing an unsupported interval.
Alternative 3a	Missing/no records or unsupported request: explain the missing evidence; do not invent a numeric answer.
Alternative 3b	Unauthorized retrieval: deny access and exclude protected records.
Alternative 4a	LLM failure: return an explicit limitation or supported deterministic response without fabricated content.

Field / step	Specification
Success postconditions	The answer is grounded in permitted records and identifies its interval.
Failure / minimal guarantees	The query interface does not silently dispatch tasks or change settings.
Implementation / evidence status	Target capability; existing announcement-script service is not an analytics-query agent. TC-34–TC-36 are planned.

4.5 Functional Requirements

Table 4.19: Active functional requirements: consolidated 17-capability baseline

ID	Functional capability requirement	Priority
FR-01	The system shall process an operator-selected video to produce tracked person observations with role labels, confidence and timestamps, together with an annotated video and structured diagnostic exports.	High
FR-02	The system shall calculate customer entry, exit and observed occupancy counts for a selected interval from configured entrance-crossing events and identify unavailable or incomplete coverage.	High
FR-04	The system shall derive staff/customer interaction records, interaction duration, approach time and potentially unattended-customer events from supported observations using the configured store service policy, preserving uncertain evidence.	High
FR-07	The system shall derive supported customer paths, zone dwell, occupancy heatmaps and sustained hot/gray-zone activity for a selected interval, distinguishing low observation coverage from low activity.	High
FR-10	The system shall support account activation or registration according to the configured account policy, login and logout, and provide Manager or Employee access according to the authenticated role.	High

ID	Functional capability requirement	Priority
FR-11	The system shall display configured camera sources and available analytical overlays to a manager, identifying source availability and observation freshness.	High
FR-12	The system shall allow a manager to select an interval and applicable zone to review consolidated customer, staff, interaction and spatial metrics with data-coverage context.	High
FR-13	The system shall allow an employee to view their own shift, assigned zone, observed activity history, current tasks and shift updates.	High
FR-17	The system shall allow a manager to select an interval and report sections, generate a narrative grounded in available metrics and dispatch records, and export the selected content as PDF.	Medium
FR-18	The system shall allow a manager to review and filter active/resolved alerts, inspect supporting context and related assignments, and record alert resolution.	Medium
FR-19	The system shall display health, available processing-throughput measures and activity records for configured pipeline components and the seven agreed agent/coordinator components, identifying unavailable telemetry.	Low
FR-20	The system shall allow an authenticated user to update permitted profile fields, change their password and save notification preferences.	Low
FR-29	The system shall allow a manager to configure camera sources, zones, staff rosters and store-specific service/dispatch policies, validating changes before they affect subsequent processing.	High
FR-34	The system shall allow an operator to evaluate detector and interaction outputs against supplied annotations and export the supported accuracy and processing-speed results with evaluation configuration.	Medium
FR-35	The system shall derive staff availability, observed activity and zone-coverage gaps using roster, assignment and interaction context, identifying unknown states rather than equating stillness with idleness.	High

ID	Functional capability requirement	Priority
FR-36	The system shall select an eligible available employee when a supported aisle staffing need arises, directly deliver an aisle instruction with its reason, and record the assignment and its subsequent status.	High
FR-37	The system shall answer a manager's store-analytics question using authorized records and identify supporting metrics and time context, or explain missing evidence and request clarification when needed.	Medium

4.6 Non-Functional Requirements and Solutions

Each requirement is separate from its short implementation/proposed approach. An approach is not evidence that the concern is satisfied. Historical NFR-11 belongs only to Appendix B; NFRs do not create additional primary UCs.

Table 4.20: Active NFR concerns, practical approaches and verification status

ID	Requirement / concern	Short solution / approach and verification
NFR-01	Repeated numerical calculations with the same inputs/configuration shall agree within a documented tolerance.	Reuse input, model/version and configuration metadata and compare repeated numerical outputs against a stated tolerance; broader pipeline repeatability remains to be profiled. TC-43 is planned; the recorded TC-25 byte-identical JSON check is a separate, stricter result for one clip.
NFR-02	Video-processing jobs shall report failures rather than fail silently.	Existing CLI input/model errors and typed failed-frame/session signals provide explicit error paths; comprehensive partial-output/job reporting is proposed. Verify corrupt inputs, model failures and interrupted exports under UC-01 rather than interpreting an error as an empty successful detection.

ID	Requirement / concern	Short solution / approach and verification
NFR-03	Main analytics pages shall be reachable within two navigation actions from the defined role landing page.	Use direct role-appropriate navigation links already present, and define the starting workspace before counting actions. TC-44 will check the actual paths; target compliance is not established by the presence of links alone.
NFR-04	Charts shall show textual values and readable consistent fonts.	Use the existing Space Grotesk, Inter and JetBrains Mono theme with chart labels and textual metric values; extend incomplete views consistently. TC-45 will check clipping/readability at documented viewport sizes.
NFR-05	Vision processing shall support CPU-only hardware with configurable sampling.	Use the existing lightweight detector/OpenVINO path and configurable scoring/tracking intervals, treating processing as sampled/offline where necessary. Recorded benchmark throughput is configuration-specific; TC-46 will verify speed and environment without promising an unmeasured real-time rate.
NFR-06	Dashboard pages shall provide acceptable responsiveness on a stated laptop/environment; no supervisor-approved numeric target exists.	Existing pages load data asynchronously; bounded interval queries and aggregate retrieval are proposed for heavier analytics. TC-46 will measure page latency separately from compilation, inference and the recorded warm-login HTTP timings; a numeric acceptance threshold remains unspecified.
NFR-07	Protected manager functions shall require an authenticated Manager and prevent role escalation.	Use signed HttpOnly sessions and server-side role checks on protected endpoints; the client route guard supplies navigation behaviour rather than sole data protection. TC-01/02 record subsets, while additional invalid/expired-session and missing-route checks remain required.

ID	Requirement / concern	Short solution / approach and verification
NFR-08	Protected backend access shall be restricted to authorized application calls.	Existing protected routes validate an internal secret and the Next.js server proxy adds the secret and actor context without exposing it to browser code. TC-02 records missing/wrong-secret rejection; verify remaining protected routes and alternate camera-secret paths separately.
NFR-09	Secrets shall be configured securely and excluded from published source/logs.	Use environment lookups already supported and maintain placeholder-only examples and excluded real secret files; complete configuration/history review remains required. TC-47 is a planned redacted audit of examples, logs and browser-delivered configuration, not a claim that every current secret is compliant.
NFR-10	No biometric identifiers shall be stored.	Limit retained operational data and avoid facial-identity templates; existing appearance descriptors/embeddings, identity associations and retention behaviour require inspection and minimisation before compliance is asserted. TC-48 will audit those paths and access/retention controls; temporary track IDs are not assumed automatically anonymous.

4.7 Acceptance Criteria

Table 4.21: Acceptance checks for all active functional capabilities

FR	Capability-level acceptance	Evidence / proposed check
FR-01	A configured sampled run exports tracked observations, roles/confidence, timestamps and readable diagnostics; invalid input/model and partial-output states are explicit.	TC-07, TC-08, TC-24; recorded CLI outputs

FR	Capability-level acceptance	Evidence / proposed check
FR-02	A labelled directional-crossing scenario gives expected in/out; unknown initial occupancy prevents an absolute count; source gaps produce partial/unavailable coverage.	TC-26 (Planned)
FR-04	Sustained/pass-by/pose scenarios retain candidate verdicts; unverified is not verified assistance. Approach/unattended results require sufficient timing history and store policy.	TC-09 (Pending); TC-21, TC-22, TC-24
FR-07	Annotated zone paths/dwell support aggregation; hot/gray-zone findings require sustained evidence and adequate coverage. Missing views are not low activity.	TC-10 (Pending)
FR-10	Valid account access opens the correct workspace; invalid credentials, inactive accounts, expired invitations/sessions and self-elevation attempts are denied; logout removes access.	TC-01; TC-02 security subset
FR-11	A configured source shows available overlays and source/processing time; offline, stale and absent-overlay states are identified.	TC-12 (Partial); TC-37 (Planned)
FR-12	Authorized interval/zone filters select corresponding metrics; invalid/no/partial results are explicit and demo values are identified.	TC-12 (Partial); TC-38 (Planned)
FR-13	Employee sees only own shift/zone/tasks and supported history; missing records show empty states and another account's records are denied.	TC-12 (Partial); TC-39 (Planned)
FR-17	A selected report exports readable PDF and evidence-grounded narrative or explicit metrics-only fallback; unavailable export stays unavailable, not Passed.	TC-13 (Unavailable)
FR-18	Filters and evidence/assignment context are inspectable; resolution records actor/time. Resolving an alert does not gate dispatch.	TC-40 (Planned); source inspection

FR	Capability-level acceptance	Evidence / proposed check
FR-19	All seven target components and configured tools have measured or explicit unknown/stale/inactive status; hard-coded state is not throughput evidence.	TC-41 (Planned); source inspection
FR-20	Permitted edits persist and read back; password/role/duplicate-email failures follow policy and do not report a saved change.	TC-42 (Planned)
FR-29	Valid camera/zone/roster/policy changes persist; invalid/conflicting/unauthorized edits retain previous valid state, and actual consumer integration is identified.	TC-27 (Planned); settings source inspection
FR-34	Compatible labels produce correct metric calculations and context; incompatible/empty labels identify unsupported metrics. Speed observations are not accuracy results.	TC-23; dated benchmark tables
FR-35	Assisting-but-stationary staff are not automatically idle; unknown account linkage and unobserved areas remain unknown; sustained coverage gaps require evidence.	TC-28 (Planned)
FR-36	Eligible account receives a direct aisle task without a manager gate; no-eligible/conflicting/stale/delivery-failure and own-status scenarios retain clear outcomes; delivery is not completion.	TC-29–TC-33 (Planned); dispatch source inspection
FR-37	Supported answers cite figures and time context; missing evidence requests clarification or explains limitation; unauthorized retrieval is denied and no operational state changes occur.	TC-34–TC-36 (Planned)

4.8 Requirements Traceability

TC identifiers and dated results retain their historical meaning; only their current capability mapping changes. Planned scenarios below and in Appendix C have not been executed. Historical floor tests are not evidence of current metric-distance capability.

Table 4.22: Current capability traceability and honest evidence status

FR	Primary UC	Responsible component	Acceptance / evidence	Implementation / evaluation status
FR-01	UC-01	Shared perception / video CLI	TC-07, TC-08, TC-24; recorded CLI outputs	Implemented CLI; recorded subset
FR-02	UC-02	Customer Behavior Agent	TC-26 (Planned)	Target; count evaluation not established
FR-04	UC-04	Interaction Agent	TC-09 (Pending); TC-21, TC-22, TC-24	Implemented candidate logic; service metrics partial
FR-07	UC-07	Customer Behavior Agent	TC-10 (Pending)	Target; demo UI
FR-10	UC-10	Account service	TC-01; TC-02 security subset	Implemented mechanisms; subset tested
FR-11	UC-11	Monitoring frontend	TC-12 (Partial); TC-37 (Planned)	Partial; recording/snapshot UI
FR-12	UC-12	Manager analytics frontend	TC-12 (Partial); TC-38 (Planned)	Partial; demo/snapshot metrics
FR-13	UC-13	Employee workspace	TC-12 (Partial); TC-39 (Planned)	Partial; own tasks plus demo history
FR-17	UC-17	Insight Narration Agent / reporting	TC-13 (Unavailable)	Target; route unavailable
FR-18	UC-18	Alert service	TC-40 (Planned); source inspection	Implemented API/UI; scenarios unverified
FR-19	UC-19	Status / Orchestrator telemetry	TC-41 (Planned); source inspection	Partial; hard-coded status
FR-20	UC-20	Profile service	TC-42 (Planned)	UI/proposed persistence
FR-29	UC-29	Store configuration	TC-27 (Planned); settings source inspection	Partial; stored config, incomplete consumers
FR-34	UC-34	Evaluation tools	TC-23; dated benchmark tables	Implemented; labels limited

FR	Primary UC	Responsible component	Acceptance / evidence	Implementation / evaluation status
FR-35	UC-35	Employee Activity Agent	TC-28 (Planned)	Target contextual analysis
FR-36	UC-36	Employee Task Assignment Agent	TC-29–TC-33 (Planned); dispatch source inspection	Partial backend; policy/integration gaps
FR-37	UC-37	Query Agent	TC-34–TC-36 (Planned)	Target; retrieval integration pending

Chapter 5

System Design

5.1 System Architecture

The target architecture comprises seven business agents/coordinator components. The mid-iteration perception CLI and current application endpoints implement only parts of that design; names in the diagram do not prove seven independently deployed services. Shared perception tools provide observations to the business agents. Interaction uses shared role/track/pose evidence and does not depend on Employee Activity's final output; Employee Activity consumes interaction context when interpreting stationary staff.




Figure 5.1: RetailPulse target system architecture: seven agent/coordinator responsibilities with shared perception tools

The application tier is separate from the vision pipeline. The Next.js frontend serves the pages and proxies backend calls. Runtime and service boundaries are shown in the deployment diagram (Figure 5.4). The architecture illustrates target responsibilities rather than asserting that every agent or connection is already integrated.

5.1.1 YOLO Model Responsibilities

The project uses two distinct YOLO model roles: a YOLO pose model supplies body-keypoint evidence for interaction analysis, while a standard YOLO object-detection model with customer/employee classes supplies person boxes and role labels. The latter is a detector trained on role classes, not a separate image-classification-only network. Interaction events are derived from pose/proximity and temporal rules rather than treating a pose prediction itself as an interaction label.

The repository contains two related execution paths. In the interaction CLI, `InteractionPipeline` uses the role detector and bounding-box body bands to nominate candidate pairs, and the pose model then judges each nominated pair (Section 6.4.2). Separately, `CVModels` in `backend/interaction/models.py` supports a detector and an optional pose checkpoint, and `FrameProcessor` matches pose boxes to tracked boxes and derives orientation evidence from keypoints. The head/hips/feet fallback is a geometric band-selection rule; it is not a third YOLO model and does not establish anatomical keypoint visibility. When the judge is switched off the pipeline runs on the role detector alone and candidates are reported as `unverified`.

5.2 Architectural Components

Table 5.1: Architectural components

Component	Description
Frontend	Next.js (App Router) and React pages, Tailwind CSS styling, Recharts charts, and jsPDF export. UI primitives live in `src/components/ui`.
Proxy layer	Next.js server-side routes that forward calls to FastAPI and attach the internal secret.
Shared perception tools	Person/role detection, tracking, identity association, zone geometry and pose/proximity; these are tools rather than additional business agents.
Interaction pipeline	Role-labelled detections, BoT-SORT tracking, body-height proximity with a pass-by filter, and a YOLO pose judge; runs as a local CLI and writes video and JSON outputs.
Insight Narration Agent	Target grounded metric/decision explanations; current LLM-assisted voice-script service does not establish report generation.
Customer Behavior Agent	Target customer footfall, movement, dwell and sustained hot/gray-zone demand with coverage context.
Employee Activity Agent	Target staff activity/availability and coverage; consumes interactions without equating stillness with idleness.
Interaction Agent	Current candidate, duration, pass-by and pose logic; supported approach/unattended integration remains incomplete.
Employee Task Assignment Agent	Current account/roster eligibility selection and direct task creation; source-zone protection and delivery assurance remain proposed.
Query Agent	Target authorized analytics-tool retrieval and grounded answers; not supplied by the current announcement generator.
Orchestrator	Target coordination using ordinary application code; current event/decision endpoint exists, but automatic CV feeding and full shared-state workflows are not established.

5.3 Interfaces and Dependencies

- Browser to Next.js: HTTP, with a signed HttpOnly session cookie for manager routes.
- Next.js to FastAPI: HTTP on `127.0.0.1:8011`, carrying an internal secret header added server-side.
- FastAPI to SQLite: local database files for accounts, cameras, alerts, tasks and interaction documents.
- Interaction CLI to filesystem: a local video and the model weights produce an annotated MP4 and JSON files (`.interactions.json`, `.rejected_interactions.json`, `.detections.json`, `.people.json`). Dashboard integration of these outputs is pending.
- Configuration: session-signing and internal-service secrets are supplied through environment variables and held server-side.
- Key dependencies: Node.js 18+, Python 3.12+, Ultralytics YOLO, OpenVINO, BoT-SORT/ByteTrack, Recharts, jsPDF.

5.4 Architecture Decisions and Rationale

Table 5.2: Architecture decisions

Decision	Rationale
CPU-only, lightweight YOLO	Matches hardware constraints and the target retailer.
Non-biometric classification	Privacy-conscious design and simpler compliance.
Next.js proxy with server-held secret	Keeps secrets and role checks out of the browser.
SQLite for application records	Zero-administration storage that suits a single-store prototype.
Offline/batch processing	Real-time guarantees are not feasible on CPU for the committed scope.
Body-height-normalised proximity	Needs no calibration and works on moving-camera footage; it replaced a calibrated floor homography that supported almost no projections.
Pose judge on proximity candidates	Separates a close pass-by from a face-to-face interaction; the verdict stays `unverified` when no pose is available.

5.5 Design Evolution

The mid-iteration scope is focused on person/role analysis, interaction detection and the web application, using offline/batch video processing. Three changes since the proposal matter.

1. Authentication was upgraded from client-side role flags to server-signed session cookies and an internal secret header.

2. A calibrated floor-homography prototype (commit `4a9023a`) was built to measure person separation in metres. It was descoped and removed (commit `8c3a6fe`) because the moving-camera footage supported almost no floor projections (Section 6.4.3).

3. Body-height-normalised proximity replaced it, and a YOLO pose judge was added (ported in commit `6560403`) because proximity alone reported close pass-bys as interactions (Table 7.5).

None of this creates a common cross-camera coordinate system; cross-camera association remains next-phase work.

5.6 Domain Model

Figure 5.2 shows the target business entities, agent responsibilities and their relationships. Observed tracks and roster/account users are distinct concepts; associations in this conceptual model do not establish an implemented track-to-account identity link. Assignments go directly to an employee account, with decision and task-event evidence.




Figure 5.2: RetailPulse conceptual domain model and target business relationships

5.7 Class Diagram

Figure 5.3 distinguishes the proposed agent/state classes from existing perception and operational records. It is a design view: names and associations describe intended responsibilities, while implementation/evaluation status remains in the requirements traceability table. The high-resolution source is retained for detailed zoomed inspection.




Figure 5.3: RetailPulse class design with implemented records and proposed agent/coordinator components

5.8 Deployment Diagram

Figure 5.4 places the browser, Next.js application, Python/FastAPI runtime, local data/model files and external speech/script services within their deployment boundaries. It includes repository prototype endpoints for context; their presence is not evidence that cross-camera association or automatic vision-to-workflow integration is complete. Session and internal-header controls must be verified per route, as discussed in the security requirements.




Figure 5.4: RetailPulse deployment view: client, application host, local persistence and external services

5.9 Data Design

The following selected fields were retained from the 20 October schema record and checked against current storage declarations during this requirements revision. Field presence does not prove integrated business-agent behaviour.

Table 5.3: Implemented persistence and exported record structure

Source / table	Actual fields or structure
backend/store_core.py: users	id,name,email,role,password_hash,active,created_at,updated_at
invitations	id,email,role,token,expires_at,accepted_at,created_by,created_at
zones	id,name,type,capacity,min_staff,created_at,updated_at
cameras	id,name,zone_id,role,source_type,source_url,online,created_at,updated_at
rosters	id,user_id,zone_id,shift,available,created_at,updated_at
settings; meta	key,value_json,updated_at; key,value respectively.
alerts	id,category,severity,title,context,href,status,source,evidence_json,created_at,resolved_at,resolved_by
orchestration_events	id,event_type,source,zone_id,severity,title,evidence_json,source_timestamp,created_at
dispatch_decisions	id,event_id,alert_id,task_id,selected_employee_id,decision,reason,policy_json,created_at
tasks	id,employee_id,target_zone_id,source_zone_id,instruction,state,trigger_alert_id,evidence_json,created_at,updated_at,due_at
task_events	id,task_id,state,actor_id,note,created_at
backend/interaction/storage.py: documents	kind,store_id,id,data; composite primary key on the first three columns; data contains JSON.

Source / table	Actual fields or structure
`jobs`	`id,store_id,status,created_at,data`; index `job_store` on `store_id,created_at`.
Tracked person	`track_id,bbox,confidence,role,role_confidence,role_evidence`; serialised centre derived from the box.
Interaction event	`employee_track_id,customer_track_id,started_at,last_seen_at,distance_body_heights,measured_by,active,duration_seconds`.

The standalone interaction distance is dimensionless body-height-normalised image separation. It must not be interpreted as the metres in the historical floor-homography records below. Figure E.1 shows selected implemented relationships.

5.9.1 Direct Assignment and Identity Boundaries

The target UC-36 delivers an aisle instruction directly to an identified employee account; there is no manager approval or approve/dismiss gate. Source inspection of `backend/app.py` finds `select_dispatch_employee`, `create_task_for_employee` and `/orchestrator/events`: the handler records an event, alert, policy decision and, when eligible, a task. The current event endpoint is Manager-authorized, but this is API access control, not a separate approval stage after selection. Automatic ingestion from the perception pipeline remains an integration dependency.

Protected API checks must be assessed per route: experimental frame-analysis/comparison subprocess routes do not use the same session-verification mechanism as the generic authenticated backend proxy. Their presence does not establish blanket access-control compliance. These source findings are integration/security work, not new dispatched-task approval requirements.

Selection currently filters active Employee accounts, roster availability and existing active tasks, preferring the target-zone roster. It does not establish source-zone coverage protection, shift-time eligibility, concurrency-safe duplicate suppression, oscillation control or reliable transport delivery; those are proposed acceptance scenarios, not implemented guarantees. Creation records `delivered`; the API accepts `acknowledged`, `in_progress`, `completed`, `declined`, `expired` and `cancelled`. It validates the requested state and task ownership but does not enforce a complete transition graph. A delivered row alone does not prove employee receipt, arrival or completion; the task-event stream is currently a ready-event stub.

Operational assignments refer to `users.id` through `tasks.employee_id`. An anonymous camera track/global identity does not automatically identify that account. Vision-based account location or personal activity requires a verified track-account link; no working link is claimed. Employee Activity consumes interaction context so stationary assistance does not become idle activity, while Interaction evaluates shared perception evidence independently.

5.9.2 Floor Calibration and Runtime Records (Descoped Floor Prototype)

Versioned calibration JSON stores camera/calibration IDs, the video reference and timestamp, original frame dimensions, the coordinate-space definition, metre units, image/floor landmarks, an image-to-floor homography, operational/exclusion polygons, distortion metadata, motion/smoothing settings and fitting diagnostics. Measurement-status metadata identifies estimated calibration inputs.

The local editable input is `data/calibration/queue_temp.landmarks.json`; generated calibration is `data/calibration/queue_temp.json`. The authoritative rectangle fields and original-frame landmark pixels are used to regenerate the matrix. A modified input with a stale stored matrix is rejected. Non-sensitive examples and the schema are stored under `config/cameras/`; footage, real calibration and diagnostics are excluded from Git.

Runtime JSONL records store frame index, actual decoded timestamp, camera/calibration identity, track ID, role, joint detection/class confidence, pixel box and foot point, supported floor position, motion diagnostics, pair distances and explicit rejection reasons. Unavailable positions/distances are JSON `null`. `observed_proxy` denotes an accepted box-bottom estimate, not verified foot visibility; `predicted` denotes short extrapolation and is excluded from supported pair measurements.

5.10 Process / Behavior Design

In the active standalone `backend/interaction/pipeline.py` path, `InteractionConfig` and `engagement.py` define engagement between employee/customer track pairs. The lowest common visible box band is selected: feet (65–100% of box height), hips (25–70%), then head (0–30%). The edge-to-edge Euclidean band gap is divided by mean pair box height. The default thresholds are 1.0, 0.8 and 0.6 body heights respectively, with a minimum apparent-height ratio of 0.6. Frame-edge truncation and nearer-person occlusion can invalidate bands; the edge margin is four pixels.

The candidate pair must persist for at least 2.0 seconds; a missing gap above 1.5 seconds ends continuity. This standalone proximity stage imposes no facing-angle test; in the interaction CLI it is followed by a pass-by filter and a pose judge (Section 6.4.2). Its defaults use the trained OpenVINO role model, three-second role retention and the configured BoT-SORT/ReID tracker. A separate frame-processing path has other interaction settings; those settings are not substituted for these standalone defaults. Proximity is an operational engagement heuristic, not proof of conversation or service. The proposed unattended-customer alert flow requires separate integration evidence.




Figure 5.5: Interaction detection process in the interaction CLI

Figure 5.5 summarises the interaction decision flow. Candidate nomination uses only boxes and tracks; the pose judge is the only stage that uses body keypoints.




Figure 5.6: Floor-distance localization and quality-checking pipeline

5.10.1 Floor-Distance Quality-Gating Process (Descoped Prototype)

The reference frame supports a provisional snapshot. Other frames require sufficient distributed static floor evidence within configured tolerances. A lack of matches is unverified alignment, not a stationary-camera decision. The current implementation monitors and rejects movement; it does not compensate for it. Metric smoothing cannot repair camera mapping errors. Trained roles, body-height proximity, duration and the pose judge are now combined in the interaction CLI; dashboard integration remains a future step, and proximity alone is not proof of assistance.

5.11 System Sequence Diagrams

Each SSD treats RetailPulse as one black-box system and shows only its external primary actor. Solid arrows are requests or the initial assignment notification; dashed arrows are responses. Combined fragments use `alt`/`opt` guards. Internal agents, databases, trackers and LLM calls are intentionally not extra lifelines. These are target interaction specifications, not proof that the complete capability is implemented. The implementation/evidence status remains in Chapter 4.

UC-10 and UC-20 apply to both Manager and Employee roles. UC-36 is system-initiated: the supported operational trigger is a note, and the first actor-facing message is the direct employee instruction. No employee request or manager approval is invented to start dispatch. Abbreviated camel-case operation names are conceptual system events, not claims about current endpoint names or schemas.

5.11.1 UC-01: Analyze a video

Primary capability: FR-01; detailed specification: UC-01.




Figure 5.7: System sequence diagram for UC-01: Analyze a video

Status: Implemented CLI; recorded subset. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.2 UC-02: Obtain entrance footfall

Primary capability: FR-02; detailed specification: UC-02.




Figure 5.8: System sequence diagram for UC-02: Obtain entrance footfall

Status: Target; count evaluation not established. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.3 UC-04: Analyze customer service interactions

Primary capability: FR-04; detailed specification: UC-04.




Figure 5.9: System sequence diagram for UC-04: Analyze customer service interactions

Status: Implemented candidate logic; service metrics partial. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.4 UC-07: Analyze spatial customer activity

Primary capability: FR-07; detailed specification: UC-07.




Figure 5.10: System sequence diagram for UC-07: Analyze spatial customer activity

Status: Target; demo UI. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.5 UC-10: Access a role-specific account

Primary capability: FR-10; detailed specification: UC-10.




Figure 5.11: System sequence diagram for UC-10: Access a role-specific account

Status: Implemented mechanisms; subset tested. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.6 UC-11: Monitor camera observations

Primary capability: FR-11; detailed specification: UC-11.




Figure 5.12: System sequence diagram for UC-11: Monitor camera observations

Status: Partial; recording/snapshot UI. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.7 UC-12: Review manager analytics

Primary capability: FR-12; detailed specification: UC-12.




Figure 5.13: System sequence diagram for UC-12: Review manager analytics

Status: Partial; demo/snapshot metrics. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.8 UC-13: Review personal workspace

Primary capability: FR-13; detailed specification: UC-13.




Figure 5.14: System sequence diagram for UC-13: Review personal workspace

Status: Partial; own tasks plus demo history. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.9 UC-17: Generate an insight report

Primary capability: FR-17; detailed specification: UC-17.




Figure 5.15: System sequence diagram for UC-17: Generate an insight report

Status: Target; route unavailable. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.10 UC-18: Manage operational alerts

Primary capability: FR-18; detailed specification: UC-18.




Figure 5.16: System sequence diagram for UC-18: Manage operational alerts

Status: Implemented API/UI; scenarios unverified. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.11 UC-19: Inspect system status

Primary capability: FR-19; detailed specification: UC-19.




Figure 5.17: System sequence diagram for UC-19: Inspect system status

Status: Partial; hard-coded status. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.12 UC-20: Manage personal settings

Primary capability: FR-20; detailed specification: UC-20.




Figure 5.18: System sequence diagram for UC-20: Manage personal settings

Status: UI/proposed persistence. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.13 UC-29: Configure store operations

Primary capability: FR-29; detailed specification: UC-29.




Figure 5.19: System sequence diagram for UC-29: Configure store operations

Status: Partial; stored config, incomplete consumers. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.14 UC-34: Evaluate analytical outputs

Primary capability: FR-34; detailed specification: UC-34.




Figure 5.20: System sequence diagram for UC-34: Evaluate analytical outputs

Status: Implemented; labels limited. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.15 UC-35: Assess staff availability and coverage

Primary capability: FR-35; detailed specification: UC-35.




Figure 5.21: System sequence diagram for UC-35: Assess staff availability and coverage

Status: Target contextual analysis. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.16 UC-36: Receive and update an aisle assignment

Primary capability: FR-36; detailed specification: UC-36.




Figure 5.22: System sequence diagram for UC-36: Receive and update an aisle assignment

Status: Partial backend; policy/integration gaps. Target sequence; see the use case for full alternatives and minimum guarantees.

5.11.17 UC-37: Ask an analytics question

Primary capability: FR-37; detailed specification: UC-37.




Figure 5.23: System sequence diagram for UC-37: Ask an analytics question

Status: Target; retrieval integration pending. Target sequence; see the use case for full alternatives and minimum guarantees.

Chapter 6

Iteration 1: Design and Implementation

6.1 Iteration Objectives

Build the application platform and data services that later vision analytics plug into, secure it, and demonstrate person/role analysis and interaction detection.

6.2 Selected Use Cases / Features

The revised baseline in Chapter 4 links current video-analysis and interaction evidence to UC-01/FR-01 and UC-04/FR-04, account access to UC-10/FR-10, representative monitoring/analytics/workspace views to UC-11–UC-13 and benchmarking to UC-34/FR-34. These are evidence subsets, not completion claims for all 17 target capabilities. Former FR-21–FR-28 and old UC-14 describe the retired floor prototype only, retained in Appendix B and the explicitly historical sections below.

6.3 Design

The design follows Chapter 5: a Next.js frontend with a server-side proxy, a FastAPI service for application and `/camera/*` workflows, SQLite for application records, and local person-distance diagnostics.

6.4 Implementation

The frontend follows the App Router layout, with one folder per page (landing, login, signup, dashboard, customer-info, employee-info, spatial-analytics, alerts, settings,

employee-home, my-performance, profile, about, camera-handoff, compare-people, voice-agent). Shared UI primitives (RetroWindow, RetroCard, RetroButton, Navbar, Footer) live in `src/components/ui`, and session-signing helpers live in `src/lib`. The backend lives in `backend/`.

6.4.1 Two-Model Vision Approach

The project uses two distinct YOLO model roles: a YOLO pose model supplies body-keypoint evidence for interaction analysis, while a standard YOLO object-detection model with customer/employee classes supplies person boxes and role labels. The latter is a detector trained on role classes, not a separate image-classification-only network. Interaction events are derived from pose/proximity and temporal rules rather than treating a pose prediction itself as an interaction label.

In the interaction pipeline the trained customer/employee detector (`best.pt`, run as an OpenVINO export on CPU) supplies role-labelled boxes, and the pose model (`yolov8n-pose.pt`) acts as an interaction judge: once distance and duration rules nominate an employee/customer pair, it confirms the pair only if someone's head is turned towards the other person. These responsibilities are distinct from tracking (BoT-SORT with appearance re-identification) and from the distance/duration rules that nominate candidates. The head/hips/feet approximation used when a full-person position is rejected belongs to the distance logic and should not be confused with employee/customer role classification.

6.4.2 Interaction Pipeline and Pose Judge

`python-mbackend.interaction.cli` runs the interaction pipeline on a video. Interaction detection has two stages. Proximity nominates a candidate: an employee and a customer must stay within a body-height-normalised distance (1.0, 0.8 or 0.6 body heights measured at the feet, hips or head band) for at least two seconds, and a customer whose position relative to the employee drifts by more than 0.5 body heights in that time is treated as walking past. The pose judge then takes four crops of the pair from the last two seconds and confirms the candidate only if, in at least half of them, someone's head (nose relative to the ears) points within 60° of the other person's head. If no pose is found or the judge fails, the verdict is `unverified` and the proximity result stands; a rejected pair is re-judged every four seconds while it stays close. For each video the CLI writes an annotated MP4 with an INTERACTION ON/OFF indicator, `.interactions.json` (confirmed), `.rejected_interactions.json` (vetoed), `.detections.json` and `.people.json`. `python-mbackend.interaction.benchmark` measures detector, interaction and speed KPIs (Chapter 7).

Running the interaction pipeline

Run every command from the repository root with the Python virtual environment active (Python 3.12+). The role weights `models/best.pt` and the pose weights `yolov8n-pose.pt` must be present locally; they are not stored in Git. Footage is also kept out of Git.

```
python -m backend.interaction.cli <path-to-video>
  -every 10 -track-every 3
python -m backend.interaction.benchmark
  backend/interaction/benchmarks/benchmark.json
python -m pytest backend/interaction -q
PYTHONPATH=backend python -m pytest backend/test_handoff_core.py
-q
```

`-every 10` scores every tenth frame and `-track-every 3` tracks every third frame, as used for the 11-clip run in Chapter 7. The tests report 44 passed for the interaction suites and 5 passed for the camera-handoff core.

6.4.3 Floor-Distance Command-Line Prototype (Descoped)

This prototype was implemented in commit `4a9023a` and removed in commit `8c3a6fe`; the files named in this and the following floor sections exist only in that history. It was descoped because the available moving-camera footage supported almost no floor projections, and body-height-normalised distance replaced it. The implementation reused the existing local trained `models/best.pt` weights, whose classes are employee and customer, without retraining or replacement weights. Shared loading/tracking helpers in `backend/vision_inference.py` provide the YOLO/ByteTrack inference route for the floor-distance prototype. The floor CLI selects both role classes; it does not substitute the earlier vertical-position role heuristic.

The entry points are `scripts/preview_floor_points.py`, `scripts/calibrate_floor.py`, `scripts/run_floor_distance.py`, and `scripts/evaluate_floor_distance.py`. Geometry, calibration diagnostics, motion monitoring, metric smoothing and evaluation are separate backend modules. The preview runs without calibration; the distance demo exports only supported metre observations and explicit unavailable states. No frontend changes were needed for this prototype.

6.5 Completed Features / Module

Table 6.1: Features completed in Iteration 1

Feature	Detail	Status
Manager dashboard pages	Dashboard, Customer Info, Employee Info, Spatial Analytics, Alerts, System Status, Settings	Done (prototype data for vision metrics)
Employee workspace	My Workspace and My Performance with rubric and daily log	Done (prototype data)
Shared pages	Landing, Login/Signup, About, Profile	Done
Reports	Configurable builder, narrative summary, PDF export	Not on tested branch (route returns 404)
Secure access	Stored accounts (PBKDF2 password hashes), signed HttpOnly session cookie and internal secret header	Done
Floor-distance prototype	Trained roles/track IDs, foot preview, calibration, alignment checks and diagnostic exports	Implemented, then descoped (`8c3a6fe`)
Interaction pipeline	Trained role detector, BoT-SORT tracking, body-height proximity, pass-by filter and YOLO pose judge; annotated video and JSON outputs	Implemented (local CLI)
Benchmark	Detector, interaction (with and without the judge) and speed KPIs	Implemented

6.6 Technical Implementation Details

Running the system. `npm run dev:all` starts Next.js on port 3000 and FastAPI on `127.0.0.1:8011`. `npm run backend:api` starts the application backend and its `/camera/*` routes. The package scripts use Unix-style environment assignment; Windows users should use the documented platform-compatible launcher or set environment

variables explicitly.

Authentication. Login verifies stored account credentials and creates a server-signed HttpOnly session cookie. Protected manager backend routes require the signed session and server-side role checks. Internal secrets are supplied through environment variables. The executed access-control checks are recorded in Chapter 7.

6.6.1 Calibration Configuration and Coordinate Conventions (Floor Prototype)

Detections use original-frame $[x_1, y_1, x_2, y_2]$ pixels. Ultralytics already restores xyxy boxes after preprocessing, so coordinates are not unletterboxed again. Frame/configuration dimension mismatches, invalid projections and stale homographies are rejected. No lens undistortion is applied; calibration and runtime share the same distorted pixel space. Intrinsic/distortion metadata slots are retained, but correction would require an explicitly consistent update of both paths.

The provisional rectangle follows A–B–D–C: AB = DC = 3.13225 ft and BD = CA = 4.2075 ft, equivalent to width 0.9547098 m and depth 1.282446 m. The configuration records the rectangle geometry and estimated lengths. Dot centres in the 479-by-479 marked screenshot were mapped to the original 1080-by-1080 video using pixel-centre resize coordinates. Frame zero was selected after image-difference comparison and visual inspection; the resized/modified screenshot correspondence remains approximate. Operational coverage is restricted to the marked rectangle.

The rectangle dimensions and original-pixel points are editable in configuration. Regeneration writes the image-to-floor matrix and fitting diagnostics without changing trained weights. Saved measurements are labelled estimated, calibration is provisional and runtime values are approximate. Point-click selection supports numbered correspondences, undo, reset and save; the headless JSON route was exercised.

6.6.2 Reproducible Execution (Floor Prototype)

These commands ran at commit `4a9023a`; the scripts are not on the current branch. From the repository root, use the existing virtual environment. The following three command groups reproduce the sampled temporary-video workflow; join wrapped continuation lines when entering each command:

```
.venv/Scripts/python.exe scripts/preview_floor_points.py
  -video data/videos/raw/queue_temp.mp4 -sample-every 30
-headless
```

```
.venv/Scripts/python.exe scripts/calibrate_floor.py
  -video data/videos/raw/queue_temp.mp4 -timestamp 0
  -landmarks data/calibration/queue_temp.landmarks.json
  -output data/calibration/queue_temp.json -headless
.venv/Scripts/python.exe scripts/run_floor_distance.py
  -video data/videos/raw/queue_temp.mp4
  -calibration data/calibration/queue_temp.json
  -motion-mode monitor -sample-every 30 -headless
```

The displayed line breaks are for typesetting; join continuation lines when entering a command. The output directory contains annotated video, top-down video, JSONL observations and summary/coverage records. Actual decoded timestamps are exported. Repository usage instructions are in `docs/floor_distance_usage.md`.

6.7 Algorithms and Technical Decisions

6.7.1 Person Floor-Position Approximation (Floor Prototype)

For a box $B = (x_1, y_1, x_2, y_2)$, the homogeneous floor-contact proxy is

$$\mathbf{p} = \begin{bmatrix} (x_1 + x_2)/2 & y_2 & 1 \end{bmatrix}^{\mathsf{T}}. \tag{6.1}$$

This is an observed proxy rather than proof that feet are visible. Boundary truncation, person overlap and manual exclusion polygons provide provisional rejection signals; seated people and chair occlusion remain limitations. An optional future foot/keypoint locator can replace this step without changing the projection interface.

6.7.2 Homography-Based Projection and Distance (Floor Prototype)

An image-to-floor homography maps the proxy into metre coordinates [11, 12]:

$$\mathbf{q} = H_{\text{image}\to\text{floor}}\mathbf{p}, \qquad X = q_1/q_3, \quad Y = q_2/q_3. \tag{6.2}$$

Non-finite values or a denominator near zero are rejected. For two supported observations from the same camera and timestamp,

$$d_{AB} = \sqrt{(X_A - X_B)^2 + (Y_A - Y_B)^2} \quad \text{metres}. \tag{6.3}$$

Four non-degenerate landmark pairs provide a direct calibration fit. With additional correspondences, the implementation fits floor-to-image using RANSAC with an explicit pixel-

space threshold, then inverts the result [14]. Inliers and fitting residuals are exported as calibration diagnostics.

6.7.3 Camera Alignment and Measurement Reliability (Floor Prototype)

The monitor compares ORB features [15] within the supported floor region, masking detected people and manual exclusions. Matches are checked using RANSAC, inlier count/ratio, spatial spread, residual displacement and supported-region displacement limits. Insufficient evidence produces `motion_unverified`; supported alignment shifts produce `motion_invalid`. Neither state allows a supported metre output. Modes `monitor` and `fixed` both enforce these checks; `snapshot` supports only the reference frame. Motion compensation is deferred because reliable distributed floor evidence was not established on the temporary clip.

Accepted positions are smoothed in metres using timestamps. Configurable speed/jump gates, short prediction limits, a separate last-reliable-observation time and track expiry preserve quality information. Predictions are excluded from supported pair distances, and alignment failures clear smoothing state. Role labels remain separate observations from the trained detector; their confidence is the joint detection/class score, not two independent probabilities. Selected track pairs or a capped set of all pairs can be exported.

6.8 Tools, Frameworks and Technologies

Table 6.2: Technology stack

Layer	Technology
Frontend	Next.js (App Router), React
Styling	Tailwind CSS, custom retro-industrial design system
Charts	Recharts
Computer vision	YOLO pose model as interaction judge; trained YOLO role detector (OpenVINO, CPU), BoT-SORT with ReID, OpenCV, NumPy; `lap` for tracking assignment; OpenCV homography/ORB in the descoped floor prototype
Application and camera API	FastAPI, SQLite
Fonts	Space Grotesk, Inter, JetBrains Mono
Runtime	Node.js 18+, Python 3.12+ (virtual environment)

6.9 Demonstration Evidence

Local UI screenshots were captured on 20 October 2026 using isolated test databases. The displayed analytics are demonstration data, not measured vision accuracy. The PDF-report route returned HTTP 404 on the tested branch, so no screenshot is claimed for that feature.

6.9.1 Interaction Pipeline Output

Figure 6.5 shows annotated output of the current interaction CLI on two local clips.

6.9.2 Floor-Distance Demonstration (Descoped Prototype)

Figures 6.6–6.8 show actual local prototype outputs from commit `4a9023a`. They demonstrate inference, calibration visualization and export.




Figure 6.1: Manager dashboard with demonstration values




Figure 6.2: Customer information view with demonstration values




Figure 6.3: Employee information view with demonstration values




Figure 6.4: Employee workspace after authenticated employee login




Figure 6.5: Interaction pipeline output. Left (IMG_8880, 30 s): employee and customer facing each other during a handover; the pose judge confirms the interaction. Right (IMG_8829, 8 s): employee and customer close together but walking away side by side; the pose judge rejects the candidate and the indicator stays OFF.




Figure 6.6: Trained role detections and track IDs with box-bottom proxies; uncalibrated preview




Figure 6.7: Provisional A–B–D–C calibration and floor grid based on estimated dimensions




Figure 6.8: Approximate top-down person-position proxies in the reference snapshot

6.10 Target Architecture and Iteration Boundary

The seven agreed agent/coordinator names in Chapter 5 describe the target design. Perception algorithms are shared tools; they are not extra business agents. Current account/alert/task endpoints and the interaction CLI provide partial foundations. Direct account-based dispatch already has a backend path, while vision-trigger integration, reliable track-account linking, staff coverage protection, Query Agent retrieval and complete reporting remain unverified or planned. No manager approval step is introduced. Historical demo scores are UI data, not a mandatory staff-ranking requirement.

6.11 Iteration Outcome

Iteration 1 covers the application platform, role-aware access, person/role analysis, interaction cues and the distance-estimation prototypes. The vision-derived dashboard metrics still use prototype data, and binding them to real agent output is the first goal of Iteration 2.

The floor-distance CLI prototype demonstrated trained role detection, tracking, provisional calibration and conservative metric export; it was descoped because the moving-camera footage supported almost no floor projections, and body-height-normalised distance replaced it. The interaction pipeline now combines trained roles, proximity, duration and a pose judge.

Chapter 7

Testing and Early Validation

7.1 Testing Strategy

Testing combines functional checks of implemented modules, integration checks across the proxy, backend, and database, security checks of access control, and, in FYP-2, quantitative evaluation of the vision agents against manually labelled clips.

7.2 Test Levels and Techniques

- **Unit level:** role/classification, engagement, pass-by, pose-judge, tracking and benchmark-metric checks with known synthetic inputs; the focused floor-geometry, failure-state, smoothing, motion and evaluation checks belonged to the descoped floor prototype.
- **Vision CLI integration:** actual trained weights and local video, exported video readability, JSONL invariants and explicit unavailable-state checks.
- **Integration level:** frontend to proxy to FastAPI to SQLite for account/application flows.
- **System level:** end-to-end use of dashboards, reports and person-analysis outputs.
- **Security testing:** direct calls without cookie or secret.
- **Vision evaluation:** detector KPIs on a held-out split and interaction precision/recall against labelled clips through `backend/interaction/benchmark.py`; broader labelled evaluation continues in FYP-2.

7.3 Test Cases

Table 7.1: Test case summary

ID	Test	Expected result	Req.
TC-01	Log in as Manager using a valid existing account	Session cookie set; manager pages open	FR-10
TC-02	Open a protected manager application route without a cookie, or call backend without the secret	Request rejected	NFR-07/08
TC-07	Person detection on a labelled clip	Detection precision/recall reported	FR-01
TC-08	Staff/customer classification on a labelled clip	Accuracy reported	FR-01
TC-09	Controlled clip with unattended customer	Unattended flag and alert raised	FR-04
TC-10	Path and dwell on a labelled clip	Zone dwell matches annotation within tolerance	FR-07
TC-12	Representative manager/employee page checks	Recorded pages render; role checks assessed only within the tested subset	FR-10–FR-13 (subset)
TC-13	Build report and export PDF	PDF contains selected sections and narrative	FR-17
TC-14	Uncalibrated trained-model preview	Role labels, IDs and foot proxies exported without fabricated metres	Historical FR-21
TC-15	Headless landmark calibration	Provisional H, grid and floor map generated	Historical FR-22/26
TC-16	Interactive point selection	Ordered clicks, undo/reset/save preserve original pixels	Historical FR-22
TC-17	Known geometry and preprocessing	Expected projections, metre units and coordinate recovery	Historical FR-23; NFR-11
TC-18	Invalid/unsupported positions	Explicit unavailable states rather than zero distances	Historical FR-24; NFR-11

ID	Test	Expected result	Req.
TC-19	Camera alignment / no features	Shifted and unverified frames suppress supported output	Historical FR-25
TC-20	Demo and diagnostic exports	Readable videos, timestamps and approximate/provisional labels	Historical FR-27/28
TC-21	Pose judge decision logic	Facing heads confirm; heads turned away or backs to camera reject; no pose or a failing judge keeps the proximity result as `unverified`	FR-04
TC-22	Pass-by and moving-camera cases	A customer walking past produces no interaction; a pair under a panning camera still interacts	FR-04
TC-23	Benchmark metric functions	One-to-one temporal-IoU matching; correct precision, recall and F1	FR-34
TC-24	Interaction CLI on the local clip set	Every clip completes; annotated video, confirmed and rejected interactions written	FR-01; FR-04 evidence; NFR-02
TC-25	Repeat run with the same inputs	Byte-identical JSON outputs for the recorded clip; stricter than numerical tolerance	NFR-01 supporting case

Detailed steps are in Appendix C.

7.4 Proposed Capability Scenarios

The revised baseline maps TC-07/08 to FR-01, TC-09/21/22 to FR-04, TC-10 to FR-07, TC-23 to FR-34 and diagnostic TC-24 primarily to FR-01. Detector results do not validate FR-02 crossing counts. TC-14–TC-20 are historical floor-prototype evidence, not active acceptance. New TC-26–TC-48 in Appendix C are Planned / Not executed;

they cover unverified functional and NFR concerns, including direct dispatch without an approval gate and authorized Query Agent retrieval. Recorded Passed, Pending, Partial and Unavailable outcomes below are unchanged.

7.5 Test Results

Table 7.2: Test execution status at mid-report

Test	Result	Notes
TC-01	Passed	Actual manager/employee account login, cookie flags, logout and wrong-credential rejection checked.
TC-02	Passed, adapted	Current settings proxy: anonymous 401, missing/wrong backend secret 401, employee access 403.
TC-13	Unavailable	Report/PDF route absent on current branch; corresponding route returned 404.
TC-12	Partial	Representative manager/employee views captured. Exhaustive role navigation not completed.
TC-07, TC-08	Measured	Held-out split (455 images): precision 0.963, recall 0.953, mAP50 0.969 (Table 7.4).
TC-09, TC-10	Pending	Unattended flags and trajectory are not yet produced (Iteration 2).
TC-21–TC-23	Passed	7 pose-judge, 2 pass-by (within the 8-test engagement suite) and 3 benchmark-metric tests.
TC-24	Passed	11 clips: 19 candidates, 17 confirmed, 2 rejected (Table 7.6).
TC-25	Passed	IMG_8829 JSON outputs byte-identical across two runs.

The application cases above were executed on 20 October 2026 against isolated SQLite databases and local development servers. All 15 retained in-scope HTTP assertions passed, including one assertion that the removed report route returned 404; that assertion is an absence check, not a feature pass. The role, engagement, identity and tracker suites were rerun for the corrected mid-iteration scope: 24 tests passed in 2.66 seconds.

After the pose judge and benchmark were added, all interaction suites were rerun with pytest: 44 tests passed in 1.72 seconds (engagement 8, role classifiers 4 and 5, identity 4, tracker 5, pose judge 7, benchmark 3, frame processor 8). UI screenshots substantiate representative views only. Three warm login HTTP requests took 69.86, 77.12 and 82.83 ms (median 77.12 ms); these exclude compilation, rendering and inference and do not establish a dashboard performance requirement.

Version boundary. Commit `8c3a6fe` removed the calibrated floor-distance source on 20 October. The floor results below preserve the earlier implementation evidence; they are not a successful rerun of removed source at current HEAD. The floor-distance software/integration evidence below was executed during the 19–20 October 2026 implementation session. The results below describe software checks, integration behavior and accepted-position coverage.

7.5.1 Floor-Distance Software and Integration Results

Table 7.3: Executed floor-distance checks and temporary-video coverage

Check / quantity	Actual result
Focused floor-distance automated suite (TC-17–TC-19 and evaluation functions)	17 tests passed; synthetic geometry/failure cases, smoothing/prediction, alignment shifts and error statistics.
Actual trained-model preview (TC-14)	Completed with local `models/best.pt`; no retraining.
Headless calibration (TC-15)	Completed; grid and versioned provisional calibration saved.
Point-click calibration (TC-16)	Point-selection interface implemented.
Sampled clip execution (TC-20)	148 processed frames, sampling every 30 source frames across the clip.
Detection observations	284 repeated observations, not 284 unique people.
Frame alignment outcomes	1 reference snapshot; 9 motion-invalid frames; 138 unverified frames.
Accepted position observations	2 of 284, approximately 0.70% accepted coverage.
Available approximate pair observations	1 reference-frame pair, including a seated-person proxy.

Check / quantity	Actual result
Video/record verification	Both 148-frame videos decode through the final frame; timestamps increase; unsupported positions have null coordinates.
Snapshot / missing-track behavior	Three-frame check preserves explicit unavailable selected-pair records.
Missing-weight handling	Actionable local missing-model error verified.

The executed commands are documented in `docs/floor_distance_usage.md`. The coverage summary is exported as `data/outputs/distance/demo/summary.json`, with observation records in `metrics.jsonl`. The 0.70% value is accepted-position coverage, not accuracy. The reference pair is an approximate box-proxy demonstration involving a seated person. No whole-clip supported metric result is claimed.

7.5.2 Interaction Pipeline and Benchmark Results

The benchmark (`backend/interaction/benchmark.py`) was run on 20 October 2026 on a CPU-only laptop, scoring and tracking every tenth frame; the full report is `evidence/benchmark_20261020.json`.

Table 7.4: Detector KPIs on the recording-level held-out split (455 images)

Class	Precision	Recall	mAP50	mAP50-95
All	0.963	0.953	0.969	0.896
Employee	0.968	0.990	0.982	–
Customer	0.958	0.916	0.955	–

Table 7.5: Interaction accuracy on the labelled clip (IMG_8829)

Decision	Precision	Recall	F1	TP / FP / FN
Proximity alone	0.50	1.00	0.67	1 / 1 / 0
Proximity + pose judge	1.00	1.00	1.00	1 / 0 / 0

The false positive removed by the judge is the 1.7–15.3 s segment in which the employee and customer walk away side by side (Figure 6.5, right). One clip with one true interaction

shows the judge's effect; it does not establish accuracy. IMG_8829 is in the detector's training split, so it is used for interaction KPIs only.

Table 7.6: Interaction CLI on 11 local clips (scored every 10th frame, tracked every 3rd)

Clip	Candidates	Confirmed	Rejected	Duration (s)	Realtime
IMG_8829	2	1	1	8.0	1.40×
IMG_8878	2	2	0	15.7	1.54×
IMG_8880	1	1	0	25.3	1.41×
IMG_8881	3	3	0	38.0	1.31×
IMG_8885	0	0	0	0	1.37×
IMG_8886	1	1	0	6.7	1.23×
IMG_8890	2	2	0	31.7	1.40×
IMG_8893	3	2	1	37.0	1.43×
IMG_8894	1	1	0	26.7	1.16×
IMG_8895	3	3	0	19.7	0.80×
IMG_8897	1	1	0	23.0	1.23×
Total	19	17	2	231.8	

Candidates, confirmations and durations are from the CLI run; the realtime factor is from the benchmark run, which also tracks every tenth frame. Ten of the 11 clips are not labelled, so their counts are pipeline outputs, not accuracy; their candidates are listed in `evidence/interaction_judge_batch_20261020.csv` for labelling. No candidate was `unverified`. Per-frame latency was 120–171 ms at the median, and judge calls took 226–401 ms each, except on IMG_8895, where they took about 893 ms; that clip missed the benchmark's 1.0× realtime target and should be re-measured. With tracking on every third frame, processing ran at 0.50–0.59× realtime.

7.6 Acceptance Testing / Validation

Acceptance follows the criteria in Chapter 4. We showed the supervisor the 70-video dataset, which he agreed to; this was the material he requested. The dataset was approved at the supervisor meeting on 12 October 2026. The separate client meeting was on 10 September 2026; see Appendix F. No numeric accuracy or response-time targets were agreed. This is dataset approval rather than acceptance of measured classification, interaction or dashboard performance. Executed local checks and screenshots provide the separate software evidence.

7.7 Edge and Failure Cases

- Staff outside their usual zone or customers in uniform-like clothing, affecting classification.
- Identity switches during occlusion, affecting dwell and interaction durations.
- Expired or missing session cookie.
- Depth ambiguity in the interaction pipeline: people at different depths whose boxes overlap can appear close, and a head turned only slightly can pass the 60° facing test (IMG_8878 at 36 s).
- Identity switches on a moving camera split one customer into several track IDs and one interaction into several (IMG_8881, IMG_8895).
- Duplicate/collinear landmarks, invalid homogeneous denominators, incompatible units or frame sizes, stale homography and extrapolation outside calibrated coverage.
- Lower-frame truncation, manual exclusions, person overlap and seated/occluded feet; box-bottom positions remain proxies.
- Missing selected tracks, predicted positions, implausible metric jumps and expired reliable observations.
- Camera shifts, insufficient floor matches or poor spatial spread: preserve unavailable measurements rather than reuse stale alignment.

7.8 Defects and Corrective Actions

The first actual tracking run exposed a missing `lap` assignment dependency; it was installed into the existing virtual environment and declared in backend requirements, after which ByteTrack inference completed. Reference-frame selection was changed to use media timestamps rather than assuming constant-rate timing. A stale-calibration guard and explicit illustrative-config rejection prevent accidental use of incompatible inputs. During the current application checks, the development frontend exhausted a 768 MB Node heap; it was restarted with a 2048 MB heap, without modifying application source. The interaction CLI originally appended an active interaction once per scored frame; it now keeps one record per interaction. Annotated videos written while skipping frames keep the source frame rate and play faster than real time; review copies were re-encoded

at the true rate. Exhaustive page navigation was not completed. The first unit-test attempt encountered SQLite permission errors in the sandbox temporary directory; using a writable repository-local temporary directory resolved the temporary-directory issue; the corrected-scope rerun subsequently passed 24 tests.

7.9 Current Validation Status

The floor-distance prototype passed its focused synthetic software checks and actual-model/video integration checks before it was descoped. The moving temporary clip supported only the calibration-reference snapshot; the remaining sampled frames were motion-invalid or unverified. The exported quality states distinguish supported approximate positions from unavailable measurements. Trained roles, body-height proximity, duration and the pose judge are now combined in the interaction pipeline, which runs on all 11 local clips; its accuracy is measured on one labelled clip only, and dashboard integration is pending.

Chapter 8

Project Management and Development Evidence

8.1 Work Completed

- Next.js application with manager, employee, and shared pages.
- Role-aware access with signed session cookies and an internal secret header.
- Trained-role/ByteTrack foot-point preview and provisional floor-distance CLI: editable calibration, motion/reliability checks, metric smoothing and diagnostic exports (since descoped).
- Two-stage interaction pipeline: trained role detector, BoT-SORT tracking, body-height proximity with a pass-by filter, and a YOLO pose judge; plus a benchmark for detector, interaction and speed KPIs.
- Executed 17 historical focused floor-distance checks; 44 current interaction unit tests and 5 handoff tests pass; detector benchmarked on 455 held-out images and the interaction pipeline run on 11 local clips.

8.2 Work Remaining

Integrating the vision agents with the dashboard, labelled detector/interaction evaluation, the Insight Narration agent on real data, and hardening. Details are in Chapter 9.

8.3 Individual Responsibilities

Table 8.1: Responsibilities

Member	Responsibility
Moiz Ansari (23I-0523)	Frontend; distance between people; head, hips and feet band handling when the full-person position is rejected
Saqib Atif (23I-0769)	Customer/employee pose detection and testing
Ruhab Ahmad (23I-0559)	Frontend, report and classification

8.4 Contribution of Each Team Member

Moiz worked on frontend development, person-to-person distance and the head/hips/feet band approach for rejected full-person positions; Saqib worked on customer/employee pose detection and testing; Ruhab worked on frontend development, the report and classification. The head/hips/feet categories describe body regions used for distance estimation, not employee/customer role classes.

Git records attribute the provisional floor-distance implementation (`4a9023a`) and report addition (`80fb3fd`) to Moiz Ansari. They attribute the interaction detector (`e3fe2af`) and video-verification record (`6c25090`) to Ruhab Ahmad. The Git author `msaqibatifj` is recorded for temporal role classification (`882f7dc`), the shared OpenVINO model (`e2b71a5`) and moving-camera engagement (`face2b5`). Git author names are shown as recorded. These are commit-author records, not a claim that each author exclusively performed every change or a complete account of non-code work.

8.5 Repository and Version Control Evidence

The project is kept in the Git repository `muhammad-moiz-ansari/retail-store-analysis` on GitHub. Work is organised on feature branches, and this report corresponds to the `feature/interaction` branch, inspected on 20 October 2026 at commit `6560403`.

8.6 Milestones and Commit Evidence

The actual floor-distance implementation commit is `4a9023a` (19 October 2026, Moiz Ansari), titled “feat(vision): add provisional floor-distance estimation pipeline”. A later

commit removed the calibrated floor-distance pipeline (`8c3a6fe`, 20 October), attributed to Git author `msaqibatifj`. Therefore historical implementation evidence must be read with its commit context. The on-screen interaction flag and one-record-per-interaction output were committed on `feature/interaction-flag` (`20db4c6`, `ee7947f`, `0411408`, 19 October 2026, Git author `msaqibatifj`); the pose judge and benchmark were developed there and ported to `feature/interaction` in commit `6560403` (20 October 2026), after unused code was removed in `cffa30b`. No Git tags were present in the inspected repository. Selected commit and author-count evidence is reproduced in Appendix D; no project-board or supervisor milestone evidence is inferred from commit dates.

8.7 Tools and Tool-Assisted Development

Development tools include Node.js and npm, a Python virtual environment, Git and GitHub, and the libraries listed in Chapter 6. We also used generative-AI assistants, disclosed in Table 8.2.

Table 8.2: Generative-AI tool use and verification

Tool	Used for	How the output was checked
Codex	Floor-distance implementation (since descoped), diagnostic runs, and revision of the report source.	Focused automated tests, local trained-model/video runs, inspection of preview and grid outputs, export readability and record-invariant checks.
Claude Code	Porting the pose judge and benchmark to the main branch, the batch and benchmark runs, and the 20 October report revision.	Automated tests, a byte-identical comparison of pipeline outputs before and after the port, and inspection of annotated frames.
Claude	General AI/development assistant.	Reviewed by the team member who owns the affected module (Table 8.1).

AI assistance does not replace the recorded test and review evidence, and each team member must be able to explain the code and text in the area they own.

8.8 External Components and Dependencies

Table 8.3: External components

Component	Use
YOLO implementation [7]	YOLOv8n pose model as interaction judge; standard YOLO detection for customer/employee classes
OpenVINO	CPU inference runtime for the role detector
ByteTrack [9] / BoT-SORT	Per-camera tracking (BoT-SORT with appearance re-identification in the interaction pipeline); `lap` supplies assignment support
OpenCV / NumPy [12]	Image processing and video input/output; homography fitting, projection and ORB matching in the descoped floor prototype
ORB [15] and RANSAC [14]	Reference-alignment evidence and robust fitting in the descoped floor prototype
FastAPI [16]	Application and camera API
Next.js and React [17]	Frontend
Recharts, Tailwind CSS	Charts, styling
SQLite	Application, job and interaction storage

Table 8.4: Dependency licence review from installed metadata and upstream notices, 20 October 2026

Component	Licence / scope
Ultralytics implementation	AGPL-3.0 or a separate Enterprise licence, according to its publisher [18]. Academic use does not by itself remove applicable obligations.
Original ByteTrack repository	MIT [19]; this does not replace the licence of the Ultralytics implementation used by the project.
OpenCV	Apache-2.0 for current releases [20].
OpenVINO	Apache-2.0 (installed metadata, version 2026.4.1).
FastAPI, pytest	MIT (installed distribution metadata).
Uvicorn, HTTPX; lap	BSD-3-Clause; BSD-2-Clause for lap (installed metadata).

Component	Licence / scope
NumPy and PyTorch	BSD-family and bundled-component notices; retain the complete installed distribution notices rather than assuming a single licence covers every component.
Pillow	MIT-CMU (installed metadata).
Next.js, React, ReactDOM, Recharts, Tailwind CSS	MIT (installed package metadata).
Inter, Space Grotesk, JetBrains Mono	SIL Open Font License 1.1 [21, 22, 23].
SQLite	Public-domain software; the application's data rights remain separate.

This is a dependency-notice inventory, not a certification of licence compliance or ownership of trained weights/video. Distribution should preserve applicable notices and satisfy the relevant licence terms. Versions installed during testing can differ from manifest ranges; the test environment contained Next.js 16.3.3, React 19.2.8 and Ultralytics 8.4.138.

8.9 Risks and Mitigation

Table 8.5: Risk register

Risk	Level	Mitigation
CPU-only inference too slow	High	Frame sampling, small models, batch processing
Staff/customer misclassification	High	Zone rules plus appearance, labelled evaluation, manager review
Limited footage for evaluation	Medium	Record or label additional clips early in FYP-2
Integration slippage	Medium	Bind one agent at a time, keep prototype data fallback
Privacy or misuse concerns	Medium	Non-biometric design, decision-support framing
Depth ambiguity in a single image	High	Height-ratio check and pose judge; labelled evaluation; reported as a limitation
Identity switches on moving footage	High	BoT-SORT re-identification and relinking; count split interactions during evaluation
Pose judge too lenient or too strict	Medium	Benchmark with and without the judge; tune facing angle and fraction on labelled clips

8.10 Security and Privacy Considerations

Manager routes require a signed HttpOnly session cookie, and direct backend calls require an internal secret header that only the server-side proxy supplies. Secrets come from environment variables. The current login verifies stored account credentials; the earlier arbitrary-email/six-character demo rule no longer describes the tested implementation. The access-control checks are described in Chapter 7.

Floor footage, calibration frames/configuration and generated diagnostics remain local under Git-ignored data directories. The report includes only selected local demonstration frames; no footage upload, persistent person crops or facial-identity records are required by the prototype.

8.11 Current Limitations

- Vision-derived dashboard metrics still use prototype or demo data; system status is available as a backend endpoint only.
- The pipeline is offline/batch, not real time.
- Single-store prototype; no multi-store deployment is claimed.
- Current authentication uses stored accounts; role-navigation checks cover representative views rather than every application route.
- The floor-distance prototype was descoped, so no distances in metres are produced; interaction distance is relative to body height and cannot fully resolve depth.
- Interaction accuracy is measured on one labelled clip only; identity switches on moving footage can split one interaction into several.
- Interaction results are available through the CLI; dashboard integration remains pending.

Chapter 9

Remaining FYP Plan

9.1 Remaining Scope

Integrate and evaluate the vision agents, bind real outputs to the dashboard, and prepare the final demonstration. Items listed as out of scope in Chapter 1 remain future work.

9.2 Remaining Modules and Features

- Integrate and evaluate Customer Behavior Agent, Employee Activity Agent, Interaction Agent and Employee Task Assignment Agent; detection, classification and interaction detection with the pose judge are already implemented in the interaction CLI.
- Evaluate interaction detection (proximity, duration, pass-by filter and pose judge) on labelled clips, including close pass-bys that are not assistance; ten local clips await labels.
- Insight Narration Agent and Query Agent over authorized real analytics; Orchestrator coordination using application code, with integration/evidence status tracked separately.
- Real data in Dashboard, Customer Info, Employee Info, Spatial Analytics, Alerts, and System Status.
- Implement camera handoff in the next phase: associate a person leaving one camera with a person entering another using timing, direction and appearance evidence. This is outside the mid-iteration deliverables; ambiguous associations must remain unresolved. An experimental two-camera handoff script and `/camera/*` job routes already exist.

9.3 Remaining Iterations

Table 9.1: Planned FYP-2 iterations

Iteration	Focus
2	Vision-component integration, real data in dashboard pages and planned cross-camera association
3	Evaluation on labelled clips, tuning of thresholds and heuristics, alerts on real events
4	Hardening, security, performance, documentation, and final demonstration

9.4 Implementation Plan

Bind agents one at a time to the dashboard, beginning with shared perception and Customer Behavior footfall, then Interaction, Employee Activity and direct account-based task assignment, keeping prototype data explicitly labelled until each capability passes its checks. Do not equate detected employee tracks with task-recipient accounts; verify the linkage and source-zone safety policy before location-based selection. Develop and evaluate cross-camera association separately from same-camera interaction detection.

9.5 Testing and Validation Plan

Label a set of clips for staff/customer, interactions, and zone dwell. Report precision, recall, and error analysis per agent. Re-run Appendix test cases after each integration and record results. Check performance on CPU and record throughput.

9.6 Deployment Plan

The deliverable is a local deployment run with the documented `npm run dev:all` flow and production build commands (`npm run build`, `npm start`). A pilot with a real retail partner is future work.

9.7 Tentative Timeline

Table 9.2: Tentative FYP-2 timeline (to be confirmed with the supervisor)

Period	Activity
Weeks 1–3	Detection and footfall integration
Weeks 4–6	Classification and engagement integration
Weeks 7–9	Trajectory, narration, dashboard binding
Weeks 10–12	Labelled role/interaction evaluation and tuning
Weeks 13–14	Hardening, security, documentation
Weeks 15–16	Final testing, demonstration, and report

9.8 Expected Final Deliverables

- Working RetailPulse system with real vision analytics and role-aware web access.
- Evaluation report with detector and interaction results (with and without the pose judge) and CPU throughput.
- Source repository with documentation and run instructions.
- Final report and demonstration.

Chapter 10

Conclusion

Retailers hold CCTV footage that could answer everyday operational questions but is rarely used for that purpose, and small and mid-sized stores often cannot afford specialised analytics. RetailPulse addresses this with a CPU-friendly, non-biometric, multi-agent design that reuses existing cameras. Research on detection, tracking, and re-identification, and a feasibility triage, shaped the scope: a single-store, three-camera prototype focused on person detection, role identification and pose-checked interaction detection.

At the mid-report stage the requirements and architecture are defined. The web application with manager and employee roles, secure session handling and person-analysis prototypes form the current implementation; report export remains a planned feature on the tested branch. An interaction pipeline combines the trained employee/customer detector, body-height-normalised proximity and a YOLO pose judge that evaluates facing evidence while retaining unverified proximity fallbacks; on the one labelled clip the judge raises interaction precision from 0.50 to 1.00, and the detector reaches mAP50 0.969 on 455 held-out images. A floor-distance CLI passed seventeen focused checks before it was descoped, and 44 current interaction unit tests pass. Dashboard vision metrics still rely on prototype data. The main risks are CPU throughput, classification accuracy, and interaction interpretation. FYP-2 will integrate the vision agents, evaluate them on labelled store footage, and harden the system for the final demonstration.

Appendix A

Proposal Action Register

The response register is in Chapter 3. The following comments are the proposal-defence feedback of 11 September 2026 as recorded by the team. No signed feedback form is attached.

A.1 Comments / Recommended Modifications

> Students have no clue what they are doing. Technical knowledge is lacking. The students do not have an understanding of the project. Students need to learn more about the requirements of the project and next time be well prepared. Should work on their presentation skills; the presenters kept pacing back and forth. Their project was poorly explained, there was no clarity on the exact features, and the overall idea was unclear. Also, they did not defend the generalizability of their project; the behavioral requirements of employees vary from retail to retail store (for example, luxury brands like Gucci, Prada, etc. don't want their employees to be constantly approaching customers), so how is their project universal for all types of retail stores? Improve your skills. It is a healthy project if it is properly focused.

A.2 Response Priorities

Improve technical preparation and feature explanations; focus the project; justify store-specific behavioural interpretation; rehearse a clearer presentation. The action register distinguishes report changes from work still planned, rather than treating the feedback as resolved solely by adding text.

Appendix B

Requirement Consolidation and Historical Register

B.1 Identifier Policy and Old-to-New Mapping

Exactly 17 active FR/primary UC pairs are defined in Chapter 4. Current UC suffixes match their FRs. Previous UCs used a different grouping: old UC-01 login maps to UC-10; old UC-02 camera view to UC-11; old UC-03/04 manager customer/staff views and old UC-05 spatial presentation to UC-12, with calculation responsibilities in UC-04/07/35; old UC-08 reports to UC-17; old UC-09 alerts to UC-18; old UC-10 status to UC-19; old UC-11 personal performance to UC-13; old UC-13 settings to UC-20. Historical UC-14 calibration is not an active UC. Removed out-of-scope identifiers are not reassigned to unrelated functions.

Table B.1: Functional requirement consolidation and retirement mapping

Previous item	Current destination	Treatment
FR-01, FR-03, FR-33	FR-01 / UC-01	Merge detection, role-labelled tracking and diagnostic export into video analysis; old FR-03/33 are no longer separate active definitions.
FR-02	FR-02 / UC-02	Retain entrance footfall; detector precision does not establish crossing-count accuracy.

Previous item	Current destination	Treatment
FR-04, FR-05, FR-30–FR-32	FR-04 / UC-04	Merge service analysis, candidate nomination, pass-by filtering, pose uncertainty and unattended evidence; move staff activity into FR-35.
FR-06	FR-35 / UC-35	Retire mandatory composite employee scoring/ranking and replace it with explainable activity, availability and coverage.
FR-07	FR-07 / UC-07	Retain spatial activity with sustained hot/gray-zone interpretation and coverage.
FR-10–FR-13	Same-numbered FR/UC pairs	Retain distinct account access, monitoring, manager views and own workspace; old UC suffixes are not reused by meaning.
FR-17	FR-17 / UC-17	Narrative and PDF export remain one report-generation capability.
FR-18–FR-20	Same-numbered FR/UC pairs	Retain alerts, system status and permitted personal settings.
FR-29	FR-29 / UC-29	Expand store policy to camera, zone, roster and dispatch configuration.
FR-34	FR-34 / UC-34	Retain operator-facing evaluation; metrics do not guarantee product performance.
Previously missing staff activity	FR-35 / UC-35	Add contextual availability and zone coverage; assisting staff are not automatically idle.
Original staffing/assignment scope	FR-36 / UC-36	Explicit direct aisle assignment and account-bound task lifecycle; no manager approval gate.
Agreed Query Agent	FR-37 / UC-37	Explicit authorized analytics question answering, separate from report narration or dispatch.
FR-21–FR-28; old UC-14	Historical register only	Floor-homography prototype removed in commit 8c3a6fe; excluded from the 17 active pairs.

B.2 Retired Floor-Prototype Functional Requirements

The records below describe the descoped prototype only, not the current body-height proximity pipeline. Their former priorities are historical. Existing design, equations and dated TC-14–TC-20 evidence remain in the implementation/testing chapters with historical labels; no metric floor accuracy is inferred for the current runtime.

Table B.2: Historical floor-prototype requirement register

Historical ID	Former requirement	Former priority
Historical FR-21	*(Descoped prototype.)* The system shall preview role labels, confidence, track IDs and box-bottom points without calibration.	High
Historical FR-22	*(Descoped prototype.)* The system shall support ordered floor correspondences through saved configuration and a point-selection interface.	High
Historical FR-23	*(Descoped prototype.)* The system shall calculate supported same-camera, same-timestamp pair separations in floor metres.	High
Historical FR-24	*(Descoped prototype.)* Invalid or unsupported positions and distances shall have explicit states/reasons and unavailable values rather than fabricated zeroes.	High
Historical FR-25	*(Descoped prototype.)* Camera alignment shall be monitored and shifted or unverified frames shall not produce supported metric output.	High
Historical FR-26	*(Descoped prototype.)* Measurements, landmarks and operational coverage shall be editable so the homography can be regenerated.	High
Historical FR-27	*(Descoped prototype.)* The system shall export annotated video, floor maps and timestamped diagnostic records.	Medium
Historical FR-28	*(Descoped prototype.)* Estimated calibration and its distance outputs shall be labelled provisional and approximate.	High

B.3 Historical UC-14: Calibrate and inspect floor distance (descoped)

Actor	Calibration operator or project team.
Precondition	Local video and trained weights exist. Image/floor landmarks or explicitly estimated rectangle dimensions are available.
Main flow	1. Generate the uncalibrated foot-point preview. 2. Select or load ordered landmarks. 3. Save calibration and inspect the grid. 4. Run the distance demo and inspect video, floor map and records.
Alternative flow	Missing files, incompatible geometry, invalid calibration, unsupported foot positions or unverified alignment produce actionable errors or unavailable measurements.
Postcondition	Local diagnostic files and their configured measurement-status metadata are produced.

B.4 Historical NFR-11 and Its Solution

Table B.3: Historical NFR solution; excluded from active NFRs

Historical ID	Requirement / concern	Short historical solution and verification
NFR-11	Unsupported floor geometry shall not yield supported metric distances; smoothing/prediction shall not conceal alignment failures.	The removed prototype checked frame geometry, matrix freshness, homogeneous denominators and region/alignment coverage, returning explicit unavailable states and excluding unsupported predictions. Historical TC-17–TC-19 exercise these guards; this is not a current metric-floor capability.

Table B.4: Floor-distance requirements traceability (descoped prototype)

Requirement	Component	Implementation / design	Test case
FR-21	*(Descoped prototype.)* Detector / preview	Shared trained inference, ByteTrack, original-pixel foot proxy	TC-14
FR-22, FR-26	Calibration	Landmark JSON, point UI and regenerable homography	TC-15, TC-16
FR-23, FR-24, NFR-11	Floor geometry	Supported projection, unit/region guards and explicit failure states	TC-17, TC-18
FR-25	*(Descoped prototype.)* Motion monitor	Masked ORB matching, RANSAC and alignment-quality gates	TC-19
FR-27, FR-28	Distance demo	Video/map/JSONL exports and provisional metadata	TC-20

Appendix C

Detailed Test Cases

Table C.1: Detailed test cases: application and interaction

ID	Steps	Expected	Result
TC-01	Log in with a valid existing Manager account; test wrong password, role mismatch and logout.	Signed cookie and dashboard; invalid credentials rejected.	Passed 20 Oct 2026
TC-02	Request current settings proxy anonymously; call backend with missing/wrong secret; try employee credentials.	HTTP 401/403 as appropriate.	Passed adapted case
TC-12	Inspect representative manager/employee views and route-guard source.	Role-specific pages and consistent restrictions.	Partial; representative views only; not exhaustive
TC-13	Build a report and export PDF.	PDF opens with selected sections.	Unavailable: report route removed (404)
TC-07, TC-08	Run the benchmark with the detector section enabled on the held-out split.	Overall and per-class precision, recall and mAP.	Measured 20 Oct 2026
TC-09, TC-10	Defined in FYP-2 against labelled clips.	See Chapter 7.	Pending

ID	Steps	Expected	Result
TC-21–TC-23	Run `test_judge.py`, `test_engagement.py` and `test_benchmark.py`.	All checks pass.	Passed
TC-24	Run the interaction CLI with `-every 10 -track-every 3` on each local clip; reopen videos and JSON.	All clips complete; confirmed and rejected interactions written.	Passed (11 clips)
TC-25	Run the CLI twice on IMG_8829 with identical settings; compare JSON files.	Byte-identical outputs.	Passed

C.1 Floor-Distance Test Procedures (Descoped Prototype)

Table C.2: Detailed test cases: descoped floor-distance prototype

ID	Steps	Expected outcome	Executed status
TC-14	Run uncalibrated preview on the local video with trained weights; inspect labels, IDs, red points and records.	Readable preview; no invented metres. Missing weights produce an actionable error.	Passed integration
TC-15	Fit the saved estimated A–B–D–C landmarks headlessly; inspect grid and generated JSON.	Correct units/order and provisional status; H and residuals saved.	Passed
TC-16	Omit headless mode; click numbered points, undo/reset, save and compare original-pixel coordinates.	Explicit correspondence order and correct display-coordinate recovery.	Interface implemented
TC-17	Run focused synthetic projection, distance, robust-fit, unit/frame and preprocessing tests.	Expected numerical geometry; reject incompatible/stale calibration.	Automated checks passed

ID	Steps	Expected outcome	Executed status
TC-18	Exercise invalid boxes/denominators, occlusion/exclusion, out-of-region, prediction and missing tracks.	Null/unavailable distances with explicit reasons; no fabricated zeroes.	Automated and CLI checks passed
TC-19	Apply synthetic camera shift and no-feature frames; run the temporary clip monitor.	Shifted/unverified frames suppress supported metric output.	Passed tested cases
TC-20	Run sampled demo; reopen both videos, inspect timestamps, provisional metadata and null coordinates.	148 frames in each video; valid records with explicit approximate/failure states.	Passed

The focused suite is invoked from the repository root with

```
.venv/Scripts/python.exe -m unittest
  backend.tests.test_floor_distance -v
```

It contains 17 tests. The local coverage evaluation command is

```
.venv/Scripts/python.exe scripts/evaluate_floor_distance.py
  -metrics data/outputs/distance/demo/metrics.jsonl
  -output data/outputs/distance/demo/evaluation.json
```

C.2 Current Capability Mapping of Recorded Checks

TC-01 primarily supports FR-10. TC-02 is security evidence for NFR-07/08. TC-07 and TC-08 support FR-01 detection/role processing, not FR-02 crossing counts. TC-09 supports FR-04; TC-10 supports FR-07; both retain Pending status. Representative TC-12 views support only the inspected portions of FR-11/12/13 and role-access behaviour, not every alert, profile or status function. TC-13 remains Unavailable for FR-17. TC-21/22 support FR-04, TC-23 supports FR-34 and TC-24 primarily supports FR-01 with FR-04 diagnostic evidence. TC-25 is the recorded stricter byte-identical case, not proof of numerical repeatability for all inputs. Historical TC-14–TC-20 remain attached to the retired floor register in Appendix B.

C.3 Planned Capability and Quality Scenarios

Every row below is Planned / Not executed. Source inspection does not change this status.

Table C.3: Additional acceptance scenarios; none executed for this documentation revision

ID	Scope	Proposed procedure	Expected result / status
TC-26	FR-02	Label entry/exit crossings; test repeat observations, camera gaps, unknown role and unknown initial occupancy.	Expected supported in/out and coverage; no invented absolute occupancy. Planned / Not executed.
TC-27	FR-29	Save valid camera/zone/roster/policy settings; reject invalid geometry, nonexistent employee, incompatible source, conflicting roster and unauthorized change; inspect downstream consumers.	Previous valid settings survive failures; consumer integration is explicitly identified. Planned / Not executed.
TC-28	FR-35	Compare stationary assisting staff, an available employee, missing break/task context, unlinked tracks and an occluded zone.	Activity uses interaction context; unknown identity/coverage does not imply idle or unstaffed. Planned / Not executed.
TC-29	FR-36	Submit a supported aisle-need event with an eligible account and no active task; inspect event, decision, task and employee workspace.	Task is created/delivered directly with target aisle and reason, with no manager approval interaction. Planned / Not executed.
TC-30	FR-36	Make every employee unavailable/inactive/busy and submit the need.	No eligible employee is dispatched; retain no-eligible outcome and unresolved need. Planned / Not executed.
TC-31	FR-36	Exercise an existing task, source-zone coverage conflict, concurrent duplicate events and rapidly alternating needs.	Policy prevents unsafe duplicate/oscillating transfers and records the reason; missing protection remains a defect, not a Passed check. Planned / Not executed.

ID	Scope	Proposed procedure	Expected result / status
TC-32	FR-36	Interrupt the employee delivery channel or make it unavailable after task creation.	Failure is observable and unresolved need remains visible; stored delivered alone is not receipt evidence. Planned / Not executed.
TC-33	FR-36	Employee reads own task and reports acknowledged, in_progress, completed or applicable declined outcome; attempt another account's task and invalid/reordered transitions.	Account-bound status history and denial of unauthorized updates; strict ordering/arrival guarantees are evaluated separately. Planned / Not executed.
TC-34	FR-37	Ask a supported interval/zone question against known permitted records.	Answer identifies correct figures and interval/source context without changing tasks/settings. Planned / Not executed.
TC-35	FR-37	Ask an ambiguous question, one with no records and an unsupported request; simulate LLM failure.	Clarification or explicit limitation rather than a fabricated numeric answer. Planned / Not executed.
TC-36	FR-37	Attempt anonymous/Employee query access and retrieval of records outside the Manager's authorized scope.	Denied/limited retrieval and no leaked evidence or hidden operational changes. Planned / Not executed.
TC-37	FR-11	Select valid, offline and stale camera sources; remove analytical overlays.	Availability, freshness and unsupported overlays are accurately identified. Planned / Not executed.
TC-38	FR-12	Select valid/invalid interval and zone filters with full, partial and empty metrics.	Views correspond to authorized filters and label missing/demo data. Planned / Not executed.
TC-39	FR-13	Use an Employee account with and without shift/history/tasks; attempt another employee's data.	Only own permitted records appear; empty states and denied access are explicit. Planned / Not executed.

ID	Scope	Proposed procedure	Expected result / status
TC-40	FR-18	Filter alerts, inspect assignment context, resolve and read back actor/time; repeat a stale resolution and test denied access.	Auditable resolution independent of dispatch authorization; stale outcomes handled honestly. Planned / Not executed.
TC-41	FR-19	Inspect all seven target components with measured, absent, stale, inactive and failed telemetry.	Missing/hard-coded worker values are not represented as measured health/throughput. Planned / Not executed.
TC-42	FR-20	Edit permitted personal fields/preferences and password; reload; test duplicate email, wrong current password and attempted role change.	Read-back proves persistence where implemented; invalid changes are rejected. Planned / Not executed.
TC-43	NFR-01	Repeat selected numerical calculations with fixed inputs/model/configuration and a documented tolerance.	Numerical repeatability assessed independently of TC-25's one-clip byte-identical result. Planned / Not executed.
TC-44	NFR-03	From the defined role landing page, count navigation actions to each main analytics view.	At most two actions for the stated navigation targets; missing destinations identified. Planned / Not executed.
TC-45	NFR-04	Review representative charts, textual values and fonts at the supported viewport sizes.	Readable labels, consistent fonts, no clipped critical values. Planned / Not executed.
TC-46	NFR-05/06	Record reference CPU/environment and sampling settings; measure video speed and page timings separately.	Configuration-specific latency/throughput reported; no unsupported universal real-time or agreed numeric response-time claim. Planned / Not executed.

ID	Scope	Proposed procedure	Expected result / status
TC-47	NFR-07–NFR-09	Audit anonymous/Employee/expired-session access, protected route secrets and placeholder configuration/history/logs without including secret values in evidence.	Required denials and redacted secret/configuration findings; outstanding routes remain explicit. Planned / Not executed.
TC-48	NFR-10	Inspect persisted appearance/identity records, face-template absence, account links, retention and authorized access paths.	Minimisation/privacy gaps documented; temporary identifiers are not assumed automatically anonymous. Planned / Not executed.

C.4 Current-Branch Reproduction

The 20 October check ran these existing files with pytest: `backend/interaction/test_engagement.py`, `test_cust_emp_classifier.py`, `test_role_classifier.py`, `test_identity.py`, `test_tracker.py` (all under the same interaction directory). Set `PYTHONPATH` to the backend directory and `TEMP`/`TMP` to a writable local test directory. Corrected-scope rerun: 24 passed in 2.66 seconds. After the pose judge and benchmark were added, `python -m pytest backend/interaction -q` passed 44 tests in 1.72 seconds. The benchmark is run with `python -m backend.interaction.benchmark backend/interaction/benchmarks/benchmark.json`. Historical floor-suite commands above refer to the implementation before its removal, not current-branch availability.

Appendix D

Repository and Contribution Evidence

Repository: `github.com/muhammad-moiz-ansari/retail-store-analysis`. Inspected branch: `feature/interaction`; HEAD: `6560403`; evidence date: 20 October 2026.

Table D.1: Selected commits verified from local Git history

Hash	Date	Git author	Recorded change
`e3fe2af`	16 Oct 2026	Ruhab Ahmad	Add interaction detection model.
`6c25090`	16 Oct 2026	Ruhab Ahmad	Record video interaction verification.
`882f7dc`	16 Oct 2026	`msaqibatifj`	Weighted customer/employee classifier with three-second hold.
`4a9023a`	19 Oct 2026	Moiz Ansari	Add provisional floor-distance estimation pipeline.
`e2b71a5`	19 Oct 2026	`msaqibatifj`	Single OpenVINO role model.
`face2b5`	20 Oct 2026	`msaqibatifj`	Distance-based engagement for moving camera.
`8c3a6fe`	20 Oct 2026	`msaqibatifj`	Remove calibrated floor-distance pipeline.
`80fb3fd`	20 Oct 2026	Moiz Ansari	Add mid-1 report.
`20db4c6`	19 Oct 2026	`msaqibatifj`	On-screen interaction flag (`feature/interaction-flag`).
`4cbe655`	20 Oct 2026	`msaqibatifj`	Remove unused vision-language-model stage.
`cffa30b`	20 Oct 2026	`msaqibatifj`	Remove unused code (interaction dataset, evaluation and model loader).

Hash	Date	Git author	Recorded change
6560403	20 Oct 2026	msaqibatifj	Pose judge, pass-by filter and benchmark.

D.1 Authorship and Milestone Evidence

At the inspected HEAD, `git shortlog -sne HEAD` records 43 commits for Moiz Ansari, 41 for `msaqibatifj` and 28 for Ruhab Ahmad, including merge commits. Counts describe recorded authorship and are not measures of effort or contribution quality. The mapping of account aliases and non-code responsibilities requires team confirmation. `git tag -list` returned no tags. No task-board history or supervisor-approved milestone record was available for this check, so none is fabricated. Textual Git evidence is supplied instead of an unverified contribution-graph screenshot.

D.2 Floor-Distance Implementation Evidence

Commit `4a9023a` records the shared inference helper, geometry/calibration/motion/smoothing/evaluation modules, four CLI scripts, focused tests, camera schema/examples and usage documentation. The selected report figures preserve local prototype outputs from that implementation. Commit `8c3a6fe` subsequently removed the source pipeline; current-branch availability must not be inferred from these historical figures. Raw video and generated diagnostics remain outside the report's tracked evidence. The new test summary is at `evidence/verification_20261020.json`; the benchmark report and interaction batch results are at `evidence/benchmark_20261020.json` and `evidence/interaction_judge_batch_20261020.csv`.

Appendix E

Additional Design Diagrams

The architecture, domain, class and deployment diagrams are in Chapter 5 (Figures 5.1, 5.2, 5.3 and 5.4). The 17 system sequence diagrams are in Section 5.11; this appendix retains only supplementary schema and diagnostic material. Figure E.1 is derived from the current SQLite foreign-key relationships in `backend/store_core.py`; it shows a selected subset, not the complete conceptual domain model.




Figure E.1: Selected implemented SQLite relationships; arrows point from referencing tables to referenced tables

E.1 Historical Floor Calibration Schema and Failure States

The floor process is shown in Figure 5.6; actual preview, calibration and map examples are in Figures 6.6–6.8. The authoritative correspondence order for the provisional rectangle is A–B–D–C. Floor coordinates are $(0,0)$, $(w,0)$, (w,d) and $(0,d)$ in metres for that order.

Record group	Key information
Identity / geometry	Schema version, camera/calibration ID, source reference, frame index/timestamp, frame size, coordinate space.
Landmarks / mapping	Original-pixel and metre correspondences, authoritative dimensions, image-to-floor H, inliers/residuals.
Operational quality	Supported polygon, exclusions, distortion handling, motion thresholds, smoothing/prediction limits.
Measurement status	Estimated calibration inputs and approximate-output metadata.
Runtime observation	Track ID, role/score, pixel foot proxy, nullable floor coordinates, motion/position state and reasons.

States include `uncalibrated`, `observed_proxy`, `predicted`, `unreliable`, `out_of_region`, `motion_unverified` and `motion_invalid`. Only supported observed proxies contribute to approximate pair distances. The localization equations are given in Equations 6.1–6.3; no 3D reconstruction is implied. These records belong to the descoped floor prototype (Section 6.4.3).

E.2 Interaction Verdict States

Each interaction candidate in the current pipeline carries one verdict; annotated output is in Figure 6.5.

Verdict	Meaning
`interaction`	The pose judge found a head turned towards the other person in at least half of the judged frames.
`no_interaction`	Poses were found but nobody faced the other person; written to `.rejected_interactions.json` and re-judged every four seconds while the pair stays close.
`unverified`	Judge switched off, no pose found, or the judge failed; the proximity result stands.

Appendix F

Meeting and Progress Evidence

Supervisor: Mr. Shehreyar Rashid. Dates, discussions and outcomes below are recorded from the team's recollection of each meeting.

Table F.1: Meeting and progress record

Date	Discussion	Outcome / Action
19 August 2026	Lack of a dataset; retailers' reluctance to share footage because of privacy concerns; the proposed project approach.	Supervisor suggested ways to address dataset access and recommended creating the team's own dataset for the time being.
8 September 2026	Review of the draft proposal-defence slides.	Supervisor advised additions and corrections and set a deadline to finalise and show the slides before the proposal defence. The deadline date was not recorded.
10 September 2026	Client meeting (Thursday).	Discussion details were not recorded.
5 October 2026	Dataset progress and presentation schedule.	Supervisor set a deadline for showing the dataset. The deadline date was not recorded.
12 October 2026	Additional supervisor meeting; presentation of the 70-video dataset.	Supervisor accepted the 70-video dataset.

Date	Discussion	Outcome / Action
14 October 2026	Work-progress update and the mid-evaluation deadline.	Supervisor requested a work update and communicated the mid-evaluation deadline; the recorded mid evaluation is 21 October 2026.

Dataset agreement. The supervisor accepted the 70-video dataset shown by the team. No numeric classification accuracy, interaction-detection accuracy or dashboard response-time threshold was agreed in that discussion. Dataset acceptance does not constitute approval of measured model performance.

Bibliography

[1] Ministry of Information Technology and Telecommunication, Pakistan, "Legislation: official listing," https://www.moitt.gov.pk/Legislations, accessed 20 October 2026.

[2] European Parliament and Council, "Regulation (EU) 2016/679 (general data protection regulation)," Official Journal of the European Union, 2016.

[3] RetailNext, "Traffic analytics," https://retailnext.net/platform/traffic-analytics, accessed 20 October 2026.

[4] Sensormatic Solutions, "Shopper insights," https://www.sensormatic.com/shopper-insights, accessed 20 October 2026.

[5] Amazon Just Walk Out, "How it works," https://www.justwalkout.com/how-it-works, accessed 20 October 2026.

[6] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, "You only look once: Unified, real-time object detection," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 779–788.

[7] G. Jocher *et al.*, "Ultralytics YOLO," https://github.com/ultralytics/ultralytics, 2023, software.

[8] A. Bewley, Z. Ge, L. Ott, F. Ramos, and B. Upcroft, "Simple online and realtime tracking," in *Proc. IEEE Int. Conf. Image Processing (ICIP)*, 2016, pp. 3464–3468.

[9] Y. Zhang, P. Sun, Y. Jiang, D. Yu, F. Weng, Z. Yuan, P. Luo, W. Liu, and X. Wang, "ByteTrack: Multi-object tracking by associating every detection box," in *Proc. European Conf. Computer Vision (ECCV)*, 2022, pp. 1–21.

[10] M. Ye, J. Shen, G. Lin, T. Xiang, L. Shao, and S. C. H. Hoi, "Deep learning for person re-identification: A survey and outlook," *IEEE Trans. Pattern Analysis and Machine Intelligence*, vol. 44, no. 6, pp. 2872–2893, 2022.

[11] R. Hartley and A. Zisserman, *Multiple View Geometry in Computer Vision*, 2nd ed. Cambridge University Press, 2004.

[12] OpenCV, "Basic concepts of the homography explained with code," https://docs.opencv.org/4.x/d9/dab/tutorial_homography.html, software documentation, accessed 20 October 2026.

[13] A. Criminisi, I. Reid, and A. Zisserman, "Single view metrology," *International Journal of Computer Vision*, vol. 40, no. 2, pp. 123–148, 2000.

[14] M. A. Fischler and R. C. Bolles, "Random sample consensus: A paradigm for model fitting with applications to image analysis and automated cartography," *Communications of the ACM*, vol. 24, no. 6, pp. 381–395, 1981.

[15] E. Rublee, V. Rabaud, K. Konolige, and G. Bradski, "ORB: An efficient alternative to SIFT or SURF," in *Proc. IEEE International Conference on Computer Vision (ICCV)*, 2011, pp. 2564–2571.

[16] S. Ramírez, "FastAPI documentation," https://fastapi.tiangolo.com/, accessed 2026.

[17] Vercel, "Next.js documentation," https://nextjs.org/docs, accessed 2026.

[18] Ultralytics, "Licensing," https://www.ultralytics.com/license, accessed 20 October 2026.

[19] FoundationVision, "Bytetrack: Mit licence," https://github.com/FoundationVision/ByteTrack/blob/main/LICENSE, accessed 20 October 2026.

[20] OpenCV, "Opencv licence," https://opencv.org/license/, accessed 20 October 2026.

[21] Google Fonts, "Inter: Open font license," https://github.com/google/fonts/blob/main/ofl/inter/OFL.txt, accessed 20 October 2026.

[22] ——, "Space grotesk: Open font license," https://github.com/google/fonts/blob/main/ofl/spacegrotesk/OFL.txt, accessed 20 October 2026.

[23] ——, "Jetbrains mono: Open font license," https://github.com/google/fonts/blob/main/ofl/jetbrainsmono/OFL.txt, accessed 20 October 2026.