HyperFrames production: launch videos, brag routes and sourced documentaries

Strengths and best use

HyperFrames makes a video composition inspectable as an HTML-based project. Reusable timing and typography are useful for product demonstrations, graphics, and short documentary explainers. The brag skill can supply a launch-video workflow, while a documentary requires its own factual and media provenance. One renderer can support both deliverables. HyperFrames (https://github.com/heygen-com/hyperframes) - brag (https://github.com/latent-spaces/brag)

Choose the current workflow

The current brag repository distinguishes a classic HyperFrames pipeline from a slim workflow. On Opus 5.5, `/brag` switches to `/brag-slim`, which uses tools already available on the machine and has no bundled assets. `/brag --full` selects the classic route. This change matters when following an older reel that assumes every invocation uses HyperFrames. Check the installed revision and its prerequisites first. Current skill (https://github.com/latent-spaces/brag/blob/main/skills/brag/SKILL.md)

For the classic Claude Code plugin route, the repository documents:

```
/plugin marketplace add latent-spaces/brag
/plugin install brag@brag
/brag --full
```

For a standalone HyperFrames project, use Node.js 22 or newer and FFmpeg. The current CLI uses `check` for validation. These are documented setup commands, not a report of a video rendered by Kiln.

```
npx hyperframes doctor
npx hyperframes init documentary-test
cd documentary-test
npx hyperframes check
npx hyperframes preview
```

After reviewing the preview:

```
npx hyperframes render --output documentary-test.mp4
```

Produce a useful short film

Begin with one audience, one proposition, and two or three observable beats. For a product launch, show the product performing the central action and its actual result. For a documentary, prepare a claim ledger before a script: claim, primary evidence, date, uncertainty, and licensed visual. Use a short storyboard to align narration, graphics, and source attribution. Render a sample before committing to a full sequence.

Separate code licensing from soundtrack, font, screenshot, stock-footage, and generated-media permissions. Keep asset receipts and narration-provider charges with the project. Free software does not establish a zero-cost production. Verify captions, safe margins, audio levels, factual wording, and legibility at the target aspect ratio. Test one export on the device where it will be watched.

Reusable prompt

```
Prepare a short video from this product or researched subject. Identify the audience and three beats, distinguish verified claims from uncertainties, and create a storyboard with asset provenance. Choose the installed brag route or a HyperFrames project explicitly. Preview one scene, record dependencies and costs, and require review before final rendering or publication.
```

Project idea

Make a 20-second demo from an owned sample app and a 45-second explainer from public primary documents. Compare editing time, factual corrections, render failures, and asset cost using the same production ledger.

Original sources

- https://www.instagram.com/reel/DdrNk5kFBFv/
- https://www.instagram.com/reel/Dd1Cklmk2bN/
- https://www.instagram.com/reel/Dezc4qeimex/
- https://www.instagram.com/reel/DexBgdGKrrl/