

YOLO and RGB-D Fusion for Oil-Palm Fresh-Fruit-Bunch Counting and Maturity Classification: A Structured Evidence-Mapping Review

Muhammad Zainal Muttaqin and Fatma Indriani

Abstract—Oil-palm fresh-fruit-bunch (FFB) counting and maturity classification require more than per-image object detection: a system must separate crowded instances, attach maturity labels to the correct bunch, and avoid repeated observations when a camera moves through a canopy. This structured evidence-mapping review examines verified literature on RGB detection, YOLO, depth estimation, RGB-D fusion, geometry, and temporal association to formulate a defensible research agenda for FFB perception. The synthesis identifies a multi-scale real-time RGB detector as an appropriate baseline, depth as a conditional geometric cue, and quality-aware feature or late fusion as testable alternatives rather than established oil-palm results. It distinguishes direct agricultural evidence from transferable evidence and specifies dataset, ablation, detection, maturity, geometry, count-error, and latency requirements for field validation.

Index Terms—YOLO, RGB-D, object detection, depth estimation, multimodal fusion, fresh-fruit-bunch counting, oil palm, evidence mapping

I. INTRODUCTION

Fresh-fruit-bunch (FFB) counting and maturity classification are often described as separate computer-vision tasks. In field operation they are not. A system must distinguish each visible bunch from fronds, shadows, and neighbouring bunches; assign a maturity label to the correct instance; and avoid counting the same bunch again when a camera or platform moves. A missed bunch biases yield estimation, whereas a duplicate or a maturity label attached to the wrong instance produces a different but equally operationally important error. The practical target is therefore a sequence-level inventory of individual bunches, not merely a high score on independent images.

This target is demanding in an oil-palm canopy. Bunches vary sharply in image scale with camera distance and viewing angle, can be partially hidden by fronds or other bunches, and are observed under a mixture of deep shadow and direct sunlight. RGB appearance is indispensable for colour and texture cues associated with maturity, but it can be ambiguous when foliage, soil, shadow, and fruit share local appearance. Modern object detection supplies a useful starting point, yet success on a generic RGB benchmark does not demonstrate that a detector will separate crowded bunches, preserve an identity over time, or tolerate outdoor sensor failure.

The YOLO family is attractive because it casts object detection as a single image-to-box-and-class mapping. The original paper reported 63.4% mAP at 45 frames per second on PASCAL VOC 2007, while Fast YOLO reached 155 frames per second at lower accuracy [1]. These results explain why single-stage detectors are appealing for moving cameras, but they are not a performance claim for FFBs. The relevant question is whether the latency advantage can be retained while resolving the particular failure modes of a plantation scene.

Depth is a plausible complementary cue. When two similarly coloured regions occupy different spatial layers, depth can help separate them; when RGB depth edges are weak, geometry can stabilize localization. Conversely, depth maps may be missing, noisy, misregistered, or non-metric. This is especially important outdoors, where a sensor and an RGB camera must be synchronized and where direct sunlight can change the reliability of active depth sensing. Depth should therefore be treated as evidence with an uncertain quality, not as an automatically beneficial fourth input channel.

This review is written as a chronological history of the field rather than a snapshot of current state-of-the-art. The reason is methodological: a research pipeline that ends in a design decision for oil palm must show *why* the field arrived at its present tools, which earlier ideas were superseded and which persist, and where each mechanism was actually validated. Accordingly, the review traces detector foundations from 2012 to 2026, monocular depth from 2014 to 2026, RGB-D dense prediction, 3D perception, pose and grasping, SLAM, cross-domain multimodal fusion, benchmark datasets, and the small number of direct agricultural systems, before converging on a falsifiable FFB experimental agenda. It asks five linked questions: (i) which RGB detector properties are relevant to real-time FFB perception; (ii) what forms of depth are available and what do they mean geometrically; (iii) where and how should RGB and depth be fused; (iv) which mechanisms connect per-frame detection to a reliable count; and (v) which conclusions are directly supported for agriculture and which remain hypotheses for oil palm? The order is deliberate. It prevents an architecture recommendation from skipping the constraints imposed by sensor quality, data, and the counting objective. Figure 1 summarizes this decomposition as a four-axis map of the corpus.

Department of Computer Science, Universitas Lambung Mangkurat, Banjarbaru, Indonesia.

The local source corpus was audited against verified PDFs on 21 July 2026.




Fig. 1. Conceptual map of the review. The FFB perception problem is decomposed along four axes — RGB detection, depth, RGB-D fusion, and geometry/association — each supported by a cluster of the reviewed literature. A single work may belong to more than one cluster, so the cluster sizes are not additive.

II. REVIEW PROTOCOL AND VERIFIED EVIDENCE CORPUS

A. Structured evidence-mapping approach

This article is a structured evidence-mapping review, which surveys the breadth of a research area and charts how its methods relate, rather than a formal systematic review computing a pooled statistic under a retrospective PRISMA protocol. It synthesizes 182 primary sources, each read from its full text so that method, reported result, and stated limitation are drawn from the paper itself rather than from a secondary description. The corpus is deliberately broad because the target problem sits at the intersection of several mature fields — real-time object detection, monocular depth estimation, RGB-D fusion, 3D localization, and temporal association — none of which was developed for oil-palm fruit, and the review’s contribution is precisely to trace how each field’s ideas transfer, or fail to transfer, to fresh-fruit-bunch (FFB) counting and maturity classification.

The literature spans a decade and a half and a wide range of venues. The foundational detection, depth, segmentation, and 3D-perception work is drawn from the principal computer-vision conferences and journals (CVPR, ICCV, ECCV, NeurIPS, and IEEE Transactions on Pattern Analysis and Machine Intelligence), the fast-moving YOLO lineage appears largely as technical reports and open-source releases that the surveys in the corpus consolidate, and the agricultural systems are published in domain venues such as *Computers and Electronics in Agriculture* and the *Journal of Field Robotics*. Figure 2 shows the temporal distribution: the corpus




Fig. 2. Temporal distribution of the 182 verified primary sources by publication year (2012–2026). The peak in 2020–2024 coincides with the parallel maturation of RGB-D fusion, foundation-model monocular depth, and end-to-end detection.

reaches back to the 2012 benchmarks that launched deep visual recognition and extends to 2026 preprints, with the bulk falling in 2020–2024, the period in which RGB-D fusion, foundation-model depth, and end-to-end detection matured in parallel. Figure 3 shows the thematic distribution across eighteen coded areas; the concentration in general RGB detection, monocular depth, and RGB-D dense prediction, set against only a handful of direct agricultural systems, is itself a central finding of the review and the reason its conclusion is a research agenda rather than a model recommendation.

Each source is represented in the supplementary evidence matrix, `docs/evidence-matrix-182.csv`, which records for every entry its title, year, thematic domain, task, modality, a method summary, the evaluation context, the reported finding, the stated limitations, and an explicit




Fig. 3. Thematic distribution of the 182 verified sources across the eighteen coded research areas. The concentration in general RGB detection, monocular depth, and RGB-D dense prediction, against only three directly agricultural entries, defines the transfer gap this review addresses.

note on its relevance — and transfer boundary — to FFB perception. Every source is cited in the main text and placed chronologically within its thematic lineage, so a reader can follow how each idea responded to the limitations of the work before it. The eighteen thematic codes — detector foundations, YOLO surveys and variants, monocular depth, RGB-D salient-object detection, RGB-D semantic segmentation, 3D detection, 6D pose, robotic grasping, RGB-D SLAM, multimodal fusion, cross-domain applications, and benchmark datasets — should not be read as equivalent evidence for FFB performance; they mark where a result was obtained and thereby make its transfer boundary visible, since a direct fruit study carries a different evidential weight from indoor RGB-D segmentation, robotic manipulation, or autonomous-driving perception.

B. Interpretation rules

Three evidence levels are used throughout. *Direct evidence* is drawn from agricultural or fruit studies and can motivate an observation about a related deployment setting, although it is still not a TBS benchmark unless the study actually uses FFB data. *Transferable evidence* comes from other domains but answers a mechanism-level question, such as whether feature fusion can resist missing depth or whether geometry helps preserve an object identity. *Design hypotheses* are proposed TBS experiments. They are not phrased as achieved field results. This distinction is central because the verified corpus does not contain a sufficient direct FFB RGB-D benchmark to establish a best model, a best fusion point, or an expected accuracy.

III. RGB DETECTION FOUNDATIONS: A CHRONOLOGICAL ARC FROM REGION PROPOSALS TO REAL-TIME TRANSFORMERS

The history of RGB detection is best read as a sequence of responses to four recurring problems: localization, scale, class imbalance, and computational cost. Zou *et al.*, surveying

twenty years of the field, frame this transition from hand-crafted features to deep detectors as the organizing storyline, and their taxonomy of one- and two-stage families is the backbone of the account that follows [2]. Figure 4 maps the four detector paradigms and the inheritance of ideas between them that this section traces. Because all of these detectors were validated on generic benchmarks, they enter this review as baseline and mechanism evidence, not as FFB performance claims.

A. The two-stage lineage (2014–2021)

The deep-detection era opens with R-CNN, whose central move was to separate the localization problem from the recognition problem. Instead of sliding a classifier across every position and scale, R-CNN accepts a few thousand class-agnostic region proposals produced by a bottom-up algorithm and runs a convolutional network only inside each proposal; localization is delegated to the proposal generator, and the network’s job is reduced to recognizing the contents of a given region [3]. This yielded 53.3% mAP on PASCAL VOC 2012, a relative improvement of more than 30% over the best hand-crafted-feature systems of its time, and it established the shared 4,096-dimensional feature vector as a compact object representation. Its weakness, however, defines the rest of the lineage: because every one of the thousands of overlapping proposals is cropped and pushed through the network as an independent image, the same convolutional computation is repeated many times, making both training and inference slow and forcing feature caches of hundreds of gigabytes to disk. For an FFB scene, where a single frame may contain dozens of overlapping bunch candidates, this per-proposal cost is exactly the property that a practical detector cannot afford.

Fast R-CNN inherited that redundancy problem and removed it by moving the proposals from pixel space to feature space. The whole image passes through the convolutional layers once; each proposal is then simply read off the resulting feature map through an RoI-pooling layer, so that overlapping proposals covering the same image region never recompute their shared convolutions [4]. Just as importantly, it collapsed R-CNN’s three-stage training into a single stage in which softmax classification and bounding-box regression are learned jointly and all layers are updated, eliminating the disk feature cache and raising accuracy at the same time. What Fast R-CNN did not solve was the origin of the proposals themselves, which were still produced by an external, un-learned algorithm that had become the pipeline’s speed bottleneck.

Faster R-CNN closed that remaining gap with the observation that the feature map the detector already computes is sufficient to generate proposals, so no separate algorithm is needed. A Region Proposal Network is placed as a fully convolutional head on top of the final feature map, predicting at every location both an objectness score and box refinements relative to a set of reference anchors of several scales and aspect ratios [5]. Proposals thus become nearly free (roughly ten milliseconds of shared computation), their quality improves together with the backbone because they are now learned, and the anchor mechanism handles multi-scale




Fig. 4. Genealogy of the RGB detector paradigms and the inheritance of ideas between them: the two-stage line (R-CNN through Sparse R-CNN), the one-stage line (SSD, RetinaNet, EfficientDet), the anchor-free line (FCOS, CenterNet), and the transformer line (DETR through the real-time DETR variants).

objects from a single image scale. This anchor-based, learned-proposal, end-to-end two-stage design became the reference accuracy architecture against which almost every later detector, including the YOLO family, was measured; for FFB research it remains a valuable occlusion baseline that tests whether a faster model is missing close or partly visible bunches because of its design rather than because of the data.

Two refinements extended the two-stage design in directions that matter directly for bunch counting. Feature Pyramid Networks addressed scale by recognizing that the multi-resolution hierarchy already present inside a convolutional backbone can be turned into a full feature pyramid if each level is enriched with semantics from the level above it. A top-down path upsamples the coarse, semantically strong maps and merges them through lateral connections with the fine, high-resolution maps, producing a set of feature maps that are simultaneously high-resolution and semantically strong, at marginal extra cost and with its largest gains on small objects [6]. Because a bunch may occupy a few pixels at one range and a large part of the frame at another, this scale behaviour is not a convenience but a requirement. Mask R-CNN then added a third, parallel branch to each candidate object that predicts a binary instance mask alongside the existing class and box branches, and replaced the coarse RoI-pooling with the quantization-free RoIAlign layer so that mask and feature are spatially aligned; it reached 37.1 mask AP on COCO test-dev and swept the 2017 instance-segmentation competition [7]. The instance mask is significant for counting because, where two bunches overlap, a mask makes the unit of counting explicit in a way that a rectangular box cannot, and it also constrains any later depth

sample to the hypothesized object rather than to a bounding rectangle that mixes foreground and background.

Much later, Sparse R-CNN showed that the two-stage idea could itself become end-to-end and NMS-free, absorbing a lesson from the transformer detectors discussed below. It discards the dense proposal machinery (both the RPN and the static anchor grid) and instead maintains a small fixed set of learnable proposal boxes paired with learnable proposal features, refined iteratively and supervised by a set-prediction loss [8]. The result is a minimalist detector with no dense priors and no non-maximum suppression, which simplifies deployment; it is included here because its clean instance-uniqueness formulation is conceptually attractive for a counting task where each bunch should correspond to exactly one committed detection. Read as a whole, this lineage supplies the accuracy-and-occlusion reference family for FFB perception: a multi-scale neck is necessary for range-varying bunches, an instance mask sharpens the unit of counting, and a strong two-stage model is the natural high-capacity comparison against which a compact real-time detector must justify any accuracy it gives up for speed.

B. One-stage and anchor-free detectors (2016–2020)

The one-stage family removed the explicit proposal stage altogether to gain the speed that two-stage detectors could not offer. SSD replaced a single coarse prediction grid with several feature maps of decreasing resolution and attached a set of fixed-shape default boxes at every location of each map, scoring all of them convolutionally in one forward pass [9]. The mechanical intuition is that deeper layers see larger

receptive fields, so predicting from a hierarchy of maps lets one network cover a range of object sizes without processing the image at multiple scales; on PASCAL VOC this matched or exceeded contemporary two-stage detectors at real-time speed. Its recurring weakness, weaker recall on small objects whose evidence lives only in the shallow, semantically weak layers, is the very problem FPN later addressed, and it is the problem a distant bunch presents.

RetinaNet then diagnosed why single-stage accuracy still lagged two-stage accuracy and located the cause not in the architecture but in the loss. A dense detector evaluates tens of thousands of candidate locations per image, of which the overwhelming majority are easy background; summed over so many examples, their individually small losses dominate the gradient and drown out the few hard foreground examples. Rather than heuristically sampling examples, focal loss reshapes cross-entropy with a modulating factor $(1 - p_t)^\gamma$ that drives the loss of confidently-correct examples toward zero while leaving hard examples largely untouched [10]. The change is small, architecture-agnostic, and portable, and it proved that the single-stage accuracy gap was an optimization artefact rather than a structural limit, a directly relevant lesson for FFB imagery, where background canopy vastly outnumbers bunch pixels and can similarly swamp training. EfficientDet carried the efficiency argument further along two axes at once: it treated multi-scale feature fusion as a learnable weighting problem, giving each input feature a trainable scalar weight inside a repeated bidirectional pyramid (BiFPN), and it replaced per-component tuning with a single compound-scaling rule that jointly scales resolution, depth, and width across the whole detector, yielding a D0–D7 family that dominates its compute class at every point [11]. For a plantation system that must run within a fixed latency and power budget, this principled speed-accuracy family is a useful template for choosing an operating point rather than a single model.

Anchor-free detectors simplified the output space by removing the anchor boxes and their hyperparameters entirely. FCOS made the feature-map location itself the training sample: every location falling inside a ground-truth box becomes a positive that predicts the object class and regresses four positive distances (left, top, right, bottom) to the box sides, with a center-ness branch that down-weights predictions far from an object’s centre [12]. This turns nearly every foreground pixel into a regression sample, removes all anchor-matching heuristics and their memory cost, and reframes detection as dense per-pixel prediction. CenterNet pushed the reduction to its limit by representing an object as a single point, the centre of its box, so that detection becomes standard keypoint estimation on a per-class heatmap, with box size, sub-pixel offset, and even 3D or pose attributes regressed from the feature at each peak, in one anchor-free, NMS-free, end-to-end pass [13]. The centre-point framing is conceptually attractive for counting because in the ideal case one heatmap peak corresponds to exactly one bunch; in practice a centre hidden by a frond or shared by two overlapping bunches can still be missed or merged, so the framing must be tested under the same crowded-scene protocol as any other detector rather than assumed to solve duplicate counting by construction. PP-YOLO belongs to this

same period but as an explicit engineering study rather than a new architecture: starting from an intact YOLOv3, it swaps in a well-supported ResNet50-vd-dcn backbone and then adds ten already-published tricks one at a time, accepting each only if it raises accuracy without increasing parameters or FLOPs, reaching 45.2% AP on COCO test-dev at 72.9 FPS [14]. Its value here is cautionary: a substantial part of reported detector progress comes from training recipe rather than architectural novelty, which is why an FFB comparison must hold recipe, resolution, and hardware fixed before attributing a gain to a model.

C. The YOLO lineage as a moving engineering frontier (2016–2026)

YOLOv1 introduced the formulation that gives the family its identity: detection as a single regression from the full image to all boxes and classes at once. Because one network sees the whole image in one evaluation, global context is available at prediction time and background false positives are low, and Fast YOLO reached 155 FPS [1]. The same design choice fixes its weaknesses, and those weaknesses are precisely the FFB failure modes: each grid cell is responsible for only one class and two boxes, so small objects that cluster together in one cell (the plantation analogue is several bunches falling in the same coarse cell) are systematically missed, and localization is coarse. Every subsequent generation is best read as a different attempt to keep the single-pass speed while removing one of these limits, and Figure 5 lays out that chronology with each version’s defining architectural marker. YOLOv2/YOLO9000 raised recall and localization precision through an accumulation of individually-ablated changes (dimension-cluster anchors, direct location prediction, higher-resolution and multi-scale training), reaching 76.8–78.6% mAP on VOC, and its WordTree mechanism jointly trained detection and classification to extend the output vocabulary to thousands of categories [15]. YOLOv3 then attacked the small-object problem structurally by making three-scale prediction, feature-pyramid style, central to the architecture on a deeper Darknet-53 residual backbone with multi-label logistic classification, at some cost in high-IoU localization [16].

The next phase professionalized the training recipe. YOLOv4 organized every available improvement into a “bag of freebies” that changes only training (Mosaic augmentation, CIoU loss, self-adversarial training) and a “bag of specials” that adds cheap inference-time modules (CSP, SPP, PAN, Mish), and combined them into a 43.5% AP COCO detector at ~65 FPS that could be trained on a single GPU [17], a democratization directly relevant to a plantation lab without cluster resources. YOLOX converted the family to an anchor-free design with a decoupled head that separates classification from localization and a SimOTA dynamic label-assignment scheme, reaching 47.3–50.0% AP [18]. YOLOv6 re-derived each component from ablations for industrial use and, notably, allowed a different architecture per model size: a single-path reparameterized backbone for small models where raw speed dominates, a more complex one for large models, with anchor-free heads and task-alignment-learning training [19]. YOLOv7




Fig. 5. Timeline of the YOLO family and its principal architectural markers, from the single-pass grid regression of YOLOv1 (2016) through anchor-free decoupled heads, re-parameterization, and the NMS-free end-to-end designs of YOLOv10 and YOLO26.

made the training-versus-inference distinction explicit through its trainable bag-of-freebies: the network may carry extra branches, auxiliary heads, and layered label assignment during training provided everything folds away or is discarded at inference, via E-ELAN blocks and planned re-parameterization [20]. Gold-YOLO then targeted the neck specifically, replacing the gradual layer-to-layer information flow of FPN/PAN with a centralized Gather-and-Distribute mechanism that collects features from all levels and redistributes them, improving multi-scale fusion [21], again a mechanism aimed at the range-varying-object problem a canopy presents.

The most recent generations converge on end-to-end, NMS-free inference, importing the transformer detectors' set-prediction philosophy into the real-time YOLO body. YOLOv9 addresses information loss in deep networks through Programmable Gradient Information, an auxiliary reversible branch that supplies reliable gradients during training at no inference cost, paired with the lightweight GELAN architecture [22]. YOLOv10 removes non-maximum suppression from inference through consistent dual assignments: a one-to-many head supplies rich supervision during training while a one-to-one head, sharing the same body, is used at inference, so no post-hoc de-duplication is needed [23]. YOLOv11 keeps the three-part YOLOv8 frame but swaps its main feature block for C3k2 and inserts a C2PSA spatial-attention module, supporting six vision tasks [24]. YOLO26 continues the simplification, removing Distribution Focal Loss and NMS from the inference graph while adding ProgLoss and a small-target assignment scheme (STAL) and a MuSGD optimizer,

reaching 40.9–57.5% mAP on COCO at 1.7–11.8 ms on a T4 GPU [25]. The NMS-free trend matters for counting because non-maximum suppression is itself a source of merge and split errors on crowded, overlapping bunches. Alongside this closed-set lineage, YOLO-World extended the paradigm to open-vocabulary detection through vision-language modelling, allowing categories to be specified at test time by text [26], a capability worth noting because a maturity taxonomy (un-ripe, underripe, ripe, overripe, rotten) may be refined without retraining from scratch.

This lineage should therefore be read as a changing set of engineering levers, not a leaderboard to be topped, and a series of surveys in the corpus makes that reading explicit. Jiang *et al.* gave an early narrative comparison that treats the whole series as one consistent line of change [27]; Terven *et al.* standardized the measurement vocabulary (AP, IoU, NMS defined before use) so that cross-version numbers sit on a common footing, and dissected the anatomy of each version [28]; Hussain read the evolution through a digital-manufacturing lens, tying each architectural change to an application need [29]; Vijayakumar and Vairavasundaram surveyed metrics, architecture, and applications in one structured reading [30]; and Sapkota *et al.* mapped YOLOv1–YOLOv10 specifically onto five agricultural tasks including fruit detection, tracking, and counting, the single closest survey in the corpus to this review's target and the natural entry point for the FFB literature [31]. Two later surveys sharpen the methodology: Jegham *et al.* replaced citation-based comparison with controlled re-runs of 33 models from seven YOLO versions across three

datasets under uniform hyperparameters, isolating architecture from recipe and finding YOLO11 strong on the speed-accuracy trade-off [32], and a decadal review then traced the whole genealogy in reverse from YOLOv12 back to YOLOv1 to show how the newest design choices recur in older forms [33]. The consistent lesson for TBS research across these surveys is that a compact YOLO with a multi-scale neck is a sensible first deployment model when latency is constrained, but the specific version must be chosen by a field failure analysis (missed distant bunches, merged neighbours, unstable identities) rather than by a reported generic COCO AP. Table I sets out the measurements that turn such a detector comparison into FFB-relevant evidence.

D. Backbones, attention, and the transformer detectors (2016–2026)

Detector progress rode on backbone progress, and the backbones in the corpus form their own short history. ResNet made very deep networks trainable by having stacked layers learn a residual function $F(x) = H(x) - x$ rather than the target mapping directly, so that a shortcut connection carries the identity and gradients flow to early layers; it is the shared feature extractor beneath much of the two-stage and fusion literature discussed throughout this review [34]. CBAM added a lightweight module that recalibrates CNN features by applying channel attention and then spatial attention in sequence, decomposing an expensive 3D attention map into two cheap 1D and 2D operations; it is nearly free to insert and recurs throughout the applied YOLO variants surveyed later [35]. The Vision Transformer then broke the convolutional monopoly on backbones by treating an image as a sentence: a 224×224 image is cut into 196 patches of 16×16 pixels, each embedded as a token, and a standard Transformer processes the sequence, matching convolutional backbones once pretrained at large scale [36]. Its quadratic attention cost made it impractical for dense, high-resolution prediction, which Swin Transformer fixed by computing self-attention only within non-overlapping local windows, giving linear cost, and shifting the window partition between layers so information still crosses window boundaries, yielding a hierarchical backbone suitable for detection and segmentation [37]; Swin V2 then scaled its capacity and input resolution with training-stability fixes [38]. PVT contributed the first convolution-free progressive pyramid, shrinking spatial resolution stage by stage like a CNN while retaining global attention, so a transformer could serve as a dense-prediction backbone [39]. ConvNeXt supplies the essential control on all of this: a pure CNN, modernized only with macro-design choices borrowed from Swin and no dynamic self-attention, remains competitive, warning against attributing gains to attention per se rather than to training and design [40], a discipline an FFB study should keep when comparing a transformer detector to a convolutional YOLO.

Transformer detectors form a parallel arc worth tracing in full because their end-to-end, NMS-free reasoning speaks directly to the counting requirement that each bunch map to exactly one detection. DETR reframed detection as direct

set prediction: the network always emits a fixed number of predictions (100, far more than the objects in a typical image) and a bipartite Hungarian matching assigns each ground-truth object to exactly one prediction, so anchors and non-maximum suppression disappear entirely [41]. This elegance came at two costs: very slow training convergence and weak small-object performance, because global attention must learn from scratch where to look and is expensive at high resolution. Deformable DETR resolved both by replacing global attention with multi-scale deformable attention, in which each query attends only to a few learned sampling points around a reference location, cutting cost and sharpening small-object localization [42]. The next several detectors each attacked the convergence problem from a different angle: Conditional DETR decoupled the content and spatial parts of the decoder query so cross-attention localizes faster [43]; DN-DETR added a query-denoising auxiliary task that reconstructs perturbed ground-truth boxes, bypassing the unstable matching that slows early training [44]; DINO combined contrastive denoising, mixed query selection, and a look-forward-twice update to reach state-of-the-art COCO results [45]; and Co-DETR enriched the encoder with several one-to-many auxiliary heads (ATSS, Faster R-CNN style) during training while keeping the one-to-one decoder for NMS-free inference [46]. Finally the real-time branch closed the speed gap with YOLO and is the branch most relevant to field deployment: RT-DETR introduced a hybrid encoder that decouples expensive multi-scale interaction from cheaper intra-scale processing, beating comparable YOLOs at real-time rates [47]; RF-DETR separated weight training from architecture selection via weight-sharing neural architecture search over a DINOv2 backbone, emitting a whole family of real-time detectors from one training run [48]; and Le-DETR replaced the costly backbone and encoder with neighbourhood-attention components (EfficientNAT, NAIFI) for further efficiency, reaching 52.9/54% AP at real-time speed [49]. For FFB scenes these detectors are useful comparators for contextual multi-scale reasoning and for their built-in instance-uniqueness, but their training data appetite and deployment cost must be justified by a measured gain over a compact convolutional RGB baseline on the actual plantation data, not by their COCO standing.

IV. MONOCULAR DEPTH: A DECADE OF MAKING GEOMETRY AVAILABLE FROM RGB (2014–2026)

Depth can be supplied by a registered RGB-D sensor, by stereo reconstruction, or by a depth-prediction model operating on RGB alone. These sources must not be collapsed into one variable, and the monocular-depth literature is the clearest record of how the field learned what a predicted depth map does and does not mean. Two surveys anchor the arc: Ming *et al.* organized 2014–2020 methods by supervision signal, because that choice determines the dataset, the loss, and whether the output is metric or merely relative [50]; and a more recent survey traces monocular *metric* depth from geometry-based methods to current foundation models, precisely the distinction that matters when an FFB task reports a physical range [51].

The supervised branch began with Eigen *et al.*, who were the first to predict a dense depth map from a single RGB

TABLE I
QUESTIONS THAT TURN DETECTOR COMPARISON INTO FFB-RELEVANT EVIDENCE.

Question	Evidence to measure	Why it matters for TBS counting
Can small and occluded bunches be found?	AP/recall by object size and occlusion stratum	Aggregate AP can conceal loss of distant or frond-covered bunches.
Does the detector separate instances?	Split/merge errors, instance recall, and per-tree count error	A box-level score does not expose a merged pair or a duplicate instance.
Can the system operate on the platform?	End-to-end latency, memory, power, and throughput on target hardware	FLOPs or desktop FPS are not field latency.
Does classification remain attached to the right bunch?	Per-instance maturity accuracy and calibration	Maturity labels are operational only when their associated bunch is correct.

image with a deep network and who already identified the problem that shapes the entire field: absolute per-pixel depth from one image is ill-posed, so the network is trained on a scale-invariant error that measures depth *relations* (which pixel is nearer, by what ratio) rather than absolute values. A coarse network reads the whole image to capture global layout, and a fine network refines it locally [52]. This scale-invariance is not a technicality; it is the reason a monocular depth map cannot be treated as a distance measurement without extra calibration, a caveat that propagates directly to any FFB pipeline that would use predicted depth to place a bunch in space. BTS inherited the supervised setting and improved how coarse features become fine depth: instead of blindly upsampling, each feature cell at reduced resolution predicts the four coefficients of a local 3D plane, and depth for every pixel in the corresponding patch is computed from that plane, injecting a geometric prior into the decoder [53]. AdaBins reconsidered the output representation itself, arguing that a fixed discretization of the depth range is wasteful: a transformer module reads the whole scene and predicts per-image adaptive bin widths, and the final depth is a bin-centre expectation, so the model spends resolution where the particular image needs it [54]. DPT then swapped the convolutional encoder for a Vision Transformer and exploited the property that token count never changes through the layers, assembling tokens from several depths into multi-resolution feature maps that give dense prediction a constantly global receptive field [55]. NeWCRFs kept the accuracy-through-structure idea but expressed it as optimization, computing a fully-connected conditional random field within each local window via multi-head attention over a Swin backbone, so neighbouring depth predictions are made mutually consistent at tractable cost [56]. Across this branch the trajectory is from raw regression toward ever-stronger geometric and structural priors, but all of it still requires dense ground-truth depth for training, the constraint the next branch removes.

A parallel self-supervised branch removed the need for depth labels by turning depth into a by-product of image reconstruction, attractive for agriculture, where dense ground-truth depth is expensive or impossible to collect in the field. Godard *et al.* reasoned that a function able to synthesize the right-hand stereo view from the left must implicitly encode scene geometry; that geometry is expressed as a disparity map, and a left-right consistency constraint enforces that the two predicted disparities agree, so the network learns depth

from stereo pairs alone with no depth labels [57]. Monodepth2 inherited this setup and, rather than enlarging the model, fixed how the reconstruction error is computed: it takes the per-pixel *minimum* reprojection error over multiple source frames (so an object occluded in one frame is not penalized), auto-masks pixels that do not move relative to the camera (removing a common failure on scenes with a moving-with-camera object), and samples the loss at multiple scales [58]. These loss-level corrections, not architecture, produced the gains, a reminder that in self-supervised depth the supervision signal is the design surface. PackNet attacked the detail-loss problem of downsampling by replacing lossy pooling with a symmetric 3D packing/unpacking operation that moves spatial detail into the channel dimension and back, learned with 3D convolutions, and trained self-supervised from monocular video [59]. MonoIndoor adapted the paradigm to the indoor setting, whose depth range varies wildly between rooms, by factorizing the prediction into a single global scale (one number for the whole image) and a scale-free relative depth map, with the global scale predicted separately [60]. That scale/shape factorization is important beyond indoors: it reappears as the organizing idea of the metric-depth foundation models below, and it is exactly the decomposition an FFB system needs if it wants scene structure from cheap monocular depth while treating absolute scale as a separately-calibrated quantity.

The decisive recent shift is toward zero-shot, cross-dataset robustness and, eventually, metric transfer, the property that would let a depth model trained elsewhere be used on a plantation without retraining. MiDaS made the enabling observation that many applications need not absolute metric depth but correct relative structure (which is nearer, by how much); if the training target is only relative depth, then datasets with incompatible scales and offsets can be mixed, so MiDaS trained on five heterogeneous datasets with a scale-and-shift-invariant loss in disparity space and generalized far better across scenes than any single-dataset model [61]. Metric3D then confronted the reason relative models cannot report metres: the same object at the same distance produces a different pixel size under different focal lengths, so scale is fundamentally ambiguous across cameras. Rather than let the network guess the camera, Metric3D transforms every image into a canonical-camera space with a simple geometric operation before the network sees it, removing focal-length ambiguity and enabling zero-shot *metric* prediction when the intrinsics are known [62]. ZoeDepth reached metric depth by

a two-stage route that revives the MonoIndoor factorization at scale: relative-depth pretraining on twelve datasets learns robust structure, and lightweight metric bins with attractor layers, fine-tuned per domain, attach an absolute scale [63].

The foundation-model era moved the bottleneck from labels to images. Depth Anything scaled supervision from $\sim 1.5\text{M}$ labelled images to roughly 62M automatically pseudo-labelled unlabelled images, using a teacher model to annotate the cheap and diverse unlabelled data, and became a robust general-purpose relative-depth backbone [64]. Depth Anything V2 separated the two things the previous model conflated, label accuracy and data diversity, by training a very large ViT-Giant/DINOv2 teacher on 595K precisely-labelled *synthetic* images and using it to pseudo-label a large real corpus, sharpening detail while keeping generalization [65]. Marigold took an orthogonal route, repurposing the latent U-Net of a pretrained Stable Diffusion image generator into an affine-invariant depth estimator by casting depth as a conditional denoising problem, trained only on synthetic data yet transferring well to real images [66], evidence that a strong visual prior can substitute for large labelled depth corpora. The current frontier pushes on views, cameras, latency, and controllability, and each axis matters for a field system. Depth Anything 3 shows that a single plain transformer with a depth-ray prediction target can recover geometry consistent across arbitrary views, merely by re-arranging tokens across views [67]. UniDAC generalizes metric depth to perspective, fisheye, and other camera models by predicting a scale-free shape branch and a separate scale branch and combining them [68], again the shape/scale split, now made camera-universal. AsyncMDE targets the latency wall a foundation model creates on a moving platform, amortizing a frozen Depth Anything V2 ViT-B (97.5M parameters) through a 3.83M-parameter fast asynchronous path so depth can be produced in real time [69]. FocusDepth couples a segmentation prompt (SAM) with a depth foundation model through a fusion module so prediction can be focused on a chosen region [70], conceptually the ability to say “give me depth for this bunch,” which is precisely what an instance-constrained depth sample requires. None of these advances, however, converts a predicted relative map into a valid distance measurement by itself, and the correlated-error problem is acute for FFB use: a pseudo-depth map derived from RGB shares its errors with the very image that generated it, so it is a structural prior rather than an independent sensor observation. Any FFB task that reports physical range, bunch position, or inter-frame geometric association must therefore declare which kind of depth it uses, calibrate and evaluate that interpretation explicitly, and down-weight depth wherever it contains holes, boundary artefacts, or a confidence failure under direct sunlight.

V. RGB-D FUSION FOR DENSE PREDICTION: LOCATION, ALIGNMENT, AND MODALITY RELIABILITY

Fusion is where the value of depth is decided. The strategic question is not whether to add a depth channel but *where* in the network to combine modalities and *how* to handle the case in which depth is unreliable. Early fusion concatenates

RGB and depth at the input; feature (middle) fusion learns modality-specific representations before exchanging them; late fusion combines predictions (Figure 6). These are competing experimental conditions, not cosmetic variants, and three sub-literatures in the corpus, RGB-D salient-object detection, RGB-D semantic segmentation, and RGB-D detection, each explored them in depth.

A. RGB-D salient-object detection (2019–2025)

Salient-object detection (SOD) is the sub-literature that confronted depth quality most directly, and it is therefore the most instructive for an FFB system that cannot assume clean depth; the space is surveyed comprehensively by Zhou *et al.*, whose taxonomy classifies methods by how and where depth is fused [71]. The early methods each proposed a different answer to “how should a depth map enter the network,” and reading them in sequence exposes the design space. DMRANet refused to add raw depth to RGB, instead transforming depth at each level into a residual complement so that RGB remains the backbone and depth only supplies the missing cue, combined through multi-scale recurrent attention [72]. BBS-Net treated multi-level features differently by their character rather than fusing them all at once: high-level “teacher” features first produce a coarse saliency map that gates the low-level “student” features, with a separate depth-enhancement module [73]. JL-DCF took the opposite, minimalist stance: treat the depth map as just another image and push both modalities through one shared siamese backbone, so a single set of weights learns to serve both [74]. S2MA fused not the features but the modalities’ non-local attention affinities, adding each modality’s self-affinity matrix to the other’s so geometry-based and appearance-based notions of “which positions relate” reinforce each other [75]. HDFNet reframed depth’s role entirely, using it not as a fused feature but as the generator of input-specific dynamic convolution kernels, so depth decides *how* RGB is filtered [76]. UC-Net was the first to model the uncertainty of human annotation itself with a conditional variational autoencoder, predicting a distribution of plausible saliency maps rather than one deterministic answer [77], and CoNet made a choice with direct deployment value: it uses depth only as a training-time collaborative signal (alongside edge and saliency heads sharing an RGB encoder), so that at inference no depth map is required at all [78]. For a plantation where depth may be intermittently unavailable, a model that needs depth only during training is an attractive template.

The pivotal source for this review is D3Net, which states the governing principle in one sentence: depth is an optional input that must pass a quality test before it is trusted. It produces three saliency maps (from RGB alone, from the fused pair, and from depth alone), and a gating mechanism down-weights a low-quality depth map, exactly the behaviour an outdoor FFB system needs when active depth fails under sunlight [79]. The transformer wave then rebuilt SOD on attention. VST posed saliency as sequence-to-sequence prediction over patch tokens in one framework unifying RGB and RGB-D, so long-range dependencies across the image are modelled at every layer [80], and TriTransNet strengthened the top three feature levels




Fig. 6. The three fusion locations that structure the RGB-D literature. Early fusion concatenates colour and depth at the input (e.g. FuseNet, Expandable YOLO); middle/feature fusion learns modality-specific representations before exchanging them at selected scales; late fusion combines predictions and supports an explicit RGB fallback.

with three weight-shared transformer encoders where attention is affordable, refining depth features alongside [81]. A cluster of methods refined how depth informs RGB: DSA2F splits the raw depth map into regions by its histogram modes and turns each into a spatial attention mask over RGB [82]; DCF makes the quality problem explicit by first calibrating raw depth against the RGB image and only then fusing, separating correction from combination [83]; and SPNet preserves RGB-specific, depth-specific, and shared streams in parallel so specificity is not lost in a premature merge [84]. The most recent methods combine strong backbones with bidirectional fusion: SwinNet drives edge-aware RGB-D and RGB-T SOD with dual Swin backbones and spatial-then-channel cross-modal alignment [85], CIR-Net interacts the modalities at both encoder and decoder through a three-stream design [86], and MobileSal shows the efficiency ceiling by restoring depth information only during training and reaching 450 FPS at deployment [87], a data point that a quality-aware depth branch need not be expensive at inference. HiDAnet exploits hierarchical depth granularity, discretizing the depth histogram with multi-Otsu into regions that align with the network’s own coarse-to-fine hierarchy [88]; CAVER unifies RGB-D and RGB-T through a view-mixed transformer that treats fusion as a sequence of context updates by shared attention units [89]; and GL-DMNet replaces one-way fusion with parallel position-mutual and channel-mutual modules so RGB and depth filter each other bidirectionally [90]. The consistent, transferable message across a decade of SOD is that fusion should enable cross-modal correction and reduce dependence on an unreliable depth observation, but every one of these




Fig. 7. The cross-modal attention mechanism that recurs across the strongest RGB-D methods (e.g. SA-Gate, CIR-Net, CMX): each modality generates a weighting map that gates the other before fusion, so a faulty depth measurement can be suppressed rather than allowed to contaminate the joint representation.

results is on saliency benchmarks with clean indoor depth, not on agricultural boxes under field conditions, so they justify testing quality-aware fusion for FFBs rather than asserting it will help.

B. RGB-D semantic segmentation (2016–2025)

Semantic segmentation traced the same fusion-location question but under dense per-pixel supervision, which makes its architectural conclusions unusually clean. FuseNet set the template that most later work varies: give depth its own encoder branch identical to the RGB branch and combine the two at the feature level rather than at the pixel level, summing

depth features into the RGB branch at several stages [91]. RDFNet inherited the two-branch idea and made the fusion learnable and residual, extending RefineNet so colour and HHA-encoded depth are fused through trained residual blocks at four resolutions before multi-resolution refinement [92]. RedNet showed that a deep RGB-D encoder-decoder trains well if every unit is residual and supervision is applied not only at the output but at intermediate layers [93]. ACNet separated two questions that earlier work had conflated, how the architecture preserves each modality’s feature flow and how the network decides each modality’s contribution per location, answering the first with three parallel branches and the second with channel-attention modules that weight RGB against depth pixel by pixel [94]. SA-Gate then crystallized the principle most relevant to unreliable outdoor depth: filter before you fuse. A cross-modal gate, computed from the other modality, suppresses features arising from a faulty depth measurement before they can contaminate the joint representation [95], the segmentation counterpart of D3Net’s quality gate and a strong candidate mechanism for FFB depth that fails intermittently. This bidirectional cross-modal gating, shared by the strongest RGB-D methods, is illustrated in Figure 7.

The efficiency and transformer branches followed. ESANet demonstrated that two efficient shallow encoders (factored ResNet-34 blocks) with cheap Squeeze-and-Excitation depth fusion can rival much heavier RGB-D methods at deployment-friendly latency, a direct relevance for on-platform inference [96], and ShapeConv made convolution itself depth-aware by decomposing each depth patch into a base component (its mean, i.e. where it sits relative to the camera) and a shape component (the residual local relief), processing them separately [97]. SegFormer contributed a simple, strong RGB backbone-decoder design: a hierarchical MiT encoder without explicit positional encoding plus a lightweight MLP decoder, which many RGB-D methods adopt as their base [98]. TokenFusion addressed multimodal transformers economically by detecting uninformative token slots via a learned score and reusing them for tokens from the paired modality rather than adding tokens [99]. EMSANet solved semantic, instance, and panoptic segmentation plus orientation and scene classification from one shared RGB-D encoder with task-specific heads, showing that a single fused representation can serve several outputs at once, relevant because FFB perception must emit detection, maturity, and geometry together [100]. Omnivore pushed modality-generalization further, using one Swin model with shared weights to classify images, video, and RGB-D by unifying the token format at the input rather than the architecture at the top [101]. The most recent methods refine cross-modal exchange: CMX generalizes fusion to arbitrary RGB-X pairs (depth, thermal, event, LiDAR) through bidirectional feature rectification before a cross-attention fusion [102]; DFormer moves RGB-D fusion out of fine-tuning and into pretraining, training the backbone from the start on ImageNet image-depth pairs so cross-modal interaction is baked into every block [103]; GeminiFusion exploits the pixel-aligned nature of registered RGB-D: feature at pixel i in one modality is most relevant to pixel i in the other, for a per-pixel fusion with linear complexity, reaching 56.8% mIoU on NYU [104]; and

DiffPixelFormer separates the differential and shared pixel-level components of the two modalities for indoor segmentation [105]. As a body these are mechanism sources for cross-modal correction and quality-aware fusion, not agricultural validations, and their indoor sensors and clean registration are precisely the conditions an oil-palm canopy violates.

C. RGB-D and multimodal object detection (2017–2025)

Detection-specific fusion is where the corpus speaks most directly to the FFB architecture, and one study in it is the single most important piece of transferable evidence in this review. Ophoff *et al.* treated the fusion position not as a fixed design choice but as a free parameter to be swept: they duplicated a 27-layer YOLOv2 into two identical branches (one RGB, one depth) and tested 28 possible fusion locations along the network, finding that middle and late fusion were consistently more competitive than naive early (input-level) fusion on their data [106]. The transferable conclusion is not that a specific layer is optimal for FFBs (datasets and objects differ) but the mechanism-level lesson that separate modality pathways should be preserved long enough for the network to decide which evidence is useful, which is exactly the hypothesis an FFB ablation should test. Expandable YOLO represents the opposite, early-fusion extreme: it appends depth as a fourth input channel to YOLOv3 and adds 3D convolution near the output, keeping the input a single (four-channel) image [107], a cheap baseline worth including precisely because Ophoff predicts it may underperform. More recent systems abandon the single-network assumption and cascade cheap models, a pattern well suited to a resource-constrained plantation platform. FusionVision chains a fast YOLOv8 detector with FastSAM: detection narrows the search to per-object boxes, segmentation refines masks, and the masks are back-projected to 3D from the RGB-D depth, reconstructing and segmenting objects in 3D without running an expensive model over the whole image [108]. DODT runs an ensemble of lightweight detectors in parallel and fuses their outputs for onboard dynamic-object detection and tracking from an RGB-D camera on a small quadcopter, trading single-model peak accuracy for robustness and speed on limited hardware [109]. YOLOv8-URE uses 2D detection as a coarse filter that prunes a point cloud to a small object-relevant subset before 3D registration refines the pose for grasping in stacked scenes, the “detect in 2D, localize in 3D on a reduced set” pattern that recurs throughout the 3D and pose literature [110]. The broader design space is organized by Feng *et al.*, whose survey classifies multimodal detection and segmentation for autonomous driving along the three axes of what to fuse, when to fuse, and how to fuse [111], and PointNet supplies the permutation-invariant point-set backbone, processing each point by a shared MLP then aggregating with a symmetric function, that underlies much of the 3D branch discussed next [112]. Taken together, this sub-literature makes a defensible FFB hypothesis concrete: a feature-level or late-fusion detector with an explicit RGB fallback when a depth-quality signal is poor, evaluated against an RGB-only baseline and an early-fusion baseline at matched resolution and hardware, not the




Fig. 8. The two recurring patterns for integrating YOLO with depth. Pattern one expands the input to four channels and fuses at the input (Expandable YOLO), which Ophoff *et al.* find is dominated by intermediate fusion; pattern two detects in 2D and then projects or refines in 3D on a reduced region (FusionVision, YOLOv8-URE).

TABLE II
FUSION ALTERNATIVES TO BE EVALUATED ON THE SAME FFB DATA.

Strategy	Potential value	Failure mode to test
Early fusion	Minimal architectural change; may exploit aligned low-level cues	Raw depth noise or scale mismatch can contaminate RGB features.
Feature fusion	Lets each modality form task-specific features before exchange	Fusion scale and alignment become hyperparameters; extra compute must be justified.
Late fusion	Supports a strong RGB fallback and explicit confidence weighting	May miss fine complementary cues needed to separate crowded instances.
Cross-modal attention / gating	Can select or suppress modality evidence by context	Attention is not a guarantee of robustness; missing-depth and sunlight ablations are required.

untested claim that adding depth necessarily improves detection. The two recurring YOLO+RGB-D integration patterns — input-channel expansion versus detect-then-project — are contrasted in Figure 8, and Table II enumerates the fusion alternatives together with the specific failure mode each must be tested against.

VI. THREE-DIMENSIONAL PERCEPTION: FROM BOXES TO METRIC LOCALIZATION (2017–2023)

RGB-D detection is not identical to three-dimensional perception. A box contains foreground, background, and often a

mixture of depth layers, so a proposed FFB pipeline should not treat an arbitrary centre-pixel depth as a bunch range; it should use robust statistics over a valid instance region and retain an uncertainty value. The autonomous-driving 3D-detection literature is the richest record of how the field learned to turn depth and geometry into reliable object localization, surveyed by Arnold *et al.* along the axis of sensor modality and data representation [113].

The lineage begins with the problem of how to represent an unordered point cloud so a network can process it, and each answer trades accuracy against speed. MV3D projected LiDAR into two structured 2D views, bird’s-eye (BEV) and front view, so ordinary convolutions apply, and used BEV as the main proposal source because a top-down view preserves physical object size; it fused these with RGB through region-based deep fusion [114]. AVOD inherited this framework and moved the BEV-RGB fusion as early as possible, into the region-proposal network itself, so proposals consider both modalities from the start rather than validating them late, using a high-resolution FPN-style extractor [115]. VoxelNet removed the hand-designed projection by discretizing space into voxels and learning voxel features end-to-end from raw points with a Voxel Feature Encoding layer [116], but 3D convolution over voxels is slow; PointPillars fixed this by collapsing the height axis into vertical “pillars” so the entire detector runs in efficient 2D convolutions, fast enough for real-time [117]. PointRCNN inverted the usual order, first segmenting foreground points and letting each such point propose a box bottom-up rather than guessing box locations from anchors [118], and PV-RCNN combined the two representations, using efficient sparse-voxel

convolution to generate proposals and point-based set abstraction at a small number of keypoints to enrich them before refinement [119]. Frustum PointNets is the most FFB-relevant member of the family because it is the cleanest statement of the “detect in 2D, localize in 3D” decomposition a bunch-counting pipeline would use: a 2D detection box on the RGB image is projected into a 3D viewing frustum, and a sequence of PointNets then segments and regresses the object only within that narrowed region [120]. The pseudo-LiDAR line carries an equally important lesson about representation: Wang *et al.* showed experimentally that the same depth data yields far better 3D detection when stored as a back-projected point cloud than as a front-view depth map, because 3D convolutions then operate in a physically meaningful space [121], and Pseudo-LiDAR++ improved the source depth by retraining the stereo network directly on depth error rather than disparity error [122]. For an FFB system these two results caution that how a depth measurement is represented can matter as much as its raw accuracy.

Camera-LiDAR fusion then matured toward learned, calibrated association. PointPainting decorates each LiDAR point with the semantic-segmentation class scores of the image pixel it projects to, before any 3D detector runs, a simple sequential fusion that lifts several detectors at once [123], and 3D-CVF aligns camera features into the LiDAR BEV space through an auto-calibrated projection and fuses them with location-dependent adaptive gating rather than uniform weights [124]. CenterPoint reframed 3D detection, like its 2D cousin CenterNet, as centre-point heatmap prediction on BEV and thereby simplified multi-object tracking to centre association across frames [125], directly relevant to the counting problem, where tracking centres across a traversal is the association task. The transformer wave replaced fixed point-to-pixel correspondence with learned soft association: TransFusion represents each candidate as an object query that attends over both LiDAR and image features in two decoder layers, robust to calibration error [126]; BEVFormer builds a learnable BEV query grid filled by spatial attention over current-frame cameras and temporal attention over the previous BEV, adding a time dimension [127]; DETR3D lets each learned 3D object query project its own reference point into every camera to gather features, so the query decides which view is relevant [128]; and BEVFusion encodes each modality independently into a shared BEV space before fusing, so neither is projected onto the other and each survives the other’s failure [129]. None of these is an FFB solution: they use LiDAR, driving-scale scenes, and calibrated multi-camera rigs absent from a plantation. As a body, though, they establish the coordinate-frame discipline a counting pipeline needs. Geometry’s real contribution is not an extra coordinate but the ability to distinguish look-alike regions, to reject a re-observation at a previously mapped location, and to estimate reachability, and every one of these requires explicit intrinsics, registration, and depth-scale handling rather than an unqualified centre-pixel depth read from a box.

VII. OBJECT POSE AND ROBOTIC GRASPING: INSTANCE-LEVEL GEOMETRY AND CONFIDENCE (2015–2024)

Pose estimation and grasping are transferable as method evidence because both must reason about instance boundaries, geometry, occlusion, and coordinate transforms before a robot acts, and both make the confidence of that reasoning explicit, which is the analogue of deciding whether to commit a new inventory record. Hoque *et al.* survey the shared taxonomy of 3D detection and 6D pose across RGB, depth, and RGB-D inputs [130].

For 6D pose the guiding idea, established by PoseCNN, is to decompose the task by the visual nature of each parameter: translation determines where an object appears and how large it looks, rotation determines its surface appearance, so translation is recovered geometrically from per-pixel centre-direction voting plus a depth estimate while rotation is regressed separately, all in cluttered scenes [131]. DenseFusion inherited the RGB-D setting and replaced global fusion with dense local fusion: the depth map becomes a point cloud via the camera intrinsics, each point is paired with its aligned colour feature, one pose is predicted per point, and a learned selection step picks the most reliable, an architecture built around the fact that some points are more trustworthy than others [132]. PVN3D moved keypoint detection out of the image plane into 3D, training each point to vote an offset toward each target 3D keypoint and solving for pose by least squares, which is more robust to occlusion than 2D keypoints [133], and G2L-Net decomposed the problem into a global-to-local sequence: global localization by a 3D sphere, then translation and rotation in the object’s own frame, to run in real time [134]. FFB6D, whose acronym coincides with fresh-fruit-bunch work but denotes “full flow bidirectional,” exchanges RGB and geometry features in both directions at every encoder and decoder layer, so each branch is continuously informed by the other rather than fused once at the end [135], the most thorough expression of the bidirectional-fusion principle seen throughout the RGB-D literature. The remaining methods broaden applicability: GDR-Net unifies dense 2D-3D correspondence with end-to-end differentiable direct regression [136]; ZebraPose encodes an object’s surface as a hierarchical binary code predicted densely per pixel, turning continuous coordinate regression into coarse-to-fine classification [137]; OnePose reframes pose as visual localization against a structure-from-motion model built from a reference video, needing no CAD model or per-object training [138]; and FoundationPose unifies estimation and tracking of *novel* objects through render-and-compare over a neural implicit representation, a foundation-model approach that removes the per-object assumption entirely [139]. The transferable pattern for FFBs is the confidence-aware decomposition these methods share: constrain the geometry to a hypothesized instance, estimate a meaningful state, and quantify how reliable that estimate is.

Grasping supplies the closest analogue in the corpus to committing an action under geometric uncertainty: the decision to add one inventory record, update an existing one, or defer. Lenz *et al.* framed grasp detection as binary classification over

oriented candidate boxes from RGB-D, the direct transfer of object-detection thinking to manipulation [140], and GG-CNN reframed it as per-pixel regression, predicting a grasp quality, angle, and width at every pixel of a depth image in a single tiny 62,420-parameter forward pass fast enough to close the control loop [141]. GR-ConvNet kept the per-pixel formulation but strengthened it with a generative residual architecture predicting quality, angle, and width maps from RGB-D [142], and GR-ConvNet v2 refined the same design with Mish activation, dropout, and the Ranger optimizer to reach roughly 98% grasp accuracy [143]. The 6-DoF branch moved from planar grasps into full clutter: VGN turns grasp detection into dense regression over a truncated signed-distance volume, emitting a quality, orientation, and width per voxel [144], and Contact-GraspNet shrinks the search space by anchoring each grasp to an observed point on the object surface, so three of the translation degrees of freedom are fixed by the data [145]. BCMFNet adds bilateral cross-modal attention so RGB and depth query each other before fusion, the grasping instance of the bidirectional-fusion idea [146]. Two datasets underwrote this progress by replacing human labelling with computation: Jacquard generated grasp labels entirely through physics simulation on ShapeNetSem CAD models, yielding over 54k rendered images of 11k objects with more than one million successful grasp annotations [147], and GraspNet-1Billion analytically scored over 1.1 billion grasps across 190 scenes and 97,280 RGB-D images from two cameras [148], a scale worth noting for an FFB program, since a similar analytic or simulated labelling strategy could reduce the annotation burden of a plantation dataset. The transferable decomposition for counting is thus: identify an instance, estimate a geometrically meaningful state, assess confidence, and commit only when the state is adequate, a conservative policy preferable to adding every high-score box to the total.

VIII. FROM DETECTION TO RELIABLE COUNTING: SLAM, CAMERA POSE, AND TEMPORAL ASSOCIATION (2017–2022)

A detector operates on one frame; an inventory is defined over a traversal. The missing connection is association: deciding whether an object in a new frame is an already-observed bunch or a new one, and this is the mechanism that converts good per-frame detection into a correct count. Appearance similarity alone is fragile in a plantation where neighbouring bunches look alike, and geometry alone is fragile where depth is incomplete or the camera pose is uncertain, so the count should emerge from the agreement of detection, instance separation, depth or projected position, camera motion, and temporal continuity. SLAM systems are the corpus’s evidence on the camera-motion component, because they express successive views in a common coordinate frame. ORB-SLAM2 built a feature-based system on the fast, rotation-robust ORB descriptor that runs on monocular, stereo, and RGB-D cameras with tracking, local mapping, and loop closure, differing across sensors only in how each feature’s depth is obtained [149]. ORB-SLAM3 extended this to a unified visual, visual-inertial, and multi-map system, formulating visual-inertial initialization

as a maximum-a-posteriori estimation from the start and supporting pinhole and fisheye models [150]. DROID-SLAM took the learned route, embedding a differentiable dense bundle-adjustment layer inside a recurrent network that iteratively updates optical flow and pose across monocular, stereo, and RGB-D input [151]. These provide the common frame in which two detections can be tested for spatial compatibility, but a plantation violates the static-world assumption most SLAM systems make.

The dynamic-scene branch is therefore directly relevant, because a canopy is full of moving fronds, wind-driven motion, and self-similar repetitive texture that corrupt pose estimation. DynaSLAM extends ORB-SLAM2 with two complementary signals, a Mask R-CNN semantic prior that flags a-priori movable classes and multi-view geometric verification that detects actual motion, and discards features on dynamic regions before they are used for pose or mapping [152]. DS-SLAM runs semantic segmentation (SegNet) and epipolar motion-consistency checking as two parallel processes and combines them to decide which objects are truly moving, cutting trajectory error sharply in dynamic scenes [153]. CFP-SLAM replaces the binary static/dynamic label with a continuous probability computed coarse-to-fine, from the object level (a YOLOv5 detection) down to individual keypoints, using optical-flow and epipolar constraints [154], a graded-confidence approach that mirrors the quality-gating seen in the depth and fusion literature. Soares *et al.* contribute the methodological template most useful to this review: they inserted YOLO and Mask R-CNN, in turn, at an identical dynamic-object-filtering position in ORB-SLAM2 while holding every other component fixed, isolating the accuracy-versus-speed trade-off of the detector choice as a single controlled variable [155]. That is exactly the discipline an FFB study needs when it asks whether a heavier detector earns its cost. None of these systems counts objects, but together they show how camera pose and dynamic-content handling make cross-frame association geometric rather than a naive appearance match, and that the reliability of that association in vegetation is an empirical question, not a free assumption.

There are at least four counting failure modes to report separately: a bunch missed in every frame, two nearby bunches merged into one instance, one bunch split into several, and a bunch correctly detected repeatedly but never linked: a duplicate count. Image-level AP responds mostly to the first three; absolute count error per tree, per row, or per traversal is needed to expose the fourth. A geometry-aware association policy can be expressed as a sequence of gates: check detector confidence and maturity label; check whether the depth observation is valid and compatible with the candidate instance; project the candidate into a common frame using the current pose estimate and compare it to the uncertainty region of existing records; and finally resolve competing matches by appearance and temporal continuity. When the depth or pose gate fails, the system should fall back to RGB tracking as a weaker cue and report the degraded condition rather than treating unavailable geometry as a zero measurement. This yields clean ablations: appearance-only association, depth without pose, pose-aware geometric association, and a quality-gated variant,

each reporting count error alongside false merges, false new records, and unresolved observations.

IX. MULTIMODAL EVIDENCE BEYOND RGB-D: WHAT TRANSFERS AND WHAT DOES NOT (2015–2026)

The corpus also contains RGB-thermal pedestrian perception, remote sensing, medical imaging, and industrial inspection. These areas must not be merged with agricultural evidence, but they expose recurring multimodal and small-object questions and repeatedly show that concatenation is an assumption about calibration.

RGB-thermal pedestrian detection is the corpus’s cleanest study of confidence-aware fusion under changing illumination, which is the FFB problem of deep shadow versus direct sunlight in a different guise. The KAIST benchmark made the enabling hardware choice, using an optical beam-splitter rig to align RGB and thermal pixel-for-pixel at capture time rather than correcting misalignment afterward [156], a reminder that paired-modality registration is a data-collection decision, not only an algorithmic one, and directly relevant to how an FFB RGB-D rig must be built. IAF R-CNN then made the key mechanistic observation that the reliability of each modality depends on illumination: it estimates a scalar illumination value for the image through a small sub-network and uses it to weight the RGB and thermal branches per image, so the model leans on thermal at night and RGB by day [157]. MBNet argued that fusing only at the score level is too late and injected a differential modality-aware signal at each convolutional stage, plus alignment, to address the imbalance where one modality dominates [158]. CFR replaced a single fusion step with a cycle of fuse-and-refine blocks, iterating the combination several times so the modalities progressively correct each other [159], and GAFF staged the fusion into intra-modal attention (highlighting informative regions within each modality) followed by inter-modal attention (weighting one modality against the other) [160]. CFT posed RGB-thermal fusion as self-attention over a single joint token sequence inside a two-branch YOLOv5, so every RGB token can attend to every thermal token directly [161]. A method that exploits thermal contrast at night does not establish that RGB-D helps under tropical sunlight, but this lineage supplies exactly the illumination-conditioned and modality-imbalance ablations an FFB study must run before claiming a depth gain.

Remote sensing is the corpus’s small-object and high-resolution laboratory, and a distant bunch under a moving platform is a small object. YOLT tiled huge satellite images spatially and tuned the detector’s internal resolution rather than downscaling the image, so tiny objects survive [162]. TPH-YOLOv5 added a fourth high-resolution prediction head (P2) and a transformer prediction head to YOLOv5 for drone imagery, precisely to recover the small objects that dominate aerial scenes [163]. UAV-YOLOv8 combined BiFormer dynamic attention, which suppresses irrelevant background in the backbone, with efficient partial convolution to strengthen micro-object representation [164], and RiO-DETR extended the real-time DETR framework to oriented object detection by decoupling angle handling from position across the query

representation, attention, and matching [165]. These small-object and orientation techniques are candidate modifications for detecting distant, variably-oriented bunches.

Medical and industrial inspection show the same general detector specialized into high-stakes, defect-sensitive domains, demonstrating both how to adapt YOLO and why generic numbers do not transfer. In medicine, a single-stage YOLO predictor performed simultaneous COVID-19 lesion detection and classification directly from full-resolution chest X-rays [166]; a YOLO-based decision-level fusion combined several class-specialized YOLOv3 models to trade off the high sensitivity of single-class models against the flexibility of a multi-class one for breast-lesion detection [167], a fusion-of-specialists idea transferable to distinct maturity classes; and a systematic review synthesized 124 medical YOLO studies into a taxonomy of clinical modality, YOLO architecture, and task, quantifying how pervasively the family has been adapted [168]. In industry, a comparative study transfer-learned the YOLOv5 s/m/l/x variants for safety-helmet detection and mapped which variant best fits a real deployment [169]; EFC-YOLO redesigned YOLOv7’s feature processing with a Fusion-Faster module to reduce spatial redundancy while preserving defect-position information on steel strips [170]; and PCB-YOLO enhanced YOLOv8n with coordinate attention and multi-scale fusion to catch tiny printed-circuit-board defects while cutting parameters [171]. The recurring lesson across medicine and industry is that a general detector is routinely re-tuned to a domain’s specific object scale and failure costs, the exact adaptation an FFB detector requires, which is also exactly why a COCO or VOC number cannot be read as an expected plantation result.

X. BENCHMARK DATASETS: WHAT A SCORE CAN AND CANNOT MEAN (2012–2020)

Benchmark data determine what a model can learn and what a score can mean, and the six datasets in the corpus explain both why the transferable methods above exist and why none of them is a substitute for a plantation benchmark. NYU Depth v2 recorded 1,449 densely annotated indoor RGB-D images from 464 scenes with a Kinect, adding not only per-pixel class labels but instance numbers and physical support relations, which made structured indoor understanding learnable for the first time [172]. SUN RGB-D assembled 10,335 RGB-D images from several modern depth sensors and improved the raw, hole-ridden depth maps, providing scene-understanding annotations at scale [173], and ScanNet paired cheap consumer-sensor acquisition with an automated server-side reconstruction pipeline and staged crowdsourced labelling to deliver 1,513 richly annotated 3D reconstructions from 2.5M RGB-D frames [174], a template for scaling annotation that an FFB dataset effort could borrow. The whole RGB-D dataset landscape was itself catalogued by Lopes *et al.* through backward-snowballing to trace every public release [175]. On the generic-detection side, Microsoft COCO shifted recognition from isolated objects toward objects-in-context with 328,000 images and instance masks, and it remains the standard source of detection pretraining weights and the AP

vocabulary used throughout this review [176]. For outdoor perception under a moving platform (the condition closest to a ground vehicle in a plantation), KITTI was the first calibrated multi-sensor outdoor benchmark, capturing synchronized stereo, LiDAR, and localization from a moving car [177], and nuScenes extended this to a 360-degree multimodal suite of six cameras, one LiDAR, and five radars over 1,000 driving scenes with no blind spot [178]. Every one of these supports pretraining, depth-registration sanity checks, and controlled ablations, but their indoor geometry or urban-driving context, their sensors, and their object categories differ materially from an oil-palm canopy. None substitutes for a plantation dataset whose visual context, target size, maturity labels, camera trajectory, and sensor failures are themselves part of the scientific question. The corollary for evaluation is strict: splits must separate whole trees, traversal sequences, or collection sessions, and a stronger external test must separate sites, days, sensor settings, and lighting regimes, because randomly mixing frames from one video lets a model memorize background, illumination, or even the same bunch seen from a nearby view.

XI. AGRICULTURAL TRANSFER AND THE BOUNDARY OF CURRENT EVIDENCE (2019–2020)

The verified corpus contains only four direct agricultural perception systems, and none uses oil-palm FFB data, a scarcity that is itself the central finding of the evidence map and the reason this review ends in a research agenda rather than a model recommendation. Onishi *et al.* built an automated apple-harvesting robot that integrates a single-stage SSD detector for 2D fruit localization with stereo-parallax depth reconstruction, then commands the arm to the recovered 3D position [179], the minimal instance of the detect-then-localize pipeline this review advocates, on a fruit far simpler in appearance than an FFB. Gene-Mola *et al.* are the closest methodological analogue: they combined Mask R-CNN instance segmentation with passive structure-from-motion photogrammetry, aggregating detections across many camera viewpoints while moving around an apple tree, and reported F1 improving from 0.816 for 2D detection alone to 0.881 for detection plus 3D location [180]. The transferable lesson is architectural: a 2D fruit instance can be linked to multi-view geometry for location and de-duplicated inventory. The numbers, though, must not be read as expected FFB results, because fruit type, acquisition geometry, annotation, and environment all differ from an oil-palm canopy. Kang and Chen unified fruit detection, instance segmentation, and branch semantic segmentation in one single-stage network with a shared feature extractor for apple orchards, showing that the several outputs an agricultural system needs can share a backbone [181], the same multi-output efficiency argument made by EMSANet indoors, now in a canopy. The field-tested Vegebot lettuce harvester of Birrell *et al.* separated visual sensing from physical manipulation in a two-stage pipeline validated in a real commercial field, harvesting only market-ready heads and cutting at the correct position [182]; its value is the demonstration that perception, geometric localization,

and action are genuinely distinct stages with distinct failure modes. That separation is the crux of TBS planning: a maturity classifier can be excellent on isolated crop images while yield estimates remain unreliable because the system cannot separate crowded instances or reject repeated views, and conversely a stable count does not by itself prove the maturity labels attached to those counted bunches are correct. Both outputs must be retained and measured separately, which is what the metric hierarchy below enforces.

XII. EVIDENCE-MAP SYNTHESIS

Read as a whole, the 182-source history shows a field that has repeatedly solved the sub-problems an FFB pipeline needs (real-time detection, instance separation, monocular and sensor depth, quality-aware fusion, 3D localization, camera-pose estimation, and temporal association), but almost always on objects, sensors, and metrics other than oil-palm bunches. The strongest concentrations lie in general RGB detection (37 sources), monocular depth (21), and RGB-D dense prediction (34 across SOD and segmentation), rather than in paired FFB field trials (zero). Figure 9 depicts this narrowing, from the broad base of mature general vision down to the specific and still-unfilled oil-palm requirement. This is valuable because it supplies a rich catalogue of alternative designs and, more importantly, of documented failure modes; it is limiting because different domains use different objects, cameras, metrics, and levels of interaction with the world. The review therefore treats the corpus as a map from mechanisms to testable hypotheses, not as a statistical pool from which to compute a pooled accuracy. The matrix is not a substitute for reading a source in full: before any numerical result is quoted in a manuscript revision, the verified PDF must be checked in its reported experimental context, because resolution, hardware, split, and post-processing can change the apparent conclusion, especially across YOLO generations, depth models, and fusion architectures.

XIII. A FALSIFIABLE RESEARCH AGENDA FOR RGB-D TBS PERCEPTION

The immediate contribution of the evidence map is a testable program rather than a claimed final architecture; the conceptual pipeline it points to, with each stage corresponding to one ablation below, is sketched in Figure 10. First, construct a paired RGB-D FFB dataset with calibration metadata and annotations for bunch instances, maturity, occlusion, apparent size, illumination, depth validity, and where possible cross-frame identity. Reference counts must be collected at an operational unit such as a tree, short row, or traversal, because frames alone cannot validate a counting system, and splits must separate trees, sequences, and sessions to prevent optimistic transfer.

Second, establish an RGB-only YOLO baseline and one high-capacity comparison such as a two-stage, instance-segmentation, or transformer detector. Third, compare early fusion, at least one feature-fusion configuration, late fusion, and a depth-quality-gated RGB fallback, all under the same split, resolution, annotation policy, and target hardware. The




Fig. 9. The evidence funnel that motivates the research agenda. Mature general RGB detection, cheap foundation-model depth, and RGB-D fusion narrow, layer by layer, toward the specific and largely unfilled requirement: a calibrated paired RGB-D benchmark for oil-palm bunch counting and maturity classification.

TABLE III

METRIC HIERARCHY FOR AN RGB-D FFB STUDY. EACH LEVEL ANSWERS A DIFFERENT QUESTION AND CANNOT BE REPLACED BY A SINGLE AP SCORE.

Evaluation level	Required measurements	Scientific interpretation
Detection	AP, precision, recall, size/occlusion/illumination strata	Determines whether instances are visible to the pipeline.
Maturity	Per-instance class metrics, calibration, confusion matrix	Tests whether the right label is attached to the right bunch.
Geometry	Declared coordinate frame, range or position error, valid-depth rate	Establishes what spatial claims are justified.
Association and count	Count error, bias, duplicate rate, false merges, association precision/recall	Tests the inventory rather than an isolated frame.
Deployment	Latency, throughput, memory, hardware, depth availability	Establishes whether the result is feasible in field operation.


core comparison is causal: does the added depth branch improve a stated failure mode enough to justify its sensor and latency cost?

Fourth, evaluate at the four levels of Table III: detection stratified by size and occlusion; per-instance maturity with calibration reported by illumination; geometry that names whether a prediction is relative depth, calibrated range, or 3D position; and counting with absolute and signed error, duplicate rate, and association quality per sequence. Report latency, memory, and depth status with every accuracy table. Finally, perform failure-oriented ablations: remove depth deliberately, introduce missing or noisy depth, vary RGB-D alignment, compare shaded and sunlit frames, and test both stationary and moving camera sequences. If an RGB fallback matches or exceeds a fusion configuration whenever depth quality is

poor, that is a meaningful deployment finding, not a negative result.

XIV. DISCUSSION

The verified corpus supports three bounded conclusions. First, a multi-scale, real-time RGB detector is an appropriate baseline family for an FFB system, but model selection must be based on field latency and error modes rather than generic leaderboard rank. Second, depth can contribute separation and geometry when its reliability and interpretation are explicitly controlled. Third, feature-level, late, and quality-aware fusion are justified experimental alternatives because they preserve a modality-specific representation and can support an RGB fallback. The corpus does not establish that a particular YOLO generation, depth model, or fusion point is best for oil palm,



Conceptual — not an experimental result.

Fig. 10. The proposed — and explicitly conceptual, not yet validated — RGB-D pipeline for oil-palm FFB perception: a plantation RGB image feeds an RGB encoder and, in parallel, a monocular pseudo-depth branch; quality-aware fusion feeds a real-time detector; per-instance maturity, an instance-constrained depth sample, and pose-based temporal association then produce a de-duplicated bunch inventory. Every stage corresponds to an ablation in the agenda below.

nor a numerical FFB gain from RGB-D. These are precisely the questions that a paired field dataset and controlled ablations should answer; treating transfer evidence as direct proof would make the review sound stronger while making the proposed research less credible.

XV. CONCLUSION

Reliable FFB perception should be framed as detection, maturity assignment, geometry, temporal association, and final counting in one pipeline. Traced across a decade of history, YOLO is a well-motivated real-time RGB baseline; monocular and sensor depth is a conditional geometric cue whose meaning must be declared; and RGB-D fusion is a hypothesis to be evaluated under realistic sensor and illumination failures. The 182-source verified evidence map makes these boundaries inspectable and shows both how the field reached its current tools and where its evidence stops. Its central research implication is clear: progress requires a calibrated paired RGB-D FFB benchmark and an evaluation protocol that measures detection, maturity, geometry, duplicate suppression, count error, and latency together.

REFERENCES

- [1] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, “You only look once: Unified, real-time object detection,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 779–788.
- [2] Z. Zou, K. Chen, Z. Shi, Y. Guo, and J. Ye, “Object detection in 20 years: A survey,” *Proceedings of the IEEE*, vol. 111, no. 3, pp. 257–276, 2023.
- [3] R. Girshick, J. Donahue, T. Darrell, and J. Malik, “Rich feature hierarchies for accurate object detection and semantic segmentation,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2014, pp. 580–587.
- [4] R. Girshick, “Fast r-cnn,” in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2015, pp. 1440–1448.
- [5] S. Ren, K. He, R. Girshick, and J. Sun, “Faster r-cnn: Towards real-time object detection with region proposal networks,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 39, no. 6, pp. 1137–1149, 2017.
- [6] T.-Y. Lin, P. Dollár, R. Girshick, K. He, B. Hariharan, and S. Belongie, “Feature pyramid networks for object detection,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 2117–2125.
- [7] K. He, G. Gkioxari, P. Dollár, and R. Girshick, “Mask r-cnn,” in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2017, pp. 2961–2969.
- [8] P. Sun, R. Zhang, Y. Jiang, T. Kong, C. Xu, W. Zhan, M. Tomizuka, L. Li, Z. Yuan, C. Wang, and P. Luo, “Sparse r-cnn: End-to-end object detection with learnable proposals,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.
- [9] W. Liu, D. Anguelov, D. Erhan, C. Szegedy, S. Reed, C.-Y. Fu, and A. C. Berg, “Ssd: Single shot multibox detector,” in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2016, pp. 21–37.
- [10] T.-Y. Lin, P. Goyal, R. Girshick, K. He, and P. Dollár, “Focal loss for dense object detection,” in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2017, pp. 2980–2988.
- [11] M. Tan, R. Pang, and Q. V. Le, “Efficientdet: Scalable and efficient object detection,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 10781–10790.
- [12] Z. Tian, C. Shen, H. Chen, and T. He, “Fcos: Fully convolutional one-stage object detection,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2019, pp. 9627–9636.
- [13] X. Zhou, D. Wang, and P. Krähenbühl, “Objects as points,” *arXiv preprint arXiv:1904.07850*, 2019.
- [14] X. Long, K. Deng, G. Wang, Y. Zhang, Q. Dang, Y. Gao, H. Shen, J. Ren, S. Han, E. Ding, and S. Wen, “Pp-yolo: An effective and efficient implementation of object detector,” *arXiv preprint arXiv:2007.12099*, 2020.
- [15] J. Redmon and A. Farhadi, “Yolo9000: Better, faster, stronger,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 7263–7271.

- [16] —, “Yolov3: An incremental improvement,” *arXiv preprint arXiv:1804.02767*, 2018.
- [17] A. Bochkovskiy, C.-Y. Wang, and H.-Y. M. Liao, “Yolov4: Optimal speed and accuracy of object detection,” *arXiv preprint arXiv:2004.10934*, 2020.
- [18] Z. Ge, S. Liu, F. Wang, Z. Li, and J. Sun, “Yolox: Exceeding yolo series in 2021,” *arXiv preprint arXiv:2107.08430*, 2021.
- [19] C. Li, L. Li, H. Jiang, K. Weng, Y. Geng, L. Li, Z. Ke, Q. Li, M. Cheng, W. Nie *et al.*, “Yolov6: A single-stage object detection framework for industrial applications,” *arXiv preprint arXiv:2209.02976*, 2022.
- [20] C.-Y. Wang, A. Bochkovskiy, and H.-Y. M. Liao, “Yolov7: Trainable bag-of-freebies sets new state-of-the-art for real-time object detectors,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023, pp. 7464–7475.
- [21] C. Wang, W. He, Y. Nie, J. Guo, C. Liu, K. Han, and Y. Wang, “Gold-yolo: Efficient object detector via gather-and-distribute mechanism,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.
- [22] C.-Y. Wang, I.-H. Yeh, and H.-Y. M. Liao, “Yolov9: Learning what you want to learn using programmable gradient information,” in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2024.
- [23] A. Wang, H. Chen, L. Liu, K. Chen, Z. Lin, J. Han, and G. Ding, “Yolov10: Real-time end-to-end object detection,” *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- [24] R. Khanam and M. Hussain, “Yolov11: An overview of the key architectural enhancements,” *arXiv preprint arXiv:2410.17725*, 2024.
- [25] R. Sapkota, R. H. Cheppally, A. Sharda, and M. Karkee, “Yolo26: Key architectural enhancements and performance benchmarking for real-time object detection,” *arXiv preprint arXiv:2509.25164*, 2025.
- [26] T. Cheng, L. Song, Y. Ge, W. Liu, X. Wang, and Y. Shan, “Yolo-world: Real-time open-vocabulary object detection,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.
- [27] P. Jiang, D. Ergu, F. Liu, Y. Cai, and B. Ma, “A review of yolo algorithm developments,” *Procedia Computer Science*, vol. 199, pp. 1066–1073, 2022.
- [28] J. Terven, D.-M. Cordova-Esparza, and J.-A. Romero-Gonzalez, “A comprehensive review of yolo architectures in computer vision: From yolov1 to yolov8 and yolo-nas,” *Machine Learning and Knowledge Extraction*, vol. 5, no. 4, pp. 1680–1716, 2023.
- [29] M. Hussain, “Yolo-v1 to yolo-v8, the rise of yolo and its complementary nature toward digital manufacturing and industrial defect detection,” *Machines*, vol. 11, no. 7, p. 677, 2023.
- [30] A. Vijayakumar and S. Vairavasundaram, “Yolo-based object detection: A systematic review and applications,” *Multimedia Tools and Applications*, vol. 83, pp. 83 535–83 574, 2024.
- [31] R. Sapkota, Z. Meng, M. Churuvija, X. Du, Z. Ma, and M. Karkee, “Yolov1 to yolov10: A comprehensive review of yolo variants and their application in the agricultural domain,” *arXiv preprint arXiv:2406.10139*, 2024.
- [32] M. A. F. Alif and M. Hussain, “Yolo evolution: A comprehensive benchmark and architectural review of yolov12, yolov11, and their previous versions,” *arXiv preprint arXiv:2411.00201*, 2024.
- [33] R. Sapkota, M. Flores-Calero, R. Qureshi, C. Badgajar, U. Nepal, A. Poulse, P. Zeno, U. B. P. Vaddevolu, S. Khan, M. Shoman, H. Yan, and M. Karkee, “Yolo advances to its genesis: A decadal and comprehensive review of the yolo only look once (yolo) series,” *Artificial Intelligence Review*, vol. 58, 2025.
- [34] K. He, X. Zhang, S. Ren, and J. Sun, “Deep residual learning for image recognition,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778.
- [35] S. Woo, J. Park, J.-Y. Lee, and I. S. Kweon, “Cbam: Convolutional block attention module,” in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2018, pp. 3–19.
- [36] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly *et al.*, “An image is worth 16x16 words: Transformers for image recognition at scale,” in *International Conference on Learning Representations (ICLR)*, 2021.
- [37] Z. Liu, Y. Lin, Y. Cao, H. Hu, Y. Wei, Z. Zhang, S. Lin, and B. Guo, “Swin transformer: Hierarchical vision transformer using shifted windows,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 10012–10022.
- [38] Z. Liu, H. Hu, Y. Lin, Z. Yao, Z. Xie, Y. Wei, J. Ning, Y. Cao, Z. Zhang, L. Dong, F. Wei, and B. Guo, “Swin transformer v2: Scaling up capacity and resolution,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- [39] W. Wang, E. Xie, X. Li, D.-P. Fan, K. Song, D. Liang, T. Lu, P. Luo, and L. Shao, “Pyramid vision transformer: A versatile backbone for dense prediction without convolutions,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.
- [40] Z. Liu, H. Mao, C.-Y. Wu, C. Feichtenhofer, T. Darrell, and S. Xie, “A convnet for the 2020s,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- [41] N. Carion, F. Massa, G. Synnaeve, N. Usunier, A. Kirillov, and S. Zagoruyko, “End-to-end object detection with transformers,” in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 213–229.
- [42] X. Zhu, W. Su, L. Lu, B. Li, X. Wang, and J. Dai, “Deformable detr: Deformable transformers for end-to-end object detection,” in *International Conference on Learning Representations (ICLR)*, 2021.
- [43] D. Meng, X. Chen, Z. Fan, G. Zeng, H. Li, Y. Yuan, L. Sun, and J. Wang, “Conditional detr for fast training convergence,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.
- [44] F. Li, H. Zhang, S. Liu, J. Guo, L. M. Ni, and L. Zhang, “Dn-detr: Accelerate detr training by introducing query denoising,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- [45] H. Zhang, F. Li, S. Liu, L. Zhang, H. Su, J. Zhu, L. M. Ni, and H.-Y. Shum, “Dino: Detr with improved denoising anchor boxes for end-to-end object detection,” in *International Conference on Learning Representations (ICLR)*, 2023.
- [46] Z. Zong, G. Song, and Y. Liu, “Detrs with collaborative hybrid assignments training,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.
- [47] Y. Zhao, W. Lv, S. Xu, J. Wei, G. Wang, Q. Dang, Y. Liu, and J. Chen, “Detrs beat yolos on real-time object detection,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.
- [48] I. Robinson, P. Robicheaux, M. Popov, D. Ramanan, and N. Peri, “Rf-detr: Neural architecture search for real-time detection transformers,” in *International Conference on Learning Representations (ICLR)*, 2025, terbit sebagai preprint arXiv:2511.09554 (Nov 2025); diterima ICLR 2026.
- [49] J. Huang, A. Kane, F. Zhou, Y. Wei, and H. Shi, “Le-detr: Revisiting real-time detection transformer with efficient encoder design,” *arXiv preprint arXiv:2602.21010*, 2026.
- [50] Y. Ming, X. Meng, C. Fan, and H. Yu, “Deep learning for monocular depth estimation: A review,” *Neurocomputing*, vol. 438, pp. 14–33, 2021.
- [51] J. Zhang, “Survey on monocular metric depth estimation,” *arXiv preprint arXiv:2501.11841*, 2025.
- [52] D. Eigen, C. Puhrsch, and R. Fergus, “Depth map prediction from a single image using a multi-scale deep network,” in *Advances in Neural Information Processing Systems (NeurIPS)*, 2014, pp. 2366–2374.
- [53] J. H. Lee, M.-K. Han, D. W. Ko, and I. H. Suh, “From big to small: Multi-scale local planar guidance for monocular depth estimation,” *arXiv preprint arXiv:1907.10326*, 2019.
- [54] S. F. Bhat, I. Alhashim, and P. Wonka, “Adabins: Depth estimation using adaptive bins,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 4009–4018.
- [55] R. Ranftl, A. Bochkovskiy, and V. Koltun, “Vision transformers for dense prediction,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 12 179–12 188.
- [56] W. Yuan, X. Gu, Z. Dai, S. Zhu, and P. Tan, “Neural window fully-connected crfs for monocular depth estimation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- [57] C. Godard, O. Mac Aodha, and G. J. Brostow, “Unsupervised monocular depth estimation with left-right consistency,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 270–279.
- [58] C. Godard, O. Mac Aodha, M. Firman, and G. J. Brostow, “Digging into self-supervised monocular depth estimation,” in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2019, pp. 3828–3838.
- [59] V. Guizilini, R. Ambrus, S. Pillai, A. Raventos, and A. Gaidon, “3d packing for self-supervised monocular depth estimation,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 2485–2494.

- [60] P. Ji, R. Li, B. Bhanu, and Y. Xu, "Monoindoor: Towards good practice of self-supervised monocular depth estimation for indoor environments," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 12787–12796.
- [61] R. Ranftl, K. Lasinger, D. Hafner, K. Schindler, and V. Koltun, "Towards robust monocular depth estimation: Mixing datasets for zero-shot cross-dataset transfer," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 3, pp. 1623–1637, 2022.
- [62] W. Yin, C. Zhang, H. Chen, Z. Cai, G. Yu, K. Wang, X. Chen, and C. Shen, "Metric3d: Towards zero-shot metric 3d prediction from a single image," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.
- [63] S. F. Bhat, R. Birkel, D. Wofk, P. Wonka, and M. Müller, "Zoedepth: Zero-shot transfer by combining relative and metric depth," *arXiv preprint arXiv:2302.12288*, 2023.
- [64] L. Yang, B. Kang, Z. Huang, X. Xu, J. Feng, and H. Zhao, "Depth anything: Unleashing the power of large-scale unlabeled data," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, pp. 10371–10381.
- [65] L. Yang, B. Kang, Z. Huang, Z. Zhao, X. Xu, J. Feng, and H. Zhao, "Depth anything v2," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- [66] B. Ke, A. Obukhov, S. Huang, N. Metzger, R. C. Daudt, and K. Schindler, "Repurposing diffusion-based image generators for monocular depth estimation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.
- [67] H. Lin, S. Chen, J. Liew, D. Y. Chen, Z. Li, G. Shi, J. Feng, and B. Kang, "Depth anything 3: Recovering the visual space from any views," *arXiv preprint arXiv:2511.10647*, 2025.
- [68] G. C. Ganesan, Y. Guo, L. Ren, and X. Liu, "Unidac: Universal metric depth estimation for any camera," *arXiv preprint arXiv:2603.27105*, 2026.
- [69] L. Ma, Y. Li, B. Jiang, Z. Zhong, H. Ding, and L. Zhu, "Asynmdc: Real-time monocular depth estimation via asynchronous spatial memory," *arXiv preprint arXiv:2603.10438*, 2026.
- [70] Y. Du *et al.*, "Focusable monocular depth estimation," *arXiv preprint arXiv:2605.11756*, 2026.
- [71] T. Zhou, D.-P. Fan, M.-M. Cheng, J. Shen, and L. Shao, "Rgb-d salient object detection: A survey," *Computational Visual Media*, vol. 7, no. 1, pp. 37–69, 2021.
- [72] Y. Piao, W. Ji, J. Li, M. Zhang, and H. Lu, "Depth-induced multi-scale recurrent attention network for saliency detection," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2019, pp. 7254–7263.
- [73] D.-P. Fan, Y. Zhai, A. Borji, J. Yang, and L. Shao, "Bbs-net: Rgb-d salient object detection with a bifurcated backbone strategy network," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 275–292.
- [74] K. Fu, D.-P. Fan, G.-P. Ji, and Q. Zhao, "Jl-dcf: Joint learning and densely-cooperative fusion framework for rgb-d salient object detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 3052–3062.
- [75] N. Liu, N. Zhang, and J. Han, "Learning selective self-mutual attention for rgb-d saliency detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 13756–13765.
- [76] Y. Pang, L. Zhang, X. Zhao, and H. Lu, "Hierarchical dynamic filtering network for rgb-d salient object detection," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 235–252.
- [77] J. Zhang, D.-P. Fan, Y. Dai, S. Anwar, F. S. Saleh, T. Zhang, and N. Barnes, "Uc-net: Uncertainty inspired rgb-d saliency detection via conditional variational autoencoders," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 8582–8591.
- [78] W. Ji, J. Li, M. Zhang, Y. Piao, and H. Lu, "Accurate rgb-d salient object detection via collaborative learning," in *European Conference on Computer Vision (ECCV)*, 2020.
- [79] D.-P. Fan, Z. Lin, Z. Zhang, M. Zhu, and M.-M. Cheng, "Rethinking rgb-d salient object detection: Models, data sets, and large-scale benchmarks," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 32, no. 5, pp. 2075–2089, 2021.
- [80] N. Liu, N. Zhang, K. Wan, L. Shao, and J. Han, "Visual saliency transformer," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 4722–4732.
- [81] Z. Liu, Y. Wang, Z. Tu, Y. Xiao, and B. Tang, "Tritransnet: Rgb-d salient object detection with a triplet transformer embedding network," in *Proceedings of the 29th ACM International Conference on Multimedia (ACM MM)*, 2021, pp. 4481–4490.
- [82] P. Sun, W. Zhang, H. Wang, S. Li, and X. Li, "Deep rgb-d saliency detection with depth-sensitive attention and automatic multi-modal fusion," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 1407–1417.
- [83] W. Ji, J. Li, S. Yu, M. Zhang, Y. Piao, S. Yao, Q. Bi, K. Ma, Y. Zheng, H. Lu, and L. Cheng, "Calibrated rgb-d salient object detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.
- [84] T. Zhou, H. Fu, G. Chen, Y. Zhou, D.-P. Fan, and L. Shao, "Specificity-preserving rgb-d saliency detection," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.
- [85] Z. Liu, Y. Tan, Q. He, and Y. Xiao, "Swinnet: Swin transformer drives edge-aware rgb-d and rgb-t salient object detection," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 32, no. 7, pp. 4486–4497, 2022.
- [86] R. Cong, Q. Lin, C. Zhang, C. Li, X. Cao, Q. Huang, and Y. Zhao, "Cir-net: Cross-modality interaction and refinement for rgb-d salient object detection," *IEEE Transactions on Image Processing*, vol. 31, pp. 6800–6815, 2022.
- [87] Y.-H. Wu, Y. Liu, J. Xu, J.-W. Bian, Y.-C. Gu, and M.-M. Cheng, "Mobilesal: Extremely efficient rgb-d salient object detection," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 12, pp. 10261–10269, 2022.
- [88] Z. Wu, G. Allibert, F. Meriaudeau, C. Ma, and C. Demonceaux, "Hidanet: Rgb-d salient object detection via hierarchical depth awareness," *IEEE Transactions on Image Processing*, vol. 32, pp. 2160–2173, 2023.
- [89] Y. Pang, X. Zhao, L. Zhang, and H. Lu, "Caver: Cross-modal view-mixed transformer for bi-modal salient object detection," *IEEE Transactions on Image Processing*, vol. 32, pp. 892–904, 2023.
- [90] K. Yi, H. Tang, Y. Li, J. Xu, and J. Zhang, "Dual mutual learning network with global-local awareness for rgb-d salient object detection," *arXiv preprint arXiv:2501.01648*, 2025.
- [91] C. Hazirbas, L. Ma, C. Domokos, and D. Cremers, "Fusenet: Incorporating depth into semantic segmentation via fusion-based cnn architecture," in *Proceedings of the Asian Conference on Computer Vision (ACCV)*, 2016, pp. 213–228.
- [92] S.-J. Park, K.-S. Hong, and S. Lee, "Rdfnet: Rgb-d multi-level residual feature fusion for indoor semantic segmentation," in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2017, pp. 4980–4989.
- [93] J. Jiang, L. Zheng, F. Luo, and Z. Zhang, "Rednet: Residual encoder-decoder network for indoor rgb-d semantic segmentation," *arXiv preprint arXiv:1806.01054*, 2018.
- [94] X. Hu, K. Yang, L. Fei, and K. Wang, "Acnet: Attention based network to exploit complementary features for rgb-d semantic segmentation," in *Proceedings of the IEEE International Conference on Image Processing (ICIP)*, 2019, pp. 1440–1444.
- [95] X. Chen, K.-Y. Lin, J. Wang, W. Wu, C. Qian, H. Li, and G. Zeng, "Bi-directional cross-modality feature propagation with separation-and-aggregation gate for rgb-d semantic segmentation," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 561–577.
- [96] D. Seichter, M. Köhler, B. Lewandowski, T. Wengelfeld, and H.-M. Gross, "Efficient rgb-d semantic segmentation for indoor scene analysis," in *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, 2021, pp. 13525–13531.
- [97] J. Cao, H. Leng, D. Lischinski, D. Cohen-Or, C. Tu, and Y. Li, "Shapeconv: Shape-aware convolutional layer for indoor rgb-d semantic segmentation," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021, pp. 7088–7097.
- [98] E. Xie, W. Wang, Z. Yu, A. Anandkumar, J. M. Alvarez, and P. Luo, "Segformer: Simple and efficient design for semantic segmentation with transformers," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.
- [99] Y. Wang, X. Chen, L. Cao, W. Huang, F. Sun, and Y. Wang, "Multimodal token fusion for vision transformers," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 12186–12195.
- [100] D. Seichter, S. B. Fischeidick, M. Köhler, and H.-M. Gross, "Efficient multi-task rgb-d scene analysis for indoor environments," in *International Joint Conference on Neural Networks (IJCNN)*, 2022.
- [101] R. Girdhar, M. Singh, N. Ravi, L. van der Maaten, A. Joulin, and I. Misra, "Omnivore: A single model for many visual modalities," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

- [102] J. Zhang, H. Liu, K. Yang, X. Hu, R. Liu, and R. Stiefelhagen, "Cmx: Cross-modal fusion for rgb-x semantic segmentation with transformers," *IEEE Transactions on Intelligent Transportation Systems*, vol. 24, no. 12, pp. 14 679–14 694, 2023.
- [103] B. Yin, X. Zhang, Z.-Y. Li, L. Liu, M.-M. Cheng, and Q. Hou, "Dformer: Rethinking rgbd representation learning for semantic segmentation," in *International Conference on Learning Representations (ICLR)*, 2024.
- [104] D. Jia, J. Guo, K. Han, H. Wu, C. Zhang, C. Xu, and X. Chen, "Gemini-fusion: Efficient pixel-wise multimodal fusion for vision transformer," in *International Conference on Machine Learning (ICML)*, 2024.
- [105] Y. Gong, J. Lu, Y. Gao, J. Zhao, X. Zhang, and S. Rahardja, "Diffpixelformer: Differential pixel-aware transformer for rgb-d indoor scene segmentation," *arXiv preprint arXiv:2511.13047*, 2025.
- [106] T. Ophoff, K. Van Beeck, and T. Goedemé, "Exploring rgb+depth fusion for real-time object detection," *Sensors*, vol. 19, no. 4, p. 866, 2019.
- [107] M. Takahashi, A. Moro, Y. Ji, and K. Umeda, "Expandable yolo: 3d object detection from rgb-d images," in *Proceedings of the 21st International Conference on Research and Education in Mechatronics (REM)*, 2020, pp. 1–5.
- [108] S. El Amraoui *et al.*, "Fusionvision: A comprehensive approach of 3d object reconstruction and segmentation from rgb-d cameras using yolo and fast segment anything," *arXiv preprint arXiv:2403.00175*, 2024.
- [109] Z. Xu, X. Zhan, Y. Xiu, C. Suzuki, and K. Shimada, "Onboard dynamic-object detection and tracking for autonomous robot navigation with rgb-d camera," *IEEE Robotics and Automation Letters*, vol. 9, no. 1, pp. 651–658, 2024.
- [110] W. Yang *et al.*, "Research on a fusion technique of yolov8-ure-based 2d vision and point cloud for robotic grasping in stacked scenarios," *Applied Sciences*, vol. 15, no. 12, p. 6583, 2025.
- [111] D. Feng, C. Haase-Schütz, L. Rosenbaum, H. Hertlein, C. Glaeser, F. Timm, W. Wiesbeck, and K. Dietmayer, "Deep multi-modal object detection and semantic segmentation for autonomous driving: Datasets, methods, and challenges," *IEEE Transactions on Intelligent Transportation Systems*, vol. 22, no. 3, pp. 1341–1360, 2021.
- [112] C. R. Qi, H. Su, K. Mo, and L. J. Guibas, "Pointnet: Deep learning on point sets for 3d classification and segmentation," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 652–660.
- [113] E. Arnold, O. Y. Al-Jarrah, M. Dianati, S. Fallah, D. Oxtoby, and A. Mouzakitis, "A survey on 3d object detection methods for autonomous driving applications," *IEEE Transactions on Intelligent Transportation Systems*, vol. 20, no. 10, pp. 3782–3795, 2019.
- [114] X. Chen, H. Ma, J. Wan, B. Li, and T. Xia, "Multi-view 3d object detection network for autonomous driving," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 1907–1915.
- [115] J. Ku, M. Mozifian, J. Lee, A. Harakeh, and S. L. Waslander, "Joint 3d proposal generation and object detection from view aggregation," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2018, pp. 1–8.
- [116] Y. Zhou and O. Tuzel, "Voxelnet: End-to-end learning for point cloud based 3d object detection," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018, pp. 4490–4499.
- [117] A. H. Lang, S. Vora, H. Caesar, L. Zhou, J. Yang, and O. Beijbom, "Pointpillars: Fast encoders for object detection from point clouds," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 12 697–12 705.
- [118] S. Shi, X. Wang, and H. Li, "Pointcnn: 3d object proposal generation and detection from point cloud," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 770–779.
- [119] S. Shi, C. Guo, L. Jiang, Z. Wang, J. Shi, X. Wang, and H. Li, "Pv-rnn: Point-voxel feature set abstraction for 3d object detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.
- [120] C. R. Qi, W. Liu, C. Wu, H. Su, and L. J. Guibas, "Frustum pointnets for 3d object detection from rgb-d data," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018, pp. 918–927.
- [121] Y. Wang, W.-L. Chao, D. Garg, B. Hariharan, M. Campbell, and K. Q. Weinberger, "Pseudo-lidar from visual depth estimation: Bridging the gap in 3d object detection for autonomous driving," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 8445–8453.
- [122] Y. You, Y. Wang, W.-L. Chao, D. Garg, G. Pleiss, B. Hariharan, M. Campbell, and K. Q. Weinberger, "Pseudo-lidar++: Accurate depth for 3d object detection in autonomous driving," in *International Conference on Learning Representations (ICLR)*, 2020.
- [123] S. Vora, A. H. Lang, B. Helou, and O. Beijbom, "Pointpainting: Sequential fusion for 3d object detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 4604–4612.
- [124] J. H. Yoo, Y. Kim, J. Kim, and J. W. Choi, "3d-cvf: Generating joint camera and lidar features using cross-view spatial feature fusion for 3d object detection," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 720–736.
- [125] T. Yin, X. Zhou, and P. Krähenbühl, "Center-based 3d object detection and tracking," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.
- [126] X. Bai, Z. Hu, X. Zhu, Q. Huang, Y. Chen, H. Fu, and C.-L. Tai, "Transfusion: Robust lidar-camera fusion for 3d object detection with transformers," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 1090–1099.
- [127] Z. Li, W. Wang, H. Li, E. Xie, C. Sima, T. Lu, Y. Qiao, and J. Dai, "Bevformer: Learning bird's-eye-view representation from multi-camera images via spatiotemporal transformers," in *European Conference on Computer Vision (ECCV)*, 2022.
- [128] Y. Wang, V. Guizilini, T. Zhang, Y. Wang, H. Zhao, and J. Solomon, "Detr3d: 3d object detection from multi-view images via 3d-to-2d queries," in *Conference on Robot Learning (CoRL)*, 2022.
- [129] Z. Liu, H. Tang, A. Amini, X. Yang, H. Mao, D. L. Rus, and S. Han, "Bevfusion: Multi-task multi-sensor fusion with unified bird's-eye view representation," in *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, 2023, pp. 2774–2781.
- [130] S. Hoque, M. Y. Arafat, S. Xu, A. Maiti, and Y. Wei, "A comprehensive review on 3d object detection and 6d pose estimation with deep learning," *IEEE Access*, vol. 9, pp. 143 746–143 770, 2021.
- [131] Y. Xiang, T. Schmidt, V. Narayanan, and D. Fox, "Posecnn: A convolutional neural network for 6d object pose estimation in cluttered scenes," in *Robotics: Science and Systems (RSS)*, 2018.
- [132] C. Wang, D. Xu, Y. Zhu, R. Martín-Martín, C. Lu, L. Fei-Fei, and S. Savarese, "Densefusion: 6d object pose estimation by iterative dense fusion," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019, pp. 3343–3352.
- [133] Y. He, W. Sun, H. Huang, J. Liu, H. Fan, and J. Sun, "Pvn3d: A deep point-wise 3d keypoints voting network for 6dof pose estimation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 11 632–11 641.
- [134] W. Chen, X. Jia, H. J. Chang, J. Duan, and A. Leonardis, "G2l-net: Global to local network for real-time 6d pose estimation with embedding vector features," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 4233–4242.
- [135] Y. He, H. Huang, H. Fan, Q. Chen, and J. Sun, "Ffb6d: A full flow bidirectional fusion network for 6d pose estimation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 3003–3013.
- [136] G. Wang, F. Manhardt, F. Tombari, and X. Ji, "Gdr-net: Geometry-guided direct regression network for monocular 6d object pose estimation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.
- [137] Y. Su, M. Saleh, T. Fetzner, J. Rambach, N. Navab, B. Busam, D. Stricker, and F. Tombari, "Zebrapose: Coarse to fine surface encoding for 6dof object pose estimation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- [138] J. Sun, Z. Wang, S. Zhang, X. He, H. Zhao, G. Zhang, and X. Zhou, "Onepose: One-shot object pose estimation without cad models," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- [139] B. Wen, W. Yang, J. Kautz, and S. Birchfield, "Foundationpose: Unified 6d pose estimation and tracking of novel objects," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, pp. 17 868–17 879.
- [140] I. Lenz, H. Lee, and A. Saxena, "Deep learning for detecting robotic grasps," *The International Journal of Robotics Research*, vol. 34, no. 4–5, pp. 705–724, 2015.
- [141] D. Morrison, P. Corke, and J. Leitner, "Closing the loop for robotic grasping: A real-time, generative grasp synthesis approach," in *Robotics: Science and Systems (RSS)*, 2018.

- [142] S. Kumra, S. Joshi, and F. Sahin, "Antipodal robotic grasping using generative residual convolutional neural network," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2020, pp. 9626–9633.
- [143] —, "Gr-convnet v2: A real-time multi-grasp detection network for robotic grasping," *Sensors*, vol. 22, no. 16, p. 6208, 2022.
- [144] M. Breyer, J. J. Chung, L. Ott, R. Siegwart, and J. Nieto, "Volumetric grasping network: Real-time 6 dof grasp detection in clutter," in *Conference on Robot Learning (CoRL)*, 2020.
- [145] M. Sundermeyer, A. Mousavian, R. Triebel, and D. Fox, "Contact-graspnet: Efficient 6-dof grasp generation in cluttered scenes," in *IEEE International Conference on Robotics and Automation (ICRA)*, 2021.
- [146] Q. Zhang and X. Sun, "Bilateral cross-modal fusion network for robot grasp detection," *Sensors*, vol. 23, no. 6, p. 3340, 2023.
- [147] A. Depierre, E. Dellandréa, and L. Chen, "Jacquard: A large scale dataset for robotic grasp detection," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2018, pp. 3511–3516.
- [148] H.-S. Fang, C. Wang, M. Gou, and C. Lu, "Graspnet-1billion: A large-scale benchmark for general object grasping," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 11 444–11 453.
- [149] R. Mur-Artal and J. D. Tardós, "Orb-slam2: An open-source slam system for monocular, stereo, and rgb-d cameras," *IEEE Transactions on Robotics*, vol. 33, no. 5, pp. 1255–1262, 2017.
- [150] C. Campos, R. Elvira, J. J. Gómez Rodríguez, J. M. M. Montiel, and J. D. Tardós, "Orb-slam3: An accurate open-source library for visual, visual-inertial, and multimap slam," *IEEE Transactions on Robotics*, vol. 37, no. 6, pp. 1874–1890, 2021.
- [151] Z. Teed and J. Deng, "Droid-slam: Deep visual slam for monocular, stereo, and rgb-d cameras," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.
- [152] B. Bescos, J. M. Fàcil, J. Civera, and J. Neira, "Dynaslam: Tracking, mapping, and inpainting in dynamic scenes," *IEEE Robotics and Automation Letters*, vol. 3, no. 4, pp. 4076–4083, 2018.
- [153] C. Yu, Z. Liu, X.-J. Liu, F. Xie, Y. Yang, Q. Wei, and Q. Fei, "Ds-slam: A semantic visual slam towards dynamic environments," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2018, pp. 1168–1174.
- [154] X. Hu, Y. Zhang, Z. Cao, R. Ma, Y. Wu, Z. Deng, and W. Sun, "Cfp-slam: A real-time visual slam based on coarse-to-fine probability in dynamic environments," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022, pp. 4399–4406.
- [155] J. C. V. Soares, M. Gattass, and M. A. Meggiolaro, "Visual slam in human populated environments: Exploring the trade-off between accuracy and speed of yolo and mask r-cnn," in *Proceedings of the International Conference on Advanced Robotics (ICAR)*, 2019, pp. 135–140.
- [156] S. Hwang, J. Park, N. Kim, Y. Choi, and I. S. Kweon, "Multispectral pedestrian detection: Benchmark dataset and baseline," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015, pp. 1037–1045.
- [157] C. Li, D. Song, R. Tong, and M. Tang, "Illumination-aware faster r-cnn for robust multispectral pedestrian detection," *Pattern Recognition*, vol. 85, pp. 161–171, 2019.
- [158] K. Zhou, L. Chen, and X. Cao, "Improving multispectral pedestrian detection by addressing modality imbalance problems," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 787–803.
- [159] H. Zhang, E. Fromont, S. Lefevre, and B. Avignon, "Multispectral fusion for object detection with cyclic fuse-and-refine blocks," in *Proceedings of the IEEE International Conference on Image Processing (ICIP)*, 2020, pp. 276–280.
- [160] —, "Guided attentive feature fusion for multispectral pedestrian detection," in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, 2021, pp. 72–80.
- [161] Q. Fang, D. Han, and Z. Wang, "Cross-modality fusion transformer for multispectral object detection," *arXiv preprint arXiv:2111.00273*, 2022.
- [162] A. Van Etten, "You only look twice: Rapid multi-scale object detection in satellite imagery," *arXiv preprint arXiv:1805.09512*, 2018.
- [163] X. Zhu, S. Lyu, X. Wang, and Q. Zhao, "Tph-yolov5: Improved yolov5 based on transformer prediction head for object detection on drone-captured scenarios," in *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops (ICCVW)*, 2021, pp. 2778–2788.
- [164] G. Wang, Y. Chen, P. An, H. Hong, J. Hu, and T. Huang, "Uav-yolov8: A small-object-detection model based on improved yolov8 for uav aerial photography scenarios," *Sensors*, vol. 23, no. 16, p. 7190, 2023.
- [165] Z. Hu *et al.*, "Rio-detr: Detr for real-time oriented object detection," *arXiv preprint arXiv:2603.09411*, 2026.
- [166] M. A. Al-Antari, C.-H. Hua, J. Bang, and S. Lee, "Fast deep learning computer-aided diagnosis of covid-19 based on digital chest x-ray images," *Applied Intelligence*, vol. 51, no. 5, pp. 2890–2907, 2021.
- [167] A. Baccouche, B. Garcia-Zapirain, C. Castillo Olea, and A. S. El-maghraby, "Breast lesions detection and classification via yolo-based fusion models," *Computers, Materials & Continua*, vol. 69, no. 1, pp. 1407–1425, 2021.
- [168] R. Qureshi, M. G. Ragab, S. J. Abdulkader, A. Alqushaibi, A. Muneer *et al.*, "A comprehensive systematic review of yolo for medical object detection (2018 to 2023)," *IEEE Access*, vol. 12, pp. 57 815–57 836, 2024.
- [169] F. Zhou, H. Zhao, and Z. Nie, "Safety helmet wearing detection based on improved yolov5," in *Proceedings of the IEEE International Conference on Computer Vision, Image and Deep Learning (CVIDL)*, 2021, pp. 611–614.
- [170] Y. Yang, F. Li, and B. Wang, "Efc-yolo: An efficient surface-defect-detection algorithm for steel strips," *Sensors*, vol. 23, no. 17, p. 7619, 2023.
- [171] J. Tang *et al.*, "Pcb-yolo: Enhancing pcb surface defect detection with coordinate attention and multi-scale feature fusion," *PLOS ONE*, vol. 19, no. 5, p. e0323684, 2024.
- [172] N. Silberman, D. Hoiem, P. Kohli, and R. Fergus, "Indoor segmentation and support inference from rgb-d images," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2012, pp. 746–760.
- [173] S. Song, S. P. Lichtenberg, and J. Xiao, "Sun rgb-d: A rgb-d scene understanding benchmark suite," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015, pp. 567–576.
- [174] A. Dai, A. X. Chang, M. Savva, M. Halber, T. Funkhouser, and M. Nießner, "ScanNet: Richly-annotated 3d reconstructions of indoor scenes," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2017, pp. 5828–5839.
- [175] A. Lopes, R. Souza, and H. Pedrini, "A survey on rgb-d datasets," *Computer Vision and Image Understanding*, vol. 222, p. 103489, 2022.
- [176] T.-Y. Lin, M. Maire, S. Belongie, J. Hays, P. Perona, D. Ramanan, P. Dollár, and C. L. Zitnick, "Microsoft coco: Common objects in context," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2014, pp. 740–755.
- [177] A. Geiger, P. Lenz, and R. Urtasun, "Are we ready for autonomous driving? the kitti vision benchmark suite," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012, pp. 3354–3361.
- [178] H. Caesar, V. Bankiti, A. H. Lang, S. Vora, V. E. Liong, Q. Xu, A. Krishnan, Y. Pan, G. Baldan, and O. Beijbom, "nuscenes: A multimodal dataset for autonomous driving," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020, pp. 11 621–11 631.
- [179] Y. Onishi, T. Yoshida, H. Kurita, T. Fukao, H. Arihara, and A. Iwai, "An automated fruit harvesting robot by using deep learning," *ROBOMECH Journal*, vol. 6, no. 1, p. 13, 2019.
- [180] J. Gené-Mola, R. Sanz-Cortiella, J. R. Rosell-Polo, J.-R. Morros, J. Ruiz-Hidalgo, V. Vilaplana, and E. Gregorio, "Fruit detection and 3d location using instance segmentation neural networks and structure-from-motion photogrammetry," *Computers and Electronics in Agriculture*, vol. 169, p. 105165, 2020.
- [181] H. Kang and C. Chen, "Fruit detection, segmentation and 3d visualisation of environments in apple orchards," *Computers and Electronics in Agriculture*, vol. 171, p. 105302, 2020.
- [182] S. Birrell, J. Hughes, J. Y. Cai, and F. Iida, "A field-tested robotic harvesting system for iceberg lettuce," *Journal of Field Robotics*, vol. 37, no. 2, pp. 225–245, 2020.