

ANN Accelerator Controller

User Manual

A SystemVerilog Controller for a Y-Flash Memristor Array

Team: Mohammad Abu Ammar & Lana Bakrieh
Supervisor: Nir Ben-Haim
Institution: Technion — VLSI Laboratory

July 11, 2026

Contents

1	Project Goal & Overview	2
2	Architecture Components	2
2.1	Parallel Interface (<code>parallel_interface</code>)	2
2.2	ANN Controller (<code>ann_controller</code>)	2
2.3	Input Buffer (<code>input_buffer</code>)	3
3	Parameter Configuration	3
4	Top-Level I/O Interface	4
4.1	Command Encoding	5
5	Execution & Simulation Guide	5
5.1	Prerequisites	5
5.2	List available modules and testbenches	6
5.3	Compile	6
5.4	Run a single testbench (console / batch)	6
5.5	Run with GUI + waveforms	6
5.6	Run all testbenches for a module	6
5.7	Clean generated artifacts	6
5.8	Detailed runbooks	6
5.9	Available testbenches	6

1 Project Goal & Overview

The **ANN Accelerator Controller** is a digital control unit, written in SystemVerilog, that drives an Analog Neural Network (ANN) implemented on a **Y-Flash memristor crossbar array**. It acts as the bridge between a host processor and the analog in-memory-computing core.

The controller accepts five commands from a host through a parallel interface and translates them into precisely timed *pulse trains* that the analog array requires:

- **Programming** a quantized weight into a selected memristor cell.
- **Verifying** the programmed value with a closed feedback loop and automatically re-programming or erasing on mismatch.
- **Erasing** a cell.
- **Reading** a stored weight back from the array.
- **Inference**: collecting an 8×8 input image into an input buffer and streaming it bit-serially into the array for matrix-vector multiplication.

The central design challenge — and the project’s main contribution — is the **closed-loop program/verify algorithm**. Because memristor programming is analog and imprecise, the controller reads back each weight after programming. If the cell is *under-programmed*, it re-applies program pulses (up to `MAX_PROG_RETRIES`); if it is *over-programmed*, it erases the cell and retries. A lookup table (LUT) sets the number of program-pulse repetitions per target weight value, allowing weight-dependent pulse shaping.

2 Architecture Components

The system consists of three RTL modules and three supporting packages. The top-level module is `ann_controller`.

Role	Module name	Source file
Parallel Interface	<code>parallel_interface</code>	<code>rtl/Parallel_Interface/parallel_interface.sv</code>
ANN Controller (top)	<code>ann_controller</code>	<code>rtl/Controller/controller.sv</code>
Input Buffer	<code>input_buffer</code>	<code>rtl/Input_Buffer/input_buffer.sv</code>

2.1 Parallel Interface (`parallel_interface`)

Decodes the 32-bit host word `host_data` into an 8-bit data byte and a 16-bit address, passes through the 3-bit command `host_cmd`, and asserts `valid` only when the command is active and the one-hot address tail is well formed. The host word layout is `host_data[31:24]` = data byte and `host_data[23:0]` = one-hot {PE, SA, column, row}.

2.2 ANN Controller (`ann_controller`)

The heart of the system. It implements a 9-state main FSM (`S_IDLE`, `S_RESET`, `S_PROGRAM`, `S_VERIFY`, `S_ERASE`, `S_READ`, `S_COLLECT_DATA`, `S_COMPUTE`, `S_RESULT`) plus three sub-FSMs for the PROGRAM, VERIFY, and ERASE sequences. It generates the 3-bit `pulses` mode bus and the packed 32-bit `ann_address` (data byte + one-hot address) toward the analog core, and orchestrates the input buffer during inference.

2.3 Input Buffer (input_buffer)

A 64×8 -bit memory. During inference it is loaded with an 8×8 image; during compute it outputs eight channels D0–D7, one bit per channel per cycle (bit-serial, LSB-first). During weight verification it returns the full byte at the addressed location.

3 Parameter Configuration

All defaults are defined in `controller_pkg` and the supporting packages. The top module is parameterizable:

```
module ann_controller #(
    parameter int ADDR_WIDTH          = controller_pkg::DEFAULT_ADDR_WIDTH,    //
        8
    parameter int WEIGHT_WIDTH        = controller_pkg::DEFAULT_WEIGHT_WIDTH, //
        16
    parameter bit USE_WEIGHT_PULSE_LUT = 1'b1,
    parameter string WEIGHT_PULSE_LUT_FILE =
        "target/Controller/programming_inputs/weight_pulse_lut.mem"
) ( ... );
```

Parameter	Default	Description
ADDR_WIDTH	8	Host address width (default).
WEIGHT_WIDTH	16	Weight data width (default).
USE_WEIGHT_PULSE_LUT	1	Enable LUT-driven program-pulse repeat count.
WEIGHT_PULSE_LUT_FILE	(path)	\$readmemh LUT file: weight → repeat count.
<i>Architecture primary variables (controller_pkg)</i>		
NUM_PE	4	Number of processing elements (PEs).
NUM_SA	4	Sub-arrays (SAs) per PE (must be a perfect square).
SA_ROWS	8	Rows within one SA.
SA_COLS	8	Columns within one SA.
<i>Address Map</i>		
PE_ID_WIDTH	$\$clog2(\text{NUM_PE}) = 2$	PE select; weight address MSBs (default [9:8]).
SA_ID_WIDTH	$\$clog2(\text{NUM_SA}) = 2$	SA select (default [7:6]).
ROW_ID_WIDTH	$\$clog2(\text{SA_ROWS}) = 3$	Row within SA (default weight addr [5:3]).
COL_ID_WIDTH	$\$clog2(\text{SA_COLS}) = 3$	Column within SA (default weight addr [2:0]).
PE_WIDTH	NUM_PE = 4	One-hot PE bus width on <code>ann_address</code> .
SA_WIDTH	NUM_SA = 4	One-hot SA bus width on <code>ann_address</code> .
ROW_WIDTH	SA_ROWS = 8	One-hot row bus width.
COL_WIDTH	SA_COLS = 8	One-hot column bus width.

Parameter	Default	Description
<i>Pulse generation (controller_pkg)</i>		
TREAD	2	READ burst width (clock cycles).
TPROG	5	PROGRAM burst width.
TERASE	2	ERASE burst width.
TINF	8	INFERENCE burst width (min 8 for bit-serial).
PULSE_GAP	1	Idle (HiZ) cycles between bursts.
PULSE_NUM_READ	1	Number of READ bursts per operation.
PULSE_NUM_PROG	1	Number of PROGRAM bursts per operation.
PULSE_NUM_ERASE	1	Number of ERASE bursts per operation.
PULSE_NUM_INF	1	Number of INFERENCE bursts per operation.
MAX_PROG_RETRIES	3	Re-PROG attempts before falling back to ERASE.
<i>Buffer / array sizing</i>		
BUFFER_SIZE	MNIST_PIXELS = 64	Input-buffer depth (8×8 image).
BUFFER_ADDR_WIDTH	$\lceil \log_2(\text{BUFFER_SIZE}) \rceil = 6$	Buffer address width.
BUFFER_DATA_WIDTH	8	Buffer word width.
TOTAL_WEIGHT_LOCATIONS	$\text{NUM_PE} \times \text{NUM_SA} \times \text{SA_ROWS} \times \text{SA_COLS} = 1024$	Array cells.
MAX_MATRIX_COLS	$\text{NUM_PE} \times \text{PE_COLS} = 64$	Max weight-matrix columns.
DEFAULT_NUM_WEIGHTS	640	Default 10×64 weight matrix.

4 Top-Level I/O Interface

The following table lists every port of the top-level module `ann_controller` with its exact direction, bit-width, and function inferred from the RTL.

Table 2: `ann_controller` port list

Signal	Dir	Width	Description
<i>Global</i>			
clk	In	1	System clock.
rst_n	In	1	Active-low asynchronous reset.
<i>Controller $\leftrightarrow$ Parallel Interface</i>			
valid	In	1	Asserted when a command/data beat is ready.
data	In	8	Data byte from the parallel interface (weight/pixel payload).
address	In	16	Decoded address {reserved[15:10], block[9:8], sub_block[7:6], col[5:3], row[2:0]}.
cmd	In	3	Command (CMD_HIZ/READ/PROG/ERASE/INF).

Signal	Dir	Width	Description
<i>Controller ↔ ANN Core</i>			
ann_reset	Out	1	Reset pulse toward the ANN core (asserted in S_RESET).
op_done	In	1	Core handshake: advances PROG/ERASE sub-FSMs.
ann_address	Out	32	Packed bus: [31:24] data byte, [23:0] one-hot {PE,SA,col,row}.
pulses	Out	3	Pulse-mode bus (HIZ/READ/PROG/ERASE/INF) gated by burst timing.
weight_read_data	In	4	Quantized weight read back from the memristor during VERIFY.
<i>Controller ↔ Input Buffer</i>			
buf_reg_add	Out	6	Buffer address.
buf_reg_ctrl	Out	3	Buffer control (CTRL_IDLE/DATA_LOAD/COMPUTE/RESULT_OUT/WEIGHT_READ).
buf_read_write	Out	1	1 = write to buffer, 0 = read.
buf_bit_sel	Out	3	Bit index 0–7 for bit-serial D0–D7 output (LSB-first).
buf_data_out	Out	8	Data written into the buffer (from host / parallel interface).
buf_ready	In	1	Buffer ready/valid flag.
buf_data	In	8	Full byte read from the buffer at the current address.
<i>Status</i>			
busy	Out	1	High whenever the controller is not in S_IDLE.

4.1 Command Encoding

Command	cmd[2:0]	Operation
CMD_HIZ	000	Idle / high-impedance, no pulses.
CMD_READ	001	Read a weight from the addressed cell.
CMD_PROG	010	Program a weight (LUT-shaped pulse train) then auto-verify.
CMD_ERASE	011	Erase the addressed cell.
CMD_INF	100	Collect 8×8 data and run bit-serial inference.

5 Execution & Simulation Guide

The project is driven by `scripts/run_sim.py`, which wraps ModelSim’s `vlog` (compile) and `vsim` (simulate). Run all commands from the project root.

5.1 Prerequisites

- ModelSim / QuestaSim ASE (Intel FPGA 17.0) with `vlog/vsim` on PATH.

- Python 3.8+ (plus numpy, scikit-learn for stimulus generation).

5.2 List available modules and testbenches

```
python scripts/run_sim.py list
```

5.3 Compile

```
# RTL only
python scripts/run_sim.py compile -m Controller -t rtl
# Full verification set (RTL + testbenches)
python scripts/run_sim.py compile -m Controller -t verif
```

5.4 Run a single testbench (console / batch)

```
python scripts/run_sim.py sim -m Controller -tb controller_prog_verify_lut_tb
```

5.5 Run with GUI + waveforms

Passing `-do-file` opens the ModelSim GUI and loads the wave layout. Use the `*_waves_tb` wrapper testbench with its matching `.do`:

```
python scripts/run_sim.py sim -m Controller \
  -tb controller_prog_verify_lut_tb_waves_tb \
  --do-file tb/Controller/do/waves/controller_prog_verify_lut_tb_waves.do
```

5.6 Run all testbenches for a module

```
python scripts/run_sim.py run_all -m Controller
python scripts/run_sim.py run_all -m Input_Buffer -m Parallel_Interface
```

5.7 Clean generated artifacts

```
python scripts/run_sim.py clean -a % work/ + target/ outputs
python scripts/run_sim.py clean -w % work/ only
python scripts/run_sim.py clean -t -m Controller
```

5.8 Detailed runbooks

Per-testbench compile/run commands (batch and GUI wave) are maintained under `docs/verification/`:

- `TESTBENCH_CATALOG.md` — what each testbench checks
- `REGULAR_TESTBENCH_RUNBOOK.md` — batch (`vsim -c`) runs
- `WAVE_TESTBENCH_RUNBOOK.md` — GUI + `-do-file` wave runs

5.9 Available testbenches

Module	Testbenches
Controller	controller_addr_pulse_tb, controller_prog_verify_lut_tb, controller_prog_verify_lut_10w_tb, parallel_interface_controller_integration_tb, controller_host_erase_tb, controller_inf_buffer_flow_tb, controller_host_read_reorder_tb
Input_Buffer	input_buffer_bit_serial_tb, input_buffer_reset_behavior_tb, input_buffer_full_overwrite_tb
Parallel_Interface	parallel_interface_extract_tb

Output location. Reports and logs are written under `target/<module>/` (e.g. `target/Controller/prog/prog_verify_report.txt`).