```cpp
#include <iostream>
using namespace std;

int main()
{
    int age;
    double pay;
    char section;

    cin >> age >> pay >> section;

    return 0;
}
```

```
cin >> age >> pay >> section;

[Program finished]
```

```cpp
#include <iostream>
using namespace std;

int main() {
cout << 28 / 4 - 2 << endl;
cout << 6 + 12 * 2 - 8 << endl;
cout << 4 + 8 * 2 << endl;
cout << 6 + 17 % 3 - 2 << endl;
cout << 2 + 22 * (9 - 7) << endl;
cout << (8 + 7) * 2 << endl;
cout << (16 + 7) % 2 - 1 << endl;
cout << 12 / (10 - 6) << endl;
cout << (19 - 3) * (2 + 2) / 4 << endl;

return 0;

}
```

```
5
22
20
6
46
30
0
3
16

[Program finished]
```

```
1
2  #include <iostream>
3  using namespace std;
4
5  int main() {
6      int units = 2;
7      float mass = 3.5;
8      double weight;
9
10     weight = mass * units;
11
12     cout << "Weight = " << weight;
13
14     return 0;
15 }
16
```



```
Weight = 7
[Program finished]
```

```cpp

#include <iostream>
using namespace std;

int main() {
    int a, b = 2;
    float c = 4.2;

    a = b * c;

    cout << a;

    return 0;
}

```

```
8
[Program finished]
```

```
1
2  #include <iostream>
3  using namespace std;
4
5  int main() {
6      int qty = 10, salesReps = 3;
7      double unitsEach;
8
9      unitsEach = static_cast<double>(qty) / salesReps;
10
11     cout << "Units Each = " << unitsEach;
12
13     return 0;
14 }
```

```
Units Each = 3.33333
[Program finished]
```

```cpp
#include <iostream>
#include <cstdlib>
#include <ctime>
using namespace std;

int main()
{
    int num1, num2;
    int answer;

    srand(time(0));

    num1 = rand() % 900 + 100;
    num2 = rand() % 900 + 100;

    cout << "Math Tutor" << endl;
    cout << num1 << endl;
    cout << "+ " << num2 << endl;
    cout << "-------" << endl;

    cout << "Press any key and Enter to check answer...";
    cin.get();

    answer = num1 + num2;

    cout << num1 << endl;
    cout << "+ " << num2 << endl;
    cout << "-------" << endl;
    cout << answer << endl;

    return 0;
}
```

Math Tutor

680

+ 722

Press any key and Enter to check answer...

```cpp
#include <iostream>
using namespace std;

int main()
{
    double number1, number2, sum;

    cout << "Enter a number: ";
    cin >> number1;

    cout << "Enter another number: ";
    cin >> number2;

    sum = number1 + number2;

    cout << "The sum of the two numbers is " << sum;

    return 0;
}
```

```
Enter a number: 5
Enter another number: 10
The sum of the two numbers is 15
[Program finished]
```

```cpp
#include <iostream>
using namespace std;

int main()
{
    int a = 28, b = 32, c = 37, d = 24, e = 33;
    int sum;
    float average;

    sum = a + b + c + d + e;
    average = sum / 5.0;

    cout << "Sum = " << sum << endl;
    cout << "Average = " << average << endl;

    return 0;
}
```

```
Sum = 154
Average = 30.8

[Program finished]
```

```cpp
#include <iostream>
using namespace std;

int main() {
    int num;

    cout << "Enter a number: ";
    cin >> num;

    if (num < 0) {
        cout << "Number is negative.";
    }
    else {
        cout << "Number is positive.";
    }

    return 0;
}
```

```
Enter a number: 5
Number is positive.
[Program finished]
```

```cpp
#include <iostream>
using namespace std;

int main() {
    int marks;

    cout << "Enter your marks: ";
    cin >> marks;

    if (marks >= 75) {
        cout << "Grade is A";
    }
    else if (marks >= 60) {
        cout << "Grade is B";
    }
    else if (marks >= 45) {
        cout << "Grade is C";
    }
    else {
        cout << "Grade is D";
    }

    return 0;
}
```

```
Enter your marks: 80
Grade is A
[Program finished]
```



```
7     cout << “Enter a number: “;
8     cin >> num;
9
10    if (num > 0) {
11        cout << “Number is positive“ << endl;
12
13        if (num < 10) {
14            cout << “Number has 1 digit“;
15        }
16        else if (num < 100) {
17            cout << “Number has 2 digits“;
18        }
19        else if (num < 1000) {
20            cout << “Number has 3 digits“;
21        }
22        else {
23            cout << “Number has 4 or more digits“;
24        }
25    }
26    else {
27        cout << “Number is not positive“;
28    }
29
30    return 0;
31 }
```

```
Enter a number: 567
Number is positive
Number has 3 digits
[Program finished]
```

