

Prepared By Abrar Ahmed

Modern Markup for Data Interchange

Q.1 Match the following (1,2,3,4) with (a,b,c,d)

- 1 <xsl:template match = "Greeting">
- 2 <xsl:template match = "P//EM">
- 3 <xsl:template match = "1">
- 4 <xsl:template match="Product">
 <xsl:apply-templates select="@Units"/>
 </xsl:template>

- a) Matching by ancestry
- b) Matching by attribute
- c) Matching by name
- d) Matching by root

A. a-1, b-2, c-3, d-4

B. a-1, b-3, c-2, d-4

C. a-4, b-3, c-2, d-1

D. a-2, b-4, c-1, d-3

Correct Answer: D

Reference: Book Name: Modern Markup for Data Interchange, Page no 221, Heading 7.1.7

Q.2 Match the attribute value with the description

SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A			
A1	value	B1	Value must be included	B1	B2	B3	B4
A2	#REQUIRED	B2	value is fixed	B1	B2	B3	B4
A3	#IMPLIED	B3	default	B1	B2	B3	B4
A4	#FIXED	B4	Value does not have to be included	B1	B2	B3	B4

Reference: Book name: Modern Markup for Data Interchange, Page no 70, Table 3.5

Q.3 The following are steps to create Internal DTDs. Can you arrange them in order?

1. Declare all the possible elements.
2. Declare all the possible element attributes.
3. Set the attribute data types and values.
4. Declare all the possible entities.

Prepared By Abrar Ahmed

5. Set the order in which elements must appear.	
6. Specify the permissible element children, if any.	
A. 1,2,3,4,5,6	B. 2,3,5,4,1,6
C. 1,6,5,2,3,4	D. 5,3,6,1,2,4
Correct Answer: C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 56, Heading 3.2.2	

Q.4	
<pre><xs:complexType name="Books"> <xs:simpleContent> <xs:extension base="xs:string"> <xs:attribute name="BookCode" type="xs:positiveinteger"/> </xs:extension> </xs:simpleContent> </xs:complexType></pre>	
Which of the following does the above piece of code represent?	
A. Empty Elements	B. Mixed
C. Only Elements	D. Only Text
Correct Answer: D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 104	

Q.5 Match the column.						
SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A		
A1	XSLT	B1	Language for navigating XML documents.	B1	B2	B3
A2	XPath	B2	Language for transforming XML documents.	B1	B2	B3
A3	XSL-FO	B3	Language for formatting XML documents.	B1	B2	B3
Reference: Book name: Modern Markup for Data Interchange, Page no 161						

Q.6 Match the following:	
1) '	
2) >	
3) <	
4) "	
a) <	
b) "	
c) '	

Prepared By Abrar Ahmed

d) >	
A. a-1, b-2, c-3, d-4	B. a-4, b-3, c-2, d-1
C. a-3, b-4, c-1, d-2	D. a-4, b-2, c-3, d-1
Correct Answer: C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 30, Table 1.2	

Q.7 Which of the following is the limitation of JSON?	
A. Too many data types	B. Complicated debugging
C. Support for only C languages	D. No limit on arrays and objects
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, Page no 258, Heading 8.6.1	

Q.8 Which of the following MIME type is the unofficial one for JSON?	
A. text/json	B. document/json
C. javascript/json	D. application/json
Correct Answer: A	
Reference: Book Name: Modern Markup for Data Interchange, Page no 299, Heading 10.2	

Q.9 Which of the following is a drawback of a document-oriented database?	
A. Tight coupling	B. Abstraction between logical and physical data
C. Normalization	D. Partial document navigation
Correct Answer: A	
Reference: Book Name: Modern Markup for Data Interchange, Page no 305, Heading 10.5.3	

Q.10 Which of the following function resolves the XSS and CSRF issues?	
A. jsoneval()	B. jsonparse()
C. jsonstring()	D. jsonify()
Correct Answer: D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 308, Heading 10.7.2	

Q.11 Which of the following solutions are useful to process JSON data securely? [Multiple Choice]	
A. Using JSON2 parser	B. Using the jsonstring() method
C. Using JSON-RPC	D. Using XMLHttpRequests
Correct Answer: A, D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 311, Heading 10.7.5	

Q.12 Which of the following string types is used to represent a page break especially while printing and is used as a part of test value or a Uniform Resource Locator (URL) respectively?	
A. Form feed, Carriage return	B. Reverse solidus, solidus
C. Form feed, Solidus	D. Form feed, Reverse solidus
Correct Answer: C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 273, Table 9.2	

Q.13 XML was developed over	
A. troff and TEX	B. GML
C. SGML	D. HTML

Prepared By Abrar Ahmed

Correct Answer: C

Reference: Book Name: Modern Markup for Data Interchange, Page no 88, Heading 4.1.5

Q.14 Prefixing an element in a XML document with a unique prefix prevents it from being _____

A. accessed

B. duplicated

C. deleted

D. overridden

Correct Answer: B

Reference: Book Name: Modern Markup for Data Interchange, Page no 42, Heading 2.2.2

Q.15 An _____ in XML, is a placeholder that consists of a name and a value.

A. DTD

B. ELEMENT

C. ENTITY

D. Root Element

Correct Answer: C

Reference: Book Name: Modern Markup for Data Interchange, Page no 71, Heading 3.4.4

Q.16 Which of the following part of a JSON data structure is always in double quotes?

A. Member

B. Element

C. Key

D. Literal

Correct Answer: C

Reference: Book Name: Modern Markup for Data Interchange, Page no 260, Heading 8.7

Q.17 Which of the following function converts a JavaScript value into a JSON string?

A. JSON.stringify()

B. JSON.stringify

C. JSON.tovalue()

D. JSON.Jconvert()

Correct Answer: B

Reference: Book Name: Modern Markup for Data Interchange, Page no 266

Q.18 Which of the following PHP functions decodes JSON structures?

A. Php_decode

B. Json_decode

C. Php_json_decode

D. Pj_decode

Correct Answer: B

Reference: Book Name: Modern Markup for Data Interchange, Page no 298, Table 10.1

Q.19 Match the column

SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A			
A1	fractionDigits	B1	Specifies an allowable value in an enumerated list.	B1	B2	B3	B4
A2	enumeration	B2	Restricts string types.	B1	B2	B3	B4
A3	whiteSpace	B3	Specifies the number of fractional digits in a numeric type.	B1	B2	B3	B4

Prepared By Abrar Ahmed

A4	pattern	B4	Specifies how whitespace should be treated within the type.	B1	B2	B3	B4
Reference: Book name: Modern Markup for Data Interchange, Page no 117, Table 4.2							

Q.20 Match the following (minOccur, maxOccur) with No. of times the element can occurs.							
SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A			
A1	0, 1	B1	0 or 1	B1	B2	B3	B4
A2	1, 1	B2	At least once	B1	B2	B3	B4
A3	0, *	B3	1	B1	B2	B3	B4
A4	1, *	B4	Infinite	B1	B2	B3	B4
Reference: Book name: Modern Markup for Data Interchange, Page no 107, Heading Table 4.1							

Q. 21 Which of the following is a Valid XML document?

A) `<?xml version="1.0" encoding="ISO-8859-1">`
`<!DOCTYPE Identification SYSTEM[`
`<!ELEMENT Identification (Name, Age, Gender)>`
`<!ELEMENT Name (#PCDATA)>`
`<!ELEMENT Age (#PCDATA)>`
`<!ELEMENT Gender (#PCDATA)>`
`]>`
`<Identification>`
`<Name>John Femando</Name>`
`<Age>35</Age>`
`<Gender>Male</Gender>`
`</Identification>`

B) `<?xml version="1.0" encoding="ISO-8859-1"?>`
`<!DOCTYPE Identification [`
`<!ELEMENT Identification(Name, Age, Gender)>`
`<!ELEMENT Name (#PCDATA)>`
`<!ELEMENT Age (#PCDATA)>`
`<!ELEMENT Gender (#PCDATA)>`
`]>`
`<Identification>`
`<Name>John Femando</Name>`
`<Age>35</Age>`

Prepared By Abrar Ahmed

```
<Gender>Male</Gender>
</Identffication>
```

C) <?xml version="1.0" encoding="ISO-8859-1"?>

```
<!DOCTYPE Identification [
<ELEMENT Identification (Name, Age, Gender)>
<ELEMENT Name (#PCDATA)>
<ELEMENT Age (#PCDATA)>
<ELEMENT Gender (#PCDATA)>
]>
```

```
<Identification>
  <Name>John Fernando</Name>
  <Age>35</Age>
  <Gender>Male</Gender>
</Identification>
```

D) <?xml version="10" encoding="ISO-8859-1"?>

```
<!DOCTYPE Identification [
<!ELEMENT SYSTEM Identification (Name, Age, Gender)
<ELEMENT Name (#PCDATA)>
<ELEMENT Age (#PCDATA)>
<ELEMENT Gender (#PCDATA)>
]>
```

```
<Identification>
  <Name>John Femando</Name>
  <Age>35</Age>
  <Gender>Male</Gender>
</Identification>
```

A. A

B. B

C. C

D. D

Correct Answer: C

Reference: Book Name: Modern Markup for Data Interchange, Page no 61, Heading 3.3.2

Q.22 Which of the following is a Valid XML document?

A) <?xml version="1.0" encoding="ISO-8859-1"?>

```
<IDOCYTE Flight [
<ELEMENT Flight (ID, Source, Destination, Departure, Arrival)>
<ELEMENT ID (#PCDATA)>
<ELEMENT Source (#PCDATA)>
<ELEMENT Destination (#PCDATA)>
<ELEMENT Departure (#PCDATA)>
<ELEMENT Arrival (#PCDATA)>
]>
```

```
<Flight>
  <ID>John Fernando</ID>
  <Source>Beijing</Source>
  <Destination>Amsterdam</Destination>
  <Departure>01:55 PM</Departure>
  <Arrival>09:50 PM</Arrival>
  <Duration>13hr 55mn</Duration>
</Flight>
```

Prepared By Abrar Ahmed

B) <?xml version="1" encoding="ISO-8859-1"?>
 <!DOCTYPE Flight [
 <!ELEMENT Flight (ID, Source, Destination, Departure, Arrival, Duration)>
 <!ELEMENT ID (#PCDATA)>
 <!ELEMENT Source (#PCDATA)>
 <!ELEMENT Destination (#PCDATA)>
 <!ELEMENT Departure (#PCDATA)>
 <!ELEMENT Arrival (#PCDATA)>
 <!ELEMENT Duration (#PCDATA)>
]>
 <Flight>
 <ID>John Femando</ID>
 <Source>Beijing</Source>
 <Destination>Amsterdam</Destination>
 <Departure>01:55 PM</Departure>
 <Arrival>09:50 PM</Arrival>
 <Duration>13hr 55mn</Duration>
</Flight>

C) <?xml version="1.0" encoding="ISO-8859-1"?>
 <!DOCTYPE Flight [
 <!ELEMENT Flight (ID, Source, Destination, Departure, Arrival)>
 <!ELEMENT ID (#PCDATA)>
 <!ELEMENT Source (#PCDATA)>
 <!ELEMENT Destination (#PCDATA)>
 <!ELEMENT Departure (#PCDATA)>
 <!ELEMENT Arrival (#PCDATA)>
 <!ELEMENT Duration (#PCDATA)>
 1>
 <FlightDetails>
 <ID>John Femando</ID>
 <Source>Beijing</Source>
 <Destination>Amsterdam</Destination>
 <Departure>01:55 PM</Departure>
 <Arrival>09:50 PM</Arrival>
 <Duration>13hr 55mn</Duration>
</FlightDetails>

A. A	B. B
C. C	D. -
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, No direct reference available	

Q.23 Which of the following solutions are useful to process JSON data securely? [Multiple Choice]	
A. Using JSON2 parser	B. Using the jsonString() method
C. Using JSON-RPC	D. Using XMLHttpRequests
Correct Answer: A, D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 311, Heading 10.7.5	

Q.24 Which of the following JSON feature ensures communication between two applications designed in different programming languages?	
A. Extensibility	B. Scalability

Prepared By Abrar Ahmed

C. Interoperability	D. Reusability
Correct Answer: C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 254	

Q.25 A _____ can appear between the characters in string values to make code more comprehensible	
A. White space	B. Solidus
C. Backspace	D. Reverse solidus
Correct Answer: A	
Reference: Book Name: Modern Markup for Data Interchange, Page no 275, Heading 9.1.5	

Q.26 _____ accepts data in the form of key and value pairs and each key is distinct.	
A. Vector	B. Set
C. List	D. Map
Correct Answer: D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 282, Heading 9.3.1	

Q.27 JSON _____ specifies the rules that defines the structure of a JSON document.	
A. Schema	B. Comments
C. Metadata	D. Hyper Schema
Correct Answer: A	
Reference: Book Name: Modern Markup for Data Interchange, Page no 283, Heading 9.4	

Q.28 Which of the following Gson methods are useful for implementing JSON?	
A. json_encode()	B. toJson()
C. fromJson()	D. json_decode()
Correct Answer: B, C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 298, Heading 10.1.1	

Q.29 Which of the following JSON data structures can be sorted?	
A. Dictionary	B. Map
C. Object	D. Array
Correct Answer: D	
Reference: Book Name: Modern Markup for Data Interchange, No direct reference available	

Q.30 Which of the following protocol services uses JSON?	
A. GData Web protocol	B. HTTP
C. IP	D. SOAP
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, Page no 300, Heading 10.4	

Q. 31 Identify the language from which JSON is derived.	
A. JavaScript	B. PHP
C. C	D. ECMAScript
Correct Answer: A	
Reference: Book Name: Modern Markup for Data Interchange, Page no 252, Heading 8.2	

Q.32 Which of the following syntaxes for sorting in XSLT is correct?	
A) <xsl:sort	

Prepared By Abrar Ahmed

<pre> case-order="lower-first" & "upper-first" data-type=number" "qname" & "text" order-"ascending" & "descending" select="expression"> </xsl:sort> </pre>	
B)	<pre> <xsl:sort case-order="upper-first" "lower-first" data-type="number" "qname" "text" order="ascending" "descending" select="expression"> </xsl:sort> </pre>
C)	<pre> <xsl:sort case-order="upper-first" "lower-first" data-type=number" "qname" "text" order="ascending" "descending" select="expression" /> </pre>
D)	<pre> <xsl case-order="upper-first" "lower-first" data-type=number" "qname" "text" order="ascending" "descending" select="expression"> </xsl> </pre>
A. A	B. B
C. C	D. D
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, Page no 199, Heading 6.2.11, Figure 6.38	

Q.33 A series of zero or other Unicode characters within double quotes and backslash escapes is termed as _____	
A. Array	B. String
C. Object	D. Number
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, Page no 272, Heading 9.1.2	

Q.34 Which of the following objects is used to read a JSON file and display its contents in the browser?	
A. XMLHttpRequest	B. HTTPJSONRequest
C. XMLHttpRequest	D. JSONHttpRequest
Correct Answer: C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 300, Heading 10.4	

Q.35 XML inherited DTDs from _____, which is an international standard for markup language.	
A. troff anf TEX	B. GML
C. SGML	D. HTML
Correct Answer: C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 88, Heading 4.1.5	

Prepared By Abrar Ahmed

Q.36 Which of the following are the uses of JSON? [Multiple Choice]	
A. Defining rules for sending Web data.	B. Serializing data
C. Describing process for sending web data	D. Facilitate between incompatible platforms
Correct Answer: B, D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 252	

Q.37 Match the following							
SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A			
A1	Self-describing	B1	It allows communication amongst applications coded in different languages	B1	B2	B3	B4
A2	Open	B2	It is flexible to accept new elements	B1	B2	B3	B4
A3	Interoperable	B3	It allows describing one's own field and values.	B1	B2	B3	B4
A4	Internationalization	B4	It supports Unicode norm	B1	B2	B3	B4
Reference: Book name: Modern Markup for Data Interchange, Page no 254-255							

Q.38 Which of the following aspects describes Gson? [Multiple Choice]	
A. Converts java objects into Json text	B. Offers parse() function
C. Is a java library	D. Does not serialize object
Correct Answer: A, C	
Reference: Book Name: Modern Markup for Data Interchange, Page no 297	

Q.39 Identify the errors in the following code. [Multiple Choice]	
<pre> { "peripherals"[["Mouse":[{ "brand": "Logitech", "type": "Optical", "price": 300, }}]}] </pre>	
A. P of peripherals in small case	B. Price in double quotes

Prepared By Abrar Ahmed

C. Comma after the last member of nested Mouse object	D. Colon missing after peripherals
Correct Answer: C, D	
Reference: Book Name: Modern Markup for Data Interchange, No direct reference available	

Q.40 Which of the following cannot be a part of the document prolog?	
1) <?xml version="1.0" encoding="isc-8859"?> 2) <Name>The Alchemist</Name> 3) <!ELEMENT Book {Name}> 4) <!DOCTYPE Book[?]>	
A. 1	B. 2
C. 3	D. 4
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, Direct reference not available	

Q. 41 The _____ process involves converting data into textual form and passing it to a browser or so.	
A. Creation	B. Access
C. Modification	D. Serialization
Correct Answer: D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 11	

Q.42 Match the following							
SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A			
A1	Facebook API	B1	Uses a JSON file to store metadata	B1	B2	B3	B4
A2	MongoDb	B2	Replaces SOAP to use JSON	B1	B2	B3	B4
A3	JSON-RPC	B3	Uses JSON to store values	B1	B2	B3	B4
A4	Packages	B4	Implements API to exchange data in JSON formats	B1	B2	B3	B4

Reference: Book name: Modern Markup for Data Interchange, Page no 299- 230

Prepared By Abrar Ahmed

Q.42 Match the following							
SI NO	Left Column	SI NO	Right Column	Correct Answer for Column A			
A1	Null character	B1	Changes Confidential data illegally	B1	B2	B3	B4
A2	Undefined type	B2	Calls for extra escaping for some characters	B1	B2	B3	B4
A3	Mass assignment	B3	Is an issue when used with C strings	B1	B2	B3	B4
A4	Eval	B4	Is not supported in JSON	B1	B2	B3	B4
Reference: Book name: Modern Markup for Data Interchange, Direct reference not available							

Q.43 Which of the following does not make a DTD?	
A. Attribute declaration	B. Element declaration
C. Entity declaration	D. Root Element declaration
Correct Answer: D	
Reference: Book Name: Modern Markup for Data Interchange, Page no 55	

Q.44 _____ refers to adherence to basic XML syntax rules while _____ refers to adherence to the DTDs too.	
A. Validity, Well formed	B. Well formed, Validity
C. Internal DTDs, Validity	D. Well formed, Internal DTDs
Correct Answer: B	
Reference: Book Name: Modern Markup for Data Interchange, Page no 60, Heading 3.3.1	

Prepared By Abrar Ahmed

Q.45 Identify the missing statement in the following code for displaying the city of where the second branch of the office exist.

```
Var Contact = {  
    "Name" : "Barbara George",  
    "AllowedtoVisit" : true,  
    "ContactPlaces" : [  
        {  
            "Place" : "OfficeBranch1",  
            "City" : "Florida"  
        },  
        {  
            "Place" : "OfficeBranch2",  
            "City" : "Washington"  
        }  
    ]  
};
```

A. alert("Visit
"+contact.Name+"at"+contact.ContactPlaces[1].City);

B. alert("Visit
"+contact.Name+"at"+contact.ContactPlaces[0].City);

C. alert("Visit
"+contact.Name+"at"+contact[0].ContactPlaces[1].City);

D. alert("Visit
"+contact.Name+"at"+contact[2].ContactPlaces[2].City);

Correct Answer: B

Reference: Book Name: Modern Markup for Data Interchange, Page no 263, Code Snippet 9