PT EXCAVATOR
HEAVY EQUIPMENT

CATERPILLAR 320D

OPERATING WEIGHT
20,800 KG

ENGINE POWER
138 HP

BUCKET CAPACITY
1.0 M^3

CALL FOR AVAILABILITY

+62 123 456 789

320D3
HydraulicExcavator

Technical Specifications

Engine

EngineModel	ALUW06DTI	
Net Power – ISO 9249	85 kW	114 hp
Net Power – SAE J1349	85 kW	114 hp
Gross Power – ISO 14396/SAE J1995	100 kW	134 hp
Bore	104 mm	4 in 4
Stroke	113 mm	in 351
Displacement	5.76 L	in3

- Non-certifi ed emission engine.
- Recommended for use up to 4000 m (13,120 ft) altitude with engine power derate above 3000 m (9,840 ft).
- Net power advertised is the power available at the fl ywheel when the engine is equipped with fan, air cleaner, muffl er, and alternator.
- Ratingat 1,800rpm.

Engine rpm

Operation	1,700 rpm	
Travel	1,800 rpm	

Swing Mechanism

Swing Speed	11.00 rpm	
Swing Torque	62 kN·m	45,581 lbf-ft

Weights

Operating Weight	20 800 kg	45,860 lb

- Standard undercarriage, 5.7 m (18'8") reach boom, 2.5 m (8'2") HD reach stick, 1.00 m3 (1.31 yd3) GD bucket, 600 mm (24") shoes.

Track

Standard TrackShoesWidth Number of	600 mm	24 in
Shoes (eachside) Number of Track	45 7 2	
Rollers (each side) Number of Carrier Rollers (each side)		

Drive

Maximum Gradeability	35°/70%	
Maximum Travel Speed	5.5 km/h	3.4 mph
Maximum DrawbarPull	210 kN	47,210 lbf

Hydraulic System

MainSystem–Maximum Flow – Implement	400 L/min (200 L/min × 2 pumps)	106 gal/min (53 gal/min × 2 pumps)
Maximum Pressure – Equipment – Implement	35 000 kPa	5,075 psi
Maximum Pressure – Travel	35 000 kPa	5,075 psi
Maximum Pressure – Swing	25 000 kPa	3,625 psi
Pilot System – Maximum Flow	17 L/min	4 gal/min
Pilot System – Maximum Pressure	3900 kPa	566 psi
Boom Cylinder – Bore	120 mm	5 in
Boom Cylinder – Stroke	1260 mm	50 in
Stick Cylinder – Bore	140 mm	6 in
Stick Cylinder – Stroke	1504 mm	59 in
Bucket Cylinder – Bore	120 mm	5 in
Bucket Cylinder – Stroke	1104 mm	43 in