Turk J Elec Eng & Comp Sci
() : –
doi:

QLoRA Fine-Tuning for Consumer Complaint Classification

Received: • **Accepted/Published Online:** • **Final Version:**

Abstract: Consumer financial complaint classification is a practically important text classification task for regulatory triage, customer-service routing, and institutional risk monitoring. Although locally served open-weight large language models can be used as zero-shot complaint classifiers, it remains necessary to determine whether the same models can be substantially improved through task-specific adaptation without sacrificing reproducibility or data isolation. This study evaluates that transition using a leakage-controlled parameter-efficient fine-tuning protocol. Legacy zero-shot subsets created before fine-tuning are excluded from training and preserved as a paired benchmark; the remaining corpus is split into train, validation, and internal test partitions with duplicate-aware safeguards. Qwen3-8B and Llama 3.1-8B are fine-tuned using QLoRA under a fixed two-epoch protocol and evaluated across three random seeds. On the internal test set, Qwen3-8B improves from 0.6294 to 0.8350 macro-F1, while Llama 3.1-8B improves from 0.6189 to 0.8378. On the legacy benchmark, mean macro-F1 improves by 0.1853 and 0.2289, respectively. Wilcoxon signed-rank tests over the 12 legacy subsets show consistent paired gains for accuracy, macro-F1, and weighted F1. The largest class-level improvements occur for debt collection, a difficult category frequently confused with credit reporting in zero-shot inference. These results indicate that QLoRA fine-tuning provides a robust, reproducible, and locally deployable improvement over zero-shot open-source LLM classification for consumer complaint triage.

Key words: Consumer complaint classification, large language models, QLoRA, parameter-efficient fine-tuning, zero-shot learning, data leakage, CFPB

1. Introduction

The Consumer Financial Protection Bureau (CFPB) complaint database is a large public corpus of consumer narratives describing financial disputes, product failures, debt collection issues, credit reporting problems, and banking complaints. Accurate classification of such narratives is important for regulatory monitoring, institutional triage, and the prioritisation of consumer-service workflows. The task is challenging because complaint narratives often mention multiple financial products, contain noisy informal descriptions, and must nevertheless be mapped to a single constrained product category.

Recent work has explored large language models (LLMs) for zero-shot complaint classification. In zero-shot settings, models receive the candidate categories in the prompt and must return a valid label without task-specific training. This is attractive for complaint triage because new product taxonomies or institutional routing schemes may be introduced before large labelled datasets are available. However, zero-shot classification also raises practical issues: models can confuse overlapping financial products, output labels outside the allowed taxonomy, and show sensitivity to prompt and deployment details. Once a local zero-shot baseline is established for a given open-weight model, the next methodological question is how much performance can be gained through parameter-efficient fine-tuning under a fair and leakage-controlled protocol.

This paper addresses that question. The central novelty is not a new model architecture or a new fine-tuning algorithm. Instead, the contribution is a reproducible applied evaluation and leakage-safe benchmark

© Authors retain the copyright of their works. Upon acceptance, authors grant the journal a non-exclusive right of first publication and
permission to distribute the article in all forms and media under the Creative Commons Attribution 4.0 International (CC BY 4.0) licence.

extension of a zero-shot experimental setting. We introduce a duplicate-aware train/validation/test split, exclude all legacy zero-shot subsets from model selection and training, and evaluate paired zero-shot versus QLoRA fine-tuned models in the same Hugging Face pipeline. Unlike single-model or single-seed complaint-classification studies, the present work evaluates the zero-shot-to-fine-tuned transition under paired, multi-seed, multi-model, leakage-controlled conditions. Two different 8B-class open-source model families, Qwen3-8B and Llama 3.1-8B, are evaluated across three random seeds. The final evaluation uses both a held-out internal test set and preserved legacy zero-shot subsets.

The contributions are as follows:

1. We provide a leakage-controlled transition from zero-shot open-source LLM inference to QLoRA fine-tuning for CFPB consumer complaint classification.
2. We preserve pre-existing zero-shot subsets as a legacy benchmark and explicitly exclude them from fine-tuning and model selection.
3. We compare base zero-shot and fine-tuned models within the same Hugging Face quantised inference pipeline, isolating the effect of fine-tuning from infrastructure differences.
4. We evaluate two 8B-class model families, Qwen3-8B and Llama 3.1-8B, each across seeds 42, 43, and 44.
5. We report internal test performance, legacy benchmark performance, paired Wilcoxon tests, confidence intervals, latency, off-label behaviour, and class-level error patterns.

2. Related work

Classical consumer complaint classification has relied on sparse lexical features, support vector machines, logistic regression, and later transformer encoders. BERT-style models enabled strong supervised text classification by adapting contextual representations to task-specific labels [1]; BERT, DistilBERT, and RoBERTa remain important supervised baselines for complaint categorisation [1–4]. Complaint analytics has also been studied across food-industry categorisation, telecom complaint prediction, multicriteria complaint prioritisation, CFPB topic modelling, and financial-complaint interpretability, sentiment, cause, emotion, and severity analysis [5–9]. These studies show that supervised learning can be effective for complaint taxonomies, but they do not directly address how modern open-weight generative models should be adapted and evaluated for the same task.

Recent work has made LLMs relevant to both complaint generation and complaint processing. Large-scale studies report that consumers increasingly use LLMs to draft clearer financial complaints [10, 11], suggesting that complaint corpora are themselves being reshaped by generative AI. In parallel, LLM-based complaint classification frameworks use generative models for information extraction, customer-service benchmarking, and fine-tuned complaint classification [12–14]. Closest to this study, Roumeliotis et al. evaluated 14 standard and reasoning LLMs for zero-shot CFPB complaint classification into five financial categories [15]. That work demonstrates the promise of zero-shot inference, but it focuses on a balanced 1000-record setting and does not address task-specific adaptation, multi-seed stability, or paired evaluation on both balanced and naturally imbalanced benchmarks.

PEFT provides a middle path between zero-shot inference and full fine-tuning. LoRA learns low-rank adapter matrices while freezing pretrained weights [16], and QLoRA enables quantised LLM adaptation through 4-bit NormalFloat quantisation, double quantisation, and LoRA adapters [17]. Other PEFT methods such as prefix tuning and $(IA)^3$ are also viable [18, 19], but QLoRA was selected here because it is well supported for 4-bit adaptation of 8B-class instruction models on 16 GB GPUs. The remaining methodological gap is how to connect zero-shot open-source LLM inference with supervised adaptation under a fair protocol: whether locally deployable models can be moved into PEFT without leakage, whether gains are stable across seeds and model

families, whether preserved zero-shot subsets can remain valid final benchmarks, and how the adapted models compare with lighter classical and encoder baselines. This paper addresses that applied evaluation gap rather than proposing a new LoRA or QLoRA algorithm.

3. Materials and methods

3.1. Dataset and labels

The dataset is derived from the CFPB consumer complaint database [20]. The classification task uses five product labels: `retail_banking`, `credit_reporting`, `credit_card`, `mortgages_and_loans`, and `debt_collection`. The raw complaint file contains 162,415 rows; after dropping 10 rows with missing required fields, 162,405 usable records remain. Twelve legacy zero-shot subsets, constructed in an earlier zero-shot benchmarking phase of the project before any fine-tuning experiments were planned, are stored separately and are never used for training or validation. They are retained only as paired final benchmarks for the two models fine-tuned in this paper. Each legacy subset contains 1,000 CFPB records; balanced subsets contain 200 records per class, while imbalanced subsets reflect natural prevalence with class sizes between 100 and 511. The suffix in each subset name (250 or 500) denotes the maximum narrative length in characters applied during the original zero-shot evaluation.

The natural corpus is strongly imbalanced. In the leakage-controlled train/validation/internal-test pool, `credit_reporting` accounts for 85,537 of 154,282 examples (55.44%), whereas `retail_banking` accounts for 12,932 examples (8.38%). The remaining classes are `credit_card` with 14,943 examples (9.69%), `mortgages_and_loans` with 18,367 examples (11.90%), and `debt_collection` with 22,503 examples (14.59%).

The use of both balanced and imbalanced legacy subsets is deliberate. Balanced subsets prevent the majority class from dominating aggregate scores and make class-specific weaknesses easier to detect. Imbalanced subsets preserve a more realistic prevalence pattern and therefore test whether improvements remain useful under deployment-like class priors. Reporting both views is important because a model can appear strong on an imbalanced set by favouring `credit_reporting`, while still performing poorly on minority or semantically overlapping categories such as `debt_collection`.

Complaint narratives are mostly short to medium length but have a long tail. The median narrative length is 365 characters and the 90th percentile is 1,261 characters. A 500-character training narrative limit fully covers 63.01% of examples, while 98.90% of examples are below 512 whitespace tokens. The character limit was selected to keep QLoRA training feasible on 16 GB V100 GPUs while retaining the central complaint signal for the majority of records.

3.2. Leakage-controlled split

To prevent evaluation leakage, the legacy subsets are first removed from the train/validation/internal-test pool. Narrative normalisation applies NFKC Unicode decomposition, whitespace stripping, and lowercasing; a SHA-256 hash of the normalised text is used as a deduplication key. Matching the 12,000 legacy rows (5,909 unique label–narrative pairs) back to the 162,405-row corpus excludes 8,123 rows from the fine-tuning pool through four mechanisms: (1) 4,990 exact normalised-text matches, (2) 3,096 matches where the first 250 normalised characters of a main-corpus narrative equal a legacy narrative truncated at 250 characters, (3) 23 rows whose normalised narrative belongs to the same duplicate group as a matched row but was not itself matched, and (4) 14 cross-label 250-character prefix matches where the main-corpus narrative begins with the same text as a legacy narrative from a different product category. The 250-character threshold is used because it is the

minimum truncation length among the legacy subsets, making it a conservative prefix-matching rule that also protects the 500-character legacy variants. These four mechanisms ensure that training data cannot leak any textual prefix of a legacy evaluation record, regardless of label or narrative length.

After legacy exclusion, the remaining pool contains 154,282 rows and 119,583 unique normalised narratives. The split is performed with a fixed seed of 42 and an 80/10/10 ratio, resulting in 123,427 training records, 15,427 validation records, and 15,428 internal test records. The split assigns all rows sharing the same normalised narrative to the same partition, preventing any information leakage between train, validation, and test sets even when narratives appear under different product labels. Duplicate-aware overlap checks confirm zero shared normalised narratives across all three partitions. Exact legacy hashes are also absent from the remaining pool. Legacy examples are therefore retained only for final paired benchmark evaluation.

3.3. Models

Two 8B-class open-source model families are used: Qwen3-8B, representing the Qwen3 model family [21]; and Llama 3.1-8B Instruct, representing the Llama 3 family of open-weight models [22]. Both models are evaluated as base zero-shot classifiers and as QLoRA fine-tuned classifiers. The base and fine-tuned evaluations use the same prompt format, label set, narrative truncation length, quantisation setup, and decoding strategy.

3.4. Classical and encoder supervised baselines

To provide non-LLM reference points, two families of supervised baselines are trained under the same leakage-controlled split and the same 500-character narrative truncation.

TF-IDF + Logistic Regression. The TF-IDF representation uses unigram and bigram features, Unicode accent stripping, sublinear term frequency, minimum document frequency of 2, and a maximum of 200,000 features. Logistic Regression is trained with balanced class weights, $C = 2.0$, and a maximum of 2000 iterations. Two budgets are evaluated: a 10,000-example natural training sample matching the QLoRA fixed-budget setting, and the full 123,427-example training split.

Fine-tuned transformer encoders. Three encoder-only models are fine-tuned on the same 10,000-example natural training budget used for QLoRA: BERT-base-uncased [1], DistilBERT-base-uncased [2], and RoBERTa-base [3]. Each model is fine-tuned on TRUBA for 2 epochs with a learning rate of 2×10^{-5}, effective batch size 16, linear warm-up over 6% of steps, and maximum sequence length of 512 tokens. These settings are selected as conservative, commonly used full fine-tuning settings for pretrained encoder models: unlike QLoRA, encoder fine-tuning updates the pretrained encoder weights directly, so a smaller learning rate is used to reduce the risk of destabilising the learned representations; the two-epoch budget and effective batch size 16 mirror the fixed-budget design used for QLoRA; and 512 tokens is the standard maximum input length supported by BERT-style encoders. The 500-character narrative truncation is applied before tokenisation to match the QLoRA setup. All encoder baselines use seed 42 and are evaluated on the internal test set and all 12 legacy subsets under the same metrics as the QLoRA experiments. These baselines fill the gap between simple lexical classifiers and decoder-based LLMs and provide a supervised encoder reference under the same fixed training budget.

3.5. Prompt and training format

The same chat-style classification prompt is used for zero-shot inference, QLoRA training, validation inference, internal testing, and legacy evaluation. The prompt follows the model-agnostic five-label JSON-output template

used by Roumeliotis et al. for zero-shot CFPB complaint classification [15]. Their prompt-engineering discussion motivates this design by noting that structured JSON output is more token-efficient than XML-style formatting, easier to parse consistently across different LLMs, and helpful for constraining predictions to a predefined label set. This is directly relevant to the present study because off-label outputs are operational failures in complaint-routing systems.

The operational prompt template used in this study is:

> **System:** You are an AI assistant specializing in consumer complaint classification. Classify each complaint into exactly one of these categories: retail_banking, credit_reporting, credit_card, mortgages_and_loans, and debt_collection. Return only valid JSON in this format: {"product": "chosen_category_name"}. Do not provide explanations.
>
> **User:** Complaint:
> `[NARRATIVE]`

Thus, the system message specifies the five allowed categories and enforces a single JSON field, while the user message contains the prefix `Complaint:` followed by the truncated complaint narrative.

For QLoRA training, each example is converted into a prompt–completion pair. The prompt contains the system and user messages, while the completion contains only the target JSON object with the correct product label, followed by the tokenizer end-of-sequence token. Training uses completion-only loss, so the optimisation target is the label-bearing assistant completion rather than the prompt text. No auxiliary format penalty or special JSON-specific loss is used. During inference, generated text is parsed with a constrained regular expression over the `product` field; outputs outside the five-label taxonomy are counted as off-label predictions. No retry prompting, synonym normalisation, or external constrained-decoding API is used, so the off-label analysis reflects strict raw model compliance under the fixed prompt.

3.6. Fine-tuning protocol

Qwen3-8B is used as the primary model for validation-based protocol selection. The goal of this stage is not exhaustive hyperparameter optimisation, but a limited fixed-budget protocol selection that can be applied unchanged to a second model family. Table 1 summarises the Qwen3-8B validation experiments used to choose the final protocol. The best validation macro-F1 is obtained with natural sampling, learning rate 2×10^{-4}, LoRA rank 16, and two epochs. Balanced sampling improves some minority-class behaviour in the one-epoch trials but does not improve overall validation macro-F1 after the second-stage comparison.

Table 1. Validation-stage protocol selection on Qwen3-8B. The selected final protocol is natural sampling, 2×10^{-4} learning rate, LoRA rank 16, and two epochs.

Experiment	Sampling	LR	Rank	Epochs	Macro-F1	Debt F1
Qwen3-8B pilot	natural	2×10^{-4}	16	1	0.8098	0.6429
Qwen3-8B balanced E1	balanced	2×10^{-4}	16	1	0.8040	0.6667
Qwen3-8B balanced E2	balanced	1×10^{-4}	16	1	0.7948	0.6552
Qwen3-8B balanced E3	balanced	2×10^{-4}	8	1	0.7951	0.6574
Qwen3-8B natural 2-epoch	natural	2×10^{-4}	16	2	0.8235	0.7033
Qwen3-8B balanced 2-epoch	balanced	2×10^{-4}	16	2	0.8065	0.6456

The final protocol is fixed as follows: natural training sampling; 10,000 training examples; 2,000 validation examples; two epochs; learning rate 2×10^{-4}; LoRA rank/alpha 16/32; maximum narrative length of 500

characters; maximum input length of 512 tokens; seeds 42, 43, and 44. The 10,000-example training budget is a deliberate fixed-compute design choice. The full training split contains 123,427 records, but training all models on the full split would substantially increase the computational burden of the three-seed, two-model protocol on 16 GB V100 GPUs. By using the same 10,000-example natural sample, 2,000-example validation sample, and two-epoch budget for each seed and model, the study prioritises a reproducible paired comparison over maximum possible leaderboard performance. Consequently, the reported QLoRA scores should be interpreted as fixed-budget adaptation results rather than upper-bound performance estimates. Larger training budgets may improve absolute scores and are therefore treated as future work rather than as part of the present controlled evaluation.

The same frozen protocol is then applied to Llama 3.1-8B without additional hyperparameter search. This design treats Llama 3.1-8B as a confirmatory model rather than a separately optimised model: the objective is to test whether the selected protocol transfers across model families, not to maximise the score of each model through model-specific tuning.

3.7. Experimental setup

All experiments were conducted on the TRUBA ARF high-performance computing infrastructure. Training and inference jobs were submitted with SLURM on the `akya-cuda` partition using one NVIDIA Tesla V100-SXM2 GPU with 16 GB memory and 10 CPU cores per job. The software environment used Python 3.10.20, PyTorch 2.7.1 with CUDA 11.8 wheels [23], Transformers [24], PEFT [25], TRL, bitsandbytes 0.46.1, pandas, and scikit-learn. Models were stored on shared scratch storage and loaded from local Hugging Face checkpoints in offline mode during SLURM jobs. QLoRA training used 4-bit NF4 quantisation with double quantisation and FP16 compute; QLoRA jobs used batch size 1 with gradient accumulation 16. Encoder fine-tuning used batch size 4 with gradient accumulation 4, giving the same effective batch size of 16. Final LLM inference used greedy decoding, maximum 32 generated tokens, batch size 1, and constrained JSON-style prompting with a fixed five-label taxonomy.

3.8. Evaluation and statistical analysis

The primary metrics are accuracy, macro-F1, and weighted F1. Macro-F1 is emphasised because the natural CFPB distribution is class-imbalanced. Class-level F1 is also reported, with particular attention to `debt_collection`. Internal test confidence intervals are estimated using 300 bootstrap resamples over archived prediction files. Legacy benchmark gains are evaluated with one-sided Wilcoxon signed-rank tests over the 12 paired legacy subsets, comparing base zero-shot scores with the mean fine-tuned score across the three seeds. A non-parametric paired test is used because the legacy benchmark contains only 12 subset-level observations and normality should not be assumed. The alternative hypothesis is directional because the experimental question is whether QLoRA fine-tuning improves over base zero-shot inference under the same model family and evaluation pipeline. Inference latency is measured as wall-clock generation time per example during the prediction loop, excluding model loading time, and is reported as mean seconds per example; it should therefore be interpreted as serial batch-size-1 latency rather than optimised batched throughput.

4. Results

4.1. Internal test performance

Table 2 shows the internal test results on the leakage-controlled held-out split. Both model families show large gains from QLoRA fine-tuning. Qwen3-8B improves from 0.6294 to 0.8350 macro-F1, a gain of 0.2056,

while Llama 3.1-8B improves from 0.6189 to 0.8378 macro-F1, a gain of 0.2189. Weighted F1 also increases substantially, from 0.7202 to 0.8686 for Qwen3-8B and from 0.7094 to 0.8705 for Llama 3.1-8B. The fact that macro-F1 and weighted F1 both improve is important: the models do not merely become better at the majority `credit_reporting` class, but also improve the balance of performance across the five-class taxonomy.

The class-level pattern in Table 2 is particularly relevant for the central complaint-triage problem. After fine-tuning, `debt_collection` F1 reaches 0.7546 for Qwen3-8B and 0.7613 for Llama 3.1-8B. This category is operationally important because debt collection narratives frequently mention disputed accounts, credit bureaus, and credit reports, making them easy to confuse with `credit_reporting`. The internal test results therefore support the main claim of the paper: QLoRA fine-tuning teaches the open-source LLMs the dataset-specific decision boundary that zero-shot prompting alone does not capture reliably.

Table 2. Internal test summary. Fine-tuned scores are mean ± sample standard deviation over seeds 42, 43, and 44.

Model	Base macro-F1	FT macro-F1	Gain	Base wF1	FT wF1	Gain	FT debt F1
Qwen3-8B	0.6294	0.8350±0.0017	0.2056	0.7202	0.8686±0.0011	0.1483	0.7546±0.0046
Llama 3.1-8B	0.6189	0.8378±0.0026	0.2189	0.7094	0.8705±0.0011	0.1611	0.7613±0.0072

Bootstrap confidence intervals confirm that the internal-test gains are well separated from zero for both models (Table 3). Each cell in Table 3 reports the point estimate followed by its 95% bootstrap confidence interval in brackets. For Qwen3-8B, the macro-F1 gain is 0.2060 with a 95% confidence interval of [0.1965, 0.2143]. For Llama 3.1-8B, the macro-F1 gain is 0.2191 with a 95% confidence interval of [0.2099, 0.2266]. Accuracy and weighted-F1 gains are similarly positive for both models. These intervals are narrow because the internal test set contains 15,428 examples, and none of the gain intervals approaches zero. Thus, the observed improvement is not a small fluctuation caused by a favourable sample; it is a stable effect at the prediction level.

Table 3. Bootstrap 95% confidence intervals on the internal test. Each cell reports point estimate [lower, upper]. Fine-tuned scores are seed means, gain is fine-tuned minus base, and confidence intervals are estimated from 300 bootstrap resamples over archived prediction files.

Model	Metric	Base	Fine-tuned	Gain
Qwen3-8B	accuracy	0.7351 [0.7287, 0.7411]	0.8697 [0.8648, 0.8745]	0.1346 [0.1285, 0.1402]
Qwen3-8B	macro-F1	0.6289 [0.6201, 0.6385]	0.8350 [0.8288, 0.8421]	0.2060 [0.1965, 0.2143]
Qwen3-8B	weighted F1	0.7201 [0.7119, 0.7280]	0.8685 [0.8641, 0.8735]	0.1484 [0.1409, 0.1555]
Llama 3.1-8B	accuracy	0.7319 [0.7254, 0.7391]	0.8716 [0.8667, 0.8763]	0.1397 [0.1336, 0.1457]
Llama 3.1-8B	macro-F1	0.6187 [0.6094, 0.6282]	0.8378 [0.8313, 0.8440]	0.2191 [0.2099, 0.2266]
Llama 3.1-8B	weighted F1	0.7094 [0.7014, 0.7169]	0.8704 [0.8656, 0.8744]	0.1610 [0.1534, 0.1684]

4.2. Seed stability

Seed stability is evaluated by repeating the final QLoRA protocol three times for each model family, using seeds 42, 43, and 44. The train/validation/internal-test split, 10,000-example training budget, validation set, prompt template, learning rate, LoRA configuration, number of epochs, and final evaluation sets are kept fixed. The random seed affects the stochastic parts of fine-tuning, including training-order shuffling, adapter initialisation, dropout, and low-level GPU randomness where applicable. Each seed-specific adapter is then evaluated on the same internal test set, and the mean and standard deviation of each metric are computed across the three independently fine-tuned adapters.

Across these per-seed internal test runs, macro-F1 sample standard deviation is 0.0017 for Qwen3-8B and 0.0026 for Llama 3.1-8B, indicating that the fine-tuning protocol is highly reproducible and not dependent on a single favourable random seed. Weighted F1 and accuracy show similarly tight dispersion, remaining close to approximately 0.001 across both model families. The largest per-seed spread is observed for debt-collection F1 (0.0046 for Qwen3-8B; 0.0072 for Llama 3.1-8B), which reflects the inherent difficulty of that class boundary rather than training instability.

4.3. Legacy benchmark performance

Table 4 summarises performance over the 12 preserved legacy subsets. These subsets were created before the fine-tuning experiments and were excluded from fine-tuning, validation, and protocol selection. They therefore act as an external continuity benchmark connecting the zero-shot setting to the fine-tuned setting without contaminating the training data. The average macro-F1 gain is 0.1853 for Qwen3-8B and 0.2289 for Llama 3.1-8B. Weighted F1 also increases by 0.1676 and 0.2070, respectively.

The legacy benchmark is important because it tests whether the internal-test gains survive a different evaluation construction. Unlike the internal test, the legacy benchmark contains both balanced and imbalanced subsets. The balanced subsets expose class-level weaknesses that can be hidden by majority-class prevalence, while the imbalanced subsets test a more natural complaint distribution. The gains in Table 4 show that fine-tuning improves performance across this mixed benchmark rather than overfitting to a single natural split.

Table 4. Legacy benchmark summary across 12 preserved zero-shot subsets. Fine-tuned scores are averaged over three seeds and all legacy subsets.

Model	Base macro-F1	FT macro-F1	Gain	Base wF1	FT wF1	Gain
Qwen3-8B	0.6150	0.8003	0.1853	0.6486	0.8163	0.1676
Llama 3.1-8B	0.5763	0.8053	0.2289	0.6134	0.8204	0.2070

The paired Wilcoxon tests in Table 5 show that the fine-tuned models consistently outperform their base zero-shot counterparts over the 12 legacy subsets. For each model and metric, the one-sided p value is 0.000244. Since there are 12 paired subsets, this result indicates that the improvement is directionally consistent across the preserved benchmark rather than being driven by one or two favourable subsets. The rank-biserial effect size is 1.000 for every model–metric pair because all 12 paired differences are positive. The median gains are close to the mean gains for all three metrics, which further suggests that the improvement is not dominated by an outlier subset. For example, Qwen3-8B has a mean macro-F1 gain of 0.1853 and a median macro-F1 gain of 0.1842, while Llama 3.1-8B has a mean macro-F1 gain of 0.2289 and a median macro-F1 gain of 0.2217.

Table 5. One-sided Wilcoxon signed-rank tests over 12 legacy subsets. The alternative hypothesis is that fine-tuned performance is greater than base zero-shot performance. Effect size is the matched-pairs rank-biserial correlation.

Model	Metric	Base mean	FT mean	Mean gain	Median gain	Effect	p
Qwen3-8B	accuracy	0.6593	0.8160	0.1566	0.1533	1.000	0.0002441
Qwen3-8B	macro-F1	0.6150	0.8003	0.1853	0.1842	1.000	0.0002441
Qwen3-8B	weighted F1	0.6486	0.8163	0.1676	0.1670	1.000	0.0002441
Llama 3.1-8B	accuracy	0.6394	0.8201	0.1807	0.1835	1.000	0.0002441
Llama 3.1-8B	macro-F1	0.5763	0.8053	0.2289	0.2217	1.000	0.0002441
Llama 3.1-8B	weighted F1	0.6134	0.8204	0.2070	0.2089	1.000	0.0002441

4.4. Supervised baseline comparison

Table 6 reports the TF-IDF + Logistic Regression and fine-tuned encoder baselines. With the same 10,000-example training budget used for QLoRA, TF-IDF + Logistic Regression reaches 0.8021 internal macro-F1 and 0.7965 mean legacy macro-F1. Under the same 10,000-example budget, BERT-base and RoBERTa-base reach almost identical internal macro-F1 scores of 0.8036, while DistilBERT reaches 0.7950. When TF-IDF + Logistic Regression is trained on the full 123,427-example training split, it reaches 0.8345 internal macro-F1 and 0.8279 legacy macro-F1, matching or exceeding the fine-tuned LLMs on aggregate supervised classification scores. These results show that classical and encoder baselines remain strong for a stable five-label taxonomy, while the QLoRA-tuned decoder models provide the paired zero-shot-to-fine-tuned comparison and prompt-controllable operation studied in this paper.

Table 6. Supervised baselines under the leakage-controlled split. TF-IDF variants use 500-character truncation; encoder models use a 10,000-example budget, 2 epochs, effective batch size 16, seed 42, 512-token maximum sequence length, and 500-character truncation. Legacy scores are averages over the 12 preserved subsets.

Baseline	Train examples	Internal macro-F1	Internal wF1	Legacy macro-F1	Debt F1
TF-IDF+LR 10k	10000	0.8021	0.8404	0.7965	–
TF-IDF+LR full	123427	0.8345	0.8655	0.8279	–
BERT-base	10000	0.8036	0.8479	0.7638	0.7233
RoBERTa-base	10000	0.8036	0.8470	0.7600	0.7243
DistilBERT	10000	0.7950	0.8403	0.7497	0.7138

The comparison clarifies the scope of the paper. The claim is not that QLoRA-tuned LLMs universally dominate supervised classifiers for a fixed taxonomy. Rather, locally deployable open-source LLMs can be moved from weaker zero-shot performance to a competitive supervised-classification regime using a fixed 10,000-example PEFT budget, while preserving the same promptable model family for zero-shot and fine-tuned operation. Encoder models produce deterministic categorical outputs without JSON parsing and are computationally efficient; decoder LLMs require more compute but support zero-shot inference, prompt constraints, and potential label redefinition without retraining. The full-data TF-IDF result also indicates that simple lexical models remain attractive when the taxonomy is fixed and all labelled data can be used. In this sense, the classical baselines are not treated as weak straw-man competitors; they define a practical efficiency reference. If the deployment objective is only to classify a stable five-label taxonomy with abundant labelled data, TF-IDF or encoder models may be preferable. The value of the LLM/QLoRA pipeline is instead in the paired zero-shot-to-adapted workflow, local open-weight deployment, and reuse of the same instruction-following model when taxonomies, prompts, or downstream routing requirements change.

4.5. Error analysis

Figure 1 reports row-normalised internal-test confusion matrices for both model families, comparing the base zero-shot models with the fine-tuned means across three seeds. The diagonal cells become darker after fine-tuning, indicating improved within-class recall across the five-category taxonomy. The dominant zero-shot error is the confusion of `debt_collection` with `credit_reporting`: Qwen3-8B makes this error 1,235 times in zero-shot mode and 424.7 times after fine-tuning on average, a reduction of approximately 66%; Llama 3.1-8B makes the same error 1,401 times in zero-shot mode and 435.7 times after fine-tuning, a reduction of approximately 69%. This explains the large class-level F1 gains for `debt_collection` reported in Table 2.




Figure 1. Row-normalised internal-test confusion matrices for base zero-shot and QLoRA fine-tuned models. Fine-tuned matrices are averaged over seeds 42, 43, and 44; cell annotations show row percentage and count.

The largest visual change occurs in the `debt_collection` row: Qwen3-8B increases the correct debt-collection proportion from 32.5% in zero-shot mode to 73.4% after QLoRA fine-tuning, while Llama 3.1-8B increases it from 20.7% to 73.1%. Fine-tuning also reduces several other high-frequency confusions. For Qwen3-8B, `retail_banking` → `credit_card` decreases from 561.0 to 90.3. For Llama 3.1-8B, `mortgages_and_loans` → `credit_reporting` decreases from 339.0 to 207.7, `credit_reporting` → `credit_card` decreases from 312.0 to 126.3, and `retail_banking` → `credit_card` decreases from 333.0 to 83.0. These reductions suggest that the adapters are not only memorising one problematic class but are reshaping several neighbouring decision boundaries in the financial taxonomy.

One residual issue remains visible in both models: after fine-tuning, credit reporting to debt collection becomes one of the largest remaining confusions. This is an expected trade-off when the model becomes less conservative about assigning debt collection labels; it improves recall for `debt_collection` but still leaves a boundary that should be studied in future class-specific prompting or cost-sensitive training. The figure also shows why the problem is difficult: the strongest remaining off-diagonal cells are still between `debt_collection`, `credit_reporting`, and `mortgages_and_loans`, categories that often co-occur in consumer narratives about

disputed debts, credit reports, and loan servicing. The full top-confusion counts are retained with the archived analysis outputs for reproducibility.

4.6. Latency

Fine-tuning increases inference latency because adapter-based inference is slower than base-only generation in this setup. On the internal test set, Qwen3-8B latency increases from 0.603 to 0.912 seconds per complaint, a delta of 0.309 seconds. Llama 3.1-8B latency increases from 0.487 to 0.808 seconds, a delta of 0.321 seconds.

This latency result is important for deployment interpretation. The additional cost is measurable, but it is modest relative to the accuracy and macro-F1 gains in Tables 2 and 4. In an offline regulatory analytics workflow or a semi-real-time complaint-routing system, an additional one third of a second per complaint is likely acceptable if it reduces high-impact class confusions such as `debt_collection` → `credit_reporting`. For strict real-time systems, however, these latency deltas indicate that throughput planning and batching would be necessary.

4.7. Off-label output rates

Off-label predictions are defined as generated outputs that cannot be parsed to any of the five allowed product categories. Both base and fine-tuned models produce near-zero off-label rates. For Qwen3-8B, the base model generates one off-label prediction across 15,428 internal-test examples (0.006%), while all three fine-tuned seeds produce zero off-label outputs. For Llama 3.1-8B, the base model produces zero off-label predictions on the internal test, and one isolated off-label output appears in seed 42 of the fine-tuned model (0.002% across 46,284 seed-examples). On the 12 legacy subsets, neither base nor fine-tuned models of either family produce any off-label predictions. These results confirm that the constrained JSON-output prompt format and greedy decoding reliably keep both base and fine-tuned models within the allowed label taxonomy, and that fine-tuning does not introduce taxonomy violations.

5. Discussion

The results show that PEFT substantially improves open-source LLM complaint classification under a leakage-safe evaluation protocol. The dataset statistics justify the design: the natural corpus is dominated by `credit_reporting`, whereas the preserved legacy benchmark intentionally contains both balanced and imbalanced views. This makes macro-F1, class-level analysis, and paired legacy evaluation more informative than accuracy alone. The narrative-length statistics also support the preprocessing choice: most complaints are short enough for efficient 8B-model adaptation, but the long tail still requires an explicit and reproducible truncation rule.

Tables 2 and 3 show large and statistically stable internal-test gains: macro-F1 improves by 0.2056 for Qwen3-8B and 0.2189 for Llama 3.1-8B, with bootstrap intervals indicating precise prediction-level improvements. Tables 4 and 5 provide the second layer of evidence. Because the legacy subsets are excluded from training and model selection, the Wilcoxon results across 12 subsets show that the gains are not merely internal-test artefacts but survive a protected return to the earlier zero-shot benchmark setting.

Table 6 prevents overclaiming: TF-IDF and encoder models remain strong supervised baselines for this fixed five-class taxonomy. The contribution is therefore not that PEFT universally dominates lighter models, but that it offers a locally deployable, leakage-controlled route from zero-shot open-source LLM inference to competitive supervised performance under a fixed training budget. This is useful when an organisation wants to keep the same generative model family for prompting, adaptation, and auditable local deployment rather

than introducing a separate classifier for every downstream task. The latency results add the corresponding deployment trade-off: fine-tuning costs approximately 0.31–0.32 additional seconds per complaint, which is acceptable for offline analytics, audit, compliance, or semi-real-time routing but should still be considered alongside accuracy and reproducibility.

Figure 1 explains the main error-level change. In zero-shot mode, both models over-map `debt_collection` narratives to `credit_reporting`, which is plausible because debt disputes often mention credit reports, bureaus, disputed accounts, and collections together. Fine-tuning reduces this dominant error by approximately two thirds, suggesting that the adapters learn a more dataset-specific boundary. The remaining credit-reporting/debt-collection confusions also indicate where future deployment safeguards should focus: human review, cost-sensitive training, or class-specific calibration for high-impact boundary cases. This matters because the study evaluates product-category routing rather than consumer-facing decisions, but routing errors can still delay responses to particular complaint types.

Finally, the results illustrate why leakage control is central to the comparison. If legacy zero-shot subsets had entered training, Tables 4 and 5 would no longer support a meaningful paired benchmark. By removing those records before split construction and using them only at final evaluation, the study evaluates the transition from zero-shot inference to QLoRA fine-tuning without erasing the benchmark that motivated the transition.

6. Limitations

This study does not propose a new architecture or PEFT algorithm; LoRA and QLoRA are established methods, and the contribution is a controlled empirical evaluation in a high-value application domain. The experiments use two 8B-class model families and a fixed 10,000-example training budget; larger decoder models, alternative PEFT methods, and larger training budgets remain future work. The zero-shot prompt is fixed rather than optimised, which supports paired comparison with the preserved zero-shot benchmark but does not rule out prompt sensitivity. The 500-character narrative limit keeps QLoRA training feasible on 16 GB GPUs and fully covers 63% of examples, but longer context windows could benefit long-tail complaints. Encoder baselines could also be strengthened with domain-adapted checkpoints, larger variants, or wider hyperparameter searches. Latency is measured with serial batch-size-1 inference rather than deployment-oriented batching. Finally, the CFPB corpus is English-language and domain-specific, the split is not temporal, and the protected legacy subsets are separated from training and validation but still come from the same source distribution rather than an independently collected external dataset.

7. Conclusion

This paper evaluates the transition from zero-shot open-source LLM inference to leakage-controlled QLoRA fine-tuning for consumer complaint classification. Across Qwen3-8B and Llama 3.1-8B, parameter-efficient fine-tuning produces large and stable gains over base zero-shot inference on both an internal test set and preserved legacy zero-shot subsets. The paired design shows that the gain is not merely a result of changing infrastructure, prompts, or evaluation sets; it is observed when the same model families are compared before and after task-specific adaptation under protected data splits. The findings support the use of locally deployable PEFT pipelines for regulated complaint triage settings where commercial API use may be costly, difficult to reproduce, or undesirable for data-governance reasons.

Acknowledgment and/or disclaimers, if any

The numerical experiments reported in this study were carried out on the TRUBA ARF high-performance computing infrastructure operated by TÜBİTAK ULAKBİM. The authors gratefully acknowledge the computational resources and technical infrastructure provided by TRUBA.

Declaration of Generative AI and AI-assisted technologies, if any

During the preparation of this manuscript, the authors used AI-assisted tools only for English grammar correction, wording refinement, and LaTeX formatting support. The research idea, experimental design, dataset preparation, model fine-tuning, inference runs, statistical analyses, interpretation of results, and final scientific decisions were carried out by the authors. The authors reviewed and edited all AI-assisted text and take full responsibility for the content of the manuscript.

Data availability statement

The source CFPB complaint data are publicly available from the Consumer Financial Protection Bureau. The derived split manifests, experiment scripts, classical baseline outputs, and archived metric tables are maintained in a GitHub repository that is currently private. The repository will be made available to reviewers upon request and will be considered for public release after acceptance, subject to anonymisation, repository-cleaning, storage, and model-license requirements.

Funding, if any

The authors received no specific funding for this study.

Conflict of interest, if any

The authors declare no conflict of interest.

References

[1] Devlin J, Chang MW, Lee K, Toutanova K. BERT: pre-training of deep bidirectional transformers for language understanding. In: Proceedings of NAACL-HLT; Minneapolis, MN, USA; 2019. pp. 4171-4186.

[2] Sanh V, Debut L, Chaumond J, Wolf T. DistilBERT, a distilled version of BERT: smaller, faster, cheaper and lighter. arXiv:1910.01108, 2019.

[3] Liu Y, Ott M, Goyal N, Du J, Joshi M et al. RoBERTa: a robustly optimized BERT pretraining approach. arXiv:1907.11692, 2019.

[4] Sy CY, Maceda LL, Canon MJP, Flores NM. Beyond BERT: exploring the efficacy of RoBERTa and ALBERT in supervised multiclass text classification. International Journal of Advanced Computer Science and Applications 2024; 15 (3). doi: 10.14569/IJACSA.2024.0150323.

[5] Bozyiğit F, Doğan O, Kılınç D. Categorization of customer complaints in food industry using machine learning approaches. Journal of Intelligent Systems: Theory and Applications 2022; 5 (1): 85-91. doi: 10.38016/jista.954098.

[6] Gewaly M, Saeed MS, Ammar MA. Machine learning approach for complaint prediction in the telecom industry. In: 2024 Intelligent Methods, Systems, and Applications; 2024. doi: 10.1109/IMSA61967.2024.10652677.

[7] Vairetti C, Aranguiz I, Maldonado S, Karmy JP, Leal A. Analytics-driven complaint prioritisation via deep learning and multicriteria decision-making. European Journal of Operational Research 2024; 312 (3): 1108-1118.

[8] Sangaraju VR, Bolla BK, Nayak DK, Kh J. Topic modelling on Consumer Financial Protection Bureau data: an approach using BERT based embeddings. arXiv:2205.07259, 2022.

[9] Das S, Singh A, Saha S, Maurya A. Negative review or complaint? Exploring interpretability in financial complaints. IEEE Transactions on Computational Social Systems 2024; 11 (3): 3606. doi: 10.1109/TCSS.2023.3338357.

[10] Shin M, Kim J, Shin J. The adoption and efficacy of large language models: evidence from consumer complaints in the financial industry. arXiv:2311.16466, 2025.

[11] Liang W, Zhang Y, Codreanu M, Wang J, Cao H et al. The widespread adoption of large language model-assisted writing across society. arXiv:2502.09747, 2025.

[12] Liu Y, Ouyang X, Bai R, Zhu X, Zhou Y et al. A framework for categorizing complaint text via large language model. In: 2024 7th International Conference on Advanced Algorithms and Control Engineering; 2024. doi: 10.1109/ICAACE61206.2024.10549750.

[13] Li F, Wang Y, Xu Y, Wang S, Liang J et al. Performance evaluations of large language models for customer service. International Journal of Machine Learning and Cybernetics 2025; 16: 2997-3017. doi: 10.1007/s13042-024-02432-9.

[14] Güllü M, Atagün E, Biroğul S, Barışçı N. Customer complaint classification with large language models. In: 2025 International Conference on Artificial Intelligence, Computer, Data Sciences and Applications; Antalya, Türkiye; 2025. doi: 10.1109/ACDSA65407.2025.11166338.

[15] Roumeliotis KI, Tselikas ND, Nasiopoulos DK. Think before you classify: the rise of reasoning large language models for consumer complaint detection and classification. Electronics 2025; 14: 1070. doi: 10.3390/electronics14061070.

[16] Hu EJ, Shen Y, Wallis P, Allen-Zhu Z, Li Y et al. LoRA: low-rank adaptation of large language models. In: International Conference on Learning Representations; 2022.

[17] Dettmers T, Pagnoni A, Holtzman A, Zettlemoyer L. QLoRA: efficient finetuning of quantized LLMs. In: Advances in Neural Information Processing Systems; 2023.

[18] Li XL, Liang P. Prefix-tuning: optimizing continuous prompts for generation. In: Proceedings of ACL-IJCNLP; 2021. pp. 4582-4597.

[19] Liu H, Tam D, Muqeeth M, Mohta J, Huang T et al. Few-shot parameter-efficient fine-tuning is better and cheaper than in-context learning. In: Advances in Neural Information Processing Systems; 2022.

[20] Consumer Financial Protection Bureau. Consumer complaint database. Website https://www.consumerfinance.gov/data-research/consumer-complaints/ [accessed 01 July 2026].

[21] Yang A, Li A, Yang B, Zhang B, Hui B et al. Qwen3 technical report. arXiv:2505.09388, 2025.

[22] Grattafiori A, Dubey A, Jauhri A, Pandey A, Kadian A et al. The Llama 3 herd of models. arXiv:2407.21783, 2024.

[23] Paszke A, Gross S, Massa F, Lerer A, Bradbury J et al. PyTorch: an imperative style, high-performance deep learning library. In: Advances in Neural Information Processing Systems; 2019. pp. 8024-8035.

[24] Wolf T, Debut L, Sanh V, Chaumond J, Delangue C et al. Transformers: state-of-the-art natural language processing. In: Proceedings of EMNLP: System Demonstrations; Online; 2020. pp. 38-45.

[25] Mangrulkar S, Gugger S, Debut L, Belkada Y, Paul S et al. PEFT: state-of-the-art parameter-efficient fine-tuning methods. GitHub repository, 2022.