BBS Mobile (Erlangga Network)

APK Reverse Engineering & Complete API Documentation Report

Target File:	`bbs.apk`	Framework:	`Flutter (Dart AOT, Release)`
File Size:	`53,995,982 bytes (~54 MB)`	Dart Snapshot Hash:	`ace654289f5abc240509fc941453ebc5`
SHA-256 Digest:	`ddf162649b94812ceaa6435117887adf3a14c5465387288ca4cd62a6118f1d03`	Architectures:	`arm64-v8a, armeabi-v7a, x86_64`
		Original Project:	`/Users/.../projek/payment_apps`
Package Name:	`com.example.payment_apps`	Target Base URL:	`https://stage.erlangga.net/api`
App Display Name:	`BBS (Erlangga Network)`		

1. Screen-by-Screen API Mapping (4 Main Tabs)

The app navigation is configured in `main_navigation.dart` with four primary screens:

1. Home Screen (home_screen.dart)

`TAB 1: HOME`

Associated Widgets: `StatusSection`, `InfoPaketSection`, `TagihanSection`, `StatusCard`

Required APIs:

Endpoint	Method	Auth	Purpose & Handled Data
`https://stage.erlangga.net/api/dashboard`	`GET`	`BEARER`	Fetches all core homepage sections: • **Connection Status:** PPPoE status & connection telemetry (`pppoe_username` , `status`). • **Active Internet Plan:** Subscribed plan details (`nama_paket` , `kecepatan` , `harga`). • **Current Bill Summary:** Outstanding invoice count (`unpaid_invoices_count`), bill status (`status_invoice`), and total due (`total_harga`).
`https://api.xendit.co/v2/invoices`	`POST`	API Key	Triggered when tapping **"Bayar Sekarang"** on `TagihanSection` . Generates an online payment invoice and opens `XenditWebViewScreen` .

2. History Screen (billing_history_screen.dart)

TAB 2: RIWAYAT

Associated Widgets: `BillingCard`, `BillingDetailScreen`

Required APIs:

Endpoint	Method	Auth	Purpose & Handled Data
`https://stage.erlangga.net/api/riwayat`	GET	BEARER	Retrieves full historical billing records: • Invoice identifiers (`external_id` , `sn_perangkat`). • Billing period name (`periode` , e.g., "Tagihan Agustus"). • Payment status (`status_invoice` : paid / unpaid / expired). • Amount charged (`harga` / `total_harga`). • Direct checkout URL (`invoice_url`) and validity period (`invoice_duration`).
`https://api.xendit.co/v2/invoices`	POST	API Key	Generates payment transaction for any unpaid invoices selected in `BillingDetailScreen` .
File Download API	GET	Optional	Downloads PDF receipts / invoices via `flutter_downloader` to `/storage/emulated/0/Download` .

3. Notification Screen (notification_screen.dart)

TAB 3: NOTIFIKASI

Associated Widgets: `NotificationCard`, `NotificationDetailScreen`, `CustomeEmptyState`

Required APIs:

Endpoint / Mechanism	Type	Purpose & Implementation Details
`token_fcm` (during `POST /api/login`)	Push Notification	Firebase Cloud Messaging device push token registered with backend to receive billing & broadcast alerts.
Recommended New API: `GET /api/notifications`	GET	*Implementation Note:* The current APK uses static billing broadcast cards and fallback empty state (`"Belum Ada Notifikasi"`). A dedicated `GET /api/notifications` endpoint should be implemented for dynamic notification feeds.

4. Profile Screen (profile_screen.dart)

`TAB 4: PROFIL`

Associated Widgets: `ProfileAccordionCard`, `ProfileDetailRow`, `ProfileMenuTile`

Required APIs:

Endpoint / Integration	Method	Auth	Purpose & Handled Data
`https://stage.erlangga.net/api/dashboard` *(or cached CustomerModel)*	`GET`	`BEARER`	Supplies subscriber technical & account information: • `nama_lengkap`: Subscriber full name. • `id_pelanggan`: Customer account number. • `pppoe_username`: PPPoE connection login. • `alamat_lengkap`: Installation physical address. • `sn_perangkat`: Optical Network Terminal (ONT) / Modem serial number. • `tanggal_aktif`: Service installation / activation date. • `nama_paket`: Current internet package tier.
Support Link: WhatsApp API	External Intent	None	Launches WhatsApp chat with pre-filled message: `"Halo Admin, saya mengalami kendala lupa kata sandi/akun Aplikasi Erlangga Network."`
Support Link: Mailto	External Intent	None	Opens email client addressing `Hersapms@erlangga.net` / `erlangga.net@mybbs.id`.

2. Network Client & Authentication Architecture

Environment Configuration: Runtime configuration loaded from `assets/flutter_assets/.env` containing `BASE_URL=https://stage.erlangga.net/api`.
Authentication Token: Bearer token via HTTP header `Authorization: Bearer <tokenUser>`.
Token Persistence: Stored locally as `tokenUser` via `flutter_secure_storage` (backed by Android Keystore / Tink AES-GCM EncryptedSharedPreferences).
Session Invalidation (401 Handling): Intercepts HTTP `401 Unauthorized`, logs `[UNAUTH] Sesi berakhir...`, calls `removeTokenUser`, and redirects to `/login`.

3. Complete API Specifications

`POST` **`https://stage.erlangga.net/api/login`**

Authenticates a subscriber using Customer ID and password.

Field	Type	Required	Description
`id_pelanggan`	String	Yes	Subscriber / Customer ID account code
`password`	String	Yes	Account password
`token_fcm`	String	No	Firebase Cloud Messaging push notification token

Response Model: `LoginResponseModel` (provides session Bearer token stored as `tokenUser`).

GET AUTH **https://stage.erlangga.net/api/dashboard**

Aggregates user profile, active subscription, and billing dues.

Category	Field	Type	Description
Profile	`id_pelanggan` , `nama_lengkap`	String	Customer credentials
	`pppoe_username`	String	Router PPPoE login username
	`alamat_lengkap`	String	Installation street address
	`sn_perangkat` , `tanggal_aktif`	String	Hardware Serial Number & activation date
Package	`nama_paket` , `kecepatan`	String	Plan name (e.g. "Paket Bronze 20Mbps") & speed
	`harga` / `total_harga`	Number/String	Monthly subscription fee
Tagihan	`status_invoice` , `has_unpaid_bill`	String/Bool	Pending invoice flag and status
	`unpaid_invoices_count`	Integer	Outstanding bill count

GET AUTH **https://stage.erlangga.net/api/riwayat**

Lists past and present billing cycles (mapped to `BillingCard` & `BillingDetailScreen`):

Field	Type	Description
`external_id`	String	Unique invoice / transaction reference identifier
`periode`	String	Billing month / period label (e.g., "Tagihan Agustus")
`status_invoice`	String	Payment status (`paid` , `unpaid` , `expired`)
`harga` / `total_harga`	Number/String	Invoice amount due
`invoice_url`	String	Hosted payment invoice checkout URL (Xendit)
`invoice_duration`	Integer	Validity window in seconds

POST **https://api.xendit.co/v2/invoices**

Payment Gateway integration for online bill payments. Opened via in-app `XenditWebViewScreen` .

Payload Field	Source / Value	Description
`external_id`	Billing record reference	Unique transaction reference
`amount`	`total_harga`	Transaction amount to be charged
`payer_email`	Customer email / Fallback	Defaults: `Hersapms@erlangga.net` / `erlangga.net@mybbs.id`
`description`	Invoice description	e.g. "Tagihan Layanan Internet Erlangga Network"
`success_redirect_url`	`https://example.com/success`	Redirect URL on successful payment
`failure_redirect_url`	`https://example.com/failure`	Redirect URL on failed/expired payment