

1. Create a ClusterIP service for an Apache web server pod.

Create a httpd pod with this script.

apiVersion: v1

kind: Pod

metadata:

name: apache-pod

labels:

app: apache

spec:

containers:

- name: apache

image: httpd:2.4

ports:

- containerPort: 80

```
apiVersion: v1
kind: Pod
metadata:
  name: apache-pod
  labels:
    app: apache
spec:
  containers:
    - name: apache
      image: httpd:2.4
      ports:
        - containerPort: 80
```

- **kubectl apply -f apache.yml**

```
[root@master ~]# vi apache.yml
[root@master ~]# kubectl create -f apache.yml
pod/apache-pod created
[root@master ~]# kubectl get pods
NAME          READY   STATUS    RESTARTS   AGE
apache-pod    1/1     Running   0           15s
[root@master ~]#
```

Create a service for apache

- **vi apacheservice.yml**

apiVersion: v1

kind: Service

metadata:

name: apache-service

spec:

type: ClusterIP

selector:

app: apache

ports:

- protocol: TCP

port: 80 # Service port

targetPort: 80 # Pod container port

```

apiVersion: v1
kind: Service
metadata:
  name: apache-service
spec:
  type: ClusterIP
  selector:
    app: apache
  ports:
    - protocol: TCP
      port: 80      # Service port
      targetPort: 80 # Pod container port

```

- **kubectl apply -f apacheservice.yml**

```

[root@master ~]# vi apacheservice.yml
[root@master ~]# kubectl create apacheservice.yml
error: Unexpected args: [apacheservice.yml]
See 'kubectl create -h' for help and examples
[root@master ~]# kubectl create -f apacheservice.yml
service/apache-service created
[root@master ~]#

```

- **kubectl get pods**
- **kubectl get svc**

```

[root@master ~]# kubectl get pods
NAME          READY   STATUS    RESTARTS   AGE
apache-pod    1/1     Running   0           27m
[root@master ~]# kubectl get svc
NAME           TYPE        CLUSTER-IP      EXTERNAL-IP   PORT(S)    AGE
apache-service ClusterIP    10.104.6.214    <none>        80/TCP     82s
kubernetes     ClusterIP    10.96.0.1       <none>        443/TCP    2d22h

```

2. Expose an Nginx pod externally using a NodePort service.

- vi nginx.yml

apiVersion: v1

kind: Pod

metadata:

name: nginx-pod

labels:

app: nginx

spec:

containers:

- name: nginx

image: nginx

ports:

- containerPort: 80

```
apiVersion: v1
kind: Pod
metadata:
  name: nginx-pod
  labels:
    app: nginx
spec:
  containers:
  - name: nginx
    image: nginx
    ports:
    - containerPort: 80
```

- kubectl apply -f nginx.yml

```
[root@master ~]# vi nginx.yml
[root@master ~]# kubectl apply -f nginx.yml
pod/nginx-pod created
```

- vi nodeport.yml

apiVersion: v1

kind: Service

metadata:

name: nginx-nodeport

spec:

type: NodePort

selector:

app: nginx

ports:

- protocol: TCP

port: 80 # Service port

targetPort: 80 # Pod port

nodePort: 30007

```

apiVersion: v1
kind: Service
metadata:
  name: nginx-nodeport
spec:
  type: NodePort
  selector:
    app: nginx
  ports:
  - protocol: TCP
    port: 80      # Service port
    targetPort: 80 # Pod port
    nodePort: 30007

```

- **kubectl apply -f nodeport.yml**

```

[root@master ~]# vi nodeport.yml
[root@master ~]# kubectl apply -f nodeport.yml
service/nginx-nodeport created
[root@master ~]# kubectl get pods
NAME        READY   STATUS    RESTARTS   AGE
nginx-pod   1/1     Running   0           6m36s
[root@master ~]# kubectl get svc
NAME            TYPE        CLUSTER-IP    EXTERNAL-IP   PORT(S)          AGE
kubernetes      ClusterIP   10.96.0.1     <none>        443/TCP          2d22h
nginx-nodeport  NodePort    10.96.82.197  <none>        80:30007/TCP     26s
[root@master ~]#


```

- **kubectl get pods**
- **kubectl get svc**

```

[root@master ~]# kubectl get pods
NAME        READY   STATUS    RESTARTS   AGE
nginx-pod   1/1     Running   0           6m36s
[root@master ~]# kubectl get svc
NAME            TYPE        CLUSTER-IP    EXTERNAL-IP   PORT(S)          AGE
kubernetes      ClusterIP   10.96.0.1     <none>        443/TCP          2d22h
nginx-nodeport  NodePort    10.96.82.197  <none>        80:30007/TCP     26s
[root@master ~]#

```




Welcome to nginx!

If you see this page, the nginx web server is successfully installed and working. Further configuration is required.

For online documentation and support please refer to nginx.org.
Commercial support is available at nginx.com.

Thank you for using nginx.



Welcome to nginx!

If you see this page, the nginx web server is successfully installed and working. Further configuration is required.

For online documentation and support please refer to nginx.org.
Commercial support is available at nginx.com.

Thank you for using nginx.

3. Deploy a ReplicationController to maintain 3 replicas of an Nginx pod.

Create a yaml file and write the

- **vi nginxrc.yml**

apiVersion: v1

kind: ReplicationController

metadata:

name: nginx-rc

spec:

replicas: 3

selector:

app: nginx

template:

metadata:

labels:

app: nginx

spec:

containers:

- name: nginx

image: nginx

ports:

- containerPort: 80

```
apiVersion: v1
kind: ReplicationController
metadata:
  name: nginx-rc
spec:
  replicas: 3
  selector:
    app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
        - name: nginx
          image: nginx
          ports:
            - containerPort: 80
```


- **kubectl get rc**
- **kubectl get pods**

```
[root@master ~]# vi nginxrc.yml
[root@master ~]# kubectl apply -f nginxrc.yml
replicationcontroller/nginx-rc created
[root@master ~]# kubectl get rc
NAME          DESIRED    CURRENT    READY    AGE
nginx-rc      3          3          3        12s
[root@master ~]# kubectl get pods
NAME          READY    STATUS    RESTARTS   AGE
nginx-rc-7gcn2 1/1      Running   0          24s
nginx-rc-kxmdx 1/1      Running   0          24s
nginx-rc-w2qjk 1/1      Running   0          24s
[root@master ~]# kubectl get pods -o wide
NAME          READY    STATUS    RESTARTS   AGE    IP            NODE          NOMINATED NODE   READINESS GATES
nginx-rc-7gcn2 1/1      Running   0          33s    10.244.2.10   worker-02     <none>           <none>
nginx-rc-kxmdx 1/1      Running   0          33s    10.244.2.11   worker-02     <none>           <none>
nginx-rc-w2qjk 1/1      Running   0          33s    10.244.1.9    worker-01     <none>           <none>
[root@master ~]#
```

4. Scale the ReplicationController from 3 replicas to 5 replicas.

execute this command

- **kubectl scale rc nginx-rc --replicas=5**

```
[root@master ~]# kubectl scale rc nginx-rc --replicas=5
replicationcontroller/nginx-rc scaled
```

- **kubectl get rc nginx-rc**
- **kubectl get pods**

```
[root@master ~]# kubectl get rc nginx-rc
NAME          DESIRED    CURRENT    READY    AGE
nginx-rc      5          5          5        3m38s
[root@master ~]# kubectl get pods
NAME          READY    STATUS    RESTARTS   AGE
nginx-rc-7gcn2 1/1      Running   0          3m50s
nginx-rc-9zfmv 1/1      Running   0          25s
nginx-rc-kxmdx 1/1      Running   0          3m50s
nginx-rc-qcg2z 1/1      Running   0          25s
nginx-rc-w2qjk 1/1      Running   0          3m50s
[root@master ~]#
```

Or you can do another way by changing the yaml file keep the replicas as 5.

5. Create a ReplicaSet to manage pods based on multiple labels (prod and test).

apiVersion: apps/v1

kind: ReplicaSet

metadata:

name: nginx-rs

spec:

replicas: 3

selector:

matchExpressions:

- key: env

operator: In

values:

- prod

- test

template:

metadata:

labels:

app: nginx

env: prod

spec:

containers:

- name: nginx

image: nginx

ports:

- containerPort: 80

```
apiVersion: apps/v1
kind: ReplicaSet
metadata:
  name: nginx-rs
spec:
  replicas: 3
  selector:
    matchExpressions:
      - key: env
        operator: In
        values:
          - prod
          - test
  template:
    metadata:
      labels:
        app: nginx
        env: prod
    spec:
      containers:
        - name: nginx
          image: nginx
          ports:
            - containerPort: 80
```

- **kubectl apply -f prodtest.yml**
- **kubectl get rs**
- **kubectl get pods --show-labels**

```
[root@master ~]# kubectl apply -f prodtest.yml
replicaset.apps/nginx-rs created
[root@master ~]# kubectl get rs
NAME          DESIRED   CURRENT   READY   AGE
nginx-rs      3         3         3       20s
[root@master ~]# kubectl get pods --show-labels
NAME          READY   STATUS    RESTARTS   AGE   LABELS
nginx-rs-2kp65 1/1     Running   0          34s   app=nginx,env=prod
nginx-rs-f5qzh 1/1     Running   0          34s   app=nginx,env=prod
nginx-rs-s6jxq 1/1     Running   0          35s   app=nginx,env=prod
[root@master ~]#
```

6. Deploy a ReplicaSet that excludes pods with the label backend.

- **vi backend.yml**

apiVersion: apps/v1

kind: ReplicaSet

metadata:

name: nginx-rs-exclude-backend

spec:

replicas: 3

selector:

matchExpressions:

- key: role

operator: NotIn

values:

- backend

template:

metadata:

labels:

app: nginx

role: frontend

spec:

containers:

- name: nginx

image: nginx

ports:

- containerPort: 80

```
apiVersion: apps/v1
kind: ReplicaSet
metadata:
  name: nginx-rs-exclude-backend
spec:
  replicas: 3
  selector:
    matchExpressions:
      - key: role
        operator: NotIn
        values:
          - backend
  template:
    metadata:
      labels:
        app: nginx
        role: frontend
    spec:
      containers:
        - name: nginx
          image: nginx
          ports:
            - containerPort: 80
```

- **kubectl apply -f backend.yml**
- **kubectl get pods --show-labels**

```
[root@master ~]# kubectl apply -f backend.yml
replicaset.apps/nginx-rs-exclude-backend created
[root@master ~]# kubectl get rs
NAME                                DESIRED    CURRENT    READY    AGE
nginx-rs-exclude-backend            3          3          3        49s
[root@master ~]# kubectl get pods --show-labels
NAME                                READY     STATUS    RESTARTS   AGE    LABELS
nginx-rs-exclude-backend-6lzc7     1/1      Running   0           59s    app=nginx,role=frontend
nginx-rs-exclude-backend-84nxv     1/1      Running   0           59s    app=nginx,role=frontend
nginx-rs-exclude-backend-cwr9z     1/1      Running   0           59s    app=nginx,role=frontend
[root@master ~]# kubectl get pods -o wide
NAME                                READY     STATUS    RESTARTS   AGE    IP             NODE           NOMINATED NODE
nginx-rs-exclude-backend-6lzc7     1/1      Running   0           4m9s   10.244.1.16    worker-01      <none>
nginx-rs-exclude-backend-84nxv     1/1      Running   0           4m9s   10.244.2.18    worker-02      <none>
nginx-rs-exclude-backend-cwr9z     1/1      Running   0           4m9s   10.244.2.17    worker-02      <none>
[root@master ~]# kubectl get rs -o wide
NAME                                DESIRED    CURRENT    READY    AGE    CONTAINERS    IMAGES    SELECTOR
nginx-rs-exclude-backend            3          3          3        4m51s   nginx         nginx     role notin (backend)
[root@master ~]#
```

7. Test load balancing across multiple pods using a NodePort service.

- **vi nginxrs.yml**

apiVersion: apps/v1

kind: ReplicaSet

metadata:

name: nginx-rs

spec:

replicas: 3

selector:

matchLabels:

app: nginx

template:

metadata:

labels:

app: nginx

spec:

containers:

- name: nginx

image: nginx

ports:

- containerPort: 80

command: ["/bin/sh", "-c"]

args:

- |

echo "<h1>Pod: \$(hostname)</h1>" >
/usr/share/nginx/html/index.html;
nginx -g 'daemon off;'

```

apiVersion: apps/v1
kind: ReplicaSet
metadata:
  name: nginx-rs
spec:
  replicas: 3
  selector:
    matchLabels:
      app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
        - name: nginx
          image: nginx
          ports:
            - containerPort: 80
          command: ["/bin/sh", "-c"]
          args:
            - |
              echo "<h1>Pod: $(hostname)</h1>" > /usr/share/nginx/html/index.html;
              nginx -g 'daemon off;'
```

- vi nodeportservice.yml

apiVersion: v1

kind: Service

metadata:

name: nginx-nodeport

spec:

type: NodePort

selector:

app: nginx

ports:

- port: 80

targetPort: 80

nodePort: 30007


```

apiVersion: v1
kind: Service
metadata:
  name: nginx-nodeport
spec:
  type: NodePort
  selector:
    app: nginx
  ports:
  - port: 80
    targetPort: 80
    nodePort: 30007

```


- **kubectl apply -f nodeportservice.yml**
- **kubectl get svc nginx-nodeport**
- **kubectl get endpoints nginx-nodeport**

```


[root@master ~]# vi nginxrs.yml
[root@master ~]# kubectl apply -f nginxrs.yml
replicaset.apps/nginx-rs created
[root@master ~]# vi nodeportservice.yml
[root@master ~]# kubectl apply -f nodeport.yml
error: the path "nodeport.yml" does not exist
[root@master ~]# kubectl apply -f nodeportservice.yml
service/nginx-nodeport created
[root@master ~]# kubectl get svc nginx-nodeport
NAME                TYPE        CLUSTER-IP      EXTERNAL-IP  PORT(S)          AGE
nginx-nodeport      NodePort    10.109.225.143  <none>       80:30007/TCP     15s
[root@master ~]# kubectl get endpoints nginx-nodeport
Warning: v1 Endpoints is deprecated in v1.33+; use discovery.k8s.io/v1 Endpointslice
NAME                ENDPOINTS                                           AGE
nginx-nodeport      10.244.1.19:80,10.244.1.20:80,10.244.2.20:80     30s

```


Search on browser with 3 node machines public ip and port number 30007.



Pod: nginx-rs-zm542



Pod: nginx-rs-hkfb5



Pod: nginx-rs-d8cmh

8. Delete a ReplicationController without affecting the running pods.

Create a replication controller file or use the file in 3rd question.

- **vi replicationcontroller.yml**

apiVersion: v1

kind: ReplicationController

metadata:

name: nginx-rc

spec:

replicas: 3

selector:

app: nginx

template:

metadata:

labels:

app: nginx

spec:

containers:

- name: nginx

image: nginx

ports:

- containerPort: 80

```
apiVersion: v1
kind: ReplicationController
metadata:
  name: nginx-rc
spec:
  replicas: 3
  selector:
    app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
        - name: nginx
          image: nginx
          ports:
            - containerPort: 80
```

- **kubectl apply -f replicationcontroller.yml**

```
[root@master ~]# vi replicationcontroller.yml
[root@master ~]# kubectl apply -f replicationcontroller.yml
replicationcontroller/nginx-rc created
[root@master ~]# kubectl get rc
NAME          DESIRED    CURRENT    READY    AGE
nginx-rc      3          3          3        9s
```

- **kubectl delete rc nginx-rc --cascade=orphan**
- **kubectl get rc**
- **kubectl get pods --show-labels**

```
[root@master ~]# kubectl delete rc nginx-rc --cascade=orphan
replicationcontroller "nginx-rc" deleted from default namespace
[root@master ~]# kubectl get rc
No resources found in default namespace.
[root@master ~]# kubectl get pods --show-labels
NAME          READY    STATUS    RESTARTS    AGE    LABELS
nginx-rc-rcpr4 1/1      Running   0            74s    app=nginx
nginx-rc-rs4h5 1/1      Running   0            74s    app=nginx
nginx-rc-wnl76 1/1      Running   0            74s    app=nginx
```