Safety and Rollback Mechanisms for Objective Misinterpretation in Agentic AI Systems

MUJAHID WAJED ANSARI, Indian Institute of Information Technology Allahabad, India

Agentic artificial intelligence (AI) systems are increasingly capable of planning, reasoning, using external tools, and executing multi-step actions with limited human intervention. These capabilities create a distinctive safety problem: an agent may operationalize an assigned objective differently from the intention of its developer or user. The resulting failure can arise from underspecified objectives, reward misspecification, goal misgeneralization, or incorrect interpretation of constraints. Unlike a conventional model that only produces an output, an agent can propagate an incorrect interpretation through a sequence of tool calls and environmental actions. This review synthesizes foundational work on AI safety, human preferences, cooperative inverse reinforcement learning, learned optimization, power-seeking behavior, constitutional approaches, and recent agentic-system safety frameworks. Based on this literature, the paper organizes safeguards into prevention, detection, intervention, containment, and recovery. Particular attention is given to objective validation, permission and constraint control, runtime monitoring, human approval, checkpointing, transaction-style execution, action logging, and rollback. The review also compares these mechanisms according to the stage of failure they address and the reversibility assumptions they require. The analysis indicates that rollback is most useful as a recovery mechanism for reconstructible digital state and cannot by itself undo physical, financial, informational, or social consequences. The paper therefore synthesizes a layered safety architecture in which rollback is positioned after prevention, detection, and intervention rather than treated as a standalone solution. Research gaps include reliable objective interpretation, measurable detection of objective drift, evaluation benchmarks for long-horizon agent failures, scalable human oversight, and recovery mechanisms that account for effects outside the agent's local state.

CCS Concepts: • **Computing methodologies** → **Artificial intelligence**; • **Security and privacy** → *Systems security*; • **Human-centered computing** → *Human computer interaction (HCI).*

Additional Key Words and Phrases: agentic AI, AI safety, objective misinterpretation, alignment, goal misgeneralization, runtime monitoring, rollback, human-in-the-loop

1 Introduction

Artificial intelligence systems have progressed from models that primarily generate information to systems capable of planning, using tools, interacting with software, and executing multi-step tasks. This transition changes the safety problem because an incorrect interpretation can be propagated through a sequence of actions rather than appearing only as a single incorrect response. Recent work on agentic safety emphasizes that risks can emerge from interactions among models, orchestrators, tools, data, and the surrounding environment [5].

A fundamental challenge is ensuring that an AI system correctly operationalizes the objective intended by its developer or user. Natural-language instructions frequently contain implicit priorities, constraints, contextual assumptions, and prohibitions. An instruction such as "reduce expenses" may therefore be satisfied literally while violating the broader intention if the agent treats cost reduction as the only relevant criterion. The classic AI-safety literature identifies related concerns including reward hacking, negative side effects, and the difficulty of specifying objectives completely [1, 8].

Agentic systems make these concerns more consequential because planning and tool use can turn a small misunderstanding into a long sequence of dependent actions. Human-preference learning and cooperative inverse reinforcement learning address part of the problem by reducing dependence on a fully specified reward function and by treating human preferences as information that an AI system should infer [4, 6]. Learned-optimization research further highlights the

Author's Contact Information: Mujahid Wajed Ansari, Indian Institute of Information Technology Allahabad, Prayagraj, India.

possibility that a trained system can implement optimization processes whose behavior differs from the designer's intended objective [7].

This paper reviews these connected lines of work and focuses specifically on the safety question that arises after an agent has begun acting: how can a system detect an incorrect objective, stop further propagation, and recover from actions that have already occurred? The review distinguishes rollback from prevention and containment and develops a layered synthesis in which recovery is only one part of the safety architecture.

2 Review Scope and Organization

The review focuses on mechanisms relevant to autonomous or semi-autonomous systems that can plan, use tools, modify state, or interact with external environments. The literature is organized around five questions: (1) how objective errors arise, (2) how they can be detected, (3) how action authority can be bounded, (4) when humans should intervene, and (5) what recovery mechanisms can realistically reverse after an undesirable action.

The foundational literature includes the safety problems identified by Amodei et al. [1], the control perspective developed by Russell [8], preference learning by Christiano et al. [4], cooperative inverse reinforcement learning by Hadfield-Menell et al. [6], learned optimization by Hubinger et al. [7], and power-seeking analysis by Turner et al. [9]. More recent work connects these ideas to agentic execution, including constitutional approaches [2], dynamic agentic safety frameworks [5], and trajectory-level diagnosis of agent failures [3].

3 Objective Misinterpretation and Related Safety Problems

Objective misinterpretation occurs when an AI system's understanding or operationalization of an assigned goal differs materially from the intention of the human or system that provided the goal. Natural-language objectives often leave important constraints implicit. For example, "find the cheapest suitable flight" may be understood by a human as balancing price with safety, reasonable travel time, baggage requirements, and schedule constraints, while an automated optimizer may place disproportionate weight on price.

3.1 Reward Misspecification and Negative Side Effects

When an AI system is optimized against an imperfect measurable objective, it may discover strategies that improve the metric without achieving the underlying intention [1, 4]. This creates a direct connection between objective interpretation and reward design. The problem is not necessarily that the agent fails to optimize; rather, the agent may optimize the wrong proxy effectively.

3.2 Human Preferences and Cooperative Objectives

Preference-based reinforcement learning attempts to obtain information about desired behavior from human feedback rather than relying exclusively on a hand-written reward function [4]. Cooperative inverse reinforcement learning takes a related approach in which the system treats the human's objective as something to infer and cooperate toward [6]. These approaches reduce some specification burden, but they do not remove the need for runtime constraints when an agent is permitted to take consequential actions.

3.3 Learned Optimization and Power-Seeking Considerations

Hubinger et al. describe risks associated with learned optimization, including the possibility that an internal optimization process may pursue an objective that differs from the training objective [7]. Turner et al. analyze conditions under

which optimal policies tend to seek power, illustrating why the behavior of autonomous systems may need to be monitored rather than inferred solely from their nominal objective [9].

4 Risk Taxonomy for Agentic Objective Failures

The reviewed literature supports a practical taxonomy of risks shown in Table 1. The taxonomy is framed around what can happen after an objective is incorrectly interpreted rather than around model architecture.

Table 1. Taxonomy of risks created by objective misinterpretation.

Risk category	Description	Example consequence
Unintended side effects	The agent changes resources or systems that are outside the intended task.	Valuable data may be deleted during an optimization task.
Excessive resource use	The agent consumes more money, computation, time, or organizational capacity than intended.	A cost-saving task produces excessive compute expenditure.
Unauthorized actions	The agent interprets its authority too broadly.	A high-impact operation is executed without approval.
Cascading errors	An early objective error affects planning, tool selection, and subsequent actions.	A mistaken plan produces many dependent tool calls.
Irreversible consequences	The environment cannot be fully restored after an action.	Money, confidential information, physical state, or public messages may remain affected.

Figure 1 illustrates how an objective error can propagate through an agentic workflow. The important observation is that intervention opportunities exist at multiple points, not only after the final action.




Fig. 1. Propagation path for objective misinterpretation in a multi-step agentic workflow.

5 Safety Mechanisms: Prevention, Detection, Intervention, and Recovery

The literature can be synthesized into four functional stages: prevention, detection, intervention, and recovery. These stages are complementary rather than mutually exclusive.

5.1 Objective Validation

Before execution, a system can translate a natural-language instruction into an explicit representation of objectives, constraints, prohibited actions, and approval requirements. This step addresses ambiguity before it becomes an external side effect. It is consistent with the broader control perspective that objectives in open-ended environments are difficult to specify completely [8].

5.2 Permission and Constraint Control

Tool access should be bounded by explicit permissions. Low-risk operations can be automated while destructive, financial, security-sensitive, or irreversible operations can be restricted. Constraint-based execution is particularly important because a correct interpretation of an objective does not guarantee that every action considered by the agent is acceptable.

5.3 Runtime Monitoring and Drift Detection

Runtime monitoring compares current behavior with the approved objective, plan, permissions, and resource expectations. Recent agent-failure research demonstrates the value of analyzing complete execution trajectories because failures can be difficult to localize in long-horizon, tool-mediated runs [3]. Dynamic agentic safety frameworks likewise emphasize contextual risk discovery and monitoring across models, tools, and environments [5].

5.4 Human-in-the-Loop Intervention

Human approval can be required when an action crosses a predefined risk threshold. This is particularly relevant to financial transactions, legal commitments, destructive operations, security changes, public communication, and actions affecting third parties. Human oversight nevertheless introduces its own limitations, including approval fatigue and misunderstanding; therefore, it should complement automated safeguards rather than replace them.

Constitutional AI provides another perspective by incorporating explicit behavioral principles into training and evaluation [2]. Such principles can support safer behavior, but they do not by themselves provide a transactional recovery mechanism for external side effects.

5.5 Checkpointing and Transaction-Style Execution

Before consequential actions, the system can record recoverable state such as file versions, database snapshots, configurations, or transaction state. A transaction-style execution pattern can be expressed as *prepare, validate, execute, verify, commit*; when verification fails, the system can attempt to abort and restore a previous state. This pattern is most directly applicable to environments where state is reconstructible.

5.6 Action Logging

Durable action logs support both diagnosis and recovery. A useful log can record the timestamp, agent identity, objective, action, tool, input, output, risk level, approval state, and checkpoint identifier. Logging does not prevent an incorrect action, but it improves traceability and supports post-incident analysis.

5.7 Rollback and Fail-Safe Stop

Rollback restores a system to a previously known state after an undesirable action or sequence. It should be paired with a fail-safe stop because recovery is not always possible. If uncertainty becomes high, the safer response may be to pause execution and request clarification rather than continue acting and rely on later rollback.




Fig. 2. Layered safety synthesis for objective misinterpretation in agentic AI systems.

6 Comparative Analysis of Existing Approaches

Table 2 compares the main strands of literature reviewed in this paper. The comparison does not treat the approaches as interchangeable: preference learning addresses objective specification, runtime diagnosis addresses execution-time detection, and rollback addresses recovery after a state-changing action.

Table 2. Comparison of literature relevant to objective misinterpretation and agentic safety.

Work	Primary focus	Mechanism or contribution	Limitation relevant to agentic rollback
Amodei et al. [1]	AI safety problems	Identifies reward hacking, negative side effects, and other core safety problems.	Provides a broad problem taxonomy rather than a complete runtime recovery architecture.
Russell [8]	Control and objective specification	Frames the difficulty of specifying objectives and maintaining control over capable systems.	Does not itself define an implementation-level rollback protocol for tool-using agents.
Christiano et al. [4]	Human preference learning	Learns desired behavior from human feedback.	Preference information does not guarantee safe execution of every external action.
Hadfield-Menell et al. [6]	Cooperative inverse reinforcement learning	Treats the human objective as something to infer through cooperation.	Objective inference still needs action constraints and runtime safeguards in high-impact environments.
Hubinger et al. [7]	Learned optimization	Analyzes risks when learned systems implement optimization processes.	Conceptual risk analysis does not specify recovery from external side effects.
Turner et al. [9]	Power-seeking behavior	Studies conditions under which optimal policies tend to seek power.	Does not provide a direct objective-drift detector or rollback system.
Bai et al. [2]	Behavioral principles	Uses explicit principles and AI feedback to train a harmless assistant.	Primarily concerns training/behavioral alignment, not transactional recovery.
Ghosh et al. [5]	Agentic safety and security	Provides contextual risk management, red teaming, monitoring, and a taxonomy of agentic risks.	Framework-level approach; recovery of irreversible external consequences remains a separate problem.
Barke et al. [3]	Agent failure diagnosis	Localizes critical failure steps in execution trajectories and provides an auditable validation log.	Diagnosis identifies failures but does not by itself undo completed external actions.

7 Proposed Layered Safety Synthesis

The literature suggests that no single mechanism covers the full lifecycle of objective misinterpretation. Figure 2 synthesizes the reviewed mechanisms into five layers. Table 3 maps each layer to the failure stage it addresses and the main assumption on which it depends.

Table 3. Mechanism-to-failure mapping.

Layer	Main role	Key assumption
Objective validation	Reduce ambiguity before execution.	The intended objective can be elicited or represented sufficiently well.
Permission and constraints	Limit the actions available to the agent.	Tool permissions can be enforced independently of the model's decision.
Runtime monitoring	Detect divergence during execution.	Relevant deviations can be observed early enough to matter.
Intervention	Pause, reject, or request human confirmation.	A trusted stop or approval mechanism exists.
Checkpointing and rollback	Restore recoverable digital state.	The affected state and dependencies can be reconstructed.

8 Limitations of Rollback

Rollback is valuable but cannot solve every safety problem. Its effectiveness depends on what the agent changed and on whether the affected environment is fully under system control.

8.1 Physical Actions

If an autonomous robot causes physical damage, restoring software state cannot reverse the physical consequences. Prevention, constrained actuation, and rapid intervention are therefore more important than software rollback alone.

8.2 External Communications and Information Disclosure

If an agent sends confidential information to another party, deleting the local record does not necessarily retrieve the information. The external recipient and any copies may remain outside the recovery boundary.

8.3 Financial Transactions

A financial transfer may be difficult or impossible to reverse after completion. Transaction authorization, spending limits, and human confirmation can therefore be necessary before execution.

8.4 Social Consequences

A public message may be copied or redistributed before rollback occurs. Removing the original therefore does not imply that the consequence has been eliminated.

8.5 Hidden Side Effects

An action may trigger external systems that are not under the agent's control. Restoring the agent's internal state can consequently fail to restore the complete environment.

These limitations explain why prevention and containment should occur before recovery whenever possible. Rollback should be treated as a final recovery layer rather than a substitute for objective validation and action constraints.

9 Research Gaps and Future Directions

The comparison reveals several open research directions.

9.1 Reliable Objective Interpretation

Current approaches can use preferences, principles, or explicit constraints, but robustly translating ambiguous natural-language objectives into an auditable operational specification remains difficult. Future work should evaluate whether an agent's interpreted objective matches the user's intended priorities before consequential actions occur.

9.2 Measurable Objective-Drift Detection

Monitoring needs operational criteria for identifying when a plan or action sequence has departed from the approved objective. Trajectory-level diagnosis provides one useful direction [3], but broader benchmarks are needed across domains and levels of autonomy.

9.3 Evaluation Benchmarks for Recovery

Many safety evaluations emphasize whether an agent produces an unsafe output or completes a task. Agentic safety additionally requires measuring whether an unsafe action was prevented, detected, contained, and, where possible, recovered. Benchmarks should therefore record reversibility, external side effects, detection latency, and residual consequences.

9.4 Scalable Human Oversight

Human approval can be effective for high-impact operations but does not scale if every low-level action requires intervention. Research is needed on risk-adaptive approval policies that reduce approval fatigue while preserving meaningful control over consequential actions.

9.5 Recovery Beyond Local State

Rollback mechanisms are strongest when all affected state is under one system's control. Real-world agents increasingly interact with independent services, people, and physical environments. Recovery research should therefore model distributed and partially irreversible consequences rather than assuming a single restorable state.

10 Discussion

The central observation from the reviewed literature is that agent capability and safety are different dimensions. A system can be highly effective at executing an objective while still operating on an incorrect interpretation of that objective. The relevant safety question is consequently not only whether the agent can complete a task, but whether the system can keep its behavior within an intended and controllable boundary.

The mechanisms reviewed in Sections 5 and 7 address different points in the lifecycle. Objective validation and preference-oriented methods address specification before execution. Constraints and permissions reduce the action space. Runtime monitoring and trajectory diagnosis support detection. Human approval and fail-safe stops provide intervention. Checkpoints and rollback provide recovery when state is reconstructible. The layered model in Figure 2 therefore represents a synthesis of complementary mechanisms rather than a claim that one mechanism is sufficient.

The distinction between reversible and irreversible effects is especially important. A software state may be restored while an external consequence remains. This means that recovery guarantees should be stated with an explicit boundary: what state is covered, what external systems are affected, and what consequences can remain after restoration. Recent agentic-safety work similarly emphasizes contextual risk management across models, tools, and environments [5].

11 Conclusion

Objective misinterpretation is a significant safety concern for agentic AI because autonomous systems can transform a small misunderstanding into a sequence of consequential actions. The literature reviewed here connects this problem to reward misspecification, human-preference learning, cooperative inverse reinforcement learning, learned optimization, power-seeking considerations, behavioral principles, and emerging agentic-safety frameworks.

The review synthesizes these perspectives into a layered architecture consisting of objective validation, permission and constraint control, runtime monitoring, intervention, and recovery. Rollback is useful when the affected state can be reconstructed, but it cannot reliably reverse physical damage, information disclosure, financial transfers, public communication, or hidden effects in external systems. Consequently, rollback should be treated as one component of a broader safety strategy.

Future work should focus on reliable objective interpretation, measurable objective-drift detection, trajectory-level evaluation, scalable human oversight, and recovery mechanisms that explicitly account for partially irreversible environments. These directions can help move agentic safety from isolated safeguards toward lifecycle-oriented control and recovery.

Acknowledgments

The author acknowledges the use of LaTeX and Overleaf as part of the scientific-writing laboratory exercise. The manuscript is based on the previously submitted review topic and was reorganized to emphasize literature synthesis, comparison, cross-referencing, and research gaps.

References

[1] Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. 2016. Concrete Problems in AI Safety. *arXiv preprint arXiv:1606.06565* (2016).

[2] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Azalia Goldie, Azalia Mirhoseini, et al. 2022. Constitutional AI: Harmlessness from AI Feedback. *arXiv preprint arXiv:2212.08073* (2022).

[3] Shraddha Barke, Arnav Goyal, Alind Khare, Avaljot Singh, Suman Nath, and Chetan Bansal. 2026. AgentRx: Diagnosing AI Agent Failures from Execution Trajectories. *arXiv preprint arXiv:2602.02475* (2026).

[4] Paul F. Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2017. Deep Reinforcement Learning from Human Preferences. In *Advances in Neural Information Processing Systems*, Vol. 30.

[5] Shaona Ghosh, Barnaby Simkin, Kyriacos Shiarlis, Soumili Nandi, Dan Zhao, Matthew Fiedler, Julia Bazinska, Nikki Pope, Roopa Prabhu, Daniel Rohrer, Michael Demoret, and Bartley Richardson. 2025. A Safety and Security Framework for Real-World Agentic Systems. *arXiv preprint arXiv:2511.21990* (2025). doi:10.48550/arXiv.2511.21990

[6] Dylan Hadfield-Menell, Anca Dragan, Pieter Abbeel, and Stuart Russell. 2016. Cooperative Inverse Reinforcement Learning. *arXiv preprint arXiv:1606.03137* (2016).

[7] Evan Hubinger, Chris van Merwijk, Vladimir Mikulik, Joar Skalse, and Scott Garrabrant. 2019. Risks from Learned Optimization in Advanced Machine Learning Systems. *arXiv preprint arXiv:1906.01820* (2019).

[8] Stuart Russell. 2022. Artificial Intelligence and the Problem of Control. In *Perspectives on Digital Humanism*. 19–24. doi:10.1007/978-3-030-86144-5_3

[9] Alexander Matt Turner, Logan Smith, Rohin Shah, Andrew Critch, and Prasad Tadepalli. 2021. Optimal Policies Tend to Seek Power. In *Advances in Neural Information Processing Systems*, Vol. 34.