

Security Scan Report

Generated: December 22, 2025 at 15:13 | Targets: 192.168.117.128 **CRITICAL RISK**

Executive Summary

1	11	11	206	100/100
Hosts Scanned	Open Ports	Services Found	Total CVEs	Risk Score
19	50	104	33	
Critical	High	Medium	Low	

AI Threat Analysis

Threat Summary

The target system, 192.168.117.128, is overwhelmingly vulnerable due to an extremely outdated and insecure installation of the Postfix mail transfer agent (MTA) and related services (SQLgrey, polycyd). The presence of a CRITICAL vulnerability (CVE-2011-1720, likely a typo in the provided list based on severity vs year, but assumed to be the highest present) alongside multiple HIGH-rated flaws indicates severe exposure to remote code execution, denial of service, and unauthorized access. The sheer volume and age of these vulnerabilities suggest the host is likely a forgotten or unmaintained system highly susceptible to compromise.

Executive Summary

This system, 192.168.117.128, is running severely outdated mail software, Postfix, that exposes the organization to numerous severe security risks dating back over a decade. The scan identified several High and one Critical vulnerability, primarily revolving around authentication bypass, potential remote code execution through SQL injection, and denial of service attacks. We must immediately isolate this host, as it is currently an open door for unauthorized use, data compromise, or network disruption if exploited. Comprehensive remediation, likely involving a complete rebuild or migration of the mail services, is required immediately.

■ Attack Scenarios

- **Remote Code Execution/Data Exfiltration via SQL Injection:** An attacker could exploit CVE-2011-1720 (assuming the SQLgrey vulnerability description is associated with a high-severity finding) to execute arbitrary SQL commands against the underlying database used by SQLgrey, potentially leading to local file disclosure or system access if the database user has sufficient privileges.
- **Unauthenticated Mail Relay/Authentication Bypass:** Utilizing CVE-2004-1088 (CRAM-MD5 replay attack) or CVE-2004-0925 (username not cleared between attempts), an external attacker could likely send mail through the server without credentials, leading to spam relaying or phishing attacks, or potentially gain access to mailboxes if authentication persists across sessions.
- **Denial of Service (DoS) or System Instability:** An attacker could leverage multiple DoS vulnerabilities, such as CVE-2003-0540 (Postfix lock) or CVE-2007-3791 (policyd buffer overflow), to crash the mail service, rendering email functionality unavailable to legitimate users.

■ Vulnerability Findings (206 CVEs)

CVE ID	Severity	Score	Description
CVE-2001-0894	MEDIUM	5.0	Vulnerability in Postfix SMTP server before 20010228-pl07, w...
CVE-2003-0468	MEDIUM	5.0	Postfix 1.1.11 and earlier allows remote attackers to use Po...
CVE-2003-0540	MEDIUM	5.0	The address parser code in Postfix 1.1.12 and earlier allows...
CVE-2004-1088	HIGH	7.5	Postfix server for Apple Mac OS X 10.3.6, when using CRAM-MD...
CVE-2004-1113	CRITICAL	10.0	SQL injection vulnerability in SQLgrey Postfix greylisting s...
CVE-2004-0925	MEDIUM	5.0	Postfix on Mac OS X 10.3.x through 10.3.5, with SMTPD AUTH e...

CVE-2005-0337	HIGH	7.5	Postfix 2.1.3, when /proc/net/if_inet6 is not available and ...
CVE-2005-1127	MEDIUM	5.0	Format string vulnerability in the log function in Net::Serv...
CVE-2006-0213	MEDIUM	4.6	Kolab Server 2.0.1, 2.0.2 and development versions pre-2.1-2...
CVE-2007-3791	HIGH	7.5	Buffer overflow in the w_read function in sockets.c in Cami ...
CVE-2008-2936	MEDIUM	6.2	Postfix before 2.3.15, 2.4 before 2.4.8, 2.5 before 2.5.4, a...
CVE-2008-2937	LOW	1.9	Postfix 2.5 before 2.5.4 and 2.6 before 2.6-20080814 deliver...
CVE-2008-3889	LOW	2.1	Postfix 2.4 before 2.4.9, 2.5 before 2.5.5, and 2.6 before 2...
CVE-2008-3646	MEDIUM	6.8	The Postfix configuration file in Mac OS X 10.5.5 causes Pos...
CVE-2008-4977	MEDIUM	6.9	postfix_groups.pl in Postfix 2.5.2 allows local users to ove...
CVE-2009-2939	MEDIUM	6.9	The postfix.postinst script in the Debian GNU/Linux and Ubun...
CVE-2010-0230	HIGH	7.5	SUSE Linux Enterprise 10 SP3 (SLE10-SP3) and openSUSE 11.2 c...

CVE-2011-0411	MEDIUM	6.8	The STARTTLS implementation in Postfix 2.4.x before 2.4.16, ...
CVE-2011-1720	MEDIUM	6.8	The SMTP server in Postfix before 2.5.13, 2.6.x before 2.6.1...
CVE-2013-7176	MEDIUM	5.0	config/filter.d/postfix.conf in the postfix filter in Fail2b...
CVE-2008-0122	CRITICAL	10.0	Off-by-one error in the inet_network function in libbind in ...
CVE-2009-0025	MEDIUM	6.8	BIND 9.6.0, 9.5.1, 9.5.0, 9.4.3, and earlier does not proper...
CVE-2009-0265	HIGH	7.5	Internet Systems Consortium (ISC) BIND 9.6.0 and earlier doe...
CVE-2009-0696	MEDIUM	4.3	The dns_db_findrdataset function in db.c in named in ISC BIN...
CVE-2009-4022	LOW	2.6	Unspecified vulnerability in ISC BIND 9.0.x through 9.3.x, 9...
CVE-2010-0097	MEDIUM	4.3	ISC BIND 9.0.x through 9.3.x, 9.4 before 9.4.3-P5, 9.5 befor...
CVE-2010-0290	MEDIUM	4.0	Unspecified vulnerability in ISC BIND 9.0.x through 9.3.x, 9...
CVE-2010-0382	HIGH	7.6	ISC BIND 9.0.x through 9.3.x, 9.4 before 9.4.3-P5, 9.5 befor...

CVE-2010-3614	MEDIUM	6.4	named in ISC BIND 9.x before 9.6.2-P3, 9.7.x before 9.7.2-P3...
CVE-2011-1910	MEDIUM	5.0	Off-by-one error in named in ISC BIND 9.x before 9.7.3-P1, 9...
CVE-2011-4313	MEDIUM	5.0	query.c in ISC BIND 9.0.x through 9.6.x, 9.4-ESV through 9.4...
CVE-2012-1033	MEDIUM	5.0	The resolver in ISC BIND 9 through 9.8.1-P1 overwrites cache...
CVE-2012-1667	HIGH	8.5	ISC BIND 9.x before 9.7.6-P1, 9.8.x before 9.8.3-P1, 9.9.x b...
CVE-2012-3817	HIGH	7.8	ISC BIND 9.4.x, 9.5.x, 9.6.x, and 9.7.x before 9.7.6-P2; 9.8...
CVE-2012-4244	HIGH	7.8	ISC BIND 9.x before 9.7.6-P3, 9.8.x before 9.8.3-P3, 9.9.x b...
CVE-2012-5166	HIGH	7.8	ISC BIND 9.x before 9.7.6-P4, 9.8.x before 9.8.3-P4, 9.9.x b...
CVE-2014-8500	HIGH	7.8	ISC BIND 9.0.x through 9.8.x, 9.9.0 through 9.9.6, and 9.10....
CVE-2015-8000	MEDIUM	5.0	db.c in named in ISC BIND 9.x before 9.9.8-P2 and 9.10.x bef...
CVE-2015-8461	HIGH	7.1	Race condition in resolver.c in named in ISC BIND 9.9.8 befo...

CVE-2015-8704	MEDIUM	6.5	apl_42.c in ISC BIND 9.x before 9.9.8-P3, 9.9.x, and 9.10.x ...
CVE-2007-6420	MEDIUM	4.3	Cross-site request forgery (CSRF) vulnerability in the balan...
CVE-2008-0455	MEDIUM	4.3	Cross-site scripting (XSS) vulnerability in the mod_negotiat...
CVE-2008-0456	LOW	2.6	CRLF injection vulnerability in the mod_negotiation module i...
CVE-2008-2364	MEDIUM	5.0	The ap_proxy_http_process_response function in mod_proxy_htt...
CVE-2008-2939	MEDIUM	4.3	Cross-site scripting (XSS) vulnerability in proxy_ftp.c in t...
CVE-2009-1195	MEDIUM	4.9	The Apache HTTP Server 2.2.11 and earlier 2.2 versions does ...
CVE-2009-0023	MEDIUM	4.3	The apr_strmatch_precompile function in strmatch/apr_strmatc...
CVE-2009-1955	HIGH	7.5	The expat XML parser in the apr_xml_* interface in xml/apr_x...
CVE-2009-1956	MEDIUM	6.4	Off-by-one error in the apr_brigade_vprintf function in Apac...

CVE-2009-1890	HIGH	7.1	The stream_reqbody_cl function in mod_proxy_http.c in the mo...
---------------	------	-----	---

Recommendations

- ✓ ■ URGENT: Address 19 critical vulnerabilities immediately. These pose severe risk and may allow remote code execution or complete system compromise.
- ✓ ■ HIGH PRIORITY: Remediate 50 high severity vulnerabilities. Schedule patches within the next 1-2 weeks.
- ✓ ■ MEDIUM PRIORITY: Plan to address 104 medium severity issues. Include in your next maintenance window.
- ✓ ■ HARDENING: Consider reducing attack surface by closing unnecessary ports. Found 11 open ports.

Host Details

192.168.117.128

Port	Service	Product	CVEs
25/tcp	smtp	Postfix smtpd	20
53/tcp	domain	ISC BIND	20
80/tcp	http	Apache httpd	20
139/tcp	netbios-ssn	Samba smbd	20
445/tcp	netbios-ssn	Samba smbd	20
5432/tcp	postgresql	PostgreSQL DB	20
21/tcp	ftp	vsftpd	19
2121/tcp	ftp	ProFTPD	18
22/tcp	ssh	OpenSSH	20

23/tcp	telnet	Linux telnetd	20
3306/tcp	mysql	MySQL	9