Products Public GET APIs

Custom
Base UR
No dista
Optiona

Endpoint map

Screen	Method + path	Params
Product home	GET|POST products/getPublicHome	country?, lang?
Top products	GET|POST products/topProducts	lat/lng ignored
All products	GET|POST products/getAll	cate_id?, sub_cate_id?, uid?, q?, limit?
By category	GET|POST products/getProducts	cate_id?, sub_cate_id?, limit?
Search	GET|POST products/search	q REQUIRED
Detail	GET|POST products/getById	id REQUIRED
Variants	GET|POST products/getVariants	id REQUIRED
Gallery	GET|POST products/getGallery	id REQUIRED
Seller products	GET|POST products/getBySeller	id = seller uid
Sellers list	GET|POST products/getSellers	(none)
Offers	GET|POST product_offers/getActive	(none)

Shared product object (inside data / products arrays)

Field	Type	Meaning
id	int	Catalog product id
name	string	Product name
cover	string	Cover image URL/path
original_price	number	MRP
sell_price	number	Selling price (also shop_price / amount)
discount	number	Discount value as stored
customer_pays	number	Price customer pays
cate_id / sub_cate_id	int	Category ids
freelacer_id	int	Seller user id
stock / stock_qty / in_stock	mix	Stock info
rating / total_rating	mix	Ratings
in_home	0|1	Featured on home
gallery	array	[{view, label, url}]
images_list	string[]	Flat image URLs
variants	array	Variant rows
has_variants	bool	Has variants or not
payment_methods	array	e.g. cod, online
returnable / return_days	mix	Return policy
tax_amount / tax_*	mix	GST helpers on item

Root tax object (on most responses)

```
{
  "tax_rate": 0,
  "tax_inclusive": true,
  "tax_mode": "inclusive",
  "tax_type": "GST",
  "tax_country": null,
  "tax_available": false
}
```

1. products/getPublicHome

```
GET|POST /api/v1/products/getPublicHome
```

Params

Param	Required	Notes
country	no	Optional country hint
lang	no	Optional locale

Request

```
{}
```

Response keys

Key	Type	Meaning
categories	array	Product categories; each has subCates[]
products	array	Home products (shared product object)
top_products	array	Same list as products
offers	array	Active product offers/coupons
sellers	array	Product stores (id, name, cover, address, type)
product_sellers	array	Same as sellers
show_products	bool	Section enabled for country
distance_filtered	bool	Always false
tax	object	GST meta
success	bool	true
status	int	200

Sample response


```
{
  "categories": [
    {
      "id": 1,
      "name": "Skincare",
      "status": 1,
      "subCates": [
        { "id": 2, "name": "Face Serum", "cate_id": 1, "status": 1 }
      ]
    }
  ],
  "products": [
    {
      "id": 17,
      "name": "Sample Product",
      "original_price": 999,
      "sell_price": 799,
      "discount": 20,
      "customer_pays": 799,
      "gallery": [],
      "variants": [],
      "has_variants": false
```

```
    }
  ],
  "top_products": [ /* same as products */ ],
  "offers": [],
  "sellers": [
    {
      "id": 610,
      "uid": 610,
      "name": "LiveinPro Enterprises",
      "cover": "uploads/images/1770442854.jpg",
      "address": "Kakkanad, Kochi",
      "type": "product"
    }
  ],
  "product_sellers": [ /* same as sellers */ ],
  "show_products": true,
  "distance_filtered": false,
  "tax": {
    "tax_rate": 0,
    "tax_inclusive": true,
    "tax_mode": "inclusive",
    "tax_type": "GST"
  },
  "success": true,
  "status": 200
}
```


2. products/topProducts

```
GET|POST /api/v1/products/topProducts
```

Params

Param	Required	Notes
lat / lng	no	Accepted for compatibility; IGNORED (no distance)

Request

```
{}
```

Response keys

Key	Type	Meaning
products	array	Top / home products
data	array	Same as products
show_products	bool	Section enabled
distance_filtered	bool	Always false
tax	object	GST meta
success / status	bool/int	true / 200

Sample response


```
{
  "products": [
    {
      "id": 17,
```

```
      "name": "Sample Product",
      "cover": "",
      "original_price": 999,
      "sell_price": 799,
      "discount": 20,
      "customer_pays": 799,
      "rating": "0.00",
      "in_home": 1,
      "stock": 25,
      "gallery": [],
      "variants": [],
      "has_variants": false
    }
  ],
  "data": [ /* same as products */ ],
  "show_products": true,
  "distance_filtered": false,
  "tax": { "tax_rate": 0, "tax_inclusive": true },
  "success": true,
  "status": 200
}
```


Loads in_home=1 first, then fills remaining slots with other active products.

3. products/getAll

```
GET|POST /api/v1/products/getAll
```

Params

Param	Required	Notes
cate_id	no	Filter by category
sub_cate_id	no	Filter by sub category
uid	no	Seller uid (aliases: seller_id, freelancer_id, freelacer_id)
q	no	Name contains (aliases: search, keyword)
limit	no	Default 40, max 100

Request

```
{
  "cate_id": 1,
  "sub_cate_id": 2,
  "uid": 1724,
  "q": "phone",
  "limit": 40
}
```

Response keys

Key	Type	Meaning
data	array	Product list
products	array	Same as data
count	int	Number of rows returned
tax	object	GST meta
success / status	bool/int	true / 200

Sample response

```
{
  "data": [
    {
      "id": 17,
      "name": "Sample Product",
      "sell_price": 799,
      "original_price": 999,
      "gallery": [],
      "variants": []
    }
  ],
  "products": [ /* same as data */ ],
  "count": 1,
  "tax": { "tax_rate": 0, "tax_inclusive": true },
  "success": true,
  "status": 200
}
```

4. products/getProducts

```
GET|POST /api/v1/products/getProducts
```

Params

Param	Required	Notes
cate_id	no	Optional category filter
sub_cate_id	no	Optional sub category filter
limit	no	Default 40, max 100

Request

```
{
  "cate_id": 1,
  "sub_cate_id": 2,
  "limit": 40
}
```

Response shape is the same as getAll: data, products, count, tax, success, status.

5. products/search

```
GET|POST /api/v1/products/search
```

Params

Param	Required	Notes
q	YES	Search keyword (aliases: search, keyword)
limit	no	Passed through to getAll
cate_id / uid	no	Other getAll filters also work

Request

```
{ "q": "Sample" }
```

Error if q missing

```
{
  "success": false,
  "message": "q (search keyword) is required.",
  "status": 422
}
```

Success response: same shape as getAll.

6. products/getById (alias: getProductInfo)

```
GET|POST /api/v1/products/getById
```

Params

Param	Required	Notes
id	YES	Catalog product id (alias: product_id)

Request

```
{ "id": 17 }
```

Response keys

Key	Type	Meaning
data	object	Full product + gallery + variants
related	array	Related products (same seller/sub cate)
cateInfo	object|null	Category row
subCateInfo	object|null	Sub category row
soldby	object	Seller/store (id, first_name, last_name, status)
history*	mix	Seller order history - ignore on customer app
tax	object	GST meta
success / status	bool/int	true / 200

Sample response


```
{
  "data": {
    "id": 17,
    "name": "Sample Product",
    "original_price": 999,
    "sell_price": 799,
    "discount": 20,
    "customer_pays": 799,
    "stock": 25,
    "gallery": [],
    "variants": [],
    "has_variants": false,
    "freelacer_id": 1723
  },
  "related": [],
  "cateInfo": null,
  "subCateInfo": null,
  "soldby": {
    "id": 1723,
    "first_name": "Papa Bear Products",
    "last_name": " ",
    "status": 1
  },
  "history": [],
  "history_counts": {},
  "history_totals": {},
  "tax": {
    "tax_rate": 0,
```

```
    "tax_inclusive": true,
    "tax_mode": "inclusive",
    "tax_type": "GST"
  },
  "success": true,
  "status": 200
}
```


Not found


```
{
  "success": false,
  "message": "Data not found.",
  "status": 404
}
```


7. products/getVariants

```
GET|POST /api/v1/products/getVariants
```

Params

Param	Required	Notes
id	YES	Catalog product id

Request

```
{ "id": 17 }
```

Response keys

Key	Type	Meaning
data	array	Variant list
variants	array	Same as data
product_id	int	Parent product id
has_variants	bool	true if variants exist
tax	object	GST meta
success / status	bool/int	true / 200

Sample response


```
{
  "data": [],
  "variants": [],
  "product_id": 17,
  "has_variants": false,
  "tax": { "tax_rate": 0, "tax_inclusive": true },
  "success": true,
  "status": 200
}
```


When present, each variant has price, stock, color, measurement, optional gallery.

8. products/getGallery

```
GET|POST /api/v1/products/getGallery
```

Params

Param	Required	Notes
id	YES	Catalog product id

Request

```
{ "id": 17 }
```

Response keys

Key	Type	Meaning
data	array	Gallery rows [{view, label, url}]
gallery	array	Same as data
images	string[]	Flat URL list
cover	string	Cover image
product_id	int	Product id
success / status	bool/int	true / 200

Sample response

```
{
  "data": [
    { "view": "front", "label": "Front", "url": "https://cdn.example/front.jpg" }
  ],
  "gallery": [
    { "view": "front", "label": "Front", "url": "https://cdn.example/front.jpg" }
  ],
  "images": [ "https://cdn.example/front.jpg" ],
  "cover": "https://cdn.example/front.jpg",
  "product_id": 17,
  "success": true,
  "status": 200
}
```

9. products/getBySeller

```
GET|POST /api/v1/products/getBySeller
Aliases: getFreelancerProducts, getSellerProducts
```

Params

Param	Required	Notes
id	YES	Seller user.id / freelacer_id
uid / seller_id / ...	alt	Accepted if id omitted

Request

```
{ "id": 1724 }
```

Response keys

Key	Type	Meaning

Key	Type	Meaning
data	array	That seller's active products
products	array	Same as data
tax	object	GST meta
success / status	bool/int	true / 200

Sample response

```
{
  "data": [
    {
      "id": 12,
      "name": "Hydra Boost",
      "sell_price": 500,
      "gallery": [],
      "variants": []
    }
  ],
  "products": [ /* same as data */ ],
  "tax": { "tax_rate": 0, "tax_inclusive": true },
  "success": true,
  "status": 200
}
```

10. products/getSellers

```
GET|POST /api/v1/products/getSellers
Aliases: getStores, getProductSellers
```

Params

Param	Required	Notes
(none)	-	No body or query required

Request

```
{}
```

Response keys

Key	Type	Meaning
data	array	Seller/store list
sellers	array	Same as data
success / status	bool/int	true / 200

Each seller row

Field	Type	Meaning
id / uid	int	Seller user id
name	string	Store / display name
first_name / last_name	string	User names
cover	string	Store image
address	string|null	Address
lat / lng	string|null	Coordinates

Field	Type	Meaning
products_count	int	Active product count
type	string	Always "product"

Sample response


```
{
  "data": [
    {
      "id": 610,
      "uid": 610,
      "name": "LiveinPro Enterprises",
      "first_name": "Asif",
      "last_name": "saj",
      "cover": "uploads/images/1770442854.jpg",
      "address": "Kakkanad, Kochi",
      "lat": "10.03246",
      "lng": "76.33654",
      "products_count": 1,
      "type": "product"
    }
  ],
  "sellers": [ /* same as data */ ],
  "success": true,
  "status": 200
}
```

11. Product offers (public)

```
GET|POST /api/v1/product_offers/getActive
GET|POST /api/v1/product_offers/getPublic
POST /api/v1/product_offers/getById
```

Params

Path	Params	Notes
getActive / getPublic	(none)	Active product coupons
getById	{ "id": 37 }	One offer by id

On product offers, service_ids are product IDs. Response may also include product_ids / products.

Flutter flow

- Products tab -> products/getPublicHome (or topProducts + product_categories/getHome)
- Category -> products/getProducts { cate_id, sub_cate_id }
- Search -> products/search { q }
- Card tap -> products/getById { id }
- Optional screens -> getGallery / getVariants { id }
- Store profile -> getBySeller { id: sellerUid }
- Coupons strip -> product_offers/getActive

Notes

- Create / update / stock / offer CRUD: see PRODUCTS_CRUD_MOBILE_API and PRODUCT_OFFERS_MOBILE_API.
- Do not apply partner nearby radius to these product GET APIs.
- Prefer GET|POST so existing POST clients keep working.