

# SmartTrack API - School Admin

**Base URL:** `{{base_url}}`

School-admin slice of the SmartTrack API: the CRUD/lookup and approval endpoints a school's admin console uses to manage students, drivers, buses, routes, trips, leave requests, guest-trip approvals, notifications and support tickets.

How to use: 1. Run "Login - School Admin" first -- it saves `school_admin_token` as a collection variable that every other request in this doc authenticates with. 2. Run the Lookups folder to pull real ids (students, drivers, buses, routes) into collection variables for use in the rest of the requests.

Seeded demo account (see backend/src/db/seed.js): admin@greenfield.ae.

## Contents

- 1. Auth (1 requests)
- 2. Lookups (capture IDs) (4 requests)
- 3. QR [NEW] (2 requests)
- 4. Trips (1 requests)
- 5. Attendance (1 requests)
- 6. Leave (1 requests)
- 8. Guest Trips (1 requests)
- 9. Notifications (1 requests)
- 10. Tickets (1 requests)

## Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

| Variable                           | Default / Notes           |
|------------------------------------|---------------------------|
| <code>baseUrl</code>               | http://localhost:5000/api |
| <code>school_admin_email</code>    | admin@greenfield.ae       |
| <code>school_admin_password</code> | School@123                |
| <code>school_admin_token</code>    | (captured at runtime)     |
| <code>school_id</code>             | GREENFIELD                |
| <code>student_id</code>            | (captured at runtime)     |
| <code>bus_id</code>                | (captured at runtime)     |
| <code>safety_qr_code</code>        | (captured at runtime)     |

|               |                       |
|---------------|-----------------------|
| route_id      | (captured at runtime) |
| route_qr_code | (captured at runtime) |
| driver_id     | (captured at runtime) |
| trip_id       | (captured at runtime) |
| leave_id      | (captured at runtime) |
| guest_trip_id | (captured at runtime) |
| ticket_id     | (captured at runtime) |

## 1. Auth

### 1. Login - School Admin

**POST** `{{base_url}}/auth/login`

#### Request Body

```
{
  "email": "{{school_admin_email}}",
  "password": "{{school_admin_password}}",
  "school_id": "{{school_id}}"
}
```

#### Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

#### Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('school_admin_token', data.token);
```

## 2. Lookups (capture IDs)

### 1. List Students (school\_admin)

**GET** `{{base_url}}/students`

## Request Headers

| Header        | Value                         |
|---------------|-------------------------------|
| Authorization | Bearer {{school_admin_token}} |

## Response Example

200

```
{
  "students": []
}
```

## Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.students && data.students.length) {
  pm.collectionVariables.set('student_id', data.students[0].id);
  if (data.students[0].student_qr_code) pm.collectionVariables.set('student_qr_code', data.students[0].student_qr_code);
}
```

## 2. List Drivers (school\_admin)

GET {{base\_url}}/drivers

## Request Headers

| Header        | Value                         |
|---------------|-------------------------------|
| Authorization | Bearer {{school_admin_token}} |

## Response Example

200

```
{
  "drivers": []
}
```

## Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.drivers && data.drivers.length) pm.collectionVariables.set('driver_id', data.drivers[0].id);
```

## 3. List Buses (school\_admin)

GET {{base\_url}}/buses

## Request Headers

| Header        | Value                         |
|---------------|-------------------------------|
| Authorization | Bearer {{school_admin_token}} |

## Response Example

200

```
{
  "buses": []
}
```

#### Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.buses && data.buses.length) {
  pm.collectionVariables.set('bus_id', data.buses[0].id);
  if (data.buses[0].safety_qr_code) pm.collectionVariables.set('safety_qr_code', data.buses[0].safety_qr_code);
}
```

## 4. List Routes (school\_admin)

**GET** `{{base_url}}/routes`

#### Request Headers

| Header        | Value                                      |
|---------------|--------------------------------------------|
| Authorization | Bearer <code>{{school_admin_token}}</code> |

#### Response Example

200

```
{
  "routes": []
}
```

#### Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.routes && data.routes.length) {
  pm.collectionVariables.set('route_id', data.routes[0].id);
  if (data.routes[0].route_qr_code) pm.collectionVariables.set('route_qr_code', data.routes[0].route_qr_code);
  if (data.routes[0].stops && data.routes[0].stops.length) pm.collectionVariables.set('stop_id', data.routes[0].stops[0].id);
}
```

## 3. QR [NEW]

### 1. Resolve Bus QR (school\_admin)

**GET** `{{base_url}}/qr/{{safety_qr_code}}`

#### Request Headers

| Header        | Value                                      |
|---------------|--------------------------------------------|
| Authorization | Bearer <code>{{school_admin_token}}</code> |

#### Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

## 2. Resolve Route QR (school\_admin)

**GET** `{{base_url}}/qr/{{route_qr_code}}`

### Request Headers

| Header        | Value                                      |
|---------------|--------------------------------------------|
| Authorization | Bearer <code>{{school_admin_token}}</code> |

### Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

## 4. Trips

### 1. Create Trip (school\_admin)

**POST** `{{base_url}}/trips`

Run '2. Lookups' first so route\_id/driver\_id/bus\_id are populated. driver\_id must be the DRV-xxxx id (from /drivers), not a user id.

### Request Headers

| Header        | Value                                      |
|---------------|--------------------------------------------|
| Authorization | Bearer <code>{{school_admin_token}}</code> |

### Request Body

```
{
  "route_id": "{{route_id}}",
  "driver_id": "{{driver_id}}",
  "bus_id": "{{bus_id}}",
  "trip_type": "pickup"
}
```

### Response Example

201

```
{
  "trip": { ... }
}
```

### Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.trip) pm.collectionVariables.set('trip_id', data.trip.id);
```

## 5. Attendance

## 1. Bulk Mark Attendance (school\_admin)

**POST** `{{base_url}}/attendance/bulk`

### Request Headers

| Header                     | Value                                      |
|----------------------------|--------------------------------------------|
| <code>Authorization</code> | <code>Bearer {{school_admin_token}}</code> |

### Request Body

```
{
  "trip_id": "{{trip_id}}",
  "records": [
    { "student_id": "{{student_id}}", "status": "present" }
  ]
}
```

### Response Example

**200**

```
{
  "bulk": { ... }
}
```

## 6. Leave

### 1. Approve Leave (school\_admin)

**PATCH** `{{base_url}}/leave/{{leave_id}}`

### Request Headers

| Header                     | Value                                      |
|----------------------------|--------------------------------------------|
| <code>Authorization</code> | <code>Bearer {{school_admin_token}}</code> |

### Request Body

```
{
  "status": "approved"
}
```

### Response Example

**200**

```
{
  "{{leave_id}}": { ... }
}
```

## 8. Guest Trips

### 1. Approve Guest Trip (school\_admin)

**PATCH** `{{base_url}}/guest-trips/{{guest_trip_id}}`

## Request Headers

| Header        | Value                         |
|---------------|-------------------------------|
| Authorization | Bearer {{school_admin_token}} |

## Request Body

```
{
  "status": "approved"
}
```

## Response Example

200

```
{
  "{{guest_trip_id}}": { ... }
}
```

# 9. Notifications

## 1. Send Notification (school\_admin -> parent) [triggers push stub]

**POST** {{base\_url}}/notifications

Replace user\_id with the parent's actual USR-xxxx id (visible in the Login - Parent response). Check the backend server console for a '[push:stub] would send to ...' log line - push sending isn't real yet.

## Request Headers

| Header        | Value                         |
|---------------|-------------------------------|
| Authorization | Bearer {{school_admin_token}} |

## Request Body

```
{
  "school_id": "{{school_id}}",
  "user_id": "REPLACE_WITH_PARENT_USER_ID",
  "title": "Test notification",
  "body": "Checking the push stub logs a line in the server console",
  "type": "info"
}
```

## Response Example

201

```
{
  "notification": { ... }
}
```

# 10. Tickets

## 1. Reply to Ticket (school\_admin)

**POST** {{base\_url}}/tickets/{{ticket\_id}}/replies

## Request Headers

| Header        | Value                         |
|---------------|-------------------------------|
| Authorization | Bearer {{school_admin_token}} |

## Request Body

```
{
  "content": "Scheduling a mechanic to look at the AC tomorrow."
}
```

## Response Example

201

```
{
  "replie": { ... }
}
```