

SmartTrack API Changes - Driver

Base URL: `{{base_url}}`

Changed-APIs-only reference for the driver app -- covers just the endpoints affected by decoupling buses, routes and drivers into independent entities (a bus/driver/route are now only ever linked together via a live trip). For the full driver API surface, see SmartTrack_API_Documentation_Driver.pdf instead; this doc is a focused diff.

Summary of what changed: - Buses and drivers no longer reference each other. Wherever you fetch a driver or bus record (including your own), `assigned_bus_id` / `assigned_bus_number` / `driver_id` / `driver_name` are gone -- a driver only has a bus for as long as a trip is actually running. - Routes still return `bus_id` / `bus_number` / `driver_id` / `driver_name`, but only for whichever trip is currently in progress on that route -- expect them absent between runs, not just null. - QR scans return less. A bus's safety QR no longer includes `driver_id`; a route's QR no longer includes `bus_id` / `driver_id`. - Take Over Trip after Breakdown is newly documented below -- it already existed, but this collection never had it. Scan the ORIGINAL (breakdown) bus's safety QR, not the replacement bus's. - Report Lost Item's `bus_id` auto-fill now comes from your current/most recent trip instead of a persistent assignment.

Contents

- 2. Lookups (capture IDs) (3 requests)
- 3. QR [NEW] (2 requests)
- 4. Trips (1 requests)
- 7. Lost & Found (1 requests)

Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

Variable	Default / Notes
<code>baseUrl</code>	<code>http://localhost:5000/api</code>
<code>school_admin_token</code>	(captured at runtime)
<code>driver_token</code>	(captured at runtime)
<code>bus_id</code>	(captured at runtime)
<code>safety_qr_code</code>	(captured at runtime)
<code>route_qr_code</code>	(captured at runtime)
<code>driver_id</code>	(captured at runtime)

2. Lookups (capture IDs)

1. List Drivers (school_admin)

GET {{base_url}}/drivers

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "drivers": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.drivers && data.drivers.length) pm.collectionVariables.set('driver_id', data.drivers[0].id);
```

2. List Buses (school_admin)

GET {{base_url}}/buses

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "buses": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.buses && data.buses.length) {
  pm.collectionVariables.set('bus_id', data.buses[0].id);
  if (data.buses[0].safety_qr_code) pm.collectionVariables.set('safety_qr_code', data.buses[0].safety_qr_code);
}
```

3. List Routes (school_admin)

GET {{base_url}}/routes

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "routes": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.routes && data.routes.length) {
  pm.collectionVariables.set('route_id', data.routes[0].id);
  if (data.routes[0].route_qr_code) pm.collectionVariables.set('route_qr_code', data.routes[0].route_qr_code);
  if (data.routes[0].stops && data.routes[0].stops.length) pm.collectionVariables.set('stop_id', data.routes[0].stops[0].id);
}
```

3. QR [NEW]

1. Resolve Bus QR (school_admin)

GET `{{base_url}}/qr/{{safety_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

2. Resolve Route QR (school_admin)

GET `{{base_url}}/qr/{{route_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

4. Trips

1. **NEW** Take Over Trip after Breakdown (driver) [NEW]

POST {{base_url}}/trips/take-over

[NEW] A standby driver completes a bus-breakdown handover by scanning the ORIGINAL (breakdown) bus's safety QR code -- not the replacement bus's, since that's the only one they have physical access to. Requires a school admin to have already named this driver as new_driver_id on the bus_transfers record (via the admin console's Bus Transfer screen); otherwise this 403s with "You are not the assigned driver for this transfer." On success, trips.driver_id switches to this driver and the bus_transfers record is marked completed.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Request Body

```
{
  "safety_qr_code": "{{safety_qr_code}}"
}
```

Response Example

201

```
{
  "take-over": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.trip) pm.collectionVariables.set('trip_id', data.trip.id);
```

7. Lost & Found

1. Report Lost Item (driver)

POST {{base_url}}/lost-found

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Request Body

```
{
  "bus_id": "{{bus_id}}",
  "driver_id": "{{driver_id}}",
  "description": "Blue water bottle found on back seat"
}
```

Response Example

201

```
{
  "item": { ... }
}
```

```
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();  
if (data.item) pm.collectionVariables.set('lost_found_id', data.item.id);
```