

SmartTrack API Changes - School Admin

Base URL: `{{base_url}}`

Changed-APIs-only reference for the school admin console -- covers just the endpoints affected by decoupling buses, routes and drivers into independent entities, plus leave no longer having an approval stage. For the full admin API surface, see `SmartTrack_API_Documentation_SchoolAdmin.pdf` instead; this doc is a focused diff.

Summary of what changed: - Buses, drivers and routes no longer reference each other. `assigned_bus_id` / `assigned_bus_number` (drivers), `driver_id` / `driver_name` (buses), and `bus_id` / `driver_id` (routes, on create/update) are gone from every one of these records -- there is no more "assign a driver to a bus" or "assign a bus to a route" step. POST/PATCH requests that still send those fields aren't rejected -- they're just silently ignored, since nothing is left to write them to. - List Routes still returns `bus_id` / `bus_number` / `driver_id` / `driver_name`, but now only for whichever trip is currently in progress on that route -- an idle route simply won't have them, not just null values. - QR scans return less. A bus's safety QR no longer includes `driver_id`; a route's QR no longer includes `bus_id` / `driver_id`. - Approve Leave is now Reject Leave in practice. Every leave request comes back status "approved" the moment it's created (parent or admin), so there's nothing left in a pending queue to approve -- PATCH `.../leave/:id` with status: "rejected" is now the only reason to call this. - Bus Transfer now requires you to name a standby driver. Assigning a replacement bus (POST `/bus-transfers` or PATCH `/bus-transfers/:id/assign`) used to auto-fill `new_driver_id` from the replacement bus's assigned driver; that assignment doesn't exist anymore, so `new_driver_id` must be sent explicitly, or the standby driver's take-over scan will 403. (Not shown as a request below -- bus-transfers isn't in this collection yet -- but the field itself was already optional/accepted, so no schema change.)

Contents

- 2. Lookups (capture IDs) (3 requests)
- 3. QR [NEW] (2 requests)
- 6. Leave (1 requests)

Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

Variable	Default / Notes
<code>baseUrl</code>	<code>http://localhost:5000/api</code>
<code>school_admin_token</code>	<i>(captured at runtime)</i>
<code>safety_qr_code</code>	<i>(captured at runtime)</i>
<code>route_qr_code</code>	<i>(captured at runtime)</i>
<code>leave_id</code>	<i>(captured at runtime)</i>

2. Lookups (capture IDs)

1. List Drivers (school_admin)

GET {{base_url}}/drivers

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "drivers": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.drivers && data.drivers.length) pm.collectionVariables.set('driver_id', data.drivers[0].id);
```

2. List Buses (school_admin)

GET {{base_url}}/buses

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "buses": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.buses && data.buses.length) {
  pm.collectionVariables.set('bus_id', data.buses[0].id);
  if (data.buses[0].safety_qr_code) pm.collectionVariables.set('safety_qr_code', data.buses[0].safety_qr_code);
}
```

3. List Routes (school_admin)

GET {{base_url}}/routes

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "routes": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.routes && data.routes.length) {
  pm.collectionVariables.set('route_id', data.routes[0].id);
  if (data.routes[0].route_qr_code) pm.collectionVariables.set('route_qr_code', data.routes[0].route_qr_code);
  if (data.routes[0].stops && data.routes[0].stops.length) pm.collectionVariables.set('stop_id', data.routes[0].stops[0].id);
}
```

3. QR [NEW]

1. Resolve Bus QR (school_admin)

GET `{{base_url}}/qr/{{safety_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

2. Resolve Route QR (school_admin)

GET `{{base_url}}/qr/{{route_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

6. Leave

1. Approve Leave (school_admin)

PATCH `{{base_url}}/leave/{{leave_id}}`

[CHANGED] Leave requests are pre-approved on creation now, so this is no longer a review step -- it's how an admin revokes/rejects a leave that was already auto-approved. Set status to "rejected" to revoke one; there's nothing left in a "pending" state to approve.

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Request Body

```
{
  "status": "rejected"
}
```

Response Example

200

```
{
  "{{leave_id}}": { ... }
}
```