

SmartTrack API

Base URL: `{{base_url}}`

Backend API for the SmartTrack school-transport platform. Covers auth + the mobile-relevant flows (driver, guest_driver, parent) plus the admin CRUD needed to set up test data. See docs/mobile-api-integration.md and docs/school-admin-mobile-handoff.md in the repo for full context.

How to use: 1. Run every request in "1. Auth" > "Logins" once - each saves its token into a collection variable automatically. 2. Run "2. Lookups (capture IDs)" once - these list existing seed data and capture ids/QR codes into collection variables used by later requests. 3. Run the rest of the folders in any order. Requests that create data (trip, leave, guest trip, ticket, lost item) auto-capture the new id.

Seeded demo accounts (see backend/src/db/seed.js) are pre-filled as collection variables - change them if your DB has different data.

Contents

- 1. Auth (12 requests)
- 2. Lookups (capture IDs) (4 requests)
- 3. QR [NEW] (4 requests)
- 4. Trips (4 requests)
- 5. Attendance (5 requests)
- 6. Leave (4 requests)
- 7. Lost & Found (3 requests)
- 8. Guest Trips (3 requests)
- 9. Notifications (4 requests)
- 10. Tickets (3 requests)

Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

Variable	Default / Notes
<code>baseUrl</code>	http://localhost:5000/api
<code>super_admin_email</code>	superadmin@smartrack.ae
<code>super_admin_password</code>	Super@123
<code>school_admin_email</code>	admin@greenfield.ae
<code>school_admin_password</code>	School@123
<code>driver_email</code>	driver@smartrack.ae
<code>driver_password</code>	Driver@123

guest_driver_email	guest@smartrack.ae
guest_driver_password	Guest@123
parent_email	parent@smartrack.ae
parent_password	Parent@123
super_admin_token	(captured at runtime)
school_admin_token	(captured at runtime)
driver_token	(captured at runtime)
guest_driver_token	(captured at runtime)
parent_token	(captured at runtime)
school_id	SCH-001
student_id	(captured at runtime)
student_qr_code	(captured at runtime)
bus_id	(captured at runtime)
safety_qr_code	(captured at runtime)
route_id	(captured at runtime)
route_qr_code	(captured at runtime)
stop_id	(captured at runtime)
driver_id	(captured at runtime)
trip_id	(captured at runtime)
attendance_id	(captured at runtime)
leave_id	(captured at runtime)
lost_found_id	(captured at runtime)
guest_trip_id	(captured at runtime)
ticket_id	(captured at runtime)
notification_id	(captured at runtime)
otp	(captured at runtime)

1. Auth

1. Login - Super Admin

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{super_admin_email}}",
  "password": "{{super_admin_password}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('super_admin_token', data.token);
```

2. Login - School Admin

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{school_admin_email}}",
  "password": "{{school_admin_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('school_admin_token', data.token);
```

3. Login - Driver

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{driver_email}}",
  "password": "{{driver_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('driver_token', data.token);
```

4. Login - Guest Driver

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{guest_driver_email}}",
  "password": "{{guest_driver_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",

```

```

    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}

```

Auto-Captured Variables (test script)

```

const data = pm.response.json();
if (data.token) pm.collectionVariables.set('guest_driver_token', data.token);

```

5. Login - Parent

POST `{{base_url}}/auth/login`

Request Body

```

{
  "email": "{{parent_email}}",
  "password": "{{parent_password}}",
  "school_id": "{{school_id}}"
}

```

Response Example

200

```

{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}

```

Auto-Captured Variables (test script)

```

const data = pm.response.json();
if (data.token) pm.collectionVariables.set('parent_token', data.token);

```

6. Get Me (driver)

GET `{{base_url}}/auth/me`

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  }
}
```

7. **NEW** Update FCM Token (driver) [NEW]

PATCH `{{base_url}}/auth/fcm-token`

New self-service endpoint - any role can register its own push token. Sending is currently stubbed server-side (logged, not actually delivered).

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "fcm_token": "demo-device-token-abc123"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  }
}
```

8. Forgot Password (parent)

POST `{{base_url}}/auth/forgot-password`

Non-production responses include devOtp (no real email/SMS provider is wired up yet) - captured automatically into `{{otp}}` for the next two requests.

Request Body

```
{
  "email": "{{parent_email}}"
}
```

Response Example

200

```
{
  "message": "A verification code has been sent to your email",
  "devOtp": "<otp>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.devOtp) pm.collectionVariables.set('otp', String(data.devOtp));
```

9. Verify OTP (parent)

POST `{{base_url}}/auth/verify-otp`

Request Body

```
{
  "email": "{{parent_email}}",
  "otp": "{{otp}}"
}
```

Response Example

200

```
{
  "verified": true
}
```

10. Reset Password (parent)

POST `{{base_url}}/auth/reset-password`

Resets to the same `{{parent_password}}` so subsequent Login - Parent requests keep working.

Request Body

```
{
  "email": "{{parent_email}}",
  "otp": "{{otp}}",
  "password": "{{parent_password}}"
}
```

Response Example

200

```
{
  "message": "Password reset successfully"
}
```

11. Change Password (driver)

PATCH `{{base_url}}/auth/change-password`

Sets the new password to the same value as before, so it's safe to run repeatedly without breaking other requests.

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "currentPassword": "{{driver_password}}",
  "newPassword": "{{driver_password}}"
}
```

Response Example

200

```
{
  "message": "Password updated successfully"
}
```

12. Logout (driver)

POST `{{base_url}}/auth/logout`

Stateless JWT - this is a 204 no-op; the token remains valid until it expires. Re-run 'Login - Driver' afterwards if you need a fresh `{{driver_token}}`.

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Response Example

204

No response body.

2. Lookups (capture IDs)

1. List Students (school_admin)

GET `{{base_url}}/students`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200


```
{
  "students": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.students && data.students.length) {
  pm.collectionVariables.set('student_id', data.students[0].id);
  if (data.students[0].student_qr_code) pm.collectionVariables.set('student_qr_code', data.students[0].student_qr_code);
}
```

2. List Drivers (school_admin)

GET `{{base_url}}/drivers`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "drivers": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.drivers && data.drivers.length) pm.collectionVariables.set('driver_id', data.drivers[0].id);
```

3. List Buses (school_admin)

GET `{{base_url}}/buses`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "buses": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.buses && data.buses.length) {
  pm.collectionVariables.set('bus_id', data.buses[0].id);
  if (data.buses[0].safety_qr_code) pm.collectionVariables.set('safety_qr_code', data.buses[0].safety_qr_code);
}
```

4. List Routes (school_admin)

GET `{{base_url}}/routes`

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{school_admin_token}}</code>

Response Example

200

```
{
  "routes": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.routes && data.routes.length) {
  pm.collectionVariables.set('route_id', data.routes[0].id);
  if (data.routes[0].route_qr_code) pm.collectionVariables.set('route_qr_code', data.routes[0].route_qr_code);
  if (data.routes[0].stops && data.routes[0].stops.length) pm.collectionVariables.set('stop_id', data.routes[0].stops[0].id);
}
```

3. QR [NEW]

1. Resolve Student QR (driver)

GET `{{base_url}}/qr/{{student_qr_code}}`

Run '2. Lookups' first so `{{student_qr_code}}` is populated. Returns `{ type: 'student', entity: {...} }`.

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{driver_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

2. Resolve Bus QR (school_admin)

GET `{{base_url}}/qr/{{safety_qr_code}}`

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

3. Resolve Route QR (school_admin)

GET `{{base_url}}/qr/{{route_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

4. Resolve Unknown QR - expect 404

GET `{{base_url}}/qr/DOES-NOT-EXIST`

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

4. Trips

1. Create Trip (school_admin)

POST `{{base_url}}/trips`

Run '2. Lookups' first so route_id/driver_id/bus_id are populated. driver_id must be the DRV-xxxx id (from /drivers), not a user id.

Request Headers

Header	Value
--------	-------

Authorization	Bearer {{school_admin_token}}
---------------	-------------------------------

Request Body

```
{
  "route_id": "{{route_id}}",
  "driver_id": "{{driver_id}}",
  "bus_id": "{{bus_id}}",
  "trip_type": "pickup"
}
```

Response Example

201

```
{
  "trip": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.trip) pm.collectionVariables.set('trip_id', data.trip.id);
```

2. List Trips (driver - scoped to own trips)

GET {{base_url}}/trips

[CHANGED] Only returns trips belonging to this driver, regardless of any driver_id query param passed.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Response Example

200

```
{
  "trips": []
}
```

3. List Trips (driver, spoofed driver_id - should be ignored)

GET {{base_url}}/trips?driver_id=DRV-9999

[CHANGED] Demonstrates that a driver can't view another driver's trips by passing driver_id - the server overrides it with the caller's own driver id.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Query Param	Example Value
driver_id	DRV-9999

Response Example

200

```
{
  "trips": []
}
```

4. Update Trip Status (driver - own trip)

PATCH `{{base_url}}/trips/{{trip_id}}`

A driver may only PATCH the status field of their own trip (pre-existing behavior, unchanged).

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "status": "in_progress"
}
```

Response Example

200

```
{
  "{{trip_id}}": { ... }
}
```

5. Attendance

1. Mark Attendance (driver)

POST `{{base_url}}/attendance`

[CHANGED] Now 403s if trip_id doesn't belong to this driver.

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "trip_id": "{{trip_id}}",
  "student_id": "{{student_id}}",
  "status": "present"
}
```

Response Example

201

```
{
  "record": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.record) pm.collectionVariables.set('attendance_id', data.record.id);
```

2. **NEW** Scan Attendance (driver) **[NEW]**

POST `{{base_url}}/attendance/scan`

Resolves the student by QR code and marks them present in one call, stamping pickup_time or drop_time depending on the trip's type.

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "trip_id": "{{trip_id}}",
  "qr_code": "{{student_qr_code}}"
}
```

Response Example

200

```
{
  "scan": { ... }
}
```

3. Bulk Mark Attendance (school_admin)

POST `{{base_url}}/attendance/bulk`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Request Body

```
{
  "trip_id": "{{trip_id}}",
  "records": [
    { "student_id": "{{student_id}}", "status": "present" }
  ]
}
```

Response Example

200

```
{
  "bulk": { ... }
}
```

4. List Attendance (driver - own trips only)

GET `{{base_url}}/attendance`

[CHANGED] Scoped to this driver's own trips.

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Response Example

200

```
{
  "records": []
}
```

5. List Attendance (parent - own children only)

GET `{{base_url}}/attendance`

[CHANGED] Scoped to attendance for this parent's own child(ren), matched by login email against `parent_details.email`. Empty unless the parent's login email matches a `parent_details` row.

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "records": []
}
```

6. Leave

1. Create Leave Request (parent)

POST `{{base_url}}/leave`

[CHANGED] Fails unless `{{student_id}}` is this parent's own child (matched by login email). If '2. Lookups' captured a student that isn't this parent's, expect a 403.

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Request Body

```
{
  "student_id": "{{student_id}}",
  "from_date": "2026-09-01",
  "to_date": "2026-09-02",
  "reason": "Family trip"
}
```

Response Example

201

```
{
  "leave": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.leave) pm.collectionVariables.set('leave_id', data.leave.id);
```

2. List Leave (parent - own children only)

GET `{{base_url}}/leave`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "leave": []
}
```

3. Approve Leave (school_admin)

PATCH `{{base_url}}/leave/{{leave_id}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Request Body

```
{
  "status": "approved"
}
```

Response Example

200


```
{
  "{{leave_id}}": { ... }
}
```

4. **CHANGED** Attempt Create Leave (driver) - expect 403 [CHANGED]

POST `{{base_url}}/leave`

Drivers/guest_drivers can no longer create leave requests at all - this should now 403 (previously any authenticated role could).

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "student_id": "{{student_id}}",
  "from_date": "2026-09-01",
  "to_date": "2026-09-02"
}
```

Response Example

201

```
{
  "leave": { ... }
}
```

7. Lost & Found

1. Report Lost Item (driver)

POST `{{base_url}}/lost-found`

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "bus_id": "{{bus_id}}",
  "driver_id": "{{driver_id}}",
  "description": "Blue water bottle found on back seat"
}
```

Response Example

201

```
{
  "item": { ... }
}
```

```
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.item) pm.collectionVariables.set('lost_found_id', data.item.id);
```

2. List Lost Items (parent)

GET `{{base_url}}/lost-found`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "items": []
}
```

3. Claim Lost Item (parent)

POST `{{base_url}}/lost-found/{{lost_found_id}}/claims`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Request Body

```
{
  "student_id": "{{student_id}}",
  "claim_note": "That's my child's bottle"
}
```

Response Example

201

```
{
  "claim": { ... }
}
```

8. Guest Trips

1. Create Guest Trip (guest_driver)

POST `{{base_url}}/guest-trips`

[CHANGED] The name/phone above are intentionally wrong - check the response and confirm guest_driver_name/guest_driver_phone came back as the guest_driver account's real name/phone instead, not what

was sent.

Request Headers

Header	Value
Authorization	Bearer {{guest_driver_token}}

Request Body

```
{
  "guest_driver_name": "SPOOFED NAME (should be overridden)",
  "guest_driver_phone": "000-000-0000 (should be overridden)",
  "bus_registration": "BUS-TEST-1"
}
```

Response Example

201

```
{
  "trip": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.trip) pm.collectionVariables.set('guest_trip_id', data.trip.id);
```

2. List My Guest Trips (guest_driver)

GET {{base_url}}/guest-trips

[CHANGED] Scoped to guest trips matching this account's own phone number.

Request Headers

Header	Value
Authorization	Bearer {{guest_driver_token}}

Response Example

200

```
{
  "trips": []
}
```

3. Approve Guest Trip (school_admin)

PATCH {{base_url}}/guest-trips/{{guest_trip_id}}

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Request Body

```
{
  "status": "approved"
}
```

Response Example

200

```
{
  "{{guest_trip_id}}": { ... }
}
```

9. Notifications

1. List Notifications (parent)

GET `{{base_url}}/notifications`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "notifications": []
}
```

2. Unread Count (parent)

GET `{{base_url}}/notifications/unread-count`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "count": 0
}
```

3. Send Notification (school_admin -> parent) [triggers push stub]

POST `{{base_url}}/notifications`

Replace `user_id` with the parent's actual `USR-xxxx` id (visible in the Login - Parent response). Check the backend server console for a '[push:stub] would send to ...' log line - push sending isn't real yet.

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Request Body

```
{
  "school_id": "{{school_id}}",
  "user_id": "REPLACE_WITH_PARENT_USER_ID",
  "title": "Test notification",
  "body": "Checking the push stub logs a line in the server console",
  "type": "info"
}
```

Response Example

201

```
{
  "notification": { ... }
}
```

4. Mark All Read (parent)

PATCH {{base_url}}/notifications/read-all

Request Headers

Header	Value
Authorization	Bearer {{parent_token}}

Response Example

200

```
{
  "message": "Notifications marked as read"
}
```

10. Tickets

1. Create Ticket (guest_driver)

POST {{base_url}}/tickets

Request Headers

Header	Value
Authorization	Bearer {{guest_driver_token}}

Request Body

```
{
  "type": "Vehicle Issue",
  "priority": "medium",
  "description": "AC not working on assigned bus"
}
```

Response Example

201

```
{
  "ticket": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.ticket) pm.collectionVariables.set('ticket_id', data.ticket.id);
```

2. List My Tickets (guest_driver) [NEW - mine=true]

GET `{{base_url}}/tickets?mine=true`

Narrows to just this caller's own reported tickets, regardless of role.

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{guest_driver_token}}</code>

Query Param	Example Value
<code>mine</code>	true

Response Example

200

```
{
  "tickets": []
}
```

3. Reply to Ticket (school_admin)

POST `{{base_url}}/tickets/{{ticket_id}}/replies`

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{school_admin_token}}</code>

Request Body

```
{
  "content": "Scheduling a mechanic to look at the AC tomorrow."
}
```

Response Example

201

```
{
  "replie": { ... }
}
```