

SmartTrack API - Driver

Base URL: `{{base_url}}`

Driver-facing slice of the SmartTrack API, covering both regular drivers and guest drivers: login, trip status updates, attendance marking/QR scan, lost & found reporting, and the guest-driver-only guest-trip and ticket endpoints.

How to use: 1. Run "Login - Driver" (or "Login - Guest Driver" for the guest-trip / ticket endpoints) first -- it saves the matching `driver_token` / `guest_driver_token` collection variable used to authenticate the rest of the requests in this doc. 2. `trip_id`, `student_id`, `student_qr_code` etc. are captured automatically as you exercise the flows.

Seeded demo accounts (see backend/src/db/seed.js): `driver@smartrack.ae`, `guest@smartrack.ae`.

Contents

- 1. Auth (6 requests)
- 3. QR [NEW] (1 requests)
- 4. Trips (2 requests)
- 5. Attendance (3 requests)
- 7. Lost & Found (1 requests)
- 8. Guest Trips (2 requests)
- 10. Tickets (2 requests)

Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

Variable	Default / Notes
<code>baseUrl</code>	<code>http://localhost:5000/api</code>
<code>driver_email</code>	<code>driver@smartrack.ae</code>
<code>driver_password</code>	<code>Driver@123</code>
<code>guest_driver_email</code>	<code>guest@smartrack.ae</code>
<code>guest_driver_password</code>	<code>Guest@123</code>
<code>driver_token</code>	<i>(captured at runtime)</i>
<code>guest_driver_token</code>	<i>(captured at runtime)</i>
<code>school_id</code>	<code>SCH-001</code>
<code>student_id</code>	<i>(captured at runtime)</i>
<code>student_qr_code</code>	<i>(captured at runtime)</i>
<code>bus_id</code>	<i>(captured at runtime)</i>

driver_id	(captured at runtime)
trip_id	(captured at runtime)

1. Auth

1. Login - Driver

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{driver_email}}",
  "password": "{{driver_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('driver_token', data.token);
```

2. Login - Guest Driver

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{guest_driver_email}}",
  "password": "{{guest_driver_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
```

```
{
  "id": "USR-12345",
  "name": "Jane Doe",
  "email": "user@example.com",
  "phone": "+971500000000",
  "role": "driver",
  "school_id": "SCH-001",
  "school_name": "Greenfield International",
  "avatar": "https://example.com/avatar.jpg",
  "fcm_token": "demo-device-token",
  "created_at": "2023-01-01T00:00:00.000Z",
  "last_login": "2023-01-02T08:00:00.000Z"
},
"token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('guest_driver_token', data.token);
```

3. Get Me (driver)

GET `{{base_url}}/auth/me`

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  }
}
```

4. **NEW** Update FCM Token (driver) [NEW]

PATCH `{{base_url}}/auth/fcm-token`

New self-service endpoint - any role can register its own push token. Sending is currently stubbed server-side (logged, not actually delivered).

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "fcm_token": "demo-device-token-abc123"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  }
}
```

5. Change Password (driver)

PATCH `{{base_url}}/auth/change-password`

Sets the new password to the same value as before, so it's safe to run repeatedly without breaking other requests.

Request Headers

Header	Value
Authorization	Bearer <code>{{driver_token}}</code>

Request Body

```
{
  "currentPassword": "{{driver_password}}",
  "newPassword": "{{driver_password}}"
}
```

Response Example

200

```
{
  "message": "Password updated successfully"
}
```

6. Logout (driver)

POST `{{base_url}}/auth/logout`

Stateless JWT - this is a 204 no-op; the token remains valid until it expires. Re-run 'Login - Driver' afterwards if you need a fresh `{{driver_token}}`.

Request Headers

Header	Value
--------	-------

Authorization	Bearer {{driver_token}}
---------------	-------------------------

Response Example

204

No response body.

3. QR [NEW]

1. Resolve Student QR (driver)

GET {{base_url}}/qr/{{student_qr_code}}

Run '2. Lookups' first so {{student_qr_code}} is populated. Returns { type: 'student', entity: {...} }.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

4. Trips

1. List Trips (driver - scoped to own trips)

GET {{base_url}}/trips

[CHANGED] Only returns trips belonging to this driver, regardless of any driver_id query param passed.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Response Example

200

```
{
  "trips": []
}
```

2. Update Trip Status (driver - own trip)

PATCH {{base_url}}/trips/{{trip_id}}

A driver may only PATCH the status field of their own trip (pre-existing behavior, unchanged).

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Request Body

```
{
  "status": "in_progress"
}
```

Response Example

200

```
{
  "{{trip_id}}": { ... }
}
```

5. Attendance

1. Mark Attendance (driver)

POST {{base_url}}/attendance

[CHANGED] Now 403s if trip_id doesn't belong to this driver.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Request Body

```
{
  "trip_id": "{{trip_id}}",
  "student_id": "{{student_id}}",
  "status": "present"
}
```

Response Example

201

```
{
  "record": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.record) pm.collectionVariables.set('attendance_id', data.record.id);
```

2. **NEW** Scan Attendance (driver) [NEW]

POST {{base_url}}/attendance/scan

Resolves the student by QR code and marks them present in one call, stamping pickup_time or drop_time depending on the trip's type.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Request Body

```
{
  "trip_id": "{{trip_id}}",
  "qr_code": "{{student_qr_code}}"
}
```

Response Example

200

```
{
  "scan": { ... }
}
```

3. List Attendance (driver - own trips only)

GET {{base_url}}/attendance

[CHANGED] Scoped to this driver's own trips.

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Response Example

200

```
{
  "records": []
}
```

7. Lost & Found

1. Report Lost Item (driver)

POST {{base_url}}/lost-found

Request Headers

Header	Value
Authorization	Bearer {{driver_token}}

Request Body

```
{
  "bus_id": "{{bus_id}}",
  "driver_id": "{{driver_id}}",
  "description": "Blue water bottle found on back seat"
}
```

Response Example

201

```
{
  "item": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.item) pm.collectionVariables.set('lost_found_id', data.item.id);
```

8. Guest Trips

1. Create Guest Trip (guest_driver)

POST `{{base_url}}/guest-trips`

[CHANGED] The name/phone above are intentionally wrong - check the response and confirm guest_driver_name/guest_driver_phone came back as the guest_driver account's real name/phone instead, not what was sent.

Request Headers

Header	Value
Authorization	Bearer <code>{{guest_driver_token}}</code>

Request Body

```
{
  "guest_driver_name": "SPOOFED NAME (should be overridden)",
  "guest_driver_phone": "000-000-0000 (should be overridden)",
  "bus_registration": "BUS-TEST-1"
}
```

Response Example

201

```
{
  "trip": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.trip) pm.collectionVariables.set('guest_trip_id', data.trip.id);
```

2. List My Guest Trips (guest_driver)

GET `{{base_url}}/guest-trips`

[CHANGED] Scoped to guest trips matching this account's own phone number.

Request Headers

Header	Value
Authorization	Bearer <code>{{guest_driver_token}}</code>

Response Example

200

```
{
  "trips": []
}
```

10. Tickets

1. Create Ticket (guest_driver)

POST `{{base_url}}/tickets`

Request Headers

Header	Value
Authorization	Bearer <code>{{guest_driver_token}}</code>

Request Body

```
{
  "type": "Vehicle Issue",
  "priority": "medium",
  "description": "AC not working on assigned bus"
}
```

Response Example

201

```
{
  "ticket": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.ticket) pm.collectionVariables.set('ticket_id', data.ticket.id);
```

2. List My Tickets (guest_driver) [NEW - mine=true]

GET `{{base_url}}/tickets?mine=true`

Narrows to just this caller's own reported tickets, regardless of role.

Request Headers

Header	Value
--------	-------

Authorization	Bearer {{guest_driver_token}}
Query Param	Example Value
mine	true

Response Example

200

```
{
  "tickets": []
}
```