

SmartTrack API - School Admin

Base URL: `{{base_url}}`

School-admin slice of the SmartTrack API: the CRUD/lookup and approval endpoints a school's admin console uses to manage students, drivers, buses, routes, trips, leave requests, guest-trip approvals, notifications and support tickets.

How to use: 1. Run "Login - School Admin" first -- it saves `school_admin_token` as a collection variable that every other request in this doc authenticates with. 2. Run the Lookups folder to pull real ids (students, drivers, buses, routes) into collection variables for use in the rest of the requests.

Seeded demo account (see backend/src/db/seed.js): admin@greenfield.ae.

Contents

- 1. Auth (1 requests)
- 2. Lookups (capture IDs) (4 requests)
- 3. QR [NEW] (2 requests)
- 4. Trips (1 requests)
- 5. Attendance (1 requests)
- 6. Leave (1 requests)
- 8. Guest Trips (1 requests)
- 9. Notifications (1 requests)
- 10. Tickets (1 requests)

Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

Variable	Default / Notes
<code>baseUrl</code>	http://localhost:5000/api
<code>school_admin_email</code>	admin@greenfield.ae
<code>school_admin_password</code>	School@123
<code>school_admin_token</code>	(captured at runtime)
<code>school_id</code>	SCH-001
<code>student_id</code>	(captured at runtime)
<code>bus_id</code>	(captured at runtime)
<code>safety_qr_code</code>	(captured at runtime)

route_id	(captured at runtime)
route_qr_code	(captured at runtime)
driver_id	(captured at runtime)
trip_id	(captured at runtime)
leave_id	(captured at runtime)
guest_trip_id	(captured at runtime)
ticket_id	(captured at runtime)

1. Auth

1. Login - School Admin

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{school_admin_email}}",
  "password": "{{school_admin_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+971500000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('school_admin_token', data.token);
```

2. Lookups (capture IDs)

1. List Students (school_admin)

GET `{{base_url}}/students`

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "students": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.students && data.students.length) {
  pm.collectionVariables.set('student_id', data.students[0].id);
  if (data.students[0].student_qr_code) pm.collectionVariables.set('student_qr_code', data.students[0].student_qr_code);
}
```

2. List Drivers (school_admin)

GET {{base_url}}/drivers

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "drivers": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.drivers && data.drivers.length) pm.collectionVariables.set('driver_id', data.drivers[0].id);
```

3. List Buses (school_admin)

GET {{base_url}}/buses

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Response Example

200

```
{
  "buses": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.buses && data.buses.length) {
  pm.collectionVariables.set('bus_id', data.buses[0].id);
  if (data.buses[0].safety_qr_code) pm.collectionVariables.set('safety_qr_code', data.buses[0].safety_qr_code);
}
```

4. List Routes (school_admin)

GET `{{base_url}}/routes`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "routes": []
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.routes && data.routes.length) {
  pm.collectionVariables.set('route_id', data.routes[0].id);
  if (data.routes[0].route_qr_code) pm.collectionVariables.set('route_qr_code', data.routes[0].route_qr_code);
  if (data.routes[0].stops && data.routes[0].stops.length) pm.collectionVariables.set('stop_id', data.routes[0].stops[0].id);
}
```

3. QR [NEW]

1. Resolve Bus QR (school_admin)

GET `{{base_url}}/qr/{{safety_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

2. Resolve Route QR (school_admin)

GET `{{base_url}}/qr/{{route_qr_code}}`

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Response Example

200

```
{
  "type": "<student|bus|route>",
  "entity": { ... }
}
```

4. Trips

1. Create Trip (school_admin)

POST `{{base_url}}/trips`

Run '2. Lookups' first so route_id/driver_id/bus_id are populated. driver_id must be the DRV-xxxx id (from /drivers), not a user id.

Request Headers

Header	Value
Authorization	Bearer <code>{{school_admin_token}}</code>

Request Body

```
{
  "route_id": "{{route_id}}",
  "driver_id": "{{driver_id}}",
  "bus_id": "{{bus_id}}",
  "trip_type": "pickup"
}
```

Response Example

201

```
{
  "trip": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.trip) pm.collectionVariables.set('trip_id', data.trip.id);
```

5. Attendance

1. Bulk Mark Attendance (school_admin)

POST `{{base_url}}/attendance/bulk`

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{school_admin_token}}</code>

Request Body

```
{
  "trip_id": "{{trip_id}}",
  "records": [
    { "student_id": "{{student_id}}", "status": "present" }
  ]
}
```

Response Example

200

```
{
  "bulk": { ... }
}
```

6. Leave

1. Approve Leave (school_admin)

PATCH `{{base_url}}/leave/{{leave_id}}`

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{school_admin_token}}</code>

Request Body

```
{
  "status": "approved"
}
```

Response Example

200

```
{
  "{{leave_id}}": { ... }
}
```

8. Guest Trips

1. Approve Guest Trip (school_admin)

PATCH `{{base_url}}/guest-trips/{{guest_trip_id}}`

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Request Body

```
{
  "status": "approved"
}
```

Response Example

200

```
{
  "{{guest_trip_id}}": { ... }
}
```

9. Notifications

1. Send Notification (school_admin -> parent) [triggers push stub]

POST {{base_url}}/notifications

Replace user_id with the parent's actual USR-xxxx id (visible in the Login - Parent response). Check the backend server console for a '[push:stub] would send to ...' log line - push sending isn't real yet.

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Request Body

```
{
  "school_id": "{{school_id}}",
  "user_id": "REPLACE_WITH_PARENT_USER_ID",
  "title": "Test notification",
  "body": "Checking the push stub logs a line in the server console",
  "type": "info"
}
```

Response Example

201

```
{
  "notification": { ... }
}
```

10. Tickets

1. Reply to Ticket (school_admin)

POST {{base_url}}/tickets/{{ticket_id}}/replies

Request Headers

Header	Value
Authorization	Bearer {{school_admin_token}}

Request Body

```
{
  "content": "Scheduling a mechanic to look at the AC tomorrow."
}
```

Response Example

201

```
{
  "replie": { ... }
}
```