

SmartTrack API - Student / Parent

Base URL: `{{base_url}}`

Parent-facing slice of the SmartTrack API: everything a parent/guardian mobile or web client needs to log in, track their child's trips and attendance, request leave, and manage lost & found and notifications.

How to use: 1. Run "Login - Parent" first -- it saves `parent_token` as a collection variable that every other request in this doc authenticates with. 2. `student_id`, `trip_id`, `attendance_id`, `leave_id` and similar ids are captured automatically as you exercise the flows (or ask a school_admin to share them from the Lookups folder in the full collection).

Seeded demo account (see backend/src/db/seed.js): parent@smartrack.ae.

Contents

- 1. Auth (4 requests)
- 5. Attendance (1 requests)
- 6. Leave (2 requests)
- 7. Lost & Found (2 requests)
- 9. Notifications (3 requests)

Collection Variables

Seeded demo accounts and IDs used throughout this reference. Values left blank are captured automatically at runtime (tokens, ids, QR codes) rather than fixed ahead of time.

Variable	Default / Notes
<code>baseUrl</code>	http://localhost:5000/api
<code>parent_email</code>	parent@smartrack.ae
<code>parent_password</code>	Parent@123
<code>parent_token</code>	(captured at runtime)
<code>school_id</code>	SCH-001
<code>student_id</code>	(captured at runtime)
<code>lost_found_id</code>	(captured at runtime)
<code>otp</code>	(captured at runtime)

1. Auth

1. Login - Parent

POST `{{base_url}}/auth/login`

Request Body

```
{
  "email": "{{parent_email}}",
  "password": "{{parent_password}}",
  "school_id": "{{school_id}}"
}
```

Response Example

200

```
{
  "user": {
    "id": "USR-12345",
    "name": "Jane Doe",
    "email": "user@example.com",
    "phone": "+9715000000000",
    "role": "driver",
    "school_id": "SCH-001",
    "school_name": "Greenfield International",
    "avatar": "https://example.com/avatar.jpg",
    "fcm_token": "demo-device-token",
    "created_at": "2023-01-01T00:00:00.000Z",
    "last_login": "2023-01-02T08:00:00.000Z"
  },
  "token": "<jwt>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.token) pm.collectionVariables.set('parent_token', data.token);
```

2. Forgot Password (parent)

POST `{{base_url}}/auth/forgot-password`

Non-production responses include devOtp (no real email/SMS provider is wired up yet) - captured automatically into `{{otp}}` for the next two requests.

Request Body

```
{
  "email": "{{parent_email}}"
}
```

Response Example

200

```
{
  "message": "A verification code has been sent to your email",
  "devOtp": "<otp>"
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.devOtp) pm.collectionVariables.set('otp', String(data.devOtp));
```

3. Verify OTP (parent)

POST `{{base_url}}/auth/verify-otp`

Request Body

```
{
  "email": "{{parent_email}}",
  "otp": "{{otp}}"
}
```

Response Example

200

```
{
  "verified": true
}
```

4. Reset Password (parent)

POST `{{base_url}}/auth/reset-password`

Resets to the same `{{parent_password}}` so subsequent Login - Parent requests keep working.

Request Body

```
{
  "email": "{{parent_email}}",
  "otp": "{{otp}}",
  "password": "{{parent_password}}"
}
```

Response Example

200

```
{
  "message": "Password reset successfully"
}
```

5. Attendance

1. List Attendance (parent - own children only)

GET `{{base_url}}/attendance`

[CHANGED] Scoped to attendance for this parent's own child(ren), matched by login email against `parent_details.email`. Empty unless the parent's login email matches a `parent_details` row.

Request Headers

Header	Value
<code>Authorization</code>	<code>Bearer {{parent_token}}</code>

Response Example

200

```
{
  "records": []
}
```

6. Leave

1. Create Leave Request (parent)

POST `{{base_url}}/leave`

[CHANGED] Fails unless `{{student_id}}` is this parent's own child (matched by login email). If '2. Lookups' captured a student that isn't this parent's, expect a 403.

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Request Body

```
{
  "student_id": "{{student_id}}",
  "from_date": "2026-09-01",
  "to_date": "2026-09-02",
  "reason": "Family trip"
}
```

Response Example

201

```
{
  "leave": { ... }
}
```

Auto-Captured Variables (test script)

```
const data = pm.response.json();
if (data.leave) pm.collectionVariables.set('leave_id', data.leave.id);
```

2. List Leave (parent - own children only)

GET `{{base_url}}/leave`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "leave": []
}
```

7. Lost & Found

1. List Lost Items (parent)

GET `{{base_url}}/lost-found`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "items": []
}
```

2. Claim Lost Item (parent)

POST `{{base_url}}/lost-found/{{lost_found_id}}/claims`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Request Body

```
{
  "student_id": "{{student_id}}",
  "claim_note": "That's my child's bottle"
}
```

Response Example

201

```
{
  "claim": { ... }
}
```

9. Notifications

1. List Notifications (parent)

GET `{{base_url}}/notifications`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "notifications": []
}
```

```
}
```

2. Unread Count (parent)

GET `{{base_url}}/notifications/unread-count`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "count": 0
}
```

3. Mark All Read (parent)

PATCH `{{base_url}}/notifications/read-all`

Request Headers

Header	Value
Authorization	Bearer <code>{{parent_token}}</code>

Response Example

200

```
{
  "message": "Notifications marked as read"
}
```