

EXPERIMENT 20 – MySQL String Functions

Aim: To implement the MySQL string functions **REPLACE**, **REPEAT**, **REVERSE**, **RIGHT**, **LEFT**, **RPAD** and **LPAD**.

REPLACE()

MySQL REPLACE() replaces all the occurrences of a substring within a string. Syntax :

REPLACE(str,from_str,to_str)

```
SELECT Patient_Name,  
       REPLACE(Patient_Name, 'a', 'A') AS Replace_Output  
FROM Patient;
```

	Patient_Name	Replace_Output
▶	Arun Kumar	Arun KumAr
	Priya	PriyA
	Rahul	RAhul
	Sneha	SnehA

REPEAT()

MySQL REPEAT() repeats a string for a specified number of times.

The function returns NULL either any either of the arguments are NULL. Syntax :

REPEAT(str,count)

```
SELECT Patient_Name,  
       REPEAT(Patient_Name, 2) AS Repeat_Output  
FROM Patient;
```

	Patient_Name	Repeat_Output
▶	Arun Kumar	Arun KumarArun Kumar
	Priya	PriyaPriya
	Rahul	RahulRahul
	Sneha	SnehaSneha

REVERSE()

Returns a given string with the order

of the characters reversed. Syntax :

REVERSE(str)

```
13 • SELECT Patient_Name,
14      REVERSE(Patient_Name) AS Reverse_Output
15 FROM Patient;
```

Result Grid

Filter Rows:
Export:
Wrap Cell Content:

	Patient_Name	Reverse_Output
▶	Arun Kumar	ramuK nurA
	Priya	ayirP
	Rahul	luhaR
	Sneha	ahenS

RIGHT()

MySQL RIGHT() extracts a specified number of characters from the right side of a given string. Syntax : RIGHT(str,len)

```
18 • SELECT Patient_Name,
19      RIGHT(Patient_Name, 3) AS Right_Output
20 FROM Patient;
```

Result Grid |   Filter Rows: | Export:  | Wrap Cell Content: 

	Patient_Name	Right_Output
▶	Arun Kumar	mar
	Priya	iya
	Rahul	hul
	Sneha	eha

LEFT()

MySQL LEFT() returns a specified number of characters from the left of a given string. Both the number and the string are supplied in the arguments as str and len of the function.

Syntax : LEFT(str,len)

```

23 • SELECT Patient_Name,
24       LEFT(Patient_Name, 3) AS Left_Output
25 FROM Patient;

```

Result Grid Filter Rows: Export: Wrap Cell Content:	
Patient_Name	Left_Output
Arun Kumar	Aru
Priya	Pri
Rahul	Rah
Sneha	Sne

RPAD()

MySQL RPAD() function pads strings from right. The actual string which is to be padded as str, length of the string returned after padding as len and string which is used for padding as padstr is used as a parameters within the argument.

Syntax : RPAD(str,len,padstr)

```

28 • SELECT Patient_Name,
29       RPAD(Patient_Name, 15, '*') AS RPAD_Output
30 FROM Patient;

```

Result Grid Filter Rows: Export: Wrap Cell Content:	
Patient_Name	RPAD_Output
Arun Kumar	Arun Kumar*****
Priya	Priya*****
Rahul	Rahul*****
Sneha	Sneha*****

LPAD()

MySQL LPAD() left pads a string with another string. The actual string, a number indicating the length of the padding in characters (optional) and the string to be used for left padding - all are passed as arguments.

```

33 • SELECT Patient_Name,
34       LPAD(Patient_Name, 15, '*') AS LPAD_Output
35 FROM Patient;

```

Result Grid Filter Rows: Export: Wrap Cell Content:	
Patient_Name	LPAD_Output
Arun Kumar	*****Arun Kumar
Priya	*****Priya
Rahul	*****Rahul
Sneha	*****Sneha

ASCII()

This function returns the numeric value of the leftmost character of the string str.

Returns 0 if str is the empty string. Returns NULL if str is NULL

Syntax : ASCII(str)

```
38 • SELECT Patient_Name,  
39       ASCII(Patient_Name) AS ASCII_Output  
40 FROM Patient;
```

Result Grid		
Filter Rows:		
Export:  Wrap Cell Con		
	Patient_Name	ASCII_Output
▶	Arun Kumar	65
	Priya	80
	Rahul	82
	Sneha	83

BIN()

Returns a string representation of the binary value of N, where N is a longlong

(BIGINT) number. Returns NULL if N is NULL.

Syntax : BIN(N)

```
43 • SELECT Patient_ID,  
44       BIN(Patient_ID) AS Binary_Output  
45 FROM Patient;
```

Result Grid		
Filter Rows:		
Export:  Wrap Cell C		
	Patient_ID	Binary_Output
▶	P001	0
	P002	0
	P003	0
	P004	0

OCT()

Returns a string representation of the octal value of N, where N is a longlong

(BIGINT) number. Returns NULL if N is NULL.

Syntax : OCT(N)

```
48 • SELECT Patient_ID,  
49      OCT(Patient_ID) AS Octal_Output  
50 FROM Patient;
```

Result Grid		
Filter Rows:		
Export:  Wrap Cell		
	Patient_ID	Octal_Output
▶	P001	0
	P002	0
	P003	0
	P004	0

RESULT:

Thus the String Functions such as Replace, Repeat, Reverse, Right, Left, Rpad and Lpad are executed successfully.